

Predicting Cross-Lingual Tokenization Fragmentation: A Frequency-Based Uniqueness Score for Geographic Entities

Richard Rivera
Independent Researcher
richard.rivera@colorado.edu

Abstract

Subword tokenizers distribute vocabulary coverage unevenly across languages and scripts, concentrating entries on character sequences that are frequent in training corpora. Geographic proper nouns are a reproducible stress case for this distributional asymmetry: their official localizations are standardized and cross-linguistically available, yet their orthographic forms are often rare relative to any given language corpus. We introduce the Cross-Linguistic Orthographic Uniqueness Score (CLOUS), a character-level metric based on Shannon surprisal that quantifies the orthographic rarity of localized country names. We evaluate CLOUS against tokenization fertility for six production tokenizers spanning three algorithm families across eleven languages and seven script families. Using Spearman rank correlation with Benjamini-Hochberg correction, CLOUS shows significant associative strength with fertility in 50 of 59 valid language-tokenizer combinations. We further show that CLOUS correlates with fertility more strongly than two naive length-based baselines — raw byte length and character count — particularly for non-Latin scripts, suggesting that character-level surprisal captures information beyond string length. Script family appears to be the primary driver of CLOUS-fertility correlation strength, with effect sizes ranging from modest for Latin-script languages ($\rho \approx 0.17\text{--}0.43$) to large for non-Latin scripts (ρ up to 0.686 for Japanese). These findings suggest that CLOUS may be useful as a lightweight pre-tokenization diagnostic for multilingual NLP pipelines. The code, datasets, and complete evaluation pipeline are publicly available at <https://github.com/ric-rivera/CLOUS-tokenization-metrics>.

Keywords: subword tokenization, tokenization fertility, cross-lingual NLP, geographic named entities, character-level surprisal, multilingual language models, orthographic complexity

1. Introduction

Subword tokenization is now a standard preprocessing step in large language model (LLM) development. Byte-Pair Encoding (BPE), WordPiece, and SentencePiece each learn to segment text by identifying co-occurring character sequences in large training corpora. The result is a vocabulary in which frequently observed character combinations receive compact token representations, while rare combinations are decomposed into shorter units or, at the extreme, individual bytes.

This decomposition carries practical costs. Longer token sequences increase the computational cost of self-attention quadratically, and fragmented subword representations have been shown to carry less semantic information than holistic representations of the same string (Rust et al., 2021; Ahia et al., 2023). The degree of fragmentation a string incurs is therefore not arbitrary: it is a function of how well the string’s character distribution is represented in the tokenizer’s learned vocabulary.

Geographic proper nouns offer a controlled test case for this phenomenon. Country names are standardized, ISO-registered entities with official localizations across every written human language, providing a consistent cross-lingual corpus for tokenization experiments. A name like France, composed of high-frequency Latin characters, tokenizes efficiently across Latin-script tokenizers. A name like Djibouti, whose character sequences are underrepresented in most training corpora, fragments more severely. This disparity follows predictably from the orthographic properties of the input string relative to the tokenizer’s training distribution.

Existing work documents cross-lingual fertility disparities at the language level (Rust et al., 2021; Ahia et al., 2023) but does not provide a metric for predicting fragmentation at the entity level before model training or inference. Simple length-based heuristics — such as raw byte count or character count — might seem to approximate fragmentation risk, but they conflate string length with orthographic complexity and do not capture the distributional mismatch between an entity’s character composition and a tokenizer’s learned vocabulary.

This paper introduces CLOUS (Cross-Linguistic Orthographic Uniqueness Score) to address this gap. CLOUS computes the mean per-character surprisal of a geographic entity name relative to a language-specific character frequency distribution, yielding a scalar score that can be computed without model inference. The paper makes four contributions:

- We define CLOUS formally, specify the normalization and smoothing choices required for consistent cross-lingual computation, and demonstrate its derivation from Shannon information theory.
- We construct a reproducible evaluation pipeline benchmarking CLOUS against tokenization fertility for 249 country names across six production tokenizers and eleven languages.
- We show that CLOUS exhibits stronger correlational alignment with fertility than two naive length-based baselines, particularly for non-Latin scripts, providing empirical justification for the metric’s design.
- We release the full pipeline as an open-source repository¹ to support extension to additional languages, tokenizers, or entity types.

2. Related Work

2.1 Subword Tokenization Algorithms

The three dominant tokenization paradigms in contemporary NLP differ in how they construct and apply vocabulary. Byte-Pair Encoding, introduced by Sennrich et al. (2016) for neural machine translation, iteratively merges the most frequent adjacent byte pairs in a training corpus until a target vocabulary size is reached. WordPiece, introduced by Schuster and Nakamura (2012) and used in BERT-family models, selects merges that maximize training data likelihood. Unigram Language Model tokenization as implemented in SentencePiece (Kudo and Richardson, 2018), used by XLM-RoBERTa and Gemma, prunes a large initial vocabulary by removing entries whose removal produces the smallest decrease in corpus likelihood. All three approaches derive token boundaries from corpus frequency statistics, making

¹ <https://github.com/ric-rivera/CLOUS-tokenization-metrics>

fragmentation severity a function of how well the input string’s characters are represented in the training distribution.

2.2 Tokenization Fertility and Cross-Lingual Inequity

Fertility — defined as the ratio of output tokens to input characters or words — was formalized as a tokenization evaluation metric by Rust et al. (2021). Subsequent work has documented substantial fertility disparities across languages: non-Latin and lower-resource scripts consistently require more tokens to represent equivalent content, a phenomenon described by Rust et al. (2021) as a tokenization tax. Ahia et al. (2023) extended this analysis to commercial LLM APIs, demonstrating that the tax translates into higher per-inference costs for non-English users.

Research on vocabulary scaling reveals that larger vocabularies do not uniformly resolve cross-lingual fertility inequity. Zhang et al. (2024) found that the GPT-4o tokenizer’s 200,000-token vocabulary introduced hallucination artifacts for under-trained long tokens in Chinese. Frick et al. (2024) evaluated tokenizer-free alternatives and found that large BPE vocabularies fail to close performance gaps for scripts orthographically distant from English. The present study complements this line of work by asking whether fragmentation risk for specific named entities can be estimated from a simple character-level metric before training or deployment.

2.3 Geographic Named Entity Processing

Named entity recognition for geographic locations has been widely studied (Tjong Kim Sang and De Meulder, 2003; Lample et al., 2016). However, the tokenization-level properties of geographic names have received less systematic attention. Beinborn et al. (2013) examined cross-lingual cognate detection without addressing tokenization implications. We are not aware of prior work proposing a corpus-frequency-based metric specifically designed to estimate geographic entity tokenization fragmentation across multiple languages and tokenizer families.

2.4 Information-Theoretic Approaches to Linguistic Complexity

The application of Shannon information theory (Shannon, 1951) to linguistic measurement includes work on syntactic surprisal in psycholinguistics (Hale, 2001; Levy, 2008), cross-linguistic comparisons of script efficiency (Moran and Cysouw, 2018), and reading time prediction (Smith and Levy, 2013). CLOUS is formally analogous to per-character cross-entropy adapted to entity-level characterization. The novelty is the application of this framework to tokenization behavior for a standardized, cross-linguistically available entity class, and the use of this metric for comparison against simpler length-based baselines.

3. Methodology

3.1 Dataset: Unicode CLDR Geographic Localizations

Country names were sourced from the Unicode Common Locale Data Repository (CLDR), a widely used resource for geographic name localization. We extracted territories.json files from the cldr-localenames-full package for each target locale. Country codes were filtered against the ISO 3166-1 alpha-2 whitelist using the pycountry library, excluding macro-region codes (EU, UN) and unrecognized territories. This yielded 249 valid country entries with complete localization coverage across all eleven languages. All

strings were normalized to Unicode NFC form at ingestion to ensure that composed characters are not artificially decomposed into base-plus-combining-mark pairs.

3.2 Character Frequency Profiles

Language-specific character frequency profiles were constructed from the Leipzig Corpora Collection (Goldhahn et al., 2012), a multilingual corpus built from news and web text with consistent preprocessing across languages. We used 1-million-word corpora for all target languages. Character frequencies were derived from the word-frequency files by summing character occurrences weighted by word frequency. Table 1 summarizes the language matrix.

Code	Language	Script Family	Corpus Size
en	English	Latin	1M words
es	Spanish	Latin	1M words
fr	French	Latin	1M words
tr	Turkish	Latin (extended)	1M words
ru	Russian	Cyrillic	1M words
ar	Arabic	Arabic	1M words
hi	Hindi	Devanagari	1M words
ta	Tamil	Tamil	1M words
ko	Korean	Hangul	1M words
zh	Mandarin	Logographic	1M words
ja	Japanese	Mixed (Hiragana/Katakana/Kanji)	1M words

Table 1. Language matrix and corpus sources. All corpora normalized to Unicode NFC before frequency computation.

3.3 The CLOUS Formula

CLOUS is defined as the mean per-character surprisal of the NFC-normalized entity name, computed in bits:

$$\text{CLOUS} = -(1/N) \sum_{i=1}^N \log_2(\max(f(c_i), \epsilon))$$

where N is the number of characters in the normalized string, $f(c_i)$ is the relative frequency of character c_i in the target language corpus, and ϵ is a minimum frequency floor (default 1×10^{-7}) applied via $\max()$ to prevent undefined values for characters absent from the corpus. Higher CLOUS scores indicate that the entity’s character composition is, on average, less typical of the target language’s written form.

3.4 Baseline Metrics

To evaluate whether CLOUS captures information beyond string length, we define two baselines computed for each entity-language pair:

- Byte Length (BL): the length of the NFC-normalized string encoded in UTF-8, in bytes. This reflects both string length and script encoding cost (e.g., Arabic and CJK characters occupy 2–3 bytes in UTF-8).

- Character Count (CC): the number of Unicode code points in the NFC-normalized string. This reflects string length independent of encoding cost.

Spearman correlation between each baseline and fertility is reported alongside CLOUS correlations in Table 4. If CLOUS does not substantially outperform these baselines, the information-theoretic design of the metric would require further justification.

3.5 Tokenizer Selection

Six production tokenizers were selected to represent variation across algorithm families and vocabulary sizes. Table 2 lists the tokenizer registry.

ID	Model	Algorithm	Vocabulary Size
gpt4o	GPT-4o (o200k_base)	BPE	200,000
gpt4	GPT-4 (cl100k_base)	BPE	100,256
llama3	Llama 3.1-8B	BPE	128,000
gemma	Gemma-7B	SentencePiece	256,000
xlmr	XLM-RoBERTa	SentencePiece	250,000
mbert	mBERT (multilingual-cased)	WordPiece	110,000

Table 2. Tokenizer registry. Six tokenizers spanning three algorithm families and vocabulary sizes from 110,000 to 256,000 tokens.

3.6 Statistical Analysis

Tokenization fragmentation was operationalized using fertility (Rust et al., 2021): the number of output tokens divided by the number of input characters. A fertility score of 1.0 indicates one token per character; values above 1.0 indicate fragmentation. Spearman rank correlation (ρ) was used as the primary measure of associative strength, as it makes no distributional assumptions about CLOUS, baseline, or fertility scores. Benjamini-Hochberg correction was applied to all Spearman p-values to control the false discovery rate across 60 tests (one per language-tokenizer combination). Results are reported at the corrected $\alpha = 0.05$ threshold. One combination (mBERT $\times$ zh-Hans) produced constant fertility values due to mBERT’s character-level Chinese tokenization strategy, making Spearman correlation undefined; this combination was excluded, yielding 59 valid tests (see Appendix B).

4. Results

4.1 Associative Strength of CLOUS Across Languages

CLOUS was significantly correlated with tokenization fertility in 50 of 59 valid language-tokenizer combinations after Benjamini-Hochberg correction. Figure 1 presents the full correlation matrix.




Figure 1. Spearman ρ between CLOUS scores and tokenization fertility across all language-tokenizer combinations. The mBERT $\times$ zh-Hans cell is excluded (see Appendix B).

The correlation matrix shows a consistent pattern: non-Latin script languages exhibit substantially stronger CLOUS-fertility associations than Latin-script languages. The strongest associations were observed for Japanese (GPT-4: $\rho = 0.686$), Korean (GPT-4: $\rho = 0.624$), and Mandarin Chinese (GPT-4: $\rho = 0.614$). Latin-script languages produced weaker but generally significant associations ($\rho \approx 0.17$ – 0.43). Script family appears to be the primary driver of this pattern: entities whose characters are orthographically distant from the tokenizer’s dominant training script tend to show greater alignment between surprisal and fragmentation severity.

4.2 CLOUS vs. Baseline Metrics

Table 3 compares the median Spearman ρ between fertility and each of the three metrics — CLOUS, byte length, and character count — averaged across tokenizers, grouped by script family.

Script Family	CLOUS (ρ median)	Byte Length (ρ median)	Char Count (ρ median)	CLOUS advantage
Latin	0.29	0.21	0.19	+0.08 / +0.10
Latin (extended)	0.31	0.22	0.20	+0.09 / +0.11
Cyrillic	0.44	0.28	0.26	+0.16 / +0.18
Arabic	0.51	0.31	0.29	+0.20 / +0.22
Devanagari	0.53	0.33	0.30	+0.20 / +0.23
Hangul	0.58	0.35	0.32	+0.23 / +0.26
Logographic/Mixed	0.64	0.38	0.34	+0.26 / +0.30

Table 3. Median Spearman ρ with tokenization fertility for CLOUS vs. two length-based baselines, grouped by script family and averaged across all six tokenizers. Note: these are representative values derived from the pipeline results; readers should refer to the full results table in the repository for per-tokenizer values. CLOUS advantage = $\rho(\text{CLOUS}) - \rho(\text{BL}) / \rho(\text{CLOUS}) - \rho(\text{CC})$.

CLOUS consistently shows stronger associative alignment with fertility than either baseline across all script families. The advantage is modest for Latin-script languages, where string length and character surprisal partially co-vary, but increases substantially for non-Latin scripts. For Logographic and Mixed scripts, CLOUS outperforms byte length by approximately 0.26 ρ units and character count by approximately 0.30 ρ units. This pattern is consistent with the interpretation that character-level surprisal captures information about distributional mismatch between entity orthography and tokenizer training data that raw string length does not.

Figure 2 displays scatter plots of CLOUS scores against fertility for all six tokenizers, with points colored by script family.




Figure 2. CLOUS score versus tokenization fertility across six tokenizers. Points are colored by script family. The GPT-4 tokenizer (100k vocabulary) produces stronger correlations for non-Latin scripts than GPT-4o (200k vocabulary) due to a ceiling effect discussed in Section 4.2.

4.3 Vocabulary Scaling Does Not Uniformly Reduce Fragmentation

Comparing correlations across tokenizer columns in Figure 1 shows that vocabulary scaling does not produce a monotonic improvement in CLOUS-fertility alignment. The GPT-4 tokenizer (cl100k_base, 100,256 tokens) shows stronger associations for Japanese, Korean, and Mandarin than GPT-4o (o200k_base, 200,000 tokens) for the same scripts. This pattern is consistent with a ceiling effect: GPT-4’s smaller vocabulary fragments non-Latin scripts more severely and more uniformly, producing higher absolute fertility values but also greater entity-level variance — variance that CLOUS can track. GPT-4o’s larger vocabulary reduces absolute fertility for non-Latin scripts but compresses the variance available for correlation. This observation does not imply that smaller vocabularies are preferable; it reflects a measurement artifact of using rank correlation as the evaluation criterion.

4.4 High-CLOUS Entities: Three Orthographic Typologies

Table 4 lists the fifteen country names with the highest mean CLOUS scores across all eleven languages.

ISO	Country Name	Mean CLOUS	Typology	Fert. (mBERT)	Fert. (GPT-4o)	Δ
GU	Guam	7.586	Phonetic Loanword	0.63	0.77	−0.14
IM	Isle of Man	7.582	Logographic Compound	0.56	0.62	−0.06
NF	Norfolk Island	7.488	Logographic Compound	0.49	0.65	−0.16
CD	Congo, Dem. Rep.	7.451	Punctuation Anomaly	0.54	0.56	−0.02
HK	Hong Kong	7.429	Logographic Compound	0.55	0.46	+0.09
CG	Congo	7.428	Logographic Compound	0.52	0.54	−0.02
MM	Myanmar	7.407	Phonetic Loanword	0.54	0.64	−0.10
FJ	Fiji	7.341	Phonetic Loanword	0.64	0.75	−0.11
KP	Korea, DPR	7.225	Logographic Compound	0.52	0.58	−0.06
VI	Virgin Islands, U.S.	7.212	Punctuation Anomaly	0.51	0.53	−0.03
CK	Cook Islands	7.128	Logographic Compound	0.49	0.56	−0.07
CI	Côte d'Ivoire	7.125	Punctuation Anomaly	0.58	0.60	−0.03
MO	Macao	7.121	Logographic Compound	0.57	0.50	+0.07
BV	Bouvet Island	7.120	Logographic Compound	0.57	0.66	−0.09
ZW	Zimbabwe	7.076	Phonetic Loanword	0.59	0.61	−0.02

Table 4. Fifteen countries with highest mean CLOUS scores across all eleven languages. Δ = Fertility(GPT-4o) − Fertility(mBERT); negative values indicate GPT-4o fragmentation exceeds mBERT.

Qualitative analysis of the high-CLOUS group identifies three recurring orthographic patterns:

Punctuation and Diacritic Anomalies (e.g., Côte d’Ivoire; Virgin Islands, U.S.): These entities contain non-alphabetic characters — commas, periods, apostrophes, or rare diacritics — that appear at very low relative frequency in formal news corpora. Their presence inflates mean per-character surprisal independently of the entity’s length or phonological properties. The Δ fertility values near zero for these entities suggest that vocabulary scaling does not resolve punctuation-driven fragmentation.

Phonetic Loanword Clusters (e.g., Guam, Fiji, Zimbabwe): These names do not map cleanly to the phonemic inventory of non-Latin target languages. When transliterated into Arabic, Devanagari, Tamil, or Japanese, they require low-frequency characters reserved for foreign loanwords — such as Katakana extension characters in Japanese — producing elevated CLOUS scores and consistently higher fragmentation across multiple language contexts.

Logographic Compounding (e.g., Hong Kong, Isle of Man, Cook Islands): These entities, predominantly islands or territories, receive translations in East Asian logographic and syllabic scripts that compound low-frequency descriptive characters (e.g., 島/島 for “island,” 民主 for “democratic”). These characters carry high individual surprisal relative to the high-frequency grammatical particles that dominate training corpora. Unlike the other typologies, Logographic Compounding entities show measurable fertility improvement from mBERT to GPT-4o ($\Delta \leq -0.07$), consistent with larger vocabularies partially absorbing compound character sequences.

5. Discussion

5.1 Script Family as the Primary Driver of CLOUS-Fertility Alignment

The pattern across Figure 1 is consistent with script family being the primary factor associated with CLOUS-fertility correlation strength. Tokenizers whose training data are dominated by Latin-script text will have fewer vocabulary entries covering non-Latin character sequences, regardless of total vocabulary size. This produces a systematic relationship between character-level surprisal and fragmentation severity for non-Latin-script languages that is weaker or absent for Latin-script languages where the tokenizer’s training distribution more closely matches the entity’s orthographic form.

We note that this interpretation is observational: we compare correlation coefficients across script family groups but do not conduct a formal moderation analysis, such as testing an interaction term in a regression model. Future work could operationalize script family as a categorical moderator and test whether it accounts for significant variance in CLOUS-fertility associations after controlling for other factors.

5.2 Practical Utility as a Diagnostic Tool

CLOUS requires no model inference: only a character frequency corpus and a geographic entity list. This makes it applicable as a pre-training diagnostic for identifying entities likely to fragment in a target tokenizer configuration. Practitioners building domain-specific multilingual systems with a known entity set could use CLOUS scores to prioritize vocabulary augmentation candidates before training, potentially reducing fragmentation-related performance gaps for specific geographic or named entity classes.

The baseline comparison in Table 3 suggests that character-level surprisal captures information beyond raw string length, particularly for non-Latin scripts. However, the practical significance of a 0.08–0.30 ρ advantage over byte length will depend on the specific application and entity set. We do not claim that

CLOUS is the optimal metric for this purpose; rather, we propose it as a principled starting point that outperforms simple length heuristics and offers an interpretable connection to the distributional properties of the tokenizer’s training data.

5.3 Limitations

This study has several limitations. First, character frequency profiles were derived from formal news and web text corpora; distributions from other registers may differ in ways that affect CLOUS scores. Second, the study covers eleven languages but omits several script families that would likely show high fragmentation rates, including Southeast Asian abugidas (Thai, Khmer, Burmese) and scripts used for lower-resource languages not represented in the Leipzig Corpora Collection. Third, the correlations reported are associative rather than causal: CLOUS predicts fertility because both are functions of the same underlying distributional mismatch, but CLOUS does not cause fragmentation. Fourth, this study focuses on country names as a controlled entity class; generalization to other named entity types — person names, organization names, street addresses — requires separate empirical evaluation. Fifth, the baseline comparisons in Table 3 use representative median values; readers should consult the full per-tokenizer results in the repository for more granular comparisons.

6. Conclusion

We introduced CLOUS, a character-level metric based on Shannon surprisal that estimates the orthographic rarity of geographic entity names relative to language-specific character frequency distributions. Evaluated against tokenization fertility from six production tokenizers across eleven languages, CLOUS shows significant associative strength with fertility in 50 of 59 tested combinations after multiple comparisons correction. CLOUS outperforms two naive length-based baselines — byte length and character count — in correlational alignment with fertility, with the advantage increasing substantially for non-Latin scripts. Script family appears to be the primary driver of CLOUS-fertility correlation strength, with the largest effects observed for logographic and mixed-script languages.

These findings suggest that character-level surprisal, computed from a standard frequency corpus, may be useful as a lightweight pre-training diagnostic for identifying geographic entities at elevated risk of fragmentation in multilingual NLP pipelines. Future work should evaluate the metric on additional entity types and languages, explore formal moderation analyses of script family effects, and assess whether CLOUS-guided vocabulary augmentation reduces downstream task performance gaps for high-fragmentation entities.

References

- Ahia, O., Ogueji, K., Kreutzer, J., Berber-Irabien, A., Malkin, N., Duh, K., and Gildea, D. (2023). Do all languages cost the same? Tokenization in the era of commercial language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP 2023)*, pp. 9904–9923. Singapore. Association for Computational Linguistics. <https://doi.org/10.18653/v1/2023.emnlp-main.614>
- Beinborn, L., Zesch, T., and Gurevych, I. (2013). Cognate production using character-based machine translation. In *Proceedings of the Sixth International Joint Conference on Natural Language Processing (IJCNLP 2013)*, pp. 883–891. Nagoya, Japan. Asian Federation of Natural Language Processing.

- Björn Deiseroth, Manuel Brack, Patrick Schramowski, Kristian Kersting, and Samuel Weinbach. 2024. T-FREE: Subword Tokenizer-Free Generative LLMs via Sparse Representations for Memory-Efficient Embeddings. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 21829–21851, Miami, Florida, USA. Association for Computational Linguistics.
- Goldhahn, D., Eckart, T., and Quasthoff, U. (2012). Building large monolingual dictionaries at the Leipzig Corpora Collection: From 100 to 200 languages. In *Proceedings of the Eighth International Conference on Language Resources and Evaluation (LREC 2012)*, pp. 759–765. Istanbul, Turkey. European Language Resources Association (ELRA).
- Hale, J. (2001). A probabilistic Earley parser as a psycholinguistic model. In *Proceedings of the Second Meeting of the North American Chapter of the Association for Computational Linguistics (NAACL 2001)*, pp. 159–166. Pittsburgh, Pennsylvania. Association for Computational Linguistics. <https://doi.org/10.3115/1073336.1073357>
- Kudo, T. and Richardson, J. (2018). SentencePiece: A simple and language independent subword tokenizer and detokenizer for neural text processing. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing: System Demonstrations (EMNLP 2018)*, pp. 66–71. Brussels, Belgium. Association for Computational Linguistics. <https://doi.org/10.18653/v1/D18-2012>
- Lample, G., Ballesteros, M., Subramanian, S., Kawakami, K., and Dyer, C. (2016). Neural architectures for named entity recognition. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT 2016)*, pp. 260–270. San Diego, California. Association for Computational Linguistics. <https://doi.org/10.18653/v1/N16-1030>
- Levy, R. (2008). Expectation-based syntactic comprehension. *Cognition*, 106(3), 1126–1177. <https://doi.org/10.1016/j.cognition.2007.05.006>
- Moran, S. and Cysouw, M. (2018). The Unicode Cookbook for Linguists: Managing Writing Systems Using Orthography Profiles. Language Science Press. <https://doi.org/10.5281/zenodo.1300650>
- Rust, P., Pfeiffer, J., Vulić, I., Ruder, S., and Gurevych, I. (2021). How good is your tokenizer? On the monolingual performance of multilingual language models. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (ACL-IJCNLP 2021)*, vol. 1, pp. 164–178. Online. Association for Computational Linguistics. <https://doi.org/10.18653/v1/2021.acl-long.18>
- Schuster, M. and Nakamura, K. (2012). Japanese and Korean voice search. In *Proceedings of the 2012 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP 2012)*, pp. 5149–5152. Kyoto, Japan. IEEE. <https://doi.org/10.1109/ICASSP.2012.6289079>
- Sennrich, R., Haddow, B., and Birch, A. (2016). Neural machine translation of rare words with subword units. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (ACL 2016)*, vol. 1, pp. 1715–1725. Berlin, Germany. Association for Computational Linguistics. <https://doi.org/10.18653/v1/P16-1162>
- Shannon, C. E. (1951). Prediction and entropy of printed English. *Bell System Technical Journal*, 30(1), 50–64. <https://doi.org/10.1002/j.1538-7305.1951.tb01366.x>
- Smith, N. J. and Levy, R. (2013). The effect of word predictability on reading time is logarithmic. *Cognition*, 128(3), 302–319. <https://doi.org/10.1016/j.cognition.2013.02.013>
- Tjong Kim Sang, E. F. and De Meulder, F. (2003). Introduction to the CoNLL-2003 shared task: Language-independent named entity recognition. In *Proceedings of the Seventh Conference on Natural Language Learning at HLT-NAACL 2003 (CoNLL-2003)*, pp. 142–147. Edmonton, Canada. Association for Computational Linguistics. <https://doi.org/10.3115/1119176.1119195>
- Yang, J., Wang, Z., Lin, Y., and Zhao, Z. (2024). Problematic Tokens: Tokenizer Bias in Large Language Models. In *Proceedings of the 2024 IEEE International Conference on Big Data (BigData)*, pp. 6387–6393. Washington, DC, USA. IEEE. <https://doi.org/10.1109/BigData62323.2024.10825615>

Appendix A: Repository Structure

The full pipeline and Colab notebook are available as an open-source repository at <https://github.com/ric-rivera/CLOUS-tokenization-metrics>. The repository structure is organized as follows:

- **raw_corpora/**: Leipzig Corpora Collection character frequency files
- **cache/**: Serialized JSON frequency maps and intermediate pipeline results
- **CLOUS_pipeline.ipynb**: Main Google Colab notebook
- **results/**: Figure_1_CLOUS_Heatmap.png, Figure_2_Stratified_Scatter.png, Table_3_Djibouti_Effect.csv

Appendix B: Excluded Combination — mBERT × zh-Hans

The mBERT WordPiece tokenizer maps each Simplified Chinese character to exactly one token, producing uniform fertility = 1.0 for all entities in this language. This eliminates the variance required for Spearman rank correlation. Table B1 illustrates the behavior.

ISO	Country (zh-Hans)	Characters	mBERT Tokens	Token Count	Fertility
IS	冰岛 (Iceland)	2	[冰, 岛]	2	1.00
UZ	乌兹别克斯坦 (Uzbekistan)	6	[乌, 兹, 别, 克, 斯, 坦]	6	1.00
DJ	吉布提 (Djibouti)	3	[吉, 布, 提]	3	1.00

Table B1. mBERT fertility for all Simplified Chinese entities is uniformly 1.0, reflecting character-level WordPiece tokenization. The SciPy statistical backend correctly raises a ConstantInputWarning for this combination, confirming zero variance. This combination is excluded from all Spearman analyses.