

Power Platform Troubleshooting Guide

Version 1.0

Version Date: Jun 16, 2026

Created by:

- Ricardo de Souza

Contributors

Overview	2
Power Apps: Canvas and Model-Driven Apps	2
Delegation warnings and data limits	2
Slow app performance or load time	3
Data source or permissions errors.....	3
Form validation or blank-value save errors	3
Power Automate: Cloud Flows	4
Flow trigger not firing	4
Flow Runs Failing or Timing Out.....	5
Flow triggering unexpectedly or multiple times	6
Power Automate: Desktop Flows (RPA)	7
Attended desktop flow not running	7
Unattended RPA Flow Fails to Connect	7
UI Element Not Found or Automation Fails Mid-run.....	8
Microsoft Dataverse	9
Insufficient privileges or permission errors	9
Dataverse Operation Throttling or Timeouts	10
Solution Import or Pipeline Errors (Dataverse)	10
Power Pages	11
Web Page Changes Not Visible.....	11
Users See “Access Denied” or Missing Content.....	11
Portal site not loading or authentication issues	12
Microsoft Copilot Studio	13
Copilot Studio features not available	13
Agent responses are poor or inaccurate	13
Copilot actions failing.....	14
Conclusion	14
Official Microsoft Learn References	14

Overview

This guide describes common issues and error messages across Microsoft Power Platform components, with practical steps to diagnose root causes and apply recommended resolutions. It is organized by platform area for quick reference and is intended to support both human architects and AI assistants when troubleshooting Power Platform solutions.

Power Apps: Canvas and Model-Driven Apps

Power Apps issues often involve data connectivity, delegation limits, performance bottlenecks, or user access permissions. Use the following guidance to diagnose and resolve frequent problems.

Delegation warnings and data limits

An app shows a delegation warning or returns only a partial set of records from a data source.

- **Cause:** The formula includes a nondelegable operation, so Power Apps retrieves only the first set of records and processes the query locally. The default nondelegable query limit is 500 records and can be increased to 2,000, but this does not make the query delegable.
- **Solution:** Refactor the formula so filtering, sorting, and searching can be delegated to the data source. Prefer delegable functions and operators supported by the target connector, use Dataverse views or server-side filtering where appropriate, and treat the 2,000-row setting as a testing aid rather than a production design strategy.

Slow app performance or load time

The app is slow to start, navigate, or respond to user actions.

- **Cause:** Common causes include excessive startup logic, unnecessary data loading, too many controls on a screen, complex formulas, large payloads, or repeated connector calls.
- **Solution:** Optimize the app design for performance. Load data on demand, reduce the number of columns and records retrieved, simplify repeated formulas, and use Power

Apps Monitor to identify slow operations. Prefer delegation and small data payloads, especially for enterprise-scale apps.

Data source or permissions errors

Users receive errors such as “You don’t have permission to view this data,” or expected data does not appear.

- **Cause:** The user or application identity lacks the required permissions on the underlying data source, or a connector connection requires sharing, reauthentication, or policy review.
- **Solution:** Verify access at the data-source level. For Dataverse, assign the required security roles and table privileges. For SharePoint and other connectors, confirm list or library permissions, connection ownership, connector sharing, and any Data Loss Prevention policy restrictions. Ask the user to reopen the app after permissions or connections are corrected.

Form validation or blank-value save errors

The app fails to save blank values or displays validation errors during submission.

- **Cause:** Required-field settings, data-source constraints, formula logic, or error-handling configuration may prevent blank values from being submitted as intended.
- **Solution:** Confirm whether the target column allows blank values, review required-field settings in the form and data source, and use formula-level error handling patterns such as IfError and Errors to capture and respond to validation failures. Avoid relying on retired feature settings as a long-term troubleshooting recommendation.
- *If Power Apps integrates with Power Automate flows, also review the Power Automate troubleshooting section for flow-related issues.*

Power Automate: Cloud Flows

Cloud flow issues often involve triggers not firing, failed or delayed runs, throttling, licensing constraints, or unexpected trigger behavior. Use the following checks to isolate the cause.

Flow trigger not firing

A scheduled or event-based flow does not start as expected.

- **Possible causes:**
 - A **Data Loss Prevention (DLP)** policy might be blocking the flow's trigger or connectors (which prevents the flow from even enabling).
 - **The flow's trigger connection is broken** (e.g., credentials expired or OAuth token revoked) or the related service has connectivity issues.
 - The flow **uses a premium connector trigger** without the necessary license, so it's not allowed to run.
 - The **trigger conditions on the flow may never be met**, causing it to skip triggering.
- **Solution:** Isolate the cause systematically.
 1. **Check DLP:** Try editing and saving the flow. If it violates a DLP policy, you'll see a warning (e.g., "workflow is disabled by org policy"). Work with an admin to adjust the DLP policy or change the connectors to comply (see [Governance_Cookbook.md#enforce-data-loss-prevention-dlp-policies](#)).
 2. **Verify Connections:** Open the flow in Power Automate and re-check all connections for the trigger and actions. Re-authenticate or update credentials if any show an error.
 3. **Licensing:** Confirm the connector used in the trigger (or any actions) isn't premium beyond the user's plan. If it is, acquire the appropriate **Power Automate license** (per-user or per-flow) or use an alternative connector.
 4. **Trigger Conditions:** If the flow has a trigger condition or filters on the trigger (for example, SharePoint item triggers with conditions), review them to ensure they match real events. Remove or correct conditions that might be too restrictive. Use the flow's run history and trigger analytics to see if trigger attempts were skipped due to conditions.

5. **Environment Connectivity:** If the flow is triggered by an external system (like a webhook), confirm that all required endpoints (e.g., Power Automate endpoints) are reachable from your network (whitelisted).

Flow Runs Failing or Timing Out

The flow triggers but one or more actions consistently fail, or the flow exceeds time limits.

- **Cause:** A connector action may be returning an error, the run may exceed documented duration limits, or the flow may be hitting Power Platform request limits, connector throttling, Dataverse limits, or connected-service limits.
- **Solution:** Diagnose and address the failure point:
 1. **Examine Run History:** Identify which action fails. Check its error details for specific messages or error codes:
 - a. If the **action was throttled with HTTP 429** or delayed by service limits, reduce burst traffic, add retry-aware delays, filter data earlier, split large loops, and design around documented connector and Power Platform request limits.
 - b. If an **external service call failed (400/500 errors)**, validate the input data. For instance, null values might cause a connector's schema to reject a request (the **InvalidTemplate** error). **Insert conditions or Null-coalescing logic** to handle blanks, or adjust the target system's requirements.
 2. **Add robust error handling with scopes**, Configure run after settings, retry policies where appropriate, and logging or notification paths for failures and timeouts.
 3. If a flow consistently runs for too long, verify if it's doing more work than necessary. **Optimize the process or split the flow into smaller flows** (e.g., an upstream flow that triggers multiple child flows for parallel processing). Where possible, prefer **filtering data at the source** (like in queries) to reduce volume processed in the flow.
 4. **Test after adjustments:** After each change (e.g., adding a delay or fix), run the flow again to confirm it completes successfully or at least fails in a more manageable way.

Flow triggering unexpectedly or multiple times

The flow runs more frequently than intended, potentially duplicating actions or data changes.

- **Cause:** This often stems from triggers configured too broadly or flows **that trigger themselves inadvertently**. For example, a SharePoint “Item modified” trigger could fire again when the flow writes back to the same item, causing an infinite loop. Concurrency settings might also allow parallel triggers that conflict.
- **Solution:** Prevent re-trigger and refine trigger scope:
 1. Use **Trigger Conditions** to ensure the flow only triggers when specific conditions are met (for example, trigger on update only if a certain field value is a specific status to avoid infinite updates).
 2. If a flow **updates the same item which triggers it**, consider adding a **flag field** that the flow sets and checks to ignore self-generated updates.
 3. **Turn off concurrency** for triggers and certain actions where ordering matters, or conversely use concurrency and batching deliberately to handle legitimate high-frequency events safely.
 4. Validate there are not multiple similar flows inadvertently configured on the same trigger/event. Consolidate logic if needed.

Power Automate: Desktop Flows (RPA)

Power Automate Desktop flows (Robotic Process Automation) can encounter issues with machine connectivity, user sessions, and UI interactions. Key issues and resolutions include:

Attended desktop flow not running

An attended desktop flow does not execute when triggered.

- **Cause:** The target machine is not in the proper state for attended automation. Specifically, an attended flow will fail if **no active user session exists** or if the user's session is locked (in attended mode, someone must be logged in and the workstation unlocked). Additionally, outdated software on the machine could cause compatibility issues.
- **Solution:** Ensure the designated user is signed in and the session is active and unlocked when the attended automation runs. If the process must run without user presence, redesign it as an unattended scenario with the appropriate licensing, machine configuration, and run context. Keep Power Automate for desktop updated to avoid version mismatches.

Unattended RPA Flow Fails to Connect

An **unattended** desktop flow fails with connection or session errors (for example, “cannot create a session” or “machine not found”).

- **Cause:** Unattended automation requires an available machine with no active local user session blocking the run, a valid desktop flow connection, Remote Desktop permissions, compatible operating system configuration, and a registered machine that can communicate with Power Automate.
- **Solution:** Verify machine setup and credentials:
 1. Ensure the target machine is **online and connected** to Power Automate (check the machine's status in Power Automate's Machines list).
 2. Verify that **Remote Desktop is enabled** where required and that the account used by the desktop flow connection is **allowed to create remote desktop sessions**, typically through the Remote Desktop Users group or an equivalent approved configuration.

3. Confirm the machine's **Power Automate agent (UIFlowService)** is running. If not, start the service. If you encounter logon failures for the service, check the credentials the service uses.
4. If you see a specific error code (like **UnattendedUserSessionNotActive** or **UIFlowServiceNoRdpPermissions**), consult detailed docs for that code. Many session errors can be resolved by adjusting local security policies (ensuring no policies block that service's user from logging on).
5. After adjusting settings, **re-register the machine** in Power Automate if needed (especially if it was cloned or had major changes), then try the run again.

UI Element Not Found or Automation Fails Mid-run

The desktop flow starts but one of the actions (click, text input, etc.) fails with an error about not finding a UI element or window.

- **Cause:** The target application's interface has changed or wasn't in the expected state. For example, a button label changed, the window didn't load in time, or the selector for the UI element is not accurate enough.
- **Solution:** Refine and robustify the UI selectors:
 1. Use the **Recorder/Selector editor** to re-capture the UI element and ensure attributes used in the selector are stable (avoid IDs that change, prefer names or hierarchical anchors).
 2. Insert appropriate **delays or wait-for-element actions** in the flow to allow the application to load fully before the RPA action executes.
 3. If resolution or window state differences cause issues, try adjusting the selector to be more flexible (wildcards for slight text differences, or remove unnecessary conditions). Test the fixed steps in attended mode first to ensure reliability.

For resilient RPA design, validate environmental consistency between authoring and runtime sessions, including screen resolution, DPI, operating system version, and application state.

Microsoft Dataverse

Dataverse is the data platform behind many Power Platform solutions. Common troubleshooting areas include role-based security, service protection limits, request entitlements, solution dependencies, and integration behavior.

Insufficient privileges or permission errors

A user, application user, or process cannot create, read, update, delete, assign, or share a Dataverse record.

- **Cause:** The user or application identity does not have the necessary Dataverse security role, table privilege, access level, or record-level access for the requested operation.
- **Solution: Adjust security roles:**
 1. Identify which table and operation the error pertains to (the error message or logs usually indicate the entity and permission type). Then, in the Power Platform environment, update the user's security role to include that table permission at the appropriate scope (organization, business unit, etc.), or assign an additional role that has those rights.
 2. For Canvas Apps using Dataverse, ensure end-users have the correct roles assigned. For Power Automate flows using a Dataverse connector, ensure the connection owner or service principal has needed privileges.
 3. After changes, test the operation again.

Dataverse Operation Throttling or Timeouts

Integrations or queries to Dataverse are slow or intermittently failing, possibly with “time-out” errors.

- **Cause:** The workload may be retrieving large datasets without filters, running expensive queries, executing plug-ins or business rules on high-volume operations, or exceeding Dataverse service protection limits or Power Platform request entitlements.
- **Solution:** Optimize data access by filtering at the source, paging results, reducing unnecessary columns, batching operations appropriately, handling HTTP 429 responses with retry-after logic, and avoiding bursty integration patterns. For sustained high-volume workloads, review architecture, request allocations, service protection behavior, and any synchronous plug-ins or business rules that add processing overhead.

Solution Import or Pipeline Errors (Dataverse)

Importing a solution to a new environment fails with a generic error or missing component message.

- **Cause:** This usually signals **missing dependencies or version conflicts**. The solution might reference a component (table, flow, app, etc.) that isn't present in the target environment or depends on a solution not yet imported. If using ****Power Platform Pipelines**** or other ALM automation, some components (like certain data connections, or objects from an unsupported product) might not deploy smoothly.
- **Solution: Check the import error details** (download the error log from the failed import in Power Platform admin center). Identify the missing dependency or error code:
 1. If a dependency is missing (e.g., a specific connector or dependent solution), import that prerequisite first or include it in the solution package.
 2. If the error is generic (e.g., "Something went wrong, please try again"), try importing the solution manually to get a clearer error, or strip out less-critical components to isolate the issue.
 3. For pipeline usage, ensure that all connection references and environment variables are configured in the target environment before deploying. If the solution contains components not yet supported by pipelines (e.g., Power BI items or older Dataflow types), you may need a ****manual deployment step**** or workaround for those components.
 4. Once the cause is resolved (e.g., add missing component or fix version mismatches by exporting latest version), re-export and import again.

Power Pages

Power Pages issues often involve content publishing, server-side caching, page permissions, table permissions, web roles, authentication providers, or site configuration.

Web Page Changes Not Visible

Updates made in the Power Pages design studio (or Portal Management app) aren't showing up on the live site.

- **Cause:** The changes may not have been published, the browser may show cached content, or the server-side cache may not yet have refreshed. Configuration changes are cached and may take time to appear unless the cache is explicitly cleared.
- **Solution:** Publish the site changes, use Preview or Sync as appropriate, clear server-side cache when immediate visibility is required, and clear browser cache if needed. Also confirm that you are editing the intended site and environment.

Users See “Access Denied” or Missing Content

Certain users cannot view a page or data that they should see, or they get a login prompt unexpectedly.

- **Cause: Web roles and table permissions** may not be configured to allow those users to access that content. Power Pages uses web roles (separate from Dataverse security roles) to govern page access and data (list/form) access for authenticated users, and by default, many pages require specific roles.
- **Solution: Configure web roles and permissions.** In the Portal Management app:
 1. Ensure the web page's **Page Permissions** include the appropriate web roles for viewing (if any are set, a user needs one of those roles).
 2. Check any Lists or Forms on the page that display Dataverse data – they often require a Table Permission record allowing that web role to read those records (with correct conditions).
 3. If the user is an anonymous visitor but the page isn't meant to require login, ensure the page is marked as visible to Anonymous users (no login required).
 4. After adjusting roles/permissions, have the user refresh and try again. For debugging, use the Portal's diagnostic tools or try with an admin account to verify the page itself is functional.

Portal site not loading or authentication issues

The site fails to load, or sign-in through an identity provider such as Microsoft Entra ID or Microsoft Entra External ID does not work.

- **Cause:** The site may have provisioning, custom-domain, caching, identity-provider, redirect URI, client ID, secret, tenant, or authentication configuration issues.
- **Solution:** Troubleshoot environment and identity config:
 1. If a portal won't load at all, check the **Portal Admin Center** for any known issues or if the portal is in a provisioning state. Ensure the Azure web app service for the portal is not in a stopped state.
 2. For login issues, double-check all **Identity Provider settings** (redirect URLs, client IDs, secrets, tenant IDs) in the Portal authentication settings. A common cause is a mismatch between what's configured in the identity provider (Azure AD, etc.) and in Power Pages settings.
 3. Use the **Portal Checker** tool (available via the Power Platform admin center) or enable **diagnostic logging** to capture error details. The Portal's error log (accessible with the Browser Developer Tools or by enabling site error display via Site Settings) can give specifics if the error originates from an unhandled exception in a web template or a misconfiguration.
 4. Once identified (e.g., a bad setting or something), correct the configuration and restart the portal if needed.

Microsoft Copilot Studio

Microsoft Copilot Studio is used to create and manage agents that can use knowledge sources, generative answers, topics, actions, connectors, and Power Automate flows. Troubleshooting typically focuses on licensing, environment access, knowledge grounding, tool configuration, and action execution.

Copilot Studio features not available

The user cannot access Copilot Studio, create agents, publish agents, or use expected capabilities.

- **Cause:** The tenant, environment, or user may not have the required Copilot Studio access, user license, tenant capacity, Copilot Credits, Microsoft 365 Copilot eligibility, or admin configuration. Feature availability can also depend on region, channel, and environment settings.

- **Solution:** Verify Copilot Studio licensing and access in the Microsoft 365 admin center and Power Platform admin center. Confirm that the maker has the required user access, that tenant or pay-as-you-go capacity is configured where needed, and that the environment supports the required features before attempting to publish or run the agent.

Agent responses are poor or inaccurate

The agent provides irrelevant, incomplete, or unsupported answers.

- **Cause:** Knowledge sources, topics, instructions, generative answer configuration, actions, or data access permissions may be incomplete or misconfigured.
- **Solution:** Improve grounding and tool design.
 1. Connect the agent to relevant and approved knowledge sources and actions, and verify that the agent has permission to access the data it must use.
 2. Provide clear instructions that define the agent's role, boundaries, fallback behavior, and escalation path.
 3. Keep knowledge sources current, remove conflicting content, and validate whether the expected answer can be retrieved from the configured sources.
 4. Test representative prompts, review conversation analytics or logs where available, and refine topics, actions, instructions, and knowledge iteratively.

Copilot actions failing

The agent identifies an action, such as running a flow or retrieving data, but cannot complete it.

- **Cause:** The action, connector, flow, plugin, authentication configuration, or target API may be unavailable, misconfigured, or missing required permissions.
- **Solution:** Verify action configuration and permissions.
 1. Check that any **Power Automate flows or actions** the agent calls are present in the environment and that the agent's underlying account has access to execute them.
 2. If using a **custom plugin**, ensure it's properly deployed and the endpoints are reachable. Test the plugin in isolation if possible.
 3. Look at the **agent conversation logs** if available to see what error was returned when the action was attempted. Use that information to debug (e.g., if a flow ID was wrong, correct the reference).
 4. As a best practice, design the agent to handle failures gracefully (for example, by giving a helpful message to the user or trying alternative strategies if one tool fails).

Conclusion

By following the troubleshooting steps above, architects and AI assistants can collaboratively identify and resolve issues across Power Platform solutions. Start with the most common causes, such as configuration, permissions, licensing, connection health, and policy constraints, before investigating deeper performance, environment, or architecture issues. For preventative guidance, maintain companion best-practice documentation that covers architecture, governance, ALM, security, monitoring, and operational readiness.

Official Microsoft Learn References

The following official Microsoft Learn pages were used as reference points for the technical review and should be consulted for the latest product guidance.

- **Power Apps delegation:** Understand delegation in a canvas app — <https://learn.microsoft.com/en-us/power-apps/maker/canvas-apps/delegation-overview>
- **Power Automate cloud flow limits:** Limits of automated, scheduled, and instant flows — <https://learn.microsoft.com/en-us/power-automate/limits-and-config>
- **Power Automate throttling guidance:** Understand platform limits and avoid throttling — <https://learn.microsoft.com/en-us/power-automate/guidance/coding-guidelines/understand-limits>
- **Power Automate Desktop unattended runs:** Run unattended desktop flows — <https://learn.microsoft.com/en-us/power-automate/desktop-flows/run-unattended-desktop-flows>
- **Dataverse API limits:** Service protection API limits — <https://learn.microsoft.com/en-us/power-apps/developer/data-platform/api-limits>
- **Power Pages table permissions:** Configure table permissions — <https://learn.microsoft.com/en-us/power-pages/security/table-permissions>
- **Copilot Studio knowledge sources:** Knowledge sources summary — <https://learn.microsoft.com/en-us/microsoft-copilot-studio/knowledge-copilot-studio>
- **Copilot Studio data policies:** Configure data policies for agents — <https://learn.microsoft.com/en-us/microsoft-copilot-studio/admin-data-loss-prevention/>

- **Copilot Studio agent lifecycle:** Agent development lifecycle — <https://learn.microsoft.com/en-us/microsoft-copilot-studio/guidance/architecture/deployment-lifecycle>