

S2S-08: OpenPipeline and Grail Bucket Migration

Series: S2S | **Notebook:** 8 of 12 | **Created:** March 2026 | **Last Updated:** 03/23/2026

Overview

OpenPipeline processing rules and Grail bucket definitions control how data is routed, enriched, and retained. These must be migrated as a coordinated unit — deploying routing rules without the target bucket causes data loss.

Table of Contents

- 1. [Bucket Migration](#)
- 2. [OpenPipeline Rule Migration](#)
- 3. [Retention Policy Alignment](#)
- 4. [Coordinated Deployment](#)

Prerequisites

Requirement	Details
Target Tenant	Provisioned with appropriate license for custom buckets
Permissions	<code>storage:bucket-definitions:write</code> , <code>openpipeline:configurations:write</code>

1. Bucket Migration

Export Source Buckets

```
# Monaco export
monaco download manifest.yaml --environment source \
  --specific-settings builtin:bucket-definitions

# Or via Terraform
terraform import dynatrace_platform_bucket.my_bucket "<bucket-name>"
```

Bucket Naming for Consolidation

When consolidating tenants, bucket names may collide:

Source Tenant	Bucket Name	Target Bucket Name
US-East	app_logs	us-east_app_logs
EU-West	app_logs	eu-west_app_logs
APAC	app_logs	apac_app_logs

Alternative: If consolidating into a single logical bucket, merge routing rules to target one bucket with enrichment tags for filtering.

2. OpenPipeline Rule Migration

OpenPipeline rules define how logs, metrics, and events are processed:

Rule Type	What It Does	Migration Notes
Processing rules	Parse, transform, enrich	Port as-is if field names match
Routing rules	Route to specific buckets	Update bucket references to target names
Filtering rules	Drop or sample data	Port as-is
Extraction rules	Extract fields from content	Port as-is

3. Retention Policy Alignment

Environment	Source Retention	Target Retention	Action
Production	360 days (PCI)	360 days	Match exactly
Staging	35 days	35 days	Match or reduce
Development	7 days	7 days	Match or reduce

Compliance Note: For regulated industries, verify that retention policies in the target tenant meet all compliance requirements before cutover.

4. Coordinated Deployment

Deploy in this order:

1. **Buckets first** — create all target buckets
2. **Enrichment rules** — ensure tags are populating
3. **OpenPipeline rules** — route data to new buckets
4. **Verify** — confirm data flows to correct buckets

```
# Deploy all three in one Monaco command
monaco deploy manifest.yaml --environment target
```

Next Steps

Continue to **S2S-09: Data Continuity and Parallel Operation** to plan the dual-tenant transition period.

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.