

ORGNZ-07: Advanced Permission Patterns

Series: ORGNZ | **Notebook:** 7 of 9 | **Created:** January 2026 | **Last Updated:** 01/28/2026

Overview

This notebook covers advanced permission patterns including record-level permissions, field-based access, and combining multiple access control mechanisms for enterprise-scale data governance.

Prerequisites


Requirement	Details
Dynatrace Account	Account-level administrative access
Permissions	IAM policy management permissions
Knowledge	Completed ORGNZ-04 through ORGNZ-06

Learning Objectives

- By the end of this notebook, you will:
- Implement record-level permissions using various attributes
 - Understand field-level access restrictions
 - Combine bucket, record, and field-level policies
 - Design enterprise-scale permission architectures

Record-Level Permissions

Record-level permissions filter data at query time based on record attributes:



Supported Record-Level Conditions

Condition	Description	Example
storage:k8s.namespace.name	Kubernetes namespace	= 'production'
storage:k8s.cluster.name	Kubernetes cluster	= 'main-cluster'
storage:host.name	Host name	= 'web-server-01'
storage:dt.host_group.id	Host group	STARTSWITH 'prod-'
storage:service.name	Service name	= 'checkout'
storage:aws.account.id	AWS account	= '123456789012'
storage:gcp.project.id	GCP project	= 'my-project'
storage:dt.security_context	Custom context	MATCH ('team-*')

Record-Level Policy Examples

Kubernetes Namespace Isolation

```
{
  "name": "production-namespace-access",
  "description": "Access only to production namespace data",
  "statementQuery": "ALLOW storage:buckets:read WHERE storage:bucket-name
STARTSWITH 'default_'; ALLOW storage:logs:read WHERE
storage:k8s.namespace.name = 'production';"
}
```

Host Group Based Access

```
{
  "name": "web-tier-access",
  "description": "Access to web tier hosts only",
  "statementQuery": "ALLOW storage:buckets:read WHERE storage:bucket-name
STARTSWITH 'default_'; ALLOW storage:logs:read, storage:metrics:read WHERE
storage:dt.host_group.id STARTSWITH 'web-';"
}
```

Combined Namespace and Host Group

```
{
  "name": "prod-web-tier-access",
  "description": "Production web tier only",
  "statementQuery": "ALLOW storage:buckets:read WHERE storage:bucket-name
STARTSWITH 'default_'; ALLOW storage:logs:read WHERE
storage:k8s.namespace.name = 'production' AND storage:dt.host_group.id
STARTSWITH 'web-';"
}
```

Cloud Account Isolation

```
{
  "name": "aws-team-account-access",
  "description": "Access to specific AWS account",
  "statementQuery": "ALLOW storage:buckets:read WHERE storage:bucket-name STARTSWITH 'default_'; ALLOW storage:logs:read, storage:metrics:read, storage:spans:read WHERE storage:aws.account.id = '123456789012';"
}
```

Field-Level Access

Control access to specific fields within records:

Use Case	Implementation
Hide sensitive fields	Deny access to specific fields
Mask PII	Field-level policies
Compliance requirements	Restrict access to audit fields

Field-Level Policy Example

```
{
  "name": "restricted-field-access",
  "description": "Hide sensitive fields from general users",
  "statementQuery": "ALLOW storage:buckets:read WHERE storage:bucket-name STARTSWITH 'default_'; ALLOW storage:logs:read; DENY storage:logs:read:user.email, storage:logs:read:user.ip_address;"
}
```

Combined Permission Patterns

Pattern 1: Layered Access Control

Combine bucket and record-level permissions:

Layer 1: Bucket access

```
ALLOW storage:buckets:read WHERE bucket-name IN ('team_logs',  
'shared_logs')
```

Layer 2: Record filtering

```
ALLOW storage:logs:read WHERE k8s.namespace.name = 'team-namespace'
```

Layer 3: Field masking (optional)

```
DENY storage:logs:read:sensitive_field
```

Pattern 2: Multi-Team Shared Bucket

Multiple teams share a bucket with security context isolation:

```
// Team A policy  
{  
  "name": "team-a-shared-bucket",  
  "statementQuery": "ALLOW storage:buckets:read WHERE storage:bucket-name =  
'shared_logs'; ALLOW storage:logs:read WHERE storage:dt.security_context  
MATCH ('team-a*');"  
}  
  
// Team B policy  
{  
  "name": "team-b-shared-bucket",  
  "statementQuery": "ALLOW storage:buckets:read WHERE storage:bucket-name =  
'shared_logs'; ALLOW storage:logs:read WHERE storage:dt.security_context  
MATCH ('team-b*');"  
}
```


Pattern 3: Environment-Based Tiering

```
// Production access (restricted)
{
  "name": "production-access",
  "statementQuery": "ALLOW storage:buckets:read WHERE storage:bucket-name
STARTSWITH 'prod_'; ALLOW storage:logs:read WHERE storage:dt.security_context
= 'env:production';"
}

// Non-production access (broader)
{
  "name": "non-production-access",
  "statementQuery": "ALLOW storage:buckets:read WHERE storage:bucket-name
STARTSWITH 'default_'; ALLOW storage:logs:read WHERE
storage:dt.security_context MATCH ('env:dev*', 'env:staging*', 'env:qa*');"
}
```

Enterprise Architecture Patterns

Tiered Access Model



Geographic/Regulatory Model

Region	Buckets	Context	Policy
EU	eu_*	region:eu	bucket-name STARTSWITH 'eu_' AND security_context MATCH ('region:eu*')
US	us_*	region:us	bucket-name STARTSWITH 'us_' AND security_context MATCH ('region:us*')

Testing Permissions

```
// Test namespace-based access
fetch logs
| filter isNotNull(k8s.namespace.name)
| summarize count = count(), by:{k8s.namespace.name}
| sort count desc
```

```
// Test host group access
fetch logs
| filter isNotNull(dt.host_group.id)
| summarize count = count(), by:{dt.host_group.id}
| sort count desc
```

```
// Verify accessible data distribution
fetch logs
| summarize
    total = count(),
    withSecurityContext = countIf(isNotNull(dt.security_context)),
    withNamespace = countIf(isNotNull(k8s.namespace.name)),
    withHostGroup = countIf(isNotNull(dt.host_group.id))
```

Best Practices

Practice	Rationale
Start with least privilege	Grant minimum required access
Use groups, not individuals	Easier management, consistent access
Document all policies	Audit trail and governance
Test policies before deployment	Prevent access issues
Regular access reviews	Remove unnecessary permissions
Use MATCH for array fields	Required for correct evaluation
Combine bucket + record level	Defense in depth

Next Steps

Continue with the ORGNZ series:
- **ORGNZ-08**: Grail Segments

References

- [Configure advanced permissions with security context](#)
- [IAM policy reference](#)
- [Enhance data management with Grail](#)

This notebook was AI-generated from Dynatrace documentation and enterprise best practices. It is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.