

MZ2POL-08: Templated Policies for MZ Migration

Series: MZ2POL | **Notebook:** 9 of 9 | **Created:** February 2026 | **Last Updated:** 04/04/2026

Overview

When migrating from Management Zones at scale, organizations with dozens of MZ-based teams face the challenge of creating and maintaining an equivalent number of IAM policies. Policy templating with `${bindParam:...}` parameters eliminates this duplication.

This notebook shows how to convert common MZ access patterns into parameterized policy templates, bind them at scale via the IAM API, and validate the migrated access using DQL queries.

Table of Contents

- [1. Why Templates Matter for MZ Migration](#)
 - [2. Converting MZ Patterns to Parameterized Policies](#)
 - [3. Template Patterns for Common MZ Replacements](#)
 - [4. Bulk Binding via IAM API](#)
 - [5. Validating Migrated Access with DQL](#)
 - [6. Before/After Comparison Patterns](#)
-

Prerequisites

Requirement	Details
Dynatrace Environment	SaaS with Gen3 IAM and Grail enabled
Permissions	<code>account-iam-admin</code> for policy and binding management
API Access	OAuth client or API token with IAM management scopes
Prior Knowledge	MZ2POL-04: Policies and Boundaries (G-P-B pattern, policy syntax)
Migration Status	MZ assessment complete (MZ2POL-03), security context assigned

1. Why Templates Matter for MZ Migration

The Scale Problem

The average Dynatrace customer has **92 Management Zones** with **1,700 conditions**. Each MZ needs a policy equivalent. Without templates, that means creating and maintaining 92 individual policies.

Approach	Policies to Create	Maintenance Effort	Audit Complexity
One policy per MZ	92	High — each permission change requires 92 edits	92 policies to review
Templated policies	3-5 templates	Low — edit template once, all bindings updated	3-5 templates + bindings

Where Templates Fit in the 6-Phase Migration

Templates are most impactful in Phases 3-5 of the migration (from **MZ2POL-06**):

Phase	Activity	Template Role
Phase 1: Assessment	Inventory MZs	Classify MZ types → identify which template to use
Phase 2: Tagging	Set security context	Values become template parameter values
Phase 3: Access Management	Create policies	Create 3-5 templates instead of 92 policies
Phase 4: Implementation	Bind to groups	Bulk bind via IAM API script
Phase 5: Validation	Verify access	DQL queries to validate bindings
Phase 6: Cutover	Remove MZs	No template impact

2. Converting MZ Patterns to Parameterized Policies

Each MZ type (from the **MZ2POL REFERENCE**) maps to a specific template pattern.

Vertical MZ (Environment-Based)

Before: MZ "Production" with host group rules.

Template:

```
ALLOW storage:*:read WHERE storage:dt.security_context =
"${bindParam:environment}";
ALLOW settings:objects:read WHERE settings:dt.security_context =
"${bindParam:environment}";
```

Bindings:

- Production team: `{"parameters": {"environment": "prod"}}`
- Staging team: `{"parameters": {"environment": "staging"}}`

Horizontal MZ (Team-Based)

Before: MZ "Frontend-Team" with service tag rules.

Template:

```
ALLOW storage:logs:read WHERE storage:dt.security_context =
"${bindParam:team}";
ALLOW storage:spans:read WHERE storage:dt.security_context =
"${bindParam:team}";
ALLOW storage:metrics:read WHERE storage:dt.security_context =
"${bindParam:team}";
```

Binding: {"parameters": {"team": "team-frontend"}}

LOB MZ (Line of Business)

Before: MZ "LOB5" with combined host group + service tag rules.

Template (three-domain, matching MZ2POL-04 best practice):

```
ALLOW storage:*:read WHERE storage:dt.security_context = "${bindParam:lob}";
ALLOW storage:*:write WHERE storage:dt.security_context = "${bindParam:lob}";
ALLOW settings:objects:* WHERE settings:dt.security_context =
"${bindParam:lob}";
```

Combined with a **boundary** using the same scope:

```
environment:management-zone IN ("LOB5");
storage:dt.security_context IN ("LOB5");
settings:dt.security_context IN ("LOB5");
```

Binding: {"parameters": {"lob": "LOB5"}}

Conversion Decision Table

MZ Type	Template Type	Parameters	Boundary Needed?
Vertical (environment)	Environment-scoped	environment	Yes — restrict to environment
Horizontal (team)	Team-scoped	team	Yes — restrict to security context
LOB	Full three-domain	lob	Yes — three-domain boundary
Bucket-based	Bucket-scoped	log-bucket , span-bucket	Optional

3. Template Patterns for Common MZ Replacements

These patterns map directly from MZ permission levels to template bindings.

Pattern A: Read-Only Team Access

Replaces: User assigned "Viewer" role in a team MZ.

Template: `tpl-team-data-reader`

```
ALLOW storage:logs:read WHERE storage:dt.security_context =
"${bindParam:team}";
ALLOW storage:spans:read WHERE storage:dt.security_context =
"${bindParam:team}";
ALLOW storage:metrics:read WHERE storage:dt.security_context =
"${bindParam:team}";
ALLOW document:documents:read;
```

Binding: `{"parameters": {"team": "checkout"}}`

Pattern B: Full Team Access

Replaces: User assigned "Editor" role in a team MZ.

Template: `tpl-team-data-editor`

```
ALLOW storage:*:read WHERE storage:dt.security_context = "${bindParam:team}";
ALLOW storage:*:write WHERE storage:dt.security_context =
"${bindParam:team}";
ALLOW settings:objects:* WHERE settings:dt.security_context =
"${bindParam:team}";
ALLOW document:documents:*;
```

Binding: `{"parameters": {"team": "checkout"}}`

Pattern C: Multi-MZ Access

Replaces: User assigned to multiple MZs (e.g., "Checkout" AND "Shared-Services").

Solution: Create **two bindings** of the same template with different parameter values to the same group:

```
# Binding 1: Checkout access
curl -X POST "${API_BASE}/bindings/${POLICY_UUID}/${GROUP_UUID}" \
  -d '{"parameters": {"team": "checkout"}}'

# Binding 2: Shared services access
curl -X POST "${API_BASE}/bindings/${POLICY_UUID}/${GROUP_UUID}" \
  -d '{"parameters": {"team": "shared-services"}}'
```

Both bindings are additive — the user gets access to both scopes.

Pattern D: Regional MZ Replacement

Replaces: MZ "US-East" with region-based host group.

Template: `tpl-region-reader`

```
ALLOW storage:*:read WHERE storage:dt.security_context startsWith
"${bindParam:region-prefix}";
ALLOW settings:objects:read WHERE settings:dt.security_context startsWith
"${bindParam:region-prefix}";
```

Binding: `{"parameters": {"region-prefix": "us-east"}}`

Pattern Summary

Pattern	MZ Permission Level	Template	Key Difference
A	Viewer in MZ	<code>tpl-team-data-reader</code>	Read only
B	Editor in MZ	<code>tpl-team-data-editor</code>	Read + write
C	Multiple MZs	Same template, multiple bindings	Additive access
D	Regional MZ	<code>tpl-region-reader</code>	Prefix match

4. Bulk Binding via IAM API

Organizations with 92 MZs cannot bind one at a time via the UI. Use the IAM API for bulk operations.

Preparation Checklist

Before running bulk binding:

1. **Export MZ list** — Use **MZ2POL-00** SDK tool or Settings API
2. **Map each MZ to a group UUID** — List groups via `GET /iam/v1/accounts/{ACCOUNT}/groups`
3. **Map each MZ to a security context value** — This becomes the parameter value
4. **Choose the appropriate template** — Reader, editor, or three-domain

Bulk Binding Script

```
#!/bin/bash
# Bulk bind team-access template to all team groups
ACCOUNT_UUID="&lt;your-account-uuid&gt;"
POLICY_UUID="&lt;team-reader-template-uuid&gt;"
TOKEN="&lt;bearer-token&gt;"
API_BASE="https://api.dynatrace.com/iam/v1/repo/account/${ACCOUNT_UUID}"

# Map: team name → group UUID
declare -A TEAM_GROUPS=(
    ["checkout"]="&lt;group-uuid-checkout&gt;"
    ["payments"]="&lt;group-uuid-payments&gt;"
    ["catalog"]="&lt;group-uuid-catalog&gt;"
    ["search"]="&lt;group-uuid-search&gt;"
    ["frontend"]="&lt;group-uuid-frontend&gt;"
)

echo "Binding template ${POLICY_UUID} to ${#TEAM_GROUPS[@]} groups..."
for team in "${!TEAM_GROUPS[@]}"; do
    GROUP_UUID="${TEAM_GROUPS[$team]}"
    echo -n "  ${team} (${GROUP_UUID})... "
    HTTP_CODE=$(curl -s -X POST \
        "${API_BASE}/bindings/${POLICY_UUID}/${GROUP_UUID}" \
        -H "Authorization: Bearer ${TOKEN}" \
        -H 'Content-Type: application/json' \
        -d '{"parameters": {"team": "${team}"}}' \
        -o /dev/null -w "%{http_code}")
    if [ "$HTTP_CODE" == "201" ]; then
        echo "Created"
    elif [ "$HTTP_CODE" == "409" ]; then
        echo "Already exists"
    else
        echo "ERROR (HTTP ${HTTP_CODE})"
    fi
done
echo "Done."
```

Verification Script

After bulk binding, verify all bindings exist:


```
# List all bindings for the template policy
curl -s -X GET \
  "${API_BASE}/bindings/${POLICY_UUID}" \
  -H "Authorization: Bearer ${TOKEN}" | python3 -m json.tool
```

Error Handling

HTTP Code	Meaning	Action
201	Binding created	Success
400	Bad request	Check parameter names match policy template
401	Unauthorized	Refresh token
404	Policy/group not found	Verify UUIDs
409	Binding already exists	Skip or update

5. Validating Migrated Access with DQL

After binding templated policies, validate that migrated access matches the original MZ-based access.

```
// Validate: All services have security context for migration
fetch dt.entity.service
| summarize
  total = count(),
  withContext = countIf(isNotNull(dt.security_context)),
  missingContext = countIf(isNull(dt.security_context))
| fields total, withContext, missingContext,
  coveragePercent = round(100.0 * withContext / total, decimals: 2)

// Alternative: Smartscape on Grail (entity.name → name)
// smartscapeNodes SERVICE
// | summarize
// total = count(),
// withContext = countIf(isNotNull(dt.security_context)),
// missingContext = countIf(isNull(dt.security_context))
// | fields total, withContext, missingContext,
// coveragePercent = round(100.0 * withContext / total, decimals: 2)
```

```
// Compare: MZ membership vs security context value alignment
// Replace "Frontend-Team" and "team-frontend" with your MZ and context
values
fetch dt.entity.service
| summarize
    inMZ = countIf(in(managementZones, {"Frontend-Team"})),
    hasContext = countIf(dt.security_context == "team-frontend"),
    inBoth = countIf(in(managementZones, {"Frontend-Team"}) and
dt.security_context == "team-frontend")
| fields inMZ, hasContext, inBoth,
    match = if(inMZ == inBoth, then: "ALIGNED", else: "GAPS EXIST")
```

```
// Find entities in MZ but without matching security context
// These need security context before template binding will work
fetch dt.entity.service
| filter in(managementZones, {"Frontend-Team"})
| filter dt.security_context != "team-frontend" or
isNull(dt.security_context)
| fields entity.name, dt.security_context, managementZones, tags
| sort entity.name asc
| limit 50
```

```
// Audit recent policy binding changes for migration tracking
fetch logs, from: now() - 30d
| filter matchesPhrase(log.source, "audit")
| filter matchesPhrase(content, "binding")
| fields timestamp, content
| sort timestamp desc
| limit 100
```

6. Before/After Comparison Patterns

Validation Framework

For each migrated MZ, verify access parity:

Validation	MZ-Based (Before)	Template-Based (After)	Status
User can query logs in scope	Via MZ filter	Via security context + template binding	☐ Test

Validation	MZ-Based (Before)	Template-Based (After)	Status
User cannot query logs out of scope	MZ excludes	Boundary restricts	☐ Test
Settings access scoped	MZ-based	Settings security context in template	☐ Test
Dashboard access	MZ filter	Segment + boundary	☐ Test

Parallel Running Strategy

During validation, keep both access models active:

1. **Keep MZ active** — Don't remove MZs until template-based access is validated
2. **Add template binding** — Users gain access via both paths temporarily
3. **Test with each model** — Verify same data visible via MZ and via template
4. **Remove MZ assignment** — Only after confirming parity
5. **Monitor for issues** — Watch audit logs for denied events post-cutover

Migration Completion Checklist (Per MZ)

- ☐ Security context set on all entities that were in this MZ
- ☐ Template policy created (or existing template identified)
- ☐ Binding created with correct parameter value
- ☐ Boundary created with matching scope (all three domains)
- ☐ DQL validation — security context coverage matches MZ membership
- ☐ User testing — access parity confirmed
- ☐ MZ assignment removed from RBAC
- ☐ Audit log reviewed for denied events

For full validation procedures, see **MZ2POL-07: Validation and Troubleshooting**.

For comprehensive template syntax and patterns, see **IAM-10: Templated Policy-Group Assignments**.

Summary

In this notebook, you learned:

1. Why policy templates are essential for large-scale MZ migration (3-5 templates vs 92 policies)
2. How to convert vertical, horizontal, and LOB MZ patterns to parameterized policies
3. Four template patterns for common MZ replacement scenarios
4. Bulk binding automation via the IAM API
5. DQL queries to validate that migrated access matches original MZ access
6. Before/after comparison patterns for migration verification

Next Steps

- **MZ2POL-07: Validation and Troubleshooting** — Full validation procedures and ongoing maintenance
- **IAM-10: Templated Policy-Group Assignments** — Deep dive on template syntax, Monaco automation, and advanced patterns

References

- [Policy Templating](#)
- [Policy Management API](#)
- [Working with Policies](#)
- [Access Management Concepts](#)

This notebook was AI-generated from community-submitted and publicly available sources. This notebook series is not officially supported by Dynatrace. Always verify information against official Dynatrace documentation.