ECMWF ERA5 Data Downloader and Extractor

This script works with ERA5 reanalysis data from ECMWF. It can either download hourly ERA5 data via the CDS API and process the resulting GRIB files, or it can solely extract data from existing GRIB files. The extraction process reads GRIB files, selects a set of pre-defined meteorological and oceanographic variables using IDW (Inverse Distance Weighting) to interpolate data to an exact point, and then saves the combined data into a CSV file for analysis.

Operation Modes

The script supports **two modes** of operation:

1. Download & Process Mode

- Purpose: Downloads ERA5 data in monthly chunks using the CDS API and processes each GRIB file.
- Functionality:
 - Connects to the CDS API and downloads data in GRIB format into the grib/ folder
 - Implements robust error handling with a retry mechanism using exponential back-off.
 - Extracts key variables from each GRIB file using IDW interpolation for an accurate estimate at the exact location.
 - Respects the defined time range (default: 1940 to 2025).
 - Logs all major steps and issues to download era5 data.log.

2. Extract Only Mode

- Purpose: Processes all existing GRIB files in the grib/ folder without downloading new data.
- Functionality:
 - Uses parallel processing (via concurrent.futures) and displays a progress har
 - Ignores the defined year range and processes every GRIB file available.
 - Combines the extracted data (using the improved IDW interpolation) into a sorted CSV file for further analysis.

Key Features

- Dual Mode Operation: Choose between downloading new data (Download & Process) or extracting from existing GRIB files (Extract Only).
- Accurate Point Extraction via IDW Interpolation: Retrieves key parameters at the exact provided coordinates using Inverse Distance Weighting (IDW) interpolation over all grid points.
- Selected Variable Extraction: Retrieves key parameters:
 - swh: Significant wave height (combined wind waves and swell)
 - mwd: Mean wave direction
 - o ppld: Peak wave period
 - wind: 10 m wind speed
 - dwi: 10 m wind direction
- Robust Error Handling: Uses retries with exponential back-off (default delay: 60 seconds; maximum 3 attempts) for API requests.
- **Detailed Logging:** All download and processing activities are logged to download era5 data.log.
- Parallel Processing: Option 2 leverages multiprocessing with a progress bar to expedite GRIB file extraction.
- **Performance Metrics:** Reports overall processing time along with average times per month and per year.
- Sorted Output: The final CSV file is sorted by the datetime column.

Files Overview

File	Description
download_era5_data.py	Main script for downloading and/or extracting ERA5 reanalysis data.
download_era5_data.log	Log file capturing download and processing events.
grib/	Directory for storing raw GRIB files.
results/download_era5_data.csv	Processed data saved in CSV format.

About the ERA5 Wave Model

This dataset is derived from the **ECMWF Reanalysis v5 (ERA5) wave model**, which provides hourly estimates of essential climate variables spanning from 1940 to the present. The ERA5 wave model is a component of the ERA5 dataset, developed by the **European Centre for Medium-Range Weather Forecasts (ECMWF)**.

ERA5 Wave Model Highlights:

- Uses **state-of-the-art** numerical weather prediction models and data assimilation techniques.
- Provides hourly data at a 31 km horizontal resolution globally.
- Includes wind-wave interactions, swell propagation, and wave generation mechanisms.

- Incorporates satellite observations, buoy measurements, and reanalysis techniques to improve accuracy.
- Supplies a comprehensive **historical dataset** for research, operational forecasting, and climate applications.

More details can be found at:

- ERA5 Single Levels Dataset
- ECMWF ERA5 Overview

Installation

Install Dependencies

Ensure you have **Python 3.x** installed. Then install the required libraries using **Conda**:

```
conda install -c conda-forge eccodes cdsapi pygrib pandas tqdm
```

Alternatively, use pip:

```
pip install cdsapi pygrib pandas tqdm
```

Set Up CDS API Key

- 1. Register for an **ECMWF account** at: CDS Registration
- 2. Obtain your API key from: CDS API
- 3. Create a .cdsapirc file in your home directory (~/.cdsapirc on Linux/Mac, C:\Users\YourName\.cdsapirc on Windows):

```
url: https://cds.climate.copernicus.eu/api/v2
key: YOUR-USER-ID:YOUR-API-KEY
verify: 1
```

Usage

Run the Script

Use the following command to run the script:

```
python "download_era5_data.py"
```

Configurable Parameters

The script retrieves data at Leixões (Porto, Portugal) Oceanic Buoy with coordinates (41.14833°N, -9.58167°W). You can modify these values in the script:

```
LONGITUDE = -9.581666670
LATITUDE = +41.14833299
```

It downloads data from **1940 to 2025** (notice it takes several hours to run due to MARS server high number of requests). To change the time range, update:

```
START_YEAR = 1940
END YEAR = 2025
```

Variables Retrieved

Variable Short Name Description 140229 Significant height of combined wind waves and swell swh 140230 Mean wave direction mwd Peak wave period 140231 pp1d 10m wind speed wind 140245 140249 10m wind direction dwi

Data Storage

The downloaded data is stored in:

- GRIB files in the grib/ folder.
- **Processed CSV data in** results/download era5 data.csv.

A sample CSV row looks like:

```
datetime, swh, mwd, pp1d, wind, dwi
1940-01-01 00:00:00, 2.5, 280, 8.0, 5.2, 220
```

References