RESET PASSWORD;

```
import React, { useState } from "react";
import { Link, useSearchParams } from "react-router-dom";
import { base44 } from "@/api/base44Client";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Label } from "@/components/ui/label";
import { Lock, Loader2, AlertTriangle } from "lucide-react";
import AuthLayout from "@/components/AuthLayout";

export default function ResetPassword() {
 const [searchParams] = useSearchParams();
 const resetToken = searchParams.get("token");

 const [newPassword, setNewPassword] = useState("");
 const [confirmPassword, setConfirmPassword] = useState("");
 const [error, setError] = useState("");
 const [loading, setLoading] = useState(false);

 const handleSubmit = async (e) => {
  e.preventDefault();
  setError("");
  if (newPassword !== confirmPassword) {
   setError("Passwords do not match");
   return;
  }
  setLoading(true);
  try {
   await base44.auth.resetPassword({ resetToken, newPassword });
   window.location.href = "/login";
  } catch (err) {
   setError(err.message || "Failed to reset password");
  } finally {
   setLoading(false);
  }
 };

 if (!resetToken) {
  return (
   <AuthLayout
    icon={AlertTriangle}
    title="Invalid reset link"
    subtitle="This password reset link is missing or invalid"
    footer={
     <Link to="/forgot-password" className="text-primary font-medium hover:underline">
      Request a new link
     </Link>
    }
   >
    <p className="text-sm text-foreground text-center">
     The link you used appears to be incomplete. Please request a new password reset
```

```
email.
    </p>
   </AuthLayout>
  );
 }

 return (
  <AuthLayout
   icon={Lock}
   title="New password"
   subtitle="Enter your new password below"
  >
   {error && (
    <div className="mb-4 p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
     {error}
    </div>
   )}
   <form onSubmit={handleSubmit} className="space-y-4">
    <div className="space-y-2">
     <Label htmlFor="password">New Password</Label>
     <div className="relative">
      <Lock className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-
foreground" aria-hidden="true" />
      <Input
       id="password"
       type="password"
       autoComplete="new-password"
       autoFocus
       placeholder="••••••••"
       value={newPassword}
       onChange={(e) => setNewPassword(e.target.value)}
       className="pl-10 h-12"
       required
      />
     </div>
    </div>
    <div className="space-y-2">
     <Label htmlFor="confirm">Confirm Password</Label>
     <div className="relative">
      <Lock className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-
foreground" aria-hidden="true" />
      <Input
       id="confirm"
       type="password"
       autoComplete="new-password"
       placeholder="••••••••"
       value={confirmPassword}
       onChange={(e) => setConfirmPassword(e.target.value)}
       className="pl-10 h-12"
       required
      />
     </div>
```

```
    </div>
    <Button type="submit" className="w-full h-12 font-medium" disabled={loading}>
     {loading ? (
      <>
       <Loader2 className="w-4 h-4 mr-2 animate-spin" />
       Resetting...
      </>
     ) : (
      "Reset password"
     )}
    </Button>
   </form>
  </AuthLayout>
 );
}
```