
# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

| BSPP | T2013 |
|---|---|





**BSPP MALE**
**60° SEAT**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T2013-0302** | 5 | 3/16 | 1/8" -28 | | -0302 | 1.65 | 42 | 0.87 | 22 | | | | | 5/8 | 16 |
| **T2013-0304** | 5 | 3/16 | 1/4" -19 | | -0304 | 1.89 | 48 | 1.10 | 28 | | | | | 3/4 | 19 |
| **T2013-0402** | 6 | 1/4 | 1/8" -28 | | -0402 | 1.97 | 50 | 0.94 | 24 | | | | | | 14 |
| **T2013-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.09 | 53 | 1.10 | 28 | | | | | 3/4 | 19 |
| **T2013-0406** | 6 | 1/4 | 3/8" -19 | | -0406 | 2.09 | 53 | 1.10 | 28 | | | | | 7/8 | 22 |
| **T2013-0408** | 6 | 1/4 | 1/2" -14 | | -0408 | 2.28 | 58 | 1.30 | 33 | | | | | 1.1/16 | 27 |
| **T2013-0504** | 8 | 5/16 | 1/4" -19 | | -0504 | 2.09 | 53 | 1.10 | 28 | | | | | 3/4 | 19 |
| **T2013-0506** | 8 | 5/16 | 3/8" -19 | | -0506 | 2.13 | 54 | 1.14 | 29 | | | | | 7/8 | 22 |
| **T2013-0604** | 10 | 3/8 | 1/4" -19 | | -0604 | 2.09 | 53 | 1.10 | 28 | | | | | 3/4 | 19 |
| **T2013-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.13 | 54 | 1.14 | 29 | | | | | 7/8 | 22 |
| **T2013-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.28 | 58 | 1.30 | 33 | | | | | 1.1/16 | 27 |
| **T2013-0806** | 12 | 1/2 | 3/8" -19 | | -0806 | 2.17 | 55 | 1.18 | 30 | | | | | 7/8 | 22 |
| **T2013-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.28 | 58 | 1.34 | 34 | | | | | 1.1/16 | 27 |
| **T2013-0810** | 12 | 1/2 | 5/8" -14 | | -0810 | 2.40 | 61 | 1.42 | 36 | | | | | 1.3/16 | 30 |
| **T2013-0812** | 12 | 1/2 | 3/4" -14 | | -0812 | 2.48 | 63 | 1.54 | 39 | | | | | 1.1/4 | 32 |
| **T2013-1008** | 16 | 5/8 | 1/2" -14 | | -1008 | 2.52 | 64 | 1.30 | 33 | | | | | 1.1/16 | 27 |
| **T2013-1010** | 16 | 5/8 | 5/8" -14 | | -1010 | 2.64 | 67 | 1.46 | 37 | | | | | 1.3/16 | 30 |
| **T2013-1012** | 16 | 5/8 | 3/4" -14 | | -1012 | 2.72 | 69 | 1.50 | 38 | | | | | 1.1/4 | 32 |
| **T2013-1208** | 19 | 3/4 | 1/2" -14 | | -1208 | 2.52 | 64 | 1.34 | 34 | | | | | 1.1/16 | 27 |
| **T2013-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.72 | 69 | 1.54 | 39 | | | | | 1.1/4 | 32 |
| **T2013-1612** | 25 | 1 | 3/4" -14 | | -1612 | 2.80 | 71 | 1.57 | 40 | | | | | 1.1/4 | 32 |
| **T2013-1616** | 25 | 1 | 1" -11 | | -1616 | 2.95 | 75 | 1.77 | 45 | | | | | 1.5/8 | 41 |
| **T2013-1620** | 25 | 1 | 1.1/4" -11 | | -1620 | 3.15 | 80 | 1.93 | 49 | | | | | 2 | 50 |
| **T2013-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 3.98 | 101 | 2.01 | 51 | | | | | 2 | 50 |
| **T2013-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 4.17 | 106 | 2.13 | 54 | | | | | 2.3/16 | 55 |
| **T2013-2432** | 38 | 1.1/2 | 2" -11 | | -2432 | 4.65 | 118 | 2.64 | 67 | | | | | 2.3/4 | 70 |
| **T2013-3232** | 51 | 2 | 2" -11 | | -3232 | 4.84 | 123 | 2.64 | 67 | | | | | 2.3/4 | 70 |

## BSPP — T2017


**BSPP MALE**
**ENCAPSULATED SEAL**




| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | inch | mm | inch | mm | | | | | inch | mm |
| **T2017-0404** | 6 | 1/4 | 1/4" -19 | -0404 | 2.17 | 55 | 1.18 | 30 | | | | | 3/4 | 19 |
| **T2017-0606** | 10 | 3/8 | 3/8" -19 | -0606 | 2.13 | 54 | 1.18 | 30 | | | | | 7/8 | 22 |
| **T2017-0808** | 12 | 1/2 | 1/2" -14 | -0808 | 2.36 | 60 | 1.38 | 35 | | | | | 1.1/16 | 27 |
| **T2017-1212** | 19 | 3/4 | 3/4" -14 | -1212 | 2.72 | 69 | 1.54 | 39 | | | | | 1.1/4 | 32 |
| **T2017-1616** | 25 | 1 | 1" -11 | -1616 | 2.95 | 75 | 1.77 | 45 | | | | | 1.5/8 | 41 |
| **T2017-2020** | 31 | 1.1/4 | 1.1/4" -11 | -2020 | 3.98 | 101 | 2.01 | 51 | | | | | 2 | 50 |

## BSPP — T2020

**BSPP FEMALE**
**60 ° CONE**





| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2020-0302** | 5 | 3/16 | 1/8" -28 | -0302 | 1.61 | 41 | 0.83 | 21 | | | | 14 | 7/16 | 11 |
| **T2020-0304** | 5 | 3/16 | 1/4" -19 | -0304 | 1.61 | 41 | 0.87 | 22 | | | 3/4 | 19 | 1/2 | |
| **T2020-0402** | 6 | 1/4 | 1/8" -28 | -0402 | 1.93 | 49 | 0.91 | 23 | | | | 14 | 1/2 | |
| **T2020-0404** | 6 | 1/4 | 1/4" -19 | -0404 | 1.93 | 49 | 0.94 | 24 | | | 3/4 | 19 | 1/2 | |
| **T2020-0406** | 6 | 1/4 | 3/8" -19 | -0406 | 2.05 | 52 | 1.02 | 26 | | | 7/8 | 22 | 5/8 | 16 |
| **T2020-0504** | 8 | 5/16 | 1/4" -19 | -0504 | 1.85 | 47 | 0.87 | 22 | | | 3/4 | 19 | 9/16 | |
| **T2020-0506** | 8 | 5/16 | 3/8" -19 | -0506 | 1.93 | 49 | 0.94 | 24 | | | 7/8 | 22 | 5/8 | 16 |
| **T2020-0604** | 10 | 3/8 | 1/4" -19 | -0604 | 1.93 | 49 | 0.94 | 24 | | | 3/4 | 19 | 5/8 | 16 |
| **T2020-0606** | 10 | 3/8 | 3/8" -19 | -0606 | 2.05 | 52 | 1.06 | 26 | | | 7/8 | 22 | 5/8 | 16 |
| **T2020-0608** | 10 | 3/8 | 1/2" -14 | -0608 | 2.09 | 55 | 1.10 | 30 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T2020-0806** | 12 | 1/2 | 3/8" -19 | -0806 | 2.05 | 52 | 1.06 | 27 | | | 7/8 | 22 | 3/4 | 19 |
| **T2020-0808** | 12 | 1/2 | 1/2" -14 | -0808 | 2.09 | 53 | 1.10 | 28 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T2020-0812** | 12 | 1/2 | 3/4" -14 | -0812 | 2.13 | 57 | 1.18 | 32 | | | 1.1/4 | 32 | 1 | |
| **T2020-1008** | 16 | 5/8 | 1/2" -14 | -1008 | 2.40 | 61 | 1.18 | 30 | | | 1.1/16 | 27 | 7/8 | 22 |
| **T2020-1010** | 16 | 5/8 | 5/8" -14 | -1010 | 2.36 | 60 | 1.14 | 29 | | | 1.3/16 | 30 | 7/8 | 22 |
| **T2020-1012** | 16 | 5/8 | 3/4" -14 | -1012 | 2.28 | 58 | 1.06 | 27 | | | 1.1/4 | 32 | 1 | |
| **T2020-1208** | 19 | 3/4 | 1/2" -14 | -1208 | 2.52 | 64 | 1.30 | 33 | | | 1.1/16 | 27 | 15/16 | 24 |
| **T2020-1212** | 19 | 3/4 | 3/4" -14 | -1212 | 2.44 | 60 | 1.30 | 31 | | | 1.1/4 | 32 | 1.1/16 | 27 |
| **T2020-1216** | 19 | 3/4 | 1" -11 | -1216 | 2.72 | 67 | 1.54 | 37 | | | 1.1/2 | 38 | 1.1/16 | 27 |
| **T2020-1612** | 25 | 1 | 3/4" -14 | -1612 | 2.56 | 65 | 1.34 | 34 | | | 1.1/4 | 32 | 1.1/4 | 32 |
| **T2020-1616** | 25 | 1 | 1" -11 | -1616 | 2.68 | 68 | 1.46 | 36 | | | 1.1/2 | 38 | 1.1/4 | 32 |
| **T2020-1620** | 25 | 1 | 1.1/4" -11 | -1620 | 2.91 | 74 | 1.69 | 43 | | | 2 | 50 | 1.1/4 | 37 |
| **T2020-2020** | 31 | 1.1/4 | 1.1/4" -11 | -2020 | 3.70 | 94 | 1.77 | 45 | | | 2 | 50 | 1.5/8 | 41 |
| **T2020-2424** | 38 | 1.1/2 | 1.1/2" -11 | -2424 | 3.90 | 99 | 1.85 | 47 | | | 2.3/16 | 55 | 2 | 50 |
| **T2020-3232** | 51 | 2 | 2" -11 | -3232 | 4.33 | 110 | 2.13 | 54 | | | 2.3/4 | 70 | 2.1/2 | |
| **T2020-4040** | 63 | 2.1/2 | 2 1/2" -11 | -4040 | 4.72 | 120 | 1.73 | 44 | | | 3.1/2 | 90 | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

### BSPT — T2320


**BSPT MALE SWIVEL**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | | |
| **T2320-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.32 | 59 | 1.34 | 34 | | | 7/8 | 22 | | |
| **T2320-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.32 | 59 | 1.34 | 34 | | | 1 | | | |
| **T2320-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.80 | 71 | 1.81 | 46 | | | 1 | | | |

### BSPT — T2340


**BSPT MALE SWIVEL**
**90° ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2340-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 1.89 | 48 | 0.91 | 23 | 1.77 | 45 | 7/8 | 22 | 3/4 | 19 |
| **T2340-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 1.89 | 48 | 0.91 | 23 | 1.97 | 50 | 1 | | 3/4 | 19 |
| **T2340-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.13 | 54 | 1.14 | 29 | 2.05 | 52 | 1 | | 7/8 | 22 |
| **T2340-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.36 | 60 | 1.22 | 31 | 1.77 | 45 | 1.1/4 | 32 | 1.1/16 | 27 |

### BSPP — T2028B


**BSPP FEMALE**
**LIVE SWIVEL**
**60° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2028B-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.64 | 67 | 1.61 | 41 | | | 3/4 | 19 | 11/16 | |
| **T2028B-0604** | 10 | 3/8 | 1/4" -19 | | -0604 | 2.60 | 66 | 1.65 | 42 | | | 3/4 | 19 | 11/16 | |

## BSPP — T2024


**BSPP FEMALE**
**FLAT FACE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2024-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.85 | 47 | 0.87 | 22 | | | 3/4 | 19 | 1/2 | |
| **T2024-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 1.93 | 49 | 0.94 | 24 | | | 7/8 | 22 | 5/8 | 16 |
| **T2024-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 1.81 | 46 | 0.83 | 21 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T2024-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 1.85 | 47 | 0.87 | 22 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T2024-0812** | 12 | 1/2 | 3/4" -14 | | -0812 | 2.09 | 53 | 1.10 | 28 | | | 1.1/4 | 32 | 1 | |
| **T2024-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.28 | 58 | 1.14 | 29 | | | 1.1/4 | 32 | 1 | |
| **T2024-1216** | 19 | 3/4 | 1" -11 | | -1216 | 2.40 | 61 | 1.26 | 32 | | | 1.1/2 | 38 | 1.1/4 | 32 |
| **T2024-1616** | 25 | 1 | 1" -11 | | -1616 | 2.52 | 64 | 1.30 | 33 | | | 1.1/2 | 38 | 1.1/4 | 32 |

## BSPP — T2060


**BSPP FEMALE**
**60° CONE**
**45° ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2060-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.57 | 40 | 0.55 | 14 | 0.59 | 15 | 3/4 | 19 | 9/16 | |
| **T2060-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 1.65 | 42 | 0.67 | 17 | 0.71 | 18 | 7/8 | 22 | 3/4 | 19 |
| **T2060-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 1.81 | 46 | 0.83 | 21 | 0.71 | 18 | 1.1/16 | 27 | 7/8 | 22 |
| **T2060-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.13 | 54 | 0.98 | 25 | 0.79 | 20 | 1.1/4 | 32 | 1.1/16 | 27 |
| **T2060-1616** | 25 | 1 | 1" -11 | | -1616 | 2.32 | 59 | 1.10 | 28 | 1.02 | 26 | 1.1/2 | 38 | 1.5/16 | |
| **T2060-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 3.07 | 78 | 1.10 | 28 | 1.14 | 29 | 2 | 50 | 1.7/8 | |

## BSPP — T2475

**BSP BANJO STRAIGHT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | | | | | |
| **T2475-0404** | 6 | 1/4 | 1/4 | | 0 | -0404 | 1.97 | 50 | 0.98 | 25 | | | | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

### BSPP — T2050


**BSPP FEMALE**
**60° CONE**
**90° ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2050-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.85 | 47 | 0.83 | 21 | 0.94 | 24 | 3/4 | 19 | 9/16 | |
| **T2050-0406** | 6 | 1/4 | 3/8" -19 | | -0406 | 1.85 | 47 | 0.83 | 21 | 1.10 | 28 | 7/8 | 22 | 3/4 | 19 |
| **T2050-0506** | 8 | 5/16 | 3/8" -19 | | -0506 | 1.85 | 47 | 0.87 | 22 | 1.10 | 28 | 7/8 | 22 | 3/4 | 19 |
| **T2050-0604** | 10 | 3/8 | 1/4" -19 | | -0604 | 1.81 | 46 | 0.87 | 22 | 0.94 | 24 | 3/4 | 19 | 9/16 | |
| **T2050-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 1.89 | 48 | 0.91 | 23 | 1.10 | 28 | 7/8 | 22 | 3/4 | 19 |
| **T2050-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 1.89 | 48 | 0.91 | 23 | 1.22 | 31 | 1.1/16 | 27 | 7/8 | 22 |
| **T2050-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.13 | 54 | 1.14 | 29 | 1.22 | 31 | 1.1/16 | 27 | 7/8 | 22 |
| **T2050-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.36 | 60 | 1.22 | 31 | 1.42 | 36 | 1.1/4 | 32 | 1.1/16 | 27 |
| **T2050-1616** | 25 | 1 | 1" -11 | | -1616 | 2.48 | 63 | 1.26 | 32 | 1.77 | 45 | 1.1/2 | 38 | 1.5/16 | |
| **T2050-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 3.66 | 93 | 1.69 | 43 | 2.05 | 52 | 2 | 50 | 1.7/8 | |
| **T2050-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 4.41 | 112 | 2.36 | 60 | 2.32 | 59 | 2.3/16 | 55 | 2.1/2 | |
| **T2050-3232** | 51 | 2 | 2" -11 | | -3232 | 4.45 | 113 | 2.20 | 56 | 2.44 | 62 | 2.3/4 | 70 | 2.1/2 | |

### BSPP — T2270


**BSPP FEMALE**
**60° CONE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2270-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.36 | 60 | 1.38 | 35 | 0.67 | 17 | 3/4 | 19 | | |
| **T2270-0406** | 6 | 1/4 | 3/8" -19 | | -0406 | 2.44 | 62 | 1.46 | 37 | 0.67 | 17 | 7/8 | 22 | | |
| **T2270-0506** | 8 | 5/16 | 3/8" -19 | | -0506 | 2.60 | 66 | 1.61 | 41 | 0.71 | 18 | 7/8 | 22 | | |
| **T2270-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.60 | 66 | 1.61 | 41 | 0.71 | 18 | 7/8 | 22 | | |
| **T2270-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.76 | 70 | 1.77 | 45 | 0.79 | 20 | 1.1/16 | 27 | | |
| **T2270-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.95 | 75 | 1.97 | 50 | 0.87 | 22 | 1.1/16 | 27 | | |
| **T2270-0810** | 12 | 1/2 | 5/8" -14 | | -0810 | 2.91 | 74 | 1.93 | 49 | 0.91 | 23 | 1.3/16 | 30 | | |
| **T2270-1010** | 16 | 5/8 | 5/8" -14 | | -1010 | 3.66 | 93 | 2.44 | 62 | 0.91 | 23 | 1.3/16 | 30 | | |
| **T2270-1012** | 16 | 5/8 | 3/4" -14 | | -1012 | 3.50 | 89 | 2.28 | 58 | 1.10 | 28 | 1.1/4 | 32 | | |
| **T2270-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 4.25 | 106 | 3.11 | 77 | 1.14 | 29 | 1.1/4 | 32 | | |
| **T2270-1616** | 25 | 1 | 1" -11 | | -1616 | 4.57 | 116 | 3.35 | 83 | 1.65 | 42 | 1.1/2 | 38 | | 32 |
| **T2270-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 8.46 | 215 | 6.50 | 165 | 1.81 | 46 | 2 | 50 | | |
| **T2270-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 6.69 | 170 | 4.65 | 118 | 2.05 | 52 | 2.3/16 | 55 | | |
| **T2270-3232** | 51 | 2 | 2" -11 | | -3232 | 8.11 | 206 | 5.91 | 150 | 2.56 | 65 | 2.3/4 | 70 | | |

## BSPP — T2260


**BSPP FEMALE**
**60° CONE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2260-0302** | 5 | 3/16 | 1/8" -28 | | -0302 | 1.85 | 47 | 1.06 | 27 | 1.10 | 28 | | 14 | | |
| **T2260-0304** | 5 | 3/16 | 1/4" -19 | | -0302 | 1.85 | 47 | 1.06 | 27 | 1.14 | 29 | 3/4 | 19 | | |
| **T2260-0402** | 6 | 1/4 | 1/8" -28 | | -0402 | 2.05 | 52 | 1.06 | 27 | 1.18 | 30 | | 14 | | |
| **T2260-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.05 | 52 | 1.06 | 27 | 1.14 | 29 | 3/4 | 19 | | |
| **T2260-0406** | 6 | 1/4 | 3/8" -19 | | -0406 | 2.05 | 52 | 1.06 | 27 | 1.10 | 28 | 7/8 | 22 | | |
| **T2260-0504** | 8 | 5/16 | 1/4" -19 | | -0504 | 2.05 | 52 | 1.06 | 27 | 1.26 | 32 | 3/4 | 19 | | |
| **T2260-0506** | 8 | 5/16 | 3/8" -19 | | -0506 | 2.32 | 59 | 1.34 | 34 | 1.30 | 33 | 7/8 | 22 | | |
| **T2260-0604** | 10 | 3/8 | 1/4" -19 | | -0604 | 2.36 | 60 | 1.38 | 35 | 1.30 | 33 | 3/4 | 19 | | |
| **T2260-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.32 | 59 | 1.38 | 35 | 1.30 | 33 | 7/8 | 22 | | |
| **T2260-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.32 | 59 | 1.38 | 35 | 1.30 | 33 | 1.1/16 | 27 | | |
| **T2260-0806** | 12 | 1/2 | 3/8" -19 | | -0806 | 2.60 | 66 | 1.61 | 41 | 1.65 | 42 | 7/8 | 22 | | |
| **T2260-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.48 | 66 | 1.50 | 41 | 1.77 | 45 | 1.1/16 | 27 | | |
| **T2260-0810** | 12 | 1/2 | 5/8" -14 | | -0810 | 2.60 | 66 | 1.61 | 41 | 1.77 | 45 | 1.3/16 | 30 | | |
| **T2260-0812** | 12 | 1/2 | 3/4" -14 | | -0812 | 2.60 | 66 | 1.61 | 41 | 1.85 | 47 | 1.1/4 | 32 | | |
| **T2260-1010** | 16 | 5/8 | 5/8" -14 | | -1010 | 2.99 | 76 | 1.77 | 45 | 1.97 | 50 | 1.3/16 | 30 | | |
| **T2260-1012** | 12 | 1/2 | 3/4" -14 | | -1012 | 2.99 | 76 | 1.77 | 45 | 2.20 | 56 | 1.1/4 | 32 | | |
| **T2260-1208** | 19 | 3/4 | 1/2" -14 | | -1208 | 3.35 | 85 | 2.09 | 53 | 1.77 | 45 | | 27 | | |
| **T2260-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.35 | 87 | 2.17 | 57 | 2.32 | 59 | 1.1/4 | 32 | | |
| **T2260-1216** | 19 | 3/4 | 1" -11 | | -1216 | 3.50 | 89 | 2.24 | 57 | 2.44 | 62 | 1.1/2 | 38 | | |
| **T2260-1616** | 25 | 1 | 1" -11 | | -1616 | 3.90 | 99 | 2.68 | 74 | 3.07 | 78 | 1.1/2 | 38 | | 32 |
| **T2260-2016** | 31 | 1.1/4 | 1" -11 | | -2016 | 5.47 | 139 | 3.54 | 90 | 3.03 | 77 | 1.1/2 | 38 | | |
| **T2260-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 5.20 | 132 | 3.23 | 82 | 3.58 | 91 | 2 | 50 | | |
| **T2260-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 5.91 | 150 | 3.86 | 98 | 4.13 | 105 | 2.3/16 | 55 | | |
| **T2260-3232** | 51 | 2 | 2" -11 | | -3232 | 7.60 | 193 | 5.39 | 137 | 5.20 | 132 | 2.3/4 | 70 | | |

## BSPP — T2210

**BSPP FEMALE**
**60° CONE**
**90° LONG TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2210-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 3.35 | 85 | 2.36 | 60 | 2.01 | 51 | 3/4 | 19 | | |
| **T2210-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.91 | 74 | 1.93 | 49 | 2.32 | 59 | 7/8 | 22 | | |
| **T2210-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 3.35 | 85 | 2.36 | 60 | 2.83 | 72 | 1.1/16 | 27 | | |
| **T2210-0810** | 12 | 1/2 | 5/8" -14 | | -0810 | 2.80 | 71 | 1.81 | 46 | 2.83 | 72 | 1.3/16 | 30 | | |
| **T2210-1010** | 16 | 5/8 | 5/8" -14 | | -1010 | 3.23 | 82 | 2.01 | 51 | 3.19 | 81 | 1.3/16 | 30 | | |
| **T2210-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.50 | 87 | 2.32 | 57 | 3.74 | 95 | 1.1/4 | 32 | | |
| **T2210-1616** | 25 | 1 | 1" -11 | | -1616 | 3.78 | 96 | 2.56 | 74 | 4.57 | 116 | 1.1/2 | 38 | | |
| **T2210-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 5.87 | 149 | 3.94 | 100 | 5.59 | 142 | 2 | 50 | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

### BSPP — T2027


**BSPP FEMALE O RING**
**60° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | mm | inch | mm | inch | mm |
| **T2027-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.89 | 48 | 0.91 | 23 | | 0 | 3/4 | 19 | 1/2 | 0 |
| **T2027-0406** | 6 | 1/4 | 3/8" -19 | | -0406 | 2.04 | 52 | 1.06 | 27 | | 29 | 7/8 | 22 | 1/2 | 0 |
| **T2027-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.09 | 53 | 1.10 | 28 | | 33 | 1 1(16 | 27 | 3/4 | 0 |
| **T2027-1212** | 12 | 1/2 | 3/4" -14 | | -1212 | 2.44 | 60 | 1.30 | 31 | | 450 | 1 1/4 | 32 | 1 1/16 | 24 |
| **T2027-1616** | 25 | 1 | 1" -11 | | -1616 | 2.72 | 69 | 1.50 | 36 | | 59 | 1 1/2 | 38 | 1 1/4 | 0 |
| **T2027-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 3.70 | 94 | 1.77 | 45 | | 78 | 2 | 50 | 1/5/8 | 0 |
| **T2027-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 3.90 | 99 | 1.85 | 47 | | 91 | 2 3/16 | 55 | 2 | 0 |
| **T2027-3232** | 51 | 2 | 2" -11 | | -3232 | 4.37 | 111 | 2.17 | 55 | | 105 | 2 3/4 | 70 | 0 | 0 |

### BSPP — T2057


**BSPP**
**FEMALE O RING**
**60° CONE**
**90° ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2057-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.85 | 47 | 0.83 | 21 | 0.94 | 24 | 3/4 | 19 | 9/16 | |
| **T2057-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 1.89 | 48 | 0.91 | 23 | 1.10 | 28 | 7/8 | 22 | 3/4 | 19 |
| **T2057-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.13 | 54 | 1.14 | 29 | 1.30 | 33 | 1.1/16 | 27 | 7/8 | 22 |
| **T2057-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.36 | 60 | 1.18 | 30 | 1.50 | 38 | 1.1/4 | 32 | 1.1/16 | 27 |

## BSPP — T2277


**BSPP FEMALE O RING**
**60° CONE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2277-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.56 | 65 | 1.57 | 40 | 0.67 | 17 | 3/4 | 19 | 0 | 0 |
| **T2277-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.60 | 66 | 1.61 | 41 | 0.71 | 18 | 7/8 | 22 | 0 | 0 |
| **T2277-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.95 | 75 | 1.97 | 50 | 0.87 | 22 | 1 1/16 | 27 | 0 | 0 |
| **T2277-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 4.25 | 106 | 3.11 | 77 | 1.14 | 29 | 1 1/4 | 32 | 0 | 0 |
| **T2277-1616** | 25 | 1 | 1" -11 | | -1616 | 4.57 | 116 | 3.35 | 83 | 1.65 | 42 | 1 1/2 | 38 | 0 | 0 |
| **T2277-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 8.46 | 215 | 6.50 | 165 | 1.81 | 46 | 2 | 50 | 0 | 0 |
| **T2277-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 7.09 | 180 | 5.04 | 128 | 2.05 | 52 | 2 3/16 | 55 | 0 | 0 |
| **T2277-3232** | 51 | 2 | 2" -11 | | -3232 | 8.11 | 206 | 5.91 | 150 | 2.56 | 65 | 2 3/4 | 70 | 0 | 0 |

## BSPP — T2267

**BSPP FEMALE O RING**
**60° CONE**
**90° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2267-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.24 | 57 | 1.26 | 32 | 0.67 | 17 | 3/4 | 19 | 0 | 0 |
| **T2267-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.36 | 60 | 1.38 | 35 | 0.71 | 18 | 7/8 | 22 | 0 | 0 |
| **T2267-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.60 | 66 | 1.61 | 41 | 0.87 | 22 | 1 1/16 | 27 | 0 | 0 |
| **T2267-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.50 | 87 | 2.32 | 57 | 1.14 | 29 | 1 1/4 | 32 | 0 | 0 |
| **T2267-1616** | 25 | 1 | 1" -11 | | -1616 | 3.90 | 99 | 2.68 | 74 | 1.65 | 42 | 1 1/2 | 38 | 0 | 0 |
| **T2267-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 5.87 | 149 | 3.94 | 100 | 1.81 | 46 | 2 | 50 | 0 | 0 |
| **T2267-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 6.22 | 158 | 4.17 | 106 | 2.05 | 52 | 2 3/16 | 55 | 0 | 0 |
| **T2267-3232** | 51 | 2 | 2" -11 | | -3232 | 7.61 | 193 | 5.39 | 137 | 2.56 | 65 | 2 3/4 | 70 | 0 | 0 |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

### NPTF — T2090


**NPTF MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T2090-0302** | 5 | 3/16 | 1/8" -27 | | -0302 | 1.73 | 44 | 0.94 | 24 | | | | | 7/16 | 11 |
| **T2090-0304** | 5 | 3/16 | 1/4" -18 | | -0304 | 1.97 | 50 | 1.18 | 30 | | | | | 9/16 | |
| **T2090-0402** | 6 | 1/4 | 1/8" -27 | | -0402 | 2.01 | 51 | 1.02 | 26 | | | | | 1/2 | |
| **T2090-0404** | 6 | 1/4 | 1/4" -18 | | -0404 | 2.17 | 55 | 1.18 | 30 | | | | | 9/16 | |
| **T2090-0406** | 6 | 1/4 | 3/8" -18 | | -0406 | 2.17 | 55 | 1.18 | 30 | | | | | 11/16 | |
| **T2090-0408** | 6 | 1/4 | 1/2" -14 | | -0408 | 2.28 | 58 | 1.26 | 32 | | | | | 7/8 | 22 |
| **T2090-0504** | 8 | 5/16 | 1/4" -18 | | -0504 | 2.17 | 55 | 1.18 | 30 | | | | | 9/16 | |
| **T2090-0506** | 8 | 5/16 | 3/8" -18 | | -0506 | 2.17 | 55 | 1.18 | 30 | | | | | 11/16 | |
| **T2090-0604** | 10 | 3/8 | 1/4" -18 | | -0604 | 2.24 | 57 | 1.30 | 33 | | | | | 5/8 | 16 |
| **T2090-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 2.24 | 57 | 1.30 | 33 | | | | | 11/16 | |
| **T2090-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.44 | 62 | 1.46 | 37 | | | | | 7/8 | 22 |
| **T2090-0806** | 12 | 1/2 | 3/8" -18 | | -0806 | 2.32 | 59 | 1.38 | 35 | | | | | 11/16 | |
| **T2090-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.52 | 64 | 1.57 | 40 | | | | | 7/8 | 22 |
| **T2090-0812** | 12 | 1/2 | 3/4" -14 | | -0812 | 2.40 | 61 | 1.46 | 37 | | | | | 1.1/16 | 27 |
| **T2090-1008** | 16 | 5/8 | 1/2" -14 | | -1008 | 2.80 | 71 | 1.61 | 41 | | | | | 7/8 | 22 |
| **T2090-1012** | 16 | 5/8 | 3/4" -14 | | -1012 | 2.80 | 71 | 1.61 | 41 | | | | | 1.1/16 | 27 |
| **T2090-1208** | 19 | 3/4 | 1/2" -14 | | -1208 | 2.80 | 71 | 1.61 | 41 | | | | | 1.1/16 | 27 |
| **T2090-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.80 | 71 | 1.61 | 41 | | | | | 1.1/16 | 27 |
| **T2090-1216** | 19 | 3/4 | 1" -11,5 | | -1216 | 2.87 | 73 | 1.73 | 44 | | | | | 1.3/8 | 35 |
| **T2090-1612** | 25 | 1 | 3/4" -14 | | -1612 | 2.91 | 74 | 1.69 | 43 | | | | | 1.3/8 | 35 |
| **T2090-1616** | 25 | 1 | 1" -11,5 | | -1616 | 3.11 | 79 | 1.89 | 48 | | | | | 1.3/8 | 35 |
| **T2090-1620** | 25 | 1 | 1.1/4" -11,5 | | -1620 | 2.99 | 76 | 1.81 | 46 | | | | | 1.3/4 | |
| **T2090-2016** | 31 | 1.1/4 | 1" -11,5 | | -2016 | 4.02 | 102 | 2.05 | 52 | | | | | 1.3/4 | |
| **T2090-2020** | 31 | 1.1/4 | 1.1/4" -11,5 | | -2020 | 4.06 | 103 | 2.09 | 53 | | | | | 1.3/4 | |
| **T2090-2424** | 38 | 1.1/2 | 1.1/2" -11,5 | | -2424 | 4.21 | 107 | 2.17 | 55 | | | | | 2 | 50 |
| **T2090-3232** | 51 | 2 | 2" -11,5 | | -3232 | 4.80 | 122 | 2.60 | 66 | | | | | 2.1/2 | |

### NPTF — T2091


**NPTF MALE EXTENDED**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T2091-0406** | 6 | 1/4 | 3/8" -18 | | -0406 | 2.48 | 63 | 1.50 | 38 | | | | | 3/4 | 19 |
| **T2091-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 2.56 | 65 | 1.57 | 40 | | | | | 3/4 | 19 |

## NPTF — T2320N


**NPTF MALE SWIVEL**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | | |
| **T2320N-0402** | 6 | 1/4 | 1/8" -27 | | -0402 | 2.13 | 54 | 1.14 | 29 | | | 11/16 | | | |
| **T2320N-0404** | 6 | 1/4 | 1/4" -18 | | -0404 | 2.13 | 54 | 1.14 | 29 | | | 11/16 | | | |
| **T2320N-0406** | 6 | 1/4 | 3/8" -18 | | -0406 | 2.32 | 59 | 1.34 | 34 | | | 7/8 | 22 | | |
| **T2320N-0604** | 10 | 3/8 | 1/4" -18 | | -0604 | 2.13 | 54 | 1.14 | 29 | | | 11/16 | | | |
| **T2320N-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 2.32 | 59 | 1.34 | 34 | | | 7/8 | 22 | | |
| **T2320N-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.32 | 59 | 1.34 | 34 | | | 1 | | | |
| **T2320N-0806** | 12 | 1/2 | 3/8" -18 | | -0806 | 2.32 | 59 | 1.38 | 35 | | | 7/8 | 22 | | |
| **T2320N-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.32 | 59 | 1.38 | 35 | | | 1 | | | |
| **T2320N-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.60 | 66 | 1.46 | 37 | | | 1.1/4 | 32 | | |
| **T2320N-1616** | 25 | 1 | 1" -11,5 | | -1616 | 2.91 | 74 | 1.69 | 43 | | | 1.1/2 | 38 | | |

## NPT — T2340N

**NPT MALE SWIVEL**
**90° ELBOW**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | | | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2340N-0404** | 6 | 1/4 | 1/4" -18 | | -0404 | 1.85 | 47 | 0.83 | 21 | 1.61 | 41 | 11/16 | | 9/16 | | | |
| **T2340N-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 1.89 | 48 | 0.91 | 23 | 1.85 | 47 | 7/8 | 22 | 3/4 | 19 | | |
| **T2340N-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.13 | 54 | 1.14 | 29 | 2.09 | 53 | 1 | | 7/8 | 22 | | |
| **T2340N-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.36 | 60 | 1.22 | 31 | 2.24 | 57 | 1.1/4 | 32 | 1.1/16 | 27 | | |
| **T2340N-1616** | 25 | 1 | 1" -11,5 | | -1616 | 2.68 | 68 | 1.46 | 37 | 2.83 | 72 | 1.1/2 | 38 | 1.5/16 | | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

## NPT — T2190


**NPT FEMALE**
**FIXED**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T2190-0402** | 6 | 1/4 | 1/8" -27 | | -0402 | 1.73 | 44 | 0.75 | 19 | | | | | 9/16 | |
| **T2190-0404** | 6 | 1/4 | 1/4" -18 | | -0404 | 2.01 | 51 | 1.02 | 26 | | | | | 3/4 | 19 |
| **T2190-0406** | 6 | 1/4 | 3/8" -18 | | -0406 | 2.13 | 54 | 1.10 | 28 | | | | | 7/8 | 22 |
| **T2190-0604** | 10 | 3/8 | 1/4" -18 | | -0604 | 2.01 | 51 | 1.02 | 26 | | | | | 3/4 | 19 |
| **T2190-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 2.13 | 54 | 1.14 | 29 | | | | | 7/8 | 22 |
| **T2190-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.28 | 58 | 1.30 | 33 | | | | | 1.1/16 | 27 |
| **T2190-0806** | 12 | 1/2 | 3/8" -18 | | -0806 | 2.09 | 53 | 1.10 | 28 | | | | | 7/8 | 22 |
| **T2190-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.28 | 58 | 1.34 | 34 | | | | | 1.1/16 | 27 |
| **T2190-1012** | 16 | 5/8 | 3/4" -14 | | -1012 | 2.64 | 67 | 1.46 | 37 | | | | | 1.3/8 | 35 |
| **T2190-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.64 | 67 | 1.46 | 37 | | | | | 1.3/8 | 35 |

## NPSM — T2020N

**NPSM FEMALE**
**60 ° CONE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2020N-0402** | 6 | 1/4 | 1/8" -27 | | -0402 | 1.85 | 47 | 0.83 | 21 | | | 9/16 | | 1/2 | |
| **T2020N-0404** | 6 | 1/4 | 1/4" -18 | | -0404 | 1.85 | 47 | 0.87 | 22 | | | 11/16 | | 1/2 | |
| **T2020N-0504** | 8 | 5/16 | 1/4" -18 | | -0504 | 1.85 | 47 | 0.87 | 22 | | | 11/16 | | 9/16 | |
| **T2020N-0604** | 10 | 3/8 | 1/4" -18 | | -0604 | 1.85 | 47 | 0.87 | 22 | | | 11/16 | | 9/16 | |
| **T2020N-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 1.93 | 49 | 0.94 | 24 | | | 7/8 | 22 | 5/8 | 16 |
| **T2020N-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.05 | 52 | 1.06 | 27 | | | 1 | | 3/4 | 19 |
| **T2020N-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.01 | 51 | 1.02 | 26 | | | 1 | | 3/4 | 19 |
| **T2020N-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.28 | 58 | 1.10 | 28 | | | 1.1/4 | 32 | 1 | |
| **T2020N-1616** | 25 | 1 | 1" -11,5 | | -1616 | 2.52 | 64 | 1.30 | 33 | | | 1.1/2 | 38 | 1.1/4 | 32 |
| **T2020N-2020** | 31 | 1.1/4 | 1.1/4" -11,5 | | -2020 | 3.58 | 91 | 1.61 | 41 | | | 1 7/8 | | 1.3/4 | |
| **T2020N-2424** | 38 | 1.1/2 | 1.1/2" -11,5 | | -2424 | 3.82 | 97 | 1.77 | 45 | | | 2.1/4 | 57 | 2 | 50 |
| **T2020N-3232** | 51 | 2 | 2" -11,5 | | -3232 | 4.33 | 110 | 2.13 | 54 | | | 2.3/4 | 70 | 2.1/2 | |

## GREASE LINE

## T2861

GREASE LINE
FIXED FEMALE





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | inch | | inch | mm | inch | mm | | | | | inch | mm |
| **T2861-0408** | 6 | 1/4 | 1/2 | 5/16 | -0408 | 1.89 | 48 | 0.91 | 23 | | | | | 11/16 | |

## JIC

## T2030

JIC 37° CONE MALE





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T2030-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.17 | 55 | 1.14 | 29 | | | | | 1/2 | |
| **T2030-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 2.17 | 55 | 1.14 | 29 | | | | | 9/16 | |
| **T2030-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.17 | 55 | 1.18 | 30 | | | | | 5/8 | 16 |
| **T2030-0412** | 6 | 1/4 | 3/4" -16 | | -0412 | 2.28 | 58 | 1.26 | 32 | | | | | 13/16 | |
| **T2030-0508** | 8 | 5/16 | 1/2" - 20 | | -0508 | 2.17 | 55 | 1.14 | 29 | | | | | 9/16 | |
| **T2030-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.17 | 55 | 1.18 | 30 | | | | | 5/8 | 16 |
| **T2030-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.24 | 57 | 1.26 | 32 | | | | | 5/8 | 16 |
| **T2030-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.32 | 59 | 1.38 | 35 | | | | | 3/4 | 19 |
| **T2030-0614** | 10 | 3/8 | 7/8" -14 | | -0614 | 2.44 | 62 | 1.46 | 37 | | | | | 7/8 | 22 |
| **T2030-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.40 | 61 | 1.46 | 37 | | | | | 3/4 | 19 |
| **T2030-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.52 | 64 | 1.54 | 39 | | | | | 15/16 | 24 |
| **T2030-0817** | 12 | 1/2 | 1.1/16" -12 | | -0817 | 2.64 | 67 | 1.65 | 42 | | | | | 1.1/8 | |
| **T2030-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.80 | 71 | 1.57 | 40 | | | | | 15/16 | 24 |
| **T2030-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 2.87 | 73 | 1.69 | 43 | | | | | 1.1/8 | |
| **T2030-1214** | 19 | 3/4 | 7/8" -14 | | -1214 | 2.80 | 71 | 1.61 | 41 | | | | | 1 | |
| **T2030-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.87 | 73 | 1.73 | 44 | | | | | 1.1/8 | |
| **T2030-1219** | 19 | 3/4 | 1.3/16" -12 | | -1219 | 2.91 | 74 | 1.77 | 45 | | | | | 1.1/4 | 32 |
| **T2030-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 2.95 | 75 | 1.77 | 45 | | | | | 1.3/8 | 35 |
| **T2030-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 3.03 | 77 | 1.85 | 47 | | | | | 1.3/8 | 35 |
| **T2030-1626** | 25 | 1 | 1.5/8"-12 | | -1626 | 3.11 | 79 | 1.89 | 48 | | | | | 1.3/4 | |
| **T2030-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 4.02 | 102 | 2.05 | 52 | | | | | 1.3/4 | |
| **T2030-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 4.29 | 109 | 2.24 | 57 | | | | | 2 | 50 |
| **T2030-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 5.12 | 130 | 2.87 | 73 | | | | | 2.1/2 | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

| JIC | T2031 |
|---|---|

JIC
37° CONE MALE
METRIC HEX ONLY





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | | mm |
| **T2031-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.17 | 55 | 1.14 | 29 | | | | | | 12 |
| **T2031-0508** | 8 | 5/16 | 1/2" - 20 | | -0508 | 2.17 | 55 | 1.14 | 29 | | | | | | 14 |
| **T2031-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 2.95 | 75 | 1.77 | 45 | | | | | | 36 |
| **T2031-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 3.03 | 77 | 1.85 | 47 | | | | | | 36 |

## JSEAL™ / JIC

## T2040

JSEAL™ / JIC
FEMALE
CONVEX SEAT





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2040-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 1.61 | 41 | 0.87 | 22 | | | 9/16 | | 1/2 | |
| **T2040-0406** | 6 | 1/4 | 3/8" - 24 | | -0406 | 1.85 | 47 | 0.87 | 22 | | | 1/2 | | 1/2 | |
| **T2040-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.77 | 45 | 0.79 | 20 | | | 9/16 | | 1/2 | |
| **T2040-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 1.85 | 47 | 0.83 | 21 | | | 5/8 | 16 | 1/2 | |
| **T2040-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 1.89 | 48 | 0.91 | 23 | | | 11/16 | | 1/2 | |
| **T2040-0412** | 6 | 1/4 | 3/4" -16 | | -0412 | 1.93 | 49 | 0.94 | 24 | | | 7/8 | 22 | 1/2 | |
| **T2040-0507** | 8 | 5/16 | 7/16" -20 | | -0507 | 1.85 | 47 | 0.87 | 22 | | | 9/16 | | 9/16 | |
| **T2040-0508** | 8 | 5/16 | 1/2" - 20 | | -0508 | 1.85 | 47 | 0.87 | 22 | | | 5/8 | 16 | 9/16 | |
| **T2040-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 1.89 | 48 | 0.87 | 22 | | | 11/16 | | 9/16 | |
| **T2040-0512** | 8 | 5/16 | 3/4" -16 | | -0512 | 2.01 | 51 | 0.98 | 25 | | | 7/8 | 22 | 9/16 | |
| **T2040-0607** | 10 | 3/8 | 7/16" -20 | | -0607 | 1.85 | 47 | 0.87 | 22 | | | 9/16 | | 5/8 | 16 |
| **T2040-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 1.85 | 47 | 0.87 | 22 | | | 11/16 | | 5/8 | 16 |
| **T2040-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 1.97 | 50 | 0.98 | 25 | | | 7/8 | 22 | 5/8 | 16 |
| **T2040-0614** | 10 | 3/8 | 7/8" -14 | | -0614 | 2.05 | 52 | 1.06 | 27 | | | 1 | | 5/8 | 16 |
| **T2040-0809** | 12 | 1/2 | 9/16" -18 | | -0809 | 2.68 | 68 | 1.69 | 43 | | | 11/16 | | 3/4 | 19 |
| **T2040-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 1.97 | 50 | 0.98 | 25 | | | 7/8 | 22 | 3/4 | 19 |
| **T2040-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.05 | 52 | 1.06 | 27 | | | 1 | | 3/4 | 19 |
| **T2040-0817** | 12 | 1/2 | 1.1/16" -12 | | -0817 | 2.20 | 56 | 1.22 | 31 | | | 1.1/4 | 32 | 3/4 | 19 |
| **T2040-1012** | 16 | 5/8 | 3/4" -16 | | -1012 | 2.20 | 56 | 0.98 | 25 | | | 7/8 | 22 | 7/8 | 22 |
| **T2040-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.24 | 57 | 1.06 | 27 | | | 1 | | 7/8 | 22 |
| **T2040-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 2.40 | 61 | 1.18 | 30 | | | 1.1/4 | 32 | 7/8 | 22 |
| **T2040-1212** | 19 | 3/4 | 3/4" -16 | | -1212 | 2.36 | 60 | 1.18 | 28 | | | 7/8 | 22 | 1.1/16 | 27 |
| **T2040-1214** | 19 | 3/4 | 7/8" -14 | | -1214 | 2.48 | 63 | 1.34 | 32 | | | 1 | | 1.1/16 | 27 |
| **T2040-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.36 | 60 | 1.14 | 29 | | | 1.1/4 | 32 | 15/16 | 24 |
| **T2040-1219** | 19 | 3/4 | 1.3/16" -12 | | -1219 | 2.40 | 61 | 1.22 | 31 | | | 1.3/8 | 35 | 1.1/8 | |
| **T2040-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 2.68 | 68 | 1.50 | 36 | | | 1.1/2 | 38 | 1.1/16 | 27 |
| **T2040-1617** | 25 | 1 | 1.1/16" -12 | | -1617 | 2.56 | 65 | 1.34 | 37 | | | 1.1/4 | 32 | 1.1/4 | 32 |
| **T2040-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 2.60 | 66 | 1.38 | 33 | | | 1.1/2 | 38 | 1.1/4 | 32 |
| **T2040-1626** | 25 | 1 | 1.5/8"-12 | | -1626 | 2.83 | 72 | 1.61 | 38 | | | 2 | 50 | 1.1/4 | 32 |
| **T2040-1630** | 25 | 1 | 1.7/8"-12 | | -1630 | 3.07 | 78 | 1.85 | 47 | | | 2.1/4 | 57 | 1.1/4 | 32 |
| **T2040-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 3.62 | 92 | 1.69 | 43 | | | 2 | 50 | 1.5/8 | 41 |
| **T2040-2030** | 31 | 1.1/4 | 1.7/8"-12 | | -2030 | 3.98 | 101 | 2.05 | 52 | | | 2.1/4 | 57 | 1.5/8 | 41 |
| **T2040-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 4.13 | 105 | 2.09 | 53 | | | 2.1/4 | 57 | 2 | 50 |
| **T2040-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 4.65 | 118 | 2.44 | 62 | | | 2.7/8 | 73 | 2.1/2 | |
| **T2040-4048** | 63 | 2.1/2 | 3" -12 | | -4048 | 4.57 | 116 | 1.54 | 39 | | | 3.1/2 | 90 | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

### JSEAL™ / JIC — T2041


JSEAL™ / JIC
FEMALE CONVEX SEAT
METRIC NUT ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2041-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 1.61 | 41 | 0.87 | 22 | | | | 14 | 1/2 | |
| **T2041-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.77 | 45 | 0.79 | 20 | | | | 14 | 1/2 | |
| **T2041-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 1.89 | 48 | 0.91 | 23 | | | 3/4 | 19 | 1/2 | |
| **T2041-0507** | 8 | 5/16 | 7/16" -20 | | -0507 | 1.85 | 47 | 0.87 | 22 | | | | 14 | 9/16 | |
| **T2041-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 1.89 | 48 | 0.87 | 22 | | | 3/4 | 19 | 9/16 | |
| **T2041-0607** | 10 | 3/8 | 7/16" -20 | | -0607 | 1.85 | 47 | 0.87 | 22 | | | | 14 | 5/8 | 16 |
| **T2041-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 1.85 | 47 | 0.87 | 22 | | | 3/4 | 19 | 5/8 | 16 |
| **T2041-0809** | 12 | 1/2 | 9/16" -18 | | -0809 | 2.68 | 68 | 1.69 | 43 | | | 3/4 | 19 | 3/4 | 19 |

### JSEAL™ / JIC — T2080


JSEAL™ / JIC
FEMALE CONVEX SEAT
45° ELBOW




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2080-0406** | 6 | 1/4 | 3/8" - 24 | | -0406 | 2.09 | 53 | 1.10 | 28 | 0.51 | 13 | 1/2 | | 9/16 | |
| **T2080-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.09 | 53 | 1.10 | 28 | 0.51 | 13 | 9/16 | | 9/16 | |
| **T2080-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 2.09 | 53 | 1.10 | 28 | 0.51 | 13 | 5/8 | 16 | 9/16 | |
| **T2080-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.01 | 51 | 1.02 | 26 | 0.47 | 12 | 11/16 | | 9/16 | |
| **T2080-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.20 | 56 | 1.26 | 32 | 0.55 | 14 | 11/16 | | 3/4 | 19 |
| **T2080-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 1.65 | 42 | 0.67 | 17 | 0.59 | 15 | 7/8 | 22 | 3/4 | 19 |
| **T2080-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 1.81 | 46 | 0.83 | 21 | 0.63 | 16 | 7/8 | 22 | 7/8 | 22 |
| **T2080-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.48 | 63 | 1.50 | 38 | 0.67 | 17 | 1 | | 7/8 | 22 |
| **T2080-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.13 | 54 | 0.98 | 25 | 0.67 | 17 | 1.1/4 | 32 | 1.1/16 | 27 |
| **T2080-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 2.32 | 59 | 1.10 | 28 | 0.83 | 21 | 1.1/2 | 38 | 1.5/16 | |

## JSEAL™ / JIC — T2081


JSEAL™ / JIC
FEMALE
CONVEX SEAT
45° ELBOW
METRIC NUT ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2081-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.09 | 53 | 1.10 | 28 | 0.51 | 13 | | 14 | 9/16 | |
| **T2081-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.01 | 51 | 1.02 | 26 | 0.47 | 12 | 3/4 | 19 | 9/16 | |
| **T2081-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.20 | 56 | 1.26 | 32 | 0.55 | 14 | 3/4 | 19 | 3/4 | 19 |

## JSEAL™ / JIC — T2070

JSEAL™ / JIC
FEMALE
CONVEX SEAT
90° ELBOW





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2070-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 1.61 | 41 | 0.87 | 22 | 0.71 | 18 | 9/16 | | 9/16 | |
| **T2070-0406** | 6 | 1/4 | 3/8" - 24 | | -0406 | 1.85 | 47 | 0.87 | 22 | 0.67 | 17 | 1/2 | | 9/16 | |
| **T2070-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.85 | 47 | 0.83 | 21 | 0.67 | 17 | 9/16 | | 9/16 | |
| **T2070-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 1.85 | 47 | 0.87 | 22 | 0.67 | 17 | 5/8 | 16 | 9/16 | |
| **T2070-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 1.85 | 47 | 0.83 | 21 | 0.87 | 22 | 11/16 | | 9/16 | |
| **T2070-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 1.89 | 48 | 0.91 | 23 | 0.91 | 23 | 11/16 | | 3/4 | 19 |
| **T2070-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 1.89 | 48 | 0.91 | 23 | 0.94 | 24 | 7/8 | 22 | 3/4 | 19 |
| **T2070-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.13 | 54 | 1.14 | 29 | 1.06 | 27 | 7/8 | 22 | 7/8 | 22 |
| **T2070-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.13 | 54 | 1.14 | 29 | 1.22 | 31 | 1 | | 7/8 | 22 |
| **T2070-0817** | 12 | 1/2 | 1.1/16" -12 | | -0817 | 2.13 | 54 | 1.14 | 29 | 1.26 | 32 | 1.1/4 | 32 | 1.1/16 | 27 |
| **T2070-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.36 | 60 | 1.22 | 31 | 1.26 | 32 | 1.1/4 | 32 | 1.1/16 | 27 |
| **T2070-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 2.48 | 63 | 1.26 | 32 | 1.50 | 38 | 1.1/2 | 38 | 1.5/16 | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

### JSEAL™ / JIC — T2071


JSEAL™ / JIC FEMALE
CONVEX SEAT
90° ELBOW
METRIC NUT ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2071-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 1.61 | 41 | 0.87 | 22 | 0.71 | 18 | | 14 | 9/16 | |
| **T2071-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.85 | 47 | 0.83 | 21 | 0.67 | 17 | | 14 | 9/16 | |
| **T2071-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 1.85 | 47 | 0.83 | 21 | 0.87 | 22 | 3/4 | 19 | 9/16 | |
| **T2071-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 1.89 | 48 | 0.91 | 23 | 0.91 | 23 | 3/4 | 19 | 3/4 | 19 |

### JSEAL™ / JIC — T2250


JSEAL™ / JIC
FEMALE CONVEX SEAT
45° TUBE BEND




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2250-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.56 | 65 | 1.57 | 40 | 0.59 | 15 | 9/16 | | | |
| **T2250-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 2.28 | 58 | 1.30 | 33 | 0.59 | 15 | 5/8 | 16 | | |
| **T2250-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 0.59 | 15 | 11/16 | | | |
| **T2250-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.60 | 66 | 1.57 | 40 | 0.63 | 16 | 11/16 | | | |
| **T2250-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.48 | 63 | 1.50 | 38 | 0.55 | 14 | 11/16 | | | |
| **T2250-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.52 | 64 | 1.54 | 39 | 0.67 | 17 | 7/8 | 22 | | |
| **T2250-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.80 | 71 | 1.81 | 46 | 0.83 | 21 | 7/8 | 22 | | |
| **T2250-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.83 | 72 | 1.85 | 47 | 0.87 | 22 | 1 | | | |
| **T2250-0817** | 12 | 1/2 | 1.1/16" -12 | | -0817 | 2.83 | 72 | 1.85 | 47 | 0.83 | 21 | 1.1/4 | 32 | | |
| **T2250-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 3.66 | 93 | 2.44 | 62 | 0.94 | 24 | 1 | | | |
| **T2250-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 3.35 | 85 | 2.13 | 54 | 0.94 | 24 | 1.1/4 | 32 | | |
| **T2250-1214** | 19 | 3/4 | 7/8" -14 | | -1214 | 3.82 | 95 | 2.64 | 65 | 0.94 | 24 | 1 | | | |
| **T2250-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 4.25 | 108 | 3.03 | 77 | 1.10 | 28 | 1.1/4 | 32 | | |
| **T2250-1219** | 19 | 3/4 | 1.3/16" -12 | | -1219 | 3.66 | 93 | 2.52 | 64 | 0.94 | 24 | 1.3/8 | 35 | | |
| **T2250-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 4.69 | 117 | 3.50 | 87 | 1.50 | 38 | 1.1/2 | 38 | | |
| **T2250-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.53 | 115 | 3.31 | 82 | 1.38 | 35 | 1.1/2 | 38 | | |
| **T2250-1626** | 25 | 1 | 1.5/8"-12 | | -1626 | 4.69 | 119 | 3.50 | 86 | 1.54 | 39 | 2 | 50 | | |
| **T2250-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 5.87 | 149 | 3.94 | 100 | 1.54 | 39 | 2 | 50 | | |
| **T2250-2030** | 31 | 1.1/4 | 1.7/8"-12 | | -2030 | 5.98 | 152 | 4.06 | 103 | 1.65 | 42 | 2.1/4 | 57 | | |
| **T2250-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 7.09 | 180 | 5.04 | 128 | 1.97 | 50 | 2.1/4 | 57 | | |
| **T2250-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 8.66 | 220 | 6.46 | 164 | 2.48 | 63 | 2.7/8 | 73 | | |

## JSEAL™ / JIC — T2251


JSEAL™ / JIC FEMALE
CONVEX SEAT
45° TUBE BEND
METRIC NUT ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2251-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.56 | 65 | 1.57 | 40 | 0.59 | 15 | | 14 | | |
| **T2251-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 0.59 | 15 | 3/4 | 19 | | |
| **T2251-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.60 | 66 | 1.57 | 40 | 0.63 | 16 | 3/4 | 19 | | |
| **T2251-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.48 | 63 | 1.50 | 38 | 0.55 | 14 | 3/4 | 19 | | |

## JSEAL™ / JIC — T2243


JSEAL™ / JIC
FEMALE CONVEX SEAT
90° SHORT TUBE BEND




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2243-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.44 | 62 | 1.46 | 37 | 0.83 | 21 | 9/16 | | | |
| **T2243-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.05 | 52 | 1.06 | 27 | 0.87 | 22 | 11/16 | | | |
| **T2243-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.20 | 56 | 1.22 | 31 | 0.91 | 23 | 11/16 | | | |
| **T2243-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.68 | 68 | 1.69 | 43 | 1.14 | 29 | 7/8 | 22 | | |
| **T2243-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 3.31 | 84 | 2.09 | 53 | 1.34 | 34 | 1 | | | |
| **T2243-1214** | 19 | 3/4 | 7/8" -14 | | -1214 | 3.27 | 81 | 2.09 | 51 | 1.34 | 34 | 1 | | | |
| **T2243-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.78 | 94 | 2.60 | 64 | 1.85 | 47 | 1.1/4 | 32 | | |
| **T2243-1617** | 25 | 1 | 1.1/16" -12 | | -1617 | 3.39 | 86 | 2.17 | 58 | 1.85 | 47 | 1.1/4 | 32 | | |
| **T2243-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.41 | 112 | 3.19 | 71 | 2.28 | 58 | 1.1/2 | 38 | | |

## JSEAL™ / JIC — T2244

JSEAL™ / JIC FEMALE
CONVEX SEAT
90° SHORT TUBE BEND
METRIC NUT ONLY





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2244-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.44 | 62 | 1.46 | 37 | 0.83 | 21 | | 14 | | |
| **T2244-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.05 | 52 | 1.06 | 27 | 0.87 | 22 | 3/4 | 19 | | |
| **T2244-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.20 | 56 | 1.22 | 31 | 0.91 | 23 | 3/4 | 19 | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

### JSEAL™ / JIC — T2240


**JSEAL™ / JIC**
**FEMALE CONVEX SEAT**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2240-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.52 | 64 | 1.54 | 39 | 1.26 | 32 | 9/16 | | | |
| **T2240-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 2.24 | 57 | 1.26 | 32 | 1.26 | 32 | 5/8 | 16 | | |
| **T2240-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 1.50 | 38 | 11/16 | | | |
| **T2240-0412** | 6 | 1/4 | 3/4" -16 | | -0412 | 2.01 | 51 | 1.02 | 26 | 1.50 | 38 | 7/8 | 22 | | |
| **T2240-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.32 | 59 | 1.34 | 34 | 1.18 | 30 | 11/16 | | | |
| **T2240-0512** | 8 | 5/16 | 3/4" -16 | | -0512 | 2.36 | 60 | 1.38 | 35 | 1.61 | 41 | 7/8 | 22 | | |
| **T2240-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.32 | 59 | 1.34 | 34 | 1.02 | 26 | 11/16 | | | |
| **T2240-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.36 | 60 | 1.38 | 35 | 1.18 | 30 | 7/8 | 22 | | |
| **T2240-0614** | 10 | 3/8 | 7/8" -14 | | -0614 | 2.36 | 60 | 1.38 | 35 | 1.61 | 41 | 1 | | | |
| **T2240-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.60 | 66 | 1.61 | 41 | 1.50 | 38 | 7/8 | 22 | | |
| **T2240-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.60 | 66 | 1.61 | 41 | 1.61 | 41 | 1 | | | |
| **T2240-0817** | 12 | 1/2 | 1.1/16" -12 | | -0817 | 2.60 | 66 | 1.61 | 41 | 1.77 | 45 | 1.1/4 | 32 | | |
| **T2240-1012** | 16 | 5/8 | 3/4" -16 | | -1012 | 3.15 | 80 | 1.97 | 50 | 1.61 | 41 | 7/8 | 22 | | |
| **T2240-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.99 | 76 | 1.77 | 45 | 1.85 | 47 | 1 | | | |
| **T2240-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 2.99 | 76 | 1.77 | 45 | 1.89 | 48 | 1.1/4 | 32 | | |
| **T2240-1214** | 19 | 3/4 | 7/8" -14 | | -1214 | 3.35 | 83 | 2.17 | 53 | 1.89 | 48 | 1 | | | |
| **T2240-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.50 | 89 | 2.24 | 57 | 2.24 | 57 | 1.1/4 | 32 | | |
| **T2240-1219** | 19 | 3/4 | 1.3/16" -12 | | -1219 | 3.35 | 85 | 2.17 | 55 | 2.28 | 58 | 1.3/8 | 35 | | |
| **T2240-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 3.50 | 87 | 2.32 | 57 | 2.80 | 71 | 1.1/2 | 38 | | |
| **T2240-1617** | 25 | 1 | 1.1/16" -12 | | -1617 | 3.39 | 86 | 2.17 | 58 | 2.32 | 59 | 1.1/4 | 32 | | |
| **T2240-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 3.86 | 98 | 2.68 | 74 | 2.83 | 72 | 1.1/2 | 38 | | |
| **T2240-1626** | 25 | 1 | 1.5/8"-12 | | -1626 | 3.90 | 99 | 2.68 | 74 | 3.07 | 78 | 2 | 50 | | |
| **T2240-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 5.87 | 149 | 3.94 | 100 | 3.19 | 81 | 2 | 50 | | |
| **T2240-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 6.22 | 158 | 4.17 | 106 | 4.17 | 106 | 2.1/4 | 57 | | |
| **T2240-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 8.03 | 204 | 5.83 | 148 | 5.20 | 132 | 2.7/8 | 73 | | |

### JSEAL™ / JIC — T2241


**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**90° TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2241-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.52 | 64 | 1.54 | 39 | 1.26 | 32 | | 14 | | |
| **T2241-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 1.50 | 38 | 3/4 | 19 | | |
| **T2241-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.32 | 59 | 1.34 | 34 | 1.18 | 30 | 3/4 | 19 | | |
| **T2241-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.32 | 59 | 1.34 | 34 | 1.02 | 26 | 3/4 | 19 | | |

## JSEAL™ / JIC — T2280


**JSEAL™ / JIC**
**FEMALE CONVEX SEAT**
**90° LONG TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2280-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.68 | 68 | 1.69 | 43 | 1.85 | 47 | 9/16 | | | |
| **T2280-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.83 | 72 | 1.85 | 47 | 2.13 | 54 | 11/16 | | | |
| **T2280-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 3.03 | 77 | 2.05 | 52 | 2.17 | 55 | 11/16 | | | |
| **T2280-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 3.03 | 77 | 2.05 | 52 | 2.52 | 64 | 7/8 | 22 | | |
| **T2280-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.99 | 76 | 2.01 | 51 | 2.36 | 60 | 7/8 | 22 | | |
| **T2280-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 3.15 | 80 | 2.17 | 55 | 2.76 | 70 | 1 | | | |
| **T2280-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 3.23 | 82 | 2.01 | 51 | 2.76 | 70 | 1 | | | |
| **T2280-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 3.23 | 82 | 2.01 | 51 | 3.78 | 96 | 1.1/4 | 32 | | |
| **T2280-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.50 | 89 | 2.24 | 57 | 3.78 | 96 | 1.1/4 | 32 | | |
| **T2280-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.17 | 106 | 2.95 | 74 | 4.49 | 114 | 1.1/2 | 38 | | |
| **T2280-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 5.87 | 149 | 3.94 | 100 | 5.08 | 129 | 2 | 50 | | |
| **T2280-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 6.22 | 158 | 4.17 | 106 | 5.55 | 141 | 2.1/4 | 57 | | |
| **T2280-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 8.03 | 204 | 5.83 | 148 | 8.74 | 222 | 2.7/8 | 73 | | |

## JSEAL™ / JIC — T2281

**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**90° LONG TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2281-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.68 | 68 | 1.69 | 43 | 1.85 | 47 | | 14 | | |
| **T2281-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.83 | 72 | 1.85 | 47 | 2.13 | 54 | 3/4 | 19 | | |
| **T2281-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 3.03 | 77 | 2.05 | 52 | 2.17 | 55 | 3/4 | 19 | | |


# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

### JIS - BSPP

### T2220

JAPANESE INDUSTRIAL STANDARD (JIS)
BSPP MALE
60° CONVEX SEAT (JIS)





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T2220-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.20 | 56 | 1.22 | 31 | | | | | 11/16 | |
| **T2220-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.36 | 60 | 1.38 | 35 | | | | | 3/4 | 19 |
| **T2220-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.52 | 64 | 1.54 | 39 | | | | | 1 | |

### JIC - BSPP


### T2122

JAPANESE INDUSTRIAL STANDARD (JIS)
BSPP FEMALE
60° CONCAVE SEAT (JIS)




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2122-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.93 | 49 | 0.94 | 24 | | | 3/4 | 19 | | 14 |
| **T2122-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 1.97 | 50 | 0.98 | 25 | | | 7/8 | 22 | | 17 |
| **T2122-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.01 | 51 | 1.06 | 27 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T2122-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.05 | 52 | 1.06 | 27 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T2122-1012** | 16 | 5/8 | 3/4" -16 | | -1012 | 2.28 | 58 | 1.10 | 28 | | | | 36 | 1.1/16 | 27 |
| **T2122-1212** | 19 | 3/4 | 3/4" -16 | | -1212 | 2.36 | 60 | 1.18 | 30 | | | | 36 | 1.1/16 | 27 |
| **T2122-1616** | 25 | 1 | 1" -11 | | -1616 | 2.48 | 63 | 1.26 | 32 | | | 1.5/8 | 41 | | 36 |


## JIS — T2680




**JAPANESE INDUSTRIAL STANDARD (JIS)**
**METRIC FEMALE**
**60° CONCAVE SEAT (JIS)**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2680-0414** | 6 | 1/4 | M 14X1,5 | | -0414 | 1.77 | 45 | 0.79 | 20 | | | 3/4 | 19 | | 14 |
| **T2680-0418** | 6 | 1/4 | M 18X1,5 | | -0418 | 1.89 | 48 | 0.91 | 23 | | | 15/16 | 24 | | 17 |
| **T2680-0516** | 8 | 5/16 | M 16X1,5 | | -0516 | 1.89 | 48 | 0.91 | 23 | | | | | 5/8 | 16 |
| **T2680-0616** | 10 | 3/8 | M 16X1,5 | | -0616 | 1.85 | 47 | 0.87 | 22 | | | | 21 | | |
| **T2680-0618** | 10 | 3/8 | M 18X1,5 | | -0618 | 1.85 | 47 | 0.87 | 22 | | | 15/16 | 24 | | 17 |
| **T2680-0620** | 10 | 3/8 | M 20X1,5 | | -0620 | 2.01 | 51 | 1.02 | 26 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T2680-0622** | 10 | 3/8 | M 22X1,5 | | -0622 | 2.05 | 52 | 1.06 | 27 | | | 1.1/16 | 27 | 7/8 | 22 |
| **T2680-0822** | 12 | 1/2 | M 22X1,5 | | -0822 | 2.09 | 53 | 1.10 | 28 | | | 1.1/16 | 27 | 7/8 | 22 |
| **T2680-0824** | 12 | 1/2 | M 24X1,5 | | -0824 | 2.09 | 53 | 1.10 | 28 | | | 1.1/4 | 32 | 7/8 | 22 |
| **T2680-1024** | 16 | 5/8 | M 24X1,5 | | -1024 | 2.20 | 56 | 1.02 | 26 | | | 1.1/4 | 32 | 7/8 | 22 |
| **T2680-1030** | 16 | 5/8 | M 30X1,5 | | -1030 | 2.48 | 63 | 1.30 | 33 | | | | 36 | 1.1/4 | 32 |
| **T2680-1224** | 19 | 3/4 | M 24X1,5 | | -1224 | 2.24 | 57 | 1.06 | 27 | | | 1.1/4 | 32 | 1.1/16 | 27 |
| **T2680-1230** | 19 | 3/4 | M 30X1,5 | | -1230 | 2.52 | 64 | 1.34 | 34 | | | | 36 | 1.1/4 | 32 |
| **T2680-1233** | 19 | 3/4 | M 33X1,5 | | -1233 | 2.36 | 60 | 1.18 | 30 | | | 1.5/8 | 41 | 1.1/4 | 32 |
| **T2680-1633** | 25 | 1 | M 33X1,5 | | -1633 | 2.40 | 61 | 1.18 | 30 | | | 1.5/8 | 41 | 1.1/4 | 32 |
| **T2680-2036** | 31 | 1.1/4 | M 36X1,5 | | -2036 | 3.43 | 87 | 1.46 | 37 | | | | 46 | 1.1/2 | 38 |
| **T2680-2042** | 31 | 1.1/4 | M 42X1,5 | | -2042 | 3.50 | 89 | 1.54 | 39 | | | 2 | 50 | 1.5/8 | 41 |

## JIS — T2682





**METRIC FEMALE**
**60° CONCAVE SEAT (JIS) 45° BEND**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2682-0414** | 6 | 1/4 | M 14X1,5 | | -0414 | 2.28 | 58 | 1.30 | 33 | 0.59 | 15 | 3/4 | 19 | | |
| **T2682-0618** | 10 | 3/8 | M 18X1,5 | | -0618 | 2.52 | 64 | 1.54 | 39 | 0.75 | 19 | 15/16 | 24 | | |
| **T2682-0822** | 12 | 1/2 | M 22X1,5 | | -0822 | 2.87 | 73 | 1.89 | 48 | 0.87 | 22 | 1.1/16 | 27 | | |
| **T2682-1024** | 16 | 5/8 | M 24X1,5 | | -1024 | 3.27 | 83 | 2.09 | 53 | 0.94 | 24 | 1.1/4 | 32 | | |
| **T2682-1230** | 19 | 3/4 | M 30X1,5 | | -1230 | 3.78 | 96 | 2.64 | 67 | 1.10 | 28 | | 36 | | |
| **T2682-1633** | 25 | 1 | M 33X1,5 | | -1633 | 5.55 | 141 | 3.27 | 83 | 1.34 | 34 | | 41 | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS


### JIS — T2683




**JAPANESE INDUSTRIAL STANDARD (JIS)**
**METRIC FEMALE**
**60° CONCAVE SEAT (JIS) 90° BEND**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2683-0414** | 6 | 1/4 | M 14X1,5 | | -0414 | 2.05 | 52 | 1.06 | 27 | 1.18 | 30 | 3/4 | 19 | | |
| **T2683-0618** | 10 | 3/8 | M 18X1,5 | | -0618 | 2.36 | 60 | 1.38 | 35 | 1.30 | 33 | 15/16 | 24 | | |
| **T2683-0822** | 12 | 1/2 | M 22X1,5 | | -0822 | 2.52 | 64 | 1.54 | 39 | 1.65 | 42 | 1.1/16 | 27 | | |
| **T2683-1024** | 16 | 5/8 | M 24X1,5 | | -1024 | 2.95 | 75 | 1.77 | 45 | 1.89 | 48 | 1.1/4 | 32 | | |
| **T2683-1230** | 19 | 3/4 | M 30X1,5 | | -1230 | 3.35 | 85 | 2.20 | 56 | 2.20 | 56 | | 36 | | |
| **T2683-1633** | 25 | 1 | M 33X1,5 | | -1633 | 4.06 | 103 | 2.83 | 72 | 2.83 | 72 | | 41 | | |

### JOINER — T2900





**JOINER**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | | | |
| **T2900-0404** | 6 | 1/4 | | 1/4 | -0404 | 2.52 | 64 | 0.51 | 13 | | | | | | |
| **T2900-0505** | 8 | 5/16 | | 5/16 | -0505 | 2.52 | 64 | 0.51 | 13 | | | | | | |
| **T2900-0606** | 10 | 3/8 | | 3/8 | -0606 | 2.52 | 64 | 0.59 | 15 | | | | | | |
| **T2900-0808** | 12 | 1/2 | | 1/2 | -0808 | 2.56 | 65 | 0.59 | 15 | | | | | | |
| **T2900-1010** | 16 | 5/8 | | 5/8 | -1010 | 2.95 | 75 | 0.55 | 14 | | | | | | |
| **T2900-1212** | 19 | 3/4 | | 3/4 | -1212 | 2.95 | 75 | 0.63 | 16 | | | | | | |
| **T2900-1616** | 25 | 1 | | 1 | -1616 | 3.43 | 87 | 0.98 | 25 | | | | | | |
| **T2900-2020** | 31 | 1.1/4 | | 1.1/4 | -2020 | 4.88 | 124 | 0.94 | 24 | | | | | | |
| **T2900-2424** | 38 | 1.1/2 | | 1.1/2 | -2424 | 5.08 | 129 | 1.02 | 26 | | | | | | |
| **T2900-3232** | 51 | 2 | | 2 | -3232 | 5.47 | 139 | 1.06 | 27 | | | | | | |
| **T2900-4040** | 63 | 2.1/2 | | 2.1/2 | -4040 | 7.05 | 179 | 1.02 | 26 | | | | | | |
| **T2900-4848** | 76 | 3 | | 3 | -4848 | 7.05 | 179 | 1.02 | 26 | | | | | | |

## METRIC - DKL

## T2650

**DKL MALE**
**24° SEAT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | | | inch | mm |
| **T2650-0412** | 6 | 1/4 | M 12X1,5 | 6 | -0412 | 2.01 | 51 | 0.98 | 25 | | | | | | 14 |
| **T2650-0414** | 6 | 1/4 | M 14X1,5 | 8 | -0414 | 2.01 | 51 | 0.98 | 25 | | | | | | 14 |
| **T2650-0416** | 6 | 1/4 | M 16X1,5 | 10 | -0416 | 2.05 | 52 | 1.02 | 26 | | | | | | 17 |
| **T2650-0418** | 6 | 1/4 | M 18X1,5 | 12 | -0418 | 2.05 | 52 | 1.02 | 26 | | | | | 3/4 | 19 |
| **T2650-0516** | 8 | 5/16 | M 16X1,5 | 10 | -0516 | 2.13 | 54 | 1.14 | 29 | | | | | | 17 |
| **T2650-0518** | 8 | 5/16 | M 18X1,5 | 12 | -0518 | 2.05 | 52 | 1.02 | 26 | | | | | 3/4 | 19 |
| **T2650-0616** | 10 | 3/8 | M 16X1,5 | 10 | -0616 | 2.13 | 54 | 1.14 | 29 | | | | | | 17 |
| **T2650-0618** | 10 | 3/8 | M 18X1,5 | 12 | -0618 | 2.13 | 54 | 1.14 | 29 | | | | | 3/4 | 19 |
| **T2650-0622** | 10 | 3/8 | M 22X1,5 | 15 | -0622 | 2.05 | 52 | 1.06 | 27 | | | | | 15/16 | 24 |
| **T2650-0818** | 12 | 1/2 | M 18X1,5 | 12 | -0818 | 2.13 | 54 | 1.18 | 30 | | | | | 3/4 | 19 |
| **T2650-0822** | 12 | 1/2 | M 22X1,5 | 15 | -0822 | 2.24 | 57 | 1.26 | 32 | | | | | 7/8 | 22 |
| **T2650-0826** | 12 | 1/2 | M 26X1,5 | 18 | -0826 | 2.24 | 57 | 1.26 | 32 | | | | | 1.3/16 | 30 |
| **T2650-1026** | 16 | 5/8 | M 26X1,5 | 18 | -1026 | 2.32 | 59 | 1.14 | 29 | | | | | 1.3/16 | 30 |
| **T2650-1030** | 16 | 5/8 | M 30X2 | 22 | -1030 | 2.40 | 61 | 1.22 | 31 | | | | | 1.1/4 | 32 |
| **T2650-1226** | 19 | 3/4 | M 26X1,5 | 18 | -1226 | 2.32 | 59 | 1.18 | 30 | | | | | 1.3/16 | 30 |
| **T2650-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 2.40 | 61 | 1.26 | 32 | | | | | 1.1/4 | 32 |
| **T2650-1636** | 25 | 1 | M 36X2 | 28 | -1636 | 2.68 | 68 | 1.50 | 38 | | | | | 1.5/8 | 41 |
| **T2650-2045** | 31 | 1.1/4 | M 45X2 | 35 | -2045 | 3.66 | 93 | 1.69 | 43 | | | | | | 46 |
| **T2650-2452** | 38 | 1.1/2 | M 52X2 | 42 | -2452 | 3.90 | 99 | 1.89 | 48 | | | | | 2.3/16 | 55 |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

## METRIC - DKL | T2600


**DKL FEMALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | inch | mm | | |
| **T2600-0412** | 6 | 1/4 | M 12X1,5 | 6 | -0412 | 1.85 | 47 | 0.83 | 21 | | | | 14 | | |
| **T2600-0414** | 6 | 1/4 | M 14X1,5 | 8 | -0414 | 1.85 | 47 | 0.87 | 22 | | | | 17 | | |
| **T2600-0416** | 6 | 1/4 | M 16X1,5 | 10 | -0416 | 1.89 | 48 | 0.91 | 23 | | | 3/4 | 19 | | |
| **T2600-0516** | 8 | 5/16 | M 16X1,5 | 10 | -0516 | 1.89 | 48 | 0.91 | 23 | | | 3/4 | 19 | | |
| **T2600-0518** | 8 | 5/16 | M 18X1,5 | 12 | -0518 | 1.89 | 48 | 0.91 | 23 | | | 7/8 | 22 | | |
| **T2600-0614** | 10 | 3/8 | M 14X1,5 | 8 | -0614 | 1.85 | 47 | 0.87 | 22 | | | | 17 | | |
| **T2600-0616** | 10 | 3/8 | M 16X1,5 | 10 | -0616 | 1.89 | 48 | 0.91 | 23 | | | 3/4 | 19 | | |
| **T2600-0618** | 10 | 3/8 | M 18X1,5 | 12 | -0618 | 1.89 | 48 | 0.91 | 23 | | | 7/8 | 22 | | |
| **T2600-0622** | 10 | 3/8 | M 22X1,5 | 15 | -0622 | 2.01 | 51 | 1.02 | 26 | | | 1.1/16 | 27 | | |
| **T2600-0818** | 12 | 1/2 | M 18X1,5 | 12 | -0818 | 1.93 | 49 | 0.94 | 24 | | | 7/8 | 22 | | |
| **T2600-0822** | 12 | 1/2 | M 22X1,5 | 15 | -0822 | 1.97 | 50 | 0.98 | 25 | | | 1.1/16 | 27 | | |
| **T2600-0826** | 12 | 1/2 | M 26X1,5 | 18 | -0826 | 2.01 | 51 | 1.06 | 27 | | | 1.1/4 | 32 | | |
| **T2600-1026** | 16 | 5/8 | M 26X1,5 | 18 | -1026 | 2.20 | 56 | 1.02 | 26 | | | 1.1/4 | 32 | | |
| **T2600-1226** | 19 | 3/4 | M 26X1,5 | 18 | -1226 | 2.20 | 56 | 1.06 | 27 | | | 1.1/4 | 32 | | |
| **T2600-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 2.24 | 57 | 1.06 | 27 | | | | 36 | | |
| **T2600-1636** | 25 | 1 | M 36X2 | 28 | -1636 | 2.40 | 61 | 1.18 | 30 | | | 1.5/8 | 41 | | |
| **T2600-2045** | 31 | 1.1/4 | M 45X2 | 35 | -2045 | 3.31 | 84 | 1.34 | 34 | | | 2 | 50 | | |

## METRIC - DKL | T2660

**DKL FEMALE**
**45° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2660-0412** | 6 | 1/4 | M 12X1,5 | 6 | -0412 | 2.40 | 61 | 1.42 | 36 | 0.71 | 18 | | 14 | | |
| **T2660-0414** | 6 | 1/4 | M 14X1,5 | 8 | -0414 | 2.40 | 61 | 1.42 | 36 | 0.67 | 17 | | 17 | | |
| **T2660-0516** | 8 | 5/16 | M 16X1,5 | 10 | -0516 | 2.76 | 70 | 1.77 | 45 | 0.79 | 20 | 3/4 | 19 | | |
| **T2660-0616** | 10 | 3/8 | M 16X1,5 | 10 | -0616 | 2.76 | 70 | 1.77 | 45 | 0.79 | 20 | 3/4 | 19 | | |
| **T2660-0618** | 10 | 3/8 | M 18X1,5 | 12 | -0618 | 2.76 | 70 | 1.77 | 45 | 0.79 | 20 | 7/8 | 22 | | |
| **T2660-0822** | 12 | 1/2 | M 22X1,5 | 15 | -0822 | 2.95 | 75 | 1.97 | 50 | 0.87 | 22 | 1.1/16 | 27 | | |
| **T2660-0826** | 12 | 1/2 | M 26X1,5 | 18 | -0826 | 2.95 | 75 | 1.97 | 50 | 0.87 | 22 | 1.1/4 | 32 | | |
| **T2660-1026** | 16 | 5/8 | M 26X1,5 | 18 | -1026 | 3.54 | 90 | 2.36 | 60 | 1.10 | 28 | 1.1/4 | 32 | | |
| **T2660-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 4.06 | 103 | 2.87 | 73 | 1.26 | 32 | | 36 | | |
| **T2660-1636** | 25 | 1 | M 36X2 | 28 | -1636 | 4.45 | 113 | 3.23 | 82 | 1.65 | 42 | 1.5/8 | 41 | | |

## METRIC - DKL

## T2670

**DKL FEMALE**
**90° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2670-0412** | 6 | 1/4 | M 12X1,5 | 6 | -0412 | 2.05 | 52 | 1.06 | 27 | 1.22 | 31 | | 14 | | |
| **T2670-0414** | 6 | 1/4 | M 14X1,5 | 8 | -0414 | 2.05 | 52 | 1.06 | 27 | 1.22 | 31 | | 17 | | |
| **T2670-0416** | 6 | 1/4 | M 16X1,5 | 10 | -0416 | 2.05 | 52 | 1.06 | 27 | 1.26 | 32 | 3/4 | 19 | | |
| **T2670-0614** | 10 | 3/8 | M 14X1,5 | 8 | -0614 | 2.28 | 58 | 1.30 | 33 | 1.22 | 31 | | 17 | | |
| **T2670-0616** | 10 | 3/8 | M 16X1,5 | 10 | -0616 | 2.36 | 60 | 1.38 | 35 | 1.38 | 35 | 3/4 | 19 | | |
| **T2670-0618** | 10 | 3/8 | M 18X1,5 | 12 | -0618 | 2.32 | 59 | 1.34 | 34 | 1.38 | 35 | 7/8 | 22 | | |
| **T2670-0622** | 10 | 3/8 | M 22X1,5 | 15 | -0622 | 2.32 | 59 | 1.34 | 34 | 1.46 | 37 | 1.1/16 | 27 | | |
| **T2670-0822** | 12 | 1/2 | M 22X1,5 | 15 | -0822 | 2.56 | 65 | 1.57 | 40 | 1.73 | 44 | 1.1/16 | 27 | | |
| **T2670-0826** | 12 | 1/2 | M 26X1,5 | 18 | -0826 | 2.44 | 62 | 1.46 | 37 | 1.97 | 50 | 1.1/4 | 32 | | |
| **T2670-1026** | 16 | 5/8 | M 26X1,5 | 18 | -1026 | 3.03 | 77 | 1.85 | 47 | 2.09 | 53 | 1.1/4 | 32 | | |
| **T2670-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 3.39 | 86 | 2.20 | 56 | 2.52 | 64 | | 36 | | |
| **T2670-1636** | 25 | 1 | M 36X2 | 28 | -1636 | 3.94 | 100 | 2.72 | 69 | 2.87 | 73 | 1.5/8 | 41 | | |

## METRIC - DKM

## T2610

**DKM FEMALE**
**60° CONE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | mm | | inch | mm | inch | mm | | | | mm | inch | mm |
| **T2610-0616** | 10 | 3/8 | M 16X1,5 | 10 | -0616 | 1.91 | 49 | 0.94 | 24 | | | | 19 | | |
| **T2610-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 2.17 | 55 | 0.98 | 25 | | | | 36 | | |
| **T2610-2052** | 31 | 1.1/4 | M 52X2 | 42 | -2052 | 3.53 | 90 | 1.56 | 40 | | | | 60 | | |
| **T2610-2452** | 38 | 1.1/2 | M 52X2 | 42 | -2452 | 3.62 | 92 | 1.59 | 41 | | | | 60 | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

| METRIC - DKOL | T2501 |
|---|---|

**DKOL FEMALE**
**24° CONE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2501-0312** | 5 | 3/16 | M 12X1,5 | 6 | -0312 | 1.61 | 41 | 0.83 | 21 | | | | 14 | | |
| **T2501-0412** | 6 | 1/4 | M 12X1,5 | 6 | -0412 | 1.81 | 46 | 0.83 | 21 | | | | 14 | | |
| **T2501-0414** | 6 | 1/4 | M 14X1,5 | 8 | -0414 | 2.05 | 52 | 1.02 | 26 | | | | 17 | 1/2 | |
| **T2501-0416** | 6 | 1/4 | M 16X1,5 | 10 | -0416 | 2.13 | 54 | 1.10 | 28 | | | 3/4 | 19 | 1/2 | |
| **T2501-0514** | 8 | 5/16 | M 14X1,5 | 8 | -0514 | 1.85 | 47 | 0.87 | 22 | | | | 17 | | |
| **T2501-0516** | 8 | 5/16 | M 16X1,5 | 10 | -0516 | 2.13 | 54 | 1.14 | 29 | | | 3/4 | 19 | 9/16 | |
| **T2501-0518** | 8 | 5/16 | M 18X1,5 | 12 | -0518 | 2.17 | 55 | 1.14 | 29 | | | 7/8 | 22 | 9/16 | |
| **T2501-0612** | 10 | 3/8 | M 12X1,5 | 6 | -0612 | 2.05 | 52 | 1.05 | 27 | | | | 14 | 5/8 | 16 |
| **T2501-0614** | 10 | 3/8 | M 14X1,5 | 8 | -0614 | 2.05 | 52 | 1.06 | 27 | | | | 17 | 5/8 | 16 |
| **T2501-0616** | 10 | 3/8 | M 16X1,5 | 10 | -0616 | 2.13 | 54 | 1.14 | 29 | | | 3/4 | 19 | 5/8 | 16 |
| **T2501-0618** | 10 | 3/8 | M 18X1,5 | 12 | -0618 | 2.17 | 55 | 1.18 | 30 | | | 7/8 | 22 | 5/8 | 16 |
| **T2501-0622** | 10 | 3/8 | M 22X1,5 | 15 | -0622 | 2.24 | 57 | 1.26 | 32 | | | 1.1/16 | 27 | 5/8 | 16 |
| **T2501-0818** | 12 | 1/2 | M 18X1,5 | 12 | -0818 | 2.13 | 54 | 1.14 | 29 | | | 7/8 | 22 | 3/4 | 19 |
| **T2501-0822** | 12 | 1/2 | M 22X1,5 | 15 | -0822 | 2.24 | 57 | 1.26 | 32 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T2501-0826** | 12 | 1/2 | M 26X1,5 | 18 | -0826 | 2.28 | 58 | 1.30 | 33 | | | 1.1/4 | 32 | 3/4 | 19 |
| **T2501-1026** | 16 | 5/8 | M 26X1,5 | 18 | -1026 | 2.56 | 65 | 1.34 | 34 | | | 1.1/4 | 32 | 7/8 | 22 |
| **T2501-1030** | 16 | 5/8 | M 30X2 | 22 | -1030 | 2.60 | 66 | 1.42 | 36 | | | | 36 | 7/8 | 22 |
| **T2501-1226** | 19 | 3/4 | M 26X1,5 | 18 | -1226 | 2.68 | 66 | 1.54 | 37 | | | 1.1/4 | 32 | 1.1/16 | 27 |
| **T2501-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 2.68 | 66 | 1.50 | 36 | | | | 36 | 1.1/16 | 27 |
| **T2501-1636** | 25 | 1 | M 36X2 | 28 | -1636 | 2.91 | 74 | 1.69 | 39 | | | 1.5/8 | 41 | 1.1/4 | 32 |
| **T2501-2045** | 31 | 1.1/4 | M 45X2 | 35 | -2045 | 3.82 | 97 | 1.85 | 47 | | | 2 | 50 | 1.5/8 | 41 |
| **T2501-2452** | 38 | 1.1/2 | M 52X2 | 42 | -2452 | 3.43 | 87 | 1.38 | 35 | | | 2.3/8 | 60 | | |

## METRIC - DKOL

## T2510

**DKOL FEMALE**
**24° CONE**
**45° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2510-0412** | 6 | 1/4 | M 12X1,5 | 6 | -0412 | 2.40 | 61 | 1.42 | 36 | 0.71 | 18 | | 14 | | |
| **T2510-0414** | 6 | 1/4 | M 14X1,5 | 8 | -0414 | 2.36 | 60 | 1.38 | 35 | 0.67 | 17 | | 17 | | |
| **T2510-0416** | 6 | 1/4 | M 16X1,5 | 10 | -0416 | 2.36 | 60 | 1.38 | 35 | 0.67 | 17 | 3/4 | 19 | | |
| **T2510-0418** | 6 | 1/4 | M 18X1,5 | 12 | -0418 | 2.44 | 62 | 1.46 | 37 | 0.79 | 20 | 7/8 | 22 | | |
| **T2510-0516** | 8 | 5/16 | M 16X1,5 | 10 | -0516 | 2.76 | 70 | 1.77 | 45 | 0.79 | 20 | 3/4 | 19 | | |
| **T2510-0518** | 8 | 5/16 | M 18X1,5 | 12 | -0518 | 2.76 | 70 | 1.77 | 45 | 0.79 | 20 | | 22 | | |
| **T2510-0612** | 10 | 3/8 | M 12X1,5 | 6 | -0612 | 2.68 | 68 | 1.69 | 43 | 0.67 | 17 | | 14 | | |
| **T2510-0616** | 10 | 3/8 | M 16X1,5 | 10 | -0616 | 2.76 | 70 | 1.77 | 45 | 0.75 | 19 | 3/4 | 19 | | |
| **T2510-0618** | 10 | 3/8 | M 18X1,5 | 12 | -0618 | 2.76 | 70 | 1.77 | 45 | 0.79 | 20 | 7/8 | 22 | | |
| **T2510-0822** | 12 | 1/2 | M 22X1,5 | 15 | -0822 | 3.03 | 77 | 2.05 | 52 | 0.87 | 22 | 1.1/16 | 27 | | |
| **T2510-0826** | 12 | 1/2 | M 26X1,5 | 18 | -0826 | 3.07 | 78 | 2.09 | 53 | 0.94 | 24 | 1.1/4 | 32 | | |
| **T2510-1026** | 16 | 5/8 | M 26X1,5 | 18 | -1026 | 3.50 | 89 | 2.28 | 58 | 1.10 | 28 | 1.1/4 | 32 | | |
| **T2510-1030** | 16 | 5/8 | M 30X2 | 22 | -1030 | 3.54 | 90 | 2.36 | 60 | 1.14 | 29 | | 36 | | |
| **T2510-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 4.09 | 102 | 2.91 | 72 | 1.22 | 31 | | 36 | | |
| **T2510-1636** | 25 | 1 | M 36X2 | 28 | -1636 | 4.84 | 123 | 3.62 | 94 | 1.81 | 46 | 1.5/8 | 41 | | |
| **T2510-2045** | 31 | 1.1/4 | M 45X2 | 35 | -2045 | 5.91 | 150 | 3.98 | 101 | 1.57 | 40 | 2 | 50 | | |
| **T2510-2452** | 38 | 1.1/2 | M 52X2 | 42 | -2452 | 6.65 | 169 | 4.65 | 118 | 1.93 | 49 | 2.3/8 | 60 | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

| METRIC - DKOL | T2520 |
|---|---|

**DKOL FEMALE**
**24° CONE**
**90° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2520-0412** | 6 | 1/4 | M 12X1,5 | 6 | -0412 | 2.05 | 52 | 1.06 | 27 | 1.22 | 31 | | 14 | | |
| **T2520-0414** | 6 | 1/4 | M 14X1,5 | 8 | -0414 | 2.28 | 58 | 1.30 | 33 | 1.22 | 31 | | 17 | | |
| **T2520-0416** | 6 | 1/4 | M 16X1,5 | 10 | -0416 | 2.05 | 52 | 1.06 | 27 | 1.22 | 31 | 3/4 | 19 | | |
| **T2520-0418** | 6 | 1/4 | M 18X1,5 | 12 | -0418 | 2.28 | 58 | 1.30 | 33 | 1.34 | 34 | 7/8 | 22 | | |
| **T2520-0516** | 8 | 5/16 | M 16X1,5 | 10 | -0516 | 2.32 | 59 | 1.34 | 34 | 1.38 | 35 | 3/4 | 19 | | |
| **T2520-0518** | 8 | 5/16 | M 18X1,5 | 12 | -0518 | 2.40 | 61 | 1.42 | 36 | 1.38 | 35 | 7/8 | 22 | | |
| **T2520-0616** | 10 | 3/8 | M 16X1,5 | 10 | -0616 | 2.36 | 60 | 1.38 | 35 | 1.42 | 36 | 3/4 | 19 | | |
| **T2520-0618** | 10 | 3/8 | M 18X1,5 | 12 | -0618 | 2.36 | 60 | 1.38 | 35 | 1.38 | 35 | 7/8 | 22 | | |
| **T2520-0622** | 10 | 3/8 | M 22X1,5 | 15 | -0622 | 2.56 | 65 | 1.57 | 40 | 1.73 | 44 | 1.1/16 | 27 | | |
| **T2520-0822** | 12 | 1/2 | M 22X1,5 | 15 | -0822 | 2.60 | 66 | 1.61 | 41 | 1.73 | 44 | 1.1/16 | 27 | | |
| **T2520-0826** | 12 | 1/2 | M 26X1,5 | 18 | -0826 | 2.60 | 66 | 1.61 | 41 | 1.89 | 48 | 1.1/4 | 32 | | |
| **T2520-1026** | 16 | 5/8 | M 26X1,5 | 18 | -1026 | 3.07 | 78 | 1.89 | 48 | 2.13 | 54 | 1.1/4 | 32 | | |
| **T2520-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 3.50 | 87 | 2.32 | 57 | 2.56 | 65 | | 36 | | |
| **T2520-1636** | 25 | 1 | M 36X2 | 28 | -1636 | 3.94 | 100 | 2.72 | 45 | 3.11 | 79 | 1.5/8 | 41 | | |
| **T2520-2045** | 31 | 1.1/4 | M 45X2 | 35 | -2045 | 5.87 | 149 | 3.94 | 100 | 2.99 | 76 | 2 | 50 | | |
| **T2520-2452** | 38 | 1.1/2 | M 52X2 | 42 | -2452 | 5.94 | 151 | 3.90 | 99 | 4.02 | 102 | 2.3/8 | 60 | | |

## METRIC - DKS

## T2630

**DKS MALE**
**24° SEAT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | | | inch | mm |
| **T2630-0414** | 6 | 1/4 | M 14X1,5 | 6 | -0414 | 2.09 | 53 | 1.06 | 27 | | | | | | 17 |
| **T2630-0416** | 6 | 1/4 | M 16X1,5 | 8 | -0416 | 2.09 | 53 | 1.06 | 27 | | | | | | 17 |
| **T2630-0418** | 6 | 1/4 | M 18X1,5 | 10 | -0418 | 1.93 | 49 | 0.94 | 24 | | | | | 3/4 | 19 |
| **T2630-0420** | 6 | 1/4 | M 20X1,5 | 12 | -0420 | 2.06 | 52 | 1.06 | 27 | | | | | | |
| **T2630-0422** | 6 | 1/4 | M 22X1,5 | 14 | -0422 | 2.18 | 55 | 1.18 | 30 | | | | | | |
| **T2630-0520** | 8 | 5/16 | M 20X1,5 | 12 | -0520 | 2.17 | 55 | 1.18 | 30 | | | | | 7/8 | 22 |
| **T2630-0618** | 10 | 3/8 | M 18X1,5 | 10 | -0618 | 1.89 | 48 | 0.94 | 24 | | | | | 3/4 | 19 |
| **T2630-0620** | 10 | 3/8 | M 20X1,5 | 12 | -0620 | 2.17 | 55 | 1.18 | 30 | | | | | 7/8 | 22 |
| **T2630-0622** | 10 | 3/8 | M 22X1,5 | 14 | -0622 | 2.13 | 54 | 1.14 | 29 | | | | | 15/16 | 24 |
| **T2630-0824** | 12 | 1/2 | M 24X1,5 | 16 | -0824 | 2.13 | 54 | 1.18 | 30 | | | | | 1.1/16 | 27 |
| **T2630-0830** | 12 | 1/2 | M 30X2 | 20 | -0830 | 2.20 | 56 | 1.26 | 32 | | | | | 1.1/4 | 32 |
| **T2630-1030** | 16 | 5/8 | M 30X2 | 20 | -1030 | 2.44 | 62 | 1.22 | 31 | | | | | 1.1/4 | 32 |
| **T2630-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 2.56 | 65 | 1.38 | 35 | | | | | 1.1/4 | 32 |
| **T2630-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 2.64 | 67 | 1.46 | 37 | | | | | 1.5/8 | 41 |
| **T2630-1636** | 25 | 1 | M 36X2 | 25 | -1636 | 2.83 | 72 | 1.61 | 41 | | | | | 1.5/8 | 41 |
| **T2630-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 2.91 | 74 | 1.69 | 43 | | | | | | 46 |
| **T2630-2042** | 31 | 1.1/4 | M 42X2 | 30 | -2042 | 3.86 | 98 | 1.89 | 48 | | | | | | 46 |
| **T2630-2052** | 31 | 1.1/4 | M 52X2 | 38 | -2052 | 3.82 | 97 | 1.85 | 47 | | | | | 2.3/16 | 55 |
| **T2630-2452** | 38 | 1.1/2 | M 52X2 | 38 | -2452 | 4.12 | 105 | 2.09 | 53 | | | | | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

| METRIC - DKOS | T2711 |
|---|---|

**DKOS FEMALE**
**24° CONE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2711-0414** | 6 | 1/4 | M 14X1,5 | 6 | -0414 | 1.77 | 45 | 0.79 | 20 | | | | 17 | | |
| **T2711-0416** | 6 | 1/4 | M 16X1,5 | 8 | -0416 | 2.09 | 53 | 1.06 | 27 | | | 3/4 | 19 | 1/2 | |
| **T2711-0418** | 6 | 1/4 | M 18X1,5 | 10 | -0418 | 1.97 | 50 | 0.98 | 25 | | | 7/8 | 22 | | |
| **T2711-0518** | 8 | 5/16 | M 18X1,5 | 10 | -0518 | 2.20 | 56 | 1.22 | 31 | | | 7/8 | 22 | 9/16 | |
| **T2711-0520** | 8 | 5/16 | M 20X1,5 | 12 | -0520 | 2.20 | 56 | 1.22 | 31 | | | 15/16 | 24 | 9/16 | |
| **T2711-0616** | 10 | 3/8 | M 16X1,5 | 8 | -0616 | 2.09 | 53 | 1.10 | 28 | | | 3/4 | 19 | 5/8 | 16 |
| **T2711-0618** | 10 | 3/8 | M 18X1,5 | 10 | -0618 | 2.20 | 56 | 1.22 | 31 | | | 7/8 | 22 | 5/8 | 16 |
| **T2711-0620** | 10 | 3/8 | M 20X1,5 | 12 | -0620 | 2.20 | 56 | 1.22 | 31 | | | 15/16 | 24 | 5/8 | 16 |
| **T2711-0622** | 10 | 3/8 | M 22X1,5 | 14 | -0622 | 2.28 | 58 | 1.30 | 33 | | | 1.1/16 | 27 | 5/8 | 16 |
| **T2711-0624** | 10 | 3/8 | M 24X1,5 | 16 | -0624 | 2.28 | 58 | 1.30 | 33 | | | 1.3/16 | 30 | 5/8 | 16 |
| **T2711-0820** | 12 | 1/2 | M 20X1,5 | 12 | -0820 | 2.20 | 56 | 1.22 | 31 | | | 15/16 | 24 | 3/4 | 19 |
| **T2711-0822** | 12 | 1/2 | M 22X1,5 | 14 | -0822 | 2.28 | 58 | 1.30 | 33 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T2711-0824** | 12 | 1/2 | M 24X1,5 | 16 | -0824 | 2.28 | 58 | 1.30 | 33 | | | 1.3/16 | 30 | 3/4 | 19 |
| **T2711-1030** | 16 | 5/8 | M 30X2 | 20 | -1030 | 2.80 | 71 | 1.57 | 40 | | | | 36 | 7/8 | 22 |
| **T2711-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 2.80 | 69 | 1.65 | 40 | | | | 36 | 1.1/16 | 24 |
| **T2711-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 2.99 | 74 | 1.81 | 44 | | | | 46 | 1.1/16 | 24 |
| **T2711-1636** | 25 | 1 | M 36X2 | 25 | -1636 | 2.99 | 76 | 1.81 | 42 | | | | 46 | 1.1/4 | 32 |
| **T2711-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 3.03 | 77 | 1.81 | 42 | | | 2 | 50 | 1.1/4 | 32 |
| **T2711-2042** | 31 | 1.1/4 | M 42X2 | 30 | -2042 | 3.46 | 88 | 1.50 | 38 | | | 2 | 50 | | |
| **T2711-2052** | 31 | 1.1/4 | M 52X2 | 38 | -2052 | 3.66 | 93 | 1.69 | 43 | | | 2.3/8 | 60 | | |
| **T2711-2452** | 38 | 1.1/2 | M 52X2 | 38 | -2452 | 3.78 | 96 | 1.73 | 44 | | | 2.3/8 | 60 | | |

## METRIC - DKOS

## T2720

**DKOS FEMALE**
**24° CONE**
**45° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2720-0414** | 6 | 1/4 | M 14X1,5 | 6 | -0414 | 2.36 | 60 | 1.38 | 35 | 0.63 | 16 | | 17 | | |
| **T2720-0416** | 6 | 1/4 | M 16X1,5 | 8 | -0416 | 2.40 | 61 | 1.42 | 36 | 0.67 | 17 | 3/4 | 19 | | |
| **T2720-0418** | 6 | 1/4 | M 18X1,5 | 10 | -0418 | 2.36 | 60 | 1.38 | 35 | 0.67 | 17 | 7/8 | 22 | | |
| **T2720-0518** | 8 | 5/16 | M 18X1,5 | 10 | -0518 | 2.80 | 71 | 1.81 | 46 | 0.67 | 17 | 7/8 | 22 | | |
| **T2720-0520** | 8 | 5/16 | M 20X1,5 | 12 | -0520 | 2.80 | 71 | 1.81 | 46 | 0.79 | 20 | 15/16 | 24 | | |
| **T2720-0616** | 10 | 3/8 | M 16X1,5 | 8 | -0616 | 2.56 | 65 | 1.57 | 40 | 0.67 | 17 | 3/4 | 19 | | |
| **T2720-0618** | 10 | 3/8 | M 18X1,5 | 10 | -0618 | 2.76 | 70 | 1.77 | 45 | 0.67 | 17 | 7/8 | 22 | | |
| **T2720-0620** | 10 | 3/8 | M 20X1,5 | 12 | -0620 | 2.80 | 71 | 1.81 | 46 | 0.79 | 20 | 15/16 | 24 | | |
| **T2720-0622** | 10 | 3/8 | M 22X1,5 | 14 | -0622 | 2.80 | 71 | 1.81 | 46 | 0.79 | 20 | 1.1/16 | 27 | | |
| **T2720-0822** | 12 | 1/2 | M 22X1,5 | 14 | -0822 | 3.07 | 78 | 2.09 | 53 | 0.94 | 24 | 1.1/16 | 27 | | |
| **T2720-0824** | 12 | 1/2 | M 24X1,5 | 16 | -0824 | 3.07 | 78 | 2.09 | 53 | 0.94 | 24 | 1.3/16 | 30 | | |
| **T2720-1030** | 16 | 5/8 | M 30X2 | 20 | -1030 | 3.66 | 93 | 2.48 | 63 | 1.22 | 31 | | 36 | | |
| **T2720-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 4.09 | 102 | 2.91 | 72 | 1.38 | 35 | | 36 | | |
| **T2720-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 4.17 | 104 | 2.99 | 74 | 1.38 | 35 | | 46 | | |
| **T2720-1636** | 25 | 1 | M 36X2 | 25 | -1636 | 4.76 | 121 | 3.54 | 83 | 1.38 | 35 | | 46 | | |
| **T2720-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 4.65 | 118 | 3.43 | 85 | 1.46 | 37 | 2 | 50 | | 32 |
| **T2720-2052** | 31 | 1.1/4 | M 52X2 | 38 | -2052 | 6.14 | 156 | 4.17 | 106 | 1.89 | 48 | 2.3/8 | 60 | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

| METRIC - DKOS | T2730 |
|---|---|


**DKOS FEMALE**
**24° CONE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2730-0414** | 6 | 1/4 | M 14X1,5 | 6 | -0414 | 2.05 | 52 | 1.06 | 27 | 1.10 | 28 | | 17 | | |
| **T2730-0416** | 6 | 1/4 | M 16X1,5 | 8 | -0416 | 2.05 | 52 | 1.06 | 27 | 1.22 | 31 | 3/4 | 19 | | |
| **T2730-0418** | 6 | 1/4 | M 18X1,5 | 10 | -0418 | 2.28 | 58 | 1.30 | 33 | 1.26 | 32 | 7/8 | 22 | | |
| **T2730-0520** | 8 | 5/16 | M 20X1,5 | 12 | -0520 | 2.40 | 61 | 1.42 | 36 | 1.42 | 36 | 15/16 | 24 | | |
| **T2730-0616** | 10 | 3/8 | M 16X1,5 | 8 | -0616 | 2.36 | 60 | 1.38 | 35 | 1.26 | 32 | 3/4 | 19 | | |
| **T2730-0618** | 10 | 3/8 | M 18X1,5 | 10 | -0618 | 2.05 | 52 | 1.06 | 27 | 1.18 | 30 | 7/8 | 22 | | |
| **T2730-0620** | 10 | 3/8 | M 20X1,5 | 12 | -0620 | 2.40 | 61 | 1.42 | 36 | 1.42 | 36 | 15/16 | 24 | | |
| **T2730-0622** | 10 | 3/8 | M 22X1,5 | 14 | -0622 | 2.40 | 61 | 1.42 | 36 | 1.42 | 36 | 1.1/16 | 27 | | |
| **T2730-0822** | 12 | 1/2 | M 22X1,5 | 14 | -0822 | 2.60 | 66 | 1.61 | 41 | 1.89 | 48 | 1.1/16 | 27 | | |
| **T2730-0824** | 12 | 1/2 | M 24X1,5 | 16 | -0824 | 2.60 | 66 | 1.61 | 41 | 1.89 | 48 | 1.3/16 | 30 | | |
| **T2730-1030** | 16 | 5/8 | M 30X2 | 20 | -1030 | 2.95 | 75 | 1.77 | 45 | 2.28 | 58 | | 36 | | |
| **T2730-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 3.50 | 87 | 2.32 | 57 | 2.68 | 68 | | 36 | | |
| **T2730-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 3.50 | 87 | 2.32 | 57 | 2.68 | 68 | | 46 | | |
| **T2730-1636** | 25 | 1 | M 36X2 | 25 | -1636 | 3.94 | 100 | 2.72 | 74 | 3.03 | 77 | | 46 | | |
| **T2730-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 3.94 | 100 | 2.72 | 74 | 3.03 | 77 | 2 | 50 | | |
| **T2730-2052** | 31 | 1.1/4 | M 52X2 | 38 | -2052 | 5.31 | 135 | 3.35 | 85 | 3.50 | 89 | 2.3/8 | 60 | | |
| **T2730-2452** | 38 | 1.1/2 | M 52X2 | 38 | -2452 | 5.63 | 143 | 3.58 | 91 | 3.50 | 89 | 2.3/8 | 60 | | |

# METRIC BANJO — T2470

**METRIC BANJO**
**STRAIGHT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | inch | | inch | mm | inch | mm | | | | | | |
| **T2470-0412** | 6 | 1/4 | 12 | | -0412 | 1.89 | 48 | 0.91 | 23 | | | | | | |
| **T2470-0414** | 6 | 1/4 | 14 | | -0414 | 1.97 | 50 | 0.98 | 25 | | | | | | |
| **T2470-0416** | 6 | 1/4 | 16 | | -0416 | 2.05 | 52 | 1.06 | 27 | | | | | | |
| **T2470-0512** | 8 | 5/16 | 12 | | -0512 | 1.97 | 50 | 0.98 | 25 | | | | | | |
| **T2470-0514** | 8 | 5/16 | 14 | | -0514 | 2.52 | 64 | 1.54 | 39 | | | | | | |
| **T2470-0516** | 8 | 5/16 | 16 | | -0516 | 2.05 | 52 | 1.06 | 27 | | | | | | |
| **T2470-0612** | 10 | 3/8 | 12 | | -0612 | 1.97 | 50 | 0.98 | 25 | | | | | | |
| **T2470-0614** | 10 | 3/8 | 14 | | -0614 | 2.05 | 52 | 1.06 | 27 | | | | | | |
| **T2470-0616** | 10 | 3/8 | 16 | | -0616 | 2.05 | 52 | 1.06 | 27 | | | | | | |
| **T2470-0618** | 10 | 3/8 | 18 | | -0618 | 2.13 | 54 | 1.14 | 29 | | | | | | |
| **T2470-0620** | 10 | 3/8 | 20 | | -0620 | 2.13 | 54 | 1.14 | 29 | | | | | | |
| **T2470-0622** | 10 | 3/8 | 22 | | -0622 | 2.32 | 59 | 1.34 | 34 | | | | | | |
| **T2470-0818** | 12 | 1/2 | 18 | | -0818 | 2.13 | 54 | 1.18 | 30 | | | | | | |
| **T2470-0822** | 12 | 1/2 | 22 | | -0822 | 2.24 | 57 | 1.30 | 33 | | | | | | |
| **T2470-1022** | 16 | 5/8 | 22 | | -1022 | 2.48 | 63 | 1.26 | 32 | | | | | | |
| **T2470-1026** | 16 | 5/8 | 26 | | -1026 | 2.66 | 68 | 1.47 | 37 | | | | | | |
| **T2470-1226** | 19 | 3/4 | 26 | | -1226 | 2.68 | 68 | 1.50 | 38 | | | | | | |
| **T2470-1230** | 19 | 3/4 | 30 | | -1230 | 2.91 | 74 | 1.73 | 44 | | | | | | |
| **T2470-1236** | 19 | 3/4 | 36 | | -1236 | 3.46 | 88 | 2.28 | 58 | | | | | | |
| **T2470-1630** | 25 | 1 | 30 | | -1630 | 3.03 | 77 | 1.81 | 46 | | | | | | |
| **T2470-1636** | 25 | 1 | 36 | | -1636 | 3.50 | 89 | 2.28 | 58 | | | | | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

### ORFS — T2840


**ORFS MALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T2840-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 1.97 | 50 | 0.98 | 25 | | | | | 5/8 | 16 |
| **T2840-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.05 | 52 | 1.06 | 27 | | | | | 3/4 | 19 |
| **T2840-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.13 | 54 | 1.14 | 29 | | | | | 3/4 | 19 |
| **T2840-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.20 | 56 | 1.22 | 31 | | | | | 7/8 | 22 |
| **T2840-0616** | 10 | 3/8 | 1" - 14 | | -0616 | 2.36 | 60 | 1.38 | 35 | | | | | 1 1/16 | 27 |
| **T2840-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.28 | 58 | 1.30 | 33 | | | | | 7/8 | 22 |
| **T2840-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.36 | 60 | 1.42 | 36 | | | | | 1.1/16 | 27 |
| **T2840-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 2.64 | 67 | 1.46 | 37 | | | | | 1.1/16 | 27 |
| **T2840-1019** | 16 | 5/8 | 1.3/16" - 12 | | -1019 | 2.68 | 68 | 1.50 | 38 | | | | | 1.1/4 | 32 |
| **T2840-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 2.72 | 69 | 1.54 | 39 | | | | | 1.1/4 | 32 |
| **T2840-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 2.72 | 69 | 1.57 | 40 | | | | | 1.1/2 | 38 |
| **T2840-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 2.83 | 72 | 1.61 | 41 | | | | | 1.1/2 | 38 |
| **T2840-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 3.74 | 95 | 1.77 | 45 | | | | | 1.3/4 | |

### ORFS — T2800


**ORFS FEMALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2800-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.17 | 55 | 1.14 | 29 | | | 11/16 | | 1/2 | |
| **T2800-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.20 | 56 | 1.22 | 31 | | | 13/16 | | 1/2 | |
| **T2800-0511** | 8 | 5/16 | 11/16" -16 | | -0511 | 2.20 | 56 | 1.18 | 30 | | | 13/16 | | 5/8 | 16 |
| **T2800-0609** | 10 | 3/8 | 9/16" - 18 | | -0609 | 2.20 | 56 | 1.22 | 31 | | | 11/16 | | 5/8 | 16 |
| **T2800-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.24 | 57 | 1.26 | 32 | | | 7/8 | 22 | 5/8 | 16 |
| **T2800-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.36 | 60 | 1.38 | 35 | | | 15/16 | 24 | 5/8 | 16 |
| **T2800-0811** | 12 | 1/2 | 11/16" -16 | | -0811 | 2.28 | 58 | 1.30 | 33 | | | 7/8 | 22 | 3/4 | 19 |
| **T2800-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.40 | 61 | 1.42 | 36 | | | 15/16 | 24 | 3/4 | 19 |
| **T2800-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.56 | 63 | 1.57 | 38 | | | 1.1/8 | | 15/16 | 19 |
| **T2800-0819** | 12 | 1/2 | 1.3/16" - 12 | | -0819 | 2.60 | 66 | 1.65 | 42 | | | 1.3/8 | 35 | 3/4 | 19 |
| **T2800-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 2.80 | 71 | 1.57 | 40 | | | 1.1/8 | | 7/8 | 22 |
| **T2800-1019** | 16 | 5/8 | 1.3/16" - 12 | | -1019 | 2.91 | 74 | 1.69 | 43 | | | 1.3/8 | 35 | 7/8 | 22 |
| **T2800-1216** | 19 | 3/4 | 1" - 14 | | -1216 | 2.68 | 71 | 1.54 | 42 | | | 1.1/8 | | 1 | 24 |
| **T2800-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 2.87 | 73 | 1.61 | 41 | | | 1.3/8 | 35 | 15/16 | 24 |
| **T2800-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 2.99 | 74 | 1.85 | 45 | | | 1.5/8 | 41 | 1.1/16 | 24 |
| **T2800-1619** | 25 | 1 | 1.3/16" - 12 | | -1619 | 3.07 | 78 | 1.85 | 45 | | | 1.3/8 | 35 | 1.1/4 | 32 |
| **T2800-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 3.07 | 78 | 1.89 | 42 | | | 1.5/8 | 41 | 1.1/4 | 32 |
| **T2800-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 4.13 | 105 | 2.17 | 55 | | | 2 | 50 | 1.5/8 | 41 |
| **T2800-2432** | 38 | 1.1/2 | 2" - 12 | | -2432 | 4.33 | 110 | 2.32 | 59 | | | 2.1/4 | 57 | 2 | 50 |

## ORFS — T2801


**ORFS FEMALE**
**(ROUND BAR)**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2801-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.17 | 55 | 1.14 | 29 | | | | 17 | 1/2 | |
| **T2801-0411** | 6 | 1/4 | 11/16" - 16 | | -0411 | 2.20 | 56 | 1.22 | 31 | | | 7/8 | 22 | 1/2 | |
| **T2801-0511** | 8 | 5/16 | 11/16" - 16 | | -0511 | 2.24 | 57 | 1.26 | 32 | | | 7/8 | 22 | 9/16 | |
| **T2801-0609** | 10 | 3/8 | 9/16" - 18 | | -0609 | 2.20 | 56 | 1.22 | 31 | | | | 17 | 5/8 | 16 |
| **T2801-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.48 | 63 | 1.50 | 38 | | | 1.3/16 | 30 | 3/4 | 19 |
| **T2801-0819** | 12 | 1/2 | 1.3/16" - 12 | | -0819 | 2.60 | 66 | 1.65 | 42 | | | | 36 | 3/4 | 19 |
| **T2801-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 2.80 | 71 | 1.57 | 40 | | | 1.3/16 | 30 | 7/8 | 22 |
| **T2801-1019** | 16 | 5/8 | 1.3/16" - 12 | | -1019 | 2.91 | 74 | 1.69 | 43 | | | | 36 | 7/8 | 22 |
| **T2801-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 2.87 | 73 | 1.61 | 41 | | | | 36 | 15/16 | 24 |

## ORFS — T2813


**ORFS FEMALE**
**45° SHORT TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2813-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 0.43 | 11 | 11/16 | | | |
| **T2813-0611** | 10 | 3/8 | 11/16" - 16 | | -0611 | 2.48 | 63 | 1.50 | 38 | 0.47 | 12 | 7/8 | 22 | | |
| **T2813-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.72 | 69 | 1.73 | 44 | 0.59 | 15 | 15/16 | 24 | | |
| **T2813-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 2.99 | 76 | 1.77 | 45 | 0.63 | 16 | 1.1/8 | | | |
| **T2813-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.62 | 92 | 2.36 | 60 | 0.83 | 21 | 1.3/8 | | | |

## ORFS — T2814

**ORFS FEMALE 45°**
**SHORT TUBE BEND METRIC NUT ONLY**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2814-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 0.43 | 11 | | 17 | | |
| **T2814-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 2.99 | 76 | 1.77 | 45 | 0.63 | 16 | 1.3/16 | 30 | | |
| **T2814-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.62 | 92 | 2.36 | 60 | 0.83 | 21 | | 36 | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

| ORFS | T2810 |
|---|---|


**ORFS FEMALE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2810-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.52 | 64 | 1.54 | 39 | 0.71 | 18 | 11/16 | | | |
| **T2810-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.52 | 64 | 1.54 | 39 | 0.71 | 18 | 13/16 | | | |
| **T2810-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.76 | 70 | 1.77 | 45 | 0.79 | 20 | 7/8 | 22 | | |
| **T2810-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.56 | 65 | 1.57 | 40 | 0.67 | 17 | 15/16 | 24 | | |
| **T2810-0811** | 12 | 1/2 | 11/16" -16 | | -0811 | 3.11 | 79 | 2.13 | 54 | 0.87 | 22 | 7/8 | 22 | | |
| **T2810-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.87 | 73 | 1.93 | 49 | 0.75 | 19 | 15/16 | 24 | | |
| **T2810-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.87 | 73 | 1.89 | 48 | 0.75 | 19 | 1.1/8 | | | |
| **T2810-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 3.50 | 89 | 2.32 | 59 | 0.79 | 20 | 1.1/8 | | | |
| **T2810-1019** | 16 | 5/8 | 1.3/16" - 12 | | -1019 | 3.50 | 89 | 2.32 | 59 | 0.94 | 24 | 1.3/8 | 35 | | |
| **T2810-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 4.29 | 109 | 3.03 | 77 | 1.14 | 29 | 1.3/8 | 35 | | |
| **T2810-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 4.17 | 104 | 3.03 | 75 | 1.02 | 26 | 1.5/8 | 41 | | |
| **T2810-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 4.61 | 117 | 3.39 | 84 | 1.34 | 34 | 1.5/8 | 41 | | |
| **T2810-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 5.94 | 151 | 4.02 | 102 | 1.77 | 45 | 2 | 50 | | |

| ORFS | T2811 |
|---|---|


**ORFS FEMALE**
**45° TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2811-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.52 | 64 | 1.54 | 39 | 0.71 | 18 | | 17 | | |
| **T2811-0411** | 6 | 1/4 | 11/16" - 16 | | -0411 | 2.52 | 64 | 1.54 | 39 | 0.71 | 18 | 7/8 | 22 | | |
| **T2811-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.87 | 73 | 1.89 | 48 | 0.75 | 19 | 1.3/16 | 30 | | |
| **T2811-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 3.54 | 90 | 2.32 | 59 | 0.79 | 20 | 1.3/16 | 30 | | |
| **T2811-1019** | 16 | 5/8 | 1.3/16" - 12 | | -1019 | 3.54 | 90 | 2.32 | 59 | 0.94 | 24 | | 36 | | |
| **T2811-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 4.29 | 109 | 3.03 | 77 | 1.14 | 29 | | 36 | | |

## ORFS | T2823


**ORFS FEMALE**
**90° SHORT TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2823-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.05 | 52 | 1.06 | 27 | 0.83 | 21 | 11/16 | | | |
| **T2823-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.01 | 51 | 1.02 | 26 | 1.06 | 27 | 13/16 | | | |
| **T2823-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.24 | 57 | 1.26 | 32 | 0.94 | 24 | 7/8 | 22 | | |
| **T2823-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.36 | 60 | 1.38 | 35 | 1.14 | 29 | 15/16 | 24 | | |
| **T2823-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.68 | 68 | 1.69 | 43 | 1.18 | 30 | 15/16 | 24 | | |
| **T2823-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.60 | 66 | 1.65 | 42 | 1.38 | 35 | 1.1/8 | | | |
| **T2823-0819** | 12 | 1/2 | 1.3/16" - 12 | | -0819 | 2.64 | 67 | 1.65 | 42 | 1.89 | 48 | 1.3/8 | 35 | | |
| **T2823-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 2.76 | 70 | 1.57 | 40 | 1.26 | 32 | 1.1/8 | | | |
| **T2823-1019** | 16 | 5/8 | 1.3/16" - 12 | | -1019 | 2.99 | 76 | 1.77 | 45 | 1.89 | 48 | 1.3/8 | 35 | | |
| **T2823-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.50 | 89 | 2.24 | 57 | 1.89 | 48 | 1.3/8 | 35 | | |
| **T2823-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 3.50 | 87 | 2.32 | 57 | 2.20 | 56 | 1.5/8 | 41 | | |
| **T2823-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 4.41 | 112 | 3.19 | 79 | 2.20 | 56 | 1.5/8 | 41 | | |
| **T2823-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 5.87 | 149 | 3.94 | 100 | 2.52 | 64 | 2 | 50 | | |

## ORFS | T2824

**ORFS FEMALE**
**90° SHORT TUBE BEND**
**METRIC NUT ONLY**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2824-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.05 | 52 | 1.06 | 27 | 0.83 | 21 | | 17 | | |
| **T2824-0411** | 6 | 1/4 | 11/16" - 16 | | -0411 | 2.01 | 51 | 1.02 | 26 | 1.06 | 27 | 7/8 | 22 | | |
| **T2824-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.60 | 66 | 1.65 | 42 | 1.38 | 35 | 1.3/16 | 30 | | |
| **T2824-0819** | 12 | 1/2 | 1.3/16" - 12 | | -0819 | 2.64 | 67 | 1.65 | 42 | 1.89 | 48 | | 36 | | |
| **T2824-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 2.99 | 76 | 1.77 | 45 | 1.26 | 32 | 1.3/16 | 30 | | |
| **T2824-1019** | 16 | 5/8 | 1.3/16" - 12 | | -1019 | 2.99 | 76 | 1.77 | 45 | 1.89 | 48 | | 36 | | |
| **T2824-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.50 | 89 | 2.24 | 57 | 1.89 | 48 | | 36 | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

| ORFS | T2820 |
|---|---|


**ORFS FEMALE**
**90° MEDIUM TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2820-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 1.26 | 32 | 11/16 | | | |
| **T2820-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.28 | 58 | 1.30 | 33 | 1.50 | 38 | 13/16 | | | |
| **T2820-0511** | 8 | 5/16 | 11/16" -16 | | -0511 | 2.32 | 59 | 1.34 | 34 | 1.50 | 38 | 13/16 | | | |
| **T2820-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.36 | 60 | 1.38 | 35 | 1.50 | 38 | 7/8 | 22 | | |
| **T2820-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.48 | 63 | 1.50 | 38 | 1.34 | 34 | 15/16 | 24 | | |
| **T2820-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.60 | 66 | 1.61 | 41 | 1.61 | 41 | 15/16 | 24 | | |
| **T2820-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.60 | 66 | 1.61 | 41 | 1.85 | 47 | 1.1/8 | | | |
| **T2820-0819** | 12 | 1/2 | 1.3/16" - 12 | | -0819 | 2.60 | 66 | 1.61 | 41 | 2.28 | 58 | 1.3/8 | 35 | | |
| **T2820-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 2.99 | 76 | 1.81 | 46 | 1.85 | 47 | 1.1/8 | | | |
| **T2820-1019** | 16 | 5/8 | 1.3/16" - 12 | | -1019 | 2.99 | 76 | 1.81 | 46 | 2.28 | 58 | 1.3/8 | 35 | | |
| **T2820-1213** | 19 | 3/4 | 13/16" - 16 | | -1213 | 3.35 | 83 | 2.17 | 53 | 1.61 | 41 | 15/16 | 24 | | |
| **T2820-1216** | 19 | 3/4 | 1" - 14 | | -1216 | 3.35 | 83 | 2.17 | 53 | 1.85 | 47 | 1.1/8 | | | |
| **T2820-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.50 | 89 | 2.24 | 57 | 2.32 | 59 | 1.3/8 | 35 | | |
| **T2820-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 3.50 | 87 | 2.32 | 57 | 2.09 | 53 | 1.5/8 | 41 | | |
| **T2820-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 3.94 | 100 | 2.72 | 74 | 2.80 | 71 | 1.5/8 | 41 | | |
| **T2820-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 5.87 | 149 | 3.94 | 100 | 3.54 | 90 | 2 | 50 | | |

## ORFS | T2821


**ORFS FEMALE**
**90° MEDIUM TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2821-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 1.26 | 32 | | 17 | | |
| **T2821-0411** | 6 | 1/4 | 11/16" - 16 | | -0411 | 2.28 | 58 | 1.30 | 33 | 1.50 | 38 | 7/8 | 22 | | |
| **T2821-0511** | 8 | 5/16 | 11/16" - 16 | | -0511 | 2.32 | 59 | 1.34 | 34 | 1.50 | 38 | 7/8 | 22 | | |
| **T2821-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.60 | 66 | 1.61 | 41 | 1.85 | 47 | 1.3/16 | 30 | | |
| **T2821-0819** | 12 | 1/2 | 1.3/16" - 12 | | -0819 | 2.60 | 66 | 1.61 | 41 | 2.28 | 58 | | 36 | | |
| **T2821-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 2.99 | 76 | 1.77 | 45 | 1.85 | 47 | 1.3/16 | 30 | | |
| **T2821-1019** | 16 | 5/8 | 1.3/16" - 12 | | -1019 | 2.99 | 76 | 1.77 | 45 | 2.28 | 58 | | 36 | | |
| **T2821-1216** | 19 | 3/4 | 1" - 14 | | -1216 | 3.35 | 83 | 2.17 | 53 | 1.85 | 47 | 1.3/16 | 30 | | |
| **T2821-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.50 | 89 | 2.24 | 57 | 2.32 | 59 | | 36 | | |

## ORFS | T2830

**ORFS FEMALE**
**90° LONG TUBE BEND**





| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2830-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 1.85 | 47 | 11/16 | | | |
| **T2830-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.09 | 53 | 1.10 | 28 | 2.13 | 54 | 13/16 | | | |
| **T2830-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.36 | 60 | 1.38 | 35 | 2.17 | 55 | 7/8 | 22 | | |
| **T2830-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.36 | 60 | 1.38 | 35 | 2.52 | 64 | 15/16 | 24 | | |
| **T2830-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.68 | 68 | 1.69 | 43 | 2.56 | 65 | 15/16 | 24 | | |
| **T2830-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.80 | 71 | 1.81 | 46 | 2.76 | 70 | 1.1/8 | | | |
| **T2830-0819** | 12 | 1/2 | 1.3/16" - 12 | | -0819 | 2.64 | 67 | 1.69 | 43 | 3.78 | 96 | 1.3/8 | 35 | | |
| **T2830-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 3.23 | 82 | 2.01 | 51 | 2.76 | 70 | 1.1/8 | | | |
| **T2830-1019** | 16 | 5/8 | 1.3/16" - 12 | | -1019 | 3.23 | 82 | 2.01 | 51 | 3.78 | 96 | 1.3/8 | 35 | | |
| **T2830-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.50 | 89 | 2.24 | 57 | 3.78 | 96 | 1.3/8 | 35 | | |
| **T2830-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 3.50 | 87 | 2.32 | 57 | 4.49 | 114 | 1.5/8 | 41 | | |
| **T2830-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 4.13 | 105 | 2.91 | 74 | 4.45 | 113 | 1.5/8 | 41 | | |
| **T2830-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 5.87 | 149 | 3.94 | 100 | 5.08 | 129 | 2 | 50 | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

## ORFS — T2831


**ORFS FEMALE**
**90° LONG TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T2831-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 1.85 | 47 | | 17 | | |
| **T2831-0411** | 6 | 1/4 | 11/16" - 16 | | -0411 | 2.28 | 58 | 1.30 | 33 | 2.13 | 54 | 7/8 | 22 | | |
| **T2831-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.80 | 71 | 1.81 | 46 | 2.76 | 70 | 1.3/16 | 30 | | |
| **T2831-0819** | 12 | 1/2 | 1.3/16" - 12 | | -0819 | 2.64 | 67 | 1.69 | 43 | 3.78 | 96 | | 36 | | |
| **T2831-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 3.23 | 82 | 2.01 | 51 | 2.76 | 70 | 1.3/16 | 30 | | |
| **T2831-1019** | 16 | 5/8 | 1.3/16" - 12 | | -1019 | 3.23 | 82 | 2.01 | 51 | 3.78 | 96 | | 36 | | |
| **T2831-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.50 | 89 | 2.24 | 57 | 3.78 | 96 | | 36 | | |

## PW — T2940


**PW FEMALE**
**PRESSURE WASHER**
**SUITS KARCHER STYLE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | | |
| **T2940-0422** | 6 | 1/4 | M22 X 1,5 | | -0422 | 2.17 | 55 | 1.18 | 30 | | | | | | |
| **T2940-0522** | 8 | 5/16 | M22 X 1,5 | | -0522 | 2.17 | 55 | 1.18 | 30 | | | | | | |
| **T2940-0622** | 10 | 3/8 | M22 X 1,5 | | -0622 | 2.17 | 55 | 1.18 | 30 | | | | | | |

## PW — T2950


**PW GUN HANDLE TUBE**
**PRESSURE WASHER**
**SUITS KARCHER STYLE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | | | |
| **T2950-0410** | 6 | 1/4 | | 9,8 | -0410 | 2.56 | 65 | 1.54 | 39 | | | | | | |
| **T2950-0510** | 8 | 5/16 | | 9,8 | -0510 | 2.56 | 65 | 1.57 | 40 | | | | | | |

## RYCOLOK — T2870


**RYCOLOK MALE**
**STAPLE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | mm | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2870-0406** | 6 | 1/4 | - | 6 | -0406 | 2.52 | 64 | 1.54 | 39 | | | | | | |
| **T2870-0410** | 6 | 1/4 | - | 10 | -0410 | 2.56 | 65 | 1.57 | 40 | | | | | | |
| **T2870-0610** | 10 | 3/8 | - | 10 | -0610 | 2.48 | 63 | 1.50 | 38 | | | | | | |
| **T2870-0812** | 12 | 1/2 | - | 12 | -0812 | 2.56 | 65 | 1.61 | 41 | | | | | | |
| **T2870-0816** | 12 | 1/2 | - | 16 | -0816 | 2.56 | 65 | 1.61 | 41 | | | | | | |
| **T2870-1012** | 16 | 5/8 | - | 12 | -1012 | 2.80 | 71 | 1.57 | 40 | | | | | | |
| **T2870-1016** | 16 | 5/8 | - | 16 | -1016 | 2.72 | 69 | 1.54 | 39 | | | | | | |
| **T2870-1220** | 19 | 3/4 | - | 20 | -1220 | 2.72 | 69 | 1.54 | 39 | | | | | | |
| **T2870-1625** | 25 | 1 | - | 25 | -1625 | 3.19 | 81 | 1.97 | 50 | | | | | | |
| **T2870-2032** | 31 | 1.1/4 | - | 32 | -2032 | 3.94 | 100 | 1.97 | 50 | | | | | | |
| **T2870-2440** | 38 | 1.1/2 | - | 40 | -2440 | 4.37 | 111 | 2.36 | 60 | | | | | | |
| **T2870-3250** | 51 | 2 | - | 50 | -3250 | 4.49 | 114 | 2.28 | 58 | | | | | | |
| **T2870-4063** | 63 | 2.1/2 | - | 63 | -4063 | 6.57 | 167 | 3.54 | 90 | | | | | | |
| **T2870-4875** | 76 | 3 | - | 75 | -4875 | 7.99 | 203 | 5.00 | 127 | | | | | | |

## RYCOLOK — T2871

**RYCOLOK MALE**
**45° ELBOW**
**STAPLE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | inch | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2871-0406** | 6 | 1/4 | - | 6 | -0406 | 2.76 | 70 | 1.73 | 44 | 1.06 | 27 | | | | |
| **T2871-0410** | 6 | 1/4 | - | 10 | -0410 | 2.87 | 73 | 1.89 | 48 | 1.06 | 27 | | | | |
| **T2871-0610** | 10 | 3/8 | - | 10 | -0610 | 2.72 | 69 | 1.77 | 45 | 1.06 | 27 | | | 7/8 | 22 |
| **T2871-0812** | 12 | 1/2 | - | 12 | -0812 | 2.99 | 76 | 2.02 | 51 | 1.06 | 27 | | | | |
| **T2871-1220** | 19 | 3/4 | - | 20 | -1220 | 3.21 | 82 | 2.05 | 52 | 1.27 | 32 | | | | |
| **T2871-1625** | 25 | 1 | - | 25 | -1625 | 3.67 | 93 | 2.44 | 62 | 1.26 | 32 | | | | |
| **T2871-2032** | 31 | 1.1/4 | - | 32 | -2032 | 4.49 | 114 | 2.52 | 64 | 1.43 | 36 | | | | |
| **T2871-2440** | 38 | 1.1/2 | - | 40 | -2440 | 5.28 | 134 | 3.23 | 82 | 1.73 | 44 | | | 0 | |
| **T2871-3250** | 51 | 2 | - | 50 | -3250 | 5.63 | 143 | 3.43 | 87 | 1.81 | 46 | | | 0 | |
| **T2871-4063** | 63 | 2.1/2 | - | 63 | -4063 | 7.52 | 191 | 4.49 | 114 | 2.87 | 73 | | | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

### RYCOLOK — T2872


**RYCOLOK MALE**
**90° ELBOW**
**STAPLE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | mm | | inch | mm | inch | mm | inch | mm | | | inch | mm |
| **T2872-0406** | 6 | 1/4 | | 6 | -0406 | 1.85 | 47 | 0.83 | 21 | 1.81 | 46 | | | 3/4 | 19 |
| **T2872-0410** | 6 | 1/4 | | 10 | -0410 | 1.89 | 48 | 0.87 | 22 | 1.81 | 46 | | | 7/8 | 22 |
| **T2872-0610** | 10 | 3/8 | | 10 | -0610 | 1.89 | 48 | 0.91 | 23 | 1.81 | 46 | | | 7/8 | 22 |
| **T2872-0812** | 12 | 1/2 | | 12 | -0812 | 2.13 | 54 | 1.15 | 29 | 1.99 | 51 | | | | |
| **T2872-1016** | 16 | 5/8 | | 16 | -1016 | 2.28 | 58 | 1.11 | 28 | 2.07 | 53 | | | | |
| **T2872-1220** | 19 | 3/4 | | 20 | -1220 | 2.36 | 60 | 1.19 | 30 | 2.19 | 56 | | | | |
| **T2872-1625** | 25 | 1 | | 25 | -1625 | 2.81 | 71 | 1.60 | 41 | 2.68 | 68 | | | | |
| **T2872-2032** | 31 | 1.1/4 | | 32 | -2032 | 3.65 | 93 | 1.68 | 43 | 2.68 | 68 | | | | |
| **T2872-2440** | 38 | 1.1/2 | | 40 | -2440 | 4.45 | 113 | 2.40 | 61 | 3.35 | 85 | | | | |
| **T2872-3250** | 51 | 2 | | 50 | -3250 | 4.80 | 122 | 2.60 | 66 | 3.94 | 100 | | | | |
| **T2872-4063** | 63 | 2.1/2 | | 63 | -4063 | 6.18 | 157 | 3.15 | 80 | 5.51 | 140 | | | | |

### RYCO WEO — T2480


**RYCO WEO MALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | | | |
| **T2480-0304** | 5 | 3/16 | | 1/4 | -0304 | 1.97 | 50 | 1.22 | 31 | | | | | | |
| **T2480-0404** | 6 | 1/4 | | 1/4 | -0404 | 2.20 | 56 | 1.22 | 31 | | | | | | |
| **T2480-0406** | 6 | 1/4 | | 3/8 | -0406 | 2.36 | 60 | 1.38 | 35 | | | | | | |
| **T2480-0506** | 8 | 5/16 | | 3/8 | -0506 | 2.36 | 60 | 1.38 | 35 | | | | | | |
| **T2480-0606** | 10 | 3/8 | | 3/8 | -0606 | 2.36 | 60 | 1.38 | 35 | | | | | | |
| **T2480-0608** | 10 | 3/8 | | 1/2 | -0608 | 2.36 | 60 | 1.38 | 35 | | | | | | |
| **T2480-0808** | 12 | 1/2 | | 1/2 | -0808 | 2.36 | 60 | 1.42 | 36 | | | | | | |
| **T2480-0812** | 12 | 1/2 | | 3/4 | -0812 | 2.80 | 71 | 1.85 | 47 | | | | | | |
| **T2480-1012** | 16 | 5/8 | | 3/4 | -1012 | 2.95 | 75 | 1.73 | 44 | | | | | | |
| **T2480-1212** | 19 | 3/4 | | 3/4 | -1212 | 2.95 | 75 | 1.77 | 45 | | | | | | |
| **T2480-1616** | 25 | 1 | | 1 | -1616 | 3.43 | 87 | 2.20 | 56 | | | | | | |

## RYCO WEO — T2482


**RYCO WEO MALE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | inch | mm | | | | |
| **T2482-0404** | 6 | 1/4 | | 1/4 | -0404 | 2.72 | 69 | 1.73 | 44 | 0.98 | 25 | | | | |
| **T2482-0506** | 8 | 5/16 | | 3/8 | -0506 | 3.11 | 79 | 2.13 | 54 | 1.06 | 27 | | | | |
| **T2482-0606** | 10 | 3/8 | | 3/8 | -0606 | 3.15 | 80 | 2.17 | 55 | 1.06 | 27 | | | | |
| **T2482-0808** | 12 | 1/2 | | 1/2 | -0808 | 3.31 | 84 | 2.32 | 59 | 1.22 | 31 | | | | |
| **T2482-1012** | 16 | 5/8 | | 3/4 | -1012 | 4.02 | 102 | 2.83 | 72 | 1.57 | 40 | | | | |
| **T2482-1212** | 19 | 3/4 | | 3/4 | -1212 | 4.41 | 112 | 3.23 | 82 | 1.69 | 43 | | | | |
| **T2482-1616** | 25 | 1 | | 1 | -1616 | 5.35 | 136 | 4.13 | 105 | 2.09 | 53 | | | | |

## RYCO WEO — T2483

**RYCO WEO MALE**
**90° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | inch | mm | | | | |
| **T2483-0404** | 6 | 1/4 | | 1/4 | -0404 | 2.13 | 54 | 1.14 | 29 | 1.57 | 40 | | | | |
| **T2483-0506** | 8 | 5/16 | | 3/8 | -0506 | 2.36 | 60 | 1.38 | 35 | 2.05 | 52 | | | | |
| **T2483-0606** | 10 | 3/8 | | 3/8 | -0606 | 2.36 | 60 | 1.38 | 35 | 2.05 | 52 | | | | |
| **T2483-0608** | 10 | 3/8 | | 1/2 | -0608 | 2.40 | 61 | 1.42 | 36 | 1.85 | 47 | | | | |
| **T2483-0808** | 12 | 1/2 | | 1/2 | -0808 | 2.48 | 63 | 1.50 | 38 | 2.28 | 58 | | | | |
| **T2483-1012** | 16 | 5/8 | | 3/4 | -1012 | 3.31 | 84 | 2.13 | 54 | 3.23 | 82 | | | | |
| **T2483-1212** | 19 | 3/4 | | 3/4 | -1212 | 3.31 | 84 | 2.13 | 54 | 3.23 | 82 | | | | |
| **T2483-1616** | 25 | 1 | | 1 | -1616 | 4.06 | 103 | 2.83 | 72 | 3.82 | 97 | | | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

### SAE — T2530


**SAE MALE**
**45° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T2530-0410** | 6 | 1/4 | 5/8" -18 | | -0410 | 2.20 | 56 | 1.22 | 31 | | | | | 11/16 | |
| **T2530-0608** | 10 | 3/8 | 1/2" -20 | | -0608 | 2.24 | 57 | 1.26 | 32 | | | | | 5/8 | 16 |
| **T2530-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 2.32 | 59 | 1.34 | 34 | | | | | 3/4 | 19 |

### SAE — T2540


**SAE FEMALE**
**45° FLARE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2540-0407** | 6 | 1/4 | 7/16" - 20 | | -0407 | 1.77 | 45 | 0.75 | 19 | | | 9/16 | | 1/2 | |
| **T2540-0410** | 6 | 1/4 | 5/8" -18 | | -0410 | 1.89 | 48 | 0.91 | 23 | | | 3/4 | 19 | 5/8 | 16 |
| **T2540-0608** | 10 | 3/8 | 1/2" -20 | | -0608 | 1.77 | 45 | 0.79 | 20 | | | 5/8 | 16 | 5/8 | 16 |
| **T2540-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 1.89 | 48 | 0.91 | 23 | | | 3/4 | 19 | 5/8 | 16 |
| **T2540-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.20 | 56 | 1.06 | 27 | | | 1.1/4 | 32 | 1 | |

## SAE — T2580


SAE FEMALE
45° FLARE
45° ELBOW




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2580-0608** | 10 | 3/8 | 1/2" -20 | | -0608 | 2.20 | 56 | 1.26 | 32 | 0.55 | 14 | 5/8 | 16 | 3/4 | 19 |
| **T2580-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 2.24 | 57 | 1.26 | 32 | 0.59 | 15 | 3/4 | 19 | 3/4 | 19 |

## SAE — T2570


SAE
FEMALE
45° FLARE
90° ELBOW




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2570-0608** | 10 | 3/8 | 1/2" -20 | | -0608 | 1.89 | 48 | 0.91 | 23 | 0.87 | 22 | 5/8 | 16 | 3/4 | 19 |
| **T2570-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 1.89 | 48 | 0.91 | 23 | 0.91 | 23 | 3/4 | 19 | 3/4 | 19 |

## SAE — T2740

SAE INVERTED MALE FLARE





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | inch | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2740-0407** | 6 | 1/4 | 7/16" - 20 | 1/4 | -0407 | 2.60 | 66 | 1.57 | 40 | | | 7/16 | 11 | 1/2 | |
| **T2740-0610** | 10 | 3/8 | 5/8" -18 | 3/8 | -0610 | 2.60 | 66 | 1.61 | 41 | | | 5/8 | 16 | 5/8 | 16 |
| **T2740-0611** | 10 | 3/8 | 11/16" -16 | 7/16 | -0611 | 2.68 | 68 | 1.73 | 44 | | | 11/16 | | 5/8 | 16 |
| **T2750-0610** | 10 | 3/8 | 5/8" -18 | 3/8 | -0610 | 3.86 | 98 | 2.87 | 73 | 0.91 | 23 | 5/8 | 16 | 5/8 | 16 |
| **T2760-0407** | 6 | 1/4 | 7/16" - 20 | 1/4 | -0407 | 3.46 | 88 | 2.48 | 63 | 1.14 | 29 | 7/16 | 11 | 1/2 | |
| **T2770-0407** | 6 | 1/4 | 7/16" - 20 | 1/4 | -0407 | 2.72 | 69 | 1.73 | 44 | 1.50 | 38 | 7/16 | 11 | 1/2 | |
| **T2770-0610** | 10 | 3/8 | 5/8" -18 | 3/8 | -0610 | 3.15 | 80 | 2.17 | 55 | 1.97 | 50 | 5/8 | 16 | 5/8 | 16 |
| **T2780-0610** | 10 | 3/8 | 5/8" -18 | 3/8 | -0610 | 1.89 | 48 | 0.91 | 23 | 1.26 | 32 | 5/8 | 16 | 3/4 | 19 |
| **T2780-0611** | 10 | 3/8 | 11/16" -16 | 7/16 | -0611 | 1.69 | 43 | 0.71 | 18 | 1.42 | 36 | 11/16 | | 3/4 | 19 |
| **T2790-0610** | 10 | 3/8 | 5/8" -18 | 3/8 | -0610 | 1.69 | 43 | 0.71 | 18 | 2.36 | 60 | 5/8 | 16 | 3/4 | 19 |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

## SAE — T2780


**SAE INVERTED MALE FLARE**
**90° ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | inch | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2780-0610** | 10 | 3/8 | 5/8" -18 | 3/8 | -0610 | 1.89 | 48 | 0.91 | 23 | 1.26 | 32 | 5/8 | 16 | 3/4 | 19 |
| **T2780-0611** | 10 | 3/8 | 11/16" -16 | 7/16 | -0611 | 1.69 | 43 | 0.71 | 18 | 1.42 | 36 | 11/16 | | 3/4 | 19 |

## SAE — T2790


**SAE INVERTED MALE FLARE**
**90° LONG ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | inch | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2790-0610** | 10 | 3/8 | 5/8" -18 | 3/8 | -0610 | 1.69 | 43 | 0.71 | 18 | 2.36 | 60 | 5/8 | 16 | 3/4 | 19 |

## SAE — T2750


**SAE INVERTED MALE FLARE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | inch | | inch | mm | inch | mm | inch | mm | | | inch | mm |
| **T2750-0610** | 10 | 3/8 | 5/8" -18 | 3/8 | -0610 | 3.86 | 98 | 2.87 | 73 | 0.91 | 23 | | | 5/8 | 16 |

## SAE — T2760


**SAE INVERTED MALE FLARE**
**60° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | inch | | inch | mm | inch | mm | inch | mm | | | inch | mm |
| **T2760-0407** | 6 | 1/4 | 7/16" - 20 | 1/4 | -0407 | 3.46 | 88 | 2.48 | 63 | 1.14 | 29 | | | 1/2 | |

## SAE — T2770

**SAE INVERTED MALE FLARE**
**90° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | inch | | inch | mm | inch | mm | inch | mm | | | inch | mm |
| **T2770-0407** | 6 | 1/4 | 7/16" - 20 | 1/4 | -0407 | 2.72 | 69 | 1.73 | 44 | 1.50 | 38 | | | 1/2 | |
| **T2770-0610** | 10 | 3/8 | 5/8" -18 | 3/8 | -0610 | 3.15 | 80 | 2.17 | 55 | 1.97 | 50 | | | 5/8 | 16 |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

### DIMENSIONS FOR SAE CODE 61 AND CODE 62 FLANGES, AND RYCO CODE 62C FLANGES

| NOMINAL FLANGE | CODE 61 | | | | CODE 62 | | | | CODE 62C | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | B | | T | | B | | T | | B | | T | |
| inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch |
| 1/2 | 30,2 | 1.19 | 6,73 | 0.265 | 31,8 | 1.25 | 7,75 | 0.305 | | | | |
| 5/8 | 34,0 | 1.34 | 6,73 | 0.265 | | | | | | | | |
| 3/4 | 38,1 | 1.50 | 6,73 | 0.265 | 41,3 | 1.63 | 8,76 | 0.345 | 41,3 | 1.63 | 14,20 | 0.559 |
| 1 | 44,5 | 1.75 | 8,00 | 0.315 | 47,6 | 1.88 | 9,53 | 0.375 | 47,6 | 1.88 | 14,20 | 0.559 |
| 1.1/4 | 50,8 | 2.00 | 8,00 | 0.315 | 54,0 | 2.12 | 10,29 | 0.405 | 54,0 | 2.12 | 14,20 | 0.559 |
| 1.1/2 | 60,3 | 2.38 | 8,00 | 0.315 | 63,5 | 2.50 | 12,57 | 0.495 | 63,5 | 2.50 | 14,20 | 0.559 |
| 2 | 71,4 | 2.81 | 9,53 | 0.375 | 79,4 | 3.13 | 12,57 | 0.495 | 79,4 | 3.13 | 14,20 | 0.559 |
| 2.1/2 | 84,1 | 3.31 | 9,53 | 0.375 | | | | | | | | |
| 3 | 101,6 | 4.00 | 9,53 | 0.375 | | | | | | | | |





**NOTE:** Ryco Code 62C fittings conform to the flange OD and bolt hole patterns of SAE Code 62 but require special flange clamps.
Ryco Code 62C flange heads are thicker than SAE Code 62 and measure T = 14,2 mm (0.559 inch) in all sizes.

## SAE FLANGE — T2130

### SAE CODE 61 FLANGE

RYCO CODE 61 CLAMPS
SEE PAGES 442 & 443
O RING NOT SUPPLIED





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | |
| **T2130-0808** | 12 | 1/2 | | | -0808 | 2.72 | 69 | 1.77 | 45 | | | | | | |
| **T2130-0812** | 12 | 1/2 | | | -0812 | 2.83 | 72 | 1.89 | 48 | | | | | | |
| **T2130-1010** | 16 | 5/8 | | | -1010 | 2.95 | 75 | 1.73 | 44 | | | | | | |
| **T2130-1210** | 19 | 3/4 | | | -1210 | 2.95 | 75 | 1.77 | 45 | | | | | | |
| **T2130-1212** | 19 | 3/4 | | | -1212 | 2.99 | 76 | 1.81 | 46 | | | | | | |
| **T2130-1216** | 19 | 3/4 | | | -1216 | 3.15 | 80 | 1.97 | 50 | | | | | | |
| **T2130-1612** | 25 | 1 | | | -1612 | 3.11 | 79 | 1.89 | 48 | | | | | | |
| **T2130-1616** | 25 | 1 | | | -1616 | 3.27 | 83 | 2.05 | 52 | | | | | | |
| **T2130-1620** | 25 | 1 | | | -1620 | 3.46 | 88 | 2.24 | 57 | | | | | | |
| **T2130-1624** | 25 | 1 | | | -1624 | 4.53 | 115 | 3.31 | 84 | | | | | | |
| **T2130-2016** | 31 | 1.1/4 | | | -2016 | 4.09 | 104 | 2.13 | 54 | | | | | | |
| **T2130-2020** | 31 | 1.1/4 | | | -2020 | 4.29 | 109 | 2.32 | 59 | | | | | | |
| **T2130-2024** | 31 | 1.1/4 | | | -2024 | 5.28 | 134 | 3.35 | 85 | | | | | | |
| **T2130-2424** | 38 | 1.1/2 | | | -2424 | 5.39 | 137 | 3.39 | 86 | | | | | | |
| **T2130-2432** | 38 | 1.1/2 | | | -2432 | 5.79 | 147 | 3.78 | 96 | | | | | | |
| **T2130-3232** | 51 | 2 | | | -3232 | 5.98 | 152 | 3.78 | 96 | | | | | | |
| **T2130-3240** | 51 | 2 | | | -3240 | 6.18 | 157 | 3.98 | 101 | | | | | | |
| **T2130-4040** | 63 | 2.1/2 | | | -4040 | 6.14 | 156 | 3.11 | 79 | | | | | | |
| **T2130-4848** | 76 | 3 | | | -4848 | 6.14 | 156 | 3.15 | 80 | | | | | | |

# SAE FLANGE

# T2150

**SAE CODE 61 FLANGE**
**45° TUBE BEND**

RYCO CODE 61 CLAMPS
SEE PAGES 442 & 443
O RING NOT SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T2150-0808** | 12 | 1/2 | | | -0808 | 2.91 | 74 | 1.93 | 49 | 0.79 | 20 | | | | |
| **T2150-0812** | 12 | 1/2 | | | -0812 | 2.95 | 75 | 2.01 | 51 | 0.94 | 24 | | | | |
| **T2150-1010** | 16 | 5/8 | | | -1010 | 3.39 | 86 | 2.20 | 56 | 0.94 | 24 | | | | |
| **T2150-1210** | 19 | 3/4 | | | -1210 | 3.50 | 89 | 2.32 | 59 | 1.02 | 26 | | | | |
| **T2150-1212** | 19 | 3/4 | | | -1212 | 3.74 | 95 | 2.56 | 65 | 1.02 | 26 | | | | |
| **T2150-1216** | 19 | 3/4 | | | -1216 | 3.86 | 98 | 2.68 | 68 | 1.18 | 30 | | | | |
| **T2150-1612** | 25 | 1 | | | -1612 | 2.68 | 68 | 1.46 | 37 | 1.02 | 26 | | | | |
| **T2150-1616** | 25 | 1 | | | -1616 | 4.41 | 112 | 3.19 | 81 | 1.18 | 30 | | | | |
| **T2150-1620** | 25 | 1 | | | -1620 | 4.49 | 114 | 3.27 | 83 | 1.26 | 32 | | | | |
| **T2150-1624** | 25 | 1 | | | -1624 | 4.49 | 114 | 3.27 | 83 | 1.57 | 40 | | | | |
| **T2150-2016** | 31 | 1.1/4 | | | -2016 | 5.43 | 138 | 3.46 | 88 | 1.18 | 30 | | | | |
| **T2150-2020** | 31 | 1.1/4 | | | -2020 | 5.91 | 150 | 3.94 | 100 | 1.42 | 36 | | | | |
| **T2150-2024** | 31 | 1.1/4 | | | -2024 | 6.02 | 153 | 4.06 | 103 | 1.57 | 40 | | | | |
| **T2150-2424** | 38 | 1.1/2 | | | -2424 | 6.38 | 162 | 4.33 | 110 | 1.65 | 42 | | | | |
| **T2150-3232** | 51 | 2 | | | -3232 | 8.11 | 206 | 5.91 | 150 | 2.28 | 58 | | | | |


# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

## SAE FLANGE — T2170

**SAE CODE 61 FLANGE**
**90° TUBE BEND**


RYCO CODE 61 CLAMPS
SEE PAGES 442 & 443
O RING NOT SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T2170-0808** | 12 | 1/2 | | | -0808 | 2.56 | 65 | 1.57 | 40 | 1.61 | 41 | | | | |
| **T2170-0812** | 12 | 1/2 | | | -0812 | 2.56 | 65 | 1.57 | 40 | 1.81 | 46 | | | | |
| **T2170-1010** | 16 | 5/8 | | | -1010 | 3.07 | 78 | 1.89 | 48 | 1.89 | 48 | | | | |
| **T2170-1212** | 19 | 3/4 | | | -1212 | 3.35 | 85 | 2.17 | 55 | 2.13 | 54 | | | | |
| **T2170-1216** | 19 | 3/4 | | | -1216 | 3.35 | 85 | 2.17 | 55 | 2.36 | 60 | | | | |
| **T2170-1612** | 25 | 1 | | | -1612 | 3.54 | 90 | 2.36 | 60 | 2.13 | 54 | | | | |
| **T2170-1616** | 25 | 1 | | | -1616 | 3.90 | 99 | 2.68 | 68 | 2.68 | 68 | | | | |
| **T2170-1620** | 25 | 1 | | | -1620 | 3.98 | 101 | 2.76 | 70 | 2.72 | 69 | | | | |
| **T2170-2016** | 31 | 1.1/4 | | | -2016 | 5.04 | 128 | 3.07 | 78 | 2.68 | 68 | | | | |
| **T2170-2020** | 31 | 1.1/4 | | | -2020 | 5.12 | 130 | 3.15 | 80 | 3.07 | 78 | | | | |
| **T2170-2024** | 31 | 1.1/4 | | | -2024 | 5.51 | 140 | 3.54 | 90 | 3.19 | 81 | | | | |
| **T2170-2424** | 38 | 1.1/2 | | | -2424 | 6.14 | 156 | 4.09 | 104 | 3.66 | 93 | | | | |
| **T2170-3232** | 51 | 2 | | | -3232 | 7.60 | 193 | 5.39 | 137 | 5.12 | 130 | | | | |
| **T2170-3240** | 51 | 2 | | | -3240 | 7.76 | 197 | 5.55 | 141 | 5.28 | 134 | | | | |

## SALVAGE — T2230


**SALVAGE (LIFESAVER)**
**TUBE WELD**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | A | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | | inch | mm |
| **T2230-0404** | 6 | 1/4 | | 1/4 | -0404 | 1.73 | 44 | 0.71 | 18 | | | | | 1/2 | |
| **T2230-0405** | 6 | 1/4 | | 5/16 | -0405 | 1.73 | 44 | 0.71 | 18 | | | | | 1/2 | |
| **T2230-0406** | 6 | 1/4 | | 3/8 | -0406 | 1.73 | 44 | 0.71 | 18 | | | | | 9/16 | |
| **T2230-0505** | 8 | 5/16 | | 5/16 | -0505 | 1.69 | 43 | 0.71 | 18 | | | | | 9/16 | |
| **T2230-0606** | 10 | 3/8 | | 3/8 | -0606 | 1.69 | 43 | 0.71 | 18 | | | | | 5/8 | 16 |
| **T2230-0608** | 10 | 3/8 | | 1/2 | -0608 | 1.69 | 43 | 0.71 | 18 | | | | | 11/16 | |
| **T2230-0808** | 12 | 1/2 | | 1/2 | -0808 | 1.73 | 44 | 0.75 | 19 | | | | | 11/16 | |
| **T2230-0810** | 12 | 1/2 | | 5/8 | -0810 | 1.77 | 45 | 0.83 | 21 | | | | | 7/8 | 22 |
| **T2230-1010** | 16 | 5/8 | | 5/8 | -1010 | 2.01 | 51 | 0.79 | 20 | | | | | 1 | |
| **T2230-1012** | 16 | 5/8 | | 3/4 | -1012 | 2.01 | 51 | 0.79 | 20 | | | | | 1.1/16 | 27 |
| **T2230-1212** | 19 | 3/4 | | 3/4 | -1212 | 2.01 | 51 | 0.83 | 21 | | | | | 1 | |
| **T2230-1616** | 25 | 1 | | 1 | -1616 | 2.28 | 58 | 1.10 | 28 | | | | | 1.3/8 | 35 |
| **T2230-2020** | 31 | 1.1/4 | | 1.1/4 | -2020 | 3.19 | 81 | 1.22 | 31 | | | | | 1.3/4 | |
| **T2230-2424** | 38 | 1.1/2 | | 1.1/2 | -2424 | 3.39 | 86 | 1.34 | 34 | | | | | 2 | 50 |
| **T2230-3232** | 51 | 2 | | 2 | -3232 | 3.86 | 98 | 1.61 | 41 | | | | | 2.1/2 | |

# STANDPIPE

# T2180





## IMPERIAL STANDPIPE

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2180-0406** | 6 | 1/4 | | 3/8 | -0406 | 2.24 | 57 | 1.26 | 32 | | | | | | |
| **T2180-0606** | 10 | 3/8 | | 3/8 | -0606 | 2.24 | 57 | 1.26 | 32 | | | | | | |
| **T2180-0808** | 12 | 1/2 | | 1/2 | -0808 | 2.24 | 57 | 1.30 | 33 | | | | | | |
| **T2180-0810** | 12 | 1/2 | | 5/8 | -0810 | 2.52 | 64 | 1.57 | 40 | | | | | | |
| **T2180-1212** | 19 | 3/4 | | 3/4 | -1212 | 2.99 | 76 | 1.81 | 46 | | | | | | |
| **T2180-1616** | 25 | 1 | | 1 | -1616 | 3.23 | 82 | 2.05 | 52 | | | | | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

| STANDPIPE | T2640 |
|---|---|





### METRIC STANDPIPE

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | mm | | inch | mm | inch | mm | | | | | | |
| **T2640-0306** | 5 | 3/16 | | 6 | -0306 | 1.97 | 50 | 1.22 | 31 | | | | | | |
| **T2640-0406** | 6 | 1/4 | | 6 | -0406 | 2.20 | 56 | 1.22 | 31 | | | | | | |
| **T2640-0408** | 6 | 1/4 | | 8 | -0408 | 2.20 | 56 | 1.22 | 31 | | | | | | |
| **T2640-0410** | 6 | 1/4 | | 10 | -0410 | 2.24 | 57 | 1.26 | 32 | | | | | | |
| **T2640-0412** | 6 | 1/4 | | 12 | -0412 | 2.24 | 57 | 1.26 | 32 | | | | | | |
| **T2640-0510** | 8 | 5/16 | | 10 | -0510 | 2.24 | 57 | 1.26 | 32 | | | | | | |
| **T2640-0512** | 8 | 5/16 | | 12 | -0512 | 2.24 | 57 | 1.26 | 32 | | | | | | |
| **T2640-0610** | 10 | 3/8 | | 10 | -0610 | 2.24 | 57 | 1.26 | 32 | | | | | | |
| **T2640-0612** | 10 | 3/8 | | 12 | -0612 | 2.24 | 57 | 1.26 | 32 | | | | | | |
| **T2640-0614** | 10 | 3/8 | | 14 | -0614 | 2.48 | 63 | 1.50 | 38 | | | | | | |
| **T2640-0812** | 12 | 1/2 | | 12 | -0812 | 2.24 | 57 | 1.26 | 32 | | | | | | |
| **T2640-0814** | 12 | 1/2 | | 14 | -0814 | 2.48 | 63 | 1.54 | 39 | | | | | | |
| **T2640-0815** | 12 | 1/2 | | 15 | -0815 | 2.32 | 59 | 1.38 | 35 | | | | | | |
| **T2640-0816** | 12 | 1/2 | | 16 | -0816 | 2.52 | 64 | 1.57 | 40 | | | | | | |
| **T2640-1016** | 16 | 5/8 | | 16 | -1016 | 2.72 | 69 | 1.54 | 39 | | | | | | |
| **T2640-1018** | 16 | 5/8 | | 18 | -1018 | 2.56 | 65 | 1.38 | 35 | | | | | | |
| **T2640-1020** | 16 | 5/8 | | 20 | -1020 | 2.95 | 75 | 1.77 | 45 | | | | | | |
| **T2640-1022** | 16 | 5/8 | | 22 | -1022 | 2.64 | 67 | 1.46 | 37 | | | | | | |
| **T2640-1215** | 19 | 3/4 | | 15 | -1215 | 2.56 | 65 | 1.38 | 35 | | | | | | |
| **T2640-1220** | 19 | 3/4 | | 20 | -1220 | 2.99 | 76 | 1.81 | 46 | | | | | | |
| **T2640-1222** | 19 | 3/4 | | 22 | -1222 | 2.68 | 68 | 1.50 | 38 | | | | | | |
| **T2640-1225** | 19 | 3/4 | | 25 | -1225 | 2.99 | 76 | 1.81 | 46 | | | | | | |
| **T2640-1625** | 25 | 1 | | 25 | -1625 | 3.15 | 80 | 1.93 | 49 | | | | | | |
| **T2640-1628** | 25 | 1 | | 28 | -1628 | 3.15 | 80 | 1.93 | 49 | | | | | | |
| **T2640-1630** | 25 | 1 | | 30 | -1630 | 3.46 | 88 | 2.24 | 57 | | | | | | |

## STANDPIPE — T2643


**METRIC STANDPIPE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | mm | | inch | mm | inch | mm | inch | mm | | | | |
| **T2643-0406** | 6 | 1/4 | | 6 | -0406 | 2.64 | 67 | 1.65 | 42 | 0.81 | 21 | | | | |
| **T2643-0408** | 6 | 1/4 | | 8 | -0408 | 2.68 | 68 | 1.69 | 43 | 0.87 | 22 | | | | |
| **T2643-0410** | 6 | 1/4 | | 10 | -0410 | 2.64 | 67 | 1.65 | 42 | 0.94 | 24 | | | | |
| **T2643-0610** | 10 | 3/8 | | 10 | -0610 | 2.76 | 70 | 1.77 | 45 | 0.91 | 23 | | | | |
| **T2643-0612** | 10 | 3/8 | | 12 | -0612 | 2.83 | 72 | 1.85 | 47 | 0.98 | 25 | | | | |
| **T2643-0614** | 10 | 3/8 | | 14 | -0614 | 2.99 | 76 | 2.01 | 51 | 1.14 | 29 | | | | |
| **T2643-0815** | 12 | 1/2 | | 15 | -0815 | 3.27 | 83 | 2.28 | 58 | 1.10 | 28 | | | | |
| **T2643-0816** | 12 | 1/2 | | 16 | -0816 | 3.35 | 85 | 2.36 | 60 | 1.18 | 30 | | | | |
| **T2643-1018** | 16 | 5/8 | | 18 | -1018 | 3.66 | 93 | 2.48 | 63 | 1.20 | 31 | | | | |
| **T2643-1020** | 16 | 5/8 | | 20 | -1020 | 3.86 | 98 | 2.68 | 68 | 1.42 | 36 | | | | |
| **T2643-1222** | 19 | 3/4 | | 22 | -1222 | 3.92 | 100 | 2.76 | 70 | 1.26 | 32 | | | | |
| **T2643-1225** | 19 | 3/4 | | 25 | -1225 | 4.27 | 109 | 3.11 | 79 | 1.59 | 41 | | | | |
| **T2643-1628** | 25 | 1 | | 28 | -1628 | 4.65 | 118 | 3.43 | 87 | 1.46 | 37 | | | | |

## STANDPIPE — T2646

**METRIC STANDPIPE**
**90° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | mm | | inch | mm | inch | mm | inch | mm | | | | |
| **T2646-0406** | 6 | 1/4 | | 6 | -0406 | - | - | - | - | - | - | | | | |
| **T2646-0408** | 6 | 1/4 | | 8 | -0408 | 2.05 | 52 | 1.06 | 27 | 1.50 | 38 | | | | |
| **T2646-0410** | 6 | 1/4 | | 10 | -0410 | 2.05 | 52 | 1.06 | 27 | 1.61 | 41 | | | | |
| **T2646-0412** | 6 | 1/4 | | 12 | -0412 | 2.05 | 52 | 1.06 | 27 | 1.73 | 44 | | | | |
| **T2646-0610** | 10 | 3/8 | | 10 | -0610 | 2.36 | 60 | 1.38 | 35 | 1.69 | 43 | | | | |
| **T2646-0612** | 10 | 3/8 | | 12 | -0612 | 2.36 | 60 | 1.38 | 35 | 1.77 | 45 | | | | |
| **T2646-0614** | 10 | 3/8 | | 14 | -0614 | 2.36 | 60 | 1.38 | 35 | 2.01 | 51 | | | | |
| **T2646-0812** | 12 | 1/2 | | 12 | -0812 | 2.56 | 65 | 1.57 | 40 | 1.77 | 45 | | | | |
| **T2646-0814** | 12 | 1/2 | | 14 | -0814 | 2.56 | 65 | 1.57 | 40 | 2.01 | 51 | | | | |
| **T2646-0816** | 16 | 5/8 | | 16 | -0816 | 2.56 | 65 | 1.57 | 40 | 2.17 | 55 | | | | |
| **T2646-1018** | 16 | 5/8 | | 18 | -1018 | 3.07 | 78 | 1.89 | 48 | 2.32 | 59 | | | | |
| **T2646-1022** | 16 | 5/8 | | 22 | -1022 | 2.68 | 68 | 1.89 | 48 | 2.48 | 63 | | | | |
| **T2646-1220** | 19 | 3/4 | | 20 | -1220 | 3.35 | 85 | 2.17 | 55 | 2.72 | 69 | | | | |
| **T2646-1222** | 19 | 3/4 | | 22 | -1222 | 3.35 | 85 | 2.17 | 55 | 2.48 | 63 | | | | |
| **T2646-1225** | 19 | 3/4 | | 25 | -1225 | 3.35 | 85 | 2.17 | 55 | 2.95 | 75 | | | | |
| **T2646-1625** | 25 | 1 | | 25 | -1625 | 4.06 | 103 | 2.83 | 72 | 3.03 | 77 | | | | |
| **T2646-1630** | 25 | 1 | | 30 | -1630 | 4.06 | 103 | 2.83 | 72 | 2.64 | 67 | | | | |

# ONE-PIECE COUPLINGS

## T2000 SERIES ONE-PIECE CRIMP COUPLINGS

## TUBE BITE — T2850





**TUBE BITE**

COMPLETE WITH NUT
AND FLARELESS OLIVE

| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | inch | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T2850-0404** | 6 | 1/4 | 7/16"-20 | 1/4 | -0404 | 2.05 | 52 | 1.06 | 27 | | | 9/16 | | 1/2 | |
| **T2850-0405** | 6 | 1/4 | 1/2"-20 | 5/16 | -0405 | 2.05 | 52 | 1.06 | 27 | | | 5/8 | 16 | 9/16 | |
| **T2850-0505** | 8 | 5/16 | 1/2"-20 | 5/16 | -0505 | 2.05 | 52 | 1.06 | 27 | | | 5/8 | 16 | | |
| **T2850-0605** | 10 | 3/8 | 1/2"-20 | 5/16 | -0605 | 2.13 | 54 | 1.14 | 29 | | | 5/8 | 16 | 9/16 | |
| **T2850-0606** | 10 | 3/8 | 9/16"-18 | 3/8 | -0606 | 2.17 | 55 | 1.18 | 30 | | | 11/16 | | 5/8 | 16 |
| **T2850-0608** | 10 | 3/8 | 3/4"-16 | 1/2 | -0608 | 2.24 | 57 | 1.26 | 32 | | | 7/8 | 22 | 13/16 | |
| **T2850-0808** | 12 | 1/2 | 3/4"-16 | 1/2 | -0808 | 2.32 | 59 | 1.38 | 35 | | | 7/8 | 22 | 13/16 | |
| **T2850-0810** | 12 | 1/2 | 7/8"-14 | 5/8 | -0810 | 2.40 | 61 | 1.42 | 36 | | | 1 | | 15/16 | 24 |
| **T2850-1212** | 19 | 3/4 | 1.1/16"-12 | 3/4 | -1212 | 2.72 | 69 | 1.54 | 39 | | | 1.1/4 | 32 | 1.1/8 | |
| **T2850-1616** | 25 | 1 | 1.5/16"-12 | 1 | -1616 | 2.83 | 72 | 1.61 | 41 | | | 1.1/2 | 38 | 1.3/8 | 35 |

## UNO (O RING BOSS) — T2200




**UN O RING MALE**


O RING SUPPLIED

| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T2200-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.97 | 50 | 0.98 | 25 | | | | | 9/16 | |
| **T2200-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 1.97 | 50 | 0.98 | 25 | | | | | 5/8 | 16 |
| **T2200-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.01 | 51 | 0.98 | 25 | | | | | 11/16 | |
| **T2200-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.09 | 53 | 1.10 | 28 | | | | | 11/16 | |
| **T2200-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.13 | 54 | 1.14 | 29 | | | | | 7/8 | 22 |
| **T2200-0614** | 10 | 3/8 | 7/8" -14 | | -0614 | 2.09 | 53 | 1.10 | 28 | | | | | 1 | |
| **T2200-0812** | 12 | 1/2 | 3/4" -14 | | -0812 | 2.20 | 56 | 1.22 | 31 | | | | | 7/8 | 22 |
| **T2200-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.24 | 57 | 1.30 | 33 | | | | | 1 | |
| **T2200-0817** | 12 | 1/2 | 1.1/16" -12 | | -0817 | 2.24 | 57 | 1.26 | 32 | | | | | 1.1/4 | 32 |
| **T2200-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.52 | 64 | 1.34 | 34 | | | | | 1 | |
| **T2200-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 2.44 | 62 | 1.26 | 32 | | | | | 1.1/4 | 32 |
| **T2200-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.64 | 67 | 1.46 | 37 | | | | | 1.1/4 | 32 |
| **T2200-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 2.52 | 64 | 1.38 | 35 | | | | | 1.1/2 | 38 |
| **T2200-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 2.72 | 69 | 1.54 | 39 | | | | | 1.1/2 | 38 |
| **T2200-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 3.66 | 93 | 1.69 | 43 | | | | | 2 | 50 |

## UNO — T2380

**UN O RING**
**MALE SWIVEL**


O RING SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | | |
| **T2380-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.13 | 54 | 1.14 | 29 | | | 11/16 | | | |
| **T2380-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.32 | 59 | 1.34 | 34 | | | 7/8 | 22 | | |
| **T2380-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.32 | 59 | 1.38 | 35 | | | 7/8 | 22 | | |
| **T2380-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.32 | 59 | 1.38 | 35 | | | 1 | | | |
| **T2380-0817** | 12 | 1/2 | 1.1/16" -12 | | -0817 | 2.40 | 61 | 1.42 | 36 | | | 1.1/4 | 32 | | |
| **T2380-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.48 | 63 | 1.30 | 33 | | | 1 | | | |
| **T2380-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.60 | 66 | 1.46 | 37 | | | 1.1/4 | 32 | | |

## UNO — T2390

**UN O RING (BOSS) MALE SWIVEL**
**90° ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T2390-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 1.89 | 48 | 0.91 | 23 | 1.46 | 37 | 11/16 | | 3/4 | 19 |
| **T2390-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 1.89 | 48 | 0.91 | 23 | 1.65 | 42 | 7/8 | 22 | 3/4 | 19 |
| **T2390-0614** | 10 | 3/8 | 7/8" -14 | | -0614 | 1.89 | 48 | 0.91 | 23 | 1.69 | 43 | 1 | | 3/4 | 19 |
| **T2390-0812** | 12 | 1/2 | 3/4" -14 | | -0812 | 2.13 | 54 | 1.14 | 29 | 1.73 | 44 | 7/8 | 22 | 7/8 | 22 |
| **T2390-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.13 | 54 | 1.14 | 29 | 1.77 | 45 | 1 | | 7/8 | 22 |
| **T2390-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.36 | 60 | 1.18 | 30 | 2.01 | 51 | 1.1/4 | 32 | 1.1/16 | 27 |

# ONE-PIECE COUPLINGS

## T4000 SERIES ONE-PIECE CRIMP COUPLINGS


**HOSE COMPATIBILITY FOR T4000 SERIES**

**NON-SKIVE**
For Ryco Hose Series SRF/P, SRX/HT (sizes -12 to -48).
For Ryco Hose Series RT7/T/7N/7TN (sizes -02 to -12).
For Ryco Hose Series T5, SURVIVOR/R5 (sizes -04 to -32).
For Ryco Hose Series MP1 (sizes -04 to -20).
For Ryco Hose Series RST (sizes -08 to -48).
For Ryco Hose Series PCM (sizes -08 to -16).
For Ryco Hose Series M2/G, PL1D (sizes -04 to -12).

**NON-SKIVE**
For Ryco Hose Series TP7, TP7N, TP7T, TP7TN, TP3000, PL1D, PL1PV, , CS1000, MS1000.

## BSPT — T4010


**BSPT MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T4010-0304** | 5 | 3/16 | 1/4" -19 | | -0304 | 1.97 | 50 | 1.18 | 30 | | | | | 9/16 | |
| **T4010-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.17 | 55 | 1.18 | 30 | | | | | 9/16 | |
| **T4010-0504** | 8 | 5/16 | 1/4" -19 | | -0504 | 2.17 | 55 | 1.18 | 30 | | | | | 9/16 | |
| **T4010-0604** | 10 | 3/8 | 1/4" -19 | | -0604 | 2.20 | 56 | 1.30 | 33 | | | | | 5/8 | 16 |
| **T4010-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.20 | 56 | 1.30 | 33 | | | | | 11/16 | |
| **T4010-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.40 | 61 | 1.46 | 37 | | | | | 7/8 | 22 |
| **T4010-0806** | 12 | 1/2 | 3/8" -19 | | -0806 | 2.36 | 60 | 1.38 | 35 | | | | | 11/16 | |
| **T4010-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.56 | 65 | 1.57 | 40 | | | | | 7/8 | 22 |
| **T4010-1012** | 16 | 5/8 | 3/4" -14 | | -1012 | 2.83 | 72 | 1.61 | 41 | | | | | 1.1/16 | 27 |
| **T4010-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.83 | 72 | 1.61 | 41 | | | | | 1.1/16 | 27 |
| **T4010-1616** | 25 | 1 | 1" -11 | | -1616 | 3.19 | 81 | 1.89 | 48 | | | | | 1.3/8 | 35 |
| **T4010-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 3.90 | 99 | 2.09 | 53 | | | | | 1.3/4 | |
| **T4010-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 4.13 | 105 | 2.17 | 55 | | | | | 2 | 50 |
| **T4010-3232** | 51 | 2 | 2" -11 | | -3232 | 4.69 | 119 | 2.60 | 66 | | | | | 2.1/2 | |

## BSPP — T4013


**BSPP MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T4013-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.09 | 53 | 1.10 | 28 | | | | | 3/4 | 19 |
| **T4013-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.09 | 53 | 1.14 | 29 | | | | | 7/8 | 22 |
| **T4013-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.32 | 59 | 1.34 | 34 | | | | | 1.1/16 | 27 |
| **T4013-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.76 | 70 | 1.54 | 39 | | | | | 1.1/4 | 32 |
| **T4013-1616** | 25 | 1 | 1" -11 | | -1616 | 3.07 | 78 | 1.77 | 45 | | | | | 1.5/8 | 41 |
| **T4013-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 3.86 | 98 | 2.01 | 51 | | | | | 2 | 50 |

## BSPT — T4320


**BSPT MALE SWIVEL**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | inch | | inch | mm | inch | mm | | | inch | | | |
| **T4320-0202** | 4 | 1/8 | 3/4 | | -0202 | 1.89 | 48 | 1.34 | 34 | | | 1/2 | | | |

## BSPP — T4020


**BSPP FEMALE**
**60 ° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T4020-0304** | 5 | 3/16 | 1/4" -19 | | -0304 | 1.61 | 41 | 0.87 | 22 | | | 3/4 | 19 | 1/2 | |
| **T4020-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.93 | 49 | 0.94 | 24 | | | 3/4 | 19 | 1/2 | |
| **T4020-0504** | 8 | 5/16 | 1/4" -19 | | -0504 | 1.85 | 47 | 0.87 | 22 | | | 3/4 | 19 | 9/16 | |
| **T4020-0604** | 10 | 3/8 | 1/4" -19 | | -0604 | 1.81 | 46 | 0.87 | 22 | | | 3/4 | 19 | 9/16 | |
| **T4020-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.01 | 51 | 1.06 | 27 | | | 7/8 | 22 | 5/8 | 16 |
| **T4020-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.05 | 52 | 1.10 | 28 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T4020-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.13 | 54 | 1.14 | 29 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T4020-0812** | 12 | 1/2 | 3/4" -14 | | -0812 | 2.17 | 55 | 1.18 | 30 | | | 1.1/4 | 32 | 1 | |
| **T4020-1010** | 16 | 5/8 | 5/8" -14 | | -1010 | 2.36 | 60 | 1.14 | 29 | | | 1.3/16 | 30 | 7/8 | 22 |
| **T4020-1012** | 16 | 5/8 | 3/4" -14 | | -1012 | 2.32 | 59 | 1.06 | 27 | | | 1.1/4 | 32 | 1 | |
| **T4020-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.48 | 61 | 1.30 | 31 | | | 1.1/4 | 32 | 1.1/16 | 27 |
| **T4020-1616** | 25 | 1 | 1" -11 | | -1616 | 2.80 | 71 | 1.46 | 36 | | | 1.1/2 | 38 | 1.1/4 | 32 |
| **T4020-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 3.70 | 94 | 1.77 | 45 | | | 2 | 50 | 1.5/8 | 41 |
| **T4020-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 3.74 | 95 | 1.77 | 45 | | | 2.3/16 | 55 | 2 | 50 |
| **T4020-3232** | 51 | 2 | 2" -11 | | -3232 | 4.21 | 107 | 2.13 | 54 | | | 2.3/4 | 70 | 2.1/2 | |

## BSPT — T4340

**BSPT MALE SWIVEL**
**90° ELBOW**
**60° SEAT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | | inch | mm |
| **T4340-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.13 | 54 | 1.14 | 29 | 2.05 | 52 | 1 | | 7/8 | 22 |

# ONE-PIECE COUPLINGS

## T4000 SERIES ONE-PIECE CRIMP COUPLINGS

### BSPP — T4050


**BSPP FEMALE**
**60° CONE**
**90° ELBOW**




| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T4050-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.13 | 54 | 1.14 | 29 | 1.22 | 31 | 1.1/16 | 27 | 7/8 | 22 |
| **T4050-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 3.50 | 89 | 1.69 | 43 | 2.05 | 52 | 2 | 50 | 1.7/8 | |

### BSPP — T4260


**BSPP FEMALE**
**60° CONE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4260-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.05 | 52 | 1.06 | 27 | 1.14 | 29 | 3/4 | 19 | | |
| **T4260-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.28 | 58 | 1.38 | 35 | 1.30 | 33 | 7/8 | 22 | | |
| **T4260-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.28 | 58 | 1.38 | 35 | 1.30 | 33 | 1.1/16 | 27 | | |
| **T4260-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.48 | 63 | 1.50 | 38 | 1.77 | 45 | 1.1/16 | 27 | | |
| **T4260-1010** | 16 | 5/8 | 5/8" -14 | | -1010 | 3.03 | 77 | 1.77 | 45 | 1.97 | 50 | 1.3/16 | 30 | | |
| **T4260-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.39 | 86 | 2.17 | 55 | 2.32 | 59 | 1.1/4 | 32 | | |
| **T4260-1616** | 25 | 1 | 1" -11 | | -1616 | 4.02 | 102 | 2.68 | 74 | 3.07 | 78 | 1.1/2 | 38 | | 32 |

## NPTF — T4090


**NPTF MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T4090-0202** | 4 | 1/8 | 1/8" -27 | | -0202 | 1.34 | 34 | 0.79 | 20 | | | | | 1/2 | |
| **T4090-0302** | 5 | 3/16 | 1/8" -27 | | -0302 | 1.73 | 44 | 0.94 | 24 | | | | | 7/16 | 11 |
| **T4090-0304** | 5 | 3/16 | 1/4" -18 | | -0304 | 1.97 | 50 | 1.18 | 30 | | | | | 9/16 | |
| **T4090-0402** | 6 | 1/4 | 1/8" -27 | | -0402 | 2.01 | 51 | 1.02 | 26 | | | | | 1/2 | |
| **T4090-0404** | 6 | 1/4 | 1/4" -18 | | -0404 | 2.17 | 55 | 1.18 | 30 | | | | | 9/16 | |
| **T4090-0504** | 8 | 5/16 | 1/4" -18 | | -0504 | 2.17 | 55 | 1.18 | 30 | | | | | 9/16 | |
| **T4090-0506** | 8 | 5/16 | 3/8" -18 | | -0506 | 2.17 | 55 | 1.18 | 30 | | | | | 11/16 | |
| **T4090-0604** | 10 | 3/8 | 1/4" -18 | | -0604 | 2.20 | 56 | 1.30 | 33 | | | | | 5/8 | 16 |
| **T4090-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 2.20 | 56 | 1.30 | 33 | | | | | 11/16 | |
| **T4090-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.40 | 61 | 1.46 | 37 | | | | | 7/8 | 22 |
| **T4090-0806** | 12 | 1/2 | 3/8" -18 | | -0806 | 2.36 | 60 | 1.38 | 35 | | | | | 11/16 | |
| **T4090-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.56 | 65 | 1.57 | 40 | | | | | 7/8 | 22 |
| **T4090-0812** | 12 | 1/2 | 3/4" -14 | | -0812 | 2.44 | 62 | 1.46 | 37 | | | | | 1.1/16 | 27 |
| **T4090-1012** | 16 | 5/8 | 3/4" -14 | | -1012 | 2.83 | 72 | 1.61 | 41 | | | | | 1.1/16 | 27 |
| **T4090-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.83 | 72 | 1.61 | 41 | | | | | 1.1/16 | 27 |
| **T4090-1416** | 22 | 7/8 | 1" -11,5 | | -1416 | 2.91 | 74 | 1.69 | 43 | | | | | 1.3/8 | 35 |
| **T4090-1616** | 25 | 1 | 1" -11,5 | | -1616 | 3.19 | 81 | 1.89 | 48 | | | | | 1.3/8 | 35 |
| **T4090-1820** | 28 | 1.1/8 | 1.1/4" -11,5 | | -1820 | 3.11 | 79 | 1.81 | 46 | | | | | 1.3/4 | |
| **T4090-2016** | 31 | 1.1/4 | 1" -11,5 | | -2016 | 3.90 | 99 | 2.05 | 52 | | | | | 1.3/4 | |
| **T4090-2020** | 31 | 1.1/4 | 1.1/4" -11,5 | | -2020 | 3.90 | 99 | 2.09 | 53 | | | | | 1.3/4 | |
| **T4090-2224** | 35 | 1.3/8 | 1.1/2" -11,5 | | -2224 | 3.98 | 101 | 2.13 | 54 | | | | | 2 | 50 |
| **T4090-2424** | 38 | 1.1/2 | 1.1/2" -11,5 | | -2424 | 4.13 | 105 | 2.17 | 55 | | | | | 2 | 50 |
| **T4090-2932** | 46 | 1.13/16 | 2" -11,5 | | -2932 | 4.69 | 119 | 2.60 | 66 | | | | | 2.1/2 | |
| **T4090-3232** | 51 | 2 | 2" -11,5 | | -3232 | 4.69 | 119 | 2.60 | 66 | | | | | 2.1/2 | |

## NPTF — T4320N

**NPTF MALE SWIVEL**
**60° SEAT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | |
| **T4320N-0202** | 4 | 1/8 | 1/8" -27 | | -0202 | 1.89 | 48 | 1.34 | 34 | | | | | 1/2 | |
| **T4320N-0806** | 12 | 1/2 | 3/8" -18 | | -0806 | 2.36 | 60 | 1.38 | 35 | | | 7/8 | 22 | | |

# ONE-PIECE COUPLINGS

## T4000 SERIES ONE-PIECE CRIMP COUPLINGS

### NPSM — T4020N


**NPSM FEMALE**
**60° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T4020N-0404** | 6 | 1/4 | 1/4" -18 | | -0404 | 1.85 | 47 | 0.87 | 22 | | | 11/16 | | 1/2 | |
| **T4020N-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 1.89 | 48 | 0.94 | 24 | | | 7/8 | 22 | 5/8 | 16 |
| **T4020N-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.01 | 51 | 1.02 | 26 | | | 1 | | 3/4 | 19 |

### JIC — T4030


**JIC**
**37° CONE**
**MALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T4030-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 1.89 | 48 | 1.10 | 28 | | | | | 7/16 | 11 |
| **T4030-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.17 | 55 | 1.14 | 29 | | | | | 1/2 | |
| **T4030-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 2.17 | 55 | 1.14 | 29 | | | | | 9/16 | |
| **T4030-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.17 | 55 | 1.18 | 30 | | | | | 5/8 | 16 |
| **T4030-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.20 | 56 | 1.26 | 32 | | | | | 5/8 | 16 |
| **T4030-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.28 | 58 | 1.38 | 35 | | | | | 3/4 | 19 |
| **T4030-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.44 | 62 | 1.46 | 37 | | | | | 3/4 | 19 |
| **T4030-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.52 | 64 | 1.54 | 39 | | | | | 15/16 | 24 |
| **T4030-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.83 | 72 | 1.57 | 40 | | | | | 15/16 | 24 |
| **T4030-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 2.95 | 75 | 1.69 | 43 | | | | | 1.1/8 | |
| **T4030-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.95 | 75 | 1.73 | 44 | | | | | 1.1/8 | |
| **T4030-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 4.17 | 106 | 2.24 | 57 | | | | | 2 | 50 |

### JIC — T4031

**JIC**
**37° CONE MALE**
**METRIC HEX ONLY**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | | mm |
| **T4031-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.17 | 55 | 1.14 | 29 | | | | | | 12 |

## JSEAL™ / JIC

## T4040

**JSEAL™ / JIC FEMALE CONVEX SEAT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T4040-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 1.61 | 41 | 0.87 | 22 | | | 9/16 | | 1/2 | |
| **T4040-0308** | 5 | 3/16 | 1/2" - 20 | | -0308 | 1.61 | 41 | 0.87 | 22 | | | 5/8 | 16 | 1/2 | |
| **T4040-0309** | 5 | 3/16 | 9/16" -18 | | -0309 | 1.65 | 42 | 0.87 | 22 | | | 11/16 | | 9/16 | |
| **T4040-0406** | 6 | 1/4 | 3/8" - 24 | | -0406 | 1.85 | 47 | 0.87 | 22 | | | 1/2 | | 1/2 | |
| **T4040-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.73 | 44 | 0.75 | 19 | | | 9/16 | | 1/2 | |
| **T4040-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 1.81 | 46 | 0.83 | 21 | | | 5/8 | 16 | 1/2 | |
| **T4040-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 1.89 | 48 | 0.87 | 22 | | | 11/16 | | 1/2 | |
| **T4040-0508** | 8 | 5/16 | 1/2" - 20 | | -0508 | 1.85 | 47 | 0.87 | 22 | | | 5/8 | 16 | 9/16 | |
| **T4040-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 1.85 | 47 | 0.87 | 22 | | | 11/16 | | 9/16 | |
| **T4040-0512** | 8 | 5/16 | 3/4" -16 | | -0512 | 1.93 | 49 | 0.94 | 24 | | | 7/8 | 22 | 11/16 | |
| **T4040-0607** | 10 | 3/8 | 7/16" -20 | | -0607 | 1.85 | 47 | 0.87 | 22 | | | 9/16 | | 9/16 | |
| **T4040-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 1.85 | 47 | 0.87 | 22 | | | 11/16 | | 9/16 | 16 |
| **T4040-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.01 | 50 | 1.02 | 25 | | | 7/8 | 22 | 9/16 | 16 |
| **T4040-0809** | 12 | 1/2 | 9/16" -18 | | -0809 | 2.68 | 68 | 1.69 | 43 | | | 11/16 | | 11/16 | |
| **T4040-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 1.93 | 51 | 0.94 | 25 | | | 7/8 | 22 | 11/16 | 19 |
| **T4040-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.05 | 52 | 1.06 | 27 | | | 1 | | 11/16 | |
| **T4040-0817** | 12 | 1/2 | 1.1/16" -12 | | -0817 | 2.20 | 56 | 1.22 | 31 | | | 1.1/4 | 32 | 11/16 | |
| **T4040-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.28 | 58 | 1.06 | 27 | | | 1 | | 7/8 | 22 |
| **T4040-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 2.44 | 62 | 1.18 | 30 | | | 1.1/4 | 32 | 7/8 | 22 |
| **T4040-1214** | 19 | 3/4 | 7/8" -14 | | -1214 | 2.52 | 62 | 1.34 | 32 | | | 1 | | 1.1/16 | 27 |
| **T4040-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.44 | 60 | 1.22 | 29 | | | 1.1/4 | 32 | 1.1/16 | 27 |
| **T4040-1421** | 22 | 7/8 | 1.5/16" -12 | | -1421 | 2.56 | 65 | 1.34 | 34 | | | 1.1/2 | 38 | 1.1/4 | 32 |
| **T4040-1617** | 25 | 1 | 1.1/16" -12 | | -1617 | 2.68 | 68 | 1.34 | 37 | | | 1.1/4 | 32 | 1.1/4 | 32 |
| **T4040-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 2.72 | 69 | 1.38 | 33 | | | 1.1/2 | 38 | 1.1/4 | 32 |
| **T4040-1826** | 28 | 1.1/8 | 1.5/8"-12 | | -1826 | 2.95 | 75 | 1.61 | 41 | | | 2 | 50 | 1.5/8 | 41 |
| **T4040-2021** | 31 | 1.1/4 | 1.5/16" -12 | | -2021 | 3.62 | 92 | 1.69 | 43 | | | 1.1/2 | 38 | 1.5/8 | 41 |
| **T4040-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 3.62 | 92 | 1.69 | 43 | | | 2 | 50 | 1.5/8 | 41 |
| **T4040-2230** | 35 | 1.3/8 | 1.7/8"-12 | | -2230 | 3.58 | 91 | 1.73 | 44 | | | 2.1/4 | 57 | 2 | 50 |
| **T4040-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 4.06 | 103 | 2.09 | 53 | | | 2.1/4 | 57 | 2 | 50 |
| **T4040-2940** | 46 | 1.13/16 | 2.1/2" -12 | | -2940 | 4.45 | 113 | 2.36 | 60 | | | 2.7/8 | 73 | 2.1/2 | |
| **T4040-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 4.49 | 114 | 2.44 | 62 | | | 2.7/8 | 73 | 2.1/2 | |

# ONE-PIECE COUPLINGS

## T4000 SERIES ONE-PIECE CRIMP COUPLINGS

### JSEAL™ / JIC — T4041


JSEAL™ / JIC FEMALE
CONVEX SEAT
METRIC NUT ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | |
| **T4041-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 1.61 | 41 | 0.87 | 22 | | | | 14 | 1/2 | |
| **T4041-0309** | 5 | 3/16 | 9/16" -18 | | -0309 | 1.65 | 42 | 0.87 | 22 | | | 3/4 | 19 | 9/16 | |
| **T4041-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.73 | 44 | 0.75 | 19 | | | | 14 | 1/2 | |
| **T4041-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 1.89 | 48 | 0.87 | 22 | | | 3/4 | 19 | 1/2 | |
| **T4041-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 1.85 | 47 | 0.87 | 22 | | | 3/4 | 19 | 9/16 | |
| **T4041-0607** | 10 | 3/8 | 7/16" -20 | | -0607 | 1.85 | 47 | 0.87 | 22 | | | | 14 | 9/16 | |
| **T4041-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 1.85 | 47 | 0.87 | 22 | | | 3/4 | 19 | 9/16 | |
| **T4041-0809** | 12 | 1/2 | 9/16" -18 | | -0809 | 2.68 | 68 | 1.69 | 43 | | | 3/4 | 19 | 11/16 | |

### JSEAL™ / JIC — T4250


JSEAL™ / JIC FEMALE
CONVEX SEAT
45° TUBE BEND




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4250-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 1.97 | 50 | 1.22 | 31 | 0.39 | 10 | 9/16 | | | |
| **T4250-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.56 | 65 | 1.57 | 40 | 0.59 | 15 | 9/16 | | | |
| **T4250-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 2.28 | 58 | 1.30 | 33 | 0.59 | 15 | 5/8 | 16 | | |
| **T4250-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 0.59 | 15 | 11/16 | | | |
| **T4250-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.60 | 66 | 1.57 | 40 | 0.63 | 16 | 11/16 | | | |
| **T4250-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 3.39 | 86 | 2.13 | 54 | 0.94 | 24 | 1.1/4 | 32 | | |
| **T4250-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 4.29 | 107 | 3.11 | 77 | 1.10 | 28 | 1.1/4 | 32 | | |
| **T4250-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.65 | 118 | 3.31 | 82 | 1.38 | 35 | 1.1/2 | 38 | | |
| **T4250-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 5.87 | 149 | 3.94 | 100 | 1.54 | 39 | 2 | 50 | | |

## JSEAL™ / JIC — T4251


JSEAL™ / JIC FEMALE
CONVEX SEAT
45° TUBE BEND
METRIC NUT ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4251-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 1.97 | 50 | 1.22 | 31 | 0.39 | 10 | | 14 | | |
| **T4251-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.56 | 65 | 1.57 | 40 | 0.59 | 15 | | 14 | | |
| **T4251-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 0.59 | 15 | 3/4 | 19 | | |
| **T4251-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.60 | 66 | 1.57 | 40 | 0.63 | 16 | 3/4 | 19 | | |

## JSEAL™ / JIC — T4243

JSEAL™ / JIC FEMALE
CONVEX SEAT 90° SHORT TUBE BEND





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4243-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.44 | 62 | 1.46 | 37 | 0.83 | 21 | 9/16 | | | |
| **T4243-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.05 | 52 | 1.06 | 27 | 0.87 | 22 | 11/16 | | | |
| **T4243-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.20 | 56 | 1.22 | 31 | 0.91 | 23 | 11/16 | | | |
| **T4243-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.68 | 68 | 1.69 | 43 | 1.14 | 29 | 7/8 | 22 | | |

# ONE-PIECE COUPLINGS

## T4000 SERIES ONE-PIECE CRIMP COUPLINGS

### JSEAL™ / JIC — T4240


**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4240-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 1.85 | 47 | 1.06 | 27 | 0.98 | 25 | 9/16 | | | |
| **T4240-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.52 | 64 | 1.54 | 39 | 1.26 | 32 | 9/16 | | | |
| **T4240-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 2.24 | 57 | 1.26 | 32 | 1.26 | 32 | 5/8 | 16 | | |
| **T4240-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 1.50 | 38 | 11/16 | | | |
| **T4240-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.32 | 59 | 1.34 | 34 | 1.18 | 30 | 11/16 | | | |
| **T4240-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.32 | 59 | 1.34 | 34 | 1.02 | 26 | 11/16 | | | |
| **T4240-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.36 | 60 | 1.38 | 35 | 1.18 | 30 | 7/8 | 22 | | |
| **T4240-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.60 | 66 | 1.61 | 41 | 1.50 | 38 | 7/8 | 22 | | |
| **T4240-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.60 | 66 | 1.61 | 41 | 1.61 | 41 | 1 | | | |
| **T4240-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 3.03 | 77 | 1.77 | 45 | 1.89 | 48 | 1.1/4 | 32 | | |
| **T4240-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.54 | 88 | 2.32 | 57 | 2.24 | 57 | 1.1/4 | 32 | | |
| **T4240-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 3.98 | 101 | 2.68 | 74 | 2.83 | 72 | 1.1/2 | 38 | | |
| **T4240-1826** | 28 | 1.1/8 | 1.5/8"-12 | | -1826 | 4.74 | 121 | 3.43 | 87 | 3.19 | 81 | | | | |
| **T4240-2021** | 31 | 1.1/4 | 1.5/16" -12 | | -2021 | 5.47 | 139 | 3.54 | 90 | 2.83 | 72 | 1.1/2 | 38 | | |
| **T4240-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 5.87 | 149 | 3.94 | 100 | 3.19 | 81 | 2 | 50 | | |
| **T4240-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 6.10 | 155 | 4.17 | 106 | 4.17 | 106 | 2.1/4 | 57 | | |
| **T4240-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 7.91 | 201 | 5.83 | 148 | 5.20 | 132 | 2.7/8 | 73 | | |

### JSEAL™ / JIC — T4241


**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**90° TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4241-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.52 | 64 | 1.54 | 39 | 1.26 | 32 | | 14 | | |
| **T4241-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 1.50 | 38 | 3/4 | 19 | | |
| **T4241-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.32 | 59 | 1.34 | 34 | 1.18 | 30 | 3/4 | 19 | | |
| **T4241-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.32 | 59 | 1.34 | 34 | 1.02 | 26 | 3/4 | 19 | | |

## JSEAL™ / JIC — T4280


JSEAL™ / JIC FEMALE
CONVEX SEAT
90° LONG TUBE BEND




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4280-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 3.03 | 77 | 2.05 | 52 | 2.17 | 55 | 11/16 | | | |
| **T4280-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.99 | 76 | 2.05 | 52 | 2.17 | 55 | 11/16 | | | |
| **T4280-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.99 | 76 | 2.05 | 52 | 2.52 | 64 | 7/8 | 22 | | |

## JSEAL™ / JIC — T4281


JSEAL™ / JIC FEMALE
CONVEX SEAT
90° LONG TUBE BEND
METRIC NUT ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4281-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 3.03 | 77 | 2.05 | 52 | 2.17 | 55 | 3/4 | 19 | | |
| **T4281-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.99 | 76 | 2.05 | 52 | 2.17 | 55 | 3/4 | 19 | | |

## JIS — T4122

BSPP FEMALE
60° CONCAVE SEAT (JIS)





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T4122-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.93 | 49 | 0.94 | 24 | | | 3/4 | 19 | | 14 |
| **T4122-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 1.93 | 49 | 0.98 | 25 | | | 7/8 | 22 | | 17 |
| **T4122-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 1.99 | 51 | 1.05 | 27 | | | 1.1/16 | 27 | | |
| **T4122-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.05 | 52 | 1.06 | 27 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T4122-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.40 | 61 | 1.18 | 30 | | | | 36 | 1.1/16 | 27 |
| **T4122-1616** | 25 | 1 | 1" -11 | | -1616 | 2.60 | 66 | 1.26 | 32 | | | 1.5/8 | 41 | | 36 |

# ONE-PIECE COUPLINGS

## T4000 SERIES ONE-PIECE CRIMP COUPLINGS

### METRIC - DKL | T4600


**DKL FEMALE**
**24° / 60° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | | | inch | mm | inch | mm | | | inch | mm | | |
| **T4600-0616** | 10 | 3/8 | M 16X1,5 | | -0616 | 1.85 | 47 | 0.91 | 23 | | | 3/4 | 19 | | |
| **T4600-0618** | 10 | 3/8 | M 18X1,5 | | -0618 | 1.85 | 47 | 0.91 | 23 | | | 7/8 | 22 | | |
| **T4600-0622** | 10 | 3/8 | M 22X1,5 | | -0622 | 1.97 | 50 | 1.02 | 26 | | | 1.1/16 | 27 | | |
| **T4600-1230** | 19 | 3/4 | M 30X2 | | -1230 | 2.28 | 58 | 1.06 | 27 | | | | 36 | | |

### METRIC - DKL | T4660


**DKL FEMALE**
**24° / 60° CONE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4660-0616** | 10 | 3/8 | M 16X1,5 | | -0616 | 2.72 | 69 | 1.77 | 45 | 0.79 | 20 | 3/4 | 19 | | |
| **T4660-0618** | 10 | 3/8 | M 18X1,5 | | -0618 | 2.72 | 69 | 1.77 | 45 | 0.79 | 20 | 7/8 | 22 | | |
| **T4660-0622** | 10 | 3/8 | M 22X1,5 | | -0622 | 2.76 | 70 | 1.81 | 46 | 0.83 | 21 | 1.1/16 | 27 | | |
| **T4660-1230** | 19 | 3/4 | M 30X2 | | -1230 | 4.09 | 104 | 2.87 | 73 | 1.26 | 32 | | 36 | | |

### DKL | T4670

**DKL FEMALE**
**24° / 60° CONE**
**90° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4670-0616** | 10 | 3/8 | M 16X1,5 | | -0616 | 2.32 | 59 | 1.38 | 35 | 1.38 | 35 | 3/4 | 19 | | |
| **T4670-0618** | 10 | 3/8 | M 18X1,5 | | -0618 | 2.28 | 58 | 1.34 | 34 | 1.38 | 35 | 7/8 | 22 | | |
| **T4670-0622** | 10 | 3/8 | M 22X1,5 | | -0622 | 2.28 | 58 | 1.34 | 34 | 1.46 | 37 | 1.1/16 | 27 | | |
| **T4670-1230** | 19 | 3/4 | M 30X2 | | -1230 | 3.43 | 87 | 2.20 | 56 | 2.52 | 64 | | 36 | | |

## METRIC - DKOL

## T4501

**DKOL FEMALE**
**24° CONE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T4501-0822** | 12 | 1/2 | M 22X1,5 | | -0822 | 2.24 | 57 | 1.26 | 32 | | | 1.1/16 | 27 | 11/16 | |
| **T4501-1018** | 16 | 5/8 | M 18X1,5 | | -1018 | 2.48 | 63 | 1.23 | 31 | | | 7/8 | 22 | | |
| **T4501-1030** | 16 | 5/8 | M 30X2 | | -1030 | 2.64 | 67 | 1.42 | 36 | | | | 36 | 7/8 | 22 |

## ORFS

## T4840

**ORFS MALE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T4840-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 1.97 | 50 | 0.98 | 25 | | | | | 5/8 | 16 |
| **T4840-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.05 | 52 | 1.06 | 27 | | | | | 3/4 | 19 |
| **T4840-0513** | 8 | 5/16 | 13/16" - 16 | | -0513 | 2.20 | 56 | 1.22 | 31 | | | | | 7/8 | 22 |
| **T4840-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.09 | 53 | 1.14 | 29 | | | | | 3/4 | 19 |
| **T4840-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.17 | 55 | 1.22 | 31 | | | | | 7/8 | 22 |
| **T4840-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.28 | 58 | 1.30 | 33 | | | | | 7/8 | 22 |
| **T4840-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 2.68 | 68 | 1.46 | 37 | | | | | 1.1/16 | 27 |
| **T4840-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 2.76 | 70 | 1.54 | 39 | | | | | 1.1/4 | 32 |
| **T4840-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 2.76 | 70 | 1.57 | 40 | | | | | 1.1/2 | 38 |
| **T4840-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 2.95 | 75 | 1.61 | 41 | | | | | 1.1/2 | 38 |
| **T4840-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 3.62 | 92 | 1.77 | 45 | | | | | 1.3/4 | |

# ONE-PIECE COUPLINGS

## T4000 SERIES ONE-PIECE CRIMP COUPLINGS

## ORFS — T4800


**ORFS FEMALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T4800-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.17 | 55 | 1.14 | 29 | | | 11/16 | | 1/2 | |
| **T4800-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.20 | 56 | 1.22 | 31 | | | 13/16 | | 1/2 | |
| **T4800-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.24 | 57 | 1.26 | 32 | | | 7/8 | 22 | 9/16 | 16 |
| **T4800-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.36 | 60 | 1.38 | 35 | | | 15/16 | 24 | 9/16 | 16 |
| **T4800-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.40 | 61 | 1.42 | 36 | | | 15/16 | 24 | 11/16 | 19 |
| **T4800-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.07 | 72 | 1.85 | 41 | | | 1.3/8 | 35 | 1.1/16 | 24 |
| **T4800-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 3.03 | 75 | 1.85 | 45 | | | 1.5/8 | 41 | 1.1/16 | 24 |
| **T4800-1619** | 25 | 1 | 1.3/16" - 12 | | -1619 | 3.19 | 81 | 1.85 | 45 | | | 1.3/8 | 35 | 1.1/4 | 32 |
| **T4800-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 3.19 | 81 | 1.89 | 42 | | | 1.5/8 | 41 | 1.1/4 | 32 |
| **T4800-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 4.13 | 105 | 2.17 | 55 | | | 2 | 50 | 1.5/8 | 41 |

## ORFS — T4801


**ORFS FEMALE**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T4801-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.17 | 55 | 1.14 | 29 | | | | 17 | 1/2 | |
| **T4801-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.20 | 56 | 1.22 | 31 | | | 7/8 | 22 | 1/2 | |
| **T4801-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.07 | 72 | 1.85 | 41 | | | | 36 | 1.1/16 | 27 |
| **T4801-1619** | 25 | 1 | 1.3/16" - 12 | | -1619 | 3.19 | 81 | 1.85 | 47 | | | | 36 | 1.1/4 | 32 |

## ORFS — T4810


**ORFS FEMALE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4810-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.52 | 64 | 1.54 | 39 | 0.71 | 18 | 11/16 | | | |
| **T4810-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.72 | 69 | 1.77 | 45 | 0.79 | 20 | 7/8 | 22 | | |
| **T4810-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.52 | 64 | 1.57 | 40 | 0.67 | 17 | 15/16 | 24 | | |
| **T4810-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.91 | 74 | 1.93 | 49 | 0.75 | 19 | 15/16 | 24 | | |
| **T4810-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 3.58 | 91 | 2.32 | 59 | 0.79 | 20 | 1.1/8 | | | |
| **T4810-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 4.29 | 107 | 3.11 | 77 | 1.14 | 29 | 1.3/8 | 35 | | |
| **T4810-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 4.72 | 120 | 3.39 | 84 | 1.34 | 34 | 1.5/8 | 41 | | |
| **T4810-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 5.94 | 151 | 4.02 | 102 | 1.77 | 45 | 2 | 50 | | |

## ORFS — T4811

**ORFS FEMALE**
**45° TUBE BEND**
**METRIC NUT ONLY**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4811-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.52 | 64 | 1.54 | 39 | 0.71 | 18 | | 17 | | |
| **T4811-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 3.58 | 91 | 2.32 | 59 | 0.79 | 20 | 1.3/16 | 30 | | |
| **T4811-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 4.29 | 109 | 3.11 | 79 | 1.14 | 29 | | 36 | | |

# ONE-PIECE COUPLINGS

## T4000 SERIES ONE-PIECE CRIMP COUPLINGS

### ORFS — T4820


**ORFS FEMALE**
**90° MEDIUM TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4820-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.09 | 53 | 1.10 | 28 | 1.26 | 32 | 11/16 | | | |
| **T4820-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.28 | 58 | 1.30 | 33 | 1.50 | 38 | 13/16 | | | |
| **T4820-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.36 | 60 | 1.38 | 35 | 1.50 | 38 | 7/8 | 22 | | |
| **T4820-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.48 | 63 | 1.50 | 38 | 1.34 | 34 | 15/16 | 24 | | |
| **T4820-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.48 | 63 | 1.50 | 38 | 1.61 | 41 | 15/16 | 24 | | |
| **T4820-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.54 | 88 | 2.32 | 57 | 2.32 | 59 | 1.3/8 | 35 | | |
| **T4820-1619** | 25 | 1 | 1.3/16" - 12 | | -1619 | 4.06 | 103 | 2.72 | 69 | 2.32 | 59 | 1.3/8 | 35 | | |
| **T4820-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 4.06 | 103 | 2.72 | 74 | 2.80 | 71 | 1.5/8 | 41 | | |
| **T4820-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 5.87 | 149 | 3.94 | 100 | 3.54 | 90 | 2 | 50 | | |
| **T4820-2432** | 38 | 1.1/2 | 2" - 12 | | -2432 | 6.10 | 155 | 4.17 | 106 | 4.21 | 107 | 2.1/4 | 57 | | |

### ORFS — T4821


**ORFS FEMALE**
**90° MEDIUM TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4821-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.28 | 58 | 1.30 | 33 | 1.26 | 32 | | 17 | | |
| **T4821-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 3.03 | 77 | 1.77 | 45 | 1.85 | 47 | 1.3/16 | 30 | | |
| **T4821-1219** | 19 | 3/4 | 1.3/16" E- 12 | | -1219 | 3.54 | 88 | 2.32 | 57 | 2.32 | 59 | | 36 | | |

### ORFS — T4830


**ORFS FEMALE**
**90° LONG BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4830-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 4.25 | 108 | 2.91 | 74 | 4.45 | 113 | 1.5/8 | 41 | | |

## SAE — T4530


**SAE MALE**
**45° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T4530-0510** | 8 | 5/16 | 5/8" -18 | | -0510 | 2.20 | 56 | 1.22 | 31 | | | | | 11/16 | |
| **T4530-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 2.28 | 58 | 1.34 | 34 | | | | | 3/4 | 19 |

## SAE — T4540


**SAE FEMALE**
**45° FLARE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T4540-0410** | 6 | 1/4 | 5/8" -18 | | -0410 | 1.89 | 48 | 0.91 | 23 | | | 3/4 | 19 | 5/8 | 16 |
| **T4540-0510** | 8 | 5/16 | 5/8" -18 | | -0510 | 1.77 | 45 | 0.79 | 20 | | | 3/4 | 19 | 5/8 | 16 |
| **T4540-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 1.85 | 47 | 0.91 | 23 | | | 3/4 | 19 | 5/8 | 16 |

## SAE — T4570

**SAE FEMALE**
**45° FLARE**
**90° ELBOW**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T4570-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 1.85 | 47 | 0.91 | 23 | 0.91 | 23 | 3/4 | 19 | 3/4 | 19 |

# ONE-PIECE COUPLINGS

## T4000 SERIES ONE-PIECE CRIMP COUPLINGS

### SAE — T4550


**SAE FEMALE**
**45° FLARE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T4550-0510** | 8 | 5/16 | 5/8" -18 | | -0510 | 2.56 | 65 | 1.57 | 40 | 0.63 | 16 | 3/4 | 19 | | |
| **T4550-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 2.48 | 63 | 1.54 | 39 | 0.67 | 17 | 3/4 | 19 | 3/4 | 19 |

### SAE — T4560


**SAE FEMALE**
**45° FLARE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T4560-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 2.32 | 59 | 1.38 | 35 | 1.26 | 32 | 3/4 | 19 | | |

### SAE — T4740


**SAE INVERTED FLARE MALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T4740-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 2.60 | 66 | 1.61 | 41 | | | 9/16 | | | |
| **T4740-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.64 | 67 | 1.73 | 44 | | | 5/8 | 16 | | |

## SAE — T4750


**SAE INVERTED FLARE MALE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | | | inch | mm |
| **T4750-0510** | 8 | 5/16 | 5/8" -18 | | -0510 | 3.86 | 98 | 2.87 | 73 | 0.91 | 23 | 9/16 | | | |
| **T4750-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 3.82 | 97 | 2.87 | 73 | 0.91 | 23 | 5/8 | 16 | | |

## SAE — T4770

**SAE INVERTED FLARE MALE**
**90° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | | | inch | mm |
| **T4770-0510** | 8 | 5/16 | 5/8" -18 | | -0510 | 3.15 | 80 | 2.17 | 55 | 1.97 | 50 | 9/16 | | | |
| **T4770-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 3.11 | 79 | 2.17 | 55 | 1.97 | 50 | 5/8 | 16 | | |

# ONE-PIECE COUPLINGS

## T4000 SERIES ONE-PIECE CRIMP COUPLINGS

### DIMENSIONS FOR SAE CODE 61 AND CODE 62 FLANGES, AND RYCO CODE 62C FLANGES


| NOMINAL FLANGE | CODE 61 | | | | CODE 62 | | | | CODE 62C | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | B | | T | | B | | T | | B | | T | |
| inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch |
| 1/2 | 30,2 | 1.19 | 6,73 | 0.265 | 31,8 | 1.25 | 7,75 | 0.305 | | | | |
| 5/8 | 34,0 | 1.34 | 6,73 | 0.265 | | | | | | | | |
| 3/4 | 38,1 | 1.50 | 6,73 | 0.265 | 41,3 | 1.63 | 8,76 | 0.345 | 41,3 | 1.63 | 14,20 | 0.559 |
| 1 | 44,5 | 1.75 | 8,00 | 0.315 | 47,6 | 1.88 | 9,53 | 0.375 | 47,6 | 1.88 | 14,20 | 0.559 |
| 1.1/4 | 50,8 | 2.00 | 8,00 | 0.315 | 54,0 | 2.12 | 10,29 | 0.405 | 54,0 | 2.12 | 14,20 | 0.559 |
| 1.1/2 | 60,3 | 2.38 | 8,00 | 0.315 | 63,5 | 2.50 | 12,57 | 0.495 | 63,5 | 2.50 | 14,20 | 0.559 |
| 2 | 71,4 | 2.81 | 9,53 | 0.375 | 79,4 | 3.13 | 12,57 | 0.495 | 79,4 | 3.13 | 14,20 | 0.559 |
| 2.1/2 | 84,1 | 3.31 | 9,53 | 0.375 | | | | | | | | |
| 3 | 101,6 | 4.00 | 9,53 | 0.375 | | | | | | | | |




**NOTE:** Ryco Code 62C fittings conform to the flange OD and bolt hole patterns of SAE Code 62 but require special flange clamps.
Ryco Code 62C flange heads are thicker than SAE Code 62 and measure T = 14,2 mm (0.559 inch) in all sizes.

## RYCOLOK — T4870

**RYCOLOK MALE STAPLE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | mm | | inch | mm | inch | mm | | | | | | |
| **T4870-3250** | 51 | 2 | | 50 | -3250 | 4.33 | 110 | 2.28 | 58 | | | | | | |

## SAE FLANGE — T4130

**SAE CODE 61 FLANGE**

CLAMPS - SEE PAGES 274 & 282
O RING NOT SUPPLIED





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | |
| **T4130-1212** | 19 | 3/4 | | | -1212 | 3.03 | 77 | 1.81 | 46 | | | | | | |
| **T4130-1216** | 19 | 3/4 | | | -1216 | 3.19 | 81 | 1.97 | 50 | | | | | | |
| **T4130-1616** | 25 | 1 | | | -1616 | 3.35 | 85 | 2.05 | 52 | | | | | | |
| **T4130-1620** | 25 | 1 | | | -1620 | 3.54 | 90 | 2.24 | 57 | | | | | | |
| **T4130-2020** | 31 | 1.1/4 | | | -2020 | 4.13 | 105 | 2.32 | 59 | | | | | | |
| **T4130-2024** | 31 | 1.1/4 | | | -2024 | 5.16 | 131 | 3.35 | 85 | | | | | | |
| **T4130-2424** | 38 | 1.1/2 | | | -2424 | 5.31 | 135 | 3.39 | 86 | | | | | | |
| **T4130-2432** | 38 | 1.1/2 | | | -2432 | 5.71 | 145 | 3.78 | 96 | | | | | | |
| **T4130-3232** | 51 | 2 | | | -3232 | 5.87 | 149 | 3.78 | 96 | | | | | | |
| **T4130-4040** | 63 | 2.1/2 | | | -4040 | 5.75 | 146 | 3.11 | 79 | | | | | | |

## SAE FLANGE — T4150

**SAE CODE 61 FLANGE**
**45° TUBE BEND**

CLAMPS - SEE PAGES 274 & 282
O RING NOT SUPPLIED





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T4150-1212** | 19 | 3/4 | | | -1212 | 3.78 | 96 | 2.56 | 65 | 1.02 | 26 | | | | |
| **T4150-1616** | 25 | 1 | | | -1616 | 4.53 | 115 | 3.19 | 81 | 1.18 | 30 | | | | |
| **T4150-2020** | 31 | 1.1/4 | | | -2020 | 5.79 | 147 | 3.94 | 100 | 1.42 | 36 | | | | |
| **T4150-2420** | 38 | 1.1/2 | | | -2420 | 5.76 | 146 | 3.82 | 97 | 1.42 | 36 | | | | |
| **T4150-2424** | 38 | 1.1/2 | | | -2424 | 6.26 | 159 | 4.33 | 110 | 1.65 | 42 | | | | |
| **T4150-2432** | 38 | 1.1/2 | | | -2432 | 6.65 | 169 | 4.72 | 120 | 1.85 | 47 | | | | |

## SAE FLANGE — T4170

**SAE CODE 61 FLANGE**
**90° TUBE BEND**

CLAMPS - SEE PAGES 274 & 282
O RING NOT SUPPLIED





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T4170-1212** | 19 | 3/4 | | | -1212 | 3.39 | 86 | 2.17 | 55 | 2.13 | 54 | | | | |
| **T4170-1616** | 25 | 1 | | | -1616 | 4.02 | 102 | 2.68 | 68 | 2.68 | 68 | | | | |
| **T4170-2020** | 31 | 1.1/4 | | | -2020 | 5.00 | 127 | 3.15 | 80 | 3.07 | 78 | | | | |
| **T4170-2424** | 38 | 1.1/2 | | | -2424 | 6.02 | 153 | 4.09 | 104 | 3.66 | 93 | | | | |
| **T4170-2432** | 38 | 1.1/2 | | | -2432 | 5.75 | 146 | 3.82 | 97 | 3.90 | 99 | | | | |
| **T4170-3232** | 51 | 2 | | | -3232 | 7.48 | 190 | 5.39 | 137 | 5.12 | 130 | | | | |
| **T4170-3240** | 51 | 2 | | | -3240 | 7.64 | 194 | 5.55 | 141 | 5.28 | 134 | | | | |

## SAE FLANGE — T4173

**SAE CODE 61 FLANGE**
**90° LONG TUBE BEND**

CLAMPS - SEE PAGES 274 & 282
O RING NOT SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T4173-1620** | 25 | 1 | | | -1620 | 3.98 | 101 | 2.64 | 67 | 3.66 | 93 | | | | |


# ONE-PIECE COUPLINGS

## T4000 SERIES ONE-PIECE CRIMP COUPLINGS

### UNO — T4200

**UN O RING MALE**


O RING SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | inch | | inch | mm | inch | mm | | | | | inch | mm |
| **T4200-0407** | 6 | 1/4 | 7/16" -20 | 1/4 | -0407 | 1.97 | 50 | 0.98 | 25 | | | | | 9/16 | |
| **T4200-1621** | 25 | 1 | 1.5/16" -12 | 1 | -1621 | 2.83 | 72 | 1.54 | 39 | | | | | 1.1/2 | 38 |


### SALVAGE / LIFESAVER — T4230

**SALVAGE / LIFESAVER**
**TUBE WELD**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | A | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | | inch | mm |
| **T4230-0506** | 8 | 5/16 | | 3/8 | -0506 | 1.69 | 43 | 0.71 | 18 | | | | | 9/16 | |
| **T4230-0606** | 10 | 3/8 | | 3/8 | -0606 | 1.65 | 42 | 0.71 | 18 | | | | | 5/8 | 16 |
| **T4230-0808** | 12 | 1/2 | | 1/2 | -0808 | 1.73 | 44 | 0.75 | 19 | | | | | 11/16 | |
| **T4230-1212** | 19 | 3/4 | | 3/4 | -1212 | 2.05 | 52 | 0.83 | 21 | | | | | 1 | |
| **T4230-1012** | 16 | 5/8 | | 3/4 | -1012 | 2.05 | 52 | 0.79 | 20 | | | | | 1.1/16 | 27 |
| **T4230-1616** | 25 | 1 | | 1 | -1616 | 2.40 | 61 | 1.10 | 28 | | | | | 1.3/8 | 35 |
| **T4230-2020** | 31 | 1.1/4 | | 1.1/4 | -2020 | 3.07 | 78 | 1.22 | 31 | | | | | 1.3/4 | |
| **T4230-2424** | 38 | 1.1/2 | | 1.1/2 | -2424 | 3.31 | 84 | 1.34 | 34 | | | | | 2 | 50 |
| **T4230-3232** | 51 | 2 | | 2 | -3232 | 3.70 | 94 | 1.61 | 41 | | | | | 2.1/2 | |

# TUBE BITE — T4850




**TUBE BITE**

COMPLETE WITH NUT
AND FLARELESS OLIVE

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T4850-0606** | 10 | 3/8 | | 3/8 | -0606 | 2.13 | 54 | 1.18 | 30 | | | 11/16 | | 5/8 | 16 |

# ONE-PIECE COUPLINGS


## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

**HOSE COMPATIBILITY FOR T6000 SERIES**

**NON-SKIVE**
For Ryco Hose Series H5000 (sizes -24 to -32).
For Ryco Hose Series H6000 (sizes -12 to -32).

## BSPT — T6010


**BSPT MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T6010-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.70 | 94 | 1.65 | 42 | | | | | 1.1/16 | 27 |
| **T6010-1616** | 25 | 1 | 1" -11 | | -1616 | 4.53 | 115 | 1.93 | 49 | | | | | 1.3/8 | 35 |
| **T6010-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 4.84 | 123 | 2.17 | 55 | | | | | 1.3/4 | |
| **T6010-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 5.67 | 144 | 2.20 | 56 | | | | | 2 | 50 |
| **T6010-3232** | 51 | 2 | 2" -11 | | -3232 | 6.93 | 176 | 2.80 | 71 | | | | | 2.1/2 | |

## BSPP — T6013


**BSPP MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T6013-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.66 | 93 | 1.61 | 41 | | | | | 1.1/4 | 32 |
| **T6013-1616** | 25 | 1 | 1" -11 | | -1616 | 4.41 | 112 | 1.81 | 46 | | | | | 1.5/8 | 41 |
| **T6013-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 4.76 | 121 | 2.09 | 53 | | | | | 2 | 50 |
| **T6013-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 5.63 | 143 | 2.17 | 55 | | | | | 2.3/16 | 55 |
| **T6013-3232** | 51 | 2 | 2" -11 | | -3232 | 6.97 | 177 | 2.83 | 72 | | | | | 2.3/4 | 70 |

## BSPP — T6020


BSPP FEMALE
60 ° CONE




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T6020-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.27 | 82 | 1.22 | 30 | | | 1.1/4 | 32 | 1.1/16 | 27 |
| **T6020-1616** | 25 | 1 | 1" -11 | | -1616 | 4.13 | 105 | 1.54 | 39 | | | 1.1/2 | 38 | 1.3/8 | 35 |
| **T6020-2016** | 31 | 1.1/4 | 1" -11 | | -2016 | 4.41 | 112 | 1.73 | 44 | | | 1.1/2 | 38 | 1.3/4 | |
| **T6020-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 4.45 | 113 | 1.77 | 45 | | | 2 | 50 | 1.3/4 | |
| **T6020-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 5.28 | 134 | 1.81 | 46 | | | 2.3/16 | 55 | 2 | 50 |
| **T6020-3232** | 51 | 2 | 2" -11 | | -3232 | 6.46 | 164 | 2.32 | 59 | | | 2.3/4 | 70 | 2.1/2 | |

## BSPP — T6022


BSPP FEMALE
60 ° CONE
HEAVY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T6022-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.46 | 88 | 1.42 | 36 | | | 1.1/4 | 32 | 1.1/8 | |
| **T6022-1616** | 25 | 1 | 1" -11 | | -1616 | 4.09 | 104 | 1.54 | 39 | | | 1.1/2 | 38 | 1.1/2 | 38 |
| **T6022-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 4.49 | 114 | 1.81 | 46 | | | 2 | | 1.3/4 | |

## BSPP — T6270

BSPP FEMALE
60° CONE
45° TUBE BEND





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T6270-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 4.88 | 124 | 2.83 | 72 | 1.14 | 29 | 1.1/4 | 32 | | |
| **T6270-1616** | 25 | 1 | 1" -11 | | -1616 | 6.22 | 158 | 3.62 | 92 | 1.54 | 39 | 1.1/2 | 38 | | |
| **T6270-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 6.97 | 177 | 4.29 | 109 | 1.81 | 46 | 2 | 50 | | |
| **T6270-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 8.50 | 216 | 5.04 | 128 | 2.05 | 52 | 2.3/16 | 55 | 2.3/16 | 55 |
| **T6270-3232** | 51 | 2 | 2" -11 | | -3232 | 9.96 | 253 | 5.83 | 148 | 2.56 | 65 | 2.3/4 | 70 | | |

# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

### BSPP — T6260


**BSPP FEMALE**
**60° CONE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T6260-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 4.29 | 109 | 2.24 | 57 | 2.28 | 58 | 1.1/4 | 32 | 1.1/16 | 27 |
| **T6260-1616** | 25 | 1 | 1" -11 | | -1616 | 5.39 | 137 | 2.80 | 71 | 3.15 | 80 | 1.1/2 | 38 | | |
| **T6260-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 6.18 | 157 | 3.50 | 89 | 3.58 | 91 | 2 | 50 | | |
| **T6260-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 7.64 | 194 | 4.17 | 106 | 4.13 | 105 | 2.3/16 | 55 | 2.3/16 | 55 |
| **T6260-3232** | 51 | 2 | 2" -11 | | -3232 | 9.45 | 240 | 5.31 | 135 | 5.20 | 132 | 2.3/4 | 70 | | |

### NPTF — T6090


**NPTF MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T6090-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.70 | 94 | 1.65 | 42 | | | | | 1.1/16 | 27 |
| **T6090-1616** | 25 | 1 | 1" -11,5 | | -1616 | 4.53 | 115 | 1.93 | 49 | | | | | 1.3/8 | 35 |
| **T6090-2020** | 31 | 1.1/4 | 1.1/4" -11,5 | | -2020 | 4.84 | 123 | 2.17 | 55 | | | | | 1.3/4 | |
| **T6090-2424** | 38 | 1.1/2 | 1.1/2" -11,5 | | -2424 | 5.67 | 144 | 2.20 | 56 | | | | | 2 | 50 |
| **T6090-3232** | 51 | 2 | 2" -11,5 | | -3232 | 6.93 | 176 | 2.80 | 71 | | | | | 2.1/2 | |

### NPTF — T6091


**NPTF MALE EXTENDED**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | | | | | |
| **T6091-3232** | 51 | 2 | 2" -11,5 | | 0 | -3232 | 8.54 | 217 | 4.45 | 113 | | | | | |

## NPSM — T6020N


NPSM FEMALE
60° CONE




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T6020N-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.23 | 82 | 1.18 | 30 | | | 1.1/4 | 32 | 1 | |
| **T6020N-1616** | 25 | 1 | 1" -11,5 | | -1616 | 4.02 | 102 | 1.46 | 37 | | | 1.1/2 | 38 | 1.3/8 | 35 |
| **T6020N-2020** | 31 | 1.1/4 | 1.1/4" -11,5 | | -2020 | 4.37 | 111 | 1.69 | 43 | | | 1.7/8 | | 1.3/4 | |
| **T6020N-2424** | 38 | 1.1/2 | 1.1/2" -11,5 | | -2424 | 5.16 | 131 | 1.73 | 44 | | | 2.1/4 | 57 | 2 | 50 |
| **T6020N-3232** | 51 | 2 | 2" -11,5 | | -3232 | 6.46 | 164 | 2.32 | 59 | | | 2.3/4 | 70 | 2.1/2 | |

## JIC — T6030


JIC 37°
CONE MALE




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T6030-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.49 | 114 | 1.89 | 48 | | | | | 1.3/8 | 35 |
| **T6030-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 5.04 | 128 | 2.36 | 60 | | | | | 1.3/4 | |
| **T6030-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 5.75 | 146 | 2.28 | 58 | | | | | 2 | 50 |
| **T6030-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 7.20 | 183 | 3.11 | 79 | | | | | 2.1/2 | |

## JIC — T6031

JIC
37° CONE MALE
METRIC HEX ONLY





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | | mm |
| **T6031-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.49 | 114 | 1.89 | 48 | | | | | | 36 |

# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS


### JSEAL™ / JIC — T6040




**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T6040-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.37 | 86 | 1.32 | 34 | | | 1.1/4 | 32 | 1.1/6 | 27 |
| **T6040-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 3.50 | 89 | 1.45 | 37 | | | 1.1/2 | 38 | 1.1/16 | 27 |
| **T6040-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.09 | 104 | 1.50 | 38 | | | 1.1/2 | 38 | 1.3/8 | 35 |
| **T6040-1626** | 25 | 1 | 1.5/8"-12 | | -1626 | 4.25 | 108 | 1.65 | 42 | | | 2 | 50 | 1.5/8 | 41 |
| **T6040-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 4.45 | 113 | 1.77 | 45 | | | 2 | 50 | 1.3/4 | |
| **T6040-2030** | 31 | 1.1/4 | 1.7/8"-12 | | -2030 | 4.65 | 118 | 1.97 | 50 | | | 2.1/4 | 57 | 2 | 50 |
| **T6040-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 5.59 | 142 | 2.13 | 54 | | | 2.1/4 | 57 | 2.3/16 | 55 |
| **T6040-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 6.77 | 172 | 2.64 | 67 | | | 2.7/8 | 73 | 2.5/8 | |


### JIC — T6045




**JIC 37° FEMALE**
**HIGH-PRESSURE**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | | |
| **T6045-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 3.96 | 101 | 1.38 | 35 | | | | | | |

### JSEAL™ / JIC — T6250





**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**45° TUBE BEND**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T6250-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 4.84 | 123 | 2.80 | 71 | 1.10 | 28 | 1.1/4 | 32 | | |
| **T6250-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 5.91 | 150 | 3.31 | 84 | 1.38 | 35 | 1.1/2 | 38 | | |
| **T6250-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 6.69 | 170 | 4.02 | 102 | 1.54 | 39 | 2 | 50 | | |
| **T6250-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 8.50 | 216 | 5.04 | 128 | 1.97 | 50 | 2.1/4 | 57 | 2.3/16 | 55 |
| **T6250-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 10.12 | 257 | 5.98 | 152 | 2.48 | 63 | 2.7/8 | 73 | | |

## JSEAL™ / JIC — T6280


**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**90° LONG TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T6280-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 4.33 | 110 | 2.28 | 58 | 3.78 | 96 | 1.1/4 | 32 | | |
| **T6280-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 5.55 | 141 | 2.95 | 75 | 4.49 | 114 | 1.1/2 | 38 | | |
| **T6280-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 6.14 | 156 | 3.46 | 88 | 5.08 | 129 | 2 | 50 | | |

## JSEAL™ / JIC — T6240


**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T6240-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 4.33 | 110 | 2.28 | 58 | 2.24 | 57 | 1.1/4 | 32 | | |
| **T6240-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 4.33 | 110 | 2.28 | 58 | 2.80 | 71 | | 38 | 1.1/2 | |
| **T6240-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 5.31 | 135 | 2.72 | 69 | 2.83 | 72 | 1.1/2 | 38 | | |
| **T6240-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 6.14 | 156 | 3.46 | 88 | 3.19 | 81 | 2 | 50 | | |
| **T6240-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 7.64 | 194 | 4.17 | 106 | 4.17 | 106 | 2.1/4 | 57 | 2.3/16 | 55 |
| **T6240-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 9.53 | 242 | 5.39 | 137 | 5.20 | 132 | 2.7/8 | 73 | | |

## JOINER — T6900

**JOINER**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | | | |
| **T6900-1212** | 19 | 3/4 | | 3/4 | -1212 | 2.83 | 72 | 0.79 | 20 | | | | | | |
| **T6900-1616** | 25 | 1 | | 1 | -1616 | 3.70 | 94 | 1.14 | 29 | | | | | | |
| **T6900-2020** | 31 | 1.1/4 | | 1.1/4 | -2020 | 3.78 | 96 | 1.10 | 28 | | | | | | |
| **T6900-2424** | 38 | 1.1/2 | | 1.1/2 | -2424 | 4.53 | 115 | 1.10 | 28 | | | | | | |
| **T6900-3232** | 51 | 2 | | 2 | -3232 | 5.55 | 141 | 1.42 | 36 | | | | | | |


# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

### METRIC - DKS

### T6630

**DKS MALE**
**24° SEAT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | | | inch | mm |
| **T6630-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 3.50 | 89 | 1.46 | 37 | | | | | 1.1/4 | 32 |
| **T6630-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 3.58 | 91 | 1.54 | 39 | | | | | | 36 |
| **T6630-1636** | 25 | 1 | M 36X2 | 25 | -1636 | 4.29 | 109 | 1.69 | 43 | | | | | 1.5/8 | 41 |
| **T6630-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 4.37 | 111 | 1.77 | 45 | | | | | | 46 |
| **T6630-2052** | 31 | 1.1/4 | M 52X2 | 38 | -2052 | 4.65 | 118 | 1.97 | 50 | | | | | 2.3/16 | 55 |
| **T6630-2452** | 38 | 1.1/2 | M 52X2 | 38 | -2452 | 5.39 | 137 | 1.97 | 50 | | | | | 2.3/16 | 55 |

### METRIC - DKOS

### T6711

**DKOS FEMALE**
**24° CONE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T6711-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 3.39 | 86 | 1.35 | 34 | | | | 36 | 0 | 0 |
| **T6711-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 3.46 | 88 | 1.42 | 36 | | | | 46 | | |
| **T6711-1636** | 25 | 1 | M 36X2 | 25 | -1636 | 4.02 | 102 | 1.42 | 36 | | | | 46 | | |
| **T6711-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 4.09 | 104 | 1.50 | 38 | | | 2 | 50 | | |
| **T6711-2052** | 31 | 1.1/4 | M 52X2 | 38 | -2052 | 4.29 | 109 | 1.61 | 41 | | | 2.3/8 | 60 | | |
| **T6711-2452** | 38 | 1.1/2 | M 52X2 | 38 | -2452 | 5.08 | 129 | 1.65 | 42 | | | 2.3/8 | 60 | | |

### METRIC - DKOS

### T6720


**DKOS FEMALE**
**24° CONE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T6720-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 5.04 | 128 | 2.99 | 76 | 1.38 | 35 | | 36 | 0 | 0 |
| **T6720-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 5.04 | 128 | 2.99 | 76 | 1.38 | 35 | | 46 | | |
| **T6720-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 6.10 | 155 | 3.50 | 89 | 1.46 | 37 | 2 | 50 | | |
| **T6720-2052** | 31 | 1.1/4 | M 52X2 | 38 | -2052 | 7.72 | 196 | 5.04 | 128 | 1.89 | 48 | 2.3/8 | 60 | | |
| **T6720-2452** | 38 | 1.1/2 | M 52X2 | 38 | -2452 | 8.54 | 217 | 5.08 | 129 | 1.89 | 48 | 2.3/8 | 60 | | |

## METRIC - DKOS — T6730


**DKOS FEMALE**
**24° CONE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T6730-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 4.37 | 111 | 2.32 | 59 | 2.68 | 68 | | 36 | 0 | 0 |
| **T6730-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 4.29 | 109 | 2.24 | 57 | 2.68 | 68 | | 46 | | |
| **T6730-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 5.35 | 136 | 2.76 | 70 | 3.03 | 77 | 2 | 50 | | |
| **T6730-2052** | 31 | 1.1/4 | M 52X2 | 38 | -2052 | 6.22 | 158 | 3.54 | 90 | 3.50 | 89 | 2.3/8 | 60 | | |
| **T6730-2452** | 38 | 1.1/2 | M 52X2 | 38 | -2452 | 7.05 | 179 | 3.58 | 91 | 3.50 | 89 | 2.3/8 | 60 | | |

## ORFS — T6840


**ORFS MALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T6840-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.66 | 93 | 1.61 | 41 | | | | | 1.1/4 | 32 |
| **T6840-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 4.25 | 108 | 1.69 | 43 | | | | | 1.1/2 | 38 |
| **T6840-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 4.76 | 121 | 2.09 | 53 | | | | | 1.43/50 | 47 |
| **T6840-2432** | 38 | 1.1/2 | 2" - 12 | | -2432 | 5.31 | 135 | 1.85 | 47 | | | | | 2.1/4 | 57 |

## ORFS — T6800

**ORFS FEMALE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T6800-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.78 | 96 | 1.73 | 44 | | | 1.3/8 | 35 | 1.1/8 | |
| **T6800-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 4.17 | 106 | 2.13 | 54 | | | 1.5/8 | 41 | 1.3/8 | 35 |
| **T6800-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 4.76 | 121 | 2.20 | 56 | | | 1.5/8 | 41 | 1.3/8 | 35 |
| **T6800-1627** | 25 | 1 | 1.11/16" - 12 | | -1627 | 4.96 | 126 | 2.40 | 61 | | | 2 | 50 | 1.3/4 | |
| **T6800-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 5.08 | 129 | 2.40 | 61 | | | 2 | 50 | 1.3/4 | |
| **T6800-2432** | 38 | 1.1/2 | 2" - 12 | | -2432 | 6.18 | 157 | 2.72 | 69 | | | 2.1/4 | 57 | 2.1/4 | 57 |

# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

### ORFS — T6801


**ORFS FEMALE**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | mm | inch | |
| **T6801-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.78 | 96 | 1.73 | 44 | | | | 36 | 1.1/8 | |

### ORFS — T6810


**ORFS FEMALE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T6810-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 4.65 | 118 | 2.60 | 66 | 1.14 | 29 | 1.3/8 | 35 | | |
| **T6810-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 6.02 | 153 | 3.43 | 87 | 1.34 | 34 | 1.5/8 | 41 | | |
| **T6810-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 6.97 | 177 | 4.29 | 109 | 1.77 | 45 | 2 | 50 | | |
| **T6810-2432** | 38 | 1.1/2 | 2" - 12 | | -2432 | 8.46 | 215 | 5.00 | 127 | 2.09 | 53 | 2.1/4 | 57 | | |

### ORFS — T6811


**ORFS FEMALE**
**45° TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | | mm | | |
| **T6811-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 4.65 | 118 | 2.60 | 66 | 1.14 | 29 | | 36 | | |

## ORFS — T6820


**ORFS FEMALE**
**90° MEDIUM TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T6820-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 4.21 | 107 | 2.17 | 55 | 2.32 | 59 | 1.3/8 | 35 | | |
| **T6820-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 4.37 | 111 | 2.32 | 59 | 2.09 | 53 | 1.5/8 | 41 | 1.1/16 | 27 |
| **T6820-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 5.39 | 137 | 2.80 | 71 | 2.80 | 71 | 1.5/8 | 41 | | |
| **T6820-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 6.18 | 157 | 3.50 | 89 | 3.54 | 90 | 2 | 50 | | |
| **T6820-2432** | 38 | 1.1/2 | 2" - 12 | | -2432 | 7.64 | 194 | 4.17 | 106 | 4.21 | 107 | 2.1/4 | 57 | | |

## ORFS — T6821


**ORFS FEMALE**
**90° MEDIUM TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | | mm | | |
| **T6821-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 4.21 | 107 | 2.17 | 55 | 2.32 | 59 | | 36 | | |

## RYCOLOK — T6871

**RYCOLOK MALE**
**45° ELBOW- STAPLE**
O RING & BACK UP RING SUPPLIED





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | inch | mm | | | inch | |
| **T6871-3250** | 51 | 2 | | 50 | -3250 | 7.56 | 192 | 3.43 | 87 | 1.81 | 46 | | | 2.1/2 | |

# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

### RYCOLOK — T6872


**RYCOLOK MALE**
**90° ELBOW- STAPLE**
O RING & BACK UP RING SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | mm | | inch | mm | inch | mm | inch | mm | | | | |
| **T6872-1220** | 19 | 3/4 | | 20 | -1220 | 3.31 | 84 | 1.26 | 32 | 2.19 | 56 | | | | |
| **T6872-1625** | 25 | 1 | | 25 | -1625 | 4.25 | 108 | 1.67 | 42 | 2.68 | 68 | | | | |

### RYCOLOK — T6870


**RYCOLOK**
**MALE STAPLE**
O RING & BACK UP RING SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | mm | | inch | mm | inch | mm | | | | | | |
| **T6870-1220** | 19 | 3/4 | | 20 | -1220 | 3.66 | 93 | 1.61 | 41 | | | | | | |
| **T6870-1625** | 25 | 1 | | 25 | -1625 | 4.53 | 115 | 1.93 | 49 | | | | | | |
| **T6870-2032** | 31 | 1.1/4 | | 32 | -2032 | 4.72 | 120 | 2.05 | 52 | | | | | | |
| **T6870-2440** | 38 | 1.1/2 | | 40 | -2440 | 5.83 | 148 | 2.40 | 61 | | | | | | |
| **T6870-3250** | 51 | 2 | | 50 | -3250 | 6.57 | 167 | 2.48 | 63 | | | | | | |

### RYCOLOK — T6876


**RYCO SUPERLOK MALE**
**STAPLE**
O RING & BACK UP RING SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | mm | | inch | mm | inch | mm | | | | | | |
| **T6876-1220** | 19 | 3/4 | | 20 | -1220 | 4.02 | 102 | 1.97 | 50 | | | | | | |
| **T6876-1625** | 25 | 1 | | 25 | -1625 | 5.31 | 135 | 2.72 | 69 | | | | | | |
| **T6876-2032** | 31 | 1.1/4 | | 32 | -2032 | 5.55 | 141 | 2.87 | 73 | | | | | | |
| **T6876-2440** | 38 | 1.1/2 | | 40 | -2440 | 6.57 | 167 | 3.11 | 79 | | | | | | |
| **T6876-3250** | 51 | 2 | | 50 | -3250 | 7.44 | 189 | 3.31 | 84 | | | | | | |

## DIMENSIONS FOR SAE CODE 61 AND CODE 62 FLANGES, AND RYCO CODE 62C FLANGES


| NOMINAL FLANGE | CODE 61 | | | | CODE 62 | | | | CODE 62C | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | B | | T | | B | | T | | B | | T | |
| inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch |
| 1/2 | 30,2 | 1.19 | 6,73 | 0.265 | 31,8 | 1.25 | 7,75 | 0.305 | | | | |
| 5/8 | 34,0 | 1.34 | 6,73 | 0.265 | | | | | | | | |
| 3/4 | 38,1 | 1.50 | 6,73 | 0.265 | 41,3 | 1.63 | 8,76 | 0.345 | 41,3 | 1.63 | 14,20 | 0.559 |
| 1 | 44,5 | 1.75 | 8,00 | 0.315 | 47,6 | 1.88 | 9,53 | 0.375 | 47,6 | 1.88 | 14,20 | 0.559 |
| 1.1/4 | 50,8 | 2.00 | 8,00 | 0.315 | 54,0 | 2.12 | 10,29 | 0.405 | 54,0 | 2.12 | 14,20 | 0.559 |
| 1.1/2 | 60,3 | 2.38 | 8,00 | 0.315 | 63,5 | 2.50 | 12,57 | 0.495 | 63,5 | 2.50 | 14,20 | 0.559 |
| 2 | 71,4 | 2.81 | 9,53 | 0.375 | 79,4 | 3.13 | 12,57 | 0.495 | 79,4 | 3.13 | 14,20 | 0.559 |
| 2.1/2 | 84,1 | 3.31 | 9,53 | 0.375 | | | | | | | | |
| 3 | 101,6 | 4.00 | 9,53 | 0.375 | | | | | | | | |




**NOTE:** Ryco Code 62C fittings conform to the flange OD and bolt hole patterns of SAE Code 62 but require special flange clamps.
Ryco Code 62C flange heads are thicker than SAE Code 62 and measure T = 14,2 mm (0.559 inch) in all sizes.

## SAE FLANGE — T6130

### SAE CODE 61 FLANGE




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | | | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | | | |
| **T6130-1212** | 19 | 3/4 | | | -1212 | 3.94 | 100 | 1.89 | 48 | | | | | | | | |
| **T6130-1216** | 19 | 3/4 | | | -1216 | 4.09 | 104 | 2.05 | 52 | | | | | | | | |
| **T6130-1616** | 25 | 1 | | | -1616 | 4.69 | 119 | 2.09 | 53 | | | | | | | | |
| **T6130-1620** | 25 | 1 | | | -1620 | 4.88 | 124 | 2.28 | 58 | | | | | | | | |
| **T6130-2020** | 31 | 1.1/4 | | | -2020 | 5.08 | 129 | 2.40 | 61 | | | | | | | | |
| **T6130-2424** | 38 | 1.1/2 | | | -2424 | 6.85 | 174 | 3.43 | 87 | | | | | | | | |
| **T6130-3232** | 51 | 2 | | | -3232 | 8.11 | 206 | 3.98 | 101 | | | | | | | | |


# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

## SAE FLANGE — T6290

**SAE CODE 61 FLANGE**
**30° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6290-1212** | 19 | 3/4 | | | -1212 | 4.88 | 124 | 2.83 | 72 | 0.71 | 18 | | | | |
| **T6290-1616** | 25 | 1 | | | -1616 | 6.30 | 160 | 3.70 | 94 | 0.87 | 22 | | | | |
| **T6290-2020** | 31 | 1.1/4 | | | -2020 | 6.85 | 174 | 4.17 | 106 | 0.79 | 20 | | | | |
| **T6290-2024** | 31 | 1.1/4 | | | -2024 | 7.05 | 179 | 4.37 | 111 | 0.94 | 24 | | | | |
| **T6290-2424** | 38 | 1.1/2 | | | -2424 | 8.11 | 206 | 4.65 | 118 | 1.02 | 26 | | | | |
| **T6290-2432** | 38 | 1.1/2 | | | -2432 | 8.58 | 218 | 5.12 | 130 | 1.26 | 32 | | | | |
| **T6290-3232** | 51 | 2 | | | -3232 | 10.20 | 259 | 6.06 | 154 | 1.57 | 40 | | | | |

## SAE FLANGE — T6150

**SAE CODE 61 FLANGE**
**45° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6150-1212** | 19 | 3/4 | | | -1212 | 4.72 | 120 | 2.68 | 68 | 1.02 | 26 | | | | |
| **T6150-1216** | 19 | 3/4 | | | -1216 | 4.80 | 122 | 2.76 | 70 | 1.18 | 30 | | | | |
| **T6150-1616** | 25 | 1 | | | -1616 | 5.87 | 149 | 3.27 | 83 | 1.18 | 30 | | | | |
| **T6150-1620** | 25 | 1 | | | -1620 | 5.94 | 151 | 3.35 | 85 | 1.26 | 32 | | | | |
| **T6150-2020** | 31 | 1.1/4 | | | -2020 | 6.69 | 170 | 4.02 | 102 | 1.50 | 38 | | | | |
| **T6150-2424** | 38 | 1.1/2 | | | -2424 | 8.03 | 204 | 4.57 | 116 | 1.65 | 42 | | | | |
| **T6150-3232** | 51 | 2 | | | -3232 | 10.04 | 255 | 5.91 | 150 | 2.28 | 58 | | | | |

## SAE FLANGE — T6300

**CODE 61 FLANGE**
**60° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6300-1212** | 19 | 3/4 | | | -1212 | 5.20 | 132 | 3.15 | 80 | 1.46 | 37 | | | | |
| **T6300-1216** | 19 | 3/4 | | | -1216 | 5.28 | 134 | 3.23 | 82 | 1.61 | 41 | | | | |
| **T6300-1616** | 25 | 1 | | | -1616 | 6.50 | 165 | 3.90 | 99 | 1.81 | 46 | | | | |
| **T6300-1620** | 25 | 1 | | | -1620 | 6.42 | 163 | 3.82 | 97 | 1.77 | 45 | | | | |
| **T6300-2020** | 31 | 1.1/4 | | | -2020 | 7.36 | 187 | 4.69 | 119 | 2.01 | 51 | | | | |
| **T6300-2024** | 31 | 1.1/4 | | | -2024 | 7.44 | 189 | 4.76 | 121 | 2.13 | 54 | | | | |
| **T6300-2424** | 38 | 1.1/2 | | | -2424 | 9.13 | 232 | 5.67 | 144 | 2.36 | 60 | | | | |
| **T6300-2432** | 38 | 1.1/2 | | | -2432 | 9.25 | 235 | 5.79 | 147 | 2.68 | 68 | | | | |
| **T6300-3232** | 51 | 2 | | | -3232 | 11.46 | 291 | 7.32 | 186 | 3.23 | 82 | | | | |

## SAE — T6170

**CODE 61 FLANGE**
**90° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | inch | mm | | | | |
| **T6170-1212** | 19 | 3/4 | | - | -1212 | 4.33 | 110 | 2.28 | 58 | 2.13 | 54 | | | | |
| **T6170-1216** | 19 | 3/4 | | - | -1216 | 4.29 | 109 | 2.24 | 57 | 2.36 | 60 | | | | |
| **T6170-1616** | 25 | 1 | | - | -1616 | 5.35 | 136 | 2.76 | 70 | 2.68 | 68 | | | | |
| **T6170-1620** | 25 | 1 | | - | -1620 | 5.35 | 136 | 2.76 | 70 | 2.72 | 69 | | | | |
| **T6170-2020** | 31 | 1.1/4 | | - | -2020 | 6.22 | 158 | 3.54 | 90 | 3.07 | 78 | | | | |
| **T6170-2424** | 38 | 1.1/2 | | - | -2424 | 7.56 | 192 | 4.09 | 104 | 3.66 | 93 | | | | |
| **T6170-3232** | 51 | 2 | | - | -3232 | 9.53 | 242 | 5.39 | 137 | 5.12 | 130 | | | | |

# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

### SAE FLANGE — T6330





**CODE 62 FLANGE**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | |
| **T6330-1212** | 19 | 3/4 | | | -1212 | 4.13 | 105 | 2.09 | 53 | | | | | | |
| **T6330-1216** | 19 | 3/4 | | | -1216 | 4.25 | 108 | 2.20 | 56 | | | | | | |
| **T6330-1612** | 25 | 1 | | | -1612 | 4.72 | 120 | 2.17 | 55 | | | | | | |
| **T6330-1616** | 25 | 1 | | | -1616 | 4.84 | 123 | 2.24 | 57 | | | | | | |
| **T6330-1620** | 25 | 1 | | | -1620 | 5.28 | 134 | 2.72 | 69 | | | | | | |
| **T6330-2016** | 31 | 1.1/4 | | | -2016 | 5.47 | 139 | 2.80 | 71 | | | | | | |
| **T6330-2020** | 31 | 1.1/4 | | | -2020 | 5.47 | 139 | 2.80 | 71 | | | | | | |
| **T6330-2024** | 31 | 1.1/4 | | | -2024 | 6.65 | 169 | 3.98 | 101 | | | | | | |
| **T6330-2420** | 38 | 1.1/2 | | | -2420 | 6.22 | 158 | 2.76 | 70 | | | | | | |
| **T6330-2424** | 38 | 1.1/2 | | | -2424 | 7.40 | 188 | 3.98 | 101 | | | | | | |
| **T6330-2432** | 38 | 1.1/2 | | | -2432 | 8.11 | 206 | 4.69 | 119 | | | | | | |
| **T6330-3224** | 51 | 2 | | | -3224 | 8.31 | 211 | 4.21 | 107 | | | | | | |
| **T6330-3232** | 51 | 2 | | | -3232 | 8.98 | 228 | 4.84 | 123 | | | | | | |

### SAE FLANGE — T6333




**RYCO CODE 62C FLANGE**
O RING NOT SUPPLIED


CLAMPS - SEE PAGES 274 & 282

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | |
| **T6333-1212** | 19 | 3/4 | | | -1212 | 5.51 | 140 | 3.46 | 88 | | | | | | |
| **T6333-1216** | 19 | 3/4 | | | -1216 | 5.51 | 140 | 3.46 | 88 | | | | | | |
| **T6333-1616** | 25 | 1 | | | -1616 | 6.14 | 156 | 3.54 | 90 | | | | | | |
| **T6333-1620** | 25 | 1 | | | -1620 | 6.14 | 156 | 3.54 | 90 | | | | | | |
| **T6333-2020** | 31 | 1.1/4 | | | -2020 | 6.18 | 157 | 3.50 | 89 | | | | | | |
| **T6333-2024** | 31 | 1.1/4 | | | -2024 | 6.18 | 157 | 3.50 | 89 | | | | | | |
| **T6333-2424** | 38 | 1.1/2 | | | -2424 | 6.89 | 175 | 3.43 | 87 | | | | | | |
| **T6333-3232** | 51 | 2 | | | -3232 | 8.46 | 215 | 4.37 | 111 | | | | | | |

## SAE FLANGE — T6334

**RYCO CODE 62C D-RING FLANGE**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | |
| **T6334-1212** | 19 | 3/4 | | | -1212 | 4.57 | 116 | 2.52 | 64 | | | | | | |
| **T6334-1216** | 19 | 3/4 | | | -1216 | 4.57 | 116 | 2.52 | 64 | | | | | | |
| **T6334-1616** | 25 | 1 | | | -1616 | 5.16 | 131 | 2.56 | 65 | | | | | | |
| **T6334-1620** | 25 | 1 | | | -1620 | 5.47 | 139 | 2.87 | 73 | | | | | | |
| **T6334-2020** | 31 | 1.1/4 | | | -2020 | 6.34 | 161 | 3.66 | 93 | | | | | | |
| **T6334-2024** | 31 | 1.1/4 | | | -2024 | 6.18 | 157 | 3.50 | 89 | | | | | | |
| **T6334-2424** | 38 | 1.1/2 | | | -2424 | 6.77 | 172 | 3.31 | 84 | | | | | | |
| **T6334-3232** | 51 | 2 | | | -3232 | 9.02 | 229 | 4.92 | 125 | | | | | | |

## CODE 62 — T6335

**RYCO CODE 62K FLANGE**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | |
| **T6335-1616** | 25 | 1 | | | -1616 | 5.04 | 128 | 2.44 | 62 | | | | | | |
| **T6335-1620** | 25 | 1 | | | -1620 | 4.80 | 122 | 2.20 | 56 | | | | | | |
| **T6335-2016** | 31 | 1.1/4 | | | -2016 | 7.20 | 183 | 4.53 | 115 | | | | | | |
| **T6335-2020** | 31 | 1.1/4 | | | -2020 | 6.42 | 163 | 3.74 | 95 | | | | | | |
| **T6335-2024** | 31 | 1.1/4 | | | -2024 | 5.83 | 148 | 3.15 | 80 | | | | | | |
| **T6335-2424** | 38 | 1.1/2 | | | -2424 | 7.68 | 195 | 4.21 | 107 | | | | | | |
| **T6335-2432** | 38 | 1.1/2 | | | -2432 | 7.05 | 179 | 3.62 | 92 | | | | | | |
| **T6335-3224** | 51 | 2 | | | -3224 | 9.92 | 252 | 5.79 | 147 | | | | | | |
| **T6335-3232** | 51 | 2 | | | -3232 | 8.94 | 227 | 4.80 | 122 | | | | | | |


# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

### SAE FLANGE — T6912

**RYCO CODE 62K FLANGE**
**15° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6912-1616** | 25 | 1 | | | -1616 | 7.52 | 191 | 4.92 | 125 | 0.67 | 17 | | | | |
| **T6912-2024** | 31 | 1.1/4 | | | -2024 | 9.21 | 234 | 6.54 | 166 | 0.71 | 18 | | | | |
| **T6912-2424** | 38 | 1.1/2 | | | -2424 | 11.06 | 281 | 7.64 | 194 | 0.94 | 24 | | | | |
| **T6912-2432** | 38 | 1.1/2 | | | -2432 | 11.10 | 282 | 7.68 | 195 | 1.06 | 27 | | | | |

### SAE FLANGE — T6440

**SAE CODE 62 FLANGE**
**22.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6440-1212** | 19 | 3/4 | | | -1212 | 5.20 | 132 | 3.15 | 80 | 0.63 | 16 | | | | |
| **T6440-1216** | 19 | 3/4 | | | -1216 | 5.16 | 131 | 3.11 | 79 | 0.55 | 14 | | | | |
| **T6440-1616** | 25 | 1 | | | -1616 | 6.18 | 157 | 3.58 | 91 | 0.63 | 16 | | | | |
| **T6440-2020** | 31 | 1.1/4 | | | -2020 | 7.01 | 178 | 4.33 | 110 | 0.67 | 17 | | | | |
| **T6440-2024** | 31 | 1.1/4 | | | -2024 | 7.32 | 186 | 4.65 | 118 | 0.87 | 22 | | | | |
| **T6440-2424** | 38 | 1.1/2 | | | -2424 | 8.46 | 215 | 5.00 | 127 | 0.94 | 24 | | | | |
| **T6440-3232** | 51 | 2 | | | -3232 | 10.71 | 272 | 6.57 | 167 | 1.10 | 28 | | | | |

### SAE FLANGE — T6445

**RYCO CODE 62K FLANGE**
**22.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6445-3232** | 51 | 2 | | | -3232 | 12.76 | 324 | 8.62 | 219 | 1.77 | 45 | | | | |

## SAE FLANGE — T6443

**RYCO CODE 62C FLANGE**
**22.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6443-1212** | 19 | 3/4 | | | -1212 | 5.28 | 134 | 3.23 | 82 | 0.71 | 18 | | | | |
| **T6443-1216** | 19 | 3/4 | | | -1216 | 5.39 | 137 | 3.35 | 85 | 0.79 | 20 | | | | |
| **T6443-1616** | 25 | 1 | | | -1616 | 6.34 | 161 | 3.74 | 95 | 0.63 | 16 | | | | |
| **T6443-1620** | 25 | 1 | | | -1620 | 6.38 | 162 | 3.78 | 96 | 0.75 | 19 | | | | |
| **T6443-2020** | 31 | 1.1/4 | | | -2020 | 7.17 | 182 | 4.49 | 114 | 0.75 | 19 | | | | |
| **T6443-2024** | 31 | 1.1/4 | | | -2024 | 7.32 | 186 | 4.65 | 118 | 0.87 | 22 | | | | |
| **T6443-2424** | 38 | 1.1/2 | | | -2424 | 8.46 | 215 | 5.00 | 127 | 0.94 | 24 | | | | |
| **T6440-3232** | 51 | 2 | | | -3232 | 10.71 | 272 | 6.57 | 167 | 1.10 | 28 | | | | |

## SAE FLANGE — T6444

**RYCO CODE 62C D-RING FLANGE**
**22.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6444-1212** | 19 | 3/4 | | | -1212 | 5.24 | 133 | 3.19 | 81 | 0.59 | 15 | | | | |
| **T6444-1616** | 25 | 1 | | | -1616 | 6.10 | 155 | 3.50 | 89 | 0.63 | 16 | | | | |
| **T6444-1620** | 25 | 1 | | | -1620 | 4.17 | 106 | 1.61 | 41 | 0.63 | 16 | | | | |
| **T6444-2020** | 31 | 1.1/4 | | | -2020 | 7.17 | 182 | 4.49 | 114 | 0.75 | 19 | | | | |


# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

## SAE FLANGE — T6450

**SAE CODE 62 FLANGE**
**30° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6450-1212** | 19 | 3/4 | | | -1212 | 4.92 | 125 | 2.87 | 73 | 0.75 | 19 | | | | |
| **T6450-1616** | 25 | 1 | | | -1616 | 6.14 | 156 | 3.54 | 90 | 0.87 | 22 | | | | |
| **T6450-1620** | 25 | 1 | | | -1620 | 6.14 | 156 | 3.54 | 90 | 0.98 | 25 | | | | |
| **T6450-2020** | 31 | 1.1/4 | | | -2020 | 7.01 | 178 | 4.33 | 110 | 0.87 | 22 | | | | |
| **T6450-2024** | 31 | 1.1/4 | | | -2024 | 7.20 | 183 | 4.53 | 115 | 0.98 | 25 | | | | |
| **T6450-2424** | 38 | 1.1/2 | | | -2424 | 8.78 | 223 | 5.31 | 135 | 1.30 | 33 | | | | |
| **T6450-3232** | 51 | 2 | | | -3232 | 10.67 | 271 | 6.54 | 166 | 1.57 | 40 | | | | |

## SPECIAL FLANGE — T6453

**RYCO CODE 62C FLANGE**
**30° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6453-1212** | 19 | 3/4 | | | -1212 | 5.16 | 131 | 3.11 | 79 | 0.91 | 23 | | | | |
| **T6453-1616** | 25 | 1 | | | -1616 | 6.97 | 177 | 4.37 | 111 | 0.94 | 24 | | | | |
| **T6453-1620** | 25 | 1 | | | -1620 | 7.09 | 180 | 4.49 | 114 | 0.98 | 25 | | | | |
| **T6453-2020** | 31 | 1.1/4 | | | -2020 | 7.32 | 186 | 4.65 | 118 | 0.98 | 25 | | | | |
| **T6453-2024** | 31 | 1.1/4 | | | -2024 | 7.28 | 185 | 4.61 | 117 | 1.02 | 26 | | | | |
| **T6453-2424** | 38 | 1.1/2 | | | -2424 | 8.46 | 215 | 5.00 | 127 | 1.18 | 30 | | | | |

## SPECIAL FLANGE — T6454

**RYCO CODE 62C D-RING FLANGE**
**30° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6454-1212** | 19 | 3/4 | | | -1212 | 5.28 | 134 | 3.23 | 82 | 0.91 | 23 | | | | |
| **T6454-1616** | 25 | 1 | | | -1616 | 6.85 | 174 | 4.25 | 108 | 0.94 | 24 | | | | |
| **T6454-2020** | 31 | 1.1/4 | | | -2020 | 7.28 | 185 | 4.61 | 117 | 0.98 | 25 | | | | |
| **T6454-2024** | 31 | 1.1/4 | | | -2024 | 7.28 | 185 | 4.61 | 117 | 1.02 | 26 | | | | |

## SPECIAL FLANGE — T6455

**RYCO CODE 62K FLANGE**
**30° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6455-2020** | 31 | 1.1/4 | | | -2020 | 9.41 | 239 | 6.73 | 171 | 1.57 | 40 | | | | |
| **T6455-2024** | 31 | 1.1/4 | | | -2024 | 9.21 | 234 | 6.54 | 166 | 1.50 | 38 | | | | |
| **T6455-2424** | 38 | 1.1/2 | | | -2424 | 10.67 | 271 | 7.24 | 184 | 1.97 | 50 | | | | |
| **T6455-3232** | 51 | 2 | | | -3232 | 12.52 | 318 | 8.39 | 213 | 2.17 | 55 | | | | |


# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

## SPECIAL FLANGE — T6350

**SAE CODE 62 FLANGE**
**45° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6350-1212** | 19 | 3/4 | | | -1212 | 4.76 | 121 | 2.72 | 69 | 1.10 | 28 | | | | |
| **T6350-1216** | 19 | 3/4 | | | -1216 | 4.92 | 125 | 2.87 | 73 | 1.22 | 31 | | | | |
| **T6350-1612** | 25 | 1 | | | -1612 | 5.43 | 138 | 2.83 | 72 | 1.10 | 28 | | | | |
| **T6350-1616** | 25 | 1 | | | -1616 | 5.91 | 150 | 3.31 | 84 | 1.22 | 31 | | | | |
| **T6350-1620** | 25 | 1 | | | -1620 | 5.94 | 151 | 3.35 | 85 | 1.34 | 34 | | | | |
| **T6350-2020** | 31 | 1.1/4 | | | -2020 | 6.73 | 171 | 4.06 | 103 | 1.50 | 38 | | | | |
| **T6350-2024** | 31 | 1.1/4 | | | -2024 | 6.85 | 174 | 4.17 | 106 | 1.61 | 41 | | | | |
| **T6350-2424** | 38 | 1.1/2 | | | -2424 | 7.91 | 201 | 4.45 | 113 | 1.77 | 45 | | | | |
| **T6350-2432** | 38 | 1.1/2 | | | -2432 | 8.23 | 209 | 4.76 | 121 | 1.97 | 50 | | | | |
| **T6350-3232** | 51 | 2 | | | -3232 | 10.24 | 260 | 6.10 | 155 | 2.36 | 60 | | | | |

## SPECIAL FLANGE — T6353

**RYCO CODE 62C FLANGE**
**45° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6353-1212** | 19 | 3/4 | | | -1212 | 4.88 | 124 | 2.83 | 72 | 1.22 | 31 | | | | |
| **T6353-1216** | 19 | 3/4 | | | -1216 | 4.88 | 124 | 2.83 | 72 | 1.30 | 33 | | | | |
| **T6353-1616** | 25 | 1 | | | -1616 | 6.02 | 153 | 3.43 | 87 | 1.38 | 35 | | | | |
| **T6353-1620** | 25 | 1 | | | -1620 | 5.91 | 150 | 3.31 | 84 | 1.46 | 37 | | | | |
| **T6353-2020** | 31 | 1.1/4 | | | -2020 | 6.85 | 174 | 4.17 | 106 | 1.61 | 41 | | | | |
| **T6353-2024** | 31 | 1.1/4 | | | -2024 | 7.01 | 178 | 4.33 | 110 | 1.65 | 42 | | | | |
| **T6353-2424** | 38 | 1.1/2 | | | -2424 | 11.81 | 300 | 8.39 | 213 | 1.81 | 46 | | | | |
| **T6353-3232** | 51 | 2 | | | -3232 | 10.47 | 266 | 6.34 | 161 | 2.40 | 61 | | | | |

## SPECIAL FLANGE — T6354

**RYCO CODE 62C D-RING FLANGE**
**45° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6354-1212** | 19 | 3/4 | | | -1212 | 4.84 | 123 | 2.80 | 71 | 1.22 | 31 | | | | |
| **T6354-1216** | 19 | 3/4 | | | -1216 | 4.96 | 126 | 2.91 | 74 | 1.30 | 33 | | | | |
| **T6354-1616** | 25 | 1 | | | -1616 | 6.18 | 157 | 3.58 | 91 | 1.38 | 35 | | | | |
| **T6354-1620** | 25 | 1 | | | -1620 | 5.83 | 148 | 3.23 | 82 | 1.46 | 37 | | | | |
| **T6354-2020** | 31 | 1.1/4 | | | -2020 | 6.85 | 174 | 4.17 | 106 | 1.61 | 41 | | | | |
| **T6354-2024** | 31 | 1.1/4 | | | -2024 | 7.01 | 178 | 4.33 | 110 | 1.69 | 43 | | | | |

## SPECIAL FLANGE — T6355

**RYCO CODE 62K FLANGE**
**45° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6355-1616** | 25 | 1 | | | -1616 | 6.85 | 174 | 4.25 | 108 | 1.97 | 50 | | | | |
| **T6355-1620** | 25 | 1 | | | -1620 | 6.81 | 173 | 4.21 | 107 | 1.97 | 50 | | | | |
| **T6355-2016** | 31 | 1.1/4 | | | -2016 | 8.70 | 221 | 6.02 | 153 | 2.17 | 55 | | | | |
| **T6355-2020** | 31 | 1.1/4 | | | -2020 | 8.90 | 226 | 6.22 | 158 | 2.36 | 60 | | | | |
| **T6355-2024** | 31 | 1.1/4 | | | -2024 | 9.29 | 236 | 6.61 | 168 | 2.36 | 60 | | | | |
| **T6355-2420** | 38 | 1.1/2 | | | -2420 | 9.65 | 245 | 6.20 | 158 | 2.87 | 73 | | | | |
| **T6355-2424** | 38 | 1.1/2 | | | -2424 | 10.00 | 254 | 6.57 | 167 | 3.15 | 80 | | | | |
| **T6355-2432** | 38 | 1.1/2 | | | -2432 | 9.65 | 245 | 6.22 | 158 | 3.74 | 95 | | | | |
| **T6355-3224** | 51 | 2 | | | -3224 | 11.38 | 289 | 7.28 | 185 | 3.35 | 85 | | | | |
| **T6355-3232** | 51 | 2 | | | -3232 | 11.73 | 298 | 7.60 | 193 | 3.54 | 90 | | | | |


# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

### SPECIAL FLANGE — T6359

**RYCO CODE 62K D-RING FLANGE**
**45° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6359-3232** | 51 | 2 | | | -3232 | 13.90 | 353 | 9.76 | 248 | 5.31 | 135 | | | | |

### SPECIAL FLANGE — T6465

**RYCO CODE 62K FLANGE**
**60° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6465-2424** | 38 | 1.1/2 | | | -2424 | 11.30 | 287 | 7.87 | 200 | 3.70 | 94 | | | | |
| **T6465-3232** | 51 | 2 | | | -3232 | 13.62 | 346 | 9.49 | 241 | 4.72 | 120 | | | | |

### SPECIAL FLANGE — T6360

**SAE CODE 62 FLANGE**
**67.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6360-1212** | 19 | 3/4 | | | -1212 | 4.96 | 126 | 2.91 | 74 | 1.85 | 47 | | | | |
| **T6360-1216** | 19 | 3/4 | | | -1216 | 5.08 | 129 | 3.03 | 77 | 1.73 | 44 | | | | |
| **T6360-1616** | 25 | 1 | | | -1616 | 6.18 | 157 | 3.58 | 91 | 2.01 | 51 | | | | |
| **T6360-1620** | 25 | 1 | | | -1620 | 6.34 | 161 | 3.74 | 95 | 2.83 | 72 | | | | |
| **T6360-2020** | 31 | 1.1/4 | | | -2020 | 7.95 | 202 | 5.28 | 134 | 2.83 | 72 | | | | |
| **T6360-2024** | 31 | 1.1/4 | | | -2024 | 8.11 | 206 | 5.43 | 138 | 2.91 | 74 | | | | |

## SPECIAL FLANGE — T6914

**RYCO CODE 62K FLANGE**
**70° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6914-1616** | 25 | 1 | | | -1616 | 7.13 | 181 | 4.53 | 115 | 2.76 | 70 | | | | |
| **T6914-2020** | 31 | 1.1/4 | | | -2020 | 9.33 | 237 | 6.65 | 169 | 3.78 | 96 | | | | |

## SPECIAL FLANGE — T6916

**RYCO CODE 62K FLANGE**
**75° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6916-2432** | 38 | 1.1/2 | | | -2432 | 10.39 | 264 | 6.97 | 177 | 5.43 | 138 | | | | |

## SPECIAL FLANGE — T6918

**RYCO CODE 62K FLANGE**
**80° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6918-3232** | 51 | 2 | | | -3232 | 11.69 | 297 | 7.56 | 192 | 6.30 | 160 | | | | |


# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

## SPECIAL FLANGE — T6363

**RYCO CODE 62C FLANGE**
**67.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6363-1212** | 19 | 3/4 | | | -1212 | 5.00 | 127 | 2.95 | 75 | 2.05 | 52 | | | | |
| **T6363-1216** | 19 | 3/4 | | | -1216 | 5.04 | 128 | 2.99 | 76 | 2.09 | 53 | | | | |
| **T6363-1616** | 25 | 1 | | | -1616 | 6.18 | 157 | 3.58 | 91 | 2.09 | 53 | | | | |
| **T6363-1620** | 25 | 1 | | | -1620 | 6.22 | 158 | 3.62 | 92 | 2.20 | 56 | | | | |
| **T6363-2020** | 31 | 1.1/4 | | | -2020 | 7.24 | 184 | 4.57 | 116 | 2.64 | 67 | | | | |
| **T6363-2024** | 31 | 1.1/4 | | | -2024 | 6.93 | 176 | 4.25 | 108 | 2.99 | 76 | | | | |
| **T6363-2424** | 38 | 1.1/2 | | | -2424 | 8.66 | 220 | 5.20 | 132 | 3.03 | 77 | | | | |

## SPECIAL FLANGE — T6364

**RYCO CODE 62C D-RING FLANGE**
**67.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6364-1212** | 19 | 3/4 | | | -1212 | 5.00 | 127 | 2.95 | 75 | 2.05 | 52 | | | | |
| **T6364-1216** | 19 | 3/4 | | | -1216 | 5.16 | 131 | 3.11 | 79 | 2.09 | 53 | | | | |
| **T6364-1616** | 25 | 1 | | | -1616 | 6.18 | 157 | 3.58 | 91 | 2.09 | 53 | | | | |
| **T6364-1620** | 25 | 1 | | | -1620 | 6.22 | 158 | 3.62 | 92 | 2.20 | 56 | | | | |
| **T6364-2020** | 31 | 1.1/4 | | | -2020 | 7.13 | 181 | 4.45 | 113 | 2.64 | 67 | | | | |
| **T6364-2024** | 31 | 1.1/4 | | | -2024 | 6.93 | 176 | 4.25 | 108 | 2.99 | 76 | | | | |

## SPECIAL FLANGE — T6374

**RYCO CODE 62C D-RING FLANGE**
**67.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6374-1212** | 19 | 3/4 | | | -1212 | 4.29 | 109 | 2.24 | 57 | 2.44 | 62 | | | | |
| **T6374-1216** | 19 | 3/4 | | | -1216 | 4.29 | 109 | 2.24 | 57 | 2.60 | 66 | | | | |
| **T6374-1616** | 25 | 1 | | | -1616 | 5.28 | 134 | 2.68 | 68 | 2.83 | 72 | | | | |
| **T6374-1620** | 25 | 1 | | | -1620 | 5.39 | 137 | 2.80 | 71 | 2.95 | 75 | | | | |
| **T6374-2020** | 31 | 1.1/4 | | | -2020 | 6.02 | 153 | 3.35 | 85 | 3.27 | 83 | | | | |
| **T6374-2024** | 31 | 1.1/4 | | | -2024 | 6.18 | 157 | 3.50 | 89 | 3.35 | 85 | | | | |

## SPECIAL FLANGE — T6460

**SAE CODE 62 FLANGE**
**60° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6460-1212** | 19 | 3/4 | | | -1212 | 5.28 | 134 | 3.23 | 82 | 1.42 | 36 | | | | |
| **T6460-1216** | 19 | 3/4 | | | -1216 | 5.28 | 134 | 3.23 | 82 | 1.50 | 38 | | | | |
| **T6460-1616** | 25 | 1 | | | -1616 | 6.46 | 164 | 3.86 | 98 | 1.73 | 44 | | | | |
| **T6460-1620** | 25 | 1 | | | -1620 | 6.50 | 165 | 3.90 | 99 | 1.81 | 46 | | | | |
| **T6460-2020** | 31 | 1.1/4 | | | -2020 | 6.69 | 170 | 4.02 | 102 | 1.97 | 50 | | | | |
| **T6460-2024** | 31 | 1.1/4 | | | -2024 | 7.60 | 193 | 4.92 | 125 | 2.28 | 58 | | | | |
| **T6460-2424** | 38 | 1.1/2 | | | -2424 | 9.61 | 244 | 6.14 | 156 | 2.80 | 71 | | | | |
| **T6460-2432** | 38 | 1.1/2 | | | -2432 | 9.76 | 248 | 6.30 | 160 | 3.11 | 79 | | | | |
| **T6460-3232** | 51 | 2 | | | -3232 | 12.83 | 326 | 8.70 | 221 | 3.98 | 101 | | | | |


# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

## SPECIAL FLANGE — T6463

**RYCO CODE 62C FLANGE**
**60° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6463-1212** | 19 | 3/4 | | | -1212 | 5.28 | 134 | 3.23 | 82 | 1.81 | 46 | | | | |
| **T6463-1216** | 19 | 3/4 | | | -1216 | 5.51 | 140 | 3.46 | 88 | 1.65 | 42 | | | | |
| **T6463-1616** | 25 | 1 | | | -1616 | 6.50 | 165 | 3.90 | 99 | 1.85 | 47 | | | | |
| **T6463-1620** | 25 | 1 | | | -1620 | 6.69 | 170 | 4.09 | 104 | 1.93 | 49 | | | | |
| **T6463-2020** | 31 | 1.1/4 | | | -2020 | 7.52 | 191 | 4.84 | 123 | 2.20 | 56 | | | | |
| **T6463-2024** | 31 | 1.1/4 | | | -2024 | 7.20 | 183 | 4.53 | 115 | 2.60 | 66 | | | | |
| **T6463-2424** | 38 | 1.1/2 | | | -2424 | 9.17 | 233 | 5.71 | 145 | 2.68 | 68 | | | | |

## SPECIAL FLANGE — T6464

**RYCO CODE 62C D-RING FLANGE**
**60° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6464-1212** | 19 | 3/4 | | | -1212 | 5.35 | 136 | 3.31 | 84 | 1.65 | 42 | | | | |
| **T6464-1216** | 19 | 3/4 | | | -1216 | 5.35 | 136 | 3.31 | 84 | 1.65 | 42 | | | | |
| **T6464-1616** | 25 | 1 | | | -1616 | 6.42 | 163 | 3.82 | 97 | 1.85 | 47 | | | | |
| **T6464-1620** | 25 | 1 | | | -1620 | 6.57 | 167 | 3.98 | 101 | 1.93 | 49 | | | | |
| **T6464-2020** | 31 | 1.1/4 | | | -2020 | 7.48 | 190 | 4.80 | 122 | 2.20 | 56 | | | | |
| **T6464-2024** | 31 | 1.1/4 | | | -2024 | 8.43 | 214 | 5.75 | 146 | 2.60 | 66 | | | | |

## SPECIAL FLANGE — T6375

**RYCO CODE 62K FLANGE**
**90° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6375-1616** | 25 | 1 | | | -1616 | 6.02 | 153 | 3.43 | 87 | 3.54 | 90 | | | | |
| **T6375-1620** | 25 | 1 | | | -1620 | 6.02 | 153 | 3.43 | 87 | 3.94 | 100 | | | | |
| **T6375-2016** | 31 | 1.1/4 | | | -2016 | 6.42 | 163 | 3.74 | 95 | 3.54 | 90 | | | | |
| **T6375-2020** | 31 | 1.1/4 | | | -2020 | 7.83 | 199 | 5.16 | 131 | 4.72 | 120 | | | | |
| **T6375-2024** | 31 | 1.1/4 | | | -2024 | 7.83 | 199 | 5.16 | 131 | 4.72 | 120 | | | | |
| **T6375-2420** | 38 | 1.1/2 | | | -2420 | 8.76 | 223 | 5.31 | 135 | 5.12 | 130 | | | | |
| **T6375-2424** | 38 | 1.1/2 | | | -2424 | 8.86 | 225 | 5.43 | 138 | 5.51 | 140 | | | | |
| **T6375-2432** | 38 | 1.1/2 | | | -2432 | 8.86 | 225 | 5.43 | 138 | 6.30 | 160 | | | | |
| **T6375-3224** | 51 | 2 | | | -3224 | 10.42 | 265 | 6.30 | 160 | 6.89 | 175 | | | | |
| **T6375-3232** | 51 | 2 | | | -3232 | 10.94 | 278 | 6.81 | 173 | 7.09 | 180 | | | | |

## SPECIAL FLANGE — T6370

**SAE CODE 62 FLANGE**
**90° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6370-1212** | 19 | 3/4 | | | -1212 | 4.29 | 109 | 2.24 | 57 | 2.20 | 56 | | | | |
| **T6370-1216** | 19 | 3/4 | | | -1216 | 4.29 | 109 | 2.24 | 57 | 2.40 | 61 | | | | |
| **T6370-1612** | 25 | 1 | | | -1612 | 4.96 | 126 | 2.36 | 60 | 2.20 | 56 | | | | |
| **T6370-1616** | 25 | 1 | | | -1616 | 5.28 | 134 | 2.68 | 68 | 2.76 | 70 | | | | |
| **T6370-1620** | 25 | 1 | | | -1620 | 5.35 | 136 | 2.76 | 70 | 2.80 | 71 | | | | |
| **T6370-2016** | 31 | 1.1/4 | | | -2016 | 5.79 | 147 | 3.11 | 79 | 2.76 | 70 | | | | |
| **T6370-2020** | 31 | 1.1/4 | | | -2020 | 6.14 | 156 | 3.46 | 88 | 3.15 | 80 | | | | |
| **T6370-2024** | 31 | 1.1/4 | | | -2024 | 6.18 | 157 | 3.50 | 89 | 3.39 | 86 | | | | |
| **T6370-2424** | 38 | 1.1/2 | | | -2424 | 7.36 | 187 | 3.90 | 99 | 3.86 | 98 | | | | |
| **T6370-2432** | 38 | 1.1/2 | | | -2432 | 7.56 | 192 | 4.09 | 104 | 4.09 | 104 | | | | |
| **T6370-3232** | 51 | 2 | | | -3232 | 10.63 | 270 | 6.50 | 165 | 5.16 | 131 | | | | |


# ONE-PIECE COUPLINGS

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

## SPECIAL FLANGE — T6373

**RYCO CODE 62C FLANGE**
**90° BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6373-1212** | 19 | 3/4 | | | -1212 | 4.33 | 110 | 2.28 | 58 | 2.44 | 62 | | | | |
| **T6373-1216** | 19 | 3/4 | | | -1216 | 4.33 | 110 | 2.28 | 58 | 2.56 | 65 | | | | |
| **T6373-1616** | 25 | 1 | | | -1616 | 5.28 | 134 | 2.68 | 68 | 2.91 | 74 | | | | |
| **T6373-1620** | 25 | 1 | | | -1620 | 5.28 | 134 | 2.68 | 68 | 2.95 | 75 | | | | |
| **T6373-2020** | 31 | 1.1/4 | | | -2020 | 6.10 | 155 | 3.43 | 87 | 3.27 | 83 | | | | |
| **T6373-2024** | 31 | 1.1/4 | | | -2024 | 6.18 | 157 | 3.50 | 89 | 3.35 | 85 | | | | |
| **T6373-2424** | 38 | 1.1/2 | | | -2424 | 7.68 | 195 | 4.21 | 107 | 3.94 | 100 | | | | |
| **T6373-3232** | 51 | 2 | | | -3232 | 9.72 | 247 | 5.59 | 142 | 5.24 | 133 | | | | |

## SPECIAL FLANGE — T6936

**RYCO CODE 62K FLANGE**
**100° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6936-2020** | 31 | 1.1/4 | | | -2020 | 7.40 | 188 | 4.72 | 120 | 4.92 | 125 | | | | |
| **T6936-3232** | 51 | 2 | | | -3232 | 9.84 | 250 | 5.71 | 145 | 7.87 | 200 | | | | |

## SPECIAL FLANGE — T6932

**RYCO CODE 62K FLANGE**
**105° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6932-2424** | 38 | 1.1/2 | | | -2424 | 7.32 | 186 | 3.90 | 99 | 6.18 | 157 | | | | |

## SPECIAL FLANGE — T6930

**SAE CODE 62 FLANGE**
**110° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6930-2424** | 38 | 1.1/2 | | | -2424 | 9.02 | 229 | 5.59 | 142 | 4.69 | 119 | | | | |
| **T6930-2432** | 38 | 1.1/2 | | | -2432 | 9.09 | 231 | 5.63 | 143 | 4.80 | 122 | | | | |
| **T6930-3232** | 51 | 2 | | | -3232 | 10.28 | 261 | 6.14 | 156 | 6.02 | 153 | | | | |

## SPECIAL FLANGE — T6933

**RYCO CODE 62C FLANGE**
**110° TUBE BEND**
O RING NOT SUPPLIED


CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T6933-2424** | 38 | 1.1/2 | | | -2424 | 9.02 | 229 | 5.55 | 141 | 4.72 | 120 | | | | |
| **T6933-3232** | 51 | 2 | | | -3232 | 9.84 | 250 | 5.71 | 145 | 5.35 | 136 | | | | |

## HAMMER UNION — T61502

**FIGURE 1502**
**HAMMER/WING MALE (WITH NUT)**
**STANDARD SERVICE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | | |
| **T61502-2432** | 38 | 1.1/2 | 4.1/8 | | -2432 | 7.83 | 199 | 4.41 | 112 | | | | | | |
| **T61502-3232** | 51 | 2 | 4.1/8 | | -3232 | 8.70 | 221 | 4.57 | 116 | | | | | | |

## T6000 SERIES ONE-PIECE CRIMP COUPLINGS

| HAMMER UNION | T61501 |
|---|---|

FIGURE 1502
HAMMER/WING FEMALE (WITH SEAL)
STANDARD SERVICE




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | | |
| **T61501-2432** | 38 | 1.1/2 | 4.1/8 | | -2432 | 7.09 | 180 | 3.66 | 93 | | | | | | |
| **T61501-3232** | 51 | 2 | 4.1/8 | | -3232 | 7.95 | 202 | 3.82 | 97 | | | | | | |

# T7000 SERIES ONE-PIECE CRIMP COUPLINGS




## HOSE COMPATIBILITY FOR T7000 SERIES

**NON-SKIVE**
For Ryco Hose Series H3000D/S (sizes -20 to -32).
For Ryco Hose Series H4000D/S (sizes -06 to -32).
For Ryco Hose Series H5000D/S (sizes -06 to -24).
For Ryco Hose Series H6000D/S (sizes -06 to -20).
For Ryco Hose Series T2D/S/C (sizes -06 to -32).
For Ryco Hose Series E2, HSPD (sizes -06 to -16).
For Ryco Hose Series H12D/S (sizes -06 to -20).
For Ryco Hose Series R4SH, HSHD (sizes -20 to -32).
For Ryco Hose Series T2, TXA2D, SURVIVOR/2 (sizes -06 to -32).
For Ryco Hose Series D2B (sizes -24 to -32).
For Ryco Hose Series R4SP (cover must be skived) (all sizes).

**SKIVE**
For Ryco Hose Series R4SPD (cover must be skived) all sizes.

## BSPT — T7010


**BSPT MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T7010-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.44 | 62 | 1.30 | 33 | | | | | 11/16 | |
| **T7010-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.64 | 67 | 1.57 | 40 | | | | | 7/8 | 22 |
| **T7010-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.83 | 72 | 1.61 | 41 | | | | | 1.1/16 | 27 |
| **T7010-1616** | 25 | 1 | 1" -11 | | -1616 | 3.58 | 91 | 1.89 | 48 | | | | | 1.3/8 | 35 |
| **T7010-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 4.13 | 105 | 2.09 | 53 | | | | | 1.3/4 | |
| **T7010-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 4.37 | 111 | 2.17 | 55 | | | | | 2 | 50 |
| **T7010-3232** | 51 | 2 | 2" -11 | | -3232 | 5.08 | 129 | 2.60 | 66 | | | | | 2.1/2 | |

## BSPT — T7014

**BSPT MALE HEAVY**
**60° SEAT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | | |
| **T7014-1616** | 25 | 1 | 1" -11 | | -1616 | 3.57 | 91 | 1.88 | 48 | | | | | | 36 |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### BSPP — T7013


**BSPP MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | inch | mm | inch | mm | | | | | inch | mm |
| **T7013-0606** | 10 | 3/8 | 3/8" -19 | -0606 | 2.32 | 59 | 1.14 | 29 | | | | | 7/8 | 22 |
| **T7013-0808** | 12 | 1/2 | 1/2" -14 | -0808 | 2.40 | 61 | 1.34 | 34 | | | | | 1.1/16 | 27 |
| **T7013-0810** | 12 | 1/2 | 5/8" -14 | -0810 | 2.52 | 64 | 1.42 | 36 | | | | | 1.3/16 | 30 |
| **T7013-1212** | 19 | 3/4 | 3/4" -14 | -1212 | 2.76 | 70 | 1.54 | 39 | | | | | 1.1/4 | 32 |
| **T7013-1216** | 19 | 3/4 | 3/4" -14 | -1216 | 2.91 | 74 | 1.69 | 43 | | | | | 1.5/8 | 41 |
| **T7013-1616** | 25 | 1 | 1" -11 | -1616 | 3.46 | 88 | 1.77 | 45 | | | | | 1.5/8 | 41 |
| **T7013-2020** | 31 | 1.1/4 | 1.1/4" -11 | -2020 | 4.06 | 103 | 2.01 | 51 | | | | | 2 | 50 |
| **T7013-2424** | 38 | 1.1/2 | 1.1/2" -11 | -2424 | 4.37 | 111 | 2.13 | 54 | | | | | 2.3/16 | 55 |
| **T7013-3232** | 51 | 2 | 2" -11 | -3232 | 5.12 | 130 | 2.64 | 67 | | | | | 2.3/4 | 70 |

### BSPP — T7020


**BSPP FEMALE**
**60 ° CONE**




| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T7020-0606** | 10 | 3/8 | 3/8" -19 | -0606 | 2.20 | 56 | 1.06 | 27 | | | 7/8 | 22 | 5/8 | 16 |
| **T7020-0808** | 12 | 1/2 | 1/2" -14 | -0808 | 2.20 | 56 | 1.10 | 28 | | | 1.1/16 | 27 | 11/16 | |
| **T7020-1010** | 16 | 5/8 | 5/8" -14 | -1010 | 2.40 | 61 | 1.14 | 29 | | | 1.3/16 | 30 | 7/8 | 22 |
| **T7020-1212** | 19 | 3/4 | 3/4" -14 | -1212 | 2.52 | 62 | 1.30 | 31 | | | 1.1/4 | 32 | 1.1/16 | 27 |
| **T7020-1216** | 19 | 3/4 | 1" -11 | -1216 | 2.76 | 68 | 1.54 | 37 | | | 1.1/2 | 38 | 1.1/16 | 27 |
| **T7020-1616** | 25 | 1 | 1" -11 | -1616 | 3.15 | 80 | 1.46 | 36 | | | 1.1/2 | 38 | 1.1/4 | 32 |
| **T7020-2016** | 31 | 1.1/4 | 1" -11 | -2016 | 3.74 | 95 | 1.73 | 44 | | | 1.1/2 | 38 | 1.5/8 | 41 |
| **T7020-2020** | 31 | 1.1/4 | 1.1/4" -11 | -2020 | 3.78 | 96 | 1.77 | 45 | | | 2 | 50 | 1.5/8 | 41 |
| **T7020-2424** | 38 | 1.1/2 | 1.1/2" -11 | -2424 | 3.98 | 101 | 1.77 | 45 | | | 2.3/16 | 55 | 2 | 50 |
| **T7020-3232** | 51 | 2 | 2" -11 | -3232 | 4.61 | 117 | 2.13 | 54 | | | 2.3/4 | 70 | 2.1/2 | |

## BSPP — T7022


**BSPP FEMALE**
**60 ° CONE**
**HEAVY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T7022-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.28 | 58 | 1.22 | 31 | | | 1 | | 1 | |
| **T7022-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.56 | 65 | 1.34 | 34 | | | 1.1/4 | 32 | 1.1/8 | |
| **T7022-1616** | 25 | 1 | 1" -11 | | -1616 | 3.15 | 80 | 1.46 | 37 | | | 1.1/2 | 38 | 1.1/2 | 38 |
| **T7022-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 3.78 | 96 | 1.73 | 44 | | | 2 | 50 | 1.3/4 | |

## BSPP — T7060


**BSPP FEMALE**
**60° CONE**
**45° ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T7060-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 1.93 | 49 | 0.83 | 21 | 0.71 | 18 | 1.1/16 | 27 | 7/8 | 22 |
| **T7060-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.17 | 55 | 0.98 | 25 | 0.79 | 20 | 1.1/4 | 32 | 1.1/16 | 27 |
| **T7060-1616** | 25 | 1 | 1" -11 | | -1616 | 2.80 | 71 | 1.10 | 28 | 1.02 | 26 | 1.1/2 | 38 | 1.5/16 | |
| **T7060-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 3.15 | 80 | 1.10 | 28 | 1.14 | 29 | 2 | 50 | 1.7/8 | |

## BSPP — T7050

**BSPP FEMALE**
**60° CONE**
**90° ELBOW**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T7050-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.05 | 52 | 0.91 | 23 | 1.10 | 28 | 7/8 | 22 | 3/4 | 19 |
| **T7050-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.24 | 57 | 1.14 | 29 | 1.22 | 31 | 1.1/16 | 27 | 7/8 | 22 |
| **T7050-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.40 | 61 | 1.22 | 31 | 1.42 | 36 | 1.1/4 | 32 | 1.1/16 | 27 |
| **T7050-1616** | 25 | 1 | 1" -11 | | -1616 | 2.95 | 75 | 1.26 | 32 | 1.77 | 45 | 1.1/2 | 38 | 1.5/16 | |
| **T7050-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 3.74 | 95 | 1.69 | 43 | 2.05 | 52 | 2 | 50 | 1.7/8 | |
| **T7050-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 4.61 | 117 | 2.36 | 60 | 2.32 | 59 | 2.3/16 | 55 | 2.1/2 | |
| **T7050-3232** | 51 | 2 | 2" -11 | | -3232 | 4.69 | 119 | 2.20 | 56 | 2.44 | 62 | 2.3/4 | 70 | 2.1/2 | |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### BSPP — T7270


**BSPP FEMALE**
**60° CONE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7270-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.76 | 70 | 1.61 | 41 | 0.71 | 18 | 7/8 | 22 | | |
| **T7270-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 3.07 | 78 | 1.97 | 50 | 0.87 | 22 | 1.1/16 | 27 | | |
| **T7270-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 4.33 | 108 | 3.11 | 77 | 1.14 | 29 | 1.1/4 | 32 | | |
| **T7270-1616** | 25 | 1 | 1" -11 | | -1616 | 5.04 | 128 | 3.35 | 83 | 1.65 | 42 | 1.1/2 | 38 | | 32 |
| **T7270-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 8.50 | 216 | 6.50 | 165 | 1.81 | 46 | 2 | 50 | | |
| **T7270-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 6.85 | 174 | 4.65 | 118 | 2.05 | 52 | 2.3/16 | 55 | | |
| **T7270-3232** | 51 | 2 | 2" -11 | | -3232 | 8.39 | 213 | 5.91 | 150 | 2.56 | 65 | 2.3/4 | 70 | | |

### BSPP — T7260


**BSPP FEMALE**
**60° CONE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7260-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.52 | 64 | 1.38 | 35 | 1.30 | 33 | 7/8 | 22 | | |
| **T7260-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.56 | 65 | 1.50 | 38 | 1.77 | 45 | 1.1/16 | 27 | | |
| **T7260-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.39 | 88 | 2.17 | 57 | 2.32 | 59 | 1.1/4 | 32 | | |
| **T7260-1616** | 25 | 1 | 1" -11 | | -1616 | 4.37 | 111 | 2.68 | 74 | 3.07 | 78 | 1.1/2 | 38 | | |
| **T7260-2016** | 31 | 1.1/4 | 1" -11 | | -2016 | 5.55 | 141 | 3.54 | 90 | 3.03 | 77 | 1.1/2 | 38 | | |
| **T7260-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 5.28 | 134 | 3.23 | 82 | 3.58 | 91 | 2 | 50 | | |
| **T7260-2424** | 38 | 1.1/2 | 1.1/2" -11 | | -2424 | 6.06 | 154 | 3.86 | 98 | 4.13 | 105 | 2.3/16 | 55 | | |
| **T7260-3232** | 51 | 2 | 2" -11 | | -3232 | 7.87 | 200 | 5.39 | 137 | 5.20 | 132 | 2.3/4 | 70 | | |

## BSPP — T7210


**BSPP FEMALE**
**60° CONE**
**90° LONG TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7210-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.54 | 88 | 2.32 | 57 | 3.74 | 95 | 1.1/4 | 32 | | |
| **T7210-1616** | 25 | 1 | 1" -11 | | -1616 | 4.25 | 108 | 2.56 | 74 | 4.57 | 116 | 1.1/2 | 38 | | |
| **T7210-2020** | 31 | 1.1/4 | 1.1/4" -11 | | -2020 | 5.94 | 151 | 3.94 | 100 | 5.59 | 142 | | | | |

## BSPO — T7027


**BSPP FEMALE O RING**
**60° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T7027-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.52 | 62 | 1.30 | 31 | | | 1.1/4 | 32 | 1.1/16 | 27 |
| **T7027-1616** | 25 | 1 | 1" -11 | | -1616 | 3.15 | 80 | 1.46 | 36 | | | 1.1/2 | 38 | 1.1/4 | 32 |

## BSPO — T7057

**BSPP FEMALE O RING**
**60° CONE**
**90° ELBOW**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T7057-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.40 | 61 | 1.18 | 30 | 1.50 | 38 | 1.1/4 | 32 | 1.1/16 | 27 |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### BSPO — T7277


**BSPP FEMALE O RING**
**60° CONE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7277-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 3.07 | 78 | 1.97 | 50 | 0.87 | 22 | 1.1/16 | 27 | | |
| **T7277-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 4.33 | 108 | 3.11 | 77 | 1.14 | 29 | 1.1/4 | 32 | | |
| **T7277-1616** | 25 | 1 | 1" -11 | | -1616 | 5.00 | 127 | 3.31 | 83 | 1.38 | 35 | 1.1/2 | 38 | | |

### BSPO — T7267


**BSPP FEMALE O RING**
**60° CONE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7267-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.72 | 69 | 1.61 | 41 | 1.73 | 44 | 1.1/16 | 27 | | |
| **T7267-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.54 | 88 | 2.32 | 57 | 2.32 | 59 | 1.1/4 | 32 | | |
| **T7267-1616** | 25 | 1 | 1" -11 | | -1616 | 4.57 | 116 | 2.87 | 74 | 2.95 | 75 | 1.1/2 | 38 | | |

### NPTF — T7090


**NPTF MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T7090-0604** | 10 | 3/8 | 1/4" -18 | | -0604 | 2.44 | 62 | 1.30 | 33 | | | | | 5/8 | 16 |
| **T7090-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 2.44 | 62 | 1.30 | 33 | | | | | 11/16 | |
| **T7090-0806** | 12 | 1/2 | 3/8" -18 | | -0806 | 2.44 | 62 | 1.38 | 35 | | | | | 11/16 | |
| **T7090-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.64 | 67 | 1.57 | 40 | | | | | 7/8 | 22 |
| **T7090-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.83 | 72 | 1.61 | 41 | | | | | 1.1/16 | 27 |
| **T7090-1612** | 25 | 1 | 3/4" -14 | | -1612 | 3.39 | 86 | 1.69 | 43 | | | | | 1.3/8 | 35 |
| **T7090-1616** | 25 | 1 | 1" -11,5 | | -1616 | 3.58 | 91 | 1.89 | 48 | | | | | 1.3/8 | 35 |
| **T7090-2016** | 31 | 1.1/4 | 1" -11,5 | | -2016 | 4.09 | 104 | 2.05 | 52 | | | | | 1.3/4 | |
| **T7090-2020** | 31 | 1.1/4 | 1.1/4" -11,5 | | -2020 | 4.13 | 105 | 2.09 | 53 | | | | | 1.3/4 | |
| **T7090-2424** | 38 | 1.1/2 | 1.1/2" -11,5 | | -2424 | 4.37 | 111 | 2.17 | 55 | | | | | 2 | 50 |
| **T7090-3232** | 51 | 2 | 2" -11,5 | | -3232 | 5.08 | 129 | 2.60 | 66 | | | | | 2.1/2 | |

## NPTF — T7091


**NPTF MALE EXTENDED**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | |
| **T7091-3232** | 51 | 2 | 2" -11,5 | | -3232 | 6.69 | 170 | 4.21 | 107 | | | | | 2.1/2 | |

## NPSM — T7020N


**NPSM FEMALE**
**60° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T7020N-2020** | 31 | 1.1/4 | 1.1/4" -11,5 | | -2020 | 3.66 | 93 | 1.61 | 41 | | | 1.7/8 | | 1.3/4 | |
| **T7020N-2424** | 38 | 1.1/2 | 1.1/2" -11,5 | | -2424 | 4.02 | 102 | 1.77 | 45 | | | 2.1/4 | 57 | 2 | 50 |
| **T7020N-3232** | 51 | 2 | 2" -11,5 | | -3232 | 4.61 | 117 | 2.13 | 54 | | | 2.3/4 | 70 | 2.1/2 | |

## JIC — T7030

**JIC 37°**
**CONE MALE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T7030-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.40 | 61 | 1.26 | 32 | | | | | 5/8 | 16 |
| **T7030-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.52 | 64 | 1.46 | 37 | | | | | 3/4 | 19 |
| **T7030-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.64 | 67 | 1.54 | 39 | | | | | 15/16 | 24 |
| **T7030-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.87 | 73 | 1.57 | 40 | | | | | 15/16 | 24 |
| **T7030-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.95 | 75 | 1.73 | 44 | | | | | 1.1/8 | |
| **T7030-1219** | 19 | 3/4 | 1.3/16" -12 | | -1219 | 2.95 | 75 | 1.77 | 45 | | | | | 1.1/4 | 32 |
| **T7030-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 2.99 | 76 | 1.77 | 45 | | | | | 1.3/8 | 35 |
| **T7030-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 3.54 | 90 | 1.85 | 47 | | | | | 1.3/8 | 35 |
| **T7030-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 4.09 | 104 | 2.05 | 52 | | | | | 1.3/4 | |
| **T7030-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 4.45 | 113 | 2.24 | 57 | | | | | 2 | 50 |
| **T7030-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 5.35 | 136 | 2.87 | 73 | | | | | 2.1/2 | |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### JIC — T7031


JIC 37° CONE MALE
METRIC HEX ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | | mm |
| **T7031-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 2.99 | 76 | 1.77 | 45 | | | | | | 36 |
| **T7031-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 3.54 | 90 | 1.85 | 47 | | | | | | 36 |

### JSEAL™ / JIC — T7040


JSEAL™ / JIC FEMALE
CONVEX SEAT




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T7040-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.01 | 51 | 0.87 | 22 | | | 11/16 | | 9/16 | 16 |
| **T7040-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.01 | 51 | 0.87 | 22 | | | 3/4 | 19 | 9/16 | |
| **T7040-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.17 | 54 | 1.02 | 25 | | | 7/8 | 22 | 9/16 | 16 |
| **T7040-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.01 | 53 | 0.94 | 25 | | | 7/8 | 22 | 11/16 | 19 |
| **T7040-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.17 | 55 | 1.06 | 27 | | | 1 | | 11/16 | |
| **T7040-0817** | 12 | 1/2 | 1.1/16" -12 | | -0817 | 2.32 | 59 | 1.22 | 31 | | | 1.1/4 | 32 | 11/16 | |
| **T7040-1012** | 16 | 5/8 | 3/4" -16 | | -1012 | 2.28 | 58 | 0.98 | 25 | | | 7/8 | 22 | 7/8 | 22 |
| **T7040-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.32 | 59 | 1.06 | 27 | | | 1 | | 7/8 | 22 |
| **T7040-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 2.48 | 63 | 1.18 | 30 | | | 1.1/4 | 32 | 7/8 | 22 |
| **T7040-1212** | 19 | 3/4 | 3/4" -16 | | -1212 | 2.40 | 59 | 1.18 | 28 | | | 7/8 | 22 | 1.1/16 | 27 |
| **T7040-1214** | 19 | 3/4 | 7/8" -14 | | -1214 | 2.56 | 63 | 1.34 | 32 | | | 1 | | 1.1/16 | 27 |
| **T7040-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.44 | 60 | 1.22 | 29 | | | 1.1/4 | 32 | 1.1/16 | 27 |
| **T7040-1219** | 19 | 3/4 | 1.3/16" -12 | | -1219 | 2.44 | 62 | 1.22 | 31 | | | 1.3/8 | 35 | 1.1/8 | |
| **T7040-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 2.72 | 67 | 1.50 | 36 | | | 1.1/2 | 38 | 1.1/16 | 27 |
| **T7040-1617** | 25 | 1 | 1.1/16" -12 | | -1617 | 3.03 | 77 | 1.34 | 37 | | | 1.1/4 | 32 | 1.1/4 | 32 |
| **T7040-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 3.07 | 78 | 1.38 | 33 | | | 1.1/2 | 38 | 1.1/4 | 32 |
| **T7040-1626** | 25 | 1 | 1.5/8"-12 | | -1626 | 3.31 | 84 | 1.61 | 38 | | | 2 | 50 | 1.1/4 | 32 |
| **T7040-2021** | 31 | 1.1/4 | 1.5/16" -12 | | -2021 | 3.70 | 94 | 1.69 | 43 | | | 1.1/2 | 38 | 1.5/8 | 41 |
| **T7040-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 3.70 | 94 | 1.69 | 43 | | | 2 | 50 | 1.5/8 | 41 |
| **T7040-2030** | 31 | 1.1/4 | 1.7/8"-12 | | -2030 | 4.06 | 103 | 2.05 | 52 | | | 2.1/4 | 57 | 1.5/8 | 41 |
| **T7040-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 4.29 | 109 | 2.09 | 53 | | | 2.1/4 | 57 | 2 | 50 |
| **T7040-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 4.88 | 124 | 2.44 | 62 | | | 2.7/8 | 73 | 2.1/2 | |

## JSEAL™ / JIC — T7041


JSEAL™ / JIC FEMALE
CONVEX SEAT
METRIC NUT ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | mm |
| **T7041-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.52 | 64 | 1.34 | 34 | 1.02 | 26 | 3/4 | 19 | | 16 |

## JIC — T7039


JIC
37° CONE
MALE SWIVEL JOINT




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | | |
| **T7039-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 3.23 | 82 | 2.09 | 53 | | | 1 | 0 | | |
| **T7039-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 3.39 | 86 | 2.32 | 59 | | | | 36 | | |
| **T7039-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.74 | 95 | 2.56 | 65 | | | 1.1/2 | 38 | | |
| **T7039-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.92 | 125 | 3.23 | 82 | | | | 46 | | |

## JIC - HEAVY DUTY — T7045

JIC
37° FEMALE HIGH-PRESSURE





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T7045-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 2.99 | 76 | 1.30 | 33 | | | 1.5/8 | 41 | 1.1/4 | 32 |
| **T7045-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 3.62 | 92 | 1.57 | 40 | | | 2 | 50 | 1.3/4 | |
| **T7045-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 4.45 | 113 | 2.20 | 56 | | | 2.1/4 | 57 | 2 | 50 |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### JSEAL™ / JIC — T7080


**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**45° ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T7080-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 1.93 | 49 | 0.83 | 21 | 0.63 | 16 | 7/8 | 22 | 7/8 | 22 |
| **T7080-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.56 | 65 | 1.50 | 38 | 0.67 | 17 | 1 | | 7/8 | 22 |
| **T7080-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.17 | 55 | 0.98 | 25 | 0.67 | 17 | 1.1/4 | 32 | 1.1/16 | 27 |
| **T7080-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 2.80 | 71 | 1.10 | 28 | 0.83 | 21 | 1.1/2 | 38 | 1.5/16 | |

### JSEAL™ / JIC — T7070


**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**90° ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **T7070-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.24 | 57 | 1.14 | 29 | 1.22 | 31 | 1 | | 7/8 | 22 |
| **T7070-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.40 | 61 | 1.22 | 31 | 1.26 | 32 | 1.1/4 | 32 | 1.1/16 | 27 |
| **T7070-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 2.95 | 75 | 1.26 | 32 | 1.50 | 38 | 1.1/2 | 38 | 1.5/16 | |

### METRIC - DKOL — T7250


**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7250-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 3.43 | 87 | 2.13 | 54 | 0.94 | 24 | 1.1/4 | 32 | | |
| **T7250-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 4.33 | 108 | 3.11 | 77 | 1.10 | 28 | 1.1/4 | 32 | | |
| **T7250-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 4.72 | 118 | 3.50 | 87 | 1.50 | 38 | 1.1/2 | 38 | | |
| **T7250-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 5.00 | 127 | 3.31 | 82 | 1.38 | 35 | 1.1/2 | 38 | | |
| **T7250-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 5.94 | 151 | 3.94 | 100 | 1.54 | 39 | 2 | 50 | | |
| **T7250-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 7.24 | 184 | 5.04 | 128 | 1.97 | 50 | 2.1/4 | 57 | | |
| **T7250-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 8.94 | 227 | 6.46 | 164 | 2.48 | 63 | 2.7/8 | 73 | | |

## JSEAL™ / JIC — T7251


JSEAL™ / JIC
FEMALE CONVEX SEAT
45° TUBE BEND
METRIC NUT ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7251-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.68 | 68 | 1.50 | 38 | 0.55 | 14 | 3/4 | 19 | | |

## JIC — T7243


JSEAL™ / JIC FEMALE
CONVEX SEAT
90° SHORT TUBE BEND




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7243-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.40 | 61 | 1.22 | 31 | 0.91 | 23 | 11/16 | | | |
| **T7243-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.80 | 71 | 1.69 | 43 | 1.14 | 29 | 7/8 | 22 | | |
| **T7243-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 3.39 | 86 | 2.09 | 53 | 1.34 | 34 | 1 | | | |
| **T7243-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.82 | 95 | 2.60 | 64 | 1.85 | 47 | 1.1/4 | 32 | | |
| **T7243-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.88 | 124 | 3.19 | 79 | 2.28 | 58 | 1.1/2 | 38 | | |

## JSEAL™ / JIC — T7244

JSEAL™ / JIC FEMALE
CONVEX SEAT
90° SHORT TUBE BEND
METRIC NUT ONLY





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7244-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.40 | 61 | 1.22 | 31 | 0.91 | 23 | 3/4 | 19 | | |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### JIC — T7240


JSEAL™ / JIC FEMALE
CONVEX SEAT
90° TUBE BEND




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7240-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.52 | 64 | 1.34 | 34 | 1.02 | 26 | 11/16 | | | |
| **T7240-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.56 | 65 | 1.38 | 35 | 1.18 | 30 | 7/8 | 22 | | |
| **T7240-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.72 | 69 | 1.61 | 41 | 1.50 | 38 | 7/8 | 22 | | |
| **T7240-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.72 | 69 | 1.61 | 41 | 1.61 | 41 | 1 | | | |
| **T7240-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 3.07 | 78 | 1.77 | 45 | 1.85 | 47 | 1 | | | |
| **T7240-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 3.07 | 78 | 1.77 | 45 | 1.89 | 48 | 1.1/4 | 32 | | |
| **T7240-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.54 | 88 | 2.32 | 57 | 2.24 | 57 | 1.1/4 | 32 | | |
| **T7240-1221** | 19 | 3/4 | 1.5/16" -12 | | -1221 | 3.54 | 88 | 2.32 | 57 | 2.80 | 71 | 1.1/2 | 38 | | |
| **T7240-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.37 | 111 | 2.68 | 74 | 2.83 | 72 | 1.1/2 | 38 | | |
| **T7240-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 5.94 | 151 | 3.94 | 100 | 3.19 | 81 | 2 | 50 | | |
| **T7240-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 6.38 | 162 | 4.17 | 106 | 4.17 | 106 | 2.1/4 | 57 | | |
| **T7240-3240** | 51 | 2 | 2.1/2" -12 | | -3240 | 8.31 | 211 | 5.83 | 148 | 5.20 | 132 | 2.7/8 | 73 | | |

### JSEAL™ / JIC — T7241


JSEAL™ / JIC FEMALE
CONVEX SEAT
90° TUBE BEND
METRIC NUT ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7241-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.52 | 64 | 1.34 | 34 | 1.02 | 26 | 3/4 | 19 | | |

## JSEAL™ / JIC — T7245


**JIC 37° FEMALE**
**HIGH-PRESSURE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7245-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.53 | 115 | 2.83 | 72 | 2.83 | 72 | 1 5/8 | | | |
| **T7245-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 5.51 | 140 | 3.46 | 88 | 3.07 | 78 | 2 | 50 | | |
| **T7245-2430** | 38 | 1.1/2 | 1.7/8"-12 | | -2430 | 6.26 | 159 | 4.06 | 103 | 4.17 | 106 | 2.1/4 | 57 | | |

## JIC — T7280


**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**90° LONG TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7280-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.54 | 88 | 2.32 | 57 | 3.78 | 96 | 1.1/4 | 32 | | |
| **T7280-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.65 | 118 | 2.95 | 74 | 4.49 | 114 | 1.1/2 | 38 | | |
| **T7280-2026** | 31 | 1.1/4 | 1.5/8"-12 | | -2026 | 5.94 | 151 | 3.94 | 100 | 5.08 | 129 | 2 | 50 | | |

## JIC — T7044

**JIC**
**37° FEMALE SWIVEL JOINT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | | |
| **T7044-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.80 | 71 | 1.65 | 42 | | | 1 | 25 | | |
| **T7044-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.83 | 72 | 1.77 | 45 | | | | 36 | | |
| **T7044-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.03 | 77 | 1.81 | 46 | | | 1.1/2 | 38 | | |
| **T7044-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.17 | 106 | 2.48 | 63 | | | | 46 | | |


# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### JIS - BSP

### T7122

**METRIC FEMALE**
**60° CONCAVE SEAT (JIS)**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T7122-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.17 | 55 | 1.06 | 27 | | | 1.1/16 | 27 | 3/4 | 19 |
| **T7122-1012** | 16 | 5/8 | 3/4" -14 | | -1012 | 2.36 | 60 | 1.10 | 28 | | | | 36 | 1.1/16 | 27 |
| **T7122-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.40 | 61 | 1.18 | 30 | | | | 36 | 1.1/16 | 27 |
| **T7122-1616** | 25 | 1 | 1" -11 | | -1616 | 2.95 | 75 | 1.26 | 32 | | | 1.5/8 | 41 | | 36 |

### JIS - METRIC

### T7680


**METRIC FEMALE**
**60° CONCAVE SEAT (JIS)**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T7680-0618** | 10 | 3/8 | M 18X1,5 | | -0618 | 2.01 | 51 | 0.87 | 22 | | | 15/16 | 24 | | 17 |
| **T7680-0822** | 12 | 1/2 | M 22X1,5 | | -0822 | 2.17 | 55 | 1.10 | 28 | | | 1.1/16 | 27 | 7/8 | 22 |
| **T7680-0824** | 12 | 1/2 | M 24X1,5 | | -0824 | 2.17 | 55 | 1.10 | 28 | | | 1.1/4 | 32 | 7/8 | 22 |
| **T7680-1024** | 16 | 5/8 | M 24X1,5 | | -1024 | 2.28 | 58 | 1.02 | 26 | | | 1.1/4 | 32 | 7/8 | 22 |
| **T7680-1224** | 19 | 3/4 | M 24X1,5 | | -1224 | 2.28 | 58 | 1.06 | 27 | | | 1.1/4 | 32 | 1.1/16 | 27 |
| **T7680-1230** | 19 | 3/4 | M 30X1,5 | | -1230 | 2.56 | 65 | 1.34 | 34 | | | | 36 | 1.1/4 | 32 |
| **T7680-1633** | 25 | 1 | M 33X1,5 | | -1633 | 2.87 | 73 | 1.18 | 30 | | | 1.5/8 | 41 | 1.1/4 | 32 |
| **T7680-1636** | 25 | 1 | M 36X1,5 | | -1636 | 3.15 | 80 | 1.46 | 37 | | | | 46 | 1.1/2 | 38 |
| **T7680-2036** | 31 | 1.1/4 | M 36X1,5 | | -2036 | 3.50 | 89 | 1.46 | 37 | | | | 46 | 1.1/2 | 38 |
| **T7680-2042** | 31 | 1.1/4 | M 42X1,5 | | -2042 | 3.58 | 91 | 1.54 | 39 | | | 2 | 50 | 1.5/8 | 41 |
| **T7680-2442** | 38 | 1.1/2 | M 42X1,5 | | -2442 | 3.82 | 97 | 1.61 | 41 | | | 2 | 50 | | 46 |

## JOINER — T7900


JOINER




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | | | |
| **T7900-0606** | 10 | 3/8 | | 3/8 | -0606 | 2.87 | 73 | 0.59 | 15 | | | | | | |
| **T7900-0808** | 12 | 1/2 | | 1/2 | -0808 | 2.76 | 70 | 0.59 | 15 | | | | | | |
| **T7900-1212** | 19 | 3/4 | | 3/4 | -1212 | 3.07 | 78 | 0.63 | 16 | | | | | | |
| **T7900-1616** | 25 | 1 | | 1 | -1616 | 4.37 | 111 | 0.98 | 25 | | | | | | |
| **T7900-2020** | 31 | 1.1/4 | | 1.1/4 | -2020 | 5.04 | 128 | 0.94 | 24 | | | | | | |
| **T7900-2424** | 38 | 1.1/2 | | 1.1/2 | -2424 | 5.43 | 138 | 1.02 | 26 | | | | | | |
| **T7900-3232** | 51 | 2 | | 2 | -3232 | 5.98 | 152 | 1.06 | 27 | | | | | | |

## METRIC - DKOL — T7501


DKOL FEMALE
24° CONE




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T7501-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 2.72 | 67 | 1.50 | 36 | | | | 36 | 1.1/16 | 27 |
| **T7501-1636** | 25 | 1 | M 36X2 | 28 | -1636 | 3.39 | 86 | 1.69 | 39 | | | 1.5/8 | 41 | 1.1/4 | 32 |
| **T7501-2045** | 31 | 1.1/4 | M 45X2 | 35 | -2045 | 3.86 | 98 | 1.85 | 47 | | | 2 | 50 | 1.5/8 | 41 |
| **T7501-2452** | 38 | 1.1/2 | M 52X2 | 42 | -2452 | 3.58 | 91 | 1.38 | 35 | | | 2.3/8 | 60 | | |

## METRIC - DKOL — T7510

DKOL FEMALE
24° CONE
45° TUBE BEND





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7510-2452** | 38 | 1.1/2 | M 52X2 | 42 | -2452 | 6.85 | 174 | 4.65 | 118 | 1.93 | 49 | 2.3/8 | 60 | | |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### METRIC DKOL — T7520


**DKOL FEMALE**
**24° CONE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7520-2452** | 38 | 1.1/2 | M 52X2 | 42 | -2452 | 6.10 | 155 | 3.90 | 99 | 4.02 | 102 | 2.3/8 | 60 | | |

### METRIC - DKS — T7630


**DKS MALE**
**24° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | | | inch | mm |
| **T7630-2042** | 31 | 1.1/4 | M 42X2 | 30 | -2042 | 3.94 | 100 | 1.89 | 48 | | | | | | 46 |
| **T7630-2052** | 31 | 1.1/4 | M 52X2 | 38 | -2052 | 3.90 | 99 | 1.85 | 47 | | | | | 2.3/16 | 55 |

### METRIC - DKOS — T7711


**DKOS FEMALE**
**24° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T7711-0618** | 10 | 3/8 | M 18X1,5 | 10 | -0618 | 2.36 | 60 | 1.22 | 31 | | | 7/8 | 22 | 9/16 | |
| **T7711-0620** | 10 | 3/8 | M 20X1,5 | 12 | -0620 | 2.40 | 61 | 1.22 | 31 | | | 15/16 | 24 | 9/16 | |
| **T7711-0622** | 10 | 3/8 | M 22X1,5 | 14 | -0622 | 2.48 | 63 | 1.30 | 33 | | | 1.1/16 | 27 | 9/16 | |
| **T7711-0824** | 12 | 1/2 | M 24X1,5 | 16 | -0824 | 2.40 | 61 | 1.30 | 33 | | | 1.3/16 | 30 | 11/16 | |
| **T7711-1030** | 16 | 5/8 | M 30X2 | 20 | -1030 | 2.83 | 72 | 1.57 | 40 | | | | 36 | 7/8 | 22 |
| **T7711-1036** | 16 | 5/8 | M 36X2 | 25 | -1036 | 2.99 | 76 | 1.73 | 44 | | | | 46 | 7/8 | 22 |
| **T7711-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 2.87 | 71 | 1.65 | 40 | | | | 36 | 1.1/16 | 27 |
| **T7711-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 3.03 | 75 | 1.81 | 44 | | | | 46 | 1.1/16 | 27 |
| **T7711-1242** | 19 | 3/4 | M 42X2 | 30 | -1242 | 3.07 | 76 | 1.85 | 45 | | | 2 | 50 | 1.1/16 | 27 |
| **T7711-1630** | 25 | 1 | M 30X2 | 20 | -1630 | 3.35 | 85 | 1.65 | 40 | | | | 36 | 1.1/4 | 32 |
| **T7711-1636** | 25 | 1 | M 36X2 | 25 | -1636 | 3.50 | 89 | 1.81 | 42 | | | | 46 | 1.1/4 | 32 |
| **T7711-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 3.50 | 89 | 1.81 | 42 | | | 2 | 50 | 1.1/4 | 32 |
| **T7711-2042** | 31 | 1.1/4 | M 42X2 | 30 | -2042 | 3.54 | 90 | 1.50 | 38 | | | 2 | 50 | | |
| **T7711-2052** | 31 | 1.1/4 | M 52X2 | 38 | -2052 | 3.74 | 95 | 1.69 | 43 | | | 2.3/8 | 60 | | |
| **T7711-2452** | 38 | 1.1/2 | M 52X2 | 38 | -2452 | 3.94 | 100 | 1.73 | 44 | | | 2.3/8 | 60 | | |

## METRIC - DKOS | T7720


**DKOS FEMALE**
**24° CONE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7720-0824** | 12 | 1/2 | M 24X1,5 | 16 | -0824 | 3.19 | 81 | 2.09 | 53 | 0.94 | 24 | 1.3/16 | 30 | | |
| **T7720-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 4.13 | 103 | 2.91 | 72 | 1.38 | 35 | | 36 | | |
| **T7720-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 4.21 | 105 | 2.99 | 74 | 1.38 | 35 | | 46 | | |
| **T7720-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 5.12 | 130 | 3.43 | 85 | 1.46 | 37 | 2 | 50 | | |
| **T7720-2052** | 31 | 1.1/4 | M 52X2 | 38 | -2052 | 6.22 | 158 | 4.17 | 106 | 1.89 | 48 | 2.3/8 | 60 | | |

## METRIC - DKOS | T7730

**DKOS FEMALE**
**24° CONE**
**90° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7730-0618** | 10 | 3/8 | M 18X1,5 | 10 | -0618 | 2.20 | 56 | 1.06 | 27 | 1.18 | 30 | 7/8 | 22 | | |
| **T7730-0824** | 12 | 1/2 | M 24X1,5 | 16 | -0824 | 2.72 | 69 | 1.61 | 41 | 1.89 | 48 | 1.3/16 | 30 | | |
| **T7730-1024** | 16 | 5/8 | M 24X1,5 | 16 | -1024 | 3.07 | 78 | 1.77 | 45 | 1.89 | 48 | 1.3/16 | 30 | | |
| **T7730-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 3.54 | 88 | 2.32 | 57 | 2.68 | 68 | | 36 | | |
| **T7730-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 3.54 | 88 | 2.32 | 57 | 2.68 | 68 | | 46 | | |
| **T7730-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 4.41 | 112 | 2.72 | 74 | 3.03 | 77 | 2 | 50 | | |
| **T7730-2042** | 31 | 1.1/4 | M 42X2 | 30 | -2042 | 4.80 | 122 | 2.76 | 70 | 3.03 | 77 | 2 | 50 | | |
| **T7730-2052** | 31 | 1.1/4 | M 52X2 | 38 | -2052 | 5.39 | 137 | 3.35 | 85 | 3.50 | 89 | 2.3/8 | 60 | | |
| **T7730-2452** | 38 | 1.1/2 | M 52X2 | 38 | -2452 | 5.79 | 147 | 3.58 | 91 | 3.50 | 89 | 2.3/8 | 60 | | |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### ORFS — T7840


**ORFS MALE**




| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T7840-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.28 | 58 | 1.14 | 29 | | | | | 3/4 | 19 |
| **T7840-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.36 | 60 | 1.30 | 33 | | | | | 7/8 | 22 |
| **T7840-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 2.76 | 70 | 1.54 | 39 | | | | | 1.1/4 | 32 |
| **T7840-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 3.31 | 84 | 1.61 | 41 | | | | | 1.1/2 | 38 |
| **T7840-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 3.82 | 97 | 1.77 | 45 | | | | | 1.3/4 | |

### ORFS — T7800


**ORFS FEMALE**




| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T7800-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.44 | 62 | 1.26 | 32 | | | 7/8 | 22 | 9/16 | 16 |
| **T7800-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.56 | 65 | 1.38 | 35 | | | 15/16 | 24 | 9/16 | 16 |
| **T7800-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.52 | 64 | 1.42 | 36 | | | 15/16 | 24 | 11/16 | 19 |
| **T7800-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.64 | 67 | 1.57 | 40 | | | 1.1/8 | | 15/16 | 24 |
| **T7800-0819** | 12 | 1/2 | 1.3/16" - 12 | | -0819 | 2.72 | 69 | 1.65 | 42 | | | 1.3/8 | 35 | 11/16 | |
| **T7800-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 2.83 | 72 | 1.57 | 40 | | | 1.1/8 | | 7/8 | 22 |
| **T7800-1216** | 19 | 3/4 | 1" - 14 | | -1216 | 2.76 | 73 | 1.54 | 42 | | | 1.1/8 | | 1 | |
| **T7800-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.07 | 72 | 1.85 | 41 | | | 1.3/8 | 35 | 1.1/16 | 27 |
| **T7800-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 3.03 | 75 | 1.85 | 45 | | | 1.5/8 | 41 | 1.1/16 | 27 |
| **T7800-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 3.58 | 91 | 1.89 | 42 | | | 1.5/8 | 41 | 1.1/4 | 32 |
| **T7800-1627** | 25 | 1 | 1.11/16" - 12 | | -1627 | 3.66 | 93 | 1.97 | 46 | | | 2 | 50 | 1.1/4 | 32 |
| **T7800-2023** | 31 | 1.1/4 | 1.7/16" - 12 | | -2023 | 4.41 | 112 | 2.40 | 61 | | | 1.5/8 | 41 | 1.5/8 | 41 |
| **T7800-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 4.17 | 106 | 2.17 | 55 | | | 2 | 50 | 1.5/8 | 41 |
| **T7800-2432** | 38 | 1.1/2 | 2" - 12 | | -2432 | 4.53 | 115 | 2.32 | 59 | | | 2.1/4 | 57 | 2 | 50 |

## ORFS — T7801


**ORFS FEMALE**
**METRCI NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **T7801-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.44 | 62 | 1.26 | 32 | | | 7/8 | 22 | 9/16 | |
| **T7801-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.60 | 66 | 1.50 | 38 | | | 1.3/16 | 30 | 11/16 | |
| **T7801-0819** | 12 | 1/2 | 1.3/16" - 12 | | -0819 | 2.72 | 69 | 1.65 | 42 | | | | 36 | 11/16 | |
| **T7801-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 2.83 | 72 | 1.57 | 40 | | | 1.3/16 | 30 | 7/8 | 22 |
| **T7801-1216** | 19 | 3/4 | 1" - 14 | | -1216 | 2.91 | 72 | 1.73 | 42 | | | 1.3/16 | 30 | 1.1/16 | 27 |
| **T7801-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.07 | 72 | 1.85 | 41 | | | | 36 | 1.1/16 | 27 |

## ORFS — T7810

**ORFS FEMALE**
**45° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | mm |
| **T7810-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.91 | 74 | 1.77 | 45 | 0.79 | 20 | 7/8 | 22 | | |
| **T7810-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.72 | 69 | 1.57 | 40 | 0.67 | 17 | 15/16 | 24 | | |
| **T7810-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.99 | 76 | 1.93 | 49 | 0.75 | 19 | 15/16 | 24 | | |
| **T7810-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.95 | 75 | 1.89 | 48 | 0.75 | 19 | 1.1/8 | | | |
| **T7810-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 3.58 | 91 | 2.32 | 59 | 0.79 | 20 | 1.1/8 | | | |
| **T7810-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 4.33 | 108 | 3.11 | 77 | 1.14 | 29 | 1.3/8 | 35 | | |
| **T7810-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 4.25 | 106 | 3.03 | 75 | 1.02 | 26 | 1.5/8 | 41 | | |
| **T7810-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 5.08 | 129 | 3.39 | 84 | 1.34 | 34 | 1.5/8 | 41 | | |
| **T7810-1627** | 25 | 1 | 1.11/16" - 12 | | -1627 | 5.08 | 129 | 3.39 | 80 | 1.26 | 32 | 2 | 50 | | |
| **T7810-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 6.02 | 153 | 4.02 | 102 | 1.77 | 45 | 2 | 50 | | |
| **T7810-2432** | 38 | 1.1/2 | 2" - 12 | | -2432 | 7.36 | 187 | 5.16 | 131 | 2.09 | 53 | 2.1/4 | 57 | | |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### ORFS — T7811


**ORFS FEMALE**
**45° TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7811-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.99 | 76 | 1.89 | 48 | 0.75 | 19 | 1.3/16 | 30 | | |
| **T7811-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 3.62 | 92 | 2.32 | 59 | 0.79 | 20 | 1.3/16 | 30 | | |

### ORFS — T7823


**ORFS FEMALE**
**90° SHORT TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7823-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.54 | 88 | 2.32 | 57 | 1.89 | 48 | 1.3/8 | 35 | | |
| **T7823-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 4.88 | 124 | 3.19 | 79 | 2.20 | 56 | 1.5/8 | 41 | | |
| **T7823-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 5.94 | 151 | 3.94 | 100 | 2.52 | 64 | 2 | 50 | | |

### ORFS — T7824


**ORFS FEMALE**
**90° SHORT TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | | mm | | |
| **T7824-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.54 | 88 | 2.32 | 57 | 1.89 | 48 | | 36 | | |

## ORFS | T7820


**ORFS FEMALE**
**90° MEDIUM TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | mm |
| **T7820-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.56 | 65 | 1.38 | 35 | 1.50 | 38 | 7/8 | 22 | | |
| **T7820-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.68 | 68 | 1.50 | 38 | 1.34 | 34 | 15/16 | 24 | | |
| **T7820-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.56 | 65 | 1.50 | 38 | 1.61 | 41 | 15/16 | 24 | | |
| **T7820-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.72 | 69 | 1.61 | 41 | 1.85 | 47 | 1.1/8 | | | |
| **T7820-0819** | 12 | 1/2 | 1.3/16" - 12 | | -0819 | 2.72 | 69 | 1.61 | 41 | 2.28 | 58 | 1.3/8 | 35 | | |
| **T7820-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 3.07 | 78 | 1.81 | 46 | 1.85 | 47 | 1.1/8 | | | |
| **T7820-1216** | 19 | 3/4 | 1" - 14 | | -1216 | 3.39 | 84 | 2.17 | 53 | 1.85 | 47 | 1.1/8 | | | |
| **T7820-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.54 | 88 | 2.32 | 57 | 2.32 | 59 | 1.3/8 | 35 | | |
| **T7820-1223** | 19 | 3/4 | 1.7/16" - 12 | | -1223 | 3.54 | 88 | 2.32 | 57 | 2.09 | 53 | 1.5/8 | 41 | | |
| **T7820-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 4.41 | 112 | 2.72 | 74 | 2.80 | 71 | 1.5/8 | 41 | | |
| **T7820-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 5.94 | 151 | 3.94 | 100 | 3.54 | 90 | 2 | 50 | | |
| **T7820-2432** | 38 | 1.1/2 | 2" - 12 | | -2432 | 6.38 | 162 | 4.17 | 106 | 4.21 | 107 | 2.1/4 | 57 | | |

## ORFS | T7821

**ORFS FEMALE**
**90° MEDIUM TUBE BEND**
**METRIC NUT ONLY**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7821-0816** | 12 | 1/2 | 1" - 14 | | -0816 | 2.72 | 69 | 1.61 | 41 | 1.85 | 47 | 1.3/16 | 30 | | |
| **T7821-0819** | 12 | 1/2 | 1.3/16" - 12 | | -0819 | 2.72 | 69 | 1.61 | 41 | 2.28 | 58 | | 36 | | |
| **T7821-1016** | 16 | 5/8 | 1" - 14 | | -1016 | 3.07 | 78 | 1.77 | 45 | 1.85 | 47 | 1.3/16 | 30 | | |
| **T7821-1216** | 19 | 3/4 | 1" - 14 | | -1216 | 3.39 | 86 | 2.17 | 55 | 1.85 | 47 | 1.3/16 | 30 | | |
| **T7821-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.54 | 88 | 2.32 | 57 | 2.32 | 59 | | 36 | | |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### ORFS — T7830


**ORFS FEMALE**
**90° LONG TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7830-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.44 | 62 | 1.30 | 33 | 2.17 | 55 | 7/8 | 22 | | |
| **T7830-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.76 | 70 | 1.69 | 43 | 2.56 | 65 | 15/16 | 24 | | |
| **T7830-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.50 | 88 | 2.28 | 57 | 3.78 | 96 | 1.3/8 | 35 | | |
| **T7830-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 4.61 | 117 | 2.91 | 74 | 4.45 | 113 | 1.5/8 | 41 | | |
| **T7830-2027** | 31 | 1.1/4 | 1.11/16" - 12 | | -2027 | 5.94 | 151 | 3.94 | 100 | 5.08 | 129 | 2 | 50 | | |

### ORFS — T7831


**ORFS FEMALE**
**90° LONG TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **T7831-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.54 | 88 | 2.32 | 57 | 3.78 | 96 | | 36 | | |

### RYCOLOK — T7870


**RYCOLOK MALE**
**STAPLE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | | | |
| **T7870-0610** | 10 | 3/8 | | 10 | -0610 | 2.64 | 67 | 1.50 | 38 | | | | | | |
| **T7870-0812** | 12 | 1/2 | | 12 | -0812 | 2.68 | 68 | 1.61 | 41 | | | | | | |
| **T7870-1016** | 16 | 5/8 | | 16 | -1016 | 2.80 | 71 | 1.54 | 39 | | | | | | |
| **T7870-1220** | 19 | 3/4 | | 20 | -1220 | 2.76 | 70 | 1.54 | 39 | | | | | | |
| **T7870-1625** | 25 | 1 | | 25 | -1625 | 3.66 | 93 | 1.97 | 50 | | | | | | |
| **T7870-2032** | 31 | 1.1/4 | | 32 | -2032 | 4.02 | 102 | 1.97 | 50 | | | | | | |
| **T7870-2440** | 38 | 1.1/2 | | 40 | -2440 | 4.57 | 116 | 2.36 | 60 | | | | | | |
| **T7870-3250** | 51 | 2 | | 50 | -3250 | 4.72 | 120 | 2.28 | 58 | | | | | | |
| **T7870-4063** | 63 | 2.1/2 | | 63 | -4063 | 6.57 | 167 | 3.54 | 90 | | | | | | |

## RYCOLOK — T7871


**RYCOLOK MALE**
**45° ELBOW**
**STAPLE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | inch | mm | | | inch | mm |
| **T7871-0610** | 10 | 3/8 | | 10 | -0610 | 2.91 | 74 | 1.77 | 45 | 1.06 | 27 | | | 7/8 | 22 |
| **T7871-0812** | 12 | 1/2 | | 12 | -0812 | 3.09 | 79 | 2.02 | 51 | 1.07 | 27 | | | | |
| **T7871-1220** | 19 | 3/4 | | 20 | -1220 | 3.26 | 83 | 2.05 | 52 | 1.27 | 32 | | | | |
| **T7871-1625** | 25 | 1 | | 25 | -1625 | 4.13 | 105 | 2.46 | 62 | 1.43 | 36 | | | | |
| **T7871-2032** | 31 | 1.1/4 | | 32 | -2032 | 4.57 | 116 | 2.53 | 64 | 1.43 | 36 | | | | |
| **T7871-2440** | 38 | 1.1/2 | | 40 | -2440 | 5.43 | 138 | 3.23 | 82 | 1.73 | 44 | | | | |
| **T7871-3250** | 51 | 2 | | 50 | -3250 | 5.91 | 150 | 3.43 | 87 | 1.81 | 46 | | | | |

## RYCOLOK — T7872

**RYCOLOK MALE**
**90° ELBOW**
**STAPLE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | mm | | inch | mm | inch | mm | inch | mm | | | inch | mm |
| **T7872-0610** | 10 | 3/8 | | 10 | -0610 | 2.05 | 52 | 0.91 | 23 | 1.81 | 46 | | | 7/8 | 22 |
| **T7872-0812** | 12 | 1/2 | | 12 | -0812 | 2.22 | 57 | 1.15 | 29 | 1.99 | 51 | | | | |
| **T7872-1016** | 16 | 5/8 | | 16 | -1016 | 2.37 | 60 | 1.11 | 28 | 2.07 | 53 | | | | |
| **T7872-1220** | 19 | 3/4 | | 20 | -1220 | 2.40 | 61 | 1.19 | 30 | 2.19 | 56 | | | | |
| **T7872-1625** | 25 | 1 | | 25 | -1625 | 3.29 | 84 | 1.60 | 41 | 2.68 | 68 | | | | |
| **T7872-2032** | 31 | 1.1/4 | | 32 | -2032 | 3.72 | 95 | 1.68 | 43 | 2.68 | 68 | | | | |
| **T7872-2440** | 38 | 1.1/2 | | 40 | -2440 | 4.61 | 117 | 2.40 | 61 | 3.35 | 85 | | | | |


# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### RYCO SUPERLOK — T7876

**RYCO SUPERLOK MALE**
**STAPLE**


O RING & BACK UP RING SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | | | |
| **T7876-0812** | 12 | 1/2 | | 12 | -0812 | 2.83 | 72 | 1.77 | 45 | | | | | | |
| **T7876-1220** | 19 | 3/4 | | 20 | -1220 | 3.11 | 79 | 1.89 | 48 | | | | | | |
| **T7876-1625** | 25 | 1 | | 25 | -1625 | 4.37 | 111 | 2.68 | 68 | | | | | | |
| **T7876-2032** | 31 | 1.1/4 | | 32 | -2032 | 4.80 | 122 | 2.76 | 70 | | | | | | |
| **T7876-2440** | 38 | 1.1/2 | | 40 | -2440 | 5.31 | 135 | 3.07 | 78 | | | | | | |
| **T7876-3250** | 51 | 2 | | 50 | -3250 | 5.55 | 141 | 3.11 | 79 | | | | | | |

### RYCO WEO — T7480


**RYCO WEO MALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | | | |
| **T7480-0606** | 10 | 3/8 | | 3/8 | -0606 | 2.52 | 64 | 1.38 | 35 | | | | | | |
| **T7480-0808** | 12 | 1/2 | | 1/2 | -0808 | 2.48 | 63 | 1.42 | 36 | | | | | | |
| **T7480-1012** | 16 | 5/8 | | 3/4 | -1012 | 3.03 | 77 | 1.73 | 44 | | | | | | |
| **T7480-1212** | 19 | 3/4 | | 3/4 | -1212 | 2.99 | 76 | 1.77 | 45 | | | | | | |
| **T7480-1616** | 25 | 1 | | 1 | -1616 | 3.90 | 99 | 2.20 | 56 | | | | | | |

### RYCO WEO — T7482


**RYCO WEO MALE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | | | |
| | DN | inch | | inch | | inch | mm | inch | mm | inch | mm | | | | | | |
| **T7482-0606** | 10 | 3/8 | | 3/8 | -0606 | 3.31 | 84 | 2.17 | 55 | 1.06 | 27 | | | | | | |
| **T7482-0808** | 12 | 1/2 | | 1/2 | -0808 | 3.39 | 86 | 2.32 | 59 | 1.22 | 31 | | | | | | |
| **T7482-1012** | 16 | 5/8 | | 3/4 | -1012 | 4.09 | 104 | 2.83 | 72 | 1.57 | 40 | | | | | | |
| **T7482-1212** | 19 | 3/4 | | 3/4 | -1212 | 4.45 | 113 | 3.23 | 82 | 1.69 | 43 | | | | | | |

## RYCO WEO | T7483

**RYCO WEO MALE**
**90° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | inch | mm | | | | |
| **T7483-0606** | 10 | 3/8 | | 3/8 | -0606 | 2.52 | 64 | 1.38 | 35 | 2.05 | 52 | | | | |
| **T7483-0808** | 12 | 1/2 | | 1/2 | -0808 | 2.56 | 65 | 1.50 | 38 | 2.28 | 58 | | | | |
| **T7483-1012** | 16 | 5/8 | | 3/4 | -1012 | 3.39 | 86 | 2.13 | 54 | 3.23 | 82 | | | | |
| **T7483-1212** | 19 | 3/4 | | 3/4 | -1212 | 3.35 | 85 | 2.13 | 54 | 3.23 | 82 | | | | |
| **T7483-1616** | 25 | 1 | | 1 | -1616 | 4.53 | 115 | 2.83 | 72 | 3.82 | 97 | | | | |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### DIMENSIONS FOR SAE CODE 61 AND CODE 62 FLANGES, AND RYCO CODE 62C FLANGES

| NOMINAL FLANGE | CODE 61 | | | | CODE 62 | | | | CODE 62C | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | B | | T | | B | | T | | B | | T | |
| inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch |
| 1/2 | 30,2 | 1.19 | 6,73 | 0.265 | 31,8 | 1.25 | 7,75 | 0.305 | | | | |
| 5/8 | 34,0 | 1.34 | 6,73 | 0.265 | | | | | | | | |
| 3/4 | 38,1 | 1.50 | 6,73 | 0.265 | 41,3 | 1.63 | 8,76 | 0.345 | 41,3 | 1.63 | 14,20 | 0.559 |
| 1 | 44,5 | 1.75 | 8,00 | 0.315 | 47,6 | 1.88 | 9,53 | 0.375 | 47,6 | 1.88 | 14,20 | 0.559 |
| 1.1/4 | 50,8 | 2.00 | 8,00 | 0.315 | 54,0 | 2.12 | 10,29 | 0.405 | 54,0 | 2.12 | 14,20 | 0.559 |
| 1.1/2 | 60,3 | 2.38 | 8,00 | 0.315 | 63,5 | 2.50 | 12,57 | 0.495 | 63,5 | 2.50 | 14,20 | 0.559 |
| 2 | 71,4 | 2.81 | 9,53 | 0.375 | 79,4 | 3.13 | 12,57 | 0.495 | 79,4 | 3.13 | 14,20 | 0.559 |
| 2.1/2 | 84,1 | 3.31 | 9,53 | 0.375 | | | | | | | | |
| 3 | 101,6 | 4.00 | 9,53 | 0.375 | | | | | | | | |





**NOTE:** Ryco Code 62C fittings conform to the flange OD and bolt hole patterns of SAE Code 62 but require special flange clamps.
Ryco Code 62C flange heads are thicker than SAE Code 62 and measure T = 14,2 mm (0.559 inch) in all sizes.

## SAE FLANGE — T7130

**SAE CODE 61 FLANGE**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | |
| **T7130-0808** | 12 | 1/2 | | | -0808 | 2.83 | 72 | 1.77 | 45 | | | | | | |
| **T7130-0812** | 12 | 1/2 | | | -0812 | 2.95 | 75 | 1.89 | 48 | | | | | | |
| **T7130-1210** | 19 | 3/4 | | | -1210 | 2.99 | 76 | 1.77 | 45 | | | | | | |
| **T7130-1212** | 19 | 3/4 | | | -1212 | 3.03 | 77 | 1.81 | 46 | | | | | | |
| **T7130-1216** | 19 | 3/4 | | | -1216 | 3.19 | 81 | 1.97 | 50 | | | | | | |
| **T7130-1220** | 19 | 3/4 | | | -1220 | 3.46 | 88 | 2.24 | 57 | | | | | | |
| **T7130-1616** | 25 | 1 | | | -1616 | 3.74 | 95 | 2.05 | 52 | | | | | | |
| **T7130-1620** | 25 | 1 | | | -1620 | 3.94 | 100 | 2.24 | 57 | | | | | | |
| **T7130-1624** | 25 | 1 | | | -1624 | 5.00 | 127 | 3.31 | 84 | | | | | | |
| **T7130-2016** | 31 | 1.1/4 | | | -2016 | 4.17 | 106 | 2.13 | 54 | | | | | | |
| **T7130-2020** | 31 | 1.1/4 | | | -2020 | 4.37 | 111 | 2.32 | 59 | | | | | | |
| **T7130-2024** | 31 | 1.1/4 | | | -2024 | 5.35 | 136 | 3.35 | 85 | | | | | | |
| **T7130-2420** | 38 | 1.1/2 | | | -2420 | 4.57 | 116 | 2.36 | 60 | | | | | | |
| **T7130-2424** | 38 | 1.1/2 | | | -2424 | 5.59 | 142 | 3.39 | 86 | | | | | | |
| **T7130-2432** | 38 | 1.1/2 | | | -2432 | 5.98 | 152 | 3.78 | 96 | | | | | | |
| **T7130-3232** | 51 | 2 | | | -3232 | 6.26 | 159 | 3.78 | 96 | | | | | | |
| **T7130-3240** | 51 | 2 | | | -3240 | 6.46 | 164 | 3.98 | 101 | | | | | | |
| **T7130-4040** | 63 | 2.1/2 | | | -4040 | 6.14 | 156 | 3.11 | 79 | | | | | | |

## SAE FLANGE — T7140

**SAE CODE 61 FLANGE**
**22.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7140-1212** | 19 | 3/4 | | | -1212 | 4.06 | 103 | 2.83 | 72 | 0.47 | 12 | | | | |
| **T7140-1216** | 19 | 3/4 | | | -1216 | 4.17 | 106 | 2.95 | 75 | 0.59 | 15 | | | | |
| **T7140-1616** | 25 | 1 | | | -1616 | 5.12 | 130 | 3.43 | 87 | 0.55 | 14 | | | | |
| **T7140-1620** | 25 | 1 | | | -1620 | 5.12 | 130 | 3.43 | 87 | 0.51 | 13 | | | | |
| **T7140-2020** | 31 | 1.1/4 | | | -2020 | 6.22 | 158 | 4.17 | 106 | 0.63 | 16 | | | | |
| **T7140-2024** | 31 | 1.1/4 | | | -2024 | 6.34 | 161 | 4.29 | 109 | 0.79 | 20 | | | | |
| **T7140-2424** | 38 | 1.1/2 | | | -2424 | 6.85 | 174 | 4.65 | 118 | 0.94 | 24 | | | | |
| **T7140-2432** | 38 | 1.1/2 | | | -2432 | 7.48 | 190 | 5.28 | 134 | 1.06 | 27 | | | | |
| **T7140-3232** | 51 | 2 | | | -3232 | 8.86 | 225 | 6.38 | 162 | 0.98 | 25 | | | | |

## SAE - FLANGE — T7150

**SAE CODE 61 FLANGE**
**45° TUBE BEND**

CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7150-0808** | 12 | 1/2 | - | | -0808 | 2.99 | 76 | 1.93 | 49 | 0.79 | 20 | | | | |
| **T7150-0812** | 12 | 1/2 | - | | -0812 | 3.07 | 78 | 2.01 | 51 | 0.94 | 24 | | | | |
| **T7150-1210** | 19 | 3/4 | - | | -1210 | 3.54 | 90 | 2.32 | 59 | 1.02 | 26 | | | | |
| **T7150-1212** | 19 | 3/4 | - | | -1212 | 3.78 | 96 | 2.56 | 65 | 1.02 | 26 | | | | |
| **T7150-1216** | 19 | 3/4 | - | | -1216 | 3.90 | 99 | 2.68 | 68 | 1.18 | 30 | | | | |
| **T7150-1616** | 25 | 1 | - | | -1616 | 4.88 | 124 | 3.19 | 81 | 1.18 | 30 | | | | |
| **T7150-1620** | 25 | 1 | - | | -1620 | 4.96 | 126 | 3.27 | 83 | 1.26 | 32 | | | | |
| **T7150-2016** | 31 | 1.1/4 | - | | -2016 | 5.51 | 140 | 3.46 | 88 | 1.18 | 30 | | | | |
| **T7150-2020** | 31 | 1.1/4 | - | | -2020 | 5.98 | 152 | 3.94 | 100 | 1.42 | 36 | | | | |
| **T7150-2024** | 31 | 1.1/4 | - | | -2024 | 6.10 | 155 | 4.06 | 103 | 1.57 | 40 | | | | |


# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

## SAE FLANGE — T7300

**SAE CODE 61 FLANGE**
**60° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7300-1212** | 19 | 3/4 | | | -1212 | 4.29 | 109 | 3.07 | 78 | 1.46 | 37 | | | | |
| **T7300-1216** | 19 | 3/4 | | | -1216 | 4.37 | 111 | 3.15 | 80 | 1.61 | 41 | | | | |
| **T7300-1616** | 25 | 1 | | | -1616 | 5.43 | 138 | 3.74 | 95 | 1.77 | 45 | | | | |
| **T7300-1620** | 25 | 1 | | | -1620 | 5.51 | 140 | 3.82 | 97 | 1.77 | 45 | | | | |
| **T7300-2020** | 31 | 1.1/4 | | | -2020 | 6.50 | 165 | 4.45 | 113 | 2.01 | 51 | | | | |
| **T7300-2024** | 31 | 1.1/4 | | | -2024 | 6.81 | 173 | 4.76 | 121 | 2.13 | 54 | | | | |
| **T7300-2424** | 38 | 1.1/2 | | | -2424 | 7.68 | 195 | 5.47 | 139 | 2.36 | 60 | | | | |
| **T7300-2432** | 38 | 1.1/2 | | | -2432 | 7.99 | 203 | 5.79 | 147 | 2.68 | 68 | | | | |
| **T7300-3232** | 51 | 2 | | | -3232 | 9.13 | 232 | 6.65 | 169 | 3.66 | 93 | | | | |

## SAE FLANGE — T7290

**SAE CODE 61 FLANGE**
**30° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7290-1212** | 19 | 3/4 | | | -1212 | 3.98 | 101 | 2.76 | 70 | 0.71 | 18 | | | | |
| **T7290-1616** | 25 | 1 | | | -1616 | 5.04 | 128 | 3.35 | 85 | 0.71 | 18 | | | | |
| **T7290-2020** | 31 | 1.1/4 | | | -2020 | 6.14 | 156 | 4.09 | 104 | 0.79 | 20 | | | | |
| **T7290-2024** | 31 | 1.1/4 | | | -2024 | 6.42 | 163 | 4.37 | 111 | 0.94 | 24 | | | | |
| **T7290-2424** | 38 | 1.1/2 | | | -2424 | 6.85 | 174 | 4.65 | 118 | 1.02 | 26 | | | | |
| **T7290-2432** | 38 | 1.1/2 | | | -2432 | 7.32 | 186 | 5.12 | 130 | 1.26 | 32 | | | | |
| **T7290-3232** | 51 | 2 | | | -3232 | 8.62 | 219 | 6.14 | 156 | 1.57 | 40 | | | | |

## SAE FLANGE — T7160

**SAE CODE 61 FLANGE**
**67.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7160-1212** | 19 | 3/4 | | | -1212 | 4.06 | 103 | 2.83 | 72 | 1.77 | 45 | | | | |
| **T7160-1216** | 19 | 3/4 | | | -1216 | 4.09 | 104 | 2.87 | 73 | 1.93 | 49 | | | | |
| **T7160-1616** | 25 | 1 | | | -1616 | 5.16 | 131 | 3.46 | 88 | 1.93 | 49 | | | | |
| **T7160-1620** | 25 | 1 | | | -1620 | 5.16 | 131 | 3.46 | 88 | 2.05 | 52 | | | | |
| **T7160-2020** | 31 | 1.1/4 | | | -2020 | 6.02 | 153 | 3.98 | 101 | 2.64 | 67 | | | | |
| **T7160-2024** | 31 | 1.1/4 | | | -2024 | 6.34 | 161 | 4.29 | 109 | 2.52 | 64 | | | | |
| **T7160-2424** | 38 | 1.1/2 | | | -2424 | 7.48 | 190 | 5.28 | 134 | 2.76 | 70 | | | | |
| **T7160-2432** | 38 | 1.1/2 | | | -2432 | 7.48 | 190 | 5.28 | 134 | 3.11 | 79 | | | | |
| **T7160-3232** | 51 | 2 | | | -3232 | 9.09 | 231 | 6.61 | 168 | 3.74 | 95 | | | | |

## SAE FLANGE — T7170

**SAE CODE 61 FLANGE**
**90° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7170-0808** | 12 | 1/2 | | | -0808 | 2.64 | 67 | 1.57 | 40 | 1.61 | 41 | | | | |
| **T7170-0812** | 12 | 1/2 | | | -0812 | 2.64 | 67 | 1.57 | 40 | 1.81 | 46 | | | | |
| **T7170-1210** | 19 | 3/4 | | | -1210 | 3.23 | 82 | 2.01 | 51 | 1.89 | 48 | | | | |
| **T7170-1212** | 19 | 3/4 | | | -1212 | 3.39 | 86 | 2.17 | 55 | 2.13 | 54 | | | | |
| **T7170-1216** | 19 | 3/4 | | | -1216 | 3.39 | 86 | 2.17 | 55 | 2.36 | 60 | | | | |
| **T7170-1612** | 25 | 1 | | | -1612 | 4.06 | 103 | 2.36 | 60 | 2.13 | 54 | | | | |
| **T7170-1616** | 25 | 1 | | | -1616 | 4.37 | 111 | 2.68 | 68 | 2.68 | 68 | | | | |
| **T7170-1620** | 25 | 1 | | | -1620 | 4.45 | 113 | 2.76 | 70 | 2.72 | 69 | | | | |
| **T7170-1624** | 25 | 1 | | | -1624 | 4.37 | 111 | 2.68 | 68 | 2.87 | 73 | | | | |
| **T7170-2016** | 31 | 1.1/4 | | | -2016 | 5.12 | 130 | 3.07 | 78 | 2.68 | 68 | | | | |
| **T7170-2020** | 31 | 1.1/4 | | | -2020 | 5.20 | 132 | 3.15 | 80 | 3.07 | 78 | | | | |
| **T7170-2024** | 31 | 1.1/4 | | | -2024 | 5.59 | 142 | 3.54 | 90 | 3.19 | 81 | | | | |
| **T7170-2424** | 38 | 1.1/2 | | | -2424 | 6.30 | 160 | 4.09 | 104 | 3.66 | 93 | | | | |
| **T7170-2432** | 38 | 1.1/2 | | | -2432 | 6.02 | 153 | 3.82 | 97 | 3.90 | 99 | | | | |
| **T7170-3232** | 51 | 2 | | | -3232 | 7.87 | 200 | 5.39 | 137 | 5.12 | 130 | | | | |
| **T7170-3240** | 51 | 2 | | | -3240 | 8.03 | 204 | 5.55 | 141 | 5.28 | 134 | | | | |


# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

## SAE FLANGE — T7171

**SAE CODE 61 FLANGE**
**90° SPECIAL TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7171-0812** | 12 | 1/2 | | | -0812 | 3.07 | 78 | 2.01 | 51 | 2.87 | 73 | | | | |
| **T7171-1216** | 19 | 3/4 | | | -1216 | 3.39 | 86 | 2.17 | 55 | 3.11 | 79 | | | | |
| **T7171-2024** | 31 | 1.1/4 | | | -2024 | 5.35 | 136 | 3.31 | 84 | 3.19 | 81 | | | | |
| **T7171-2432** | 38 | 1.1/2 | | | -2432 | 6.26 | 159 | 4.06 | 103 | 4.49 | 114 | | | | |
| **T7171-3232** | 51 | 2 | | | -3232 | 7.91 | 201 | 5.43 | 138 | 6.50 | 165 | | | | |
| **T7171-3240** | 51 | 2 | | | -3240 | 8.03 | 204 | 5.55 | 141 | 4.49 | 114 | | | | |

## SAE FLANGE — T7172

**SAE CODE 61 FLANGE**
**90° SPECIAL TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7172-1212** | 19 | 3/4 | | | -1212 | 3.43 | 87 | 2.20 | 56 | 3.74 | 95 | | | | |
| **T7172-1616** | 25 | 1 | | | -1616 | 4.49 | 114 | 2.80 | 71 | 2.64 | 67 | | | | |
| **T7172-1624** | 25 | 1 | | | -1624 | 4.37 | 111 | 2.68 | 68 | 4.25 | 108 | | | | |
| **T7172-2020** | 31 | 1.1/4 | | | -2020 | 5.35 | 136 | 3.31 | 84 | 3.62 | 92 | | | | |
| **T7172-2024** | 31 | 1.1/4 | | | -2024 | 5.51 | 140 | 3.46 | 88 | 4.65 | 118 | | | | |
| **T7172-2424** | 38 | 1.1/2 | | | -2424 | 6.26 | 159 | 4.06 | 103 | 5.83 | 148 | | | | |

## SAE — T7173

**SAE CODE 61 FLANGE**
**90° LONG TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7173-1212** | 19 | 3/4 | | | -1212 | 3.50 | 89 | 2.32 | 59 | 3.07 | 78 | | | | |
| **T7173-1616** | 25 | 1 | | | -1616 | 4.49 | 114 | 2.80 | 71 | 3.70 | 94 | | | | |
| **T7173-1620** | 25 | 1 | | | -1620 | 4.33 | 110 | 2.64 | 67 | 3.66 | 93 | | | | |
| **T7173-2020** | 31 | 1.1/4 | | | -2020 | 5.20 | 132 | 3.15 | 80 | 4.25 | 108 | | | | |

## SAE FLANGE — T7174

**SAE CODE 61 FLANGE**
**90° SPECIAL TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7174-1212** | 19 | 3/4 | | | -1212 | 3.39 | 86 | 2.17 | 55 | 3.78 | 96 | | | | |
| **T7174-1616** | 25 | 1 | | | -1616 | 4.45 | 113 | 2.76 | 70 | 4.65 | 118 | | | | |
| **T7174-1620** | 25 | 1 | | | -1620 | 4.37 | 111 | 2.68 | 68 | 4.65 | 118 | | | | |
| **T7174-2020** | 31 | 1.1/4 | | | -2020 | 5.39 | 137 | 3.35 | 85 | 5.12 | 130 | | | | |
| **T7174-2424** | 38 | 1.1/2 | | | -2424 | 6.06 | 154 | 3.86 | 98 | 5.83 | 148 | | | | |
| **T7174-2432** | 38 | 1.1/2 | | | -2432 | 6.30 | 160 | 4.09 | 104 | 6.77 | 172 | | | | |
| **T7174-3232** | 51 | 2 | | | -3232 | 8.03 | 204 | 5.55 | 141 | 7.99 | 203 | | | | |

## SAE FLANGE — T7910

**SAE CODE 61 FLANGE**
**110° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7910-1212** | 19 | 3/4 | | | -1212 | 4.06 | 103 | 2.87 | 73 | 2.64 | 67 | | | | |
| **T7910-1616** | 25 | 1 | | | -1616 | 4.92 | 125 | 3.23 | 82 | 3.15 | 80 | | | | |
| **T7910-1620** | 25 | 1 | | | -1620 | 4.92 | 125 | 3.23 | 82 | 3.35 | 85 | | | | |
| **T7910-2020** | 31 | 1.1/4 | | | -2020 | 5.59 | 142 | 3.54 | 90 | 3.74 | 95 | | | | |
| **T7910-2024** | 31 | 1.1/4 | | | -2024 | 5.59 | 142 | 3.54 | 90 | 3.86 | 98 | | | | |
| **T7910-2424** | 38 | 1.1/2 | | | -2424 | 8.03 | 204 | 5.83 | 148 | 4.57 | 116 | | | | |
| **T7910-2432** | 38 | 1.1/2 | | | -2432 | 8.07 | 205 | 5.87 | 149 | 4.84 | 123 | | | | |
| **T7910-3232** | 51 | 2 | | | -3232 | 7.76 | 197 | 5.28 | 134 | 5.98 | 152 | | | | |


# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

## SAE FLANGE — T7330

**SAE CODE 62 FLANGE**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | |
| **T7330-0808** | 12 | 1/2 | | | -0808 | 2.87 | 73 | 1.81 | 46 | | | | | | |
| **T7330-0812** | 12 | 1/2 | | | -0812 | 3.31 | 84 | 2.24 | 57 | | | | | | |
| **T7330-1008** | 16 | 5/8 | | | -1008 | 3.07 | 78 | 1.77 | 45 | | | | | | |
| **T7330-1012** | 16 | 5/8 | | | -1012 | 3.46 | 88 | 2.20 | 56 | | | | | | |
| **T7330-1212** | 19 | 3/4 | | | -1212 | 3.23 | 82 | 2.01 | 51 | | | | | | |
| **T7330-1216** | 19 | 3/4 | | | -1216 | 3.35 | 85 | 2.13 | 54 | | | | | | |
| **T7330-1612** | 25 | 1 | | | -1612 | 3.78 | 96 | 2.09 | 53 | | | | | | |
| **T7330-1616** | 25 | 1 | | | -1616 | 3.90 | 99 | 2.20 | 56 | | | | | | |
| **T7330-1620** | 25 | 1 | | | -1620 | 4.33 | 110 | 2.64 | 67 | | | | | | |
| **T7330-2016** | 31 | 1.1/4 | | | -2016 | 4.76 | 121 | 2.72 | 69 | | | | | | |
| **T7330-2020** | 31 | 1.1/4 | | | -2020 | 4.76 | 121 | 2.72 | 69 | | | | | | |
| **T7330-2024** | 31 | 1.1/4 | | | -2024 | 5.94 | 151 | 3.90 | 99 | | | | | | |
| **T7330-2424** | 38 | 1.1/2 | | | -2424 | 6.14 | 156 | 3.94 | 100 | | | | | | |
| **T7330-2432** | 38 | 1.1/2 | | | -2432 | 6.85 | 174 | 4.61 | 117 | | | | | | |
| **T7330-3232** | 51 | 2 | | | -3232 | 7.09 | 180 | 4.65 | 118 | | | | | | |

## SAE CODE 62 — T7440

**SAE CODE 62 FLANGE**
**22.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7440-1212** | 19 | 3/4 | | | -1212 | 3.98 | 101 | 2.76 | 70 | 0.47 | 12 | | | | |
| **T7440-1216** | 19 | 3/4 | | | -1216 | 4.29 | 109 | 3.07 | 78 | 0.55 | 14 | | | | |
| **T7440-1616** | 25 | 1 | | | -1616 | 5.20 | 132 | 3.50 | 89 | 0.63 | 16 | | | | |
| **T7440-2020** | 31 | 1.1/4 | | | -2020 | 6.26 | 159 | 4.21 | 107 | 0.67 | 17 | | | | |
| **T7440-2024** | 31 | 1.1/4 | | | -2024 | 6.61 | 168 | 4.57 | 116 | 0.87 | 22 | | | | |
| **T7440-2424** | 38 | 1.1/2 | | | -2424 | 7.17 | 182 | 4.96 | 126 | 0.94 | 24 | | | | |
| **T7440-3232** | 51 | 2 | | | -3232 | 8.86 | 225 | 6.38 | 162 | 1.10 | 28 | | | | |

## SAE FLANGE — T7450

**SAE CODE 62 FLANGE**
**30° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7450-1212** | 19 | 3/4 | | | -1212 | 4.09 | 104 | 2.87 | 73 | 0.75 | 19 | | | | |
| **T7450-1616** | 25 | 1 | | | -1616 | 5.16 | 131 | 3.46 | 88 | 0.87 | 22 | | | | |
| **T7450-1620** | 25 | 1 | | | -1620 | 5.24 | 133 | 3.54 | 90 | 0.87 | 22 | | | | |
| **T7450-2020** | 31 | 1.1/4 | | | -2020 | 6.30 | 160 | 4.25 | 108 | 0.87 | 22 | | | | |
| **T7450-2024** | 31 | 1.1/4 | | | -2024 | 6.46 | 164 | 4.41 | 112 | 0.98 | 25 | | | | |
| **T7450-2424** | 38 | 1.1/2 | | | -2424 | 7.09 | 180 | 4.88 | 124 | 1.30 | 33 | | | | |

## SAE FLANGE — T7350

**SAE CODE 62 FLANGE**
**45° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7350-0808** | 12 | 1/2 | | | -0808 | 2.99 | 76 | 1.93 | 49 | 0.79 | 20 | | | | |
| **T7350-1212** | 19 | 3/4 | | | -1212 | 3.82 | 97 | 2.60 | 66 | 1.10 | 28 | | | | |
| **T7350-1216** | 19 | 3/4 | | | -1216 | 3.98 | 101 | 2.76 | 70 | 1.22 | 31 | | | | |
| **T7350-1612** | 25 | 1 | | | -1612 | 4.65 | 118 | 2.95 | 75 | 1.10 | 28 | | | | |
| **T7350-1616** | 25 | 1 | | | -1616 | 4.92 | 125 | 3.23 | 82 | 1.22 | 31 | | | | |
| **T7350-1620** | 25 | 1 | | | -1620 | 5.04 | 128 | 3.35 | 85 | 1.34 | 34 | | | | |
| **T7350-2016** | 31 | 1.1/4 | | | -2016 | 5.55 | 141 | 3.50 | 89 | 1.26 | 32 | | | | |
| **T7350-2020** | 31 | 1.1/4 | | | -2020 | 5.91 | 150 | 3.86 | 98 | 1.50 | 38 | | | | |
| **T7350-2024** | 31 | 1.1/4 | | | -2024 | 6.06 | 154 | 4.02 | 102 | 1.61 | 41 | | | | |
| **T7350-2424** | 38 | 1.1/2 | | | -2424 | 6.65 | 169 | 4.45 | 113 | 1.73 | 44 | | | | |
| **T7350-2432** | 38 | 1.1/2 | | | -2432 | 6.93 | 176 | 4.72 | 120 | 2.13 | 54 | | | | |
| **T7350-3232** | 51 | 2 | | | -3232 | 8.46 | 215 | 5.98 | 152 | 2.36 | 60 | | | | |


# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

## SAE FLANGE — T7460

**SAE CODE 62 FLANGE**
**60° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7460-1212** | 19 | 3/4 | | | -1212 | 4.37 | 111 | 3.15 | 80 | 1.42 | 36 | | | | |
| **T7460-1216** | 19 | 3/4 | | | -1216 | 4.45 | 113 | 3.23 | 82 | 1.65 | 42 | | | | |
| **T7460-1616** | 25 | 1 | | | -1616 | 5.47 | 139 | 3.78 | 96 | 1.73 | 44 | | | | |
| **T7460-1620** | 25 | 1 | | | -1620 | 5.51 | 140 | 3.82 | 97 | 1.81 | 46 | | | | |
| **T7460-2020** | 31 | 1.1/4 | | | -2020 | 6.65 | 169 | 4.61 | 117 | 2.01 | 51 | | | | |
| **T7460-2024** | 31 | 1.1/4 | | | -2024 | 6.85 | 174 | 4.80 | 122 | 2.28 | 58 | | | | |
| **T7460-2424** | 38 | 1.1/2 | | | -2424 | 7.72 | 196 | 5.51 | 140 | 2.52 | 64 | | | | |

## SAE FLANGE — T7360

**SAE CODE 62 FLANGE**
**67.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7360-1212** | 19 | 3/4 | | | -1212 | 4.09 | 104 | 2.87 | 73 | 1.85 | 47 | | | | |
| **T7360-1216** | 19 | 3/4 | | | -1216 | 4.13 | 105 | 2.91 | 74 | 1.89 | 48 | | | | |
| **T7360-1616** | 25 | 1 | | | -1616 | 4.84 | 123 | 3.15 | 80 | 2.01 | 51 | | | | |
| **T7360-1620** | 25 | 1 | | | -1620 | 4.88 | 124 | 3.19 | 81 | 2.13 | 54 | | | | |
| **T7360-2020** | 31 | 1.1/4 | | | -2020 | 6.50 | 165 | 4.45 | 113 | 2.83 | 72 | | | | |
| **T7360-2024** | 31 | 1.1/4 | | | -2024 | 6.06 | 154 | 4.02 | 102 | 2.91 | 74 | | | | |

## SAE FLANGE — T7370

**SAE CODE 62 FLANGE**
**90° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7370-0808** | 12 | 1/2 | | | -0808 | 2.72 | 69 | 1.65 | 42 | 1.61 | 41 | | | | |
| **T7370-0812** | 12 | 1/2 | | | -0812 | 2.72 | 69 | 1.65 | 42 | 1.81 | 46 | | | | |
| **T7370-1008** | 16 | 5/8 | | | -1008 | 2.99 | 76 | 1.73 | 44 | 1.65 | 42 | | | | |
| **T7370-1012** | 16 | 5/8 | | | -1012 | 3.15 | 80 | 1.89 | 48 | 2.20 | 56 | | | | |
| **T7370-1212** | 19 | 3/4 | | | -1212 | 3.39 | 86 | 2.17 | 55 | 2.20 | 56 | | | | |
| **T7370-1216** | 19 | 3/4 | | | -1216 | 3.39 | 86 | 2.17 | 55 | 2.40 | 61 | | | | |
| **T7370-1612** | 25 | 1 | | | -1612 | 4.06 | 103 | 2.36 | 60 | 2.20 | 56 | | | | |
| **T7370-1616** | 25 | 1 | | | -1616 | 4.37 | 111 | 2.68 | 68 | 2.76 | 70 | | | | |
| **T7370-1620** | 25 | 1 | | | -1620 | 4.45 | 113 | 2.76 | 70 | 2.80 | 71 | | | | |
| **T7370-2016** | 31 | 1.1/4 | | | -2016 | 5.00 | 127 | 2.95 | 75 | 2.76 | 70 | | | | |
| **T7370-2020** | 31 | 1.1/4 | | | -2020 | 5.35 | 136 | 3.31 | 84 | 3.15 | 80 | | | | |
| **T7370-2024** | 31 | 1.1/4 | | | -2024 | 5.31 | 135 | 3.27 | 83 | 3.39 | 86 | | | | |
| **T7370-2420** | 38 | 1.1/2 | | | -2420 | 5.51 | 140 | 3.31 | 84 | 3.15 | 80 | | | | |
| **T7370-2424** | 38 | 1.1/2 | | | -2424 | 6.06 | 154 | 3.86 | 98 | 3.86 | 98 | | | | |
| **T7370-2432** | 38 | 1.1/2 | | | -2432 | 6.30 | 160 | 4.09 | 104 | 4.09 | 104 | | | | |

## SAE FLANGE — T7930

**SAE CODE 62 FLANGE**
**110° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | inch | mm | | | | |
| **T7930-2424** | 38 | 1.1/2 | | - | -2424 | 7.80 | 198 | 5.59 | 142 | 4.69 | 119 | | | | |
| **T7930-2432** | 38 | 1.1/2 | | - | -2432 | 8.11 | 206 | 5.91 | 150 | 4.96 | 126 | | | | |
| **T7930-3232** | 51 | 2 | | - | -3232 | 7.76 | 197 | 5.28 | 134 | 6.02 | 153 | | | | |


# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### SPECIAL FLANGE — T7333

**RYCO CODE 62C FLANGE**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | |
| **T7333-1212** | 19 | 3/4 | | | -1212 | 3.66 | 93 | 2.44 | 62 | | | | | | |
| **T7333-1216** | 19 | 3/4 | | | -1216 | 3.66 | 93 | 2.44 | 62 | | | | | | |
| **T7333-1616** | 25 | 1 | | | -1616 | 4.21 | 107 | 2.52 | 64 | | | | | | |
| **T7333-1620** | 25 | 1 | | | -1620 | 4.53 | 115 | 2.83 | 72 | | | | | | |
| **T7333-2020** | 31 | 1.1/4 | | | -2020 | 5.47 | 139 | 3.43 | 87 | | | | | | |
| **T7333-2024** | 31 | 1.1/4 | | | -2024 | 5.47 | 139 | 3.43 | 87 | | | | | | |
| **T7333-2424** | 38 | 1.1/2 | | | -2424 | 6.18 | 157 | 3.98 | 101 | | | | | | |
| **T7333-3232** | 51 | 2 | | | -3232 | 6.61 | 168 | 4.17 | 106 | | | | | | |

### SPECIAL FLANGE — T7443

**RYCO CODE 62C FLANGE**
**22.5° TUBE BEND**
O RING NOT SUPPLIED

CLAMPS - SEE PAGES 274 & 282





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7443-1212** | 19 | 3/4 | | | -1212 | 4.33 | 110 | 3.11 | 79 | 0.59 | 15 | | | | |
| **T7443-1216** | 19 | 3/4 | | | -1216 | 4.57 | 116 | 3.35 | 85 | 0.79 | 20 | | | | |
| **T7443-1616** | 25 | 1 | | | -1616 | 5.20 | 132 | 3.50 | 89 | 0.63 | 16 | | | | |
| **T7443-1620** | 25 | 1 | | | -1620 | 5.35 | 136 | 3.66 | 93 | 0.63 | 16 | | | | |
| **T7443-2020** | 31 | 1.1/4 | | | -2020 | 6.26 | 159 | 4.21 | 107 | 0.67 | 17 | | | | |
| **T7443-2024** | 31 | 1.1/4 | | | -2024 | 7.44 | 189 | 5.39 | 137 | 0.87 | 22 | | | | |
| **T7443-2424** | 38 | 1.1/2 | | | -2424 | 7.17 | 182 | 4.96 | 126 | 0.94 | 24 | | | | |

### SPECIAL FLANGE — T7444

**RYCO CODE 62C FLANGE**
**D-RING FLANGE 22.5° TUBE BEND**
O RING NOT SUPPLIED


CLAMPS - SEE PAGES 274 & 282




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7444-1212** | 19 | 3/4 | | | 3/4 | -1212 | 4.33 | 110 | 3.11 | 79 | 0.59 | | | | |
| **T7444-1616** | 25 | 1 | | | 1 | -1616 | 5.20 | 132 | 3.50 | 89 | 0.63 | | | | |
| **T7444-1620** | 25 | 1 | | | 1.1/4 | -1620 | 5.35 | 136 | 3.66 | 93 | 0.63 | | | | |
| **T7444-2020** | 31 | 1.1/4 | | | 1.1/4 | -2020 | 6.26 | 159 | 4.21 | 107 | 0.67 | | | | |

## SPECIAL FLANGE — T7453


**RYCO CODE 62C FLANGE**
**30° TUBE BEND**
O RING NOT SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7453-1212** | 19 | 3/4 | | | -1212 | 4.45 | 113 | 3.23 | 82 | 0.91 | 23 | | | | |
| **T7453-1616** | 25 | 1 | | | -1616 | 5.94 | 151 | 4.25 | 108 | 0.94 | 24 | | | | |
| **T7453-1620** | 25 | 1 | | | -1620 | 6.06 | 154 | 4.37 | 111 | 0.98 | 25 | | | | |
| **T7453-2020** | 31 | 1.1/4 | | | -2020 | 6.57 | 167 | 4.53 | 115 | 0.98 | 25 | | | | |
| **T7453-2024** | 31 | 1.1/4 | | | -2024 | 6.54 | 166 | 4.49 | 114 | 1.02 | 26 | | | | |
| **T7453-2424** | 38 | 1.1/2 | | | -2424 | 7.20 | 183 | 5.00 | 127 | 1.18 | 30 | | | | |

## SPECIAL FLANGE — T7454

**RYCO CODE 62C D-RING FLANGE**
**30° TUBE BEND**
O RING NOT SUPPLIED





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7454-1212** | 19 | 3/4 | | | -1212 | 4.45 | 113 | 3.23 | 82 | 0.91 | 23 | | | | |
| **T7454-1616** | 25 | 1 | | | -1616 | 5.16 | 131 | 3.46 | 88 | 0.94 | 24 | | | | |
| **T7454-2020** | 31 | 1.1/4 | | | -2020 | 6.57 | 167 | 4.53 | 115 | 0.98 | 25 | | | | |
| **T7454-2024** | 31 | 1.1/4 | | | -2024 | 6.57 | 167 | 4.53 | 115 | 1.02 | 26 | | | | |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

## SPECIAL FLANGE — T7353


**RYCO CODE 62C FLANGE**
**45° TUBE BEND**
O RING NOT SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7353-1212** | 19 | 3/4 | | | -1212 | 3.94 | 100 | 2.72 | 69 | 1.22 | 31 | | | | |
| **T7353-1216** | 19 | 3/4 | | | -1216 | 4.06 | 103 | 2.83 | 72 | 1.30 | 33 | | | | |
| **T7353-1616** | 25 | 1 | | | -1616 | 5.24 | 133 | 3.54 | 90 | 1.38 | 35 | | | | |
| **T7353-1620** | 25 | 1 | | | -1620 | 5.12 | 130 | 3.43 | 87 | 1.46 | 37 | | | | |
| **T7353-2020** | 31 | 1.1/4 | | | -2020 | 6.14 | 156 | 4.09 | 104 | 1.61 | 41 | | | | |
| **T7353-2024** | 31 | 1.1/4 | | | -2024 | 6.30 | 160 | 4.25 | 108 | 1.69 | 43 | | | | |
| **T7353-2424** | 38 | 1.1/2 | | | -2424 | 6.73 | 171 | 4.53 | 115 | 1.81 | 46 | | | | |
| **T7353-3232** | 51 | 2 | | | -3232 | 8.62 | 219 | 6.14 | 156 | 2.40 | 61 | | | | |

## SPECIAL FLANGE — T7354


**RYCO CODE 62C D-RING FLANGE**
**45° TUBE BEND**
O RING NOT SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7354-1212** | 19 | 3/4 | | | -1212 | 3.94 | 100 | 2.72 | 69 | 1.22 | 31 | | | | |
| **T7354-1216** | 19 | 3/4 | | | -1216 | 2.44 | 62 | 1.22 | 31 | 1.30 | 33 | | | | |
| **T7354-1616** | 25 | 1 | | | -1616 | 5.24 | 133 | 3.54 | 90 | 1.38 | 35 | | | | |
| **T7354-1620** | 25 | 1 | | | -1620 | 4.92 | 125 | 3.23 | 82 | 1.46 | 37 | | | | |
| **T7354-2020** | 31 | 1.1/4 | | | -2020 | 6.14 | 156 | 4.09 | 104 | 1.61 | 41 | | | | |
| **T7354-2024** | 31 | 1.1/4 | | | -2024 | 6.14 | 156 | 4.09 | 104 | 1.69 | 43 | | | | |

## SPECIAL FLANGE — T7463


**RYCO CODE 62C FLANGE**
**60° TUBE BEND**
O RING NOT SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7463-1212** | 19 | 3/4 | | | -1212 | 4.45 | 113 | 3.23 | 82 | 1.65 | 42 | | | | |
| **T7463-1216** | 19 | 3/4 | | | -1216 | 4.49 | 114 | 3.27 | 83 | 1.85 | 47 | | | | |
| **T7463-1616** | 25 | 1 | | | -1616 | 5.47 | 139 | 3.78 | 96 | 1.85 | 47 | | | | |
| **T7463-1620** | 25 | 1 | | | -1620 | 5.71 | 145 | 4.02 | 102 | 1.93 | 49 | | | | |
| **T7463-2020** | 31 | 1.1/4 | | | -2020 | 6.77 | 172 | 4.72 | 120 | 2.20 | 56 | | | | |
| **T7463-2024** | 31 | 1.1/4 | | | -2024 | 6.57 | 167 | 4.53 | 115 | 2.60 | 66 | | | | |
| **T7463-2424** | 38 | 1.1/2 | | | -2424 | 7.87 | 200 | 5.67 | 144 | 2.68 | 68 | | | | |

## SPECIAL FLANGE — T7464

**RYCO CODE 62C D-RING FLANGE**
**60° TUBE BEND**
O RING NOT SUPPLIED





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7464-1212** | 19 | 3/4 | | | -1212 | 4.45 | 113 | 3.23 | 82 | 1.65 | 42 | | | | |
| **T7464-1216** | 19 | 3/4 | | | -1216 | 2.44 | 62 | 1.22 | 31 | 1.65 | 42 | | | | |
| **T7464-1616** | 25 | 1 | | | -1616 | 5.47 | 139 | 3.78 | 96 | 1.85 | 47 | | | | |
| **T7464-1620** | 25 | 1 | | | -1620 | 5.67 | 144 | 3.98 | 101 | 1.93 | 49 | | | | |
| **T7464-2020** | 31 | 1.1/4 | | | -2020 | 6.77 | 172 | 4.72 | 120 | 2.20 | 56 | | | | |
| **T7464-2024** | 31 | 1.1/4 | | | -2024 | 6.61 | 168 | 4.57 | 116 | 2.60 | 66 | | | | |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

## SPECIAL FLANGE — T7363


**RYCO CODE 62C FLANGE**
**67.5° TUBE BEND**
O RING NOT SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7363-1212** | 19 | 3/4 | | | -1212 | 4.17 | 106 | 2.95 | 75 | 2.05 | 52 | | | | |
| **T7363-1216** | 19 | 3/4 | | | -1216 | 4.33 | 110 | 3.11 | 79 | 2.09 | 53 | | | | |
| **T7363-1616** | 25 | 1 | | | -1616 | 5.28 | 134 | 3.58 | 91 | 2.09 | 53 | | | | |
| **T7363-1620** | 25 | 1 | | | -1620 | 5.31 | 135 | 3.62 | 92 | 2.20 | 56 | | | | |
| **T7363-2020** | 31 | 1.1/4 | | | -2020 | 6.50 | 165 | 4.45 | 113 | 2.64 | 67 | | | | |
| **T7363-2024** | 31 | 1.1/4 | | | -2024 | 7.40 | 188 | 5.35 | 136 | 2.99 | 76 | | | | |
| **T7363-2424** | 38 | 1.1/2 | | | -2424 | 7.56 | 192 | 5.35 | 136 | 3.03 | 77 | | | | |

## SPECIAL FLANGE — T7364


**RYCO CODE 62C D-RING FLANGE**
**67.5° TUBE BEND**
O RING NOT SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7364-1212** | 19 | 3/4 | | | -1212 | 4.33 | 110 | 3.11 | 79 | 2.05 | 52 | | | | |
| **T7364-1216** | 19 | 3/4 | | | -1216 | 2.44 | 62 | 1.22 | 31 | 2.09 | 53 | | | | |
| **T7364-1616** | 25 | 1 | | | -1616 | 5.28 | 134 | 3.58 | 91 | 2.09 | 53 | | | | |
| **T7364-1620** | 25 | 1 | | | -1620 | 5.31 | 135 | 3.62 | 92 | 2.20 | 56 | | | | |
| **T7364-2020** | 31 | 1.1/4 | | | -2020 | 6.50 | 165 | 4.45 | 113 | 2.64 | 67 | | | | |
| **T7364-2024** | 31 | 1.1/4 | | | -2024 | 6.22 | 158 | 4.17 | 106 | 2.99 | 76 | | | | |

## SPECIAL FLANGE — T7373


**RYCO CODE 62C FLANGE**
**90° TUBE BEND**
O RING NOT SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7373-1212** | 19 | 3/4 | | | -1212 | 3.39 | 86 | 2.17 | 55 | 2.44 | 62 | | | | |
| **T7373-1216** | 19 | 3/4 | | | -1216 | 3.39 | 86 | 2.17 | 55 | 2.60 | 66 | | | | |
| **T7373-1616** | 25 | 1 | | | -1616 | 4.37 | 111 | 2.68 | 68 | 2.83 | 72 | | | | |
| **T7373-1620** | 25 | 1 | | | -1620 | 4.37 | 111 | 2.68 | 68 | 2.95 | 75 | | | | |
| **T7373-2020** | 31 | 1.1/4 | | | -2020 | 5.39 | 137 | 3.35 | 85 | 3.27 | 83 | | | | |
| **T7373-2024** | 31 | 1.1/4 | | | -2024 | 5.43 | 138 | 3.39 | 86 | 3.35 | 85 | | | | |
| **T7373-2424** | 38 | 1.1/2 | | | -2424 | 6.06 | 154 | 3.86 | 98 | 3.78 | 96 | | | | |
| **T7373-3232** | 51 | 2 | | | -3232 | 7.87 | 200 | 5.39 | 137 | 5.24 | 133 | | | | |

## SPECIAL FLANGE — T7378


**RYCO CODE 62C FLANGE**
**90° TUBE BEND**
O RING NOT SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7378-2020** | 31 | 1.1/4 | | | -2020 | 5.39 | 137 | 3.35 | 85 | 5.91 | 150 | | | | |
| **T7378-2024** | 31 | 1.1/4 | | | -2024 | 5.43 | 138 | 3.39 | 86 | 5.31 | 135 | | | | |

## SPECIAL FLANGE — T7374

**RYCO CODE 62C D-RING FLANGE**
**110° TUBE BEND**
O RING NOT SUPPLIED





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | | | | |
| **T7374-1212** | 19 | 3/4 | | | -1212 | 3.39 | 86 | 2.17 | 55 | 2.44 | 62 | | | | |
| **T7374-1216** | 19 | 3/4 | | | -1216 | 3.39 | 86 | 2.17 | 55 | 2.60 | 66 | | | | |
| **T7374-1616** | 25 | 1 | | | -1616 | 4.37 | 111 | 2.68 | 68 | 2.83 | 72 | | | | |
| **T7374-1620** | 25 | 1 | | | -1620 | 4.49 | 114 | 2.80 | 71 | 2.95 | 75 | | | | |
| **T7374-2020** | 31 | 1.1/4 | | | -2020 | 5.39 | 137 | 3.35 | 85 | 3.27 | 83 | | | | |
| **T7374-2024** | 31 | 1.1/4 | | | -2024 | 5.43 | 138 | 3.39 | 86 | 3.35 | 85 | | | | |

# ONE-PIECE COUPLINGS

## T7000 SERIES ONE-PIECE CRIMP COUPLINGS

### STANDPIPE — T7933


**RYCO CODE 62C FLANGE**
**110° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | inch | mm | inch | | | |
| **T7933-2424** | 38 | 1.1/2 | | | 1.1/2 | -2424 | 7.76 | 197 | 5.55 | 141 | 4.72 | 120 | | | |

### STANDPIPE — T7640


**METRIC STANDPIPE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | | | |
| **T7640-0814** | 12 | 1/2 | | 14 | -0814 | 2.60 | 66 | 1.54 | 39 | | | | | | |
| **T7640-1220** | 19 | 3/4 | | 20 | -1220 | 3.03 | 77 | 1.81 | 46 | | | | | | |
| **T7640-2030** | 31 | 1.1/4 | | 30 | -2030 | 4.37 | 111 | 2.32 | 59 | | | | | | |

### SALVAGE / LIFESAVER — T7230


**SALVAGE (LIFESAVER)**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | | inch | mm |
| **T7230-0808** | 12 | 1/2 | | 1/2 | -0808 | 1.81 | 46 | 0.75 | 19 | | | | | 11/16 | |
| **T7230-0810** | 12 | 1/2 | | 5/8 | -0810 | 1.89 | 48 | 0.83 | 21 | | | | | 7/8 | 22 |
| **T7230-1210** | 19 | 3/4 | | 5/8 | -1210 | 2.24 | 57 | 1.02 | 26 | | | | | 1.1/8 | |
| **T7230-1212** | 19 | 3/4 | | 3/4 | -1212 | 2.05 | 52 | 0.83 | 21 | | | | | 1 | |
| **T7230-1216** | 19 | 3/4 | | 1 | -1216 | 2.28 | 58 | 1.10 | 28 | | | | | 1.3/8 | 35 |
| **T7230-1612** | 25 | 1 | | 3/4 | -1612 | 2.72 | 69 | 1.02 | 26 | | | | | 1.3/8 | 35 |
| **T7230-1616** | 25 | 1 | | 1 | -1616 | 2.80 | 71 | 1.10 | 28 | | | | | 1.3/8 | 35 |
| **T7230-1620** | 25 | 1 | | 1.1/4 | -1620 | 2.83 | 72 | 1.14 | 29 | | | | | 1.3/4 | |
| **T7230-2016** | 31 | 1.1/4 | | 1 | -2016 | 3.27 | 83 | 1.22 | 31 | | | | | 1.3/4 | |
| **T7230-2020** | 31 | 1.1/4 | | 1.1/4 | -2020 | 3.27 | 83 | 1.22 | 31 | | | | | 1.3/4 | |
| **T7230-2424** | 38 | 1.1/2 | | 1.1/2 | -2424 | 3.54 | 90 | 1.34 | 34 | | | | | 2 | 50 |
| **T7230-3232** | 51 | 2 | | 2 | -3232 | 4.09 | 104 | 1.61 | 41 | | | | | 2.1/2 | |

## UNO (O RING BOSS) — T7200


**UN O RING MALE**
O RING SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **T7200-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.68 | 68 | 1.46 | 37 | | | | | 1.1/4 | 32 |
| **T7200-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 3.23 | 82 | 1.54 | 39 | | | | | 1.1/2 | 38 |

## HAMMER UNION — T71501


**FIGURE 1502 MALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | | | | | |
| **T71501-2432** | 38 | 1.1/2 | 4.1/8 | | 2 | -2432 | 5.83 | 148 | 3.58 | 91 | | | | | |
| **T71501-3232** | 51 | 2 | 4.1/8 | | 2 | -3232 | 6.06 | 154 | 3.62 | 92 | | | | | |

## HAMMER UNION — T71502

**FIGURE 1502 (WITH NUT)**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | | | | | |
| **T71502-2432** | 38 | 1.1/2 | 4.1/8 | | 2 | -2432 | 6.57 | 167 | 4.33 | 110 | | | | | |
| **T71502-3232** | 51 | 2 | 4.1/8 | | 2 | -3232 | 6.81 | 173 | 4.37 | 111 | | | | | |

# ONE-PIECE COUPLINGS


## TP000 SERIES ONE-PIECE CRIMP COUPLINGS

**HOSE COMPATIBILITY FOR TP000 SERIES**

**NON-SKIVE**
For Ryco Hose Series TP7, TP7N, TP7T, TP7TN, TP8, TP8N, TP8T, TP8TN, TP3000 (all sizes).

## BSPT — TP010


**BSPT MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **TP010-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.32 | 59 | 1.30 | 33 | | | | | 9/16 | |
| **TP010-0406** | 6 | 1/4 | 3/8" -19 | | -0406 | 2.28 | 58 | 1.22 | 31 | | | | | 11/16 | |
| **TP010-0506** | 8 | 5/16 | 3/8" -19 | | -0506 | 2.09 | 53 | 1.22 | 31 | | | | | 11/16 | |
| **TP010-0604** | 10 | 3/8 | 1/4" -19 | | -0604 | 2.44 | 62 | 1.38 | 35 | | | | | 5/8 | 16 |
| **TP010-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.44 | 62 | 1.38 | 35 | | | | | 11/16 | |
| **TP010-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.64 | 67 | 1.57 | 40 | | | | | 7/8 | 22 |
| **TP010-0806** | 12 | 1/2 | 3/8" -19 | | -0806 | 2.64 | 67 | 1.42 | 36 | | | | | 11/16 | |
| **TP010-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.83 | 72 | 1.61 | 41 | | | | | 7/8 | 22 |
| **TP010-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.03 | 77 | 1.69 | 43 | | | | | 1.1/16 | 27 |
| **TP010-1616** | 25 | 1 | 1" -11 | | -1616 | 3.39 | 86 | 1.93 | 49 | | | | | 1.3/8 | 35 |

## BSPP — TP020

**BSPP FEMALE**
**60 ° CONE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **TP020-0304** | 5 | 3/16 | 1/4" -19 | | -0304 | 2.05 | 52 | 1.02 | 26 | | | 3/4 | 19 | 1/2 | |
| **TP020-0402** | 6 | 1/4 | 1/8" -28 | | -0402 | 2.09 | 53 | 1.02 | 26 | | | | 14 | 1/2 | |
| **TP020-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.09 | 53 | 1.06 | 27 | | | 3/4 | 19 | 1/2 | |
| **TP020-0406** | 6 | 1/4 | 3/8" -19 | | -0406 | 2.20 | 56 | 1.14 | 29 | | | 7/8 | 22 | 5/8 | 16 |
| **TP020-0504** | 8 | 5/16 | 1/4" -19 | | -0504 | 2.01 | 51 | 0.94 | 24 | | | 3/4 | 19 | 9/16 | 14 |
| **TP020-0506** | 8 | 5/16 | 3/8" -19 | | -0506 | 2.20 | 56 | 1.14 | 29 | | | 7/8 | 22 | 5/8 | 16 |
| **TP020-0604** | 10 | 3/8 | 1/4" -19 | | -0604 | 2.05 | 52 | 0.94 | 24 | | | 3/4 | 19 | 9/16 | 14 |
| **TP020-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.24 | 57 | 1.14 | 29 | | | 7/8 | 22 | 5/8 | 16 |
| **TP020-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.28 | 58 | 1.22 | 31 | | | 1.1/16 | 27 | 3/4 | 19 |
| **TP020-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.32 | 59 | 1.10 | 28 | | | 1.1/16 | 27 | 3/4 | 19 |
| **TP020-0810** | 12 | 1/2 | 5/8" -14 | | -0810 | 2.36 | 60 | 1.14 | 29 | | | 1.3/16 | 30 | 7/8 | 22 |
| **TP020-0812** | 12 | 1/2 | 3/4" -14 | | -0812 | 2.44 | 62 | 1.22 | 31 | | | 1.1/4 | 32 | 1 | 0 |
| **TP020-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.60 | 66 | 1.18 | 30 | | | 1.1/4 | 32 | 1 | |
| **TP020-1616** | 25 | 1 | 1" -11 | | -1616 | 2.99 | 76 | 1.50 | 38 | | | 1.1/2 | 38 | 1.1/4 | 32 |

## BSPP

## TP050

**BSPP FEMALE**
**60° CONE**
**90° ELBOW**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **TP050-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.93 | 49 | 0.87 | 22 | 0.94 | 24 | 3/4 | 19 | 9/16 | |
| **TP050-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 1.97 | 50 | 0.91 | 23 | 1.10 | 28 | 7/8 | 22 | 3/4 | 19 |
| **TP050-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.32 | 59 | 1.14 | 29 | 1.22 | 31 | 1.1/16 | 27 | 7/8 | 22 |

## JIS

## TP122

**BSPP FEMALE**
**60° CONCAVE SEAT (JIS)**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **TP122-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.01 | 51 | 0.94 | 24 | | | 3/4 | 19 | | 14 |
| **TP122-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.17 | 55 | 1.06 | 27 | | | 7/8 | 22 | | 17 |
| **TP122-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.20 | 56 | 1.14 | 29 | | | 1.1/16 | 27 | 7/8 | 22 |
| **TP122-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.32 | 59 | 1.14 | 29 | | | 1.1/16 | 27 | 7/8 | 22 |
| **TP122-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.44 | 62 | 1.10 | 28 | | | | 36 | 1.1/16 | 27 |

## BSPP

## TP260

**BSPP FEMALE**
**60° CONE**
**90° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP260-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.13 | 54 | 1.10 | 28 | 1.14 | 29 | 3/4 | 19 | | |
| **TP260-0406** | 6 | 1/4 | 3/8" -19 | | -0406 | 2.13 | 54 | 1.10 | 28 | 1.10 | 28 | 7/8 | 22 | | |
| **TP260-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.44 | 62 | 1.38 | 35 | 1.30 | 33 | 7/8 | 22 | | |
| **TP260-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.44 | 62 | 1.38 | 35 | 1.30 | 33 | 1.1/16 | 27 | | |
| **TP260-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.68 | 68 | 1.50 | 38 | 1.77 | 45 | 1.1/16 | 27 | | |
| **TP260-0810** | 12 | 1/2 | 5/8" -14 | | -0810 | 2.76 | 70 | 1.57 | 40 | 1.77 | 45 | 1.3/16 | 30 | | |
| **TP260-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.58 | 91 | 2.17 | 55 | 2.32 | 59 | 1.1/4 | 32 | | |
| **TP260-1616** | 25 | 1 | 1" -11 | | -1616 | 4.09 | 104 | 2.68 | 68 | 3.07 | 78 | 1.1/2 | 38 | | |

# ONE-PIECE COUPLINGS

## TP000 SERIES ONE-PIECE CRIMP COUPLINGS

### BSPP — TP270


**BSPP FEMALE**
**60° CONE**
**|45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP270-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.44 | 62 | 1.42 | 36 | 0.67 | 17 | 3/4 | 19 | | |
| **TP270-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.80 | 71 | 1.73 | 44 | 0.71 | 18 | 7/8 | 22 | | |
| **TP270-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 3.15 | 80 | 1.97 | 50 | 0.87 | 22 | 1.1/16 | 27 | | |
| **TP270-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 4.17 | 106 | 2.76 | 70 | 1.14 | 29 | 1.1/4 | 32 | | |
| **TP270-1616** | 25 | 1 | 1" -11 | | -1616 | 4.76 | 121 | 3.35 | 85 | 1.65 | 42 | 1.1/2 | 38 | | |

### BSP - BANJO — TP475

**BSP BANJO STRAIGHT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **TP475-0404** | 6 | 1/4 | 1/4 | | -0404 | 2.05 | 52 | 0.98 | 25 | | | | | | |
| **TP475-0506** | 8 | 5/16 | 3/8 | | -0506 | 2.12 | 54 | 1.07 | 27 | | | | | | |
| **TP475-0606** | 10 | 3/8 | 3/8 | | -0606 | 2.17 | 55 | 1.06 | 27 | | | | | | |
| **TP475-0608** | 10 | 3/8 | 1/2 | | -0608 | 2.20 | 56 | 1.10 | 28 | | | | | | |
| **TP475-0808** | 12 | 1/2 | 1/2 | | -0808 | 2.32 | 59 | 1.10 | 28 | | | | | | |
| **TP475-1212** | 19 | 3/4 | 3/4 | | -1212 | 2.67 | 68 | 1.23 | 31 | | | | | | |
| **TP475-1616** | 25 | 1 | 1 | | -1616 | 3.23 | 82 | 1.75 | 45 | | | | | | |

## NPTF

## TP090

**NPTF MALE**
**60° SEAT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **TP090-0302** | 5 | 3/16 | 1/8" -27 | | -0302 | 2.13 | 54 | 1.10 | 28 | | | | | 1/2 | |
| **TP090-0304** | 5 | 3/16 | 1/4" -18 | | -0304 | 2.28 | 58 | 1.26 | 32 | | | | | 9/16 | |
| **TP090-0402** | 6 | 1/4 | 1/8" -27 | | -0402 | 2.17 | 55 | 1.10 | 28 | | | | | 1/2 | |
| **TP090-0404** | 6 | 1/4 | 1/4" -18 | | -0404 | 2.32 | 59 | 1.30 | 33 | | | | | 9/16 | |
| **TP090-0406** | 6 | 1/4 | 3/8" -18 | | -0406 | 2.32 | 59 | 1.30 | 33 | | | | | 11/16 | |
| **TP090-0506** | 8 | 5/16 | 3/8" -18 | | -0506 | 2.36 | 60 | 1.30 | 33 | | | | | 11/16 | |
| **TP090-0604** | 10 | 3/8 | 1/4" -18 | | -0604 | 2.44 | 62 | 1.38 | 35 | | | | | 5/8 | 16 |
| **TP090-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 2.44 | 62 | 1.38 | 35 | | | | | 11/16 | |
| **TP090-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.64 | 67 | 1.57 | 40 | | | | | 7/8 | 22 |
| **TP090-0806** | 12 | 1/2 | 3/8" -18 | | -0806 | 2.64 | 67 | 1.42 | 36 | | | | | 11/16 | |
| **TP090-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.83 | 72 | 1.61 | 41 | | | | | 7/8 | 22 |
| **TP090-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.03 | 77 | 1.69 | 43 | | | | | 1.1/16 | 27 |
| **TP090-1616** | 25 | 1 | 1" -11,5 | | -1616 | 3.39 | 86 | 1.93 | 49 | | | | | 1.3/8 | 35 |

## NPTF

## TP340N

**NPTF MALE SWIVEL**
**90° ELBOW**
**60° SEAT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **TP340N-0304** | 5 | 3/16 | 1/4" -18 | | -0304 | 1.85 | 47 | 0.87 | 22 | 1.61 | 41 | 11/16 | | 9/16 | |
| **TP340N-0404** | 6 | 1/4 | 1/4" -18 | | -0404 | 1.93 | 49 | 0.87 | 22 | 1.61 | 41 | 11/16 | | 9/16 | |
| **TP340N-0506** | 8 | 5/16 | 3/8" -18 | | -0506 | 1.97 | 50 | 0.91 | 23 | 1.77 | 45 | 7/8 | 22 | 3/4 | 19 |
| **TP340N-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 1.97 | 50 | 0.91 | 23 | 1.77 | 45 | 7/8 | 22 | 3/4 | 19 |
| **TP340N-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.32 | 59 | 1.14 | 29 | 2.01 | 51 | 1 | | 7/8 | 22 |

# ONE-PIECE COUPLINGS

## TP000 SERIES ONE-PIECE CRIMP COUPLINGS

### NPSM — TP020N


**NPSM FEMALE**
**60° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | | inch | |
| **TP020N-0404** | 6 | 1/4 | 1/4" -18 | | -0404 | 2.01 | 51 | 0.94 | 24 | | | 11/16 | | 1/2 | |

### JIC — TP030


**JIC**
**37° CONE MALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **TP030-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 2.28 | 58 | 1.26 | 32 | | | | | 1/2 | |
| **TP030-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.32 | 59 | 1.26 | 32 | | | | | 1/2 | |
| **TP030-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 2.32 | 59 | 1.26 | 32 | | | | | 9/16 | |
| **TP030-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.28 | 58 | 1.22 | 31 | | | | | 5/8 | 16 |
| **TP030-0508** | 8 | 5/16 | 1/2" - 20 | | -0508 | 2.32 | 59 | 1.26 | 32 | | | | | 9/16 | 14 |
| **TP030-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.32 | 59 | 1.26 | 32 | | | | | 5/8 | 16 |
| **TP030-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.44 | 62 | 1.38 | 35 | | | | | 5/8 | 16 |
| **TP030-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.52 | 64 | 1.46 | 37 | | | | | 3/4 | 19 |
| **TP030-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.72 | 69 | 1.54 | 39 | | | | | 3/4 | 19 |
| **TP030-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.83 | 72 | 1.61 | 41 | | | | | 15/16 | 24 |
| **TP030-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.11 | 79 | 1.77 | 45 | | | | | 1.1/8 | |
| **TP030-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 3.35 | 85 | 1.89 | 48 | | | | | 1.3/8 | 35 |

### JIC — TP031


**JIC MALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **TP031-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | | | | | | | | | | |
| **TP031-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | | | | | | | | | | |
| **TP031-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | | | | | | | | | | |
| **TP031-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | | | | | | | | | | |

## JSEAL™ / JIC — TP040


JIC 37°
CONE MALE




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **TP040-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 1.97 | 50 | 0.94 | 24 | | | 9/16 | | 1/2 | |
| **TP040-0308** | 5 | 3/16 | 1/2" - 20 | | -0308 | 1.97 | 50 | 0.94 | 24 | | | 5/8 | 16 | 1/2 | |
| **TP040-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.01 | 51 | 0.98 | 25 | | | 9/16 | | 1/2 | |
| **TP040-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 2.01 | 51 | 0.98 | 25 | | | 5/8 | 16 | 1/2 | |
| **TP040-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.05 | 52 | 0.98 | 25 | | | 11/16 | | 9/16 | |
| **TP040-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.05 | 52 | 0.98 | 25 | | | 11/16 | | 9/16 | |
| **TP040-0607** | 10 | 3/8 | 7/16" -20 | | -0607 | 1.95 | 50 | 0.88 | 22 | | | | | | |
| **TP040-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.05 | 52 | 0.98 | 25 | | | 11/16 | | 9/16 | |
| **TP040-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.13 | 54 | 1.06 | 27 | | | 7/8 | 22 | 11/16 | |
| **TP040-0809** | 12 | 1/2 | 9/16" -18 | | -0809 | 2.13 | 54 | 0.91 | 23 | | | 11/16 | | 11/16 | |
| **TP040-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.17 | 55 | 0.94 | 24 | | | 7/8 | 22 | 11/16 | |
| **TP040-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.44 | 62 | 1.22 | 31 | | | 1 | | 13/16 | |
| **TP040-1214** | 19 | 3/4 | 7/8" -14 | | -1214 | 2.72 | 69 | 1.38 | 35 | | | 1 | | 1 | |
| **TP040-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.72 | 69 | 1.30 | 33 | | | 1.1/4 | 32 | 1 | |
| **TP040-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 2.99 | 76 | 1.50 | 38 | | | 1.1/2 | 38 | 1.1/4 | 32 |

## JSEAL™ / JIC — TP041

JSEAL™ / JIC FEMALE
CONVEX SEAT
METRIC NUT ONLY





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | | |
| **TP041-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 1.97 | 50 | 0.94 | 24 | | | | 14 | | |
| **TP041-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.01 | 51 | 0.98 | 25 | | | | 14 | | |
| **TP041-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.05 | 52 | 0.98 | 25 | | | 3/4 | 19 | | |
| **TP041-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.05 | 52 | 0.98 | 25 | | | 3/4 | 19 | | |
| **TP041-0607** | 10 | 3/8 | 7/16" -20 | | -0607 | 1.95 | 50 | 0.87 | 22 | | | | 14 | | |
| **TP041-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.05 | 52 | 0.98 | 25 | | | 3/4 | 19 | | |
| **TP041-0809** | 12 | 1/2 | 9/16" -18 | | -0809 | 2.13 | 54 | 0.91 | 23 | | | 3/4 | 19 | | |

# ONE-PIECE COUPLINGS

## TP000 SERIES ONE-PIECE CRIMP COUPLINGS

### JSEAL™ / JIC — TP250


**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP250-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.36 | 60 | 1.34 | 34 | 0.59 | 15 | 9/16 | | | |
| **TP250-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.36 | 60 | 1.34 | 34 | 0.59 | 15 | 11/16 | | | |
| **TP250-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.56 | 65 | 1.50 | 38 | 0.55 | 14 | 11/16 | | | |
| **TP250-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.60 | 66 | 1.54 | 39 | 0.67 | 17 | 7/8 | 22 | | |
| **TP250-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.99 | 76 | 1.81 | 46 | 0.83 | 21 | 7/8 | 22 | | |
| **TP250-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 3.03 | 77 | 1.85 | 47 | 1.85 | 47 | 1 | | | |
| **TP250-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 4.21 | 107 | 2.80 | 71 | 1.10 | 28 | 1.1/4 | 32 | | |

### JSEAL™ / JIC — TP251


**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**45° TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP251-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.36 | 60 | 1.34 | 34 | 0.59 | 15 | | 14 | | |
| **TP251-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.36 | 60 | 1.34 | 34 | 0.59 | 15 | 3/4 | 19 | | |
| **TP251-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.56 | 65 | 1.50 | 38 | 0.55 | 14 | 3/4 | 19 | | |

## JSEAL™ / JIC — TP240


JSEAL™ / JIC
FEMALE CONVEX SEAT
90° TUBE BEND




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP240-0307** | 5 | 3/16 | 7/16" -20 | | -0307 | 2.09 | 53 | 1.02 | 26 | 1.26 | 32 | 9/16 | | | |
| **TP240-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.09 | 53 | 1.02 | 26 | 1.26 | 32 | 9/16 | | | |
| **TP240-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 2.09 | 53 | 1.02 | 26 | 1.26 | 32 | 5/8 | 16 | | |
| **TP240-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.09 | 53 | 1.02 | 26 | 1.50 | 38 | 11/16 | | | |
| **TP240-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.09 | 53 | 1.02 | 26 | 1.50 | 38 | 11/16 | | | |
| **TP240-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.44 | 62 | 1.38 | 35 | 0.98 | 25 | 11/16 | | | |
| **TP240-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.44 | 62 | 1.38 | 35 | 1.18 | 30 | 7/8 | 22 | | |
| **TP240-0809** | 12 | 1/2 | 9/16" -18 | | -0809 | 2.56 | 65 | 1.38 | 35 | 0.98 | 25 | 11/16 | | | |
| **TP240-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.76 | 70 | 1.57 | 40 | 1.61 | 41 | 7/8 | 22 | | |
| **TP240-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.76 | 70 | 1.57 | 40 | 1.61 | 41 | 1 | | | |
| **TP240-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.62 | 92 | 2.20 | 56 | 2.24 | 57 | 1.1/4 | 32 | | |
| **TP240-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.09 | 104 | 2.68 | 68 | 2.83 | 72 | 1.1/2 | 38 | | |

## JSEAL™ / JIC — TP241

JSEAL™ / JIC FEMALE
CONVEX SEAT
90° TUBE BEND
METRIC NUT ONLY





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP241-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.09 | 53 | 1.02 | 26 | 1.26 | 32 | | 14 | | |
| **TP241-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.09 | 53 | 1.02 | 26 | 1.50 | 38 | 3/4 | 19 | | |
| **TP241-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 2.09 | 53 | 1.02 | 26 | 1.50 | 38 | 3/4 | 19 | | |
| **TP241-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.44 | 62 | 1.38 | 35 | 0.98 | 25 | 3/4 | 19 | | |
| **TP241-0809** | 12 | 1/2 | 9/16" -18 | | -0809 | 2.56 | 65 | 1.38 | 35 | 0.98 | 25 | 3/4 | 19 | | |

# ONE-PIECE COUPLINGS

## TP000 SERIES ONE-PIECE CRIMP COUPLINGS


### JSEAL™ / JIC — TP280




**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**90° LONG TUBE BEND**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP280-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 3.11 | 79 | 2.05 | 52 | 2.17 | 55 | 11/16 | | | |
| **TP280-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 3.39 | 86 | 2.32 | 59 | 2.52 | 64 | 7/8 | 22 | | |


### JSEAL™ / JIC — TP281




**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**90° LONG TUBE BEND**
**METRIC NUT ONLY**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP281-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 3.11 | 79 | 2.05 | 52 | 2.17 | 55 | 3/4 | 19 | | |

### METRIC - DKL — TP650





**DKL MALE**
**24° SEAT**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | | | inch | mm |
| **TP650-0412** | 6 | 1/4 | M 12X1,5 | 6 | -0412 | 2.17 | 55 | 0.98 | 25 | | | | | | 14 |
| **TP650-0414** | 6 | 1/4 | M 14X1,5 | 8 | -0414 | 2.17 | 55 | 0.98 | 25 | | | | | | 14 |
| **TP650-0416** | 6 | 1/4 | M 16X1,5 | 10 | -0416 | 2.20 | 56 | 1.14 | 29 | | | | | | 17 |
| **TP650-0516** | 8 | 5/16 | M 16X1,5 | 10 | -0516 | 2.20 | 56 | 1.14 | 29 | | | | | | 17 |
| **TP650-0518** | 8 | 5/16 | M 18X1,5 | 12 | -0518 | 2.09 | 53 | 1.06 | 27 | | | | | 3/4 | 19 |
| **TP650-0616** | 10 | 3/8 | M 16X1,5 | 10 | -0616 | 2.32 | 59 | 1.22 | 31 | | | | | | 17 |
| **TP650-0618** | 10 | 3/8 | M 18X1,5 | 12 | -0618 | 2.32 | 59 | 1.22 | 31 | | | | | 3/4 | 19 |
| **TP650-0622** | 10 | 3/8 | M 22X1,5 | 15 | -0622 | 2.24 | 57 | 1.18 | 30 | | | | | 15/16 | 24 |
| **TP650-0822** | 12 | 1/2 | M 22X1,5 | 15 | -0822 | 2.52 | 64 | 1.34 | 34 | | | | | 7/8 | 22 |
| **TP650-0826** | 12 | 1/2 | M 26X1,5 | 18 | -0826 | 2.52 | 64 | 1.34 | 34 | | | | | 1.3/16 | 30 |
| **TP650-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 2.64 | 67 | 1.30 | 33 | | | | | 1.1/4 | 32 |
| **TP650-1636** | 25 | 1 | M 36X2 | 28 | -1636 | 2.99 | 76 | 1.50 | 38 | | | | | 1.5/8 | 41 |

## METRIC - DKOL

## TP501

**DKOL FEMALE**
**24° CONE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | inch | mm | | |
| **TP501-0412** | 6 | 1/4 | M 12X1,5 | 6 | -0412 | 1.89 | 48 | 0.87 | 22 | | | | 14 | | |
| **TP501-0414** | 6 | 1/4 | M 14X1,5 | 8 | -0414 | 1.93 | 49 | 0.87 | 22 | | | | 17 | | |
| **TP501-0416** | 6 | 1/4 | M 16X1,5 | 10 | -0416 | 1.97 | 50 | 0.94 | 24 | | | 3/4 | 19 | | |
| **TP501-0514** | 8 | 5/16 | M 14X1,5 | 8 | -0514 | 1.93 | 49 | 0.87 | 22 | | | | 17 | | |
| **TP501-0516** | 8 | 5/16 | M 16X1,5 | 10 | -0516 | 2.09 | 53 | 1.02 | 26 | | | 3/4 | 19 | | |
| **TP501-0518** | 8 | 5/16 | M 18X1,5 | 12 | -0518 | 2.05 | 52 | 1.02 | 26 | | | 7/8 | 22 | | |
| **TP501-0616** | 10 | 3/8 | M 16X1,5 | 10 | -0616 | 1.97 | 50 | 0.91 | 23 | | | 3/4 | 19 | | |
| **TP501-0618** | 10 | 3/8 | M 18X1,5 | 12 | -0618 | 2.01 | 51 | 0.94 | 24 | | | 7/8 | 22 | | |
| **TP501-0822** | 12 | 1/2 | M 22X1,5 | 15 | -0822 | 2.20 | 56 | 0.98 | 25 | | | 1.1/16 | 27 | | |
| **TP501-0826** | 12 | 1/2 | M 26X1,5 | 18 | -0826 | 2.28 | 58 | 1.10 | 28 | | | 1.1/4 | 32 | | |
| **TP501-1226** | 19 | 3/4 | M 26X1,5 | 18 | -1226 | 2.52 | 64 | 1.18 | 30 | | | 1.1/4 | 32 | | |
| **TP501-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 2.44 | 62 | 1.14 | 29 | | | | 36 | | |
| **TP501-1636** | 25 | 1 | M 36X2 | 28 | -1636 | 2.83 | 72 | 1.34 | 34 | | | 1.5/8 | 41 | | |

## METRIC - DKOL

## TP510

**DKOL FEMALE**
**24° CONE**
**45° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP510-0412** | 6 | 1/4 | M 12X1,5 | 6 | -0412 | 2.44 | 62 | 1.42 | 36 | 0.71 | 18 | | 14 | | |
| **TP510-0414** | 6 | 1/4 | M 14X1,5 | 8 | -0414 | 2.44 | 62 | 1.38 | 35 | 0.67 | 17 | | 17 | | |
| **TP510-0516** | 8 | 5/16 | M 16X1,5 | 10 | -0516 | 2.13 | 54 | 1.06 | 27 | 1.22 | 31 | 3/4 | 19 | | |
| **TP510-0518** | 8 | 5/16 | M 18X1,5 | 12 | -0518 | 2.52 | 64 | 1.46 | 37 | 0.79 | 20 | 7/8 | 22 | | |
| **TP510-0616** | 10 | 3/8 | M 16X1,5 | 10 | -0616 | 2.83 | 72 | 1.77 | 45 | 0.75 | 19 | 3/4 | 19 | | |
| **TP510-0618** | 10 | 3/8 | M 18X1,5 | 12 | -0618 | 2.83 | 72 | 1.77 | 45 | 0.79 | 20 | 7/8 | 22 | | |
| **TP510-0822** | 12 | 1/2 | M 22X1,5 | 15 | -0822 | 3.19 | 81 | 2.01 | 51 | 0.87 | 22 | 1.1/16 | 27 | | |
| **TP510-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 4.21 | 107 | 2.87 | 73 | 1.22 | 31 | | 36 | | |
| **TP510-1636** | 25 | 1 | M 36X2 | 28 | -1636 | 5.00 | 127 | 3.58 | 91 | 1.81 | 46 | 1.5/8 | 41 | | |

# ONE-PIECE COUPLINGS

## TP000 SERIES ONE-PIECE CRIMP COUPLINGS

### METRIC - DKOL | TP520


**DKOL FEMALE**
**24° CONE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP520-0412** | 6 | 1/4 | M 12X1,5 | 6 | -0412 | 2.20 | 56 | 1.06 | 27 | 1.22 | 31 | | 14 | | |
| **TP520-0414** | 6 | 1/4 | M 14X1,5 | 8 | -0414 | 2.17 | 55 | 1.02 | 26 | 1.22 | 31 | | 17 | | |
| **TP520-0416** | 6 | 1/4 | M 16X1,5 | 10 | -0416 | 2.13 | 54 | 1.06 | 27 | 1.22 | 31 | 3/4 | 19 | | |
| **TP520-0516** | 8 | 5/16 | M 16X1,5 | 10 | -0516 | 2.13 | 54 | 1.06 | 27 | 1.22 | 31 | 3/4 | 19 | | |
| **TP520-0518** | 8 | 5/16 | M 18X1,5 | 12 | -0518 | 2.13 | 54 | 1.06 | 27 | 1.42 | 36 | 7/8 | 22 | | |
| **TP520-0616** | 10 | 3/8 | M 16X1,5 | 10 | -0616 | 2.40 | 61 | 1.34 | 34 | 1.38 | 35 | 3/4 | 19 | | |
| **TP520-0618** | 10 | 3/8 | M 18X1,5 | 12 | -0618 | 2.48 | 63 | 1.42 | 36 | 1.38 | 35 | 7/8 | 22 | | |
| **TP520-0822** | 12 | 1/2 | M 22X1,5 | 15 | -0822 | 2.76 | 70 | 1.57 | 40 | 1.73 | 44 | 1.1/16 | 27 | | |
| **TP520-0826** | 12 | 1/2 | M 26X1,5 | 18 | -0826 | 2.76 | 70 | 1.57 | 40 | 1.89 | 48 | 1.1/4 | 32 | | |
| **TP520-1230** | 19 | 3/4 | M 30X2 | 22 | -1230 | 3.54 | 90 | 2.20 | 56 | 2.56 | 65 | | 36 | | |
| **TP520-1636** | 25 | 1 | M 36X2 | 28 | -1636 | 4.13 | 105 | 2.72 | 69 | 3.11 | 79 | 1.5/8 | 41 | | |

### METRIC - DKS | TP630

**DKS MALE**
**24° SEAT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | | | inch | mm | inch | mm | | | | | inch | mm |
| **TP630-0416** | 6 | 1/4 | M 16X1,5 | | -0416 | 2.24 | 57 | 1.06 | 27 | | | | | | 17 |
| **TP630-0418** | 6 | 1/4 | M 18X1,5 | | -0418 | 2.13 | 54 | 0.91 | 23 | | | | | 3/4 | 19 |
| **TP630-0520** | 8 | 5/16 | M 20X1,5 | | -0520 | 2.32 | 59 | 1.26 | 32 | | | | | 7/8 | 22 |
| **TP630-0620** | 10 | 3/8 | M 20X1,5 | | -0620 | 2.36 | 60 | 1.26 | 32 | | | | | 7/8 | 22 |
| **TP630-0622** | 10 | 3/8 | M 22X1,5 | | -0622 | 2.32 | 59 | 1.22 | 31 | | | | | 15/16 | 24 |
| **TP630-0824** | 12 | 1/2 | M 24X1,5 | | -0824 | 2.44 | 62 | 1.22 | 31 | | | | | 1.1/16 | 27 |
| **TP630-1230** | 19 | 3/4 | M 30X2 | | -1230 | 2.80 | 71 | 1.46 | 37 | | | | | 1.1/4 | 32 |
| **TP630-1236** | 19 | 3/4 | M 36X2 | | -1236 | 2.87 | 73 | 1.54 | 39 | | | | | 1.5/8 | 41 |
| **TP630-1642** | 25 | 1 | M 42X2 | | -1642 | 3.23 | 82 | 1.73 | 44 | | | | | | 46 |

## METRIC - DKOS

## TP711

**DKOS FEMALE**
**24° CONE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | | | inch | mm | | |
| **TP711-0414** | 6 | 1/4 | M 14X1,5 | 6 | -0414 | 1.93 | 49 | 0.79 | 20 | | | | 17 | | |
| **TP711-0416** | 6 | 1/4 | M 16X1,5 | 8 | -0416 | 2.09 | 53 | 0.91 | 23 | | | 3/4 | 19 | | |
| **TP711-0418** | 6 | 1/4 | M 18X1,5 | 10 | -0418 | 2.13 | 54 | 0.98 | 25 | | | 7/8 | 22 | | |
| **TP711-0518** | 8 | 5/16 | M 18X1,5 | 10 | -0518 | 2.13 | 54 | 1.06 | 27 | | | 7/8 | 22 | | |
| **TP711-0520** | 8 | 5/16 | M 20X1,5 | 12 | -0520 | 2.13 | 54 | 1.06 | 27 | | | 15/16 | 24 | | |
| **TP711-0620** | 10 | 3/8 | M 20X1,5 | 12 | -0620 | 2.13 | 54 | 1.06 | 27 | | | 15/16 | 24 | | |
| **TP711-0622** | 10 | 3/8 | M 22X1,5 | 14 | -0622 | 2.20 | 56 | 1.14 | 29 | | | 1.1/16 | 27 | | |
| **TP711-0624** | 10 | 3/8 | M 24X1,5 | 16 | -0624 | 2.20 | 56 | 1.14 | 29 | | | 1.3/16 | 30 | | |
| **TP711-0824** | 12 | 1/2 | M 24X1,5 | 16 | -0824 | 2.32 | 59 | 1.10 | 28 | | | 1.3/16 | 30 | | |
| **TP711-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 2.60 | 66 | 1.30 | 33 | | | | 36 | | |
| **TP711-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 2.76 | 70 | 1.42 | 36 | | | | 46 | | |
| **TP711-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 2.95 | 75 | 1.50 | 38 | | | 2 | 50 | | |

## METRIC - DKOS

## TP720

**DKOS FEMALE**
**24° CONE**
**45° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | | | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | | | |
| **TP720-0414** | 6 | 1/4 | M 14X1,5 | 6 | -0414 | 2.52 | 64 | 1.38 | 35 | 0.63 | 16 | | 17 | | | | |
| **TP720-0416** | 6 | 1/4 | M 16X1,5 | 8 | -0416 | 2.56 | 65 | 1.42 | 36 | 0.67 | 17 | 3/4 | 19 | | | | |
| **TP720-0418** | 6 | 1/4 | M 18X1,5 | 10 | -0418 | 2.52 | 64 | 1.38 | 35 | 0.67 | 17 | 7/8 | 22 | | | | |
| **TP720-0518** | 8 | 5/16 | M 18X1,5 | 10 | -0518 | 2.44 | 62 | 1.38 | 35 | 0.67 | 17 | 7/8 | 22 | | | | |
| **TP720-0520** | 8 | 5/16 | M 20X1,5 | 12 | -0520 | 2.87 | 73 | 1.81 | 46 | 0.79 | 20 | 15/16 | 24 | | | | |
| **TP720-0620** | 10 | 3/8 | M 20X1,5 | 12 | -0620 | 2.87 | 73 | 1.81 | 46 | 0.79 | 20 | 15/16 | 24 | | | | |
| **TP720-0622** | 10 | 3/8 | M 22X1,5 | 14 | -0622 | 2.87 | 73 | 1.81 | 46 | 0.79 | 20 | 1.1/16 | 27 | | | | |
| **TP720-0824** | 12 | 1/2 | M 24X1,5 | 16 | -0824 | 3.27 | 83 | 2.09 | 53 | 0.94 | 24 | 1.3/16 | 30 | | | | |
| **TP720-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 4.25 | 108 | 2.91 | 74 | 1.38 | 35 | | 36 | | | | |
| **TP720-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 4.33 | 110 | 2.99 | 76 | 1.38 | 35 | | 46 | | | | |
| **TP720-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 4.84 | 123 | 3.43 | 87 | 1.46 | 37 | 2 | 50 | | | | |

# ONE-PIECE COUPLINGS

## TP000 SERIES ONE-PIECE CRIMP COUPLINGS

### METRIC - DKOS — TP730


**DKOS FEMALE**
**24° CONE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | mm | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP730-0414** | 6 | 1/4 | M 14X1,5 | 6 | -0414 | 2.20 | 56 | 1.06 | 27 | 1.10 | 28 | | 17 | | |
| **TP730-0416** | 6 | 1/4 | M 16X1,5 | 8 | -0416 | 2.20 | 56 | 1.06 | 27 | 1.22 | 31 | 3/4 | 19 | | |
| **TP730-0418** | 6 | 1/4 | M 18X1,5 | 10 | -0418 | 2.20 | 56 | 1.06 | 27 | 1.14 | 29 | 7/8 | 22 | | |
| **TP730-0520** | 8 | 5/16 | M 20X1,5 | 12 | -0520 | 2.48 | 63 | 1.42 | 36 | 1.42 | 36 | 15/16 | 24 | | |
| **TP730-0620** | 10 | 3/8 | M 20X1,5 | 12 | -0620 | 2.48 | 63 | 1.42 | 36 | 1.42 | 36 | 15/16 | 24 | | |
| **TP730-0622** | 10 | 3/8 | M 22X1,5 | 14 | -0622 | 2.48 | 63 | 1.42 | 36 | 1.42 | 36 | 1.1/16 | 27 | | |
| **TP730-0824** | 12 | 1/2 | M 24X1,5 | 16 | -0824 | 2.76 | 70 | 1.57 | 40 | 1.89 | 48 | 1.3/16 | 30 | | |
| **TP730-1230** | 19 | 3/4 | M 30X2 | 20 | -1230 | 3.43 | 87 | 2.13 | 54 | 2.68 | 68 | | 36 | | |
| **TP730-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 3.50 | 89 | 2.17 | 55 | 2.68 | 68 | | 46 | | |
| **TP730-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 4.13 | 105 | 2.72 | 69 | 3.03 | 77 | 2 | 50 | | |

### METRIC — TP470


**METRIC BANJO**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | |
| **TP470-0412** | 6 | 1/4 | | | -0412 | 1.97 | 50 | 0.91 | 23 | | | | | | |
| **TP470-0414** | 6 | 1/4 | | | -0414 | 2.05 | 52 | 0.98 | 25 | | | | | | |
| **TP470-0614** | 10 | 3/8 | | | -0614 | 2.17 | 55 | 1.06 | 27 | | | | | | |
| **TP470-0618** | 10 | 3/8 | | | -0618 | 2.24 | 57 | 1.14 | 29 | | | | | | |
| **TP470-0622** | 10 | 3/8 | | | -0622 | 2.44 | 62 | 1.38 | 35 | | | | | | |
| **TP470-0818** | 12 | 1/2 | | | -0818 | 2.36 | 60 | 1.14 | 29 | | | | | | |
| **TP470-0822** | 12 | 1/2 | | | -0822 | 2.48 | 63 | 1.26 | 32 | | | | | | |

## STANDPIPE — TP640


**METRIC STANDPIPE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | mm | | inch | mm | inch | mm | | | | | | |
| **TP640-0306** | 5 | 3/16 | | 6 | -0306 | 2.20 | 56 | 1.22 | 31 | | | | | | |
| **TP640-0406** | 6 | 1/4 | | 6 | -0406 | 2.28 | 58 | 1.22 | 31 | | | | | | |
| **TP640-0408** | 6 | 1/4 | | 8 | -0408 | 2.28 | 58 | 1.22 | 31 | | | | | | |
| **TP640-0410** | 6 | 1/4 | | 10 | -0410 | 2.40 | 61 | 1.34 | 34 | | | | | | |
| **TP640-0612** | 10 | 3/8 | | 12 | -0612 | 2.44 | 62 | 1.34 | 34 | | | | | | |
| **TP640-0815** | 12 | 1/2 | | 15 | -0815 | 2.52 | 64 | 1.34 | 34 | | | | | | |
| **TP640-0816** | 12 | 1/2 | | 16 | -0816 | 2.72 | 69 | 1.54 | 39 | | | | | | |

## STANDPIPE — TP643


**METRIC STANDPIPE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | mm | | inch | mm | inch | mm | inch | mm | | | | |
| **TP643-0306** | 5 | 3/16 | | 6 | -0306 | 2.68 | 68 | 1.65 | 42 | 0.83 | 21 | | | | |
| **TP643-0410** | 6 | 1/4 | | 10 | -0410 | 2.72 | 69 | 1.65 | 42 | 0.94 | 24 | | | | |

## STANDPIPE — TP646

**METRIC STANDPIPE**
**90° TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | mm | | inch | mm | inch | mm | inch | mm | | | | |
| **TP646-0306** | 5 | 3/16 | | 6 | -0306 | 2.05 | 52 | 1.02 | 26 | 1.34 | 34 | | | | |
| **TP646-0410** | 6 | 1/4 | | 10 | -0410 | 2.13 | 54 | 1.06 | 27 | 1.61 | 41 | | | | |

# ONE-PIECE COUPLINGS

## TP000 SERIES ONE-PIECE CRIMP COUPLINGS

### ORFS — TP800


**ORFS FEMALE**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | inch | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **TP800-0409** | 6 | 1/4 | 9/16" - 18 | - | -0409 | 2.28 | 58 | 1.22 | 31 | | | 11/16 | | 9/16 | |
| **TP800-0411** | 6 | 1/4 | 11/16" -16 | - | -0411 | 2.44 | 62 | 1.42 | 36 | | | 13/16 | | 11/16 | |
| **TP800-0511** | 8 | 5/16 | 11/16" -16 | - | -0511 | 2.44 | 62 | 1.42 | 36 | | | 13/16 | | 5/8 | 16 |
| **TP800-0611** | 10 | 3/8 | 11/16" -16 | - | -0611 | 2.36 | 60 | 1.30 | 33 | | | 13/16 | | 5/8 | 16 |
| **TP800-0613** | 10 | 3/8 | 13/16" - 16 | - | -0613 | 2.56 | 65 | 1.46 | 37 | | | 15/16 | 24 | 3/4 | 19 |
| **TP800-0813** | 12 | 1/2 | 13/16" - 16 | - | -0813 | 2.60 | 66 | 1.42 | 36 | | | 15/16 | 24 | 3/4 | 19 |
| **TP800-1219** | 19 | 3/4 | 1.3/16" - 12 | - | -1219 | 3.19 | 81 | 1.77 | 45 | | | 1.3/8 | 35 | 1.1/8 | |
| **TP800-1223** | 19 | 3/4 | 1.7/16" - 12 | - | -1223 | 3.46 | 88 | 2.13 | 54 | | | 1.5/8 | 41 | 1.3/8 | 35 |
| **TP800-1623** | 25 | 1 | 1.7/16" - 12 | - | -1623 | 3.62 | 92 | 2.17 | 55 | | | 1.5/8 | 41 | 1.3/8 | 35 |

### ORFS — TP801


**ORFS FEMALE**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | | |
| **TP801-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.28 | 58 | 1.22 | 31 | | | | 17 | | |
| **TP801-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.44 | 62 | 1.42 | 36 | | | 7/8 | 22 | | |
| **TP801-0511** | 8 | 5/16 | 11/16" -16 | | -0511 | 2.44 | 62 | 1.42 | 36 | | | 7/8 | 22 | | |
| **TP801-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.19 | 81 | 1.77 | 45 | | | | 36 | | |

## ORFS — TP810


**ORFS FEMALE**
**45° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP810-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.60 | 66 | 1.57 | 40 | 0.71 | 18 | 11/16 | | | |
| **TP810-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.60 | 66 | 1.57 | 40 | 0.71 | 18 | 13/16 | | | |
| **TP810-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.83 | 72 | 1.77 | 45 | 0.79 | 20 | 13/16 | | | |
| **TP810-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.64 | 67 | 1.57 | 40 | 0.67 | 17 | 15/16 | 24 | | |
| **TP810-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 3.07 | 78 | 1.89 | 48 | 0.75 | 19 | 15/16 | 24 | | |
| **TP810-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.86 | 98 | 2.52 | 64 | 1.14 | 29 | 1.3/8 | 35 | | |

## ORFS — TP811


**ORFS FEMALE**
**45° TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | | mm | | |
| **TP811-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.60 | 66 | 1.57 | 40 | 0.71 | 18 | | 17 | | |
| **TP811-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 3.86 | 98 | 2.52 | 64 | 1.14 | 29 | | 36 | | |

## ORFS — TP820

**ORFS FEMALE**
**90° MEDIUM TUBE BEND**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TP820-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.17 | 55 | 1.14 | 29 | 1.26 | 32 | 11/16 | | | |
| **TP820-0411** | 6 | 1/4 | 11/16" -16 | | -0411 | 2.32 | 59 | 1.30 | 33 | 1.50 | 38 | 13/16 | | | |
| **TP820-0511** | 8 | 5/16 | 11/16" -16 | | -0511 | 2.32 | 59 | 1.30 | 33 | 1.50 | 38 | 13/16 | | | |
| **TP820-0611** | 10 | 3/8 | 11/16" -16 | | -0611 | 2.40 | 61 | 1.34 | 34 | 1.50 | 38 | 13/16 | | | |
| **TP820-0613** | 10 | 3/8 | 13/16" - 16 | | -0613 | 2.64 | 67 | 1.57 | 40 | 1.34 | 34 | 15/16 | 24 | | |
| **TP820-0813** | 12 | 1/2 | 13/16" - 16 | | -0813 | 2.68 | 68 | 1.50 | 38 | 1.61 | 41 | 15/16 | 24 | | |
| **TP820-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 5.04 | 128 | 3.62 | 92 | 2.32 | 59 | 1.3/8 | 35 | | |
| **TP820-1623** | 25 | 1 | 1.7/16" - 12 | | -1623 | 4.13 | 105 | 2.72 | 69 | 2.80 | 71 | 1.5/8 | 41 | | |

# ONE-PIECE COUPLINGS

## TP000 SERIES ONE-PIECE CRIMP COUPLINGS

### ORFS — TP821


**ORFS FEMALE**
**90° MEDIUM TUBE BEND**
**METRIC NUT ONLY**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | | mm | | |
| **TP821-0409** | 6 | 1/4 | 9/16" - 18 | | -0409 | 2.17 | 55 | 1.14 | 29 | 1.26 | 32 | | 17 | | |
| **TP821-1219** | 19 | 3/4 | 1.3/16" - 12 | | -1219 | 5.04 | 128 | 3.62 | 92 | 2.32 | 59 | | 36 | | |

### SAE — TP540


**SAE FEMALE**
**45° FLARE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **TP540-0410** | 6 | 1/4 | 5/8" -18 | | -0410 | 2.05 | 52 | 0.98 | 25 | | | 3/4 | 19 | 5/8 | 16 |
| **TP540-0510** | 8 | 5/16 | 5/8" -18 | | -0510 | 2.05 | 52 | 1.02 | 26 | | | 3/4 | 19 | 5/8 | 16 |
| **TP540-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 2.05 | 52 | 0.98 | 25 | | | 3/4 | 19 | 5/8 | 16 |

### SAE — TP570

**SAE FEMALE**
**45° FLARE**
**90° ELBOW**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **TP570-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 1.97 | 50 | 0.91 | 23 | 0.91 | 23 | 3/4 | 19 | 3/4 | 19 |

# TT000 SERIES ONE-PIECE CRIMP COUPLINGS

| HOSE COMPATIBILITY FOR TT000 SERIES | |
|---|---|
| **NON-SKIVE**<br>For Ryco Hose Series RTH1 (all sizes). | **SKIVE** |

## BSPT — TT010


**BSPT MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **TT010-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 2.09 | 53 | 1.18 | 30 | | | | | 9/16 | |
| **TT010-0604** | 10 | 3/8 | 1/4" -19 | | -0604 | 2.24 | 57 | 1.30 | 33 | | | | | 5/8 | 16 |
| **TT010-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.24 | 57 | 1.30 | 33 | | | | | 11/16 | |
| **TT010-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.44 | 62 | 1.46 | 37 | | | | | 7/8 | 22 |
| **TT010-0806** | 12 | 1/2 | 3/8" -19 | | -0806 | 2.44 | 62 | 1.38 | 35 | | | | | 11/16 | |
| **TT010-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.64 | 67 | 1.57 | 40 | | | | | 7/8 | 22 |
| **TT010-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.95 | 75 | 1.61 | 41 | | | | | 1.1/16 | 27 |
| **TT010-1616** | 25 | 1 | 1" -11 | | -1616 | 3.31 | 84 | 1.89 | 48 | | | | | 1.3/8 | 35 |

## BSPT — TT320

**BSPT MALE SWIVEL**
**60° SEAT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | | | |
| **TT320-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.91 | 74 | 1.81 | 46 | | | 1 | | | |

# ONE-PIECE COUPLINGS

## TT000 SERIES ONE-PIECE CRIMP COUPLINGS

### BSPP — TT020


**BSPP FEMALE**
**60 ° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **TT020-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.81 | 46 | 0.94 | 24 | | | 3/4 | 19 | 1/2 | |
| **TT020-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.01 | 51 | 1.06 | 27 | | | 7/8 | 22 | 5/8 | 16 |
| **TT020-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.20 | 56 | 1.14 | 29 | | | 1.1/16 | 27 | 3/4 | 19 |
| **TT020-1008** | 16 | 5/8 | 1/2" -14 | | -1008 | 2.40 | 61 | 1.06 | 27 | | | 1.1/16 | 27 | 1 | |
| **TT020-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.44 | 65 | 1.10 | 31 | | | 1.1/4 | 32 | 1 | |
| **TT020-1616** | 25 | 1 | 1" -11 | | -1616 | 2.87 | 73 | 1.46 | 36 | | | 1.1/2 | 38 | 1.1/4 | 32 |

### BSPP — TT050


**BSPP FEMALE**
**60° CONE**
**90° ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **TT050-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.24 | 57 | 1.14 | 29 | 1.22 | 31 | 1.1/16 | 27 | 7/8 | 22 |

### BSPP — TT260


**BSPP FEMALE**
**60° CONE**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TT260-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.97 | 50 | 1.06 | 27 | 1.14 | 29 | 3/4 | 19 | | |
| **TT260-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 2.32 | 59 | 1.38 | 35 | 1.30 | 33 | 7/8 | 22 | | |
| **TT260-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.56 | 65 | 1.50 | 38 | 1.77 | 45 | 1.1/16 | 27 | | |
| **TT260-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.46 | 88 | 2.17 | 55 | 2.32 | 59 | 1.1/4 | 32 | | |
| **TT260-1616** | 25 | 1 | 1" -11 | | -1616 | 4.09 | 104 | 2.68 | 68 | 3.07 | 78 | 1.1/2 | 38 | | |

## JIC — TT030


JIC
37° CONE
MALE




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **TT030-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.05 | 52 | 1.14 | 29 | | | | | 1/2 | |
| **TT030-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 2.05 | 52 | 1.14 | 29 | | | | | 9/16 | |
| **TT030-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 2.05 | 52 | 1.18 | 30 | | | | | 5/8 | 16 |
| **TT030-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.24 | 57 | 1.26 | 32 | | | | | 5/8 | 16 |
| **TT030-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.32 | 59 | 1.38 | 35 | | | | | 3/4 | 19 |
| **TT030-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.52 | 64 | 1.46 | 37 | | | | | 3/4 | 19 |
| **TT030-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.64 | 67 | 1.54 | 39 | | | | | 15/16 | 24 |

## JIC — TT031

JIC
37° CONE MALE
METRIC HEX ONLY





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | | mm |
| **TT031-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 2.05 | 52 | 1.14 | 29 | | | | | | 12 |

# ONE-PIECE COUPLINGS

## TT000 SERIES ONE-PIECE CRIMP COUPLINGS

### JSEAL™ / JIC — TT040


JSEAL™ / JIC FEMALE
CONVEX SEAT




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **TT040-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.73 | 44 | 0.87 | 22 | | | 9/16 | | 1/2 | |
| **TT040-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 1.73 | 44 | 0.87 | 22 | | | 5/8 | 16 | 1/2 | |
| **TT040-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 1.77 | 45 | 0.87 | 22 | | | 11/16 | | 9/16 | |
| **TT040-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 1.85 | 47 | 0.87 | 22 | | | 11/16 | | 9/16 | |
| **TT040-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 1.93 | 50 | 0.94 | 25 | | | 7/8 | 22 | 11/16 | |
| **TT040-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.01 | 51 | 0.94 | 24 | | | 7/8 | 22 | 5/8 | 16 |
| **TT040-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.13 | 54 | 1.06 | 27 | | | 1 | | 5/8 | 16 |
| **TT040-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.40 | 61 | 1.06 | 27 | | | 1 | | 7/8 | 22 |
| **TT040-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 2.48 | 63 | 1.14 | 29 | | | 1.1/4 | 32 | 1 | |
| **TT040-1214** | 19 | 3/4 | 7/8" -14 | | -1214 | 2.44 | 66 | 1.14 | 32 | | | 1 | | 1 | |
| **TT040-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.48 | 62 | 1.14 | 29 | | | 1.1/4 | 32 | 1 | |
| **TT040-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 2.83 | 72 | 1.42 | 33 | | | 1.1/2 | 38 | 1.1/4 | 32 |

### JSEAL™ / JIC — TT041


JSEAL™ / JIC FEMALE
CONVEX SEAT
METRIC NUT ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | | mm |
| **TT041-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.54 | 39 | 0.67 | 17 | | | | 14 | | |
| **TT041-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 1.57 | 40 | 0.67 | 17 | | | 3/4 | 19 | | |
| **TT041-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 1.65 | 47 | 0.67 | 22 | | | 3/4 | 19 | | 14 |

### JSEAL™ / JIC — TT250


JSEAL™ / JIC FEMALE
CONVEX SEAT
45° TUBE BEND




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | | | |
| **TT250-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.48 | 63 | 1.50 | 38 | 0.55 | 14 | 11/16 | | | |
| **TT250-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.91 | 74 | 1.85 | 47 | 0.87 | 22 | 1 | | | |

## JSEAL™ / JIC — TT251


JSEAL™ / JIC FEMALE
CONVEX SEAT
45° TUBE BEND
METRIC NUT ONLY




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TT251-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.48 | 63 | 1.50 | 38 | 0.55 | 14 | 3/4 | 19 | | |

## JSEAL™ / JIC — TT240


JSEAL™ / JIC FEMALE
CONVEX SEAT
90° TUBE BEND




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TT240-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.93 | 49 | 1.02 | 26 | 1.26 | 32 | 9/16 | | | |
| **TT240-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 1.93 | 49 | 1.02 | 26 | 1.26 | 32 | 5/8 | 16 | | |
| **TT240-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 1.93 | 49 | 1.02 | 26 | 1.50 | 38 | 11/16 | | | |
| **TT240-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.36 | 59 | 1.38 | 34 | 0.98 | 26 | 11/16 | | | |
| **TT240-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 2.32 | 59 | 1.38 | 35 | 1.18 | 30 | 7/8 | 22 | | |
| **TT240-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.68 | 68 | 1.61 | 41 | 1.50 | 38 | 7/8 | 22 | | |
| **TT240-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.68 | 68 | 1.61 | 41 | 1.61 | 41 | 1 | | | |
| **TT240-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 3.23 | 82 | 1.89 | 48 | 1.85 | 47 | 1 | | | |
| **TT240-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 3.50 | 90 | 2.20 | 57 | 2.24 | 57 | 1.1/4 | 32 | | |
| **TT240-1621** | 25 | 1 | 1.5/16" -12 | | -1621 | 4.09 | 104 | 2.68 | 74 | 2.83 | 72 | 1.1/2 | 38 | | 32 |

## JSEAL™ / JIC — TT241

JSEAL™ / JIC FEMALE
CONVEX SEAT
90° TUBE BEND
METRIC NUT ONLY





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **TT241-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.93 | 49 | 1.02 | 26 | 1.26 | 32 | | 14 | | |
| **TT241-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 1.93 | 49 | 1.02 | 26 | 1.50 | 38 | 3/4 | 19 | | |
| **TT241-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.36 | 59 | 1.38 | 34 | 0.98 | 26 | 3/4 | 19 | | |

# ONE-PIECE COUPLINGS

## TT000 SERIES ONE-PIECE CRIMP COUPLINGS

### NPTF — TT090


**NPTF MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **TT090-0404** | 6 | 1/4 | 1/4" -18 | | -0404 | 2.09 | 53 | 1.18 | 30 | | | | | 9/16 | |
| **TT090-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 2.24 | 57 | 1.30 | 33 | | | | | 11/16 | |
| **TT090-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.64 | 67 | 1.57 | 40 | | | | | 7/8 | 22 |
| **TT090-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.95 | 75 | 1.61 | 41 | | | | | 1.1/16 | 27 |
| **TT090-1616** | 25 | 1 | 1" -11,5 | | -1616 | 3.31 | 84 | 1.89 | 48 | | | | | 1.3/8 | 35 |

### METRIC - DKL — TT600


**DKL FEMALE**
**24°/ 60° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | | | inch | mm | inch | mm | | | inch | mm | | |
| **TT600-0414** | 6 | 1/4 | M 14X1,5 | | -0414 | 1.73 | 44 | 0.87 | 22 | | | | 17 | | |
| **TT600-0822** | 12 | 1/2 | M 22X1,5 | | -0822 | 2.09 | 53 | 0.98 | 25 | | | 1.1/16 | 27 | | |

### METRIC - DKL — TT670


**DKL FEMALE**
**24°/ 60**
**90° TUBE BEND**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | | | |
| | DN | inch | mm | | | inch | mm | inch | mm | inch | mm | inch | mm | | | | |
| **TT670-0414** | 6 | 1/4 | M 14X1,5 | | -0414 | 1.97 | 50 | 1.06 | 27 | 1.22 | 31 | | 17 | | | | |
| **TT670-0822** | 12 | 1/2 | M 22X1,5 | | -0822 | 2.64 | 67 | 1.57 | 40 | 1.73 | 44 | 1.1/16 | 27 | | | | |

## SAE

## TT540




**SAE FEMALE**
**45° FLARE**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **TT540-0407** | 6 | 1/4 | 7/16" - 20 | | -0407 | 1.65 | 42 | 0.75 | 19 | | | 9/16 | | 1/2 | |
| **TT540-0408** | 6 | 1/4 | 1/2" -20 | | -0408 | 1.65 | 42 | 0.79 | 20 | | | 5/8 | 16 | 9/16 | |
| **TT540-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 1.85 | 47 | 0.91 | 23 | | | 3/4 | 19 | 5/8 | 16 |
| **TT540-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 1.81 | 46 | 0.87 | 22 | | | 7/8 | 22 | 11/16 | |
| **TT540-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.05 | 52 | 0.98 | 25 | | | 7/8 | 22 | 11/16 | |
| **TT540-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.09 | 53 | 0.98 | 25 | | | 1 | | 13/16 | |
| **TT540-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.32 | 59 | 0.98 | 25 | | | 1 | | 13/16 | |
| **TT540-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 2.36 | 60 | 1.02 | 26 | | | 1.1/4 | 32 | 1 | |
| **TT540-1214** | 19 | 3/4 | 7/8" -14 | | -1214 | 2.32 | 59 | 1.02 | 26 | | | 1 | | 1 | |
| **TT540-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.36 | 60 | 1.06 | 27 | | | 1.1/4 | 32 | 1 | |


# ONE-PIECE COUPLINGS

## TG000 SERIES ONE-PIECE CRIMP COUPLINGS

| HOSE COMPATIBILITY FOR TG000 SERIES | |
|---|---|
| **NON-SKIVE**<br>For Ryco Hose Series TPGL (all sizes). | **SKIVE** |

## BSPT — TG010


**BSPT MALE**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **TG010-0202** | 4 | 1/8 | 1/8" -28 | | -0202 | 1.93 | 49 | 1.02 | 26 | | | | | 7/16 | 11 |

## BSPT — TG320


**BSPT MALE SWIVEL**
**60° SEAT**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | | | |
| **TG320-0202** | 4 | 1/8 | 1/8" -28 | | -0202 | 1.81 | 46 | 0.91 | 23 | | | 1/2 | | | |

## BSPP — TG020

**BSPP FEMALE**
**60 ° CONE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | mm | inch | mm |
| **TG020-0202** | 4 | 1/8 | 1/8" -28 | | -0202 | 1.85 | 47 | 0.94 | 24 | | | | 14 | 7/16 | 11 |

## NPTF

## TG090

NPTF MALE
60° SEAT





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | | mm |
| **TG090-0202** | 4 | 1/8 | 1/8" -27 | | -0202 | 1.93 | 49 | 1.02 | 26 | | | | | | 12 |

## NPT

## TG320N

NPT MALE SWIVEL
60° SEAT





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | | | |
| **TG320N-0202** | 4 | 1/8 | 1/8" -27 | | -0202 | 1.81 | 46 | 0.91 | 23 | | | 11/16 | | | |

## NPSM

## TG020N

NPSM FEMALE
60° SEAT





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | | inch | mm |
| **TG020N-0202** | 4 | 1/8 | 1/8" -27 | | -0202 | 1.89 | 48 | 0.98 | 25 | | | 9/16 | | 7/16 | 11 |

# ONE-PIECE COUPLINGS

## TG000 SERIES ONE-PIECE CRIMP COUPLINGS


### JIC — TG030




**JIC**
**37° CONE MALE**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | |
| **TG030-0207** | 4 | 1/8 | 7/16" -20 | | -0207 | 2.01 | 51 | 1.10 | 28 | | | | | 1/2 | |


### JSEAL™ / JIC — TG040




**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | | inch | mm |
| **TG040-0207** | 4 | 1/8 | 7/16" -20 | | -0207 | 1.77 | 45 | 0.87 | 22 | | | 9/16 | | 7/16 | 11 |

### STANDPIPE — TG640





**METRIC STANDPIPE**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | mm | | inch | mm | inch | mm | | | | | | |
| **TG640-0206** | 4 | 1/8 | | 6 | -0206 | 2.13 | 54 | 1.22 | 31 | | | | | | |
| **TG640-0208** | 4 | 1/8 | | 8 | -0208 | 2.13 | 54 | 1.22 | 31 | | | | | | |

## BSPP

## TW4027

**BSPP FEMALE O RING**
**60° CONE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **TW4027-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 3.07 | 78 | 1.10 | 28 | | | 7/8 | 22 | 11/16 | |
| **TW4027-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 3.31 | 84 | 1.14 | 29 | | | 1.1/16 | 27 | 11/16 | |
| **TW4027-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 3.58 | 91 | 1.26 | 32 | | | 1.1/4 | 32 | 1.1/16 | 27 |
| **TW4027-1616** | 25 | 1 | 1" -11 | | -1616 | 3.74 | 95 | 1.50 | 38 | | | 1.1/2 | 38 | 1.1/4 | 32 |

## NPTF

## TW4090

**NPTF MALE**
**60° SEAT**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **TW4090-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 3.58 | 91 | 1.61 | 41 | | | | | 11/16 | |
| **TW4090-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 4.02 | 102 | 1.85 | 47 | | | | | 7/8 | 22 |
| **TW4090-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 4.29 | 109 | 2.01 | 51 | | | | | 1.1/16 | 27 |
| **TW4090-1616** | 25 | 1 | 1" -11,5 | | -1616 | 4.57 | 116 | 2.32 | 59 | | | | | 1.3/8 | 35 |

## DKOS

## TW4711

**DKOS FEMALE**
**24° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | mm | | inch | mm | inch | mm | | | inch | mm | inch | mm |
| **TW4711-0622** | 10 | 3/8 | M 22X1,5 | 14 | -0622 | 3.35 | 85 | 1.34 | 34 | | | 1.1/16 | 27 | 11/16 | |
| **TW4711-0624** | 10 | 3/8 | M 24X1,5 | 16 | -0624 | 3.35 | 85 | 1.38 | 35 | | | 1.1/4 | 32 | 11/16 | |
| **TW4711-0824** | 12 | 1/2 | M 24X1,5 | 16 | -0824 | 3.58 | 91 | 1.42 | 36 | | | 1.1/4 | 32 | 11/16 | |
| **TW4711-1236** | 19 | 3/4 | M 36X2 | 25 | -1236 | 4.06 | 103 | 1.77 | 45 | | | | 46 | 1.1/16 | 27 |
| **TW4711-1642** | 25 | 1 | M 42X2 | 30 | -1642 | 4.13 | 105 | 1.89 | 48 | | | 2 | 50 | 1.1/4 | 32 |


# PUSH-ON & SUCTION & RETURN COUPLINGS

## 8000 SERIES PUSH-ON COUPLINGS

| HOSE COMPATIBILITY FOR 8000 SERIES |
|---|
| For Ryco Hose Series PL1D. |

## BSPP — 8111


**BSPP O RING & RETAINING RING MALE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **8111-1008** | 16 | 5/8 | 1/2" -14 | | -1008 | 1.93 | 49 | 0.94 | 24 | | | | | 1.1/16 | 27 |

## BSPP — 8020


**BSPP FEMALE**
**60 ° CONE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | | |
| **8020-0402** | 6 | 1/4 | 1/8" -28 | | -0402 | 1.34 | 34 | 0.59 | 15 | | | | 14 | | |
| **8020-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.38 | 35 | 0.59 | 15 | | | 3/4 | 19 | | |
| **8020-0406** | 6 | 1/4 | 3/8" -19 | | -0406 | 1.46 | 37 | 0.67 | 17 | | | 7/8 | 22 | | |
| **8020-0502** | 8 | 5/16 | 1/8" -28 | | -0502 | 1.34 | 34 | 0.59 | 15 | | | | 14 | | |
| **8020-0504** | 8 | 5/16 | 1/4" -19 | | -0504 | 1.38 | 35 | 0.59 | 15 | | | 3/4 | 19 | | |
| **8020-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 1.54 | 39 | 0.67 | 17 | | | 7/8 | 22 | | |
| **8020-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 1.61 | 41 | 0.75 | 19 | | | 1.1/16 | 27 | | |
| **8020-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 1.73 | 44 | 0.75 | 19 | | | 1.1/16 | 27 | | |
| **8020-1008** | 16 | 5/8 | 1/2" -14 | | -1008 | 1.73 | 44 | 0.75 | 19 | | | 1.1/16 | 27 | | |
| **8020-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.17 | 55 | 0.75 | 19 | | | 1.1/4 | 32 | | |

## BSPP — 8060


**BSPP FEMALE**
**60° CONE**
**45° ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **8060-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.60 | 66 | 1.18 | 30 | 0.79 | 20 | 1.1/4 | 32 | 1.1/16 | 27 |

## BSPP — 8050


**BSPP FEMALE**
**60° CONE**
**90° ELBOW**




| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm |
| **8050-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.30 | 33 | 0.51 | 13 | 0.94 | 24 | 3/4 | 19 | 9/16 | |
| **8050-0504** | 8 | 5/16 | 1/4" -19 | | -0504 | 1.30 | 33 | 0.51 | 13 | 0.94 | 24 | 3/4 | 19 | 9/16 | |
| **8050-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 1.54 | 39 | 0.67 | 17 | 1.14 | 29 | 7/8 | 22 | 3/4 | 19 |
| **8050-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 1.77 | 45 | 0.75 | 19 | 1.22 | 31 | 1.1/16 | 27 | 7/8 | 22 |
| **8050-1008** | 16 | 5/8 | 1/2" -14 | | -1008 | 1.85 | 47 | 0.83 | 21 | 1.38 | 35 | 1.1/16 | 27 | 1.1/16 | 27 |
| **8050-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.28 | 58 | 0.87 | 22 | 1.42 | 36 | 1.1/4 | 32 | 1.1/16 | 27 |

## BSPT — 8010

**BSPT MALE**
**60° SEAT**





| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm |
| **8010-0402** | 6 | 1/4 | 1/8" -28 | | -0402 | 1.46 | 37 | 0.71 | 18 | | | | | | 12 |
| **8010-0404** | 6 | 1/4 | 1/4" -19 | | -0404 | 1.65 | 42 | 0.87 | 22 | | | | | | 14 |
| **8010-0406** | 6 | 1/4 | 3/8" -19 | | -0406 | 1.65 | 42 | 0.87 | 22 | | | | | 3/4 | 19 |
| **8010-0502** | 8 | 5/16 | 1/8" -28 | | -0502 | 1.46 | 37 | 0.71 | 18 | | | | | | 12 |
| **8010-0504** | 8 | 5/16 | 1/4" -19 | | -0504 | 1.65 | 42 | 0.87 | 22 | | | | | | 14 |
| **8010-0506** | 8 | 5/16 | 3/8" -19 | | -0506 | 1.65 | 42 | 0.87 | 22 | | | | | 3/4 | 19 |
| **8010-0604** | 10 | 3/8 | 1/4" -19 | | -0604 | 1.73 | 44 | 0.87 | 22 | | | | | | 14 |
| **8010-0606** | 10 | 3/8 | 3/8" -19 | | -0606 | 1.73 | 44 | 0.87 | 22 | | | | | 3/4 | 19 |
| **8010-0608** | 10 | 3/8 | 1/2" -14 | | -0608 | 2.01 | 51 | 1.14 | 29 | | | | | 7/8 | 22 |
| **8010-0806** | 12 | 1/2 | 3/8" -19 | | -0806 | 1.89 | 48 | 0.87 | 22 | | | | | 3/4 | 19 |
| **8010-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.13 | 54 | 1.14 | 29 | | | | | 7/8 | 22 |
| **8010-0812** | 12 | 1/2 | 3/4" -14 | | -0812 | 2.13 | 54 | 1.14 | 29 | | | | | 1.1/16 | 27 |
| **8010-1008** | 16 | 5/8 | 1/2" -14 | | -1008 | 2.13 | 54 | 1.14 | 29 | | | | | 7/8 | 22 |
| **8010-1208** | 19 | 3/4 | 1/2" -14 | | -1208 | 2.56 | 65 | 1.14 | 29 | | | | | 15/16 | 24 |
| **8010-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.56 | 65 | 1.14 | 29 | | | | | 1.1/16 | 27 |

# PUSH-ON & SUCTION & RETURN COUPLINGS

## 8000 SERIES PUSH-ON COUPLINGS


### NPTF — 8090




**NPTF MALE**
**60° SEAT**

| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | inch | mm |
| **8090-0402** | 6 | 1/4 | 1/8" -27 | | -0402 | 1.46 | 37 | 0.71 | 18 | | | | 1/2 | |
| **8090-0404** | 6 | 1/4 | 1/4" -18 | | -0404 | 1.65 | 42 | 0.87 | 22 | | | | 9/16 | |
| **8090-0502** | 8 | 5/16 | 1/8" -27 | | -0502 | 1.46 | 37 | 0.71 | 18 | | | | 1/2 | |
| **8090-0504** | 8 | 5/16 | 1/4" -18 | | -0504 | 1.65 | 42 | 0.87 | 22 | | | | 9/16 | |
| **8090-0604** | 10 | 3/8 | 1/4" -18 | | -0604 | 1.73 | 44 | 0.87 | 22 | | | | 9/16 | |
| **8090-0606** | 10 | 3/8 | 3/8" -18 | | -0606 | 1.73 | 44 | 0.87 | 22 | | | | 11/16 | |
| **8090-0806** | 12 | 1/2 | 3/8" -18 | | -0806 | 1.89 | 48 | 0.87 | 22 | | | | 11/16 | |
| **8090-0808** | 12 | 1/2 | 1/2" -14 | | -0808 | 2.13 | 54 | 1.14 | 29 | | | | 7/8 | 22 |
| **8090-1212** | 19 | 3/4 | 3/4" -14 | | -1212 | 2.60 | 66 | 1.18 | 30 | | | | 1.1/16 | 27 |


### JIC — 8030




**JIC**
**37° CONE MALE**

| PART NO. | HOSE SIZE | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | inch | mm |
| **8030-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.61 | 41 | 0.87 | 22 | | | | 1/2 | |
| **8030-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 1.61 | 41 | 0.87 | 22 | | | | 1/2 | |
| **8030-0508** | 8 | 5/16 | 1/2" - 20 | | -0508 | 1.61 | 41 | 0.87 | 22 | | | | 1/2 | |
| **8030-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 1.73 | 44 | 0.87 | 22 | | | | 5/8 | 16 |
| **8030-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 1.81 | 46 | 0.94 | 24 | | | | 3/4 | 19 |
| **8030-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 1.97 | 50 | 0.94 | 24 | | | | 3/4 | 19 |
| **8030-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 2.13 | 54 | 1.10 | 28 | | | | 7/8 | 22 |
| **8030-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.13 | 54 | 1.10 | 28 | | | | 7/8 | 22 |
| **8030-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.64 | 67 | 1.22 | 31 | | | | 1.1/8 | |


## JSEAL™ / JIC — 8040




**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**

| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | | |
| **8040-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.30 | 33 | 0.51 | 13 | | | 9/16 | | | |
| **8040-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 1.30 | 33 | 0.51 | 13 | | | 5/8 | 16 | | |
| **8040-0409** | 6 | 1/4 | 9/16" -18 | | -0409 | 1.30 | 33 | 0.55 | 14 | | | 11/16 | | | |
| **8040-0508** | 8 | 5/16 | 1/2" - 20 | | -0508 | 1.30 | 33 | 0.51 | 13 | | | 5/8 | 16 | | |
| **8040-0509** | 8 | 5/16 | 9/16" -18 | | -0509 | 1.30 | 33 | 0.55 | 14 | | | 11/16 | | | |
| **8040-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 1.42 | 36 | 0.55 | 14 | | | 11/16 | | | |
| **8040-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 1.46 | 37 | 0.59 | 15 | | | 7/8 | 22 | | |
| **8040-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 1.61 | 41 | 0.59 | 15 | | | 7/8 | 22 | | |
| **8040-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 1.73 | 44 | 0.75 | 19 | | | 1 | | | |
| **8040-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 1.73 | 44 | 0.75 | 19 | | | 1 | | | |
| **8040-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.20 | 56 | 0.79 | 20 | | | 1.1/4 | 32 | | |

## JSEAL™ / JIC — 8070




**JSEAL™ / JIC FEMALE**
**CONVEX SEAT**
**90° ELBOW**


| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | | | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **8070-0407** | 6 | 1/4 | 7/16" -20 | | -0407 | 1.38 | 35 | 0.59 | 15 | 0.71 | 18 | 9/16 | | 9/16 | | | |
| **8070-0408** | 6 | 1/4 | 1/2" - 20 | | -0408 | 1.30 | 33 | 0.51 | 13 | 0.67 | 17 | 5/8 | 16 | 9/16 | | | |
| **8070-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 1.54 | 39 | 0.67 | 17 | 0.91 | 23 | 11/16 | | 3/4 | 19 | | |
| **8070-0612** | 10 | 3/8 | 3/4" -16 | | -0612 | 1.54 | 39 | 0.67 | 17 | 0.94 | 24 | 7/8 | 22 | 3/4 | 19 | | |
| **8070-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 1.77 | 45 | 0.75 | 19 | 1.06 | 27 | 7/8 | 22 | 7/8 | 22 | | |
| **8070-0814** | 12 | 1/2 | 7/8" -14 | | -0814 | 1.77 | 45 | 0.75 | 19 | 1.22 | 31 | 1 | | 7/8 | 22 | | |
| **8070-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.28 | 58 | 0.87 | 22 | 1.26 | 32 | 1.1/4 | 32 | 1.1/16 | 27 | | |

# PUSH-ON & SUCTION & RETURN COUPLINGS

## 8000 SERIES PUSH-ON COUPLINGS

### JSEAL™ / JIC — 8240


JSEAL™ / JIC FEMALE
CONVEX SEAT
90° TUBE BEND




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | | | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **8240-0609** | 10 | 3/8 | 9/16" -18 | | -0609 | 2.05 | 52 | 1.18 | 30 | 1.50 | 38 | 11/16 | | | | | |
| **8240-0812** | 12 | 1/2 | 3/4" -16 | | -0812 | 2.52 | 64 | 1.50 | 38 | 1.61 | 41 | 7/8 | 22 | | | | |
| **8240-1014** | 16 | 5/8 | 7/8" -14 | | -1014 | 2.72 | 69 | 1.69 | 43 | 1.89 | 48 | 1 | | | | | |

### JOINER — 8900


JOINER




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | | | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | | | |
| **8900-0404** | 6 | 1/4 | | | -0404 | 1.89 | 48 | 0.31 | 8 | | | | | | | | |
| **8900-0505** | 8 | 5/16 | | | -0505 | 1.89 | 48 | 0.31 | 8 | | | | | | | | |
| **8900-0606** | 10 | 3/8 | | | -0606 | 2.09 | 53 | 0.31 | 8 | | | | | | | | |
| **8900-0808** | 12 | 1/2 | | | -0808 | 2.40 | 61 | 0.35 | 9 | | | | | | | | |
| **8900-1010** | 16 | 5/8 | | | -1010 | 2.24 | 57 | 0.20 | 5 | | | | | | | | |
| **8900-1212** | 19 | 3/4 | | | -1212 | 3.23 | 82 | 0.35 | 9 | | | | | | | | |

### SAE — 8530


SAE MALE
45° CONE




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | | | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | | inch | mm | | |
| **8530-0510** | 8 | 5/16 | 5/8" -18 | | -0510 | 1.69 | 43 | 0.91 | 23 | | | | | 5/8 | 16 | | |
| **8530-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 1.77 | 45 | 0.91 | 23 | | | | | 5/8 | 16 | | |
| **8530-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.80 | 71 | 1.38 | 35 | | | | | 1.1/16 | 27 | | |

## SAE — 8540


**SAE FEMALE**
**45° FLARE**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | | |
| **8540-0510** | 8 | 5/16 | 5/8" -18 | | -0510 | 1.30 | 33 | 0.55 | 14 | | | 3/4 | 19 | | |
| **8540-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 1.42 | 36 | 0.55 | 14 | | | 3/4 | 19 | | |
| **8540-1017** | 16 | 5/8 | 1.1/16" -12 | | -1017 | 1.69 | 43 | 0.67 | 17 | | | 1.1/4 | 32 | | |
| **8540-1217** | 19 | 3/4 | 1.1/16" -12 | | -1217 | 2.09 | 53 | 0.67 | 17 | | | 1.1/4 | 32 | | |

## SAE — 8570


**SAE FEMALE**
**45° FLARE**
**90° ELBOW**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | | | |
| | DN | inch | inch | | | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | | |
| **8570-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 1.54 | 39 | 0.67 | 17 | 0.91 | 23 | 3/4 | 19 | 3/4 | 19 | | |

## SAE — 8740

**SAE INVERTED FLARE**
**MALE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | inch | mm | | |
| **8740-0407** | 6 | 1/4 | 7/16" - 20 | | -0407 | 1.65 | 42 | 0.87 | 22 | | | 7/16 | 11 | | |
| **8740-0408** | 6 | 1/4 | 1/2" -20 | | -0408 | 1.73 | 44 | 0.94 | 24 | | | 1/2 | | | |
| **8740-0508** | 8 | 5/16 | 1/2" -20 | | -0508 | 1.73 | 44 | 0.94 | 24 | | | 1/2 | | | |
| **8740-0510** | 8 | 5/16 | 5/8" -18 | | -0510 | 1.85 | 47 | 1.06 | 27 | | | 5/8 | 16 | | |
| **8740-0610** | 10 | 3/8 | 5/8" -18 | | -0610 | 1.93 | 49 | 1.06 | 27 | | | 5/8 | 16 | | |

# PUSH-ON & SUCTION & RETURN COUPLINGS

## 8000 SERIES PUSH-ON COUPLINGS

## SALVAGE — 8230


**SALVAGE (LIFESAVER)**




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | inch | mm |
| **8230-0406** | 6 | 1/4 | | 3/8 | -0406 | 1.34 | 34 | 0.55 | 14 | | | | 5/8 | 16 |
| **8230-0604** | 10 | 3/8 | | 1/4 | -0604 | 1.42 | 36 | 0.55 | 14 | | | | 1/2 | |
| **8230-0606** | 10 | 3/8 | | 3/8 | -0606 | 1.42 | 36 | 0.55 | 14 | | | | 11/16 | |
| **8230-0808** | 12 | 1/2 | | 1/2 | -0808 | 1.57 | 40 | 0.55 | 14 | | | | 3/4 | 19 |
| **8230-0810** | 12 | 1/2 | | 5/8 | -0810 | 1.65 | 42 | 0.63 | 16 | | | | 7/8 | 22 |
| **8230-1010** | 16 | 5/8 | | 5/8 | -1010 | 1.65 | 42 | 0.63 | 16 | | | | 7/8 | 22 |
| **8230-1212** | 19 | 3/4 | | 3/4 | -1212 | 2.05 | 52 | 0.63 | 16 | | | | 1.1/16 | 27 |

## STANDPIPE — 8180

**IMPERIAL STANDPIPE**





| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | $H_M$ | |
| | DN | inch | | inch | | inch | mm | inch | mm | | | | inch | mm |
| **8180-0404** | 6 | 1/4 | | 1/4 | -0404 | 1.93 | 49 | 1.18 | 30 | | | | 1/2 | |
| **8180-0405** | 6 | 1/4 | | 5/16 | -0405 | 1.93 | 49 | 1.18 | 30 | | | | 1/2 | |
| **8180-0406** | 6 | 1/4 | | 3/8 | -0406 | 1.97 | 50 | 1.22 | 31 | | | | 1/2 | |
| **8180-0606** | 10 | 3/8 | | 3/8 | -0606 | 2.09 | 53 | 1.22 | 31 | | | | 9/16 | |
| **8180-0608** | 10 | 3/8 | | 1/2 | -0608 | 2.09 | 53 | 1.22 | 31 | | | | 9/16 | |
| **8180-0808** | 12 | 1/2 | | 1/2 | -0808 | 2.20 | 56 | 1.22 | 31 | | | | 11/16 | |
| **8180-1212** | 19 | 3/4 | | 3/4 | -1212 | 3.19 | 81 | 1.77 | 45 | | | | 1.1/16 | 27 |

## UNO — 8200

**UN O RING MALE (O RING BOSS)**


O RING SUPPLIED




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | $H_M$ | |
| | DN | inch | inch | | | inch | mm | inch | mm | | | | inch | mm |
| **8200-0812** | 12 | 1/2 | 3/4" -14 | | -0812 | 1.81 | 46 | 0.79 | 20 | | | | 7/8 | 22 |

## 200 COUPLING NIPPLE — 8100


SPECIALS




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | | | | inch | mm | inch | mm | | | | | | |
| **8100-0404** | 6 | 1/4 | | | -0404 | 1.81 | 46 | 1.06 | 27 | | | | | | |
| **8100-0604** | 10 | 3/8 | | | -0604 | 1.93 | 49 | 1.06 | 27 | | | | | | |

## STANDPIPE — 8640

METRIC STANDPIPE




| PART NO. | HOSE SIZE | | THREAD SIZE | TUBE SIZE | DASH SIZE | DIMENSIONS | | | | | | SPANNER | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | L | | $C_A$ | | $D_L$ | | $H_F$ | | $H_M$ | |
| | DN | inch | mm | | | inch | mm | inch | mm | | | | | inch | mm |
| **8640-0406** | 6 | 1/4 | 6 | | -0406 | 1.93 | 49 | 1.18 | 30 | | | | | 1/2 | |
| **8640-0408** | 6 | 1/4 | 8 | | -0408 | 1.93 | 49 | 1.18 | 30 | | | | | 1/2 | |
| **8640-1220** | 19 | 3/4 | 20 | | -1220 | 3.27 | 83 | 1.85 | 47 | | | | | 1.1/8 | |
| **8640-1222** | 19 | 3/4 | 22 | | -1222 | 2.95 | 75 | 1.54 | 39 | | | | | 1.1/8 | |