

PyRIS - Python RIvers by Satellite

Usage manual

PyRIS v3 (Python 3)

Riccardo Bonanomi *

University of Trento
2024

*University of Trento - Center Agriculture Food Environment (C3A) - riccardo.bonanomi@unitn.it

License

MIT License

Copyright (c) 2018 fmonegaglia

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Introduction to this manual

PyRIS is a software developed by Federico Monegaglia¹ (Monegaglia et al., 2018) and it can be used to analyse meandering river from Landsat² satellite multi-spectral images. The original code could be found in a GitHub³ repository, but this is not available anymore, and it was written in Python 2⁴. Monegaglia then developed PyRISdem that adds to PyRIS the ability to extract the slope of the free surface from SRTM⁵ data, but it has not yet been published.

Both software were then translated from Python 2 to Python 3 by the author of this manual. Together with Marta Crivellaro⁶, we added the support for mask generated from external sources, such as Google Earth Engine (GEE from here on).

The up-to-date code can be found at <https://github.com/riccardobonanomi/pyris3>.

This manual is under development and it is not written by the original developer of the software. At the moment, is only describing PyRIS and not PyRISdem. Feel free to report any issue or mistake at riccardo.bonanomi@unitn.it.

¹f.monegaglia@gmail.com

²<https://landsat.gsfc.nasa.gov/>

³<https://github.com/fmonegaglia/pyris>

⁴<https://www.python.org/>

⁵<https://www2.jpl.nasa.gov/srtm/>

⁶University of Trento - Center Agriculture Food Environment (C3A)

Contents

1	Introduction	3
2	Version tracking	3
3	Installation	3
3.1	Linux	4
3.2	Windows	5
3.2.1	Standalone Python	5
3.2.2	Anaconda	6
3.3	Mac	7
3.4	Uninstall	7
4	Input data	7
4.1	Configuration file	7
4.2	Landsat data	9
4.3	Raw mask files	9
5	Usage	9
5.1	Help message and configuration file	9
5.2	Draw black mask	10
5.3	Merge	11
5.4	Segmenting Landsat data and raw mask importing	11
5.4.1	Landsat data	11
5.4.2	Raw masks	12
5.4.3	Raw gee masks	12
5.4.4	Clean gee masks	12
5.4.5	Output files	12
5.5	Manual mask cleaning	12
5.5.1	Single mode	12
5.5.2	All mode	12
5.6	Skeletonization	13
5.7	Axis extraction	13
5.8	Migration evaluation	13
5.9	Bar extraction	14
6	Output	14
6.1	Mask and geotransf files	15
6.2	Skeleton file	15
6.3	Axis file	15
6.4	Migration file	16
6.5	Bendsep, interpolation and values files	16
7	Final remarks	16
	References	17

1 Introduction

PyRIS - Python Rivers by Satellite - is a open source software and package based on the freely available programming code Python⁴. PyRIS allows for the analysis of meandering and single threaded rivers morphodynamic characteristics using multitemporal satellite imagery (Monegaglia et al., 2018).

PyRIS allows for the extraction of river axis, channel width, axis curvature and inflection angle from binary masks. The mask can be either produced by the software from Landsat² imagery or imported from an external source (such as the ones produced by GEE). Moreover, when two or more axis are available, the software is able to correlate the bends through the analysis of the inflection points and to evaluate the migration vectors. Finally, it is able to detect channel bars and track their migration. For a more in depth review of the code capability refer to the original publication (Monegaglia et al., 2018).

2 Version tracking

In Table 1 we find the history of the various version of the software with a brief description of its main features. Note that it is only accurate for version higher than 3.0.0, the ones developed by the author of this guide.

Table 1: PyRIS version and main new features

Version	Date	Author	Main new features
1.0	2018	Federico Monegaglia	PyRIS deployment
3.0.0	2022	Riccardo Bonanomi	Converted to python 3
3.1.0	2022	Riccardo Bonanomi	Added GEE mask analysis capability
3.1.1	2023/03/20	Riccardo Bonanomi	Added ability to skip masks when segmenting Landsat or importing GEE mask
3.1.2	2023/04/19	Riccardo Bonanomi	Added ability to draw blacks mask on gee mask
3.1.3	2024/01/18	Riccardo Bonanomi	Fixed bug in migration evaluation
3.1.4	2024/02/05	Riccardo Bonanomi	Added skipping capability of non .tif files in external masks
3.1.5	2024/02/13	Riccardo Bonanomi	Removed clean gee options
3.2.0	2024/02/13	Riccardo Bonanomi	Moved from gee to raw mask options
3.2.1	2024/04/23	Riccardo Bonanomi	Improved manual mask cleaning functionalities
3.2.2	2024/06/09	Riccardo Bonanomi	Fixed Landsat 8-9 bug, fixed axis-files bug, fixed bars bug

3 Installation

To install PyRIS we need the installation of GDAL⁷ and of the following Python packages:

- setuptools (it is usually installed with pip and it is only needed for the installation process),
- numpy,
- scipy,

⁷<https://gdal.org/>

- matplotlib,
- scikit-image,
- gdal
- imagecodecs.

The installation procedure depends by the user operating system. We describe here the procedure for Linux and Windows.

3.1 Linux

On Linux PyRIS is a software that can be used from the command line and has been thoroughly tested. Moreover, the ability to merge different Landsat images is only possible in Linux at the moment. To install PyRIS we first need to install pip with

```
sudo apt-get install python-pip
```

and then GDAL, that can be done following this tutorial⁸:

```
sudo apt-get install python-dev
sudo add-apt-repository ppa:ubuntugis/ppa
sudo apt-get update
sudo apt-get install gdal-bin
sudo apt-get install libgdal-dev
export CPLUS_INCLUDE_PATH=/usr/include/gdal
export C_INCLUDE_PATH=/usr/include/gdal
```

after installing GDAL, in order to install the Python package we need to check the GDAL version with

```
ogrinfo --version
```

and then we can install it with

```
sudo pip install GDAL==<GDAL VERSION FROM OGRINFO>
```

note that the package wheel could be needed and it can be installed with

```
sudo pip install wheel
```

We need to install also the other python packages needed for PyRIS with

```
pip install setuptools numpy scipy matplotlib scikit-image imagecodecs
```

or using the requirement file in the pyris3 folder with

```
pip install -r requirements.txt
```

After this we can download the source code from GitHub with

```
git clone https://github.com/riccardobonanomi/pyris3.git
```

if you have Git⁹ or simply downloading the zip from the repository¹⁰.

From the pyris3 folder we need to launch the command

⁸<https://motherego-py.readthedocs.io/en/latest/development/how-to/gdal-ubuntu-pkg.html>

⁹<https://git-scm.com/>

¹⁰<https://github.com/riccardobonanomi/pyris3.git>

```
pip install .
```

and PyRIS will be installed. The old `python setup.py install` is now deprecated and using `pip` should be preferred.

To test it we can simply call

```
pyris -h
```

to print out the help message or

```
pyris -i <test filename>
```

to output a standard configuration file named `<test filename>`. The latter approach allows to test the PyRIS module, while the help script only test the existence of the software, but not its functioning. PyRIS can also be installed without admin privilege or in a virtual environment, but if you do not have admin privilege to install GDAL this becomes tricky. The procedure is not yet described here, but feel free to contact the author for help with it.

3.2 Windows

On Windows we have two main options, using Anaconda¹¹ or using a standalone Python⁴ installation. The author prefers the latter approach, but the former allows for an easier GDAL installation.

3.2.1 Standalone Python

After installing Python 3 from <https://www.python.org/downloads/> and adding it to the path (the Python installer should do it on its own), we need to install GDAL and its Python package. This is somewhat tricky and OSGeo¹² installation of GDAL do not necessarily work.

At <https://sandbox.oarc.ucla.edu/tutorials/installing-gdal-for-windows> the author found a procedure that worked.

From the website <https://www.gisinternals.com/index.html> we download and install first the core installer and then the Python bindings, for the appropriate version of GDAL and Python that we have. We then need to add the GDAL path (e.g. `C:\Program Files\GDAL`) to the Path System Environment Variable and the path need to be higher than the OSGeo installation, if we have one. Moreover we need to create two more Environment Variable, one named `GDAL_DATA`, pointing to the `gdal-data` folder (e.g. `C:\Program Files\GDAL\gdal-data`), and one named `GDAL_DRIVER_PATH`, pointing to the `gdalplugins` folder (e.g. `C:\Program Files\GDAL\gdalplugins`). To test the installation we can just type in the command prompt

```
ogrinfo --version
```

and the output should match the version we installed.

After installing GDAL, we need to install all the Python packages needed using

```
pip install setuptools numpy scipy matplotlib scikit-image imagecodecs
```

or using the requirement file in the `pyris3` folder with

```
pip install -r requirements.txt
```

from the command prompt.

We then download the PyRIS source code from the repository¹⁰ either with

¹¹<https://www.continuum.io/>

¹²<https://www.osgeo.org/>

```
git clone https://github.com/riccardobonanomi/pyris3.git
```

or downloading the zip folder.

From the pyris3 folder we need to launch the command

```
pip install .
```

in the command prompt and PyRIS will be installed. The old `python setup.py install` is now deprecated and using `pip` should be preferred.

In Windows however PyRIS is not a software like in Linux, the procedure only installs the PyRIS modules and creates the `pyrisw.py` wrapper script, that acts as the Linux software. To use it we just need to add the Scripts folder, in the Python executable folder to the Path and then associate Python as the default software to open `.py` files. Doing so, we will be able to use PyRIS just by typing

```
pyrisw.py
```

in the command prompt. If we do not want to choose Python as the default software we just need to type the path of the `pyrisw.py` script, either in the Python path or the build folder in the pyris3 folder. In this case we just need to type

```
python <path-to-script>\pyrisw.py
```

in the command prompt like a normal Python script. To test, like for the Linux case, we can just use the `-h` flag to print the help message or the `-i` flag with a test filename to output a standard configuration file. As seen for the Linux case, the latter allows to test also the PyRIS module and not only the main script.

3.2.2 Anaconda

After installing Anaconda from <https://www.continuum.io/downloads>, we need to add Python to the Environment Variables.

We need to install GDAL running from the Anaconda prompt

```
conda install gdal
```

and then we can install the various packages like for the Linux case with

```
pip install setuptools numpy scipy matplotlib scikit-image imagecodecs
```

or using the requirement file in the pyris3 folder with

```
pip install -r requirements.txt
```

also from the Anaconda prompt.

After this we can download the PyRIS source code as seen for the Python standalone case and run

```
pip install .
```

in the Anaconda prompt from the pyris3 folder and PyRIS will be installed.

The old `python setup.py install` is now deprecated and using `pip` should be preferred.

To launch it and test it we can refer to the Python standalone case, just using the Anaconda prompt instead of the command prompt.

Known errors Using Anaconda an error can show up during the installation of PyRIS that reads

On Windows, with Python ≥ 3.8 , DLLs are no longer imported from the PATH.
If `gdalXXX.dll` is in the PATH, then set the `USE_PATH_FOR_GDAL_PYTHON=YES` environment variable to feed the PATH into `os.add_dll_directory()`.

In this case the user just needs to either specify it in this instance of the prompt with

```
SET USE_PATH_FOR_GDAL_PYTHON=YES
```

or, more permanently, the user can set the variable at the environment level using (inside the environment)

```
conda env config vars set USE_PATH_FOR_GDAL_PYTHON=YES
```

and the reactivating the environment.

Sometimes when reinstalling PyRIS an another error with GDAL appears and the user will need to reinstall GDAL, uninstalling it first with

```
conda uninstall gdal
```

3.3 Mac

On Mac OS it should work just like in Linux, so we can refer to that section.

3.4 Uninstall

If you want to uninstall it, regardless the platform you can use `pip uninstall pyris` like a regular pip package. You could also delete all the package file, the wrapper script and the package info from you Python folder but this approach is less effective.

With the older deprecated `python setup.py install` installation method it was necessary to uninstall an old installation before installing a new version, but this is not the case any more with the use of pip.

4 Input data

4.1 Configuration file

The original code requires a configuration file with the following structure:

```
[Data]
input =
output =
flow_from =
channel_width = None

[Segmentation]
method = MIX
thresholding = global
black_masks = []

[Pruning]
```



```
prune_iter = 25
```

```
[Axis]  
reconstruction_method = std  
maxiter = 100000
```

that can be created using the `-i` or `--init` flags followed by the name of the file. The file is not needed when only evaluating the migration rate specifying the axis folder or files.

The Data section contains information about the input and output data, in particular we need to specify:

- `input`, the path to the Landsat folder, which is not needed when using the raw mask options (`-R`);
- `output`, with the output folder that will contain all the PyRIS outputs;
- `flow_from`, to specify the direction from which the water flows, it accepts:
 - `t` = top;
 - `b` = bottom;
 - `r` = right;
 - `l` = left;
- `channel_width`, to specify the minimum river width to consider, it can not be left as `None` as it is initialized when creating the configuration file; we suggest to choose a lower value than the actual width since nothing below this value will be considered.

The Segmentation section contains parameters regarding the river mask segmentation, that is the process that extract the river mask from the Landsat images. The data needed are:

- `method`, to specify the indexes used to segment the image, we can use:
 - `NDVI`, the Normalized Difference Vegetation Index;
 - `MNDWI`, the Modified Normalized Difference Water Index;
 - `BAR`, that is the SWIR, the Short Wave InfraRed Band;
 - `MIX`, that is a combination of the previous indexes and the default option;
 - `AWEI`, not yet implemented;
- `thresholding`, the thresholding method for the chosen index, the available option are:
 - `global`, to apply a global Otsu threshold (default);
 - `local`, to apply a local Otsu threshold, more time consuming;
- `black_mask`, that contains an array of coordinates array for each rectangular area of the image to exclude from the analysis. It can be populate through the `--select-black-mask` flag.

The Pruning section only contains the `prune_iter` parameter, that sets the maximum pruning iteration counter (the default value is 25). The Axis section contains the parameters used to extract the axis from the mask. It needs:

- `reconstruction_method`, to specify with method to use to choose between branches at a junction, among:

- std, standard method, a mix between length and width constraints (default value);
- length, to choose the branch with the highest length;
- width, to choose the branch with the highest average width;
- maxiter, maximum iteration for the axis extraction (the default value is 100000).

4.2 Landsat data

The Landsat data folder has to be specified in the configuration file and it will contain a sub-folder for each image, containing the various bands. The data can be downloaded through the USGS's Earth Explorer¹³ and the naming of the subfolder for each year shall remain the one you Earth Explorer gives when you download the data.

4.3 Raw mask files

The software is able to analyse external binary masks from whatever source and not only Landsat, provided that they are in the .tif format and with an UTM projection. They need to be put in a raw sub-folder in the output folder or they can be put in an external folder that can be specified with the --raw-dir <path-to-mask-dir> option.

The code was first developed to include mask extracted with the GEE code developed by Marta Crivellaro¹⁴. Up until now the mask from GEE were extracted for permafrost rivers and to be able to do so the code uses the Perona-Malik filter to reduce the noise and analyse the summer envelope. Knowing this PyRIS does not know the precise day and assigns automatically as a day 213, while the year is extracted from the mask name.

PyRIS is able to use already clean masks, where the feature choice has been done externally, in a GIS or other software, and non-clean masks, where the feature choice is done in PyRIS with an identical method as for the Landsat case.

5 Usage

5.1 Help message and configuration file

To launch the software use the command pyris on Linux or pyrisw.py on Windows. The help page that follows will appear when using the -h flag and shows all the software commands.

```
usage: pyrisw.py [-h] [-v] [-i] [--select-black-mask SELECT_BLACK_MASK]
                [--merge MERGE [MERGE ...]] [--output OUTPUT] [-S]
                [--label LABEL] [--clean-mask [CLEAN_MASK ...]]
                [--clean-label CLEAN_LABEL] [-R] [--raw-dir RAW_DIR]
                [-C] [--gee-clean-dir GEE_CLEAN_DIR] [-K] [-A] [--mask-dir MASK_DIR]
                [--no-geo] [-M] [--axis-files AXIS_FILES [AXIS_FILES ...]]
                [--axis-dir AXIS_DIR] [--axis-columns AXIS_COLUMNS AXIS_COLUMNS]
                [--output-dir OUTPUT_DIR] [--pfreq PFREQ] [-B] [--show] [config]
```

PyRIS v3.2.2 :: Python - RIvers from Satellite

positional arguments:

¹³<https://earthexplorer.usgs.gov/>

¹⁴University of Trento - Center Agriculture Food Environment (C3A)

```

config                input configuration file

optional arguments:
-h, --help            show this help message and exit
-v, --version          show program's version number and exit
-i, --init             initialize a config file with default settings
--select-black-mask SELECT_BLACK_MASK
                      interactively draw black masks from landsat data
--merge MERGE [MERGE ...]
                      landsat folders to be merged together (requires
                      gdal_merge)
--output OUTPUT        where merged landsat are to be stored
--label LABEL          if auto, pyris will try to label masks by itself. other
                      options are max and all
-S, --segmentation     perform segmentation of all the landsat folders
-R, --raw-mask-import  import raw .tif masks obtained outside PyRIS to be cleaned
--raw-dir RAW_DIR      dir in which to read ordered-by-name raw .tif mask
--clean-mask [CLEAN_MASK ...]
                      manually clean some branches
--clean-label CLEAN_LABEL
                      if all it will apply the cleaning to all the subsequent ones too
-K, --skeletonization  skeletonize masks
-A, --axis             extract main channel axis from channel mask
--mask-dir MASK_DIR    directory containing mask files
--no-geo              do not georeference mask files
-M, --migration        compute migration rates of subsequent axis
--axis-files AXIS_FILES [AXIS_FILES ...]
                      ordered sequence of files for which the migration rates
                      must be computed
--axis-dir AXIS_DIR    dir in which to read ordered-by-name axis files (if
                      --axis-files is not specified)
--axis-columns AXIS_COLUMNS AXIS_COLUMNS
                      columns containing axis coordinates
--output-dir OUTPUT_DIR
                      directory where outputs of migration rates will be stored
--pfreq PFREQ          an interpolation step between points to be used as a
                      frequency filter (a few channel widths in pixels).
-B, --bars            compute the position of channel bars
--show               show results after computing

```

To create an empty configuration file, as described in the input section, use the `-i` or `--init` flag followed by the file name. The configuration file is needed for each step minus the manual cleaning of masks and the migration evaluation from a specified axis folder.

5.2 Draw black mask

PyRIS let you draw areas to exclude from the mask extraction for Landsat data and raw masks using `--select-black-mask <path-to-landsat-dir-or-to-gee-mask>`. We need to specify the path to the Landsat folder for one image or for one GEE mask (with the file extension) that is representative, since the mask will be drawn one and for all. The command opens a display of the chosen data where the black mask can be drawn interactively, drawing the rectangles to exclude holding the

left click while moving the pointers and for every area draw the local coordinates will be printed on the terminal; when you finish the selection simply close the display and the mask will be saved. The command does not modify the files, but it saves in the configuration files (that must be specified) the coordinates of the excluded areas under the `black_mask` entry of the [Segmentation] section, that can also be modified from the text editor.

5.3 Merge

The merge option uses the GDAL command `merge` to join more than a Landsat image for each year. It is used specifying `--merge <path-to-landsat-to-merge>`. The output folder needs to be specified with `--output <path-to-output-folder>`. This features requires GDAL merge and as for now only works on Linux, but the author is working on extending it also to Windows.

5.4 Segmenting Landsat data and raw mask importing

Since the output data of this processes are the same, but the procedures are a little different in three cases, we will first present the three commands and then we will speak about the output files. If a mask is already been extracted from a specific year the software will skip the image, unless the mask and `geotransf` file are deleted.

5.4.1 Landsat data

With the flag `-S` or `--segmentation`, with the configuration file, PyRIS will begin the segmentation of the Landsat data and the mask extraction, with the data and the option specified in the configuration file, as seen in subsection 4.1. The mask are extracted using the index or indexes specified in the `method` entry of the configuration file and it uses a global or local thresholding using the specified option in the `thresholding`. The software also applies filters to clean holes in the planform and to remove small objects using the width specified in the `channel_width` entry as base measure for the various filters and area removal used.

After this process the user need to select the mask features to analyse. With the `--label <option>` the user is able to specify the optional automatic mask choice methods. The available options are:

- `auto`, to use the `max`, option when using local thresholding (specified in the configuration file), and `all`, when using global thresholding;
- `all`, to choose every feature present in the mask;
- `max`, to choose the largest feature present in the mask.

If the label option is not specified, a display prompt will appear for each Landsat image and the user will see all the features available labelled with a number. After closing the prompt PyRIS will ask to enter in the terminal the feature number to select, separated with a space if the user wants multiple features. The choice of multiple features still has some issues, but the author is working to solve them. To discard an image you can input any negative number and the software will skip that year and save the name of the rejected mask in a log file name as the configuration file. After choosing the feature the software will fill hole in the mask and remove small objects, to clean the mask.

The segmentation of the Landsat data is the PyRIS command that has the higher resources load, especially on the RAM, and we started using GEE also to avoid this issue.

5.4.2 Raw masks

Using the `-R` or `--raw-mask-import` flags PyRIS will import the raw external mask and extract the features that can be chosen as for the Landsat case: the `--label <option>` flag works also for this case and, if no automatic mask choice is used, the user will choose the features to analyse for in the same way as per the Landsat case. As in the Landsat case the mask will then be cleaned removing small objects and filling holes.

5.4.3 Raw gee masks

Using the `-G` or `--gee-mask-import` flags are deprecated in version 2.1, the raw mask options work exactly the same.

5.4.4 Clean gee masks

The `-C` or `--clean-gee-mask-import` flags are deprecated, the `-R` with the `--label all` option work exactly the same.

5.4.5 Output files

Whichever road you choose, all this commands will create a `geotransf` file and a mask file in their respective folders (folders structure, file naming and file contents will be described in section 6).

5.5 Manual mask cleaning

After the user creates the mask file, the `--clean-mask` allow for manual cleaning of the mask files.

5.5.1 Single mode

Using just the configuration file and the `--clean-mask` flag will open all the masks in the mask folder. To specify a single or multiple masks the user can specify their name like (eventually using also the path) `--clean-mask <mask-to-clean-1 mask-to-clean-2>`. If the user does not wish to specify a configuration file it is possible just to specify a folder with `--clean-mask <path-to-dir-to-clean>` or a list of masks with `--clean-mask <path-to-mask-to-clean-1 path-to-mask-to-clean-2>`, however without a configuration file the removal of small objects will use a river width of 3 pixels instead of the one specified in the configuration file. This command will open a display prompt where each mask is shown and the user can drag, while left clicking, selecting the areas to remove from the mask. After closing the prompt, the coordinates of the removed areas will appear in the terminal, followed by the message `overwrite mask file? [y/n]`, that lets the user choose whether to apply this changes or not if any selection was made in the prompt. This is particularly useful to speed up the axis extraction in rivers with high number of branches that needs to be removed. Be aware that this process modifies the mask file directly and to revert it you will need to extract the mask from the Landsat data or from the raw masks. This behaviour will be achieved also adding the flag `--clean-label single`

5.5.2 All mode

If the user wishes to clean an image and apply the mask to the subsequent ones, for example to remove an oxbow lake after a cutoff, the user can use `--clean-mask` and the `--clean-label all`. The software will loop through the masks and when the user draws one or more areas on one of them and agreed to the overwrite, like in the basic mask cleaning, it will remove those areas also in all the images

after that ones. If the user wishes to specify where to start the cleaning, instead of looping through all the images, it can be done with `--clean-mask <mask-to-clean>` followed by the label.

5.6 Skeletonization

The river skeleton can be extracted from the mask using the `-K` or `--skeletonization` flag and saves it in the `skeleton` folder. The skeletonization processes prunes spurs from the river and depending by the number of this spurs the pruning process can take a while. Each pruning iteration is printing on the terminal for each of the features found in the mask. Be careful when you manually clean the mask, since if you delete completely a feature the software will give an error in this stage. This command will create a skeleton file, described in section 6. If the software detects more than 15 junction it will prompt the following warning:

```
'''
'Warning!'
'Expected at least <Number-of-junctions> recursion level.'
'Consider increasing the pruning iteration or calling pyris with the
--clean-mask flag'
'''
```

since it can lead to slow axis extraction or even non-correct paths choice when close to the domain edges. This warning will appear even if the pruning had plenty of iteration and stopped before the maximum number of pruning iterations inputted by the user in the `prune_iter` entry of the configuration files.

The user can also specify the mask folder with `--mask-dir <path-to-mask-dir>`. If a particular mask has already been skeletonized previously the software will skip it, unless the skeleton file is deleted.

5.7 Axis extraction

From the skeleton and the mask PyRIS extracts the river axis and its inflection angle, curvature and width using the `-A` or `--axis` flag. For each feature selected in the segmentation process the software will search for a primitive where to put the beginning of the axis and it will extract the axis choosing for each junction which branch to keep based on the `reconstruction_method` specified in the configuration file with one of the three options described in section 4.1. The software iterates until it reaches the end of the axis or the `max_iter` parameter specified in the configuration file. The axis is then added to the previous feature axis and when all the features of the mask are analysed, the axis is interpolated with a cubic spline calculating also the inflection angle, the curvature and the width on the new interpolated axis. With multiple features the software does not work properly, as said earlier, because it often does not start from the correct side for each feature, but the author is working to fix the issue.

With the `--mask-dir <path-to-mask-dir>` the user can specify the position of the mask folder and with the `--no-geo` the mask will not be georeferenced. If the mask are not georeferenced every output data is in pixel (the same units as the one in the mask files). The command will save an axis file for each year in the `axis` folder, that will be described in section 6. If a particular axis has already been extracted the software will skip it, unless the axis file is deleted.

5.8 Migration evaluation

Using the `-M` or `--migration` flag the software correlates the bends between two consecutive planimetrys and evaluates the migration rate for each point for the bend that it manages to correlate. The

migration evaluation is the only step where the software overrides already existing data, but it is usually not a problem since the process is really fast compared to the other steps. The user can specify the individual files (in the txt or npy format) to use to perform the calculation indicating the ordered sequence of filenames with `--axis-files <axis-file-1 axis-file-2>` specifying also the path in the file name or providing the config file if the axis are in the axis folder. Moreover he can specify the folder where to find the axis files with `--axis-dir <path-to-axis-dir>`, that will be analysed ordered by name. When specifying the files or the folder it is possible also to specify which columns are the x and y ones to use for the computation with `--axis-columns <x-column y-column>`.

The user can also specify the output directory with `--output-dir <path-to-output-dir>` and the smoothing coefficient for the channel with `--pfreq <pfreq>`. The value needs to be 1 or greater, with 1 being the default option, that means no smoothing applied. The smoothing is performed with a Inverse Continuous Wavelet Transform (ICWT hereinafter).

The software will save a file for each year containing the correlated bend indices and the migration rates, the actual structure of the file and the data will be described in section 6. The migration is always saved in the first year of the two, so the last file will have just NaN as migration rates.

The software is also able to show the results of the migration evaluation with the option `--show`.

Keep in mind that the correlation process and the migration evaluation is not always successful, especially with fast varying meandering rivers or with a low number of planimetries over long time intervals.

5.9 Bar extraction

With the `-B` or `--bars` the software will extract the position of the sediment bars and track their migration. This function computes the free bars evolution in the river, but in order to do so needs to calculate the satellite image indexes once again and so it needs the presence of the Landsat data in the folder specified in the configuration file and it can not be used on the data extracted from external masks. The feature is still experimental and it has not been tested yet by the author of this guide.

With the `--show` flag the software will show the output results of the bars extraction.

6 Output

PyRIS produced various output files for each command. The file are all named with the name of the planimetry they represent using the year and the day of the year (`<year>_<day-of-year>.<ext>`) and they are each saved in a folder named with the type of the file. All the files are Python and Numpy¹⁵ specific files (`.npy` and `.p`) to allow for faster calculation, but they can easily be converted to readable formats using simple Python commands.

The file produced by each command are:

- a mask file and a `geotransf` file;
- a skeleton file;
- a axis file;
- a migration file, produced by the migration evaluation;
- a `bendsep`, an interpolation, a values file and a `barcorr`, in the bars folder, that are a single file for each river, and not one per planimetry.

¹⁵<https://numpy.org/>

The description of the content of each file can be found in the next subsections, divided by the command that produced it.

6.1 Mask and geotransf files

A mask and a geotransf for each planimetry file are produced for each planimetry by the segmentation of the Landsat data or the extraction of the features from the external masks.

The geotransf file is a pickle (.p) file which contains the information needed to switch from the internal reference system of the image in pixel to the UTM reference system that the original data was in and allows for conversion in metric units of the outputs. It contains a dictionary with the following structure.

```
{'PixelSize': <PixelSize-value>, 'X': <X-value>, 'Y': <Y-value>,  
'Lx': <Lx-value>, 'Ly': <Ly-value>}
```

The 'PixelSize' field contains the pixel width, the X and Y are the x and y coordinates of the upper-left corner of the upper-left pixel, and the Lx and Ly are the number of pixels in the x and y directions.

The mask file is a .npy file that contains a matrix with the shape of the original data (Lx x Ly pixels) populated with 1 for each pixel of chosen feature and 0 for each pixel that does not contains it.

6.2 Skeleton file

A skeleton file for each planimetry is produced by the skeletonization process and is also a .npy file containing a matrix with the same shape as the original data. The matrix contains the skeleton of the mask, so the centreline pixel of each feature, numbered with a integer different for each separate feature, while the background has value 0.

6.3 Axis file

An axis file for each planimetry is produced by the axis extraction process and is a .npy file containing a table with one row for each planimetry point. Each planimetry points has 8 entries that are, in order:

- x , the geo-referenced x coordinate;
- y , the geo-referenced y coordinate;
- s , the along the axis coordinate, in meters;
- θ , the inflection angle of the centreline;
- C_s , the curvature of the centreline;
- B , the channel half width;
- x_p , the local x coordinate, using the pixel as unit of measure;
- y_p , the local y coordinate, using the pixel as unit of measure.

If the file are generated using the `--no-geo` option all the variables will be in the local coordinate system, using the pixel as unit of measure.

6.4 Migration file

A migration file for each planimetry is produced by the migration command and is a .npz file containing a table with one row for each planimetry point. For each point we have 7 entries:

- dx , the x component of the migration vector between this planimetry and the next one;
- dy , the y component of the migration vector between this planimetry and the next one;
- dz , the module of the migration vector between this planimetry and the next one;
- $ICWTC$, the curvature filtered using the ICWT filter;
- BI , a progressive index for each bend of this planimetry, each point of a bend will have the same value, greater or equal than 0, and the point before the first inflection point and after the last inflection point will be equal to -1;
- $B12$, the index of the correlated bend in the next planimetry;
- BUD , the index of the position of the point in the bend, this can have values:
 - 0 = the point is the bend apex;
 - -1 = the point is upstream of the bend apex;
 - +1 = the point is downstream of the bend apex;
 - 2 = the point is an inflection point.

Since the migration is evaluated between one planimetry and the next one, the last one will have NaN values in all the migration vector components and -1 in all the $B12$ values. The point before the first inflection point or after the last will also have NaN in all the migration vector components. The migration vector are measured in the same units as the axis, so they are in meters if the data is geo-referenced, in pixel if the `--no-geo` options was used or in the axis unit of measure for user inputted axis files. Since they are vector, to evaluate the rate the user will need to divide the vector components by the time between two planimetries.

6.5 Bendsep, interpolation and values files

The bar detection command produces a total of four .npz files, the `bendsep` file, the `interpolation` file, the `values` file and the `barcorr`. Since the author of this guide did not test this function the content of the files are not yet described here.

7 Final remarks

PyRIS is a rather powerful software, but it is not perfect, so we encourage you to check the correctness of the data extracted with original data, to ensure that the results are correctly representing the feature you want to analyse.

Moreover the author is encouraging any suggestions, comments and feature request to improve the present manual and the PyRIS software.

References

Monegaglia, E., G. Zolezzi, I. Güneralp, A. J. Henshaw, and M. Tubino (2018). “Automated extraction of meandering river morphodynamics from multitemporal remotely sensed data”. In: *Environmental Modelling & Software* 105, pp. 171–186. DOI: 10.1016/j.envsoft.2018.03.028.