

# MS Registry REST API Resources

## Contents

|                                |          |
|--------------------------------|----------|
| <b>Document Version</b>        | <b>2</b> |
| <b>GET /auth/test</b>          | <b>3</b> |
| Resource Information . . . . . | 3        |
| Resource Errors . . . . .      | 3        |
| Example . . . . .              | 3        |
| Response . . . . .             | 3        |
| <b>GET /user</b>               | <b>3</b> |
| Resource Information . . . . . | 4        |
| Response Parameters . . . . .  | 4        |
| Resource Errors . . . . .      | 4        |
| Example . . . . .              | 4        |
| Response . . . . .             | 4        |
| Resource Information . . . . . | 5        |
| Response Parameters . . . . .  | 5        |
| Resource Errors . . . . .      | 5        |
| Example . . . . .              | 6        |
| Response . . . . .             | 6        |
| <b>POST /user/consent</b>      | <b>6</b> |
| Resource Information . . . . . | 6        |
| Request Parameters . . . . .   | 6        |
| Response Parameters . . . . .  | 7        |
| Resource Errors . . . . .      | 7        |
| Example . . . . .              | 7        |
| Response . . . . .             | 7        |
| <b>GET /diary</b>              | <b>7</b> |
| Resource Information . . . . . | 8        |
| Response Parameters . . . . .  | 8        |
| Resource Errors . . . . .      | 8        |
| Example . . . . .              | 8        |
| Response . . . . .             | 8        |
| <b>POST /diary</b>             | <b>9</b> |
| Resource Information . . . . . | 9        |

|                                   |           |
|-----------------------------------|-----------|
| Request Parameters . . . . .      | 9         |
| Response Parameters . . . . .     | 9         |
| Resource Errors . . . . .         | 9         |
| Example . . . . .                 | 10        |
| Response . . . . .                | 10        |
| <b>GET /survey</b>                | <b>10</b> |
| Resource Information . . . . .    | 10        |
| Response Parameters . . . . .     | 10        |
| Resource Errors . . . . .         | 10        |
| Example . . . . .                 | 11        |
| Response . . . . .                | 11        |
| <b>GET /survey/get/&lt;id&gt;</b> | <b>11</b> |
| Resource Information . . . . .    | 12        |
| Request Parameters . . . . .      | 12        |
| Response Parameters . . . . .     | 12        |
| Resource Errors . . . . .         | 12        |
| Example . . . . .                 | 12        |
| Response . . . . .                | 13        |
| <b>POST /survey</b>               | <b>13</b> |
| Resource Information . . . . .    | 13        |
| Request Parameters . . . . .      | 13        |
| Response Parameters . . . . .     | 13        |
| Resource Errors . . . . .         | 13        |
| Example . . . . .                 | 14        |
| Response . . . . .                | 14        |

## Document Version

**Date** 2016-04-08

**Version** v0.3.2

**Authors** Filippo Panessa <filippo.panessa@gmail.com>

**Copyright** Copyright (c) 2016 S3IT, Zentrale Informatik, University of Zurich

Welcome to the MS Registry REST API. Below, you'll find a full listing of all the available endpoints. As we add more endpoints, they will be automatically documented here.

The endpoint's documentation section includes what query parameters the endpoint will accept, what the JSON object's parameters will be in the response, and an example query/response.

This documentation is for most recent version of the MS Registry REST API, version **v0.3.2**.

## GET /auth/test

Test Bearer Token authentication.

### Resource Information

|                          |                       |
|--------------------------|-----------------------|
| Method                   | GET                   |
| URL                      | /auth/test            |
| Requires authentication? | Yes                   |
| Requires Role?           | Every Role can access |

### Resource Errors

These are the possible errors returned by this endpoint.

| status | code                   | message                                     |
|--------|------------------------|---|
| 403    | authorization_required | Authorization header is expected            |
| 401    | invalid_header         | Authorization header must start with Bearer |
| 401    | invalid_header         | Token not found                             |
| 400    | token_expired          | Token is expired                            |
| 400    | invalid_audience       | Incorrect audience                          |
| 400    | invalid_signature      | Token signature is invalid                  |

### Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/auth/test'
```

### Response

```
{
  "status": 200,
  "code": "authorization_success",
  "description": "All good. You only get this message if you're authenticated."
}
```

## GET /user

Get metadata about the current user.

## Resource Information

|                          |                       |
|--------------------------|-----------------------|
| Method                   | GET                   |
| URL                      | /api/v1.0/user        |
| Requires authentication? | Yes                   |
| Requires Role?           | Every Role can access |

## Response Parameters

| Parameter           | Type                | Description  |
|---------------------|---------------------|--|
| <b>uniqueID</b>     | (string)            | That's the unique ID of the user, received from OAuth server             |
| <b>member_since</b> | (iso 8601 datetime) | Datetime the user joined   |
| <b>last_seen</b>    | (iso 8601 datetime) | Datetime last seen user. This field is updated on every user interaction |

## Resource Errors

These are the possible errors returned by this endpoint.

| status | code                   | message                                     |
|--------|------------------------|---|
| 403    | authorization_required | Authorization header is expected            |
| 401    | invalid_header         | Authorization header must start with Bearer |
| 401    | invalid_header         | Token not found                             |
| 400    | token_expired          | Token is expired                            |
| 400    | invalid_audience       | Incorrect audience                          |
| 400    | invalid_signature      | Token signature is invalid                  |
| 404    | not_found              | Couldn't found a User with UniqueID={}      |

## Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user'
```

## Response

```
{
  "uniqueID": "auth0|569cf82bfc02d8a0339beef4",
  "member_since": "2016-03-04T17:03:37",
  "last_seen": "2016-03-04T17:05:12"
}
```

GET /user/consent/info —————

Get information about user acceptance of Informed Consent.

## Resource Information

|                          |                        |
|--------------------------|------------------------|
| Method                   | GET                    |
| URL                      | /api/v1.0/user/consent |
| Requires authentication? | Yes                    |
| Requires Role?           | Patient, Relative      |

## Response Parameters

Relative Role

| Parameter        | Type     | Description                                     |
|------------------|----------|---|
| <b>birthdate</b> | (string) | Birthdate in this form<br>%DD.%MM.%YYYY         |
| <b>sex</b>       | (string) | Sex. Possibly values are ‘male’ and<br>‘female’ |
| <b>signature</b> | (string) | Signature by Initials, max 3 digits             |

Patient Role

| Parameter                          | Type     | Description                                     |
|------------------------------------|----------|---|
| <b>birthdate</b>                   | (string) | Birthdate in this form<br>%DD.%MM.%YYYY         |
| <b>sex</b>                         | (string) | Sex. Possibly values are ‘male’ and<br>‘female’ |
| <b>signature</b>                   | (string) | Signature by Initials, max 3 digits             |
| <b>physician_contact_permitted</b> | (bool)   | Physician contact permitted                     |
| <b>data_exchange_cohort</b>        | (bool)   | Data exchange cohort                            |
| <b>medical_record_abstraction</b>  | (bool)   | Medical record abstraction                      |

## Resource Errors

These are the possible errors returned by this endpoint.

| status | code                   | message  |
|--------|------------------------|--|
| 403    | authorization_required | Authorization header is expected               |
| 401    | invalid_header         | Authorization header must start with<br>Bearer |

| status | code              | message                                |
|--------|-------------------|--|
| 401    | invalid_header    | Token not found                        |
| 400    | token_expired     | Token is expired                       |
| 400    | invalid_audience  | Incorrect audience                     |
| 400    | invalid_signature | Token signature is invalid             |
| 401    | unauthorized      | Insufficient Roles                     |
| 404    | not_found         | Couldn't found a User with UniqueID={} |

## Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/consent'
```

## Response

```
{
  "birthdate": "18.09.1974",
  "sex": "M",
  "signature": "FP",
  "data_exchange_cohort": true,
  "date_signed": "2016-03-30T14:33:48.011000",
  "medical_record_abstraction": true,
  "data_exchange_cohort": true,
  "physician_contact_permitted": true
}
```

## POST /user/consent

Set user acceptance of Informed Consent.

## Resource Information

|                          |                        |
|--------------------------|------------------------|
| Method                   | POST                   |
| URL                      | /api/v1.0/user/consent |
| Requires authentication? | Yes                    |
| Requires Role?           | Patient, Relative      |

## Request Parameters

| Parameter | Type   | Description   |
|-----------|--------|---|
| consent   | (bool) | Set True is Informed Consent has been accepted, False otherwise |

| Parameter | Type | Description |
|-----------|------|-------------|
|-----------|------|-------------|

## Response Parameters

| Parameter      | Type   | Description   |
|----------------|--------|---|
| <b>success</b> | (bool) | Return True if content was accepted and registered, False otherwise |

## Resource Errors

These are the possible errors returned by this endpoint.

| status | code                   | message                                     |
|--------|------------------------|---|
| 403    | authorization_required | Authorization header is expected            |
| 401    | invalid_header         | Authorization header must start with Bearer |
| 401    | invalid_header         | Token not found                             |
| 401    | invalid_header         | Authorization header must be Bearer + token |
| 400    | token_expired          | Token is expired                            |
| 400    | invalid_audience       | Incorrect audience                          |
| 400    | invalid_signature      | Token signature is invalid                  |
| 401    | unauthorized           | Insufficient Roles                          |

## Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
-X POST -d '{"consent": true}' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/consent'
```

## Response

```
{
  "success": true
}
```

## GET /diary

Get User's Diary.

## Resource Information

|                          |                   |
|--------------------------|-------------------|
| Method                   | GET               |
| URL                      | /api/v1.0/diary   |
| Requires authentication? | YES               |
| Requires Role?           | Patient, Relative |

## Response Parameters

| Parameter | Type                | Description  |
|-----------|---------------------|--|
| diary     | (json file)         | Return user's Diary. Returned value is a RAW JSON file |
| timestamp | (iso 8601 datetime) | Datetime the diary was updated                         |

## Resource Errors

These are the possible errors returned by this endpoint.

| status | code                   | message                                     |
|--------|------------------------|---|
| 403    | authorization_required | Authorization header is expected            |
| 401    | invalid_header         | Authorization header must start with Bearer |
| 401    | invalid_header         | Token not found                             |
| 401    | invalid_header         | Authorization header must be Bearer + token |
| 400    | token_expired          | Token is expired                            |
| 400    | invalid_audience       | Incorrect audience                          |
| 400    | invalid_signature      | Token signature is invalid                  |
| 401    | unauthorized           | Insufficient Roles                          |

## Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/diary'
```

## Response

```
{
  "diary": {
    "value": "any"
  },
}
```



```
    "timestamp": "2016-03-23T15:03:41.643000"
}
```

## POST /diary

Write User's Diary or Update it. In case of Update, Backend keeps track of previous Diary versions.

### Resource Information

|                          |                   |
|--------------------------|-------------------|
| Method                   | POST              |
| URL                      | /api/v1.0/diary   |
| Requires authentication? | Yes               |
| Requires Role?           | Patient, Relative |
| Requires IC Accepted?    | Yes               |

### Request Parameters

| Parameter | Type        | Description   |
|-----------|-------------|---------------|
| diary     | (json file) | RAW JSON file |

### Response Parameters

| Parameter | Type   | Description   |
|-----------|--------|---|
| success   | (bool) | Return True if diary was accepted, False if JSON File is not well formatted |

### Resource Errors

These are the possible errors returned by this endpoint.

| status | code                   | message                                     |
|--------|------------------------|---|
| 403    | authorization_required | Authorization header is expected            |
| 401    | invalid_header         | Authorization header must start with Bearer |
| 401    | invalid_header         | Token not found                             |
| 401    | invalid_header         | Authorization header must be Bearer + token |
| 400    | token_expired          | Token is expired                            |
| 400    | invalid_audience       | Incorrect audience                          |
| 400    | invalid_signature      | Token signature is invalid                  |

| status | code         | message                          |
|--------|--------------|----------------------------------|
| 401    | unauthorized | Insufficient Roles               |
| 401    | unauthorized | Consent Information not accepted |

## Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
-X POST -d '{"value': 'any'}" \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/diary'
```

## Response

```
{
  "success": true
}
```

## GET /survey

Get All Surveys compiled by User.

## Resource Information

|                          |                   |
|--------------------------|-------------------|
| Method                   | GET               |
| URL                      | /api/v1.0/survey  |
| Requires authentication? | YES               |
| Requires Role?           | Patient, Relative |

## Response Parameters

| Parameter | Type                | Description   |
|-----------|---------------------|---|
| surveys   | (array)             | Return list of all Surveys compiled by User as JSON array |
| id        | (string)            | Return Survey ID  |
| survey    | (json file)         | Return User's Survey. Returned value is a RAW JSON file   |
| timestamp | (iso 8601 datetime) | Datetime the survey was inserted                          |

## Resource Errors

These are the possible errors returned by this endpoint.

| status | code                   | message                                     |
|--------|------------------------|---|
| 403    | authorization_required | Authorization header is expected            |
| 401    | invalid_header         | Authorization header must start with Bearer |
| 401    | invalid_header         | Token not found                             |
| 401    | invalid_header         | Authorization header must be Bearer + token |
| 400    | token_expired          | Token is expired                            |
| 400    | invalid_audience       | Incorrect audience                          |
| 400    | invalid_signature      | Token signature is invalid                  |
| 401    | unauthorized           | Insufficient Roles                          |

## Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/survey'
```

## Response

```
{
  "surveys": [
    {
      "id": "56f2c662ec71bc2c6b001040",
      "survey": {
        "value": "any"
      },
      "timestamp": "2016-03-23T16:37:54.765000"
    },
    {
      "id": "56f2c7cdec71bc2c6b001041",
      "survey": {
        "value": "any"
      },
      "timestamp": "2016-03-23T16:43:57.800000"
    }
  ]
}
```

## GET /survey/get/<id>

Get All Surveys compiled by User.

## Resource Information

|                          |                           |
|--------------------------|---------------------------|
| Method                   | GET                       |
| URL                      | /api/v1.0/survey/get/<id> |
| Requires authentication? | YES                       |
| Requires Role?           | Patient, Relative         |

## Request Parameters

| Parameter | Type     | Description |
|-----------|----------|-------------|
| id        | (string) | Survey ID   |

## Response Parameters

| Parameter | Type                | Description   |
|-----------|---------------------|---|
| id        | (string)            | Return Survey ID  |
| survey    | (json file)         | Return user's Survey. Returned value is a RAW JSON file |
| timestamp | (iso 8601 datetime) | Datetime the survey was inserted                        |

## Resource Errors

These are the possible errors returned by this endpoint.

| status | code                   | message                                     |
|--------|------------------------|---|
| 403    | authorization_required | Authorization header is expected            |
| 401    | invalid_header         | Authorization header must start with Bearer |
| 401    | invalid_header         | Token not found                             |
| 401    | invalid_header         | Authorization header must be Bearer + token |
| 400    | token_expired          | Token is expired                            |
| 400    | invalid_audience       | Incorrect audience                          |
| 400    | invalid_signature      | Token signature is invalid                  |
| 401    | unauthorized           | Insufficient Roles                          |

## Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/survey/get/56f2c662ec71bc2c6b001040'
```

## Response

```
{
  "id": "56f2c662ec71bc2c6b001040",
  "survey": {
    "value": "any"
  },
  "timestamp": "2016-03-23T16:37:54.765000"
}
```

## POST /survey

Insert a new User's Survey.

## Resource Information

|                          |                   |
|--------------------------|-------------------|
| Method                   | POST              |
| URL                      | /api/v1.0/survey  |
| Requires authentication? | Yes               |
| Requires Role?           | Patient, Relative |
| Requires IC Accepted?    | Yes               |

## Request Parameters

| Parameter | Type        | Description   |
|-----------|-------------|---------------|
| survey    | (json file) | RAW JSON file |

## Response Parameters

| Parameter | Type   | Description  |
|-----------|--------|--|
| success   | (bool) | Return True if survey was accepted, False if JSON File is not well formatted |

## Resource Errors

These are the possible errors returned by this endpoint.

| status | code                   | message                                     |
|--------|------------------------|---|
| 403    | authorization_required | Authorization header is expected            |
| 401    | invalid_header         | Authorization header must start with Bearer |

| status | code              | message                                     |
|--------|-------------------|---|
| 401    | invalid_header    | Token not found                             |
| 401    | invalid_header    | Authorization header must be Bearer + token |
| 400    | token_expired     | Token is expired                            |
| 400    | invalid_audience  | Incorrect audience                          |
| 400    | invalid_signature | Token signature is invalid                  |
| 401    | unauthorized      | Insufficient Roles                          |
| 401    | unauthorized      | Consent Information not accepted            |

## Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
-X POST -d '{"value': 'any'}" \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/survey'
```

## Response

```
{
  "success": true
}
```