

MS Registry REST API Resources

Contents

Document Version	3
GET /auth/test	3
Resource Information	3
Resource Errors	3
Example	4
Response	4
GET /user	4
Resource Information	4
Response Parameters	4
Resource Errors	5
Example	5
Response	5
GET /user/consent/info	5
Resource Information	5
Response Parameters	5
Resource Errors	6
Example	6
Response	7
GET /user/consent	7
Resource Information	7
Response Parameters	7
Resource Errors	7
Example	8
Response	8
POST /user/consent	8
Resource Information	8
Request Parameters	8
Response Parameters	9
Resource Errors	9
Example	9
Response	10

GET /user/diary	10
Resource Information	10
Request Parameters	10
Response Parameters	10
Resource Errors	11
Example	11
Response	11
GET /user/diary/<id>	11
Resource Information	11
Request Parameters	12
Response Parameters	12
Resource Errors	12
Example	12
Response	13
POST /user/diary	13
Resource Information	13
Request Parameters	13
Response Parameters	13
Resource Errors	13
Example	14
Response	14
POST /user/diary/<id>	14
Resource Information	14
Request Parameters	14
Response Parameters	15
Resource Errors	15
Example	15
Response	15
GET /user/survey	15
Resource Information	15
Request Parameters	16
Response Parameters	16
Resource Errors	16
Example	17
Response	17
GET /user/survey/<id>	17
Resource Information	18
Request Parameters	18
Response Parameters	18
Resource Errors	18
Example	19
Response	19
POST /user/survey	19
Resource Information	19

Request Parameters	19
Response Parameters	19
Resource Errors	20
Example	20
Response	20
POST /user/survey/<id>	20
Resource Information	20
Request Parameters	21
Response Parameters	21
Resource Errors	21
Example	21
Response	22

Document Version

Date 2016-06-03

Version v0.5.0

Authors Filippo Panessa <filippo.panessa@gmail.com>

Copyright Copyright (c) 2016 S3IT, Zentrale Informatik, University of Zurich

Welcome to the MS Registry REST API. Below, you'll find a full listing of all the available endpoints. As we add more endpoints, they will be automatically documented here.

The endpoint's documentation section includes what query parameters the endpoint will accept, what the JSON object's parameters will be in the response, and an example query/response.

This documentation is for most recent version of the MS Registry REST API, version **v0.5.0**.

GET /auth/test

Test Bearer Token authentication.

Resource Information

Method	GET
URL	/auth/test
Requires authentication?	Yes
Requires Role?	Every Role can access

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/auth/test'
```

Response

```
{
  "code": "authorization_success",
  "description": "All good. You only get this message if you're authenticated."
}
```

GET /user

Get metadata about the current user.

Resource Information

Method	GET
URL	/api/v1.0/user
Requires authentication?	Yes
Requires Role?	Every Role can access

Response Parameters

Parameter	Type	Description
uniqueID	(string)	That's the unique ID of the user, received from OAuth server
member_since	(iso 8601 datetime)	Datetime the user joined
last_seen	(iso 8601 datetime)	Datetime last seen user. This field is updated on every user interaction

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid
404	not_found	Couldn't found a User with UniqueID={}

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user'
```

Response

```
{
  "uniqueID": "auth0|569cf82bfc02d8a0339beef4",
  "member_since": "2016-03-04T17:03:37",
  "last_seen": "2016-03-04T17:05:12"
}
```

GET /user/consent/info

Get detailed informations about user acceptance of Informed Consent.

Resource Information

Method	GET
URL	/api/v1.0/user/consent/info
Requires authentication?	Yes
Requires Role?	Patient, Relative

Response Parameters

Relative Role

Parameter	Type	Description
birthdate	(string)	Birthdate in this form %DD.%MM.%YYYY
sex	(string)	Sex. Possibly values are 'male' and 'female'
signature	(string)	Signature by Initials, max 3 digits

Patient Role

Parameter	Type	Description
birthdate	(string)	Birthdate in this form %DD.%MM.%YYYY
sex	(string)	Sex. Possibly values are 'male' and 'female'
signature	(string)	Signature by Initials, max 3 digits
physician_contact_permitted	(bool)	Physician contact permitted
data_exchange_cohort	(bool)	Data exchange cohort
medical_record_abstraction	(bool)	Medical record abstraction

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid
401	unauthorized	Insufficient Roles
404	not_found	Couldn't found a User with UniqueID={}

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/consent/info'
```

Response

```
{
  "birthdate": "18.09.1974",
  "sex": "M",
  "signature": "FP",
  "data_exchange_cohort": true,
  "date_signed": "2016-03-30T14:33:48.011000",
  "medical_record_abstraction": true,
  "data_exchange_cohort": true,
  "physician_contact_permitted": true
}
```

GET /user/consent

Get brief information about user acceptance of Informed Consent.

Resource Information

Method	GET
URL	/api/v1.0/user/consent
Requires authentication?	Yes
Requires Role?	Patient, Relative

Response Parameters

Parameter	Type	Description
accepted	(bool)	Return True if Consent Information was accepted, False otherwise

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid
401	unauthorized	Insufficient Roles

status	code	message
404	not_found	Couldn't found a User with UniqueID={}

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/consent'
```

Response

```
{
  "accepted": true
}
```

POST /user/consent

Set user acceptance of Informed Consent.

Resource Information

Method	POST
URL	/api/v1.0/user/consent
Requires authentication?	Yes
Requires Role?	Patient, Relative

Request Parameters

Relative Role

Parameter	Type	Description
birthdate	(string)	Birthdate in this form %DD.%MM.%YYYY
sex	(string)	Sex. Possibly values are 'male' and 'female'
signature	(string)	Signature by Initials, max 3 digits

Patient Role

Parameter	Type	Description
birthdate	(string)	Birthdate in this form %DD.%MM.%YYYY

Parameter	Type	Description
sex	(string)	Sex. Possibly values are 'male' and 'female'
signature	(string)	Signature by Initials, max 3 digits
physician_contact_permitted	(bool)	Physician contact permitted
data_exchange_cohort	(bool)	Data exchange cohort
medical_record_abstraction	(bool)	Medical record abstraction

Response Parameters

Parameter	Type	Description
success	(bool)	Return True if content was accepted and registered, False otherwise

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found
401	invalid_header	Authorization header must be Bearer + token
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid
401	unauthorized	Insufficient Roles
405	method_not_allowed	

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
-X POST -d '{"physician_contact_permitted": true, \
  "data_exchange_cohort": true, \
  "medical_record_abstraction": true, \
  "sex": "male", \
  "signature": "FP", \
  "birthdate": "18.09.1974"}' \
```

```
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/consent'
```

Response

```
{  
  "success": true  
}
```

GET /user/diary

Get All Diary entries compiled by User.

Resource Information

Method	GET
URL	/api/v1.0/user/diary
Requires authentication?	YES
Requires Role?	Patient, Relative

Request Parameters

Parameter	Type	Description
from	(iso 8601 datetime)	If used, query returns Diary entries starting from this datetime. It could be used in combination with <i>until</i> parameter
until	(iso 8601 datetime)	If used, query returns Diary entries starting from this datetime. It could be used in combination with <i>from</i> parameter

Response Parameters

Parameter	Type	Description
diaries	(array)	Return list of all Diaries compiled by User as JSON array
id	(string)	Return Diary ID
diary	(json object)	Return User's Diary. Returned value is a JSON object
timestamp	(iso 8601 datetime)	Datetime the diary was inserted or updated

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found
401	invalid_header	Authorization header must be Bearer + token
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid
401	unauthorized	Insufficient Roles

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/diary?from=2016-04-01T00:00:00.000000&until=2016-04-08T11:36:37.177000'
```

Response

```
{
  "diaries": [
    {
      "diary": {
        "value": "any"
      },
      "id": "5707ba42ec71bc038226c84b",
      "timestamp": "2016-04-08T11:36:37.177000"
    }
  ]
}
```

GET /user/diary/<id>

Get User's Diary by Diary ID.

Resource Information

Method	GET
URL	/api/v1.0/user/diary/<id>

Requires authentication? YES
Requires Role? Patient, Relative

Request Parameters

Parameter	Type	Description
id	(string)	Diary ID

Response Parameters

Parameter	Type	Description
id	(string)	Return Diary ID
diary	(json object)	Return user's Diary. Returned value is a JSON object
timestamp	(iso 8601 datetime)	Datetime the diary was inserted or updated

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found
401	invalid_header	Authorization header must be Bearer + token
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid
401	unauthorized	Insufficient Roles
404	not_found	Couldn't found a Diary with id={}

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/diary/56f2c662ec71bc2c6b001040'
```

Response

```
{
  "id": "5707ba42ec71bc038226c84b",
  "diary": {
    "value": "any"
  },
  "timestamp": "2016-04-08T11:36:37.177000"
}
```

POST /user/diary

Insert new User's Diary entry.

Resource Information

Method	POST
URL	/api/v1.0/user/diary
Requires authentication?	Yes
Requires Role?	Patient, Relative
Requires IC Accepted?	Yes

Request Parameters

Parameter	Type	Description
diary	(json object)	Any JSON object

Response Parameters

Parameter	Type	Description
success	(bool)	Return True if diary is accepted

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found

status	code	message
401	invalid_header	Authorization header must be Bearer + token
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid
401	unauthorized	Insufficient Roles
401	unauthorized	Consent Information not accepted
405	method_not_allowed	

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
-X POST -d '{"diary": {"any": "value"}}' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/diary'
```

Response

```
{
  "success": true
}
```

POST /user/diary/<id>

Update User's Diary by Diary ID.

Resource Information

Method	POST
URL	/api/v1.0/user/diary/<id>
Requires authentication?	YES
Requires Role?	Patient, Relative

Request Parameters

Parameter	Type	Description
id	(string)	Diary ID
diary	(json object)	Any JSON object

Response Parameters

Parameter	Type	Description
success	(bool)	Return True if diary is accepted

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found
401	invalid_header	Authorization header must be Bearer + token
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid
401	unauthorized	Insufficient Roles
404	not_found	Couldn't found a Diary with id={}

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
-X POST -d '{"diary": {"any": "value"}}' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/diary/56f2c662ec71bc2c6b001040'
```

Response

```
{
  "success": true
}
```

GET /user/survey

Get All Survey entries compiled by User.

Resource Information

Method

GET

URL	/api/v1.0/user/survey
Requires authentication?	YES
Requires Role?	Patient, Relative

Request Parameters

Parameter	Type	Description
from	(iso 8601 datetime)	If used, query returns Survey entries starting from this datetime. It could be used in combination with <i>until</i> , <i>tags</i> and <i>ongoing</i> parameters
until	(iso 8601 datetime)	If used, query returns Survey entries starting from this datetime. It could be used in combination with <i>from</i> , <i>tags</i> and <i>ongoing</i> parameters
tags	(array)	If used, query returns all entries with declared TAGs. It could be used in combination with <i>from</i> , <i>until</i> and <i>ongoing</i> parameters
ongoing	(bool)	If used, query returns all entries with ongoing value requested. It could be used in combination with <i>from</i> , <i>until</i> and <i>tags</i> parameters

Response Parameters

Parameter	Type	Description
surveys	(array)	Return list of all Surveys compiled by User as JSON array
id	(string)	Return Survey ID
survey	(json object)	Return User's Survey. Returned value is a JSON object
timestamp	(iso 8601 datetime)	Datetime the survey was inserted
tags	(array)	Return list of all TAGs assigned to a Survey entry
ongoing	(bool)	Ongoing value is a boolean flag that refer to completed Surveys

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected

status	code	message
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found
401	invalid_header	Authorization header must be Bearer + token
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid
401	unauthorized	Insufficient Roles

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/survey?from=2016-03-01T00:00:00.000000&until=2016-03-12T17:01:57.800000'
```

Response

```
{
  "surveys": [
    {
      "id": "56f2c662ec71bc2c6b001040",
      "survey": {
        "value": "any"
      },
      "tags": ["layer2", "other_tag"],
      "ongoing": true,
      "timestamp": "2016-03-03T16:37:54.765000"
    },
    {
      "id": "56f2c7cdec71bc2c6b001041",
      "survey": {
        "value": "any"
      },
      "tags": ["layer3"],
      "ongoing": false,
      "timestamp": "2016-03-12T17:01:57.800000"
    }
  ]
}
```

GET /user/survey/<id>

Get User's Survey by Survey ID.

Resource Information

Method	GET
URL	/api/v1.0/user/survey/<id>
Requires authentication?	YES
Requires Role?	Patient, Relative

Request Parameters

Parameter	Type	Description
id	(string)	Survey ID

Response Parameters

Parameter	Type	Description
id	(string)	Return Survey ID
survey	(json object)	Return user's Survey. Returned value is a JSON object
timestamp	(iso 8601 datetime)	Datetime the survey was inserted or updated
tags	(array)	Return list of all TAGs assigned to a Survey entry
ongoing	(bool)	Ongoing value is a boolean flag that refer to completed Surveys

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found
401	invalid_header	Authorization header must be Bearer + token
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid
401	unauthorized	Insufficient Roles
404	not_found	Couldn't found a Survey with id={}

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/survey/56f2c662ec71bc2c6b001040'
```

Response

```
{
  "id": "56f2c662ec71bc2c6b001040",
  "survey": {
    "value": "any"
  },
  "tags": ["layer2", "other_tag"],
  "ongoing": false,
  "timestamp": "2016-03-23T16:37:54.765000"
}
```

POST /user/survey

Insert a new User's Survey.

Resource Information

Method	POST
URL	/api/v1.0/user/survey
Requires authentication?	Yes
Requires Role?	Patient, Relative
Requires IC Accepted?	Yes

Request Parameters

Parameter	Type	Description
survey	(json object)	Any JSON object
tags	(array)	List of all TAGs assigned to this Survey entry. It cannot be null
ongoing	(bool)	Ongoing value is a boolean flag that refer to completed Surveys. It cannot be null

Response Parameters

Parameter	Type	Description
success	(bool)	Return True if Survey is accepted

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found
401	invalid_header	Authorization header must be Bearer + token
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid
401	unauthorized	Insufficient Roles
401	unauthorized	Consent Information not accepted
405	method_not_allowed	

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
-X POST -d '{"survey": {"value": "any"}, "tags": ["layer2"], "ongoing": true}' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/survey'
```

Response

```
{
  "success": true
}
```

POST /user/survey/<id>

Update User's Survey by Survey ID.

Resource Information

Method	POST
URL	/api/v1.0/user/survey/<id>

Requires authentication? YES
Requires Role? Patient, Relative

Request Parameters

Parameter	Type	Description
id	(string)	Survey ID
survey	(json object)	Any JSON object
tags	(array)	List of all TAGs assigned to this Survey entry. If null, TAGs are not updated
ongoing	(bool)	Ongoing value is a boolean flag that refer to completed Surveys. It cannot be null

Response Parameters

Parameter	Type	Description
success	(bool)	Return True if Survey is accepted

Resource Errors

These are the possible errors returned by this endpoint.

status	code	message
403	authorization_required	Authorization header is expected
401	invalid_header	Authorization header must start with Bearer
401	invalid_header	Token not found
401	invalid_header	Authorization header must be Bearer + token
400	token_expired	Token is expired
400	invalid_audience	Incorrect audience
400	invalid_signature	Token signature is invalid
401	unauthorized	Insufficient Roles
404	not_found	Couldn't found a Survey with id={}

Example

```
curl \
-H 'authorization: Bearer YOUR_API_TOKEN' \
-X POST -d '{"survey": {"value": "any"}, "tags": ["layer2", "othertag"], "ongoing": true}' \
'https://ws.msregistry.s3it.uzh.ch/api/v1.0/user/survey/56f2c662ec71bc2c6b001040'
```

Response

```
{  
  "success": true  
}
```