Sapienza University of Rome

Cybersecurity
PhD in Cybersecurity

Ethical hacking

Thesis Advisor
Prof. XXX XXX

Candidate
Name
matricola

Academic Year MMXIX-MMXXII (XXXV cycle)

Contents

1 Casing the Establishment **1**
1.1 Hackers tools . . . 1
1.1.1 *Tor* . . . 1
1.1.2 Vidalia . . . 2
1.1.3 Privoxy . . . 2
1.2 Footprinting . . . 2
1.2.1 publicly available information . . . 2
1.2.2 Public Database Security Countermeasures . . . 3

2 Scanning **4**
2.1 Objectives . . . 4
2.2 Determining if the system is alive . . . 4
2.2.1 same subnet . . . 4
2.2.2 remote host/router . . . 4

Bibliography **5**

Chapter 1

Casing the Establishment

1.1 Hackers tools

It's All About Anonymity, Stupid (IAAAS)

Hackers use a wide variety of tools:

- *The Onion Router (Tor)*, wich uses Layered cryptography with SOCKS proxy and Anonymous outgoing TCP connections
- Tor GUI client (Vidalia) and Privoxy (web filtering proxy)
- Google on browser for juicy targets
- tor-resolve instead of host for IP addresses
- proxychains to force connections through Tor and Nmap to scan service on targets
- socat to relay persistently, netcat to send requests to servers

1.1.1 *Tor*

How it works:

1. Alice *Tor* client obtain a list of *Tor* nodes from a directory server
2. Alice *Tor* client picks a random path trough the nodes to the destination, using encrypted links



Figure 1.1: first step



Figure 1.2: second step

1.1.2 Vidalia

Vidalia is a discontinued cross-platform GUI for controlling Tor. It allows the user to start, stop or view the status of Tor

1.1.3 Privoxy

Privoxy is a free web proxy for enhancing privacy, manipulating cookies and modifying web page data and HTTP headers before the page is rendered by the browser. E.g. filtering web pages and removing advertisements. Privoxy can be customized by users.

1.2 Footprinting

What is footprinting? its the profiling of the target organization. It has to be done to give a picture of what the hacker can see. It has to be done regularly to minimize info leaks and implement monitoring

The profiling comprehend:

- Internet: domain names, network blocks and subnets, IP, TCP/UDP services, access controll, IDS, DNS hostnames, CPU arch, system enumeration
- intranet: network protocols, intranet domain names, network blocks, IP, TCP/UDP services
- Remote access: phone numbers, remote system type, VPN, authentication mechanism
- Extranet: domain names, connection source and destination, access control, type of connection

Profiling steps:

1. Determine the scope of the activities
2. get proper authorization trough politics and founding
3. use publicly available information
4. WHOIS and DNS enumeration: Domain names, IP addresses, port numbers
5. DNS interrogation: obtain info about the organization by querying DNS server, DNS zone transfer by untrusted users. Use nslookup to map all resource records. Search with grep,sed,awk,perl
6. network reconnaissance: topology and access path diagram using traceroute, tracert, visualroute, McAfee's NeoTrace, Foundstone's Trout, Owasp AMASS

1.2.1 publicly available information

There are a lot of information on the internet that we can use:

- HTML source code: using website mirroring tool for offline viewing, and reading things inside comment tags
- Enumerate hidden files and directories

- remote access to internal resources via browser: proxy to internal service
- looking for other website other than the main (web, test, VPN sites)
- related organization, to do a social engeneering attack or, in outsourced web developement, partners might not be as secure
- location details such as images or geolocalization: needed for surveillance, social engeneering, unauthorized access
- names: usernames, e-mail addresses
- phone number, phisical addresses
- employees personal details: home phone number, address, social security number, credit history, family ancestry, photos
- busness directory services
- job posting and resumes, ex employees
- employee home computers, for remote access to target, keystroke logger to see the passwords
- company history: mergers, acquisitions, scandals, layoff, hiring, reorganization, outsourcing, temorary contractors, business info, stock market sites
- privacy and security policies
- archived information

1.2.2 Public Database Security Countermeasures

A lot of countermeasures can be taken to minimize the leakage of data:

- keeping administrative contacts up to date
- anonymize administrative contacts
- authenticate updates rigidly
- restrict zone transfer to only authorized servers
- Configure a firewall to deny unauthorized connection to TCP port 53
- configure not to provide internal DNS info
- discourage the use of HINFO records
- use intrusion detection: snort,bro
- Configure border routers to limit ICMP and UDP traffic to specific systems

Chapter 2

Scanning

2.1 Objectives

1. determining if the system is alive
2. determining witch service are running or listening
3. detecting operating system
4. Processing and storing data

2.2 Determining if the system is alive

2.2.1 same subnet

Using ping sweeps: we can use ARP-SCAN, Nmap, Cain

NMAP sends an ICMP ECHO request and ARP ping and TCP ping. If the target network is monitored by in IDS you could trigger an alert for the extra traffic generated

2.2.2 remote host/router

ICMP ECHO REQUEST, ICMP ECHO REPLY,ICMP TIMESTAMP,ICMP ADDRESS MASK
Ping: OS utilities for ECHO RREQUEST/REPLY

Bibliography

[]