

Specifications

Product Model	MC200CM v4.30	MC210CS v6.20	MC220L v4.30	MC100CM v6.20	MC110CS v7.20	MC111CS v7.20	MC112CS v7.20
Product Picture							
Standards	IEEE 802.3, IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x			IEEE 802.3, IEEE 802.3i, IEEE 802.3u			
Interface	2 1000Mbps SC/UPC ports 1 10/100/1000Mbps RJ45 port		1 SFP port 1 10/100/1000Mbps RJ45 port	2 100Mbps SC/UPC ports 1 10/100Mbps RJ45 port		1 100Mbps SC/UPC port 1 10/100Mbps RJ45 port	
Transmission Distance	0.55km (50/125um), 0.22km (62.5/125um)	20km	Depends on the inserting SFP module	2km	20km		
Transmission Media	Multi-mode Fiber, TP	Single-mode Fiber, TP	Multi/Single-mode Fiber, TP	Multi-mode Fiber, TP	Single-mode Fiber, TP		
Wave Length	850nm	1310nm	Depend on used SFP module	1310nm		1550nmTX 1310nmRX	1310nmTX 1550nmRX
Dimensions (W × D × H)	3.7 × 2.9 × 1.1 in. (94.5 × 73.0 × 27.0 mm)						
Environment	Operating Temperature: 0°C to 50°C (32°F to 122°F) Storage Temperature: -40°C to 70°C (-40°F to 158°F) Operating Humidity: 10% to 90% non-condensing Storage Humidity: 5% to 90% non-condensing						
Power Supply	9V/0.6A						
Max Power Consumption	1.59W	2.04W	1.78W	1.19W	1.1W	1.33W	1.23W
Certifications	CE, FCC						