


KSZ9477 EVB/Demo Board with Atmel SAMA5D3 SoC

Table of Contents	
Sheet	Description
1	Block Diagram
2	Power Regulation
3	Power Connections - Switch and SoC
4	KSZ9477S Switch and RGMII
5	Ethernet Port Connectors
6	SoC Main - Flash, SD card, USB
7	SDRAM
8	GPIO and LCD Connectors

Revision History			
Revision	Date	Revision Summary	Author
A00	6/23/2016	Pre-release	Kelly Maas
B	12/15/2016	Release	Kelly Maas
B1	3/9/2017	Update KSZ9477 SGMII pin names, update notes	Kelly Maas

Block Diagram



A

B

C



D

A


B

C


D




2.5V / 1A
Requirement: 0.4A




3.3V / 6A
Requirement: 2A




















1.8V / 1A
Requirement: 0.2A



1.2V / 3A
Requirement: 1.6A







RGMII layout requirements


1. Match trace lengths within 10 to 100 mils.
2. RX signals do not need to be length match to TX signals.
3. Due to RGMII timing error in port 6 of KSZ9477, plus SAMA5D36 compliance to RGMII v1.3, GTXCK must be routed for additional 2.5ns delay relative to GTXCTL.

To replace Xtal with DSC1101 oscillator, remove R11 and R126, and install R12.


KSZ9477S Configuration Strap Options		
	Open	Closed
GRXD0	RGMII: 1000 Mb/s	RGMII: 100 Mb/s
LED2_0	1000B-T master or 10/100 MDI	1000B-T slave or 10/100 MDI-X
LED4_0	Enable AN or 100B-TX	Disable AN or 1000B-T
LED1_0	Quiet-WIRE off	Quiet-WIRE on
LED1_1	Flow control on	Flow control off
LED2_1	Normal link up	Fast link up
LED4_1	SPI	I2C
LED5_1	Start switch	Don't start switch
IBA	IBA off	IBA enabled
No option: LED3_1 RXD6_3:2 RXD6_1 SYNCKO		
No option for MDC/MDIO Port 6 fixed as RGMII Not relevant when port is RGMII S_REFCLKP/M input clock not used		

KSZ9477 Configuration Strap Options


KSZ9477 Output Header




Jitter Blocker




SPI Activity LED



SPI / I2C Aardvark





MCU SPI




Install all 4 jumpers at J19 for MCU to control KSZ9477 via SPI.
Remove all jumpers at J19 when connecting external SPI or I2C controller to header J18.

KSZ9477 Reset 200ms delay








JTAG



SERIAL COMM





SAMA5D36 is not currently using pins 1 and 5 of J10



Reset / 200ms delay


NAND FLASH



SD CARD

Preferred location is bottom side of board

DDR2 SDRAM



Keep nets as short as possible. Therefore DDR2 devices have to be placed as close as possible to SAMA5D3. The layout EBI DDR2 should use controlled impedance traces of Z0= 50ohm.

Address, control and data traces may not exceed 1.3 inches (33mm).
Address, control and data traces must be length matched to within 0.1 inch (2.54mm).
Address, control and data traces must match the data group trace lengths to within 0.25 inch (6.35mm).

