AN5513

Getting Started with KSZ9897

Authors: Prescott Sakai and Randall Hoskin Microchip Technology Inc.

1.0 INTRODUCTION

This document is intended to provide a customer with all the essential information needed to select the correct Ethernet switch within the KSZ Gigabit Ethernet switch family and to quickly start designing both hardware (HW) and software (SW) for the KSZ9897 7-Port Gigabit Ethernet Switch. The KSZ family of Gigabit Ethernet Switches is popular and enables a non-blocking switching fabric with many advanced features. It can be used as a standard switch without requiring a processor. Alternatively, it can also be run in Managed mode to enable key features and set up the switch.

1.1 Sections

This document covers the following sections:

- · Section 2.0, "Product and Family Overview"
- · Section 3.0, "Switch Configuration Options"
- Section 4.0, "Software Guide"
- · Section 5.0, "Hardware and EVB Guide"
- · Section 6.0, "The Microchip Knowledge Base"
- · Section 7.0, "Documentation"

1.2 References

Related documentation is covered in Section 7.0, "Documentation". The latest KSZ9897 documentation is available on the KSZ9897 product page. Additionally, the EVB code referenced in this document is available from a GitHub link on the Microchip Ethernet page.

2.0 PRODUCT AND FAMILY OVERVIEW

The KSZ9897 belongs to a family of devices with various configurations and features enabled. Table 1 describes this family of devices. The KSZ9897 device is a subset of and closely related to the KSZ9477, with some documentation and collateral shared between the two.

TABLE 1: I²C/SMBUS INTERFACE PIN STRAPPING TRUTH TABLE

| Feature | KSZ9893R | KSZ9563 | KSZ9567 | KSZ9896 | KSZ9897S | KSZ9897R | KSZ9477 |
|---|------------------------------------|-------------------------|----------------------------------|-------------------------------|----------------------------------|-------------------------|----------------------------------|
| Bandwidth | 10Base-T / 100Base-TX / 1000Base-T | | | | | | |
| Ports | 3 | 3 | 7 | 6 | 7 | 7 | 7 |
| Interfaces | 1xRGMII/ MII/RMII | 1xRGMII/ MII/RMII | 1xSGMII, 1xRGMII/ MII/RMII | 1xGMII/ RGMII/MII/ RMII | 1xSGMII, 1xRGMII/ MII/RMII | 2xRGMII/ MII/RMII | 1xSGMII, 1xRGMII/ MII/RMII |
| Integrated 10/100/1000 BASE-T PHYs | 2x | 2x | 5x | 5x | 5x | 5x | 5x |
| VLAN IDs | 4K | | | | | | |
| QoS | 4 queues | | | | | | |
| IEEE 1588v2/ 802.1AS | | X | X | | | | Х |
| AVB | | | | | | | Х |
| Network Fault Recovery (DLR/ HSR) | | | | | | | Х |
| Energy Efficient Ethernet | Х | Х | | Х | | | |
| Temperature Range | 0 to 70C, -40 to 85C | 0 to 70C, -40 to 85C | -40 to 85C | 0 to 70C, -40 to 85C | 0 to 70C, -40 to 85C | 0 to 70C, -40 to 85C | -40 to 85C |
| Package | 64 Pin VQFN | 64 Pin VQFN | 128 Pin TQFP | 128 Pin TQFP | 128 Pin TQFP | 128 Pin TQFP | 128 Pin TQFP |
| Package Dimension | 8x8 mm | 8x8 mm | 14x14 mm | 14x14 mm | 14x14 mm | 14x14 mm | 14x14 mm |

3.0 SWITCH CONFIGURATION OPTIONS

The KSZ family of switches provides various methods for configuring and operating the switch. The method used will be determined by the required features and system availability. There are trade-offs and limitations to each method, and certain features can only be enabled via certain methods. The four main operation modes are:

- · Pin-Strapping
- Serial Interface Configuration: I²C, SPI, MIIM
- · Ethernet In-Band Access (IBA) Configuration
- Host Processor Configuration

Additional information can be found in AN2577 Getting Started with Gigabit Ethernet Switch Configuration Options.

4.0 SOFTWARE GUIDE

4.1 Linux[®] DSA

The KSZ9897 Linux[®] DSA driver is found in the Linux Kernel. Microchip[®] is continuously adding updates and features, along with the community. The latest kernel source can be found at https://github.com/torvalds/linux/tags with the latest formatted documentation at https://www.kernel.org/doc/html/latest/.

4.2 SPI Microchip® Driver

This driver is hosted on Microchip's GitHub and currently supports the Linux 6.6 kernel. Begin by selecting your needed kernel version from https://github.com/Microchip-Ethernet/EVB-KSZ9477/tree/master/KSZ/linux-drivers/ksz9897 and follow the instructions in the linux-M.m/doc/README file.

Development of this driver began before Linux DSA reached maturity and still offers some capabilities beyond what is currently supported by Linux DSA.

Given that the KSZ9477 is a superset of the KSZ9897, many of the Microchip's drivers and evaluation products use the KSZ9477 instead of the KSZ9897.

5.0 HARDWARE AND EVB GUIDE

5.1 EVB-KSZ9897-1

An Unmanaged Mode Evaluation Board that is connected via a USB to Ethernet Bridge. The switch configuration is done through a Linux-based GUI or command-line tooling.

Visit the EVB-KSZ9897-1 product page to access the latest collateral, including:

- · EVB-KSZ9897 Gigabit Ethernet Switch Evaluation Board User's Guide
- EVB-KSZ9897 Software User Guide, Software Image ISO, and Source Code
- · EVB-KSZ9897 Evaluation Board Bill of Materials
- EVB-KSZ9897 Evaluation Board Schematics (PDF)
- EVB-KSZ9897 Evaluation Board Gerber Files
- EVB-KSZ9897 Evaluation Board Design Files (Altium)

5.2 EVB-KSZ9477-1

A Managed Mode Evaluation Board comes with a pre-programmed NAND flash that contains a Linux image. This image provides tools that can be used to exercise the board. Additionally, <u>you can customize the image by building a custom kernel and either downloading it to the NAND flash or booting it through the microSD card slot located on the bottom of the PCB.</u>

Visit the EVB-KSZ9477-1 product page to access the latest collateral, including:

- · EVB-KSZ9477 Gigabit Ethernet Switch Evaluation Board User's Guide
- EVB-KSZ9477 Demo Images, Image Programming Guides, and Image Source Code
- EVB-KSZ9477 Software Setup Guide
- EVB-KSZ9477 Source Build Instructions
- EVB-KSZ9xxx Switch Driver Setup Guide
- EVB-KSZ9477 Evaluation Board Bill of Materials
- EVB-KSZ9477 Evaluation Board Schematics (PDF)
- EVB-KSZ9477 Evaluation Board Gerber Files
- EVB-KSZ9477 Evaluation Board Design Files (Altium)
- · KSZ Switch Utilities User Guide

5.2.1 USING THE KSZ9477 TO EVALUATE THE KSZ9897

The KSZ9897 device is a subset of and closely related to the KSZ9477, with the main difference being the additional support for PTP (IEEE[®]1588), AVB, and DLR/HSR in the KSZ9477. The KSZ9897S contains the same SGMII port as the KSZ9477 however, the KSZ9897R has a second RGMII port.

5.2.2 USING LINUX® DSA ON EVB-KSZ9477

The EVB-KSZ9477 can also be customized to run via the Linux DSA driver in a choice of Microchip provided Linux kernel versions. Here are the relevant KB articles:

- EVB-KSZ9477: How to Use the Linux DSA Driver
- Building different Linux Kernel Version for SAMA5D3-EDS and EVB-KSZ9477

6.0 THE MICROCHIP KNOWLEDGE BASE

Most support collateral for the KSZ9897 can be found on the KSZ9897 product page on the Microchip website. This includes links to Evaluation Board (EVB), application notes, files, and ordering information through Microchip Direct.

There are other resources available through the Microchip Knowledge Base (KB). This database is searchable for pertinent information. For example, here are some relevant KB articles:

- · An Overview of Linux Drivers for KSZ Switch Families
- EVB-KSZ9477: How to Use the Linux DSA Driver
- Unused Ports on the KSZ9897, 9896, 9567, 9477, 8567 and 8565

7.0 DOCUMENTATION

The KSZ9897 product page includes links to many documentation resources, as shown in Table 2.

TABLE 2: KSZ9897 DOCUMENTATION

| Category | Resource | Notes | |
|--|--|--|--|
| Data Sheet and Errata | KSZ9897R 7-Port Gigabit Ethernet Switch with Two RGMII/MII/RMIII Interfaces | Core device data sheet - includes the device register map | |
| | KSZ9897S 7-Port Gigabit Ethernet Switch with SGMII and RGMII/MII/ RMII Interface | Core device data sheet - includes the device register map | |
| | KSZ9897S Silicon Errata and Data Sheet Clarification | The errata document should be consulted by end system integrators to ensure the end application is not affected by device errata and follows necessary mitigation or workarounds. | |
| | KSZ9897R Silicon Errata and Data Sheet Clarification | The errata document should be consulted by end system integrators to ensure that the end application is not affected by device errata and follows necessary mitigation or workarounds. | |
| Schematic and PCB Design Guidelines | KSZ989x/KSZ956x/KSZ9477 Hard- ware Design Checklist | KSZ9897 schematic design requirements in a simple format | |
| | Gigabit Ethernet Guide | Generalized system design guidance (schematic level and layout level) for Microchip Gigabit Ethernet applications | |
| Modeling | KSZ9897R IBIS | KSZ9897R IBIS Model for SI (signal integrity) and timing simulation of the RGMII/MII/RMII interfaces | |
| | KSZ9897S IBIS | KSZ9897S IBIS Model for SI (signal integrity) and timing simulation of the RGMII/MII/RMII interfaces | |

TABLE 2: KSZ9897 DOCUMENTATION (CONTINUED)

| Category | Resource | Notes | |
|-------------------|--|--|--|
| Application Notes | Ethernet Theory of Operation | A basic introduction to Ethernet. | |
| | Getting Started with Gigabit Ethernet Switch Configuration Options | A comparison of the switch management methods and which features are supported with each. | |
| | Interfacing the SGMII Port on KSZ9xx7S and KSZ8567S Switches | Introduction to SGMII (Serial Gigabit media independent interface). | |
| | Ethernet Compliance Testing for 10BASE-T, 100BASE-TX, and 1000BASE-T | Overview of the Ethernet compliance tests, including instructions on how to run the tests and interpret the results. | |
| | Ethernet over Plastic Optical Fibre | Introduction to Plastic Optical Fibre with implementation guidance. | |
| | Capacitive Coupling Ethernet Transceivers without Using Transformers | Guidance on how to implement a system without the use of transformers, which can save system costs and minimize the physical PCB size. | |
| | Management Interfaces for Micrel Switches | Discussion on numerous switch management methods, both <i>in-band</i> (i.e., through ethernet) and <i>out-of-band</i> (i.e.,through inter-chip interface). | |
| | | Note : Micrel was acquired by Microchip Technology in 2015. | |
| | 1000BASE-T Transmitter Distortion | Deep dive discussion on IEEE 802.3-2008 transmitter distortion specification and analysis of Microchip Ethernet PHY distortion test results. | |
| | Transient Protection in Power Over Ethernet Applications | Guidance on how to implement PoE and properly protect the system components from PoE-related voltage transients. | |

APPENDIX A: APPLICATION NOTE REVISION HISTORY

TABLE A-1: REVISION HISTORY

| Revision Level & Date | Section/Figure/Entry | Correction |
|---------------------------|----------------------|-----------------|
| DS00005513A (07-31-24) | All | Initial release |

THE MICROCHIP WEBSITE

Microchip provides online support via our WWW site at www.microchip.com. This website is used as a means to make files and information easily available to customers. Accessible by using your favorite Internet browser, the website contains the following information:

- Product Support Data sheets and errata, application notes and sample programs, design resources, user's
 guides and hardware support documents, latest software releases and archived software
- General Technical Support Frequently Asked Questions (FAQ), technical support requests, online discussion groups, Microchip consultant program member listing
- Business of Microchip Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

CUSTOMER CHANGE NOTIFICATION SERVICE

Microchip's customer notification service helps keep customers current on Microchip products. Subscribers will receive e-mail notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, access the Microchip website at www.microchip.com. Under "Support", click on "Customer Change Notification" and follow the registration instructions.

CUSTOMER SUPPORT

Users of Microchip products can receive assistance through several channels:

- · Distributor or Representative
- · Local Sales Office
- Field Application Engineer (FAE)
- Technical Support

Customers should contact their distributor, representative or Field Application Engineer (FAE) for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in the back of this document.

Technical support is available through the website at: http://microchip.com/support

Note the following details of the code protection feature on Microchip products:

- · Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not
 mean that we are guaranteeing the product is "unbreakable" Code protection is constantly evolving. Microchip is committed to
 continuously improving the code protection features of our products.

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at https://www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Kleer, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet-Wire, SmartFusion, SyncWorld, TimeCesium, TimeHub, TimePictra, TimeProvider, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, Anyln, AnyOut, Augmented Switching, BlueSky, BodyCom, Clockstudio, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, EyeOpen, GridTime, IdealBridge, IGaT, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, IntelliMOS, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, MarginLink, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, mSiC, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, Power MOS IV, Power MOS 7, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQI, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, Trusted Time, TSHARC, Turing, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, and Symmcom are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies. © 2024, Microchip Technology Incorporated and its subsidiaries.

All Rights Reserved.

ISBN: 978-1-6683-0052-7

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.



Worldwide Sales and Service

AMERICAS

Corporate Office 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200

Tel: 480-792-7200 Fax: 480-792-7277 Technical Support:

http://www.microchip.com/ support

Web Address: www.microchip.com

Atlanta Duluth, GA

Tel: 678-957-9614 Fax: 678-957-1455

Austin, TX Tel: 512-257-3370

Boston

Westborough, MA Tel: 774-760-0087 Fax: 774-760-0088

Chicago Itasca, IL

Tel: 630-285-0071 Fax: 630-285-0075

Dallas

Addison, TX Tel: 972-818-7423 Fax: 972-818-2924

Detroit Novi, MI

Tel: 248-848-4000

Houston, TX

Tel: 281-894-5983 Indianapolis

Noblesville, IN Tel: 317-773-8323 Fax: 317-773-5453 Tel: 317-536-2380

Los Angeles

Mission Viejo, CA Tel: 949-462-9523 Fax: 949-462-9608 Tel: 951-273-7800

Raleigh, NC Tel: 919-844-7510

New York, NY Tel: 631-435-6000

San Jose, CA Tel: 408-735-9110 Tel: 408-436-4270

Canada - Toronto Tel: 905-695-1980 Fax: 905-695-2078

ASIA/PACIFIC

Australia - Sydney Tel: 61-2-9868-6733

China - Beijing Tel: 86-10-8569-7000

China - Chengdu Tel: 86-28-8665-5511

China - Chongqing Tel: 86-23-8980-9588

China - Dongguan Tel: 86-769-8702-9880

China - Guangzhou Tel: 86-20-8755-8029

China - Hangzhou Tel: 86-571-8792-8115

China - Hong Kong SAR Tel: 852-2943-5100

China - Nanjing Tel: 86-25-8473-2460

China - Qingdao Tel: 86-532-8502-7355

China - Shanghai Tel: 86-21-3326-8000

China - Shenyang Tel: 86-24-2334-2829

China - Shenzhen Tel: 86-755-8864-2200

China - Suzhou Tel: 86-186-6233-1526

China - Wuhan

Tel: 86-27-5980-5300 **China - Xian** Tel: 86-29-8833-7252

China - Xiamen
Tel: 86-592-2388138

China - Zhuhai Tel: 86-756-3210040

ASIA/PACIFIC

India - Bangalore Tel: 91-80-3090-4444

India - New Delhi Tel: 91-11-4160-8631

India - Pune Tel: 91-20-4121-0141

Japan - Osaka Tel: 81-6-6152-7160

Japan - Tokyo

Tel: 81-3-6880- 3770 Korea - Daegu

Tel: 82-53-744-4301

Korea - Seoul Tel: 82-2-554-7200

Malaysia - Kuala Lumpur Tel: 60-3-7651-7906

Malaysia - Penang Tel: 60-4-227-8870

Philippines - Manila Tel: 63-2-634-9065

Singapore Tel: 65-6334-8870

Taiwan - Hsin Chu Tel: 886-3-577-8366

Taiwan - Kaohsiung Tel: 886-7-213-7830

Taiwan - Taipei Tel: 886-2-2508-8600

Thailand - Bangkok Tel: 66-2-694-1351

Vietnam - Ho Chi Minh Tel: 84-28-5448-2100

EUROPE

Austria - Wels Tel: 43-7242-2244-39 Fax: 43-7242-2244-393

Denmark - Copenhagen Tel: 45-4485-5910

Fax: 45-4485-2829 Finland - Espoo Tel: 358-9-4520-820

France - Paris
Tel: 33-1-69-53-63-20

Fax: 33-1-69-30-90-79 **Germany - Garching**

Tel: 49-8931-9700 **Germany - Haan** Tel: 49-2129-3766400

Germany - Heilbronn Tel: 49-7131-72400

Germany - Karlsruhe Tel: 49-721-625370

Germany - Munich Tel: 49-89-627-144-0 Fax: 49-89-627-144-44

Germany - Rosenheim Tel: 49-8031-354-560

Israel - Hod Hasharon Tel: 972-9-775-5100

Italy - Milan Tel: 39-0331-742611

Fax: 39-0331-466781

Tel: 39-049-7625286

Netherlands - Drunen
Tel: 31-416-690399
Fax: 31-416-690340

Norway - Trondheim Tel: 47-7288-4388

Poland - Warsaw Tel: 48-22-3325737

Romania - Bucharest Tel: 40-21-407-87-50

Spain - Madrid Tel: 34-91-708-08-90 Fax: 34-91-708-08-91

Sweden - Gothenberg Tel: 46-31-704-60-40

Sweden - Stockholm Tel: 46-8-5090-4654

UK - Wokingham Tel: 44-118-921-5800 Fax: 44-118-921-5820