# Block diagram of VSC7512/VSC8514 unmanaged 8+2 port switch




## Table of contents



## Revision history

| Version: | Date: | Author: | Main change(s): |
|---|---|---|---|
| 01-00 | 2015-11-03 | MAG | First release |
| 01-01 | 2016-02-10 | MAG | Swapped R1/R8 (2V5 LDO) |
| 01-02 | 2016-02-12 | MAG | J10,C149,C150,C151,C155,C165,C166,C167,C168 mounted (was not mounted) |
| 01-03 | 2016-04-14 | MAG | Changes to U10 3V3/RESET, swap U4 S4 Rx polarity |
| 01-04 | 2016-04-20 | MAG | Swapped RD/GR labels on LTST-S326 (LED) inputs etc. |
| 01-05 | 2016-05-24 | MAG | Added R87/R88, added R92 |
| 02-00 | 2016-08-11 | MAG | Changed VSC7512 reference clock input circuit |

## Front layout





Hoerkaer 16
DK-2730 Herlev
Denmark

MAG


Microsemi

Company Confidential

| | | |
|---|---|---|
| Title: Block diagram | | |
| Size: A | Document Number: PCB121 | Rev: 02-00 |
| Date: Thursday, August 11, 2016 | Sheet 1 of 6 | |

## 2.5mm center pin DC jack for external PSU




## Reset generator




## VSC8514 power/decoupling




## 3V3 generation

Nominal output voltage = (0.925V/1K82)*(1K82+4K7) = 3.31V
Calculated current consumption on 3V3 = 2.2A




Place feedback components close to pin 5
Sense at SFPs through 0R resistor for separate trace

## VSC7512 power/decoupling




## Digital supplies




## Filtered analog supplies




## 2V5 generation




Nominal output voltage =
(0.8V/4K7)*(10K+4K7) = 2.50V
Ambient temperature = 50*C,
current = 1.1A, Theta-JA = 40*C/W
=> junction temperature = 85*C

## 1V0 generation

Nominal output voltage = (0.925V/10K)*(1K+10K) = 1.02V
Calculated current consumption on 1V0 = 3.0A




Place feedback components close to pin 5
Sense at VSC8514 through 0R resistor for separate trace

## Digital supplies




## Filtered analog supplies




## Power ON indicator




## Silkscreen

H5 Ser_no_Box No:
H6 ECO_Box ECO:

## Mounting holes




## Impedance test traces





Hoerkaer 16
DK-2730 Herlev
Denmark
MAG


Microsemi

Company Confidential

| | | |
|---|---|---|
| Title | Power inlet, voltage conversion, VSCxxxx power/decoup, reset | |
| Size A3 | Document Number PCB121 | Rev 02-00 |
| Date: Thursday, August 11, 2016 | Sheet 2 of 6 | |




## VSC7512 GPIO

### VSC7512 GPIO alternate functions

| GPIO # | ALT "10" | ALT "11" |
|---|---|---|
| 0 | | |
| 1 | | |
| 2 | | |
| 3 | | |
| 4 | IRQ0_OUT | TWI_SCL_MUX13 |
| 5 | IRQ1_OUT | PCI_Wake |
| 6 | TWI_SCL_MUX0 | |
| 7 | TWI_SCL_MUX1 | |
| 8 | TWI_SCL_MUX2 | IRQ0_OUT |
| 9 | TWI_SCL_MUX3 | IRQ1_OUT |
| 10 | TWI_SCL_MUX4 | SFP0_SD |
| 11 | TWI_SCL_MUX5 | SFP1_SD |
| 12 | TWI_SCL_MUX6 | SFP2_SD |
| 13 | TWI_SCL_MUX7 | SFP3_SD |
| 14 | TWI_SCL_MUX8 | SFP4_SD |
| 15 | TWI_SCL_MUX9 | SFP5_SD |
| 16 | | SPI_nCS3 |
| 17 | TWI_SCL_MUX10 | SPI_nCS4 |
| 18 | TWI_SCL_MUX11_AD | |
| 19 | TWI_SCL_MUX12_AD | |
| 20 | TACHO | TWI_SCL_MUX14_AD |
| 21 | PWM | TWI_SCL_MUX15_AD |

U4B




SFP signals on GPIOs:
- TXFAULT requires pullup (open drain)
- MODDETn requires pullup (open drain)
- RATESEL has no special requirements
- TXDISABLE requires pullup (TX init disabled)

Pullups are on SFP sheet

### VSC7512 boot mode strapping

| VCore_Cfg[3:0] | VCore-III CPU Behavior |
|---|---|
| 0 0 0 0 | Reserved. |
| 0 0 0 1 | 8051 IROM boot. Reserved for port-bringup. |
| 0 0 1 0 | 8051 IROM boot. Reserved for port-bringup. |
| 0 0 1 1 | 8051 IROM boot. Reserved for port-bringup. |
| 0 1 0 0 | 8051 IROM boot. Reserved for port-bringup. |
| 0 1 0 1 | 8051 IROM boot. Reserved for port-bringup. |
| 0 1 1 0 | 8051 IROM boot. Reserved for port-bringup. |
| 0 1 1 1 | 8051 IROM boot. Reserved for port-bringup. |
| 1 0 0 0 | 8051 IROM boot. NPI:1G FDX NoFC, VRAP. |
| 1 0 0 1 | 8051 IROM boot. PCIe |
| 1 0 1 0 | No boot. SI slave and MIIM slave @ address 0 (GPIO alternative). |
| 1 0 1 1 | No boot. SI slave and MIIM slave @ address 31 (GPIO alternative). |
| 1 1 0 0 | Reserved. |
| 1 1 0 1 | Reserved. |
| ==> 1 1 1 0 | 8051 boots from SI interface. |
| 1 1 1 1 | No boot. SI slave is enabled. |




### VSC7512 PLL strapping

| REFCLK_SEL[2:0] | Frequency | Comment |
|---|---|---|
| ==> 000 | 125MHz | The default mode. Normal operation mode with 125MHz |
| 001 | 156.25MHz | Normal operation mode with 156.25MHz ref clock |
| 010 | 250MHz | Normal operation mode with 250MHz ref clock |
| 011 | N/A | Reserved |
| 100 | 25MHz | Normal operation mode with 25MHz ref clock |
| 101 | N/A | Reserved |
| 110 | N/A | Reserved |
| 111 | N/A | Reserved |




Due to VSC7512 jitter requirements, don't use 25MHz REFCLK as base for QSGMII

### Board I2C address table

| Address | I2C slave |
|---|---|
| 1010xxx | SFP transceiver |



















Rabbit connector has double duty as connector for Microsemi QuickTest module, enabling test of selected PCB signals (definitely optional!). ADC nominal input voltage 0.57V.




Hoerkaer 16
DK-2730 Herlev
Denmark

MAG

Microsemi

Company Confidential

Title: Switch memory (SPI boot Flash, GPIO, PCIe, clocks, strapping

| Size | Document Number | Rev |
|---|---|---|
| A3 | PCB121 | 02-00 |

Date: Thursday, August 11, 2016 Sheet 3 of 6

## RJ45[8:5] (1Gbps/100Mbps/10Mbps)




## Integrated magnetics




## TVS protection on 1000BASE-T signals




## TVS protection on LED signals




## SFP[2:1] (2.5Gbps/1Gbps/100Mbps)




## SFP connectors and cage




SFP+ connector used as in-stock - standard SFP connector (not footprint compatible) may be used if prefered




No pull-ups on SFPx_SCL as these signals are "always-drive" from VSC7512

SERDES usage:
- S5 only used for test
- S6 connects to VSC8514 through QSGMII
- S7 (2.5Gbps) connects to SFP1
- Config 0: S4 (1Gbps) connects to NPI on breakoff and S8 (2.5Gbps) connects to SFP2 through breakoff
- Config c: S4 (1Gbps) connects to SFP2 through breakoff and S8 (2.5Gbps) connects to PCIe on breakoff board

## "SFP" connector for test only




## Serial LED outputs




## Port status LEDs




## System status LED




Enable SLED ports 7:0 as port status LEDs for 8x RJ45 ports (SLED port 0 is VSC7512 P0/RJ45#5, SLED port 4 is VSC8514 P0/RJ45#1, etc.),
SLED port 8 as LED for SFP1 through S7,
SLED port 9 as LED for 1G SFP2 through S4 (config c/PCIe only),
SLED port 10 as LED for 2.5G SFP2 through S8 (config 0 only),
SLED port 11 as system status LED
Enable two bits per port,
bit[1:0]=00 => yellow, 01 => red, 10 => green, 11 => off.


Hoerkaer 16
DK-2730 Herlev
Denmark


Microsemi

Company Confidential

MAG

| | | | |
|---|---|---|---|
| Title | VSC7512 ports, LEDs | | |
| Size A3 | Document Number PCB121 | | Rev 02-00 |
| Date: Thursday, August 11, 2016 | | Sheet 4 of 6 | |

## RJ45[4:1] (1Gbps/100Mbps/10Mbps)

## VSC8514 I/O and strapping




## VSC8514 QSGMII/ports




## TVS protection




## Integrated magnetics





Hoerkaer 16
DK-2730 Herlev
Denmark


Company Confidential

MAG

| | | |
|---|---|---|
| Title: VSC8514 | | |
| Size: A3 | Document Number: PCB121 | Rev: 02-00 |
| Date: Thursday, August 11, 2016 | Sheet 5 of 6 | |

## Breakoff board for connecting NPI PHY to mainboard S4 (SFP2 is 2.5Gbps S8)

Samtec connector towards mainboard, feedthrough of S8 to SFP2




CMODE pull-up/pull-down to digital translation

| With CMODE pin tied to | . with 1% . res val | Set bit 3 to: | Set bit 2 to: | Set bit 1 to: | Set bit 0 to: |
|---|---|---|---|---|---|
| GND | 0 | 0 | 0 | 0 | 0 |
| GND | 2.26k | 0 | 0 | 0 | 1 |
| GND | 4.02k | 0 | 0 | 1 | 0 |
| GND | 5.90k | 0 | 0 | 1 | 1 |
| GND | 8.25k | 0 | 1 | 0 | 0 |
| GND | 12.1k | 0 | 1 | 0 | 1 |
| GND | 16.9k | 0 | 1 | 1 | 0 |
| GND | 22.6k | 0 | 1 | 1 | 1 |
| 3V3 | 0 | 1 | 0 | 0 | 0 |
| 3V3 | 2.26k | 1 | 0 | 0 | 1 |
| 3V3 | 4.02k | 1 | 0 | 1 | 0 |
| 3V3 | 5.90k | 1 | 0 | 1 | 1 |
| 3V3 | 8.25k | 1 | 1 | 0 | 0 |
| 3V3 | 12.1k | 1 | 1 | 0 | 1 |
| 3V3 | 16.9k | 1 | 1 | 1 | 0 |
| 3V3 | 22.6k | 1 | 1 | 1 | 1 |

VSC8221 CMODE strapping

| Pin | Bit 3 control | Bit 2 control | Bit 1 control | Bit 0 (LSB) control |
|---|---|---|---|---|
| 3 | LED control[1] 0=>link/act | SQE enable 0=>SQE disabled | Reserved - | Autoneg ctrl[1] 0=>10/100/1000Base |
| 2 | Operating mode[3:0], 0000=>SERDES to CAT5, SCLK disabled | | | |
| 1 | SFP mode 1=>SFP disable | PHY address[4] 1 | SIGDET direct 1=>Output | Line impedance 0=>50R |
| 0 | PHY address[3:0], (1)1100=>0x1c, 28 dec | | | |

VSC8221 NPI single PHY




## Breakoff board for connecting PCIe cable to mainboard S8 (SFP2 is 1Gbps S4)

Samtec connector towards mainboard, feedthrough of S4 to SFP2




Flash for "special cases"




Programming header for Flash




Override VCORE_CFG of mainboard, for plug&play PCIe




No PCIeWAKE from this mainboard (use in-band beacon instead)


PCIe 1x cable connector for S8 from mainboard




Note, PCIe interface for use in controlled lab environment, so
(1) no power domain isolation,
(2) high-impedance when powered off not guaranteed for CWAKE#, CPRSNT#, CPERST#,
(3) spread spectrum clocked PCIe hosts not supported

## Breakoff board with RS232 port for old-school management





Hoerkaer 16
DK-2730 Herlev
Denmark

MAG


Microsemi

Company Confidential

Title: Breakoffs for PCIe, NPI PHY and 2nd SFP source selection - and RS232

| Size | Document Number | Rev |
|---|---|---|
| A3 | PCB121 | 02-00 |

Date: Thursday, August 11, 2016 Sheet 6 of 6