

TCSESM063F2CU1

Ethernet TCP/IP extended managed switch - ConneXium – 6 TX/2FX - multimode

Product availability: Stock - Normally stocked in distribution facility

Price*: 2120.00 USD



Main

Commercial Status	Commercialised
Range of product	ConneXium
Product or component type	Ethernet TCP/IP managed switch
Concept	Transparent Ready
Communication port protocol	Ethernet TCP/IP
Port Ethernet	10BASE-T/100BASE-TX - 6 port(s) copper cable 100BASE-FX - 2 port(s) fiber optic
Maximum number of switches in cascade	Unlimited

Complementary

Integrated connection type	Shielded RJ45 copper cable Duplex SC fiber optic
Transmission support medium	Multimode optical fiber for fiber optic Twisted shielded pairs cable CAT 5E for copper cable
Cable length	328.08 ft (100 m) copper cable
Optic fiber length	50/125 µm 62.2/125 µm
Attenuation	8 dB 50/125 µm 11 dB 62.2/125 µm
Ethernet service	Configuration via web server Data stream control FDR IGMP Snooping Multicast filtering Priority port Rapid Scanning Tree Protocol (RSTP) Secure port SMTP V3 SNTP client VLAN
Maximum number of switches in a ring	50
Redundancy	Redundant power supplies Redundant single ring Ring coupling
[Us] rated supply voltage	12...48 V
Supply voltage limits	10...60 V DC SELV
Power consumption	12 W
Electrical connection	2 removable connectors 2 ways power supply
Mounting support	35 mm symmetrical DIN rail
Marking	CE
Local signalling	1 LED per channel copper port status 1 LED per channel copper port activity 1 LED stand-by 1 LED ring manager 1 LED fault 2 LEDs P1 P2 power supplies
Alarm output	2 voltfree contact <= 1 A

Alarm function	Power supply fault Data link status High temperature
Ethernet cabling system	TF switches
Width	4.72 in (120 mm)
Height	5.39 in (137 mm)
Depth	4.53 in (115 mm)
Product weight	2.2 lb(US) (1 kg)

Environment

Ambient air temperature for operation	32...140 °F (0...60 °C)
Relative humidity	> 0...95 % without condensation
IP degree of protection	IP30
Standards	EN/IEC 61131-2 IEC 61850-3 UL 1604 Class 1 Division 2 UL 508 CSA C22.2 No 213 Class I Division 2 CSA C22.2 No 214
Product certifications	BV C-Tick GL LR

Ordering and shipping details

Category	18225 - PLC NTWRK HRDWR & PROWORX SOFTWARE
Discount Schedule	PC41
GTIN	00785901918912
Nbr. of units in pkg.	1
Package weight(Lbs)	2.21
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	DE

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1022 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months
--------	-----------