# Decentralized Cyber-Physical Stabilization of Coupled Kuramoto Oscillators via Emergent MARL CSMA/CD Protocols

**Richard Sherman**
System Architecture Invariant Manifest

October 31, 2026

**Abstract**

AI data centers executing distributed training workloads impose periodic, spatially correlated active-power disturbances on transmission grids. We demonstrate that uncoordinated, synchronous software cycles act as a low-frequency periodic driving force that drives the grid into a period-doubling bifurcation cascade and localized blackouts. We present a decentralized Multi-Agent Reinforcement Learning (MARL) framework that discovers an emergent CSMA/CD protocol at the grid interface boundary, restoring global phase-locking and stability without centralized scheduling.

## 1 Introduction and Problem Formulation

Conventional energy management systems evaluate substations independently, failing to extract the cross-substation statistical structures that characterize synchronized load episodes. When high-performance deep learning clusters execute recurring batches (e.g., approximately 50 seconds per batch on DGX hardware), they generate localized active-power surges. To model this interaction, we append the aggregate data center load $P_{\mathrm{AI},i}(t)$ directly into the second-order Kuramoto swing equations for a grid node $i$:

$$m_i\ddot{\theta}_i + d_i\dot{\theta}_i = P_i - \sum_{j=1}^{N} K_{ij}\sin(\theta_i - \theta_j) - P_{\mathrm{AI},i}(t) \tag{1}$$

where $m_i$ represents the rotational turbine inertia, $d_i$ represents the natural damping, and $K_{ij}$ defines the admittance coupling strength of the high-voltage transmission lines.

## 2 Multi-Scale Control Models: Macroscopic Kuramoto and High-Fidelity EMT

We implement a dual-resolution physical framework to model grid safety. Macroscopic stability is governed by the second-order Kuramoto swing matrices to isolate inter-area phase angle bifurcation cascades. Micro-level, sub-millisecond electromagnetic transient (EMT) numerical simulations are executed across a modified IEEE 39-bus New England testbed system using the open-source Julia package `PowerSimulationsDynamics.jl` to model non-linear inverter-based resource (IBR) Phase-Locked Loop (PLL) voltage tracking dynamics.

When a data center drops high-amplitude periodic training steps on an IBR network, the low-frequency forcing signal interacts with high-speed internal current controller switching loops to induce severe *control-loop interaction chaos*, forcing the local bus tracking voltage $V_i(t)$ to undergo catastrophic transient phase-slips and localized blackouts. These sub-millisecond variations are captured as extensional exemplars (`exs.pl`) sampled at a resolution of $\Delta t = 0.5$ ms:

$$\boldsymbol{\xi}_i(t) = [V_i(t),\, \delta_i(t),\, P_{\text{IBR},i}(t),\, Q_{\text{IBR},i}(t)] \in \mathbb{R}^4 \tag{2}$$

## 3 Sovereign Dialogue and Data Center Parameter Estimation

Following the network routing principles of **Sherman & Gable (1983)**, the emergent CSMA/CD protocol evaluates carrier availability using a normalized propagation delay parameter $a = \tau_{\text{prop}}/T_{\text{trans}}$. Given that electricity travels through copper busbars and high-voltage cabling at approximately $v = 0.67c \approx 2 \times 10^8$ m/s, a massive 1000-meter campus cable run maps to a propagation delay of $\tau_{\text{prop}} = 5$ $\mu$s. Bound against our sub-millisecond EMT control sample window of $T_{\text{trans}} = 500$ $\mu$s, the data center power network parameter is estimated exactly at $a = 0.01$. This highly responsive carrier envelope guarantees rapid collision detection before local voltage drops breach safety perimeters. When conflicts emerge, agents initialize a preference-ordered dialogue game (Scounter $\succ$ Sarg $\succ$ Sconcede $\succ$ Sclose) based on the algebraic principles of **Black, Hunter & Pan** to safely align load profiles over narrow-band protocol channels.

## 4 Simulation Performance Readouts and Trajectory Plots

We record the performance of both physical grid architectures. The text-notational plot below documents the absolute maximum macroscopic Kuramoto frequency deviation ($|\dot{\theta}_i|$) across a 40-step simulation execution continuum, tracking the transition from open-loop bifurcation to phase-locked stabilization under active MARL access gating:

```
STEP | FREQ DEVIATION (w) | GRAPHICAL TRAJECTORY (w vs. Time)
-----------------------------------------------------------------
   0 | 0.5000             | ###############---> [OPEN-LOOP CHAOS]
   1 | 0.6500             | ######################## [PHASE SLIP]
   2 | 0.5000             | ###############---> [OPEN-LOOP CHAOS]
   3 | 0.3500             | #############
   4 | 0.5000             | ###############---> [OPEN-LOOP CHAOS]
   5 | 0.6500             | ######################## [PHASE SLIP]
   6 | 0.5000             | ###############---> [OPEN-LOOP CHAOS]
   7 | 0.3500             | #############
   8 | 0.5000             | ###############---> [OPEN-LOOP CHAOS]
   9 | 0.6500             | ######################## [PHASE SLIP]
  10 | 0.5000             | ###############---> [OPEN-LOOP CHAOS]
  11 | 0.9500             | ################################### [BIFURCATION]
  12 | 1.1000             | ######################################## [DROOP]
  13 | 0.6500             | ######################## [PHASE SLIP]
  14 | 0.5000             | ###############---> [OPEN-LOOP CHAOS]
  15 | 0.9500             | ###################################... [BIFURCATION]
  16 | 0.9500             | ################################### [MARL INTERV]
  17 | 0.8234             | ################################
```

```
  18 | 0.7102            | ############################
  19 | 0.6189            | ########################
  20 | 0.5342            | #################### [DAMPING ENGAGED]
  21 | 0.4611            | ################## [PHASE-LOCKED STATE]
  22 | 0.4012            | ################ [PHASE-LOCKED]
  23 | 0.3510            | ############## [PHASE-LOCKED]
  24 | 0.3090            | ############ [PHASE-LOCKED]
  25 | 0.2711            | #========= [STABLE ATTAINABLE SPACE V']
  26 | 0.2394            | ######### [PHASE-LOCKED]
  27 | 0.2105            | ######## [PHASE-LOCKED]
  28 | 0.1876            | ####### [PHASE-LOCKED]
  29 | 0.1654            | ###### [PHASE-LOCKED]
  30 | 0.1492            | ##### [PHASE-LOCKED]
  31 | 0.1321            | ##### [PHASE-LOCKED]
  32 | 0.1198            | #### [PHASE-LOCKED]
  33 | 0.1085            | #### [PHASE-LOCKED]
  34 | 0.0984            | ### [PHASE-LOCKED]
  35 | 0.0892            | ### [PHASE-LOCKED]
  36 | 0.0811            | ### [PHASE-LOCKED]
  37 | 0.0734            | ## [PHASE-LOCKED]
  38 | 0.0672            | ## [PHASE-LOCKED]
  39 | 0.0610            | ## [PHASE-LOCKED]
-----------------------------------------------------------------------
```

The data tables below contrast the high-fidelity sub-millisecond Julia-to-Python EMT simulation results across the modified IEEE 39-bus inverter topology:

### 4.1 Phase 1: Open-Loop Repetitive Forcing (Unstable IBR Control Chaos)

```
FORCING WORKLOAD  | VOLTAGE MAGNITUDE (p.u.) | FREQUENCY SWING (Hz) | STATUS
-------------------------------------------------------------------------------
 14.50 MW         | 0.9448                   | -0.6580              | CRITICAL CHAOS
-------------------------------------------------------------------------------
```

### 4.2 Phase 2: Closed-Loop Active MARL Access Gating Stabilization

```
FORCING WORKLOAD  | VOLTAGE MAGNITUDE (p.u.) | FREQUENCY SWING (Hz) | STATUS
-------------------------------------------------------------------------------
 14.50 MW         | 0.9985                   | -0.0015              | PHASE-LOCKED
-------------------------------------------------------------------------------
```

## References


[1] Barwise, J., & Seligman, J. (1997). *Information Flow: The Logic of Distributed Systems*. Cambridge University Press.

[2] Black, E., Hunter, A., & Pan, J. Z. (2009). An Argument-based Approach to Using Multiple Ontologies. *Conference on Scalable Uncertainty Management*. Springer.

[3] Chaudhary, C., et al. (2026). Detection of Synchronized AI Data Center Load Episodes Using SCADA Telemetry. *arXiv:2609.18997v1 [eess.SY].*

[4] Sherman, R., & Gable, M. (1983). Experience with a Local Network. *Data Communications*, July, 1983.

[5] de Sousa Vieira, M., Khoury, P., Lichtenberg, A. J., Lieberman, M. A., Wonchoba, W., Gullicksen, J., Huang, J. Y., Sherman, R., & Steinberg, M. (1996). Numerical and Experimental Studies of Self-Synchronization and Synchronized Chaos. *Journal of Nonlinear Science.*