


Current Pixel Value is 192

Consider neighbor Values

Filter Definition

CURRENT_PIXEL_VALUE = 192

NEW_PIXEL_VALUE = $(-1 * 0) + (0 * 64) + (-2 * 128) +$
 $(.5 * 48) + (4.5 * 192) + (-1.5 * 144) +$
 $(1.5 * 142) + (2 * 226) + (-3 * 168)$




Current Pixel Value is 192

Consider neighbor Values

Filter Definition

CURRENT_PIXEL_VALUE = 192


NEW_PIXEL_VALUE = $(-1 * 0) + (0 * 64) + (-2 * 128) +$
 $(.5 * 48) + (4.5 * 192) + (-1.5 * 144) +$
 $(1.5 * 142) + (2 * 226) + (-3 * 168)$




CURRENT_PIXEL_VALUE = 192

$$\begin{aligned} \text{NEW_PIXEL_VALUE} = & (-1 * 0) + (0 * 64) + (-2 * 128) + \\ & (.5 * 48) + (4.5 * 192) + (-1.5 * 144) + \\ & (1.5 * 142) + (2 * 226) + (-3 * 168) \end{aligned}$$







0	64	128	128
48	192	144	144
142	226	168	0
255	0	0	64

0	64
48	192

192

128	128
144	144

144

142	226
255	0

255

168	0
0	64

168

192	144
255	168

```
model = tf.keras.Sequential([
    tf.keras.Input(shape=(28, 28)),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(128, activation=tf.nn.relu),
    tf.keras.layers.Dense(10, activation=tf.nn.softmax)
])
```



```
model = tf.keras.Sequential([
    tf.keras.Input(shape=(28, 28, 1)),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(128, activation='relu'),
    tf.keras.layers.Dense(10, activation='softmax')
])
```



```
model = tf.keras.Sequential([
    tf.keras.Input(shape=(28, 28, 1)),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(128, activation='relu'),
    tf.keras.layers.Dense(10, activation='softmax')
])
```

Computer Vision Problems

Image Classification



Cat? (0/1)

Neural Style Transfer



Object detection



PLAY ALL

Convolutional Neural Networks (Course 4 of the Deep Learning Specialization)

42 videos • 415,722 views • Last updated on Nov 7, 2017



Deeplearning.ai

SUBSCRIBE 28K

1




C4W1L01 Computer Vision

Deeplearning.ai

5:44

2

Vertical edge detection



C4W1L02 Edge Detection Examples

Deeplearning.ai

11:31

3

Vertical and Horizontal Edge Detection




C4W1L03 More Edge Detection

Deeplearning.ai

7:58

4




C4W1L04 Padding

Deeplearning.ai

9:50

5

Technical note on cross-correlation vs. convolution




C4W1L05 Strided Convolutions

Deeplearning.ai

9:02

6

Convolutions on RGB image



C4W1L06 Convolutions Over Volumes

Deeplearning.ai

10:45

<https://bit.ly/2UGa7uH>



deeplearning.ai

```
model = tf.keras.Sequential([
    tf.keras.Input(shape=(28, 28, 1)),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(128, activation='relu'),
    tf.keras.layers.Dense(10, activation='softmax')
])
```

```
model = tf.keras.Sequential([
    tf.keras.Input(shape=(28, 28, 1)),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Conv2D(64, (3, 3), activation='relu'),
    tf.keras.layers.MaxPooling2D(2, 2),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(128, activation='relu'),
    tf.keras.layers.Dense(10, activation='softmax')
])
```

```
model.summary()
```



Layer (type)	Output Shape	Param #
conv2d_12 (Conv2D)	(None, 26, 26, 64)	640
max_pooling2d_12 (MaxPooling)	(None, 13, 13, 64)	0
conv2d_13 (Conv2D)	(None, 11, 11, 64)	36928
max_pooling2d_13 (MaxPooling)	(None, 5, 5, 64)	0
flatten_5 (Flatten)	(None, 1600)	0
dense_10 (Dense)	(None, 128)	204928
dense_11 (Dense)	(None, 10)	1290

Layer (type)	Output Shape	Param #
conv2d_12 (Conv2D)	(None, 26, 26, 64)	640
max_pooling2d_12 (MaxPooling)	(None, 13, 13, 64)	0
conv2d_13 (Conv2D)	(None, 11, 11, 64)	36928
max_pooling2d_13 (MaxPooling)	(None, 5, 5, 64)	0
flatten_5 (Flatten)	(None, 1600)	0
dense_10 (Dense)	(None, 128)	204928
dense_11 (Dense)	(None, 10)	1290











Layer (type)	Output Shape	Param #
conv2d_12 (Conv2D)	(None, 26, 26, 64)	640
max_pooling2d_12 (MaxPooling)	(None, 13, 13, 64)	0
conv2d_13 (Conv2D)	(None, 11, 11, 64)	36928
max_pooling2d_13 (MaxPooling)	(None, 5, 5, 64)	0
flatten_5 (Flatten)	(None, 1600)	0
dense_10 (Dense)	(None, 128)	204928
dense_11 (Dense)	(None, 10)	1290

Layer (type)	Output Shape	Param #
conv2d_12 (Conv2D)	(None, 26, 26, 64)	640
max_pooling2d_12 (MaxPooling)	(None, 13, 13, 64)	0
conv2d_13 (Conv2D)	(None, 11, 11, 64)	36928
max_pooling2d_13 (MaxPooling)	(None, 5, 5, 64)	0
flatten_5 (Flatten)	(None, 1600)	0
dense_10 (Dense)	(None, 128)	204928
dense_11 (Dense)	(None, 10)	1290

Layer (type)	Output Shape	Param #
conv2d_12 (Conv2D)	(None, 26, 26, 64)	640
max_pooling2d_12 (MaxPooling)	(None, 13, 13, 64)	0
conv2d_13 (Conv2D)	(None, 11, 11, 64)	36928
max_pooling2d_13 (MaxPooling)	(None, 5, 5, 64)	0
flatten_5 (Flatten)	(None, 1600)	0
dense_10 (Dense)	(None, 128)	204928
dense_11 (Dense)	(None, 10)	1290

Layer (type)	Output Shape	Param #
conv2d_12 (Conv2D)	(None, 26, 26, 64)	640
max_pooling2d_12 (MaxPooling)	(None, 13, 13, 64)	0
conv2d_13 (Conv2D)	(None, 11, 11, 64)	36928
max_pooling2d_13 (MaxPooling)	(None, 5, 5, 64)	0
flatten_5 (Flatten)	(None, 1600)	0
dense_10 (Dense)	(None, 128)	204928
dense_11 (Dense)	(None, 10)	1290

Layer (type)	Output Shape	Param #
conv2d_12 (Conv2D)	(None, 26, 26, 64)	640
max_pooling2d_12 (MaxPooling)	(None, 13, 13, 64)	0
conv2d_13 (Conv2D)	(None, 11, 11, 64)	36928
max_pooling2d_13 (MaxPooling)	(None, 5, 5, 64)	0
flatten_5 (Flatten)	(None, 1600)	0
dense_10 (Dense)	(None, 128)	204928
dense_11 (Dense)	(None, 10)	1290