FORENSIC · 2026-09-06 · REVISED

Agent Identity Protocol — Forensic Audit & AI-Stack Extension

Part I is a line-by-line analysis of six divergent branches, assessed against source code rather than documentation. Part II audits the AI-stack extension built on top of it and re-verifies the two P0 fixes that landed mid-build. Part III is the AIRI reference documentation itself — protocol, threat model, limitations, architecture, versioning and the normative byte encoding. Every claim carries an evidence class and a `file:line` citation.

BRANCHES AUDITED 6	DOCUMENTS 18
P0 FINDINGS 2 · both now closed	BLOCKERS OPEN 8 + 1 new P1
WORKSPACE TESTS 912 · 0 failed	PRODUCTION PROMOTION Not permitted

PRINCIPAL FINDING · EXECUTION-PROVEN

Containment cannot fire. The containment gate requires evidence strength `Proven` for a workload violation; the reconciliation engine caps every workload violation at `Attested` exactly. An exhaustive 32-cell sweep under a maximally permissive policy returns `Contain` in four cells — all four requiring a `Reconciliation` the engine cannot emit. Neither the warrant crate nor the containment crate has ever called the reconciler. Full derivation in Report 04 §3. **Still open** as blocker B-3.

WHAT CHANGED SINCE THE FIRST REVISION

Both `P0` findings — the missing verifier clock and the unbound delegation issuer — were closed by the production branch while the extension was being built, and were re-verified here rather than accepted on their commit messages. That verification found a new `P1`: the clock fix landed in `aip-protocol` and never reached `aip-service`, whose `/verify` endpoint still applies no temporal bound (**B-1a**, Extension 10). Report 11 records two deliverables that were incomplete when first reported — one of them wrongly reported as done — and closes both.

HOW TO READ THIS

> Reports are ordered as a dossier, not a narrative: **00** establishes the evidence base and reproduction method, **01–05** are the technical findings, **06–08** are the readiness, IP and diligence readings drawn from them. Assertions are labelled `CODE-PROVEN`, `EXECUTION-PROVEN`, `DOCUMENTED`, `INFERRED` or `UNKNOWN`. Severity runs `P0` catastrophic to `P4` informational.

REPORT 00

Evidence Base

Audit date: 2026-09-06 **Auditor posture:** forensic, read-only. No product source, test, or configuration file was modified. No commit was created on any product path. No branch was checked out or merged. **Repository HEAD during audit:** `16493c5` on `claude/aip-security-architecture-audit-zpf9b3`; working tree clean throughout. **Toolchain:** cargo 1.94.1 / rustc 1.94.1 (2026-03-25).

Acquisition method

All six branch trees were obtained without altering the working tree:

```
git fetch origin <ref>
git archive <ref> | tar -x -C scratchpad/sixbranch/<alias>
```

No `git checkout`, no `git worktree`, no `git merge`. Every claim below is anchored to a path of the form `<alias>/<path>:<line>`, where `<alias>` denotes the extracted tree of that branch.

Branch aliases

ALIAS	REF	HEAD
`main`	`main`	`872dbf375838`
`prod`	`claude/codebase-production-readiness-wm6idp`	`82da7a6af110`
`audit`	`claude/aip-security-architecture-audit-zpf9b3`	`16493c58aed3`
`importot`	`import/orbitaltrust-accountability-layer`	`6cc439f19016`
`valladder`	`codex/val-ladder-sync`	`ae46a3a2f4e2`
`aipv4`	`codex/aip-v4-accountability`	`73bf70cf9e68`

Claim discipline

Every claim in these reports carries one of the following labels. Where a claim is unlabelled it is `CODE-PROVEN`.

LABEL	MEANING
`CODE-PROVEN`	Read directly from source at a cited path and line.
`EXECUTION-PROVEN`	Demonstrated by running code; the probe and its output are reproduced.
`TEST-PROVEN`	Established by a test that actually exercises the property in question.
`DOCUMENTED`	Asserted by a document in the repository; not independently verified.
`INFERRED`	A conclusion drawn from proven facts; the inference is stated.
`UNKNOWN`	Not determinable from the current codebase.

Severity scale

LEVEL	MEANING
P0	Catastrophic — the system asserts a security property it does not hold.
P1	Production blocker.
P2	Material risk; must be tracked and scheduled.
P3	Non-blocking defect or hazard.
P4	Informational.

Execution evidence collected

All figures produced during this audit on the toolchain above.

TARGET	ROOT	PASSED	FAILED	IGNORED	SUITES	EXIT
prod	`aip-standalone`	787	0	3	78	0
main	`aip-standalone`	143	0	1	6	0
audit	`aip-standalone`	143	0	1	6	0
importot	`aip-standalone`	143	0	1	6	0
valladder	`aip-standalone`	146	0	0	5	0
aipv4	`aip-standalone`	142	0	0	5	0
valladder	`aegis-quantum`	110	0	0	12	0
main	`aip-service`	38	0	0	3	0
prod	`aip-service`	39	0	0	3	0

Zero test failures were observed on any branch or root. Zero compiler warnings were emitted by the prod workspace or the aegis-quantum workspace.

Roots not exercised by any run above (each is a separate Cargo root and is not reached by `cargo test --workspace` in `aip-standalone`): `importot/orbitaltrust-accountability/rust/{ot-accountability-core, ot-sentinel,ot-verifier,ot-mcp-gateway}`, `importot/orbitaltrust-accountability/python-sdk`, `aipv4/aegis-quantum`, and `aip-service` on all branches except where run above.

What "0 failed" does and does not establish

It establishes that every assertion the authors wrote holds. It does not establish that the assertions cover the security properties claimed. Report 03 (Security Invariant Matrix) and Report 04 (Runtime Accountability Trace) separate these two questions, and in three cases — the containment path, the aegis-quantum LRU bound, and the aegis-quantum PQC exchange — the tests pass while the property they appear to cover is untested.

REPORT 01

Line-by-Line Forensic Audit

0. Scope statement and honesty boundary

This audit read 58,268 Rust LOC across six branch trees in one pass. It did not read every line of every file, and this report does not pretend otherwise. §1 lists the files subjected to line-level analysis. §7 lists files enumerated and sized but **not** read, marked `NOT DETERMINABLE FROM CURRENT CODEBASE` where a property would require reading them.

Where a file was read in full, findings are stated with line citations. Where a file was read in part, the range read is given.

1. Files subjected to line-level analysis

FILE (BRANCH)	LINES	READ
`main` + `prod` `aip-core/src/capability.rs`	507 / 583	full diff, both trees
`main` + `prod` `aip-core/src/delegation.rs`	636 / 813	full diff, both trees
`main` + `prod` `aip-protocol/src/verification.rs`	709 / 773	full diff, both trees
`main` + `prod` `aip-protocol/src/bundle.rs`	673 / 673	`verify_bundle_signature`
`main` … `aipv4` `aip-core/src/store.rs`	—	`IdentityStore::save`, 4 trees
`main` + `prod` `aip-service/src/evidence.rs`	604 / 651	full diff
`prod` `aip-reconcile/src/reconcile.rs`	2,008	1–200 full; structural map of 200–2008
`prod` `aip-reconcile/src/result.rs`	835	verdict enums, `Reconciliation`, `EvidenceRef`
`prod` `aip-warrant/src/warrant.rs`	437	1–100, `evaluate` 172–300, `is_protected`
`prod` `aip-warrant/src/policy.rs`	161	`WarrantPolicy`, `Severity`
`prod` `aip-containment/src/contain.rs`	384	header, `gates` 1–90, `contain` 279–365
`prod` `aip-observe/src/attest.rs`	894	1–95
`prod` `aip-nexora/src/merkle.rs`	359	domain-separation section
`valladder` `aegis-quantum-userspace/src/pqc.rs`	723	1–200 + test map
`valladder` `aegis-quantum-circuit-breaker/src/lib.rs`	757	27–135 full
`valladder` `aegis-quantum/stress-tests/{src/lib.rs,tests/lru_exhaustion_test.rs}`	156 / 47	full

2. `aip-core/src/capability.rs`

2.1 `canonical_token_payload` — main

`main/…/capability.rs:208-231` . Reconstructed from the read:

```
buf.extend_from_slice(jti);              // 16 bytes, fixed — fine
buf.extend_from_slice(issuer_id.as_bytes());   // UNBOUNDED, NO PREFIX
buf.extend_from_slice(agent_id.as_bytes());    // UNBOUNDED, NO PREFIX
for action in &scope.allowed { … }
buf.push(0xFF);                          // separator a payload can contain
for action in &scope.denied { … }
buf.extend_from_slice(&issued_at.to_le_bytes());
// expires_at: ABSENT
```

`encode_scope_action` (`main/…/capability.rs:232-242`) encodes `Custom(s)` as `0x01 ‖ s ‖ 0x00` .

Findings.

- **L-1 (`P0`).** Adjacent unprefixed strings are not injective. `("ab","c")` and `("a","bc")` yield identical bytes.
- **L-2 (`P0`).** `expires_at` is not in the signed preimage but *is* enforced by `check_temporal_validity` downstream. The verifier enforces a field the issuer never signed.
- **L-3 (`P1`).** No domain tag. A `ScopedToken` signature and a `DelegationToken` signature over structurally similar content are interchangeable.
- **L-4 (`P2`).** `0xFF` is used as an allowed/denied separator and `0x00` as a custom-action terminator. Both are bytes a `Custom(String)` action can contain, so a custom action with an interior NUL is ambiguous with two adjacent actions, and the allowed/denied boundary is forgeable by a crafted action name.

All four are present on `main` , `audit` , `importot` , `valladder` , `aipv4` .

2.2 `canonical_token_payload` — prod

`prod/…/capability.rs:221-238` . All four findings closed:

```
put_domain(&mut buf, SCOPED_TOKEN_DOMAIN);   // L-3
buf.extend_from_slice(jti);                  // fixed 16
put_str(&mut buf, issuer_id);                // L-1
put_str(&mut buf, agent_id);                 // L-1
encode_scope(&mut buf, scope);               // L-4
put_u64(&mut buf, issued_at);
put_opt_u64(&mut buf, &expires_at);          // L-2
```

`expires_at` is computed once at `:144` and threaded to both the payload and the struct, so the signed value and the carried value cannot diverge — a small detail that matters, because the previous code computed `expires_in_ms.map(|d| now_ms + d)` inline at the struct literal.

`verify_scoped_token` (`:170-176`) passes `token.expires_at` into the recomputed payload, so the check is closed on both sides.

Tests that genuinely exercise the property (`:253-330` , `:424-490`):
`test_mutate_expires_at_extend_rejected` ,
`test_mutate_expires_at_some_to_none_rejected` ,
`test_mutate_expires_at_none_to_some_rejected` ,
`test_token_payload_adjacent_ids_do_not_collide` ,
`test_token_payload_custom_action_interior_nul_unambiguous` ,
`test_token_payload_expiry_presence_is_distinct` ,
`test_token_payload_starts_with_domain_tag` .

The interior-NUL test is the strongest of these: it distinguishes `Custom("x\0y")` from `[Custom("x"), Custom("y")]` from `allowed=[Custom("x")], denied=[Custom("y")]` — three arrangements that the old encoder could confuse.

3. `aip-core/src/delegation.rs`

3.1 `verify_delegation_chain` — prod, read in full

`prod/…/delegation.rs:179-244` . Five checks per hop, in this order:

#	CHECK	LINE	ERROR
1	`hop.parent_jti == prev_jti`	:200	`LineageInvalid`
2	`hop.depth == i+1`	:206	`LineageInvalid`
3	`is_scope_subset(hop.scope, prev_scope)`	:211	`AttenuationViolation`
4	issuer signature over recomputed payload	:219	`SignatureInvalid`
5	`hop.expires_at` does not outlive parent's	:227-235	`AttenuationViolation`

Finding L-5 (`P0` **, all six branches).** There is no check that `hop.issuer_id` equals the previous hop's `grantee_id` , or — for hop 0 — the root token's `agent_id` . The chain is linked by JTI and by depth. The *identities* are not linked. Any principal whose key is present in `issuer_public_keys` can present itself as the issuer of a hop whose `parent_jti` matches, and all five checks pass.

The consequence is precise: delegation is authenticated (someone with a trusted key signed this hop) but not attributed (that someone need not be the party the previous hop delegated to). A "chain of custody" that does not check custody.

Checked, not a finding — the depth bound is correct. The limit is `if chain.len() >= MAX_DELEGATION_DEPTH` (`:190`), and `create_sub_delegation` rejects `new_depth >= MAX_DELEGATION_DEPTH` (`:120`). With `MAX_DELEGATION_DEPTH = 8` and root delegations starting at depth 1 (`:77`), the maximum accepted depth is 7. This initially reads as an off-by-one, and it is not: the module's invariant list states the bound as `depth < MAX_DELEGATION_DEPTH` (`:18`), a strict inequality, and both call sites implement exactly that. Recorded here because an automated scan and a first reading both flag it, and the next auditor should not have to re-derive the answer.

3.2 Ordering of check 4 before check 5 — correct, and deliberately so

The comment at `:224-226` explains it:

> *checked after authenticity so a forged expiry is reported as `SignatureInvalid`, and an issuer that genuinely over-delegated is reported as `AttenuationViolation`.*

This is right. The two conditions are different accusations — tampering versus exceeding authority — and collapsing them would destroy forensic information. `test_legitimately_signed_hop_outliving_parent_rejected` (`:520-575`) pins it by forging a hop with the *genuine* delegating key and requiring `AttenuationViolation` specifically, with a control case at equal expiry that must succeed.

4. `aip-protocol/src/verification.rs`

4.1 The complete main→prod delta

64 lines, three changes, nothing else:

1. `use aip_types::EXECUTION_BINDING_VERSION;` (`:24`)
2. `check_execution_binding` — new rule R15 (`:484-533`), called at `:266`
3. `check_structure` problem strings widened `&str` → `String` (`:333-355`) so the unsupported-version message can name the version

4.2 R15 — read in full

```
fn check_execution_binding(packet, e) -> bool {
    let Some(b) = &packet.execution_binding else {
        return e.record(EXECUTION_BINDING, true,
            "no execution binding present; process-instance attribution unavailable");
    };
    // version, agent match, pid != 0, pid_start_time_ticks != 0,
    // boot_id != [0;16], exe_content_sha256 != [0;32]
}
```

Assessment: correct and correctly scoped. Three things are right about it:

- Absence is *reported as passing*, not failed. A packet without a binding is not attributable to a process instance; that is a statement about what the record can support, not a defect in the record.
- The success message says "**NOT independently observed**" in the record itself, so a consumer reading the report cannot mistake a self-report for an observation.
- The call site comment at `:266-268` states it "Does NOT affect the trust floor: a self-report cannot raise evidence strength". The trust-floor derivation

at `:270-280` does not reference the R15 result. Verified by reading the derivation.

4.3 `check_temporal_validity` — unchanged, and the `P0`

`prod/…/verification.rs:535-585`. Byte-identical to main (both bodies extracted and hashed: `dbafa0086c1b34af`). It performs three comparisons:

```
if decided < issued_at                    → "decision predates issuance"
if decided > exp                          → "decision after expiry"
if action.performed_at > exp              → "action after expiry"
if action.performed_at < decision.decided_at → "action before its decision"
```

Every comparison is between two values **carried inside the packet**. `VerificationContext` (`:29-43`) carries issuer keys, counterparty keys, revoked JTIs, trace data and receipt data — and no clock.

Finding L-7 (`P0`, all branches with this file). A packet whose internal timestamps are mutually consistent passes regardless of how far they sit from real time. Combined with the absence of any replay rule among R1–R15, a captured packet remains verifiable indefinitely and a fabricated one can be dated arbitrarily. The system's temporal claims are internal-consistency claims only.

The fix is small — a `now_ms` field and a bound — and the fact that R15 was added without adding it is the notable part.

5. `aip-reconcile` — the verdict engine

5.1 Verification order

`reconcile.rs:5-9` declares it, and the code follows it:

> *structure → expected signature → expected window → observer signatures → observer trust → chain/continuity → identity → decision id → binding → action → parameters → time → strength → result. A failed prerequisite is never skipped and never upgraded.*

`prologue` (`:1131-1213`) implements everything the two entry points share and returns a finished record on early exit, so a failed prerequisite *cannot* fall through — there is no path that continues past it.

5.2 `Draft` and the four proof-carrying flags

`reconcile.rs:37-62`. Four fields exist solely to carry evidence that a precondition was actually established:

FIELD	SET BY	GATES
`coverage_recomputed`	`recompute_coverage` only	`PhantomClaim`
`action_continuity_verified`	`compare_action` only	`VerifiedExecution`
`lineage`	`reconcile_lineage` only	`LineageViolation`
`wire`	Gate 2 corroboration	nothing — informational

The comments state the maintenance intent explicitly: a future edit that forgets the recomputation "downgrades to `CannotProve` instead of asserting non-execution". This is the right way to express a safety property.

`wire` is documented as unable to raise or lower the verdict, and `precondition_holds` does not reference it. Verified.

5.3 `precondition_holds` — read in full, findings

`reconcile.rs:89-137`. See Report 04 §2.1 for the table.

Finding L-8 (`P3`). `SensorIntegrityFailure` and `ContinuityFailure` are the only two classes with no structural precondition — their arm is `strength >= EvidenceStrength::Attested` alone. Every workload-directed verdict must present a witness in the record; neither observer-directed verdict must. For a system whose threat model includes a host that benefits from discrediting its observer, the asymmetry runs the wrong way.

Mitigating: `classify_observer_error` (`:209-228`) is careful about which failures earn `Proven` — signature arithmetic does, a bad local trust anchor does not — and the match is exhaustive so a new variant breaks the build. The care is present at the classification site; it is the precondition that is thin.

Finding L-9 (`P2`). `Reconciliation` (`result.rs:679-699`) has fourteen `pub` fields. `ActionComparison`'s positive variants are protected by a private-field seal with `pub(crate)` constructors; the record carrying the verdict is not. Any consumer crate can construct a verdict directly, bypassing `finish()` and `precondition_holds`. The crate's own consumers do exactly this (`aip-containment/tests/containment.rs:104`).

The authors identified constructor control as the correct mechanism and applied it one level too shallow.

5.4 `compare_action` and `place_transition` — structural read only

`reconcile.rs:385-689`. Read at the level of doc comments and control-flow shape, not statement by statement. Two properties are stated and appear consistent with the code read:

- A transition placed **before** the decision "is not the authorized action, whoever claims it — and it also disqualifies presence evidence of the same connection", i.e. the "existed, but was not made" case.
- "Host claims only ever *restrict* a verdict."

`NOT DETERMINABLE FROM CURRENT CODEBASE` at this audit depth: whether every path through `compare_action` honours the second property. It requires a statement-level read of 230 lines and is the highest-value remaining target for a follow-up pass.

6. `aegis-quantum` (valladder / aipv4 only)

6.1 `circuit-breaker/src/lib.rs:27-135` — read in full

```
pub struct CircuitBreaker {
    window_ns: u64,
    threshold: usize,
    connections: HashMap<ConnectionKey, ConnectionState>,   // unbounded
}
```

`record_event` (`:65`) does `self.connections.entry(*key).or_insert_with(…)` . No method removes an entry. `reset` (`:109`) clears one connection's timestamps and leaves the entry. `reset_all` (`:117`) clears the map and is called by nothing on a timer or a bound.

Finding L-10 (`P1`). Per-key memory is bounded (the deque cannot exceed `threshold + 1` before `tripped` short-circuits further pushes), but the *number of keys* is not. An adversary varying the connection tuple allocates one entry per tuple without limit, in the component whose documented purpose is to stop "one rogue agent hammering an endpoint in a tight loop."

Finding L-11 (`P3`). `new()` (`:52`) computes `window_ms * 1_000_000` with unchecked `u64` multiplication and validates neither argument. `threshold = 0` trips on the first event; `window_ms = 0` yields a one-nanosecond window.

Finding L-12 (`P3`). Once `tripped` , the timestamp deque is retained indefinitely — `record_event` returns at `:76` before any eviction runs. Tripping the breaker is the cheapest route to permanent per-key retention.

Finding L-13 (`P3`). `timestamp_ns` is caller-supplied and assumed monotonic. Nothing enforces it. The eviction cutoff is `timestamp_ns.saturating_sub(self.window_ns)` , so a caller feeding non-monotonic values shrinks the cutoff and stops eviction early.

Finding L-14 (`P1`) — the test that does not test this. `stress-tests/tests/lru_exhaustion_test.rs` (read in full, 47 lines) calls `simulate_lru_saturation` and `MockLruSessionMap` , both defined at `stress-tests/src/lib.rs:19,84` . Neither test constructs a `CircuitBreaker` . The crate depends on `aegis-quantum-circuit-breaker` but the exhaustion tests do not use it. Two passing tests named for a bound the product code does not have.

6.2 `userspace/src/pqc.rs` — read 1–200

Finding L-15 (`P1`). `process_packet_event` (`:157-165`) logs the event's addresses and discards it, then calls

`hybrid_x25519_kyber768_key_exchange()`. That function (`:90-131`) creates `client_secret`, `server_secret`, and the Kyber keypair in the same process, encapsulates to a public key it just made, decapsulates with the private half it still holds, and compares two secrets derived entirely from key material it owns. `secrets_match` is arithmetically always true.

There is no peer, no socket, no session-map write. The doc comment is honest (`:152` "For TRL-4, we simulate the full round-trip"); the crate description and the type name `PqcValidationReport` are not.

Finding L-16 (`P3`). `algorithm` is reported as `"Kyber-768 (ML-KEM)"`. The dependency is `pqcrypto-kyber 0.8.1`, which implements round-3 Kyber. FIPS 203 ML-KEM is a different construction. The label conflates them.

Finding L-17 (`P2`). `pqcrypto-kyber = "0.8"` and `pqcrypto-traits = "0.3"` are caret ranges on cryptographic dependencies.

Not a finding — `hybrid_session_hash` (`:134-142`) is correct: domain-separated under `AIRON-AEGIS-HYBRID-v1`, both secrets length-prefixed before hashing. The construction is the recommended hybrid pattern. It is exercised only against itself.

7. Enumerated but not read

Sized and located; no line-level claim is made about them. Any property depending on these is `NOT DETERMINABLE FROM CURRENT CODEBASE` at this audit depth.

FILE	LINES
`prod` `aip-observe/src/observed.rs`	1,289
`prod` `aip-observe/src/probe.rs`	915
`prod` `aip-observe/src/attest.rs` (96–894)	799
`prod` `aip-observe/src/{linux,perf,wiretap,sockstate,runtime,continuity,health,fanotify,sched,store,socksend}.rs`	4,101
`prod` `aip-reconcile/src/reconcile.rs` (200–2008)	1,808
`prod` `aip-reconcile/src/{action,result,inputs,ids}.rs`	2,004
`prod` `aip-nexora/src/commitment.rs`	650
`prod` `aip-authorize/src/{expected,decision,actions}.rs`	1,135
`prod` `aip-agent/src/*.rs`	1,612
`prod` `aip-containment/src/{record,actuator,attribution,replay}.rs`	1,100
`importot` all four Rust roots + Python SDK + 12,166 TS LOC	~35,000
`valladder` `airon-verify`	948
`aegis-quantum-ebpf/src/main.rs`	322
`aegis-quantum-userspace/src/af_xdp.rs`	497

The highest-value unread targets, in order: `reconcile.rs:200-2008` (the verdict derivation paths themselves), `observed.rs` (the observation type system the verdicts rest on), and `aip-observe/src/probe.rs` (the untrusted boundary).

8. Finding index

ID	SEV	SUMMARY	BRANCHES AFFECTED
L-1	P0	Signing payload not injective	main, audit, importot, valladder, aipv4
L-2	P0	`expires_at` enforced but not signed	main, audit, importot, valladder, aipv4
L-3	P1	No domain separation in token payloads	main, audit, importot, valladder, aipv4
L-4	P2	`0xFF` / `0x00` separators collide with custom action names	main, audit, importot, valladder, aipv4
L-5	P0	Delegation issuer not bound to previous grantee	**all six**
L-7	P0	Verifier has no clock	main, prod, audit, importot
L-8	P3	Observer-directed verdicts have no structural precondition	prod
L-9	P2	`Reconciliation` constructible outside the engine	prod
L-10	P1	Circuit-breaker connection map unbounded	valladder, aipv4
L-11	P3	`CircuitBreaker::new` unchecked arithmetic, no validation	valladder, aipv4
L-12	P3	Tripped connections retain state indefinitely	valladder, aipv4
L-13	P3	Timestamp monotonicity assumed, not enforced	valladder, aipv4
L-14	P1	Exhaustion test exercises a mock, not the product	valladder
L-15	P1	PQC "exchange" has no counterparty	valladder, aipv4
L-16	P3	Kyber labelled as ML-KEM	valladder, aipv4
L-17	P2	Cryptographic dependencies unpinned	valladder, aipv4

REPORT 02

Six-Branch Differential

Companion to `00_EVIDENCE_BASE.md`. Every figure here is CODE-PROVEN unless labelled otherwise.

1. Topology

ALIAS	HEAD	MERGE-BASE WITH `main`	AHEAD	BEHIND	FILES Δ	+LINES	−LINES
main	`872dbf375838`	`872dbf375838`	0	0	0	0	0
prod	`82da7a6af110`	`872dbf375838`	**103**	0	168	**66,074**	225
audit	`16493c58aed3`	`872dbf375838`	1	0	8	945	0
importot	`6cc439f19016`	`872dbf375838`	1	0	116	35,673	0
valladder	`ae46a3a2f4e2`	**`cd660f6bd626`**	29	**17**	191	22,925	11,622
aipv4	`73bf70cf9e68`	**`cd660f6bd626`**	7	**17**	124	11,136	11,684

`cd660f6bd626` is the repository's **initial commit**. `valladder` and `aipv4` are therefore not branches off main's line of development; they are architectural forks from the repository's origin. Each is 17 commits behind main and shares none of main's subsequent work.

2. Authorship and chronology

BRANCH	COMMITS AHEAD	AUTHORS	DATE SPAN
prod	103	`Claude <noreply@anthropic.com>` (103)	2026-08-23 → 2026-09-06
importot	1	`richardrich999888-rgb` (1)	2026-08-28
valladder	29	`richardrich999888-rgb` (29)	2026-05-31 → 2026-06-03
aipv4	7	`richardrich999888-rgb` (7)	2026-05-31 → 2026-06-03

Finding D-1 (P4, CODE-PROVEN). `valladder` and `aipv4` are the *oldest* work in the repository, not the newest: their commits predate main's tip by roughly three months and fork from the initial commit. The brief's caution against assuming newer code is better is resolved here in the opposite direction — these two branches are historical experiments, and the audit treats them as such on evidence, not on branch names.

Finding D-2 (P2, CODE-PROVEN). All 103 commits on `prod` — 66,074 added lines — carry a single machine author identity. Commit metadata records no independent human review of any commit. This is a governance fact, not a code defect, and it is material to Report 08.

3. Language and size inventory

BRANCH	FILES	.RS FILES	RUST LOC	TS LOC	MD LOC	TOTAL LOC
main	116	50	16,653	0	6,901	27,780
prod	**266**	**139**	**58,268**	0	30,847	93,629
audit	124	50	16,653	0	7,846	28,725
importot	232	100	37,389	12,166	7,820	63,453
valladder	157	66	19,709	0	4,613	46,538
aipv4	92	52	16,466	0	3,359	27,237

`audit` differs from `main` by exactly the 945 lines of `.claude/skills/` added in commit `16493c5` ; its Rust tree is byte-identical to main's, and its test run is identical (143/0/1). It contributes no product code.

4. Crate inventory

4.1 Crates present on `prod` and absent from `main`

CRATE	RUST LOC	WORKSPACE MEMBER
`aip-observe`	7,313	yes
`aip-reconcile`	4,070	yes
`ghost-demo`	1,861	yes
`aip-agent`	1,612	yes
`aip-containment`	1,537	yes
`aip-authorize`	1,194	yes
`aip-nexora`	1,020	yes
`aip-warrant`	638	yes

Growth in pre-existing crates: `aip-core` 5,179 → 6,155; `aip-types` 619 → 949; `aip-crypto` 309 → 394; `aip-test` 329 → 451.

4.2 Crates present on `valladder` / `aipv4` and absent from `main` and `prod`

`aegis-quantum/` is a **third independent Cargo root** (neither `aip-standalone` nor `aip-service` reaches it).

CRATE	VALLADDER LOC	AIPV4 LOC
`aegis-quantum-userspace`	1,674	1,540
`aegis-quantum-circuit-breaker`	757	757
`aegis-quantum-common`	417	405
`aegis-quantum-ebpf`	322	322
`stress-tests`	156	absent
`benchmarks`	1	1

`valladder`'s `aegis-quantum` is a strict superset of `aipv4`'s: it adds `stress-tests/`, `scripts/`, `VALIDATION_LADDER.md`, and `benchmarks/examples/`. `valladder` additionally carries `airon-verify` (948 LOC) as an `aip-standalone` workspace member.

Finding D-3 (`P3`, `CODE-PROVEN`). `AUDIT_CORRECTIONS.md` §1 on `main` states that an `aegis/` component does not exist. That statement is true of `main` and false of the repository: `aegis-quantum/` exists on two branches totalling roughly 3,300 Rust LOC. A reader taking that document as repository-wide would conclude the component was never written.

5. Workspace membership and test reachability

BRANCH	AIP-STANDALONE MEMBERS
main	aip-types, aip-crypto, aip-core, aip-protocol, aip-test, aip-cli, aip-verify, aip-real-tests, banking_demo
prod	+ aip-authorize, aip-observe, aip-reconcile, aip-agent, aip-warrant, aip-nexora, aip-containment, ghost-demo
valladder	aip-types, aip-crypto, aip-core, aip-protocol, **airon-verify**, aip-test, aip-cli, aip-real-tests (no `aip-verify`)
aipv4	aip-types, aip-crypto, aip-core, aip-protocol, aip-test, aip-cli, aip-real-tests (no `aip-verify`)

Finding D-4 (`P2`, `CODE-PROVEN`). `aip-service` is a separate Cargo package on every branch and is a member of no workspace. `cargo test --workspace` run in `aip-standalone` — the command the repository's documentation and CI use — never compiles or tests the HTTP service. The service must be tested by a second, separate invocation. Every unremediated service-tier finding in Report 03 lives in code that the primary test command does not reach.

6. Implementation differential on shared components

Classification per the brief: **A** stronger than main · **B** weaker · **C** complementary · **D** duplicate · **E** superseded · **F** experimental · **G** unsafe · **H** incomplete · **I** incompatible.

6.1 `aip-core/src/capability.rs` — `canonical_token_payload`

BRANCH	SIGNED PAYLOAD COVERS `EXPIRES_AT` ?	ENCODING	DOMAIN TAG	CLASS
main	**no**	raw concatenation	none	baseline
prod	**yes**	prefix-free (`aip_types::canonical`)	`AIP/ScopedToken/v1`	**A**
audit	no	raw concatenation	none	**D** (identical to main)
importot	no	raw concatenation	none	**D**
valladder	no	raw concatenation	none	**D**
aipv4	no	raw concatenation	none	**D**

`prod` replaces the ad-hoc encoder with `put_domain` / `put_str` / `encode_scope` / `put_u64` / `put_opt_u64` and threads `expires_at` through both `issue_scoped_token` and `verify_scoped_token`. Three adversarial tests pin the property (extend, `Some` → `None`, `None` → `Some`), plus injectivity tests for adjacent identifiers, interior-NUL custom actions, and expiry presence.

6.2 `aip-core/src/delegation.rs` — `canonical_delegation_payload` and chain verification

BRANCH	`EXPIRES_AT` SIGNED	TEMPORAL ATTENUATION ENFORCED	ISSUER↔GRANTEE BOUND	CLASS
main	no	no	**no**	baseline
prod	**yes**	**yes** (`AttenuationViolation`)	**no**	**A** (partial)
audit / importot / valladder / aipv4	no	no	no	**D**

`prod` adds `verify_delegation_token_signature` as the single correct hop check, and rule 5: a bounded parent cannot yield an unbounded or later-expiring child. It does **not** add the check `chain[i].issuer_id == chain[i-1].grantee_id`. See Report 03, invariant I-3.

6.3 `aip-protocol/src/verification.rs`

`prod` is main + 64 lines. The whole of the difference is:

- import of `aip_types::EXECUTION_BINDING_VERSION`;
- a new rule **R15 EXECUTION_BINDING** (`prod/…/verification.rs:480-533`), which validates a self-reported binding's version, agent match, and non-degenerate process/executable identity, and which explicitly does not affect the trust floor;
- `check_structure` problem strings widened from `&str` to `String` to report the offending version number.

`check_temporal_validity` is **byte-identical** between main and prod (51 lines, SHA-256 prefix `dbafa0086c1b34af` on both). `VerificationContext` is byte-identical. Classification: **A**, narrowly — R15 adds a well-formedness rule and adds no trust.

6.4 `aip-protocol/src/bundle.rs`

Byte-identical between main and prod (673 lines). `verify_bundle_signature` at `:437` still verifies the manifest against `manifest.signer_public_key` — a key carried by the object being verified. Classification: **D**.

6.5 `aip-service/src/handlers.rs`

BRANCH	LINES	SHA-256 (FIRST 16)
main	400	`b5341baf3c4e0b03`
prod	400	`b5341baf3c4e0b03`
audit	400	`b5341baf3c4e0b03`
importot	400	`b5341baf3c4e0b03`
valladder	631	`3b75c84fafecc369`
aipv4	400	`b99f81cbd3071a80`

Finding D-5 (`P1`, `CODE-PROVEN`). `prod`'s 103 commits and 66,074 added lines did not change one byte of the HTTP request handlers. `keys.rs` is likewise byte-identical (`affac328a2977622`) on main, prod, audit and importot. `IdentityStore::save` is byte-identical on all four branches that have it. Every service-tier and key-at-rest finding carried forward from the base audit is therefore unremediated on `prod`.

`valladder` diverges by +231 lines, adding `issue_passport`, `verify_passport`, `viewer()`, `token_from_headers_or_body`, `unauthorized`, `now_unix_seconds` and `metadata_string`. Classification: **C** (complementary — a passport surface main does not have) and **F** (experimental — it predates the EvidencePacket service layer).

`valladder` and `aipv4` lack `auth.rs`, `authority.rs`, `evidence.rs`, `lib.rs`, `store.rs`, `store/` and `test_support.rs` entirely. They are not reduced versions of main's service; they are earlier ones. Classification: **E** (superseded) for the shared surface.

6.6 `aip-service/src/evidence.rs`

`prod` is main + 47 lines: a trust-boundary doc comment on `verify_request` and one characterization test, `weakness_generate_then_verify_accepts_self_issued_authority` (`prod/aip-service/src/evidence.rs:588-624`). The test asserts that a caller holding only its own key can self-issue an ADMIN root token, have the service seal a packet exercising it, and have `verify_request` return `valid` by naming its own key as the trusted issuer.

Finding D-6 (P2 **,** CODE-PROVEN **).** This is a *pinned known weakness*, not a fix. The test's own comment says the endpoint "is unchanged". Classification: **A** for honesty of documentation, **D** for behaviour.

7. Summary judgment per branch

BRANCH	JUDGMENT	BASIS
prod	**The only branch carrying material new capability.** Class **A** on the cryptographic core, class **D** on the service tier.	§4.1, §6.1–6.6
main	Baseline. Nothing on any other branch is subsumed by it except by age.	§1
audit	Class **D**. Adds tooling only, no product code.	§3
importot	Class **C** and **I**. 35,673 lines in four unbuilt Rust roots plus a Python SDK and 12,166 TS LOC; wire-incompatible chaining (see base audit PR #3 section). Adds zero tests to `aip-standalone` (143/0/1, identical to main).	§3, §5
valladder	Class **F** and **C**. Oldest line; unique `aegis-quantum` and `airon-verify`; carries every main-era cryptographic defect.	§2, §4.2, §6.1–6.2
aipv4	Class **F** and **E**. Strict subset of valladder's contribution.	§4.2

REPORT 03

Security Invariant Matrix

Each invariant is stated as a property the system must hold, then assessed per branch against source, not documentation. "Holds" means the code enforces it; "fails" means an input exists that violates it and is accepted.

Legend: ✓ holds · ✗ fails · ~ partial · **n/a** component absent

1. Matrix

#	INVARIANT	MAIN	PROD	AUDIT	IMPORTOT	VALLADDER	AIPV4
I-1	A token's signature covers its expiry	✗	✓	✗	✗	✗	✗
I-2	A delegation hop's signature covers its expiry	✗	✓	✗	✗	✗	✗
I-3	A delegation hop's issuer is the previous hop's grantee	✗	✓	✗	✗	✗	✗
I-4	A child delegation cannot outlive its parent	✗	✓	✗	✗	✗	✗
I-5	Signing payloads are prefix-free (injective)	✗	✓	✗	✗	✗	✗
I-6	Signing payloads are domain-separated	✗	✓	✗	✗	✗	✗
I-7	The verifier bounds packet age against its own clock	✗	~	✗	✗	n/a	n/a
I-8	A packet cannot be replayed undetected	✗	✗	✗	✗	n/a	n/a
I-9	A bundle's signer key is not supplied by the bundle	✗	✗	✗	✗	n/a	n/a
I-10	Private keys are not written world-readable	✗	✗	✗	✗	✗	✗
I-11	Private key material is not accepted in request bodies	✗	✗	✗	✗	n/a	n/a
I-12	The trust floor is derived, never asserted	✓	✓	✓	✓	✓	✓
I-13	Absence of evidence yields no verdict	n/a	✓	n/a	n/a	n/a	n/a
I-14	A positive verdict cannot be constructed outside the engine	n/a	~	n/a	n/a	n/a	n/a
I-15	Observation content never reaches `Proven` strength	n/a	✓	n/a	n/a	n/a	n/a
I-16	The observer's signing key is unreachable from the observed host	n/a	✓	n/a	n/a	n/a	n/a
I-17	Coverage is re-derived, never read from the claim	n/a	✓	n/a	n/a	n/a	n/a
I-18	Containment requires a warrant the engine can actually issue	n/a	✗	n/a	n/a	n/a	n/a
I-19	Per-connection tracking state is bounded	n/a	n/a	n/a	n/a	✗	✗
I-20	The PQC exchange has a counterparty	n/a	n/a	n/a	n/a	✗	✗

2. Findings

I-1 / I-2 / I-4 / I-5 / I-6 — signing payload integrity

Status on prod: RESOLVED. `CODE-PROVEN`, `TEST-PROVEN`.

`prod/aip-standalone/aip-core/src/capability.rs:221-238` and `prod/…/delegation.rs:415-437` replace raw concatenation with the shared prefix-free encoder and lead each payload with a domain tag (`AIP/ScopedToken/v1`, `AIP/DelegationToken/v1`). `expires_at` is carried with an explicit presence byte via `put_opt_u64`, so `None` and `Some(0)` have distinct preimages.

Tests genuinely exercising the property (all passing, part of the 787):
`test_mutate_expires_at_extend_rejected`,
`test_mutate_expires_at_some_to_none_rejected`,
`test_mutate_expires_at_none_to_some_rejected`,
`test_mutate_delegation_expires_at_extend_rejected`,
`test_mutate_delegation_expires_at_some_to_none_rejected`,
`test_legitimately_signed_hop_outliving_parent_rejected`,
`test_scoped_token_signature_cannot_verify_as_delegation`,
`test_token_payload_adjacent_ids_do_not_collide`,
`test_token_payload_custom_action_interior_nul_unambiguous`.

The last of these is the one that matters most and is easy to overlook: the old encoder terminated custom scope actions with a NUL byte, so a custom action containing an interior NUL was ambiguous with two separate actions. The new encoder length-prefixes, and the test pins all three confusable arrangements apart.

`test_legitimately_signed_hop_outliving_parent_rejected` is the strongest test in the repository's cryptographic core: it constructs a hop that is *validly signed by the genuine delegating key* and still expires later than its parent, and requires the chain to reject it as `AttenuationViolation`. That is enforcement of a policy the signature cannot express, which is the correct shape.

Status on every other branch: OPEN. All five branches other than prod carry main's encoder verbatim.

I-3 — issuer↔grantee binding

> ***RESOLVED on prod, 2026-09-06*** *(commit `8daffe3`), after this audit was filed.* `verify_delegation_chain` *now tracks* `prev_holder` *— the root token's grantee, then each hop's grantee — and refuses a hop whose* `issuer_id` *is not the party that held the parent. The check is unconditional, so every caller including* `aip-service` *inherits it. Independently verified; see the AIRI extension's* `P0_VERIFICATION_ADDENDUM.md` *§1. The original finding follows.*

I-3 — issuer↔grantee binding (as filed: `P0`, OPEN ON ALL BRANCHES)

`CODE-PROVEN`. `prod/aip-standalone/aip-core/src/delegation.rs:179-244`. `verify_delegation_chain` performs five checks per hop: parent JTI linkage, depth monotonicity, scope subset, issuer signature, temporal attenuation. It never checks that `hop.issuer_id` equals the previous hop's `grantee_id` (or, for

hop 0, the root token's `agent_id`). The chain is linked by JTI and by depth, but the *identities* along it are not linked.

Consequence: an attacker holding any key trusted in `issuer_public_keys` can substitute themselves as the issuer of a hop whose `parent_jti` matches, and the chain verifies. Delegation is thereby authenticated but not attributed.

`prod` reduced the surface (a forged expiry now fails as `SignatureInvalid`), but the substitution itself remains accepted. The counter is one comparison per hop; it is absent.

I-7 — verifier clock

> ***PARTLY RESOLVED on prod, 2026-09-06*** *(commit `fdf380c`), after this audit was filed. Rule* ***R16 VERIFICATION_TIME_BOUND*** *adds a verifier-supplied time — never the system clock, so offline and air-gapped verification stay possible — and records the rule as NOT EVALUATED, rather than as a pass, when no time is given. The matrix now reads* **~** *rather than* ✓ *for prod because the bound is opt-in and* ***`aip-service` does not take it****:* `verification_time_ms` *is set nowhere in the service, so* `/verify` *remains unbounded and its handlers decide on* `result.valid` *alone. That residual is tracked as* ***B-1a (*** `P1` ***)****. See* `P0_VERIFICATION_ADDENDUM.md` *§2. The original finding follows.*

I-7 — verifier clock (as filed: `P0`, OPEN ON PROD)

`CODE-PROVEN`. `check_temporal_validity` (`prod/aip-standalone/aip-protocol/src/verification.rs:535-585`) is byte-identical to main's — verified by extracting both bodies and comparing SHA-256 (`dbafa0086c1b34af` on both). It compares packet-internal timestamps against each other only: decision vs. issuance, actions vs. expiry, actions vs. decision. `VerificationContext` (`:29-43`) has no `now_ms` field on either branch.

Consequence: a packet whose every internal timestamp is mutually consistent but set fifty years in the future passes all fourteen rules and reaches `AuthorityBound` with `tampered = false`. This was demonstrated by probe in the base audit and nothing on any branch changes it.

~~**This is the single most important unremediated finding.** R15 on prod adds a *fifteenth* rule and still does not introduce a verifier clock.~~

Superseded. A *sixteenth* rule, R16, introduced exactly that bound three commits later. What survives of this finding is its service-tier half, B-1a.

I-8 / I-9 / I-10 / I-11 — carried forward, unremediated

All four are byte-for-byte unchanged on prod (see Report 02 §6.4, §6.5).

- **I-9**: `bundle.rs:437` verifies a manifest against `manifest.signer_public_key`, a field of the object under verification. Any party can produce a self-consistent bundle.
- **I-10**: `IdentityStore::save` (`aip-core/src/store.rs:138`) calls `std::fs::write` on a JSON document containing private keys, with no `set_permissions` call, on all six branches.

- **I-11**: `aip-service/src/evidence.rs:125,130` accept private seeds as hex in request bodies.

I-13 / I-15 / I-17 — the reconciler's epistemic discipline (prod only)

Status: HOLDS. `CODE-PROVEN`, `TEST-PROVEN`.

- **I-13**: `ReconciliationResult::default()` is `CannotProve` (`aip-reconcile/src/result.rs:30-56`), asserted by `result::tests::default_result_is_cannot_prove`. `reconcile_expectation` documents `None` observer evidence as a legitimate input yielding `CANNOT_PROVE`, never a verdict.
- **I-15**: `precondition_holds` requires `strength == Attested` exactly for every content-derived verdict, with the stated rationale that procfs content is root-forgeable. `Proven` is reserved for signature and chain arithmetic a third party can recompute.
- **I-17**: `recompute_coverage` (`aip-reconcile/src/reconcile.rs:1060-1120`) re-derives coverage from the attested batches rather than reading the collector's `attested_coverage` field, on the stated ground that every input to that field is authored by the host-side probe. `PhantomClaim` cannot leave `finish` without `coverage_recomputed`.

This is the correct design and it is implemented as described.

I-14 — verdict forgeability (`P2`, PARTIAL)

`CODE-PROVEN`. The engine applies two different levels of protection to two parts of the same record.

Protected: `ActionComparison`'s positive variants require an `ActionEvidenceSeal` whose field is private and whose constructors are `pub(crate)` (`aip-reconcile/src/result.rs:312-322`). No caller outside the crate can produce `ActionComparison::Match`.

Unprotected: `Reconciliation` itself (`aip-reconcile/src/result.rs:679-699`) has **all fourteen fields `pub`**. Any downstream crate can construct a `Reconciliation` literal with an arbitrary `result` and `strength`, bypassing `finish()` and therefore `precondition_holds` entirely.

The crate's own consumers demonstrate this: `aip-containment/tests/containment.rs:104` defines a `record(result, strength, …)` helper that does exactly this, and `:132` uses it to build `proven_phantom()` — a `PhantomClaim` at `Proven` strength, which §I-18 proves the engine cannot emit.

The asymmetry is the finding. The authors identified constructor control as the right mechanism and applied it to the action comparison but not to the record that carries the verdict.

I-16 — observer key locality

Status: HOLDS as designed, with a stated deployment obligation. `CODE-PROVEN`. `aip-observe/src/attest.rs:1-30`. `CollectorSigner` holds the key; `crate::probe` has no key field and no signing method;

`ObservationBatch` has no signature field. `sequence` is assigned by the collector, and `attested_at_ms` is the collector's own clock. The signed preimage is domain-separated under `SYNTRIASS/GHOST/OBSERVER_HEAD/v1` and the head is computed, never carried.

The module doc states plainly that the transport proving a batch came from the registered probe is a deployment obligation, not a code property. That is an honest and correct statement of the boundary.

I-18 — containment reachability (`P1`, FAILS ON PROD)

`EXECUTION-PROVEN`. This is the principal new finding of this audit and is traced in full in Report 04 §3. In summary:

`aip-containment/src/contain.rs` gate 3 requires `warrant.response == ResponseClass::Contain`; gate 5 requires `evidence_strength == Proven` (explicit match, no ordering); gate 6 requires a workload-violation result class.

`aip-warrant/src/warrant.rs:213-223` sets `strength_cap = Contain` only for `EvidenceStrength::Proven`, and `response = min3(result_cap, strength_cap, severity_cap)`.

`aip-reconcile/src/reconcile.rs:89-137` caps every workload-violation class (`UnattributedEffect`, `PhantomClaim`, `IdentityDivergence`, `LineageViolation`) at `strength == Attested` **exactly**. The only classes that may carry `Proven` are `SensorIntegrityFailure` and `ContinuityFailure`, whose `result_cap` is `Constrain` and `Alert`.

Therefore no reconciliation the engine can emit yields a `Contain` warrant. An exhaustive 32-cell sweep under a maximally permissive policy confirms it (Report 04 §3.3): `Contain` appears in 4 cells, all 4 requiring a forged `Reconciliation`.

Neither `aip-containment` nor `aip-warrant` ever calls `reconcile_expectation`, `reconcile_observation`, or `reconcile_lineage` — `grep` across both crates returns nothing. 2,286 lines of containment and warrant tests exercise the gates against synthetic records only.

I-19 — circuit-breaker state bound (`P1`, FAILS ON valladder AND aipv4)

`CODE-PROVEN`. `valladder/aegis-quantum/aegis-quantum-circuit-breaker/ src/lib.rs:32-38`. `CircuitBreaker.connections` is a `HashMap<ConnectionKey, ConnectionState>`. `record_event` inserts on every unseen key (`:65-72`). No method removes an entry: `reset` clears one connection's timestamps but leaves the entry; `reset_all` clears the map but nothing calls it on a timer or a bound. There is no LRU, no TTL eviction and no capacity cap.

Per-key memory *is* bounded (the deque cannot exceed `threshold + 1` before tripping), but the *number of keys* is not. An adversary varying the connection tuple allocates one entry per tuple, without limit, in the component whose stated purpose is to defend against a rogue agent "hammering an endpoint in a tight loop."

The test that appears to cover this does not. `stress-tests/tests/lru_exhaustion_test.rs` asserts that a `MockLruSessionMap` evicts to capacity. `MockLruSessionMap` is defined at `stress-

`tests/src/lib.rs:19` — a purpose-built mock in the test crate. The test never constructs a `CircuitBreaker`. It proves a mock LRU works; it proves nothing about the product.

Secondary defects in the same file:

- `new()` computes `window_ms * 1_000_000` with unchecked `u64` multiplication and validates neither `window_ms` nor `threshold` (P3). `threshold = 0` trips on the first event.
- Once `tripped`, the timestamp deque is retained indefinitely (P3).
- `timestamp_ns` is caller-supplied and assumed monotonic; nothing enforces it (P3).

I-20 — PQC exchange counterparty (P1, FAILS ON valladder AND aipv4)

CODE-PROVEN. `valladder/aegis-quantum/aegis-quantum-userspace/src/ pqc.rs:157-165`:

```
pub fn process_packet_event(event: &PacketEvent) -> PqcValidationReport {
    tracing::debug!(/* logs src/dst */);
    hybrid_x25519_kyber768_key_exchange()
}
```

The event is logged and then discarded. `hybrid_x25519_kyber768_key_exchange` (`:90-131`) generates *both* peers' X25519 secrets and the Kyber keypair in the same process, encapsulates to a public key it just created, decapsulates with the private half it still holds, and compares two secrets derived from key material it owns entirely. `secrets_match` is arithmetically always true. There is no peer, no network, no transport, and no write to the BPF session map the module doc describes.

The doc comment is honest — it says "For TRL-4, we simulate the full round-trip" — but the crate description states the component "performs Kyber PQC key exchange", and the type is named `PqcValidationReport`. Read from the outside, this is a latency benchmark presented as a security control.

The combiner itself is correctly built: `hybrid_session_hash` (`:134-142`) is domain-separated (`AIRON-AEGIS-HYBRID-v1`) and length-prefixes both secrets. That construction is sound. It is exercised only against itself.

No adversarial test exists. All 110 aegis-quantum tests pass; none supplies a wrong ciphertext, a tampered public key, or a second party. `test_algorithm_name_is_kyber768` asserts a string literal. `test_100_key_exchanges_all_unique_secrets` asserts RNG non-collision, which is a property of `getrandom`, not of this code.

Supporting defects:

- `pqcrypto-kyber = "0.8"` (resolved `0.8.1`) is a caret range, not pinned, in a cryptographic dependency (P2).
- The report labels its output `"Kyber-768 (ML-KEM)"`. Round-3 Kyber and FIPS 203 ML-KEM are not the same construction; the label conflates them (

P3).

- `test_kyber768_performance_under_5ms` is a wall-clock assertion inside a unit test — nondeterministic and load-sensitive (P3).

3. Invariants that hold and deserve to be said plainly

Auditing is not only enumeration of defects. Four properties are enforced correctly and are unusual enough to be worth naming:

1. **The trust floor is derived from what verified, never asserted by the packet** (I-12), on every branch.
2. **The default verdict is "cannot prove"** (I-13), and the type system enforces it through a single choke point.
3. **Content-derived facts are structurally barred from the highest evidence class** (I-15).
4. **Coverage claims authored by the observed host are re-derived rather than trusted** (I-17).


Properties 2–4 exist only on `prod`.

REPORT 04

Runtime Accountability Trace

Scope: the `prod` branch, which is the only branch carrying the observation → reconciliation → warrant → containment stack.

1. The pipeline as built



The two arrows into `aip-warrant` and `aip-containment` are not exercised anywhere in the repository. See §3.4.

2. Verdict derivation — the choke point

`aip-reconcile/src/reconcile.rs:89-137`. Every verdict, whichever branch of the engine proposes it, passes through one function:

```
fn finish(self, result, strength, reason) -> Reconciliation {
    let (result, strength, reason) = if self.precondition_holds(result, strength) {
        (result, strength, reason)
    } else {
        (CannotProve, Heuristic, InvariantNotSatisfied)     // fail-closed
    };
    …
}
```

This is the correct shape: per-branch logic decides *which* class to propose, and a single independent predicate decides whether the evidence in hand permits it. A proposal that fails is not rejected with an error — it is silently downgraded to "cannot prove", which is the safe direction.

2.1 Preconditions, verbatim in effect

VERDICT	STRUCTURAL REQUIREMENT	STRENGTH
`CannotProve`	none	any
`VerifiedExecution`	`ActionComparison::Match` (engine-only constructor) **and** `IdentityComparison::Match` **and** `action_continuity_verified`	`== Attested`
`UnattributedEffect`	a `CoverageStatement` in the evidence list	`== Attested`
`PhantomClaim`	`coverage_recomputed` **and** `IdentityComparison::NoReference` **and** `availability.is_covered()`	`== Attested`
`IdentityDivergence`	`IdentityComparison::Divergent`	`== Attested`
`LineageViolation`	`LineageComparison::Contradicted`	`== Attested`
`SensorIntegrityFailure`	**none**	`>= Attested`
`ContinuityFailure`	**none**	`>= Attested`

Finding R-1 (`P3`, `CODE-PROVEN`). The two accusation classes aimed at the *observer* — `SensorIntegrityFailure` and `ContinuityFailure` — are the only two with no structural precondition. Their gate is a strength threshold alone, and the strength is supplied by the calling branch rather than derived from a witness in the record. Every verdict aimed at the *workload* must show a structural witness; neither verdict aimed at the sensor must. The asymmetry runs the wrong way for a system whose threat model includes a compromised host that would benefit from discrediting its observer.

2.2 Verdicts that upgrade uncertainty — none found

The brief asks specifically whether the implementation "accidentally upgrades uncertainty into VERIFIED". It does not. Three independent mechanisms prevent it:

1. `ActionComparison::Match` carries an `ActionEvidenceSeal` with a private field and `pub(crate)` constructors; no caller can hand the reconciler a match (`result.rs:312-322`).
2. `VerifiedExecution` additionally requires `action_continuity_verified` , set only by `compare_action` and only when the carrying batch lies wholly inside both the authorized window and the collector's attested coverage epoch.
3. `strength == Attested` is an equality, not a floor, so a caller passing `Proven` for a `VerifiedExecution` is downgraded rather than promoted.

`classify_observer_error` (`reconcile.rs:209-228`) shows the same care in the opposite direction: a signature that does not cover the bytes is `Proven` sensor integrity failure, because it is arithmetic anyone can recompute; an unanchored key or a malformed anchor is *not*, because accusing the observer of tampering on the strength of the verifier's own bad configuration would be a false positive at the highest evidence class. The match is exhaustive so a new variant breaks the build.

This reasoning is correct and is rare in practice.

3. Containment reachability — the principal finding

3.1 The gate chain

`aip-containment/src/contain.rs` , `fn gates` . Seventeen steps; the three that matter here:

```
3. if w.response != ResponseClass::Contain      → Refusal::ResponseNotContain
5. match w.evidence_strength {
       EvidenceStrength::Proven => {}
       other => return Err(Refusal::StrengthBelowProven(other))
   }
6. match w.reconciliation_result {
       UnattributedEffect | PhantomClaim
     | IdentityDivergence | LineageViolation => {}
       other => return Err(Refusal::ResultNotWorkloadViolation(other))
   }
```

3.2 The contradiction

Gate 6 requires one of exactly four result classes. `precondition_holds` pins all four at `strength == Attested` **exactly** (§2.1). Gate 5 requires `Proven` . `Attested != Proven` .

Independently, gate 3 requires `response == Contain` , and `aip-warrant/src/warrant.rs:213-223` grants `strength_cap = Contain` only under `EvidenceStrength::Proven` . `response` is `min3(result_cap, strength_cap, severity_cap)` and is thereafter only lowered.

The two classes that *may* carry `Proven` — `SensorIntegrityFailure` , `ContinuityFailure` — have `result_cap` of `Constrain` and `Alert` respectively, and target the `Observer` , so gates 4 and 6 reject them.

3.3 Exhaustive verification

`EXECUTION-PROVEN` **.** A read-only probe crate was built in scratchpad depending on `prod` 's `aip-reconcile` , `aip-warrant` and `aip-observe` by path. Nothing was written into the repository. It sweeps all 8 results × 4 strengths under a maximally permissive policy (`autonomous_containment = true` , `allow_constrain_on_attested = true` , every result class rated `Critical` , nothing protected, availability `Covered` , evidence list non-empty), and cross-references each cell against `precondition_holds` .

EXHAUSTIVE SWEEP · WARRANT::EVALUATE UNDER A MAXIMALLY PERMISSIVE POLICY

`autonomous_containment = true` · `allow_constrain_on_attested = true` · `severity = Critical for every class`

RECONCILIATION RESULT	HEURISTIC	CORRELATED	ATTESTED	PROVEN
`VerifiedExecution`	Observe	Observe	**Observe**	Observe
`UnattributedEffect`	Alert	Alert	**Constrain**	Contain
`PhantomClaim`	Alert	Alert	**Constrain**	Contain
`IdentityDivergence`	Alert	Alert	**Constrain**	Contain
`LineageViolation`	Alert	Alert	**Constrain**	Contain
`SensorIntegrityFailure`	Alert	Alert	**Constrain**	**Constrain**
`ContinuityFailure`	Alert	Alert	**Alert**	**Alert**
`CannotProve`	**Alert**	**Alert**	**Alert**	**Alert**

Shaded cells are engine-emittable. Faded cells require a hand-built `Reconciliation` that `precondition_holds` cannot produce.
Contain reachable from an engine-produced record: **0 of 32**. Contain reachable only by forgery: **4**.

Finding R-2 (P1, EXECUTION-PROVEN). `aip-containment` cannot actuate on any reconciliation the engine is capable of producing. 1,537 lines of containment implementation, including a real cgroup v2 freezer, and 1,436 lines of containment tests, sit behind a gate that engine output cannot satisfy. The `Contain` response class is dead with respect to the pipeline.

3.4 No end-to-end integration exists

CODE-PROVEN. `grep -rn 'reconcile_expectation\|reconcile_observation\| reconcile_lineage' aip-containment/ aip-warrant/` returns **no matches**. Neither crate has ever called the engine.

`aip-containment/tests/containment.rs:104` defines:

```
fn record(result, strength, availability, evidence) -> Reconciliation {
    Reconciliation { version: RECONCILIATION_VERSION, result, strength, … }
}
```

and `:132`:

```
fn proven_phantom() -> Reconciliation {
    record(PhantomClaim, EvidenceStrength::Proven, covered(), evidence())
}
```

`proven_phantom` is exactly the combination §3.2 proves the engine cannot emit. `EvidenceStrength::Proven` appears 29 times across the containment and warrant crates, always in hand-built records.

The tests are not wrong — they correctly verify that *given* a Proven workload violation, the seventeen gates behave as specified. They simply do not, and cannot, establish that such a warrant is obtainable.

3.5 Interpretation

Two readings are available and the evidence does not settle between them:

- **Fail-safe by construction.** The system is deliberately incapable of autonomous containment, and the gates document an interface reserved for a future evidence class that can reach `Proven`. The warrant doc comment ("Containment is *permitted* — Skill 9 decides whether to act") is consistent with this.
- **An unclosed seam.** The strength ladder was tightened in the reconciler after the containment gate was written against an earlier ladder, and the two drifted apart without an integration test to catch it.

What is *not* in doubt: the property is currently unverified in either direction, because no test crosses the boundary. Whichever reading is correct, the correct remedy is the same — an end-to-end test that drives `reconcile_*` output into `evaluate` into `contain` and asserts the actual outcome. Its absence is the finding.

4. Domain separation inventory

`CODE-PROVEN`. Fifteen distinct domain tags on `prod`, all length-prefixed via `put_domain`:

FAMILY	TAGS
`AIP/`	`AgentIdentityDocument/v1`, `CapabilityGrant/v1`, `DelegationToken/v1`, `LineageProof/v1`, `ReputationVote/v1`, `ScopedToken/v1`, `Test/v1`
`SYNTRIASS/GHOST/`	`CONTAINMENT/v1`, `CONTINUITY_REPORT/v1`, `KERNEL_EVENT/v1`, `OBSERVATION_BATCH/v1`, `OBSERVED_EXECUTION/v1`, `OBSERVED_PROCESS/v1`, `OBSERVER_HEAD/v1`, `OBSERVER_HEALTH/v1`, `RECONCILIATION/v1`, `WARRANT/v1`
`SYNTRIASS/NEXORA/`	`HEAD/v1`, `LEAF/v1`, `PROOF/v1`

A grep will also surface `"AIP/ScopedTokeN/v1"` at `aip-test/src/domain_audit.rs:66`. **This is not a typo in product code.** It is a deliberate near-miss fixture: the test builds two equal-length tags differing in one character and asserts their encodings differ. Reported here because an automated scan would flag it and a reviewer would be right to check.

5. Merkle construction

CODE-PROVEN. `aip-nexora/src/merkle.rs:9-13, 35, 74-75`. Leaves are `0x00 || …` and internal nodes `0x01 || l || r`, matching RFC 6962, and leaves are additionally domain-separated under `SYNTRIASS/NEXORA/LEAF/v1` with a kind code and length-prefixed record bytes. A leaf cannot be mistaken for an internal node, and a record of one kind cannot be replayed as another. This is correct.

REPORT 05

Cryptographic Forensics

1. Primitive inventory

CODE-PROVEN. No primitive is implemented in-tree; every one is a call into a vetted crate.

PURPOSE	PRIMITIVE	CRATE	WHERE
Signatures	Ed25519	`ed25519-dalek 2.1`	`aip-crypto`
Hashing	SHA-256	`sha2 0.10`	`aip-crypto`, all payloads
Hashing (service)	SHA3-256	`sha3`	`aip-service`
Identifier encoding	Base58	`bs58`	AIP-ID derivation
KEM (valladder/aipv4 only)	Kyber-768	`pqcrypto-kyber 0.8.1`	`aegis-quantum-userspace`
ECDH (valladder/aipv4 only)	X25519	`x25519-dalek 2.0.1`	`aegis-quantum-userspace`

No hand-rolled arithmetic, no custom curve code, no bespoke hash. This is the right call and it removes an entire class of risk.

2. Canonical encoding

The single most consequential cryptographic change across the six branches.

2.1 The defect on main (and four other branches)

`main/aip-standalone/aip-core/src/capability.rs:208-231` builds the signing payload by raw concatenation:

```
buf.extend_from_slice(jti);
buf.extend_from_slice(issuer_id.as_bytes());
buf.extend_from_slice(agent_id.as_bytes());
…
buf.push(0xFF);                       // "separator"
…
buf.extend_from_slice(&issued_at.to_le_bytes());
```

Three distinct failures:

1. **Not injective.** `issuer_id = "ab", agent_id = "c"` and `issuer_id = "a", agent_id = "bc"` produce identical bytes. A signature over one is a valid signature over the other.
2. **Not domain-separated.** Nothing distinguishes a `ScopedToken` preimage from a `DelegationToken` preimage. A signature made in one context can be presented in another.
3. **`expires_at` is not covered at all.** The field the verifier subsequently enforces is absent from the bytes the issuer signed.

The custom-action encoder compounds (1): `ScopeAction::Custom(s)` is encoded as `0x01 ‖ s ‖ 0x00`, so a custom action containing an interior NUL is ambiguous with two adjacent actions, and the `0xFF` allowed/denied separator is a byte a custom action can also contain.

2.2 The fix on prod

`prod/aip-standalone/aip-core/src/capability.rs:221-238`:

```
put_domain(&mut buf, SCOPED_TOKEN_DOMAIN);   // "AIP/ScopedToken/v1"
buf.extend_from_slice(jti);                  // fixed 16 bytes
put_str(&mut buf, issuer_id);                // u32-LE length prefix
put_str(&mut buf, agent_id);
encode_scope(&mut buf, scope);
put_u64(&mut buf, issued_at);
put_opt_u64(&mut buf, &expires_at);          // explicit presence byte
```

All three failures are closed. `put_opt_u64` gives `None` and `Some(0)` distinct preimages, which is the difference between "unbounded authority" and "already expired" — the two most consequential values the field can take.

2.3 Codec location

`CODE-PROVEN`. `aip-types/src/canonical.rs` (195 lines) exists **only on prod**. On main the prefix-free codec lives in `aip-protocol/src/canonical.rs`, where `aip-core` — the crate that mints tokens — cannot reach it. Promoting the codec to `aip-types` is what made the fix possible, and it is the correct dependency direction: the encoding is a property of the type system, not of the protocol layer.

`valladder` and `aipv4` have no `aip-types/src/canonical.rs` and carry the main-era encoder verbatim.

3. Signature coverage audit

OBJECT	FIELD	SIGNED ON MAIN	SIGNED ON PROD
`ScopedToken`	`jti`, `issuer_id`, `agent_id`, `scope`, `issued_at`	✓	✓
`ScopedToken`	**`expires_at`**	✗	✓
`DelegationToken`	`jti`, `parent_jti`, `issuer_id`, `grantee_id`, `scope`, `depth`, `issued_at`	✓	✓
`DelegationToken`	**`expires_at`**	✗	✓
`AttestedBatch`	`version, observer_id, key_version, sequence, prev_head, batch bytes`	n/a	✓
`Warrant`	`full preimage under` `SYNTRIASS/GHOST/WARRANT/v1`	n/a	✓
Bundle manifest	manifest bytes	✓	✓
Bundle manifest	**the signer's identity**	✗	✗

The last row is finding I-9. `verify_bundle_signature` (`bundle.rs:437`, identical on both branches) decodes the public key from `manifest.signer_public_key` — a field inside the manifest being verified — and checks the signature against it. The check is therefore self-referential: it establishes that whoever produced the bundle held the private half of a key they also chose to name, which is no constraint at all. Nothing binds that key to a trusted issuer.

4. Key management

`CODE-PROVEN`**, unchanged on every branch.**

- `aip-core/src/store.rs:138` — `IdentityStore::save` serializes the store (which contains private keys) with `serde_json::to_string_pretty` and writes it via `std::fs::write`. There is no `set_permissions`, no umask handling, and no attempt at atomic replace. The file lands with the process umask, typically `0644`.
- `aip-service/src/keys.rs:130` — `load_or_generate` mints a fresh keypair when the configured key file is absent **or when it exists and fails to load**. The second case is the serious one: `:144-151` catches the load error, emits `tracing::warn!("Failed to load key file — generating new keypair")`, and falls through to `Self::generate()` at `:154`. A transient read error, a permissions change, or a partially-written file therefore produces a running service under a **new identity** rather than a startup failure — and every previously issued token signed by the old key becomes unverifiable while the service reports itself healthy. This is fail-open at the identity layer.
- `aip-service/src/evidence.rs:125,130` — private seeds are accepted as hex strings in HTTP request bodies, and so pass through any request

logging, proxy, or trace collector in the path.

Positive. `aip-observe::attest` (`prod`) is the counter-example and shows the authors know how to do this: the signing key is held by `CollectorSigner` off-host, `probe` has no key field and no signing method, `ObservationBatch` has no signature field, and the module doc states the resulting property and its limits explicitly. `key_version` is carried in the signed preimage so verifiers anchor `(observer_id, key_version)` pairs — rotation is designed in rather than retrofitted.

5. Randomness

CODE-PROVEN. `random_jti` (`aip-core/src/capability.rs:205-213`) draws from the OS CSPRNG. `test_nonce_uniqueness_csprng` and `test_sha256_uniqueness_10k_inputs` pass. No `rand::thread_rng` seeding from time, no LCG, no reuse of a nonce across signatures was found on any branch.

One nondeterminism defect, in test code only: `aegis-quantum-userspace` `test_kyber768_performance_under_5ms` asserts a wall-clock bound inside a unit test (P3). The main workspace handles this correctly by contrast — `test_signing_throughput` and `test_verification_throughput` are `#[ignore]` d with the message "wall-clock throughput gate — meaningful only under `cargo test --release` ".

6. Post-quantum posture

valladder / aipv4 only. See Report 03, I-20 for the full finding. In cryptographic terms:

- The **combiner is correct**: `hybrid_session_hash` domain-separates under `AIRON-AEGIS-HYBRID-v1` and length-prefixes both the X25519 and Kyber secrets before hashing. Hybrid construction of this shape is the right pattern.
- The **protocol does not exist**: both peers are simulated in-process, so the combiner is never exercised across a trust boundary.
- The **label is wrong**: output is reported as `"Kyber-768 (ML-KEM)"` . `pqcrypto-kyber` implements round-3 Kyber; FIPS 203 ML-KEM differs from it. Conflating the two in a field named `algorithm` will mislead any downstream compliance claim.
- The **dependency is unpinned**: `pqcrypto-kyber = "0.8"` is a caret range on a cryptographic primitive.

No branch of AIP proper (main, prod) contains any post-quantum code. Any statement that the protocol is quantum-resistant is unsupported by main or prod, and supported on valladder/aipv4 only by a loopback benchmark.

7. Cryptographic verdict by branch

BRANCH	VERDICT
prod	The only branch whose token and delegation signing payloads are sound. Domain-separated, prefix-free, expiry-covering, with adversarial tests that genuinely exercise the properties. Remaining defects (I-3, I-7, I-9) are in *verification logic*, not in encoding.
main	Signing payloads are non-injective, non-domain-separated, and omit the expiry the verifier enforces.
audit / importot	Identical to main.
valladder / aipv4	Identical to main, plus a post-quantum component that measures latency rather than establishing a shared secret with anyone.

REPORT 06

Production Readiness

1. Verdict

BRANCH	CLASSIFICATION	ONE-LINE BASIS
prod	**NOT PRODUCTION READY** — pilot-capable for the observation and reconciliation tiers only	Sound crypto core and verdict engine; unremediated **P0** in packet verification; containment path unreachable and untested end-to-end; HTTP service untouched
main	**NOT PRODUCTION READY**	Signing payloads omit expiry; no verifier clock; every base-audit finding open
audit	not a product branch	tooling only
importot	**NOT ASSESSED AS PRODUCTION CODE**	four Rust roots and a Python SDK that no build or test run in this repository reaches
valladder	**PROTOTYPE**	oldest line; main-era crypto defects; unbounded circuit-breaker state; simulated PQC
aipv4	**PROTOTYPE**	strict subset of valladder

No branch should be described as production ready. `prod` is materially closer than the rest and the gap is specific and enumerable rather than diffuse.

2. Blocking issues on `prod`

Ordered by severity. Each is `CODE-PROVEN` or `EXECUTION-PROVEN`; see the cited report for the derivation.

ID	SEV	ISSUE	WHERE	REPORT
~~**B-1**~~	~~ P0 ~~	~~The verifier has no clock.~~ **CLOSED 2026-09-06** by prod `fdf380c`: rule **R16 VERIFICATION_TIME_BOUND**, a verifier-*supplied* time (never the system clock), with an absent time recorded as NOT EVALUATED rather than a pass. Independently verified.		03 I-7, addendum §2
B-1a	P1	**NEW.** The fix did not reach the service. `aip-service` never sets `verification_time_ms` (0 occurrences); `evidence.rs` builds `VerificationContext::new()` at three sites; `handlers.rs` decides on `result.valid` at five. `/verify` is unbounded.	`aip-service/src/evidence.rs:312,428,546`; `handlers.rs:125,132,140,181,249`	addendum §2.3
B-2	P0	A delegation hop's issuer is never bound to the previous hop's grantee. Any trusted key can substitute itself as issuer of a hop whose `parent_jti` matches.	`aip-core/src/delegation.rs:179-244`	03 I-3
B-3	P1	Containment cannot actuate on any engine-produced reconciliation, and no test crosses the reconcile→warrant→contain boundary.	`aip-containment/src/contain.rs` gates 3/5/6 vs `aip-reconcile/src/reconcile.rs:89-137`	04 §3
B-4	P1	A bundle is verified against a public key the bundle itself supplies.	`aip-protocol/src/bundle.rs:437`	03 I-9, 05 §3
B-5	P1	Private keys are written with default permissions; no `set_permissions`, no atomic replace.	`aip-core/src/store.rs:138`	05 §4
B-6	P1	The service mints a new identity when its key file is missing **or unreadable**, rather than failing to start.	`aip-service/src/keys.rs:130`, fall-through at `:144-154`	05 §4
B-7	P1	Private seeds are accepted in HTTP request bodies.	`aip-service/src/evidence.rs:125,130`	05 §4
B-8	P2	Packet replay is undetected — no nonce or JTI ledger at the packet layer.	`aip-protocol/src/verification.rs` (no replay rule among R1–R15)	03 I-8
B-9	P2	`Reconciliation`'s fourteen fields are all `pub`; any consumer can construct a verdict bypassing `precondition_holds`.	`aip-reconcile/src/result.rs:679-699`	03 I-14
B-10	P2	The primary test command does not reach the HTTP service.	`aip-service` is a member of no workspace, all branches	02 §5
B-11	P3	The two observer-directed verdicts have no structural precondition, only a strength threshold.	`aip-reconcile/src/reconcile.rs:129-131`	04 §2.1

2.1 What B-1 and B-2 meant together — and what closing them changed

> ***Superseded 2026-09-06.*** *Both were closed by prod and independently verified. The analysis below is retained because it explains why they were the two that mattered, and because §2.1a records what the closure did and did not buy.*

Individually each was serious. Together they composed: B-2 let an attacker holding *any* trusted issuer key insert themselves into a delegation chain, and B-1 removed the time bound that would otherwise limit how long a captured or forged chain remained usable. The system's central claim — that an evidence packet establishes *who* authorized an action and *when* — was held by neither half on any branch.

2.1a What the closure bought, and what it did not

B-2 is fully closed. The check is unconditional — inside `verify_delegation_chain`, which every caller reaches — so nothing can be left behind. `aip-service` inherits it without changing a line.

B-1 is closed in the protocol and not adopted by the service. The bound is *opt-in* by design, and correctly so: reading the system clock inside the verifier would break offline and air-gapped verification, and making an unevaluated rule fail would conflate "could not check" with "failed" — the `CANNOT_PROVE` / `FAILED` distinction this codebase is built on. The obligation that design creates is on the consumer, and `aip-service` does not meet it. That is **B-1a**.

The two fixes therefore illustrate the same lesson from opposite sides: an unconditional check propagates for free, an opt-in one propagates only as far as someone remembers to opt in. B-10 — `aip-service` being a member of no workspace — is why nobody did.

`prod` narrowed B-2's surface materially: because `expires_at` is now covered by the hop signature, a forged expiry fails as `SignatureInvalid` rather than being accepted. The identity substitution itself is untouched.

3. What `prod` demonstrably gets right

This is not a bad codebase and the report should not be read as saying so. The following are `EXECUTION-PROVEN` or `TEST-PROVEN`:

1. **787 tests, 0 failures, 0 warnings across 78 test binaries.** The suite is 5.5× main's and includes dedicated adversarial files (`aip-observe/tests/adversarial.rs` 941 lines, `aip-reconcile/tests/adversarial.rs` 1,419 lines, `aip-authorize/tests/adversarial.rs` 671 lines).
2. **The signing payload rewrite is complete and correctly tested** — see Report 05 §2.2. The interior-NUL and adjacent-identifier collision tests show the authors understood the actual failure mode, not just its name.
3. **Temporal attenuation is enforced against a valid signature** (`test_legitimately_signed_hop_outliving_parent_rejected`). Enforcing a policy the signature cannot express is the correct shape.
4. **The reconciler fails closed through a single choke point** and the default verdict is `CannotProve`.

5. **Observer key locality is designed, not asserted**, with the deployment obligation stated explicitly in the module doc rather than glossed.
6. **Coverage claims from the observed host are re-derived, not trusted.**
7. **RFC 6962 Merkle construction with correct leaf/node domain separation.**

4. Test forensics — where passing tests do not establish the property

The brief's rule that tests are not proof unless they exercise the property is load-bearing here. Three cases:

CASE	TEST	WHAT IT ACTUALLY PROVES	WHAT IT APPEARS TO PROVE
Containment	`aip-containment/tests/containment.rs` (1,032 lines) + `live_freeze.rs` (404)	Given a `Proven` workload violation, 17 gates behave as specified	That containment works end-to-end. It cannot: `proven_phantom()` at `:132` is a combination the engine cannot emit, and neither crate ever calls the reconciler.
Circuit-breaker bound	`aegis-quantum/stress-tests/tests/lru_exhaustion_test.rs`	That a `MockLruSessionMap`, defined at `stress-tests/src/lib.rs:19`, evicts to capacity	That `CircuitBreaker`'s state is bounded. It is not — `connections` is an unbounded `HashMap` with no eviction path.
PQC exchange	`aegis-quantum-userspace/src/pqc.rs` tests (12 of them)	That Kyber round-trips against itself in one process, at expected key sizes, within a wall-clock budget	That a quantum-safe session key is established with a peer. There is no peer.

In all three cases the tests pass and are not themselves defective. The gap is between what they assert and what a reader would take them to cover.

5. Coverage and reachability gaps

`CODE-PROVEN`. Roots that no test invocation in this repository reaches:

ROOT	LOC	REACHED BY
`aip-service` (all branches)	~4,200	a separate `cargo test` in that directory only
`importot/orbitaltrust-accountability/rust/ot-accountability-core`	—	nothing
`importot/…/ot-sentinel`	—	nothing
`importot/…/ot-verifier`	—	nothing
`importot/…/ot-mcp-gateway`	—	nothing
`importot/…/python-sdk`	—	nothing
`importot` TypeScript	12,166	nothing
`aipv4/aegis-quantum`	~3,000	nothing (not run in this audit)
`aegis-quantum-ebpf` (both branches)	322	excluded from the workspace; requires nightly + `bpfel-unknown-none`

`importot` adds 35,673 lines and **zero tests to `aip-standalone`** — its run is 143/0/1, identical to main's.

6. Operational hazards

ID	SEV	HAZARD
0-1	P1	`aegis-quantum-circuit-breaker` grows without bound under connection-tuple variation. Remote memory exhaustion in the component whose purpose is DoS defence. (valladder/aipv4)
0-2	P2	`CircuitBreaker::new` performs unchecked `window_ms * 1_000_000` and validates neither `window_ms` nor `threshold`. `threshold = 0` trips on the first event.
0-3	P2	Cryptographic dependencies are caret ranges, not pinned: `pqcrypto-kyber = "0.8"`, `pqcrypto-traits = "0.3"`, `sha2 = "0.10"`, `aya = "0.13"`.
0-4	P3	`aegis-quantum-ebpf` is excluded from its workspace and requires a nightly toolchain and a cross target. It is not built by any CI path visible in the repository.
0-5	P3	A wall-clock assertion inside a unit test (`test_kyber768_performance_under_5ms`) will flake on loaded CI.

7. Recommended gating sequence

Not a remediation plan — the brief forbids fixing during the audit — but the order in which the blockers must be cleared is itself a finding, because some depend on others.

1. ~~**B-1** (verifier clock).~~ **DONE.** Superseded by **B-1a**: adopt the bound in `aip-service`, and have the handlers refuse when `verification_time_checked` is false rather than reading `valid` alone.
2. ~~**B-2** (issuer ↔ grantee).~~ **DONE**, unconditionally.

3. **B-3** (containment reachability). Requires a decision first — is autonomous containment intended to be reachable at all? Until that is answered, no code change is correct. The end-to-end test should be written *before* the answer, because it documents the current behaviour either way.
4. **B-5**, **B-6**, **B-7** (key handling). Independent of each other and of the above.
5. **B-4** (bundle signer key). Requires a trust-anchor design decision analogous to `VerificationContext::trust_issuer`.
6. **B-9** (verdict constructibility) should be resolved before, not after, B-3 — sealing `Reconciliation` changes what the containment integration test can express.
7. **B-10** (workspace membership) is a one-line manifest change and should precede all of the above, because it determines whether fixes to the service tier are exercised by the primary test command at all.

REPORT 07

IP / Patent Engineering

Written for a technically competent, skeptical reader. Nothing here is a legal opinion. The question addressed is narrower and answerable from source: **which structures in this repository are concrete, non-obvious implementations rather than restatements of known practice, and are they described in the code with enough specificity to support a claim?**

Novelty is assessed against what the code *does*, not what the documents say. Where a mechanism is a competent application of known art, that is stated plainly — an audit that calls everything novel is worthless.

1. Candidate structures, ranked

1.1 The single-choke-point verdict precondition — strongest candidate

Location: `prod/aip-standalone/aip-reconcile/src/reconcile.rs:89-183`.

What it is. Every result class the engine can emit passes through one predicate, `precondition_holds(result, strength)`, which asks whether the evidence *visible in the record being emitted* permits the class being proposed. Per-branch logic decides which class to propose; this decides whether it is allowed. A proposal that fails is not an error — it is rewritten to `(CannotProve, Heuristic, InvariantNotSatisfied)`.

Why it is structurally interesting. The separation of *proposal* from *permission*, with a fail-closed rewrite rather than a rejection, means that a future edit which forgets to establish a precondition degrades the verdict instead of asserting one. The code says this explicitly of `coverage_recomputed`:

> *`PhantomClaim` cannot leave `finish` without it, so a future edit that forgets the recomputation downgrades to `CannotProve` instead of asserting non-execution.*

That is a maintenance property expressed in the type and control flow rather than in a comment or a review checklist.

Prior art it must be distinguished from. Policy decision points with obligation checks (XACML and descendants) separate decision from enforcement. Static analysers use lattice joins to keep uncertainty absorbing. What is not standard here is the combination of (a) an epistemic strength ladder in which the top class is reserved for facts a third party can recompute from held bytes, (b) per-class *structural witnesses* rather than scores, and (c) equality rather than threshold comparison on strength, so over-claiming is downgraded as readily as under-claiming.

Specification quality: high. The preconditions are exhaustively matched, the rationale for each is in the doc comments, and the fail-closed direction is stated.

1.2 The two-axis warrant ceiling with no arithmetic — strong candidate

Location: `prod/aip-standalone/aip-warrant/src/warrant.rs:172-280`.

What it is. The permitted response is `min3(result_cap, strength_cap, severity_cap)`, where each cap is an explicit `match`, followed by monotone lowering only:

```
if unavailable || !cited || protected  → response = min(response, Alert)
if response == Contain && !policy.autonomous_containment → Alert
```

Why it is structurally interesting. The module doc states the design constraint directly: "Nothing here computes a product of the two axes." The usual approach — multiply severity by confidence, threshold the product — is precisely what this refuses. A high-severity, low-evidence finding cannot borrow authority from its severity. Each axis independently *caps*; none can raise.

Prior art it must be distinguished from. CVSS-style scoring, risk matrices, and alert-scoring in SIEM products all compose severity and confidence into a scalar. The distinguishing feature is the refusal to compose, plus the enumerated set of monotone lowering conditions (unavailability, absence of citation, protected identity, operator policy), each of which names an epistemic or governance condition rather than a numeric weight.

Specification quality: high, and the ordering of `ResponseClass` is declared with the invariant that every cap is a `min` against it.

1.3 Host-authored coverage re-derivation — strong candidate

Location: `prod/aip-standalone/aip-reconcile/src/reconcile.rs:1043-1120` (`recompute_coverage`).

What it is. The collector signs a batch that includes coverage fields — `claimed_from_ms`, `claimed_to_ms`, `active_mechanisms`, `probe_run_id` — every one of which is authored by the *host-side probe*. The reconciler does not read them. It re-derives, from the attested batches alone, whether the window was continuously sampled by one probe run using a kernel-pushed mechanism, anchoring the end of the window to `health_emitted_at_ms`, a time the collector itself signed.

The reasoning in the doc comment is the substance of the invention:

> *a compromised host [could] manufacture coverage over an interval nothing sampled — and a* `PHANTOM_CLAIM` *is precisely a statement about such an interval.*

Why it is structurally interesting. A signature over host-authored claims authenticates the *collector's relay*, not the *claim's truth*. The distinction is routinely missed. The mechanism — signed relay of an untrusted claim, plus independent re-derivation by the consumer, plus a verdict class that exists only to state a negative about an interval — is a specific and describable arrangement.

Prior art it must be distinguished from. Remote attestation quotes, transparency-log consistency proofs, and audit-log gap detection all touch this. The specific arrangement of *probe (untrusted, keyless) → collector (trusted, signing, off-host, assigns sequence and clock) → reconciler (re-derives coverage rather than reading it)* is what would need to be claimed.

1.4 Keyless probe / off-host attestation boundary — moderate candidate

Location: `prod/aip-standalone/aip-observe/src/attest.rs:1-95`.

What it is. The observed host holds no signing key by construction: `probe` has no key field and no signing method; `ObservationBatch` has no signature field; `sequence` is assigned by the collector; `attested_at_ms` is the collector's clock. The signed head is computed from a domain-separated preimage and never carried, so no supplied hash is trusted. `key_version` is inside the preimage, so rotation is anchored rather than retrofitted.

Assessment. The individual elements are known practice (remote logging with signing at the collector; computed-not-carried digests; key versioning in the preimage). What is well done rather than novel is the *completeness* — the module doc enumerates exactly what an attacker with root on the observed host can and cannot forge, and the type definitions match the claim. This is strong engineering and weaker patent material than 1.1–1.3.

1.5 Temporal attenuation enforced against a valid signature — moderate candidate

Location: `prod/aip-standalone/aip-core/src/delegation.rs:220-231`.

What it is. After authenticity is established, the chain separately rejects a hop whose `expires_at` outlives its parent's — including the `None` case, where an unbounded child of a bounded parent is refused. The ordering is deliberate and documented: a *forged* expiry reports `SignatureInvalid`, a *genuinely over-delegated* one reports `AttenuationViolation`. The two are different accusations and the code keeps them distinct.

Assessment. Capability attenuation and monotone expiry narrowing are established art (macaroons, biscuits, SPKI/SDSI). The refinement worth noting is the error-class separation — distinguishing "this was tampered with" from "your issuer exceeded their authority" is diagnostically and forensically meaningful and is rarely implemented.

2. Structures that are competent but not novel

Stated plainly so the portfolio is not padded:

- **Prefix-free canonical encoding with domain tags.** Correct and necessary (Report 05 §2), but this is textbook — length-prefix everything, lead with a domain separator. Its value here is remedial, not inventive.
- **RFC 6962 Merkle with `0x00` / `0x01` leaf-node separation.** Explicitly implementing a published standard.
- **Ed25519 / SHA-256 usage.** Library calls.
- **The 17-gate containment chain.** Thorough and well-ordered, but a gate sequence is a checklist; the novelty in this area sits in 1.1 and 1.2, which decide what reaches the gates.
- **X25519+Kyber hybrid combiner.** The construction is correct (domain-separated, length-prefixed) and is the recommended pattern; it is not new, and here it is not exercised across a trust boundary at all (Report 03, I-20).

3. Material risks to any filing

These are engineering facts with IP consequences, stated because a patent examiner or an acquirer's technical diligence will find them.

IP-1 (high). The containment path — a plausible subject of any "autonomous accountability enforcement" claim — is **unreachable from the engine** (Report 04 §3, `EXECUTION-PROVEN`). A claim describing an end-to-end system that observes, reconciles, warrants and contains would not be supported by a reduction to practice, because the fourth stage cannot be entered from the third. The demonstrated system stops at `Constrain`.

IP-2 (high). The three strongest candidates (1.1, 1.2, 1.3) exist **only on `claude/codebase-production-readiness-wm6idp`**, a branch that is not merged to `main`. Whatever is filed must be anchored to that branch's tree; `main` does not contain the described mechanisms.

IP-3 (medium). All 103 commits carrying this work have a single machine author identity (Report 02 §2). Inventorship for machine-generated contributions is unsettled and jurisdiction-dependent. This needs a documented human conception and reduction-to-practice record independent of the commit log. That record does not exist in the repository.

IP-4 (medium). `SYNTRIASS`, `NEXORA`, `GHOST` and `AIRON` appear as domain-tag namespaces across the code (`SYNTRIASS/GHOST/…`, `SYNTRIASS/NEXORA/…`, `AIRON-AEGIS-HYBRID-v1`). These are wire-format constants; changing them later is a breaking protocol change. Name clearance should precede, not follow, any public deployment.

IP-5 (low). `aegis-quantum` carries `license = "UNLICENSED"` in its workspace package metadata while depending on third-party crates. This is a licensing hygiene item, not an infringement finding.

4. Drafting guidance implied by the code

If claims are drafted, the following are the load-bearing specifics that distinguish this implementation from the general idea, and they should appear in the specification because they are what makes it non-obvious:

1. Strength comparison is **equality**, not a threshold, for content-derived verdicts — over-claiming is downgraded, not accepted.
2. The top evidence class is defined by **recomputability by a third party from held bytes**, not by source or by confidence.
3. Positive action evidence is **unconstructible outside the engine** (a private field with `pub(crate)` constructors), so a caller cannot supply a match.
4. Coverage is **re-derived from batches**, with the window's end anchored to a time the collector signed.
5. The response ceiling is a **`min` of independent caps**, with an explicit prohibition on composing the axes arithmetically.
6. Observer-directed and workload-directed findings have **different targets** (`ResponseTarget::Observer` vs `Workload`), so a sensor fault can never authorize action against the workload.

Item 6 is worth emphasising: it is a small piece of code and it forecloses a whole class of attack in which compromising the sensor becomes a route to acting on the workload.

REPORT 08

Investor Defensibility

Written on the assumption that it will be read adversarially by someone whose job is to find the gap between the claim and the code. Every figure is reproducible from `00_EVIDENCE_BASE.md`.

1. What actually exists

	FIGURE
Rust LOC on the strongest branch (`prod`)	58,268
Tests passing on `prod`	787 (0 failing, 3 ignored, 78 binaries, 0 warnings)
Tests passing on `main`	143
Crates on `prod` absent from `main`	8
Adversarial-test files on `prod`	4, totalling 3,320 lines
Domain-separated wire tags	15
Branches carrying materially different architectures	4

The engineering is real. 66,074 lines were added to `prod` in fourteen days and the result compiles clean and tests clean. That is not a prototype's test posture.

2. The five things a technical diligence will find

Stated first, without cushioning, because they will surface anyway.

D-1 — The strongest work is not on `main`. `main` is 103 commits behind `claude/codebase-production-readiness-wm6idp`. Every architectural asset described in §3 — the reconciliation engine, the observation layer, the warrant ceiling, the corrected signing payloads — exists only on that unmerged branch. A reviewer cloning the default branch sees 16,653 Rust LOC and 143 tests, not 58,268 and 787.

D-2 — Containment cannot fire. `EXECUTION-PROVEN` (Report 04 §3). The gate chain requires an evidence strength of `Proven` for a workload violation; the reconciliation engine caps every workload violation at `Attested` exactly. An exhaustive 32-cell sweep under a maximally permissive policy returns `Contain` in four cells, all four requiring a hand-forged record. Neither the warrant crate nor the containment crate has ever called the reconciler.

If the product story is "it observes, proves, and then acts", the fourth verb is currently not reachable from the third. The demonstrated ceiling is `Constrain`.

D-3 — Two `P0` defects remain open on every branch. The verifier has no clock (a packet dated fifty years out passes all rules at `AuthorityBound` with `tampered = false`), and a delegation hop's issuer is never bound to the previous hop's grantee (any trusted key can substitute itself into a chain). Both are in the code that carries the protocol's central claim about who authorized what, and when.

Both are small fixes. That is the point: they are small, they are known, and they are open.

D-4 — The HTTP service was not touched. `aip-service/src/handlers.rs` is byte-identical (`b5341baf3c4e0b03`) across main, prod, audit and importot. `keys.rs` likewise. Every service-tier finding — verbatim scope handling, admin fail-open, cross-tenant revoke, private seeds accepted in request bodies, silent key regeneration on a missing key file — is unremediated. The service is also a member of no workspace, so the repository's primary test command never compiles it.

`prod` did add one thing here: a characterization test named `weakness_generate_then_verify_accepts_self_issued_authority`, which asserts that a caller can self-issue an admin token and have the service seal and then validate it. The weakness is documented and pinned. It is not fixed.

D-5 — The quantum-resistance claim is not supported by code. No post-quantum cryptography exists on `main` or `prod`. It exists on `valladder` and `aipv4` — the repository's *oldest* branches, from May–June 2026, forked from the initial commit — and there `process_packet_event` discards the packet event and runs a key exchange between two parties simulated in the same process. `secrets_match` is arithmetically always true. There is no peer, no network, and no write to the session map the documentation describes. The hybrid combiner itself is correctly constructed; it is exercised only against itself.

3. What is genuinely defensible

Also stated without cushioning, because a report that only lists problems is as useless as one that only lists strengths.

The epistemic discipline is real and it is unusual. Three properties, all `CODE-PROVEN` and `TEST-PROVEN` on `prod`:

- The default verdict is "cannot prove". Absence of evidence yields no verdict, enforced through one choke point, with a fail-closed rewrite.
- The highest evidence class is defined as *recomputable by a third party from held bytes*, and content read from the observed host is structurally barred from it because that content is root-forgeable.
- Coverage claims authored by the observed host are re-derived from the attested batches rather than read, because a signature over a host's claim authenticates the relay, not the claim.

Most systems in this space compose a severity and a confidence into a score and threshold it. This one explicitly refuses to: "Nothing here computes a product of the two axes." Each axis independently caps the response; none can raise it. That is a defensible architectural position and it is implemented as stated.

The observer boundary is designed rather than asserted. The probe on the observed host holds no key, has no signing method, and its batch type has no signature field. The collector, off-host, assigns the sequence number and the timestamp. The module documentation states precisely what an attacker with root on the observed host can forge (the content of observations *offered*) and cannot (an attestation of them), and names the remaining transport assumption as a deployment obligation rather than glossing it.

The test posture on `prod` is serious. 787 tests including 3,320 lines of dedicated adversarial tests. The delegation test that constructs a hop *validly signed by the genuine key* which nonetheless outlives its parent, and requires rejection, is the kind of test that only gets written when someone has thought about the actual threat rather than the feature list.

4. Where the tests do not cover what they appear to

Three cases, because diligence will find them and it is better that they appear here first (Report 06 §4 has the detail):

1. **Containment tests** verify seventeen gates against hand-built records that the engine cannot produce.
2. **The circuit-breaker exhaustion test** verifies a mock LRU defined in the test crate; the real `CircuitBreaker` has an unbounded `HashMap` with no eviction path — a remote memory-exhaustion vector in the component whose stated purpose is defending against runaway agents.
3. **The PQC tests** verify a loopback round-trip; none supplies a wrong ciphertext, a tampered key, or a counterparty.

None of these tests is defective. The gap is between what they assert and what their names imply.

5. Governance

All 103 commits on `prod` — 66,074 lines — carry a single machine author identity, over fourteen days. Commit metadata records no independent human review of any commit.

For an engineering-velocity narrative this is a strength. For diligence it raises two specific questions that the repository cannot currently answer: who reviewed the cryptographic changes, and what record establishes human conception for any intellectual property claim (Report 07, IP-3). Neither is a code defect. Both are answerable with process, and the answer should exist before it is asked.

6. Position

The asset is the reconciliation engine and the observation boundary, on one unmerged branch. They encode a defensible and unusually disciplined position on what a system may claim to know and on what evidence.

The liabilities are specific, enumerable, and mostly small. Two `P0` defects that are each a few lines. A containment path that needs a decision before it needs code. A service tier that was never in scope for the work that was done. A post-quantum component that measures latency rather than establishing a secret with anyone.

What would change the position most, in order:

1. Merge `prod` to `main`, or state clearly that `main` is not the product. The current arrangement means the repository's default branch understates the work by 42,000 lines and 644 tests.
2. Close the two P0s. They are small and they sit under the central claim.
3. Answer whether autonomous containment is meant to be reachable, then write the end-to-end test either way. The test documents the answer.
4. Either bring the service tier into scope or scope it out explicitly. Byte-identical handlers across four branches is a decision by default.
5. Stop describing the system as quantum-resistant until a PQC exchange has a counterparty.

None of the five is research. All five are engineering with known shapes.

EXTENSION 09

AIRI Extension Audit

Revision 2 · 2026-09-06 **Scope:** the AI-stack extension on `claude/aip-security-architecture-audit-zpf9b3`, based on `claude/codebase-production-readiness-wm6idp` (prod). **Source of truth for security decisions:** the Six-Branch Forensic Audit (`audit/2026-09-06-master-forensic/`). Branch summaries, README claims and passing tests are not treated as proof of capability — including my own.

Revision history

REV	CHANGE
1	Initial report, filed after the AIRI core, SDK and adapters.
2	Rewritten rather than patched further. Incorporates: prod's two `P0` fixes and their independent verification; one new `P1` (**B-1a**) found by that verification; deliverable **#11** (NEXORA) completed — **rev 1 reported it as done when it was not**; deliverable **#7** (schemas) completed — absent in rev 1; two hygiene defects of my own, found and fixed.

Rev 1's incorrect claim about #11 is recorded in §J and in `DELIVERABLES_COMPLETENESS.md` rather than quietly corrected. A patched document that no longer agrees with itself is an audit defect of its own, which is why this is a rewrite.

Companion documents: `P0_VERIFICATION_ADDENDUM.md` (verification of prod's `P0` fixes) · `DELIVERABLES_COMPLETENESS.md` (the fifteen deliverables, item by item).

A. Files changed

Against the pre-extension merge base `4a87210` : **69 files, 10,609 insertions, 7 deletions.** Of that, 34 files and ~8,500 insertions are prod's own `P0` work, merged and verified but not authored here. The extension's own contribution is **35 files, 2,090 insertions**.

New Rust crate — `aip-standalone/aip-airi` (1,551 src + 2,009 test LOC)

FILE	LINES	PURPOSE
`src/event.rs`	322	`AiriEvent`, canonical preimage, sign, verify
`src/corroborate.rs`	380	Claim ↔ observation comparison; the seal
`src/provenance.rs`	297	Model, tool, subprocess, framework, completion bodies
`src/chain.rs`	179	Per-execution hash chain
`src/integrate.rs`	129	Annotation beside a reconciliation, never inside it
`src/lib.rs`	92	Crate contract
`src/error.rs`	73	AIRI's own error type
`src/ids.rs`	45	Newtype identifiers
`tests/` (7 suites)	2,009	Binding, chain, adversarial, integration, NEXORA, interop, parity

New Python SDK — `sdk/python/vanian_airi` (1,946 src + 1,064 test LOC)

FILE	LINES	PURPOSE
`events.py`	386	Event model and preimage
`emitter.py`	268	Signing, chaining, the nine kinds
`context.py`	268	Execution context across four concurrency edges
`adapters/framework.py`	195	Agent-framework adapter
`identity.py`	165	Fail-closed key loading
`adapters/model.py`	157	Model / inference adapter
`adapters/tool.py`	156	Tool / API / effect adapter
`canonical.py`	128	Prefix-free encoder, byte-identical to Rust
`commitment.py`, `errors.py`, `__init__.py`, `adapters/__init__.py`	223	Commitments, failure modes, exports
`tests/` (5 suites)	1,064	Parity, boundary, context, end-to-end, schema conformance

Documentation (1,059 lines + 2 JSON schemas)

`docs/architecture/AIRI_{SPECIFICATION,THREAT_MODEL,LIMITATIONS,ARCHITECTURE,MIGRATION}.md` · `docs/schemas/{README.md,airi-encoding.md,airi-event.schema.json,airi-bundle.schema.json}`

Modified existing code

FILE	CHANGE
`aip-standalone/Cargo.toml`	`aip-airi` added as a workspace member
`aip-nexora/Cargo.toml`	`aip-airi` dependency (permitted: AIRI's reverse edge is a dev-dependency)
`aip-nexora/src/merkle.rs`	`LeafKind::AiriEvent = 0x09`, appended
`aip-nexora/src/proof.rs`	`AiriBundle`, `Component::Airi = 0x0A`, `NEXORA_PROOF_VERSION` 1 → 2
`aip-nexora/src/verify.rs`	`verify_airi_bundle`, AIRI component verdict
`.gitignore`	Python bytecode caches

`aip-reconcile`, `aip-observe`, `aip-warrant`, `aip-containment`, `aip-authorize`, `aip-core`, `aip-protocol` and `aip-service` are untouched by this extension. Changes in the first seven come from prod's `P0` work; `aip-service` is byte-identical to prod's, which is finding **B-1a**.

B. New protocols and types

Domains and codes

CONSTANT	VALUE	NOTE
`AIRI_EVENT_DOMAIN`	`SYNTRIASS/AIRI/EVENT/v1`	No collision with the 15 existing domains
`AIRI_PARAM_DOMAIN`	`SYNTRIASS/AIRI/PARAM_COMMITMENT/v1`	Not a bare SHA-256
`AIRI_EVENT_VERSION`	`1`	Unknown versions refused, not interpreted
`LeafKind::AiriEvent`	`0x09`	Appended to a frozen set
`Component::Airi`	`0x0A`	Appended after `Commitment`
`NEXORA_PROOF_VERSION`	`1` → **`2`**	v1 packages refused, not reinterpreted

Types

`AiriEvent` (nine kinds) · `AiriPayload` (seven bodies) · `Corroboration` (four outcomes, defaulting to `NotEvaluated`) · `CorroborationSeal` (`#[non_exhaustive]`) · `VerifiedChain` (`#[non_exhaustive]`) · `AiriAnnotation` · `AiriBundle` · `AiriError`.

Result classes added

None. Skill 15 permits new classes "only when the evidence semantics require a new epistemic category", and none did: a claimed-but-unobserved AI action is `PHANTOM_CLAIM`-shaped and an unobservable one is `CANNOT_PROVE`.

C. Security invariants

Thirty-one, all holding. I-A1 to I-A26 are unchanged from rev 1; I-A27 to I-A31 are new with the NEXORA and schema work.

#	INVARIANT	ENFORCEMENT
I-A1	An event cannot describe itself as independently observed	No constructor, field or variant exists
I-A2	"Independent evidence agreed" is unforgeable by the agent	`#[non_exhaustive]` seal
I-A3	AIRI cannot move a reconciliation verdict	No expression producing `ReconciliationResult` / `EvidenceStrength`
I-A4	AIRI cannot reach `Proven`	Same
I-A5	An agent signs only for itself	`signature.signer_id == agent_id`
I-A6	Every binding field is signed	8-field mutation sweep
I-A7	The preimage is injective	Length prefixes, presence bytes
I-A8	AIRI's domain is distinct from all others	Tested against 8 named domains
I-A9	Commitments are not bare SHA-256	Domain-tagged construction
I-A10	Replay/dup/drop/reorder/splice detected	Hash chain
I-A11	Deletion hidden by renumbering detected	`prev_event_hash`
I-A12	No framework is a trust anchor	5-name sweep, identical outcomes
I-A13	Sensor downtime never becomes an accusation	`NotEvaluated` on unavailable
I-A14	A vocabulary gap never becomes an accusation	`ActionClassNotComparable`
I-A15	Corroboration joins on process *instance*, not pid	Full `ProcessInstance`
I-A16	An unbound kernel event does not corroborate	`bound` required
I-A17	Presence never corroborates an act	Exhaustive effect match
I-A18	A model claim is never corroborated by a host observer	`is_externally_observable`
I-A19	The SDK cannot self-prove or self-authorize	14 forbidden names asserted absent
I-A20	Identity loading fails closed, never regenerates	Tested: no key file created
I-A21	Secrets never reach signed bytes	Commitments only
I-A22	Context does not leak between concurrent tasks	`contextvars`
I-A23	Context does not silently cross a thread	Explicit handoff required

#	INVARIANT	ENFORCEMENT
I-A24	The environment carries no key material	Identifiers only
I-A25	Python and Rust preimages are byte-identical	9 vectors, both directions
I-A26	An AIRI leaf cannot be replayed as another kind	Kind code in the leaf preimage
I-A27	**A package cannot choose the key it is judged against**	Verifier's anchor wins; mismatch refused
I-A28	**The AIRI bundle is covered by `proof_id`**	Inside `canonical_bytes`
I-A29	**A broken AIRI bundle cannot lower a re-derived verdict**	Own component verdict; tested
I-A30	**An empty bundle is refused, not vacuously verified**	Explicit check
I-A31	**Published schemas cannot silently drift from the code**	12 conformance tests

I-A27 is the most important of the new five. Without it an assembler could sign a fabricated event chain with its own key, place that key in the bundle, and have every signature check out against the key the package itself supplied. The verifier now uses its own anchor and refuses a package naming a different one.

D. Tests added

143: 81 Rust, 62 Python.

SUITE	TESTS	COVERS
`aip-airi/tests/adversarial.rs`	23	The Skill 15 matrix; each test names the claim and what can be established
`aip-airi/tests/binding.rs`	17	Eight substitution classes; injectivity; domain separation; malformed keys; version
`aip-nexora/tests/airi.rs`	**14**	**Package carriage and offline re-derivation**
`aip-airi/tests/chain.rs`	13	Replay, duplicate, drop, reorder, splice, renumbering; the documented truncation limit
`aip-airi/tests/reconcile_integration.rs`	7	Composition against the **real** reconciler
`aip-airi/tests/nexora_commitment.rs`	5	Leaf-kind separation, order sensitivity, committed-bytes identity
`aip-airi/tests/python_interop.rs`	1	Rust verifies 5 Python-signed events + a bit-flip negative
`aip-airi/tests/parity_vectors.rs`	1 (+1 generator)	Vector stability and distinctness
`sdk/python/tests/test_boundary.py`	17	The forbidden surface; fail-closed identity
`sdk/python/tests/test_context.py`	15	Four concurrency edges, propagation and isolation
`sdk/python/tests/test_schema_conformance.py`	**12**	**Schemas cannot drift from the code**
`sdk/python/tests/test_canonical_parity.py`	11	Byte-identity against 9 Rust-generated vectors
`sdk/python/tests/test_adapters_e2e.py`	7	Full agent run through all three adapters

Skill 15 matrix — 21 rows, 17 directly tested

Four rows are **inherited**: properties of `aip-authorize`, `aip-observe` or `aip-reconcile`, tested there, which AIRI defers to rather than re-implementing — observer-without-expectation, observer continuity break, stale `ExpectedExecution`, expired authority. That is a real limit on this suite's coverage and is stated rather than counted as a pass.

E. Tests passed

RUN	RESULT
Baseline (prod merged, pre-AIRI)	821 passed / 0 failed / 81 suites
After the AIRI core	888 / 0 / 90
After merging prod's `P0` fixes	898 / 0 / 90
After completing #7 and #11	**912 passed / 0 failed / 4 ignored / 91 suites**
Python SDK	**62 passed / 0 failed**
`cargo clippy -p aip-airi --all-targets`	0 warnings

912 − 821 = 91 new Rust tests, of which 10 are prod's own `P0` tests; 81 are this extension's, matching §D.

Flake. `aip-observe` `fa05_live_a_write_by_this_process_is_bound_through_the_kernels_pidfd` failed once during this session under `cargo test --workspace`, which aborted the run and truncated the totals. It passed in three consecutive isolated runs and on the final `--no-fail-fast` run. Pre-existing, live-kernel, races filesystem activity from parallel test binaries. Neither introduced nor fixed here.

Defects this work found in itself

DEFECT	FOUND BY	FIX
Python `identity_bytes` used the wrong domain tag	Parity vectors	`GHOST/ExecutionIdentity/v1`
Python `identity_bytes` omitted the `version` field	Parity vectors	Added
Python `identity_bytes` length-prefixed a fixed-width digest	Parity vectors	Raw append
Deliverable #11 reported done while materially incomplete	Self-audit against the brief	§J
12 `.pyc` build artifacts committed	Staging review	Untracked; `.gitignore` updated
Committed fixture regenerated nondeterministically every test run	Stop-hook dirty-tree check	Execution id and clock pinned; byte-stability asserted

The first three would have produced Python signatures committing to different bytes than the Python side believed it signed. The parity test caught them on its first run, which is the argument for having it.

F. Properties established

Thirty-four in `docs/architecture/AIRI_LIMITATIONS.md` §1 with citations.
The load-bearing ones:

1. An AIRI event that verifies proves **authorship and integrity, never occurrence** — enforced structurally.
2. Cross-agent, cross-execution, cross-expectation, cross-model, cross-framework and cross-kind transplantation all fail.
3. Replay, duplication, drop, reordering and splicing are detected, including deletion hidden by renumbering.
4. **AIRI evidence cannot change the reconciler's verdict or strength** — proven against the real engine, in every corroboration shape, at 150 accumulated corroborations.
5. Sensor downtime and vocabulary gaps never become accusations.
6. Python and Rust agree byte-for-byte, proven in both directions.
7. The SDK is structurally incapable of self-proving or self-authorizing.
8. Identity loading fails closed and never regenerates a key.
9. **A NEXORA package carries AIRI provenance and the offline verifier re-derives it** — signatures, chain and authorship — and **cannot be made to judge it against a key the package chose**.

G. Properties still NOT_DETERMINABLE

#	NOT ESTABLISHED	WHY
N-1	That any claimed action occurred	AIRI is self-report
N-2	That a claimed external effect landed	The caller cannot know
N-3	That a provider served the model requested	Hosted APIs return an unverifiable identifier
N-4	That specific weights were loaded	A self-computed digest describes a file, not runtime memory
N-5	That XLA, a kernel, or a GPU executed anything	Framework telemetry is framework telemetry
N-6	That an agent reported everything it did	Silence leaves an intact chain
N-7	That a chain was not truncated at the head	A prefix of a valid chain is valid
N-8	That `runtime_binding` is true	Self-reported
N-9	That a gateway's report is authoritative	Key lifecycle and transport undefined
N-10	Any post-quantum property	**No PQC exists on this branch.** No such claim is made.
N-11	That AIRI improves detection today	It contributes nothing to a verdict, by design

N-11 remains the honest headline. AIRI makes agent claims **specific, bound, checkable and now portable in a proof package**. It does not yet make the system detect more.

H. Forensic blockers

Both P0s were closed by prod during this session and independently verified (`P0_VERIFICATION_ADDENDUM.md`). That verification found one new `P1` .

ID	BLOCKER	STATUS
B-1	Verifier clock semantics	**CLOSED** in `aip-protocol` (R16)
B-1a	`aip-service` supplies no verification time; `/verify` is unbounded and handlers read `result.valid`	**OPEN (`P1`) — new**
B-2	Issuer/grantee binding	**CLOSED**, unconditional, fully adopted
B-3	Real engine-produced containment path	OPEN
B-4	Bundle signer trust	OPEN
B-5	Private-key storage	OPEN (the SDK refuses to *read* a world-readable key; the writer is unchanged)
B-6	Service key-regeneration	OPEN in `aip-service`; the SDK's own loader fails closed
B-7	Private seed handling	OPEN
B-8	Sealed reconciliation result construction	OPEN
B-9	Packet replay undetected	OPEN
B-10	Service integration (no workspace)	OPEN — **now demonstrably load-bearing: B-1a exists because of it**

Eight open, plus one new `P1` . Seven of the nine sit in or depend on the service tier and its exclusion from the workspace.

AIRI closes none of them. The two closures are prod's work, verified here rather than accepted on the strength of their commit messages.

I. Is production promotion permitted?

NO.

The gap has narrowed materially — from "two P0s under the protocol's central claim" to "one `P1` in the service request path plus the structural exclusion that caused it" — but three reasons stand, any one sufficient:

1. **B-1a is the original `P0` wearing a different hat.** The `/verify` endpoint answers `valid: true` for a future-dated packet, and every handler decides on that boolean. The protocol-layer fix does not reach the service's callers.
2. **AIRI contributes nothing to a verdict.** Deploying it yields signed, checkable, portable claims and no additional detection. That is correct staging, and it means there is nothing to promote *for*.
3. **No production evidence exists.** Every property here is `CODE-PROVEN`, `TEST-PROVEN` or `EXECUTION-PROVEN` in a harness. Corroboration rates against real traffic are unmeasured and the false-positive behaviour of `uncorroborated` on real agent workloads is unknown. A detection signal whose false-positive rate has never been characterised should not be put in front of an operator.

What promotion would require, in order: close **B-1a** and **B-10** together, since the second causes the first; close B-5 to B-7; resolve B-3 and B-8; run stages 1–2 of `AIRI_MIGRATION.md` §5 and characterise the false-positive rate; then build the §4 entry point with an adversarial suite of comparable depth to the existing reconciler's.

No post-quantum claim is made anywhere in this extension, because no post-quantum cryptography is implemented on this branch.

J. Correction to revision 1

Rev 1 §A stated deliverable **#11, NEXORA package/verifier integration**, as delivered. It was not.

What existed: one appended enum variant, `LeafKind::AiriEvent`. An event could be committed as a Merkle leaf. `NexoraProof` had no field to carry AIRI events and `verify.rs` contained no AIRI code — `grep -n 'airi'` across `aip-nexora/src` returned nothing. The package could not carry AI-stack provenance and the offline verifier could not re-derive it, which is most of the deliverable.

How the error was made: I added the leaf kind, wrote five passing tests against it, and let "the tests are green" stand in for "the deliverable is met". The tests were checking a commitment primitive, not the package integration the brief asked for. That is precisely the substitution the master audit's rule 7 exists to catch — *"do not treat tests as proof unless the tests actually exercise the relevant security property"* — committed in my own work while auditing someone else's.

How it was caught: by auditing my own output against the brief's fifteen deliverables rather than against my own summary of them, prompted by a direct question about completeness.

Now closed, with 14 tests, per §B, §C (I-A27 to I-A30) and §D.

Deliverable **#7, canonical schemas**, was absent in rev 1 and is not a correction so much as an omission; it is now closed with `docs/schemas/` and 12 conformance tests.

The general lesson, recorded because it applies beyond this document: a green test suite establishes that the assertions written hold, never that the assertions cover the requirement. Checking the second needs the requirement in hand, not the test list.

EXTENSION 10

P0 Fix Verification

Date: 2026-09-06 (later than the parent report) **Trigger:** `claude/codebase-production-readiness-wm6idp` advanced `dc8caf3 → fdf380c`, claiming to close forensic blockers **B-1** (verifier clock) and **B-2** (delegation issuer↔grantee binding). **Method:** commit messages are claims. Each fix was read at source, its adoption traced through every consumer, and the residual surface stated.

---

1. B-2 — delegation issuer must have held the parent

Status: CLOSED. Fully adopted.

`CODE-PROVEN`. `aip-standalone/aip-core/src/delegation.rs`, `verify_delegation_chain`:

```
// Who currently holds the authority being delegated. The root token's
// grantee holds it first; after each hop, that hop's grantee does.
let mut prev_holder: &str = &root_token.agent_id;
…
    if hop.issuer_id != prev_holder {
        return Err(AipError::LineageInvalid);
    }
    prev_holder = &hop.grantee_id;
```

This is exactly the check the master audit recorded as absent (finding L-5 / B-2). The chain is now linked by identity as well as by `parent_jti` and depth.

`TEST-PROVEN`. `p0_2_a_hop_issued_by_someone_who_never_held_the_parent_is_refused` constructs the right attack: Mallory, a legitimate agent whose key the verifier holds, signs a well-formed hop — correct `parent_jti`, correct depth, attenuated scope, genuine signature over its own payload — off a root token issued to Alice. Previously it verified. Now it is `LineageInvalid`.

Why this one is fully closed

The fix is **unconditional**: a check inside `verify_delegation_chain`, which every caller reaches. There is no opt-in, so no consumer can be left behind. `aip-service` gets it without changing a line.

---

2. B-1 — verifier-supplied verification-time bound

Status: CLOSED in `aip-protocol`. NOT ADOPTED in `aip-service`.

2.1 What was built, and it is well built

`CODE-PROVEN`. `aip-protocol/src/verification.rs` adds rule **R16 VERIFICATION_TIME_BOUND** plus two context fields:

```
pub verification_time_ms: Option<u64>,
pub future_tolerance_ms: u64,
```

Three design decisions are correct and worth naming:

1. **The time is supplied, never read from the system clock.** An offline verifier, an air-gapped verifier and a test all need to state what "now" means to them. Reading `SystemTime::now()` inside the verifier would have made the rule untestable and wrong for delayed verification.
2. **Absent a time, R16 is recorded as NOT EVALUATED, not as a pass.** The report carries `evaluated: bool` per rule, `verification_time_checked`, and `not_evaluated()`.
3. **The bound is not "the authority must still be valid now".** A historical packet stays verifiable after its tokens expire — offline verification depends on that — and whether the authority was valid *at decision time* remains R10's question. Conflating the two would have broken archival verification, and the test `p0_1_a_historical_packet_stays_verifiable_after_its_authority_expires` pins it.

`aip-verify` surfaces the gap to a human: `main.rs:224` prints `note: <rule> was NOT evaluated — <detail>` for every unevaluated rule.

(An earlier pass of this addendum provisionally recorded the CLI as silent. That was wrong — the grep used the wrong symbol. Corrected here rather than removed, because a withdrawn finding is itself a finding about the audit.)

2.2 The residual, stated precisely

`valid` is computed as:

```
let valid = e.checks.iter().all(|c| !c.evaluated || c.pass);
```

An unevaluated rule therefore does not make a report invalid. Prod's own test asserts this openly:

> `p0_1_without_a_bound_the_rule_is_not_evaluated_rather_than_passed` `assert!(report.valid);` *"Still valid — an unevaluated rule is not a failure — but a consumer can tell the difference, which is the whole point."*

This is the right decision, not a defect. Making `valid` false for an unevaluated rule would conflate "could not check" with "failed", which is precisely the `CANNOT_PROVE` / `FAILED` distinction the whole codebase is built on. The obligation it creates is on the consumer: reading `.valid` alone is misuse of the API, in the same way that reading `Corroboration::is_corroborated() == false` as "nothing wrong" would be.

2.3 The finding: the service tier did not adopt it

`CODE-PROVEN`.

SITE	CONSTRUCTION	VERIFICATION TIME
`aip-service/src/evidence.rs:312`	`VerificationContext::new()`	never set
`aip-service/src/evidence.rs:428`	`VerificationContext::new()`	never set
`aip-service/src/evidence.rs:546`	`VerificationContext::new()`	never set

`grep -rn 'verification_time_ms' aip-service/src/` returns **0 occurrences.**

And the handlers consume the bare boolean:

```
aip-service/src/handlers.rs:125   if result.valid …
aip-service/src/handlers.rs:132   if result.valid …
aip-service/src/handlers.rs:140   (result.valid, result.reason)
aip-service/src/handlers.rs:181   if !parent_result.valid …
aip-service/src/handlers.rs:249   if !root_result.valid …
```

`git diff origin/claude/codebase-production-readiness-wm6idp HEAD -- aip-service/` is **empty**: the service is byte-identical to prod's, i.e. untouched by the `P0` work.

Consequence. The `/verify` HTTP endpoint applies no temporal bound. A packet dated arbitrarily in the future returns `valid: true` through the API, with `verification_time_checked: false` present in the report but not consulted by any handler. The protocol-layer fix does not reach the service's callers.

2.4 New blocker

ID	SEV	FINDING
B-1a	`P1`	`aip-service` never supplies `verification_time_ms`, so every service-side verification is unbounded, and `handlers.rs` decides on `result.valid` without consulting `verification_time_checked`.

Root cause is structural and already documented. This is the same cause as master-audit findings D-5 and B-10: `aip-service` is a member of no workspace, so `cargo test --workspace` never compiles it and a fix landed in `aip-protocol` does not propagate to it by default. B-1a is the first concrete harm from that arrangement.

Remedy (not applied — this is an audit, and the service tier is outside the AI-stack extension's scope):

1. Set `ctx.verification_time_ms` in `verify_request` from a service-supplied clock, with `future_tolerance_ms` from configuration.
2. Have the handlers refuse when `!verification_time_checked`, or make the absence explicit in the API response.
3. Bring `aip-service` into the workspace so the next protocol change is compiled against it (B-10).

---

3. Revised blocker register

ID	BLOCKER	BEFORE	NOW
B-1	Verifier clock semantics	OPEN (P0)	**CLOSED in `aip-protocol`**
B-1a	Service applies no temporal bound	—	**OPEN (P1), new**
B-2	Issuer/grantee binding	OPEN (P0)	**CLOSED, fully adopted**
B-3	Real engine-produced containment path	OPEN	OPEN
B-4	Bundle signer trust	OPEN	OPEN
B-5	Private-key storage	OPEN	OPEN
B-6	Service key-regeneration	OPEN	OPEN
B-7	Private seed handling	OPEN	OPEN
B-8	Sealed reconciliation result construction	OPEN	OPEN
B-9	Packet replay undetected	OPEN	OPEN
B-10	Service integration (no workspace)	OPEN	OPEN — **now demonstrably load-bearing**

Both P0s are closed. That is the significant change: the two defects sitting directly under the protocol's central claim about *who* authorized *what* and *when* are fixed, and fixed well.

Eight blockers remain, plus one new P1. Seven of the nine now sit in or depend on the service tier and its exclusion from the workspace.

---

4. Effect on the AIRI extension

None. `aip-airi` does not consume `VerificationContext` and does not verify packets; it verifies its own events and corroborates against observer batches. Post-merge:

SUITE	RESULT
`aip-airi`	**67 passed / 0 failed**
Python SDK	**50 passed / 0 failed**
Workspace	see the parent report's E section, re-run post-merge

The extension's own conclusion is unchanged, and its central caveat now reads slightly differently: AIRI still contributes nothing to a verdict, but the substrate it would eventually contribute to is two P0s sounder than it was.

---

5. Promotion

Still **NO**, and for a narrower reason than before.

The two P0s that made promotion obviously premature are closed. What remains:

1. **B-1a is a `P1` in the request path.** A service that answers `valid: true` for a future-dated packet is the original `P0` wearing a different hat, for any consumer that reads the boolean — which is every handler today.
2. **B-3 and B-8 remain**: containment is still unreachable from engine output, and `Reconciliation`'s fields are still all `pub`.
3. **B-10 is now demonstrably load-bearing** rather than theoretical. B-1a exists because of it.
4. **AIRI still has no production evidence.** Unchanged.

The gap has narrowed from "two P0s under the central claim" to "one `P1` in the service path plus a structural exclusion that caused it". That is real progress and worth saying plainly.

EXTENSION 11

Deliverables Completeness

Answers one question: **do we have everything the brief asked for?**

Written after an audit of my own output. Two items were incomplete when the extension audit was first filed, and one of those I had reported as done. Both are now closed; the over-claim is recorded rather than quietly fixed.

The fifteen deliverables

#	DELIVERABLE	STATUS	WHERE
1	AIRI protocol specification	**DONE**	`docs/architecture/AIRI_SPECIFICATION.md`
2	Threat model	**DONE**	`docs/architecture/AIRI_THREAT_MODEL.md`
3	Python SDK / reference boundary	**DONE**	`sdk/python/vanian_airi/`
4	One reference agent-framework adapter	**DONE**	`adapters/framework.py`
5	One model / inference adapter	**DONE**	`adapters/model.py`
6	One tool / API adapter	**DONE**	`adapters/tool.py`
7	Canonical schemas	**DONE** *(was missing)*	`docs/schemas/`
8	Cryptographic binding tests	**DONE**	`aip-airi/tests/binding.rs` — 17
9	Adversarial substitution / replay tests	**DONE**	`adversarial.rs` 23, `chain.rs` 13
10	Reconciliation integration	**DONE, scoped**	`integrate.rs`, `reconcile_integration.rs` — 7
11	NEXORA package / verifier integration	**DONE** *(was partial, over-claimed)*	`aip-nexora/{proof,verify}.rs`, `tests/airi.rs` — 14
12	Limitations / evidence classification	**DONE**	`docs/architecture/AIRI_LIMITATIONS.md`
13	Migration / versioning plan	**DONE**	`docs/architecture/AIRI_MIGRATION.md`
14	Architecture diagrams / docs	**DONE**	`docs/architecture/AIRI_ARCHITECTURE.md`
15	Final audit report	**DONE**	`AIRI_EXTENSION_AUDIT.md` + two addenda

The two gaps, and what they were

#11 NEXORA — I over-claimed this

What I reported: "NEXORA package/verifier integration — done."

What actually existed: one appended enum variant, `LeafKind::AiriEvent`. An AIRI event could be committed as a Merkle *leaf*. But `NexoraProof` had no field to carry AIRI events at all, and `verify.rs` contained no AIRI code — `grep -n 'airi' aip-nexora/src/{proof,verify}.rs` returned nothing.

So the proof package could not carry AI-stack provenance, and the offline verifier could not re-derive it. That is most of deliverable #11, and calling it done was

wrong.

Why I got it wrong: I added the leaf kind, wrote five passing tests against it, and let "the tests are green" stand in for "the deliverable is met". Exactly the substitution the forensic discipline exists to catch — `aip-nexora/tests/airi.rs` was checking a commitment primitive, not the package integration the brief asked for.

Now closed:

- `AiriBundle { agent_id, agent_public_key, events }` on `NexoraProof`
- `Component::Airi = 0x0A`, appended; `NEXORA_PROOF_VERSION` 1 → 2
- Inside `canonical_bytes`, so the bundle is covered by `proof_id` — otherwise an assembler could swap the AI-stack evidence without changing the id any commitment was taken over
- `verify_airi_bundle` re-derives every signature and re-walks the chain
- 14 tests, including the one that matters most: **a package cannot choose the key it is judged against.** An assembler that signs a fabricated chain with its own key and puts that key in the bundle is refused, because the verifier's anchor wins.

#7 Canonical schemas — simply absent

No formal schema artifact existed. Now `docs/schemas/` carries `airi-event.schema.json`, `airi-bundle.schema.json` and the normative `airi-encoding.md`, with `test_schema_conformance.py` (12 tests) checking the codes, domains and versions in the docs against the code so they cannot drift.

Every schema states, in its own `description`, that it is **non-normative** and that a verifier must check the byte preimage. A schema that let someone believe validating JSON was verifying a signature would be worse than no schema.

Requirements beyond the numbered list

REQUIREMENT	STATUS
AIRI event model — 9 named types	**DONE**, all nine
Framework-neutral, thin adapters	**DONE**; `no_framework_is_a_trust_anchor` sweeps five names
Bind agent / execution / expectation / model / tool / framework / parent	**DONE**, all in the signed preimage
No secrets or raw payloads in evidence	**DONE**, commitments only, tested with a synthetic secret
Domain separation, prefix-free, versioned	**DONE**, two new domains, no collision with the existing fifteen
Substitution / tamper / replay tests	**DONE**, 53 across three suites
Python context propagation, 4 edges	**DONE**, 15 tests including a real subprocess
SDK must-nots (6 in Skill 12)	**DONE**, 5 by absence + introspection, 1 by behaviour
Declared ≠ selected ≠ executed ≠ effect	**DONE**, tables in the spec and limitations
No second reconciliation system	**DONE**, annotation only; non-escalation proven against the real engine
Default posture stays CANNOT_PROVE	**DONE**, tested
Only add result classes if needed	**DONE — none added**, every outcome maps onto the existing vocabulary
Offline verifier re-derives, refuses non-derivable	**DONE**, extended to AIRI
No PQC claims	**DONE — none made**

Skill 15 test matrix — 21 rows

Seventeen are directly tested with AIRI evidence present. Four are **inherited**: they are properties of `aip-authorize`, `aip-observe` or `aip-reconcile`, tested there, and AIRI defers to them rather than re-implementing the check.

INHERITED ROW	OWNED BY	WHY NOT RE-TESTED HERE
observer sees execution without matching expectation	`aip-reconcile` `UNATTRIBUTED_EFFECT`	AIRI adds no path to it
observer continuity break	`aip-observe`	AIRI reads `ObservationAvailability` and returns `NotEvaluated`
stale ExpectedExecution	`aip-authorize` `TemporalStatus`	AIRI carries `decision_id`, does not adjudicate it
expired authority	`aip-core`	same

That is a real limit on this suite's coverage and is stated rather than counted as a pass.

What is deliberately NOT done

Neither is an oversight; both are recorded with the reasoning.

#	NOT DONE	WHY
1	`reconcile_airi_claim` — an entry point letting an uncorroborated AIRI claim reach `PHANTOM_CLAIM`	A new way to accuse. The existing phantom-claim path needed recomputed coverage, a sealed identity comparison and 1,419 lines of adversarial tests before it could say "this did not happen". Four prerequisites in `AIRI_MIGRATION.md` §4.
2	Fixing **B-1a** (`aip-service` supplies no verification time)	Outside the extension's scope, and patching during an audit pass is what the forensic discipline forbids. Remedy specified in `P0_VERIFICATION_ADDENDUM.md` §2.4.

Evidence

RUN	RESULT
`cargo test --workspace --no-fail-fast`	**912 passed / 0 failed / 4 ignored / 91 suites**
Python SDK	**62 passed / 0 failed**
`cargo clippy -p aip-airi --all-targets`	0 warnings

Baseline before any of this work: 821 / 81 suites. **+91 Rust tests, +62 Python.**

`fa05_live_a_write_by_this_process_is_bound_through_the_kernels_pidfd` (`aip-observe`) flaked once during this session and passed in three consecutive isolated runs and on the final full run. Pre-existing, live-kernel, races filesystem activity from parallel test binaries. Not introduced here and not fixed here.

So: do we have everything?

The fifteen deliverables: yes, now. Two were not there when I first said they were, and #11 I had actively mis-reported.

Production promotion: still no, and unchanged by any of this. Eight forensic blockers remain open plus B-1a, AIRI still contributes nothing to a verdict by design, and there is no production evidence for its false-positive behaviour. Completeness of the deliverables and readiness for production are different questions, and only the first one is now answered yes.

REFERENCE 12

AIRI Specification

Status: implemented, not promoted. See `AIRI_LIMITATIONS.md` for what is established and what is not, and `AIRI_MIGRATION.md` for versioning.

1. What AIRI is

A framework-neutral schema for what an AI agent's own runtime *says* it did: which model it asked for, which tool it invoked, with which parameters, under which authorization, in which process.

One schema covers LangChain, LangGraph, LlamaIndex, AutoGen, CrewAI, OpenAI-style tool calling and bespoke runtimes. Adapters are thin translators into these types. **No framework is a trust anchor**, and nothing in the implementation branches on a framework's name to grant anything.

2. What AIRI is not


An AIRI event is **not evidence that anything happened**. It is evidence that the agent said so.

The signing key belongs to the agent. The clock belongs to the agent. The process that emits the event is the process under scrutiny. Every guarantee is of the form *"this statement was made by this agent about this execution and has not been altered since"* — never *"this occurred"*.

This is enforced structurally, not by convention:

GUARANTEE	MECHANISM
An event cannot claim independence	No constructor, field or enum variant exists by which it could
"Independent evidence agreed" is unforgeable	`CorroborationSeal` is `#[non_exhaustive]`; only `corroborate()` can produce one
AIRI cannot move a verdict	`corroborate` and `integrate` contain no expression producing a `ReconciliationResult` or an `EvidenceStrength`

3. Position in the chain



The two inputs are asymmetric on purpose. Reconciliation is where the asymmetry is spent.

4. Event model

Nine kinds. The discriminant is inside the signed preimage, so an event of one kind cannot be re-presented as another.

KIND	CODE	PAYLOAD	EXTERNALLY OBSERVABLE?
`AgentExecutionStarted`	`0x01`	`AgentStart`	no
`ModelInvocationRequested`	`0x02`	`ModelProvenance`	no
`ModelInvocationObserved`	`0x03`	`ModelProvenance`	no
`ToolInvocationRequested`	`0x04`	`ToolInvocation`	**yes**
`ToolExecutionReported`	`0x05`	`ToolReport`	**yes**
`SubprocessExecution`	`0x06`	`SubprocessReport`	**yes**
`ExecutionCompleted`	`0x07`	`Completion`	no
`ExecutionFailed`	`0x08`	`Completion`	no
`ExecutionContextPropagated`	`0x09`	`ContextPropagation`	no

`ModelInvocationObserved` is named "observed" by the specification and **is not independent observation**. The observer is the framework, inside the process under scrutiny. It carries no more weight than any other self-report, and `corroborate` will not accept it as corroboration of itself.

"Externally observable" means a host observer could in principle see a matching kernel event. A hosted-model inference leaves a socket, but that socket is the *tool*

layer's evidence; attributing it to the model layer would count one fact twice.

5. Binding fields

Every event carries:

FIELD	TYPE	MEANING
`version`	`u16`	Structure version. An unknown value is refused, not guessed.
`agent_id`	`String`	AIP-ID. Must equal `signature.signer_id` — an agent signs only for itself.
`execution_id`	`[u8;16]`	The AIRI execution instance.
`parent_execution_id`	`Option<[u8;16]>`	Application lineage, for worker/subprocess handoff.
`decision_id`	`Option<[u8;16]>`	The `ExpectedExecution` this run claims. `None` is a statement a verifier can act on.
`sequence`	`u64`	Position in this execution's chain, from 0.
`prev_event_hash`	`[u8;32]`	SHA-256 of the previous event's preimage; zero at sequence 0.
`emitted_at_ms`	`u64`	The agent's own clock. Carried, never trusted to order or place anything.
`framework`	`FrameworkIdentity`	Name, version, adapter version. Provenance, not authority.
`runtime_binding`	`Option<ExecutionBinding>`	The process the agent *believes* it is in. Self-reported.
`payload`	`AiriPayload`	One of the nine bodies.
`signature`	`Signature`	Ed25519 over the preimage below.

Three lineages kept apart

- **identity lineage** — `aip-agent`, which agent document descends from which
- **authority lineage** — delegation chains, who granted what to whom
- **application lineage** — `parent_execution_id`, which run spawned which

Nothing in AIRI reads `parent_execution_id` to widen scope. Being spawned by a run confers no authority; a child carries the same expectation or none.

6. Canonical encoding

```
preimage = put_domain("SYNTRIASS/AIRI/EVENT/v1")
         || put_u16(version)
         || put_str(agent_id)
         || execution_id                      (fixed 16, length-prefixed)
         || put_opt_bytes16(parent_execution_id)
         || put_opt_bytes16(decision_id)
         || put_u64(sequence)
         || prev_event_hash                   (fixed 32, length-prefixed)
         || put_u64(emitted_at_ms)
         || framework.encode()
         || put_opt(runtime_binding.identity_bytes())
         || put_u8(kind_code) || payload.encode()
```

Every variable-length field is length-prefixed (u32 LE) and every optional field carries a presence byte, so the encoding is injective. The domain tag leads, so an AIRI signature cannot verify as a `ScopedToken`, a `DelegationToken`, an observer head, a reconciliation record or a warrant, and none of theirs can verify here.

Domains introduced

DOMAIN	USE
`SYNTRIASS/AIRI/EVENT/v1`	Event signing preimage
`SYNTRIASS/AIRI/PARAM_COMMITMENT/v1`	Parameter, prompt, output and argv commitments

Neither collides with any of the fifteen domains already in the repository.

7. Commitments, not payloads

Prompts, tool arguments, model outputs and argument vectors never enter an event. Only commitments do:

```
commit(x) = SHA-256( put_domain("SYNTRIASS/AIRI/PARAM_COMMITMENT/v1") || put_bytes(x) )
```

Domain-separated rather than a bare SHA-256, so a digest computed elsewhere in the system — a packet hash, an observer head, a Merkle leaf — cannot be presented as a parameter commitment.

The Python SDK commits JSON with `sort_keys` and fixed separators, so the same logical arguments commit identically regardless of dict ordering. Without that, a verifier comparing two commitments of identical arguments would see a substitution that never happened.

8. Chains

Events for one execution form a hash chain. `prev_event_hash` is the SHA-256 of the previous event's signed preimage.

Detected: replay, duplication, drop, reordering, splicing from another execution or agent, and deletion hidden by renumbering.

Not detected: truncation at the head. A prefix of a valid chain is a valid chain, and nothing inside the chain distinguishes "the run ended here" from "the rest was withheld". Closing this needs either an observer or a verifier that insists on a signed completion. The limit is tested (`chain.rs::dropping_the_last_event_is_not_detectable_and_that_is_documented`) rather than papered over.

9. Corroboration

`corroborate()` compares one claim against collector-signed observation.

OUTCOME	MEANING
`NotEvaluated(reason)`	Not compared. Carries why, so silence is never read as "clean".
`Corroborated(seal)`	Independent evidence covering the window and the instance is consistent with the claim.
`Uncorroborated{reason}`	The observer covered the claim and did not see it. **The epistemically valuable case.**
`Contradicted{detail}`	Observation contradicts the agent's own account.

Order of evaluation, each step failing toward "cannot say":

1. Is this kind externally observable? → `NotExternallyObservable`
2. Is there a runtime binding to join on? → `NoRuntimeBinding`
3. Did the observer declare coverage? → `ObserverUnavailable`
4. Do any batches overlap the window? → `WindowNotCovered`
5. Is the action class mappable? → `ActionClassNotComparable`
6. Does any observation refer to the claimed instance? → `InstanceNotObserved`
7. Does any observation match the class? → `Corroborated` / `ActionClassAbsent`

Step 5 matters more than it looks: an unmappable action class returns `NotEvaluated` , never `Uncorroborated` . Turning a vocabulary gap into a phantom claim would be the worst false positive this system can make.

10. The three tool layers

```
1. Requested invocation    ToolInvocationRequested
2. Runtime execution       ToolExecutionReported
3. External effect         — no event asserts this —
```

An HTTP 200 is evidence of layer 2. A proxy, a stub, a replayed cassette, a compromised client, a load balancer that acknowledged and dropped, or a database that returned success and rolled back all produce a 200. There is no method in the SDK and no variant in the Rust types that asserts layer 3, because the process that made the call cannot know.

Only independent observation can speak to layer 3, and even then the ceiling is `Attested` — content read from the observed host is root-forgeable.

11. NEXORA

Two carriage points, both live.

As a Merkle leaf. An AIRI event commits under `LeafKind::AiriEvent` (code `0x09`), appended to the frozen set rather than renumbering it.

As a proof component. `NexoraProof` (package version **2**) carries an optional `AiriBundle` under `Component::Airi` (`0x0A`): the agent id, the key the package says signed the events, and the events themselves in emission order.

In both cases what is committed is the event's **signing preimage** — the exact bytes the agent signed — so a verifier checks one artefact rather than trusting a re-serialisation round-trip.

What the offline verifier does with it

`verify_nexora_proof` **re-derives**:

1. every event's signature, against the key the *verifier* anchored;
2. the chain, re-walked from the package's own bytes;
3. that every event's `agent_id` is the bundle's.

The result is a `ComponentVerdict` — `Verified`, `Absent`, or `Unverifiable(reason)` — plus `airi_events_verified`. It is never an upgrade to any other component.

The package cannot choose the key it is judged against. If the verifier anchored a key for this agent, that key is used and the package's must match it; a package naming a different key is refused with "does not anchor", not quietly verified against the one it supplied. Without that rule an assembler could sign a fabricated chain with its own key, put that key in the bundle, and have every signature check out.

A `Verified` verdict reached under a *self-supplied* key (verifier anchored none) means "internally consistent", which is weaker than "signed by the agent the verifier trusts" and must not be read as the latter.

Symmetry

AIRI cannot raise a verdict and a broken AIRI bundle cannot lower one. The reconciliation rests on the observer's evidence; a defect in the agent's own account is recorded as its own component verdict rather than leaking into the result. Both directions are tested (`aip-nexora/tests/airi.rs`).

12. Reconciliation

AIRI produces an `AiriAnnotation` that sits beside a `Reconciliation` , never inside it. `annotate()` takes the reconciliation by shared reference and returns a new value; it contains no expression producing a `ReconciliationResult` or an `EvidenceStrength` .

`tests/reconcile_integration.rs` drives the real engine and asserts the verdict and strength are identical with and without AIRI evidence present, in every corroboration shape.

A `reconcile_airi_claim` entry point that could reach `PHANTOM_CLAIM` from an uncorroborated AIRI claim is deliberately not implemented. See `AIRI_MIGRATION.md` §4.

REFERENCE 13

AIRI Threat Model

1. The one principle

> ***The actor should not control the evidence used to judge the actor.***

Everything below follows from it.

2. Trust boundaries

PARTY	HOLDS	TRUSTED FOR	NOT TRUSTED FOR
Agent process	its own Ed25519 key, its own clock	authorship of its own statements	anything it asserts about the world
Framework / adapter	nothing	translating callbacks into AIRI	any judgement whatsoever
Host probe	**no key**	offering observations to the collector	its own honesty (assumed hostile)
Collector	the observer key, **off-host**	sequence, timestamp, attestation	the content of what the probe reported
Decision point	its own key	issuing `ExpectedExecution`	observing execution
Reconciler	nothing	comparing, deriving a verdict	— (pure, clock-free)
Verifier	anchors it chose	everything it re-derives	anything it was handed as a conclusion

The agent and the collector are the two signing parties that matter, and the architecture's entire value is that the agent cannot reach the collector's key.

3. Adversary

Capability: full control of the agent process — arbitrary code, the agent's private key, the process clock, all framework instrumentation, all Python-level telemetry, and root on the observed host.

Goal: have Vanian certify an action that did not happen, or fail to record one that did.

Out of scope: compromise of the collector, of the decision point, or of the verifier's anchors. Those are different trust boundaries with their own controls; AIRI assumes them intact and is worthless if they are not.

4. Attacks and dispositions

4.1 Forge a claim

ATTACK	DISPOSITION
Emit an event describing work never done	**Succeeds at the claim layer, by design.** The agent may say anything. Detection is `corroborate` returning `Uncorroborated` where an observer covered the window.
Sign an event with a key the verifier does not anchor	Fails. Verification is against the anchored key. `adversarial.rs::a_forged_event_signed_by_a_key_the_verifier_does_not_anchor_fails`
Sign a statement *about another agent*	Fails: `signature.signer_id` must equal `agent_id`. `AiriError::SignerIsNotTheAgent`

4.2 Relabel a true statement

Cheaper and quieter than forging a false one. All fail, because every field below is inside the signed preimage:

SUBSTITUTION	TEST
Another agent	`an_event_does_not_verify_under_another_agents_key`
Another execution	`an_event_cannot_be_moved_to_another_execution`
Another `ExpectedExecution`	`an_event_cannot_be_moved_to_another_expected_execution`
Different parameters	`parameter_substitution_is_detected`
Different model	`model_substitution_is_detected`
Different model digest	`model_digest_substitution_is_detected`
Different framework	`framework_identity_substitution_is_detected`
Different event kind	`an_event_of_one_kind_cannot_be_presented_as_another`

4.3 Manipulate the narrative

ATTACK	DISPOSITION
Replay an event	Detected — `SequenceDuplicate`
Duplicate an event	Detected — `SequenceDuplicate`
Drop a middle event	Detected — `SequenceGap`
Reorder events	Detected — `SequenceOutOfOrder` / `SequenceGap`
Delete and renumber to close the gap	Detected — `PrevHashMismatch`. This is the attack sequence numbers alone miss.
Splice an event from another run	Detected — `ExecutionMismatch` / `PrevHashMismatch`
Truncate at the head	**NOT DETECTED.** A prefix of a valid chain is valid. See §6.
Never emit the event at all	**NOT DETECTED by AIRI.** An agent that stays silent produces a perfectly intact chain with the incriminating link absent. Only independent observation speaks to this.

The last two are the honest limits of self-reporting and are the reason AIRI is not, and cannot be, the accountability story on its own.

4.4 Manufacture corroboration

ATTACK	DISPOSITION
Claim a `runtime_binding` for a process the observer saw doing something	Fails: the join is on the full `ProcessInstance` (pid + start ticks + boot id). `an_observation_of_a_different_instance_does_not_corroborate`
Rely on an unbound kernel event that names the right pid	Fails: an unbound event names a pid, and a pid is not an instance. `a_kernel_event_the_probe_could_not_bind_does_not_corroborate`
Use "the process was alive" as evidence it acted	Fails: presence is a fact about the observer's sampling. `process_presence_alone_never_corroborates_an_act`
Use an unrelated observation of the right instance	Fails: the action class must match. `an_observation_of_the_wrong_class_does_not_corroborate`
Hand the verifier a `Corroborated` value directly	Impossible: `CorroborationSeal` is `#[non_exhaustive]`; only `corroborate()` constructs one
Claim a socket proves the *model* ran	Fails: model events are `NotExternallyObservable`. `a_model_invocation_is_never_corroborated_by_a_host_observer`

4.5 Exploit the framework layer

ATTACK	DISPOSITION
Claim a "more trusted" framework	No framework is a trust anchor. `no_framework_is_a_trust_anchor` sweeps five names and asserts identical outcomes.
Transplant a CrewAI event as LangGraph output	Fails: framework identity is in the signed preimage
Register a malicious adapter	Changes nothing. An adapter has no privileges; it produces events signed by the agent's key, which is what the agent could do anyway.

4.6 Exploit the SDK

ATTACK	DISPOSITION
Read the observer's private key from the agent process	Impossible: the SDK has no API for one, and `_reject_observer_key` raises
Call `prove()` / `issue_warrant()` / `authorize()`	Impossible: no such method. `test_boundary.py` asserts absence by introspection
Destroy the key file to get a fresh identity	Fails closed: `IdentityUnavailable`, and the test asserts no key file is created
Read a world-readable key file	Refused by default; waiving requires an explicit `require_owner_only=False`
Extract secrets from evidence	Prompts, arguments and outputs are committed, never carried. Tested with a synthetic secret.
Read the key from a child's environment	The environment carries identifiers only; tested.
Race two threads to corrupt the chain	The emitter serialises sequence and head under a lock

4.7 Resource and denial

ATTACK	DISPOSITION
Oversized field to force allocation	Refused at 4096 bytes, both sides — `FieldTooLong`
Unknown structure version	Refused, not interpreted — `UnsupportedVersion`
Malformed public key	Refused, never a pass — tested with 0, 31, 32 and 33 byte keys
Flood the collector with events	**NOT ADDRESSED.** Rate limiting is a deployment obligation.

5. Deployment obligations

Not code properties. A deployment that skips these gets less than the tests suggest.

1. **Transport authenticity from probe to collector.** `aip-observe` states this: the registry lives at the collector, but proving a batch really came from the registered probe is the transport's job.
2. **Observer key custody.** Off-host, in an enclave or HSM. An observer key on the observed host reduces the whole system to self-report.

3. **Agent key custody.** Mode 0600 or tighter, ideally an HSM. The SDK refuses group- and world-readable files but cannot defend a key already read.
4. **Anchor distribution.** Verifiers must obtain agent, observer and decision-point public keys through a channel the agent cannot influence.
5. **Rate limiting and back-pressure** at the collector.
6. **Commitment policy.** Which fields are committed, and the retention of the plaintext they commit to, is a deployment decision with privacy consequences.

6. Known limitations

Stated as limitations, not as gaps to be argued away.

#	LIMITATION	CONSEQUENCE
L-1	Chain truncation at the head is undetectable	An agent can stop reporting at any point
L-2	Silence is undetectable from AIRI alone	An action never reported leaves no AIRI trace
L-3	`runtime_binding` is self-reported	A match with the observer is consistency, not proof
L-4	`emitted_at_ms` is the agent's clock	Never used to order or place events
L-5	Model provenance is unverifiable for hosted inference	`model_digest` is `None`, honestly
L-6	Accelerator execution is not observable from the process	`accelerator` is a self-reported string
L-7	An unmappable action class cannot be compared	Returns `NotEvaluated`, never an accusation
L-8	Corroboration cannot reach `Proven`	Content from the observed host is root-forgeable
L-9	AIRI contributes nothing to a verdict today	By design at this stage — see `AIRI_MIGRATION.md` §4
L-10	Gateways are not yet trust anchors	An MCP/API gateway report is another self-report from a different self

7. What AIRI actually buys

Given all of the above, the honest summary:

AIRI does not make an agent's claims trustworthy. It makes them **specific, bound, and checkable** — so that when independent observation exists, the two can be compared, and when it does not, the system says so rather than guessing. The valuable output is not `Corroborated`; it is `Uncorroborated` and `NotEvaluated`, which are the two answers a self-reporting system normally cannot produce at all.

REFERENCE 14

Limitations & Evidence Classes

For each property: what is claimed, what class of evidence supports it, and where the claim stops. Classes follow the forensic audit's discipline.

CLASS	MEANING
`CODE-PROVEN`	Read directly from source at a cited path
`TEST-PROVEN`	A test exercises the property itself, not a stand-in
`EXECUTION-PROVEN`	Demonstrated by running code across a real boundary
`DOCUMENTED`	Asserted in a document; not independently verified
NOT_DETERMINABLE	Cannot be established from the current codebase

1. Properties established

#	PROPERTY	CLASS	EVIDENCE
P-1	An AIRI event's signature covers every field a verifier reads	TEST-PROVEN	`binding.rs::the_signature_covers_every_field_the_verifier_later_reads` — 8 single-field mutations
P-2	Cross-agent transplantation fails	TEST-PROVEN	`binding.rs` ×2
P-3	Cross-execution transplantation fails	TEST-PROVEN	`binding.rs` ×2
P-4	Parameter substitution is detected	TEST-PROVEN	`binding.rs::parameter_substitution_is_detected`
P-5	Model and model-digest substitution are detected	TEST-PROVEN	`binding.rs` ×2
P-6	Framework substitution is detected	TEST-PROVEN	`binding.rs::framework_identity_substitution_is_detected`
P-7	Event-kind substitution is detected	TEST-PROVEN	`binding.rs::an_event_of_one_kind_cannot_be_presented_as_another`
P-8	The preimage is injective across adjacent strings	TEST-PROVEN	`binding.rs::the_preimage_is_injective_across_adjacent_string_fields`
P-9	AIRI's domain collides with none of the 15 existing domains	TEST-PROVEN	`binding.rs::an_airi_preimage_is_not_a_valid_preimage_in_any_other_aip_domain`
P-10	Parameter commitments are not bare SHA-256	TEST-PROVEN	`binding.rs`, `test_canonical_parity.py`
P-11	Replay, duplication, drop, reorder and splice are detected	TEST-PROVEN	`chain.rs` — 13 tests
P-12	Deletion hidden by renumbering is detected	TEST-PROVEN	`chain.rs::renumbering_after_a_deletion_is_caught_by_the_hash_link`
P-13	The chain verifier does not sort its way out of a reordering	TEST-PROVEN	`chain.rs::the_verifier_does_not_sort_its_way_out_of_a_reordering`
P-14	An observation of a different process instance does not corroborate	TEST-PROVEN	`adversarial.rs`
P-15	An unbound kernel event does not corroborate	TEST-PROVEN	`adversarial.rs`
P-16	Process presence alone never corroborates an act	TEST-PROVEN	`adversarial.rs`
P-17	An observer that was down yields `NotEvaluated`, never an accusation	TEST-PROVEN	`adversarial.rs::observer_unavailable_is_not_evaluated_and_is_not_a_finding`


#	PROPERTY	CLASS	EVIDENCE
P-18	An unmappable action class yields `NotEvaluated`, never `Uncorroborated`	TEST-PROVEN	`adversarial.rs::an_unmappable_action_class_is_not_evaluated_rather_than_accused`
P-19	No framework is a trust anchor	TEST-PROVEN	`adversarial.rs::no_framework_is_a_trust_anchor` — sweeps 5 names
P-20	A model claim is never corroborated by a host observer	TEST-PROVEN	`adversarial.rs`
P-21	AIRI evidence cannot change the reconciler's verdict or strength	TEST-PROVEN	`reconcile_integration.rs` — drives the **real** engine, 7 tests
P-22	Corroboration cannot produce `VerifiedExecution`	TEST-PROVEN	`reconcile_integration.rs`
P-23	Accumulated AIRI evidence cannot reach `Proven`	TEST-PROVEN	`reconcile_integration.rs::no_amount_of_airi_evidence_reaches_proven`
P-24	An AIRI leaf cannot be replayed as another NEXORA leaf kind	TEST-PROVEN	`nexora_commitment.rs`
P-25	The committed bytes are the bytes that were signed	TEST-PROVEN	`nexora_commitment.rs`
P-26	The Python and Rust encoders are byte-identical	EXECUTION-PROVEN	`test_canonical_parity.py` — 9 vectors generated by Rust
P-27	Rust verifies signatures the Python SDK produced	EXECUTION-PROVEN	`python_interop.rs` — 5 events, plus a bit-flip negative
P-28	The SDK exposes no way to self-prove or self-authorize	TEST-PROVEN	`test_boundary.py` — 14 forbidden names, by introspection
P-29	Identity loading fails closed and never regenerates a key	TEST-PROVEN	`test_boundary.py` — asserts no key file is created
P-30	Secrets do not reach the signed bytes	TEST-PROVEN	`test_boundary.py`, `test_adapters_e2e.py`
P-31	Context does not leak between concurrent async tasks	TEST-PROVEN	`test_context.py` — 8 concurrent tasks
P-32	Context does not silently cross a thread boundary	TEST-PROVEN	`test_context.py`
P-33	Context survives a real subprocess without carrying key material	EXECUTION-PROVEN	`test_context.py::test_a_real_subprocess_restores_the_context`
P-34	A malformed propagated context is refused, not repaired	TEST-PROVEN	`test_context.py` — 5 malformed encodings

2. Properties NOT established

Each is a gap, not a nuance.

#	NOT ESTABLISHED	WHY	CLASS
N-1	That any claimed action occurred	AIRI is self-report; occurrence needs observation	by design
N-2	That a claimed external effect landed	The process that made the call cannot know	by design
N-3	That a provider served the model requested	Hosted APIs return an unverifiable identifier	NOT_DETERMINABLE
N-4	That specific weights were loaded	A digest the agent computes is a statement about a file, not about runtime memory	NOT_DETERMINABLE
N-5	That XLA, a native kernel, or a GPU executed anything	Framework telemetry is still framework telemetry	NOT_DETERMINABLE
N-6	That an agent reported everything it did	Silence leaves an intact chain	NOT_DETERMINABLE from AIRI
N-7	That a chain was not truncated at the head	A prefix of a valid chain is valid	NOT_DETERMINABLE from AIRI
N-8	That `runtime_binding` is true	Self-reported; a compromised process can report its real pid	by design
N-9	That an MCP or API gateway's report is authoritative	Its key lifecycle and transport are undefined	NOT_DETERMINABLE
N-10	Any post-quantum property	No PQC exists on this branch	NOT_DETERMINABLE
N-11	That AIRI improves detection today	AIRI contributes nothing to a verdict at this stage	by design — see `AIRI_MIGRATION.md` §4

3. The JAX / PyTorch / accelerator chain



LAYER	OBSERVABLE FROM AIRI?	WHAT IS RECORDED
Which model the agent requested	yes	`model_id`, signed
Which model the provider served	**no**	nothing
Framework and version	yes, self-reported	`runtime`, `runtime_version`
Weights loaded	**no**, unless measured externally	`model_digest`, normally `None`
XLA / kernel launch	**no**	nothing
GPU execution	**no**	`accelerator`, a self-reported string

Where the distinction matters, the answer is `CANNOT_PROVE`, and `corroborate` returns `NotEvaluated(NotExternallyObservable)` for every model event rather than borrowing the tool layer's socket as evidence.

4. Replay semantics for non-deterministic inference

Replay means **policy and evidence equivalence**, never bitwise reproduction of model output. Two runs of the same prompt legitimately differ. What must reproduce is the commitment structure: the same prompt bytes commit to the same digest, and the signed binding between agent, execution, expectation and model survives re-verification.

5. Inherited forensic blockers

AIRI does not close any of these. They are properties of the substrate it sits on, and all remain **OPEN**.


ID	BLOCKER	STATUS
B-1	Verifier has no clock	**CLOSED** in `aip-protocol` (R16)
B-1a	`aip-service` supplies no verification time, so its `/verify` is unbounded	**OPEN** (`P1`)
B-2	Delegation issuer not bound to previous grantee	**CLOSED**, fully adopted
B-3	Containment unreachable from engine output	OPEN
B-4	Bundle verified against a self-supplied key	OPEN
B-5	Private keys written with default permissions	OPEN (the Python SDK refuses to *read* such a file, which is not the same as fixing the writer)
B-6	Service mints a new identity on an unreadable key	OPEN in `aip-service`; the SDK's own loader fails closed
B-7	Private seeds accepted in HTTP bodies	OPEN
B-8	Packet replay undetected	OPEN
B-9	`Reconciliation` constructible outside the engine	OPEN
B-10	`aip-service` in no workspace	OPEN

Production promotion remains forbidden until these are closed and tested. Both P0s were closed by prod after this document was first written and were independently verified; see `audit/2026-09-06-airi-extension/P0_VERIFICATION_ADDENDUM.md`.

REFERENCE 15

AIRI Architecture

1. The full accountability chain



2. Why the two evidence paths are asymmetric

	AIRI	AIP-OBSERVE
Who signs	the agent	the collector
Where the key lives	in the agent process	**off the observed host**
Whose clock	the agent's	the collector's
Can root on the host forge it?	**yes**	no — it can forge what is *offered*, not the attestation
What it establishes	authorship and integrity	that a collector attested these bytes

Reconciliation is where the asymmetry is spent. Neither half alone says much; the pair does. An AIRI claim the observer covered and did not see is the interesting case, and it is only interesting *because* the observer's signature is out of the agent's reach.

3. The three boundaries the specification refuses to collapse

3.1 Tool: request ≠ execution ≠ effect

```
agent → Python → framework → client lib → kernel → network → far side
        └─ layer 1 ─┘        └─ layer 2 ─┘                  └ layer 3 ┘
        ToolInvocation       ToolReport                     no event
        Requested            (a 200 lives here)             asserts this
```

3.2 Model: declaration ≠ selection ≠ execution


```
model_id requested  ≠  model served  ≠  weights loaded  ≠  kernel ran  ≠  GPU executed
     AIRI records         unverifiable      digest only      not visible    not visible
                          from here         if measured      from here      from here
                                            externally
```

3.3 Lineage: identity ≠ authority ≠ application

```
identity lineage    aip-agent            which document descends from which
authority lineage   delegation chain     who granted what to whom
application lineage parent_execution_id  which run spawned which
```

Nothing reads `parent_execution_id` to widen scope. A subprocess an agent spawned itself carries the same expectation or none — which is what stops authority laundering through a child process.


4. Context propagation



Threads and processes require an explicit handoff. A wrapper that copied context automatically would attribute a worker's actions to whoever spawned it, and a handoff is a lineage event that should be written down.

The environment carries **identifiers only** — never a key. A child that signs loads its own identity.

5. Crate dependency graph



`aip-airi` depends on `aip-types`, `aip-crypto`, `aip-observe`, `aip-authorize`, `aip-reconcile` and `aip-nexora`. Nothing depends on `aip-airi`, so it cannot affect the existing chain except through values a caller explicitly passes it.

6. What a verifier holds

```
NexoraProof ─┬── expectation      (decision-point signed)
             ├── observer bundle  (collector signed)
             ├── AIRI leaves      (agent signed, LeafKind 0x09)
             ├── claim            (Reconciliation)
             └── warrant          (warrant-authority signed)

VerifierAnchors ─┬── decision-point keys
                 ├── observer keys  (observer_id, key_version)
                 ├── issuer keys
                 ├── warrant keys
                 └── agent public key
```

The verifier re-runs the reconciler over the package's own inputs and compares canonical digests. A package whose verdict is not derivable from its own evidence is rejected. It does not believe a serialized `Proven` because the package author signed it.

REFERENCE 16

Migration & Versioning

1. Versioned surfaces

SURFACE	CONSTANT	VALUE	CHANGE POLICY
Event structure	`AIRI_EVENT_VERSION`	`1`	Bump on any preimage layout change
Event domain	`AIRI_EVENT_DOMAIN`	`SYNTRIASS/AIRI/EVENT/v1`	New tag, never a redefinition
Commitment domain	`AIRI_PARAM_DOMAIN`	`SYNTRIASS/AIRI/PARAM_COMMITMENT/v1`	New tag, never a redefinition
NEXORA leaf kind	`LeafKind::AiriEvent`	`0x09`	Frozen; new kinds append
NEXORA package	`NEXORA_PROOF_VERSION`	`2`	Bump on any component change
NEXORA component	`Component::Airi`	`0x0A`	Frozen; new components append
JSON schemas	`docs/schemas/`	—	Non-normative; kept in step by `test_schema_conformance.py`
Adapter mapping	`FrameworkIdentity.adapter_version`	per adapter	Bump when the translation changes
Python package	`vanian_airi.__version__`	`0.1.0`	Semver against the Rust event version

2. Rules

1. **A verifier refuses an unknown version rather than interpreting it.** Fields may have moved; a best-effort parse of an unknown layout is how a signature ends up covering something other than what a verifier reads.
2. **The domain tag carries the version.** A v2 event signs under `SYNTRIASS/AIRI/EVENT/v2`, so a v1 verifier cannot be tricked into accepting a v2 event and vice versa. The version is belt as well as braces.
3. **Leaf codes are frozen.** A leaf committed today keeps verifying.
4. **Adapter versions are recorded, not trusted.** A verifier may refuse a mapping it does not know; it may not grant anything on the strength of one.

3. Adding a field, an event kind, or a payload

CHANGE	REQUIRES
New optional field	version bump; presence byte; new parity vector; substitution test
New event kind	new code appended; `is_externally_observable` decision (the match is exhaustive, so the compiler forces it); corroboration test
New payload variant	version bump; encode function; injectivity test against the neighbouring variants
New observable class	mapping in `observable_class_of`; a test that an unmapped class still returns `NotEvaluated`

Every one of those also requires regenerating the Python parity vectors:

```
cargo test -p aip-airi --test parity_vectors -- --ignored --nocapture \
  > sdk/python/tests/parity_vectors.json
cd sdk/python && python3 -m unittest discover -s tests
```

A divergence must be a build failure. The parity test caught three real defects on its first run; treating it as advisory would have shipped them.

4. The deferred change: AIRI as a verdict input

Not implemented, deliberately. Today AIRI contributes nothing to a reconciliation verdict.

The change would add a fourth entry point to `aip-reconcile` — `reconcile_airi_claim` — reusing `Draft`, `prologue` and, critically, `precondition_holds`, so it goes through the same choke point as the existing three and cannot exceed `Attested`.

It is deferred because it is a **new way to accuse**. The existing `PHANTOM_CLAIM` path required recomputed coverage, a sealed identity comparison and 1,419 lines of adversarial tests before it was trusted to say "this did not happen". A second

accusation path built without that depth is how a detection system starts producing false positives and gets switched off.

Before it is built it needs:

1. A precondition at least as strict as the existing `PhantomClaim` arm: recomputed coverage, `IdentityComparison::NoReference`, covered availability, and `strength == Attested` exactly.
2. An additional AIRI-specific precondition: an intact chain, a runtime binding, and a mappable action class. Any of those absent must yield `CannotProve`.
3. An adversarial suite of comparable depth to `aip-reconcile/tests/adversarial.rs`, specifically covering: a lying agent that omits events, an agent that fabricates a binding for an instance the observer *did* see acting, and a vocabulary gap that must not become an accusation.
4. A false-positive budget agreed with whoever operates it, because the first production week decides whether the system stays switched on.

Until all four exist, `annotate()` surfaces `uncorroborated` as a counter for policy to act on, visibly, rather than as a verdict.

5. Rollout

STAGE	STATE	GATE TO THE NEXT
0	AIRI core, SDK, adapters — **done**	—
1	Adapters deployed, events collected, nothing acts on them	Corroboration rates measured against real traffic
2	`annotate()` surfaced to operators as a dashboard signal	False-positive rate of `uncorroborated` characterised
3	§4 entry point built, behind a policy flag, advisory only	Adversarial suite complete; budget agreed
4	AIRI contributes to verdicts	Forensic blockers B-1…B-10 closed

Stage 4 is gated on the blockers, not on AIRI's own maturity: contributing to a verdict in a system whose verifier has no clock and whose delegation chains do not bind issuer to grantee would be building on sand.

5a. The v1 → v2 package break

`NEXORA_PROOF_VERSION` moved from 1 to 2 to carry `AiriBundle`. A v1 package is **refused** by a v2 verifier (`InvalidReason::UnsupportedVersion`), not reinterpreted.

The break is deliberate and cheap here: no v1 package exists outside tests, because NEXORA has never shipped. Had one existed, the alternative would have been a v1-tolerant verifier that treats a missing AIRI component as absent — sound, but it buys backward compatibility with a format nobody has.

The AIRI component is appended *after* `Commitment`, so every field a v1 package encoded sits at the byte offset it always did. The version number, not the layout, is what distinguishes them; a verifier that ignored the version and parsed positionally would read a v2 package correctly right up to the point where it ran out of v1 fields, which is exactly why the version check comes first.

6. Compatibility

- A v1 event verifies against a v1 verifier indefinitely.
- A v1 verifier refuses a v2 event with `UnsupportedVersion` — loud, not silent.
- A NEXORA package containing AIRI *leaves* verifies on a build without AIRI: the leaf kind is opaque to a verifier that does not know it, and the Merkle root still recomputes.
- A NEXORA package containing an AIRI *component* requires a v2 verifier. A v1 verifier refuses it by version, which is the loud failure, not a misparse.
- The Python SDK and the Rust crate must ship together. The parity vectors are the contract; a mismatched pair is a build failure by construction.

REFERENCE 17

Canonical Encoding & Schemas

What is normative here

The wire format is the byte encoding, not JSON. What a signature covers is the canonical preimage defined in `AIRI_SPECIFICATION.md` §6 and implemented once in `aip-airi/src/event.rs`. These schemas describe the *shape* of an AIRI object for tooling — code generation, editor completion, API documentation, request validation at a gateway — and are **not** the thing a verifier checks.

A verifier that validated JSON and skipped the preimage would be checking that a document is well formed, not that a signature covers it. The two questions are unrelated.

Files

FILE	DESCRIBES
`airi-event.schema.json`	An `AiriEvent` and all nine payload bodies
`airi-bundle.schema.json`	The `AiriBundle` carried in a NEXORA proof
`airi-encoding.md`	The normative byte layout, field by field

Byte-level conformance

The one test that establishes cross-implementation agreement is the parity suite, not these schemas:

```
cargo test -p aip-airi --test parity_vectors -- --ignored --nocapture \
  > sdk/python/tests/parity_vectors.json
cd sdk/python && python3 -m unittest tests.test_canonical_parity
```

A new implementation in any language is conformant when it reproduces those vectors byte for byte and its signatures verify under `aip-airi/tests/python_interop.rs`. Passing schema validation establishes neither.

AIRI Canonical Byte Encoding — Normative

This is the format a signature covers. The JSON schemas beside it describe object shape for tooling and are not normative.

Primitives

WRITER	BYTES
`put_u8(v)`	1 byte
`put_u16(v)`	2 bytes, little-endian
`put_u32(v)`	4 bytes, little-endian
`put_u64(v)`	8 bytes, little-endian
`put_bytes(d)`	`put_u32(len(d))` then `d`
`put_str(s)`	`put_bytes(utf8(s))`
`put_domain(t)`	`put_str(t)` — always first in a signed payload
`put_opt_str(s)`	`0x00`, or `0x01` then `put_str(s)`
`put_opt_u64(v)`	`0x00`, or `0x01` then `put_u64(v)`
`put_opt_digest(d)`	`0x00`, or `0x01` then `put_bytes(d)`
`put_opt_bytes16(v)`	`0x00`, or `0x01` then `put_bytes(v)`

Every variable-length field is length-prefixed and every optional field carries a presence byte. That is what makes the encoding injective: no two distinct values share a byte stream, so a signature commits to exactly one interpretation.

Fixed-width fields inside `identity_bytes` are appended raw, not length-prefixed. Getting this wrong is not theoretical — the first port of the Python SDK

length-prefixed `exe_content_sha256` and the parity vectors caught it before it shipped.

Domains

TAG	OBJECT
`SYNTRIASS/AIRI/EVENT/v1`	`AiriEvent` signing preimage
`SYNTRIASS/AIRI/PARAM_COMMITMENT/v1`	Parameter, prompt, output, argv commitments
`GHOST/ExecutionIdentity/v1`	`ExecutionBinding::identity_bytes` (defined in `aip-types`)

Event preimage

```
put_domain("SYNTRIASS/AIRI/EVENT/v1")
put_u16(version)                        // 1
put_str(agent_id)
put_bytes(execution_id)                 // 16
put_opt_bytes16(parent_execution_id)
put_opt_bytes16(decision_id)
put_u64(sequence)
put_bytes(prev_event_hash)              // 32
put_u64(emitted_at_ms)
put_str(framework.name)
put_str(framework.version)
put_str(framework.adapter_version)
runtime_binding: 0x00, or 0x01 then put_bytes(identity_bytes())
put_u8(kind_code)
<payload>
```

`ExecutionBinding::identity_bytes`

```
put_domain("GHOST/ExecutionIdentity/v1")
put_u16(version)
put_str(agent_id)
<raw> pid                u32 LE, 4 bytes
<raw> pid_start_ticks    u64 LE, 8 bytes
<raw> boot_id            16 bytes
<raw> exe_content_sha256 32 bytes
```

`exe_path` and `bound_at_ms` are excluded: two spellings of the same binary are one identity, and a same-path different binary is not.

Kind codes

CODE	KIND
`0x01`	`AgentExecutionStarted`
`0x02`	`ModelInvocationRequested`
`0x03`	`ModelInvocationObserved`
`0x04`	`ToolInvocationRequested`
`0x05`	`ToolExecutionReported`
`0x06`	`SubprocessExecution`
`0x07`	`ExecutionCompleted`
`0x08`	`ExecutionFailed`
`0x09`	`ExecutionContextPropagated`

Payload bodies

AgentStart — `put_opt_str(agent_role)`, `put_opt_str(framework_run_id)`

ModelProvenance — `put_str(model_id)`, `put_opt_digest(model_digest)`, `put_str(runtime)`, `put_opt_str(runtime_version)`, `put_opt_str(inference_request_id)`, `put_opt_digest(prompt_commitment)`, `put_opt_digest(output_commitment)`, `put_opt_str(accelerator)`

ToolInvocation — `put_str(tool_id)`, `put_str(action_kind)`, `put_bytes(parameter_commitment)`, `put_opt_str(tool_call_id)`, `put_opt_str(target)`

ToolReport — `put_str(tool_id)`, `put_bytes(parameter_commitment)`, `put_u8(outcome)`, `put_opt_digest(result_commitment)`, then transport status as `0x00` or `0x01` + `put_u64`

SubprocessReport — `put_str(program)`, `put_bytes(argv_commitment)`, then pid as `0x00` or `0x01` + `put_u64`

Completion — `put_u8(outcome)`, `put_opt_str(detail)`

ContextPropagation — `put_u8(boundary)`, `put_bytes(to_execution_id)`

Enum codes

`ReportedOutcome`: Success `0x01`, Failure `0x02`, Denied `0x03`, Indeterminate `0x04`. `PropagationBoundary`: AsyncTask `0x01`, Thread `0x02`, Process `0x03`, Subprocess `0x04`, WorkerQueue `0x05`.

Commitments

```
commit(x) = SHA-256( put_domain("SYNTRIASS/AIRI/PARAM_COMMITMENT/v1") ‖ put_bytes(x) )
```

Domain-separated rather than a bare SHA-256, so a digest computed elsewhere in the system — a packet hash, an observer head, a Merkle leaf — cannot be presented as a parameter commitment.

For structured values, serialise deterministically first. The Python SDK uses `json.dumps(sort_keys=True, separators=(",", ":"))`; any implementation must match, or two commitments of identical arguments will differ and a verifier will see a parameter substitution that never happened.

Signing

```
payload_hash    = SHA-256(preimage)
signature_bytes = Ed25519_sign(agent_private_key, preimage)
```

The signature is over the **preimage**, not over the hash. `signer_id` must equal the event's `agent_id`.

NEXORA carriage

An event commits as a Merkle leaf under `LeafKind::AiriEvent` (`0x09`):

```
leaf = merkle_leaf( put_domain("SYNTRIASS/NEXORA/LEAF/v1")
                  ‖ put_u8(0x09) ‖ put_bytes(signing_preimage) )
```

Inside a `NexoraProof` (package version **2**), under `Component::Airi` (`0x0A`), appended after `Commitment`:

```
put_u8(0x0A)
0x00, or 0x01 then:
  put_str(agent_id)
  put_bytes(agent_public_key)
  put_u32(len(events))
  for each: put_bytes(signing_preimage) ‖ put_signature(signature)
```

The event's own preimage is committed, not a re-serialisation, so a verifier checks one artefact rather than trusting a round-trip.

Conformance

An implementation is conformant when it reproduces `sdk/python/tests/parity_vectors.json` byte for byte and its signatures verify under `aip-airi/tests/python_interop.rs`. Schema validation establishes neither.

PART IV · ADDENDUM · 2026-09-07

Engineering Maturity, TRL & Strategic Readiness — Post-Validation Addendum

Written on top of the forensic audit, using the same evidence discipline. It assesses what the production-readiness branch can now demonstrate, what it still cannot, and what follows commercially from that distinction.

ENGINEERING STATUS

TRL 5 overall; AIRI/Sniffer Dog software accountability core approaching TRL 6; physical autonomous-system validation pending.

STANDING OF THIS ADDENDUM

This addendum reflects engineering and validation progress after the original forensic audit baseline. It does not retroactively alter the original forensic findings. Every finding in Reports 00–17 stands as filed. Where a finding has since been closed on the production branch, that is recorded as *subsequent work*, with the original finding left intact and citable. Where a finding remains open, it is listed in A15.

ASSESSED HEAD 12767ea	AUDIT BASELINE FOR THAT BRANCH 82da7a6 · +125 commits
MAIN 872dbf3 · untouched	WORKSPACE TESTS 1,691 · 0 failed · 0 warnings
OVERALL TRL (ASSESSMENT) ≈ 5	PHYSICAL VALIDATION Pending

ADDENDUM A

Executive Maturity Summary

The programme has moved, since the forensic baseline, from *"a disciplined evidence architecture with an untested observation story"* to *"a disciplined evidence*

architecture whose observation story has been exercised against an independent external observer on a real Linux kernel, was found defeatable, and was then repaired in production."

Five things are materially true now that were not true at the audit baseline, and one thing is equally true and is not softened anywhere in this document.

#	WHAT CHANGED	CLASS
1	**Real Linux runtime evidence exists.** Sniffer Dog 2.0 captured live `sched:sched_process_exec` / `sched_process_fork` samples through `perf_event_open` on kernel 6.18.44-fc-v24, with sealed, digested run artifacts.	EXECUTION-PROVEN
2	**AI-agent accountability has been exercised, not asserted.** A real AIRI subject agent emitted a correctly signed event chain and lied about the correspondence between claim and reality. Ten adversarial scenarios ran; ten behaved as required.	EXECUTION-PROVEN
3	**Mechanism-independent observation was demonstrated.** A third-party eBPF observer (A3S Observer 0.11.0, MIT) at `syscalls:sys_enter_execve` — different probe site, different project, different decoder — agreed on true events and refused to corroborate a signed false claim.	EXTERNAL-CORROBORATED
4	**Observation interference was reproduced deterministically.** A two-instruction eBPF program on the sampled tracepoint suppressed perf submission host-wide. Sniffer Dog observed 0 of 8 execs and reported **zero loss** — silence indistinguishable from non-occurrence.	EXECUTION-PROVEN
5	**The weakness was mitigated in production.** The observer enumerates foreign eBPF programs on its own tracepoints, carries `ObserverState::IntegrityUnknown` inside its signed health record, requires a gate-independent kernel-pushed mechanism before coverage licenses a non-occurrence claim, and maps the unknown state to `cannot_prove(ObserverIntegrityUnknown)`.	CODE-PROVEN EXECUTION-PROVEN
6	**Physical autonomous-system validation remains outstanding.** No robot, no airframe, no external tracker, no hardware root of trust. The robotics profile's closing gap reads, verbatim: *"No robot was involved."*	DOCUMENTED

> THE GOVERNING DILIGENCE FACT, STATED FIRST
>
> Every capability assessed here lives on `claude/codebase-production-readiness-wm6idp`. A reader who clones the default branch sees `main`, and `main` contains none of the observation, reconciliation, AIRI, UAS or robotics work — 228 commits of distance. This is the audit's own finding **D-1**, unchanged, and it is a diligence fact rather than a code defect.

Authoritative engineering checkpoint

ITEM	VALUE	VERIFICATION
Production-readiness branch	`claude/codebase-production-readiness-wm6idp`	`git ls-remote` → `12767eab64ff…`
Latest production-validation checkpoint	`12767ea`	*security(observe): close the observer-integrity boundary in production*
Latest observation-integrity / validation work	`ff52dc2`	ancestor of `12767ea`, verified
Forensic-audit baseline for that branch	`82da7a6`	ancestor of `12767ea`; **125 commits behind current head**
`main`	`872dbf3`	**untouched** — 228 commits behind

Completed work in scope for this assessment

Skills 16–24; AIRI implementation and validation; Sniffer Dog 2.0 runtime validation; independent observation validation; observation-integrity threat reproduction; observation-integrity production mitigation; the UAS accountability profile; the robotics accountability profile. **Skill specifications 25–30 exist in-tree with no corresponding crates**, and no implementation is claimed for them.

ADDENDUM B

Current Engineering State

Evidence classes follow the audit's discipline, extended with one label this addendum needs: `EXTERNAL-CORROBORATED` — an independent party or tool outside this repository confirmed it.

1. Maturity dimensions

#	DIMENSION	CLASSIFICATION	WHAT SUPPORTS IT	WHERE IT STOPS
A	**Architecture**	`CODE-PROVEN` `TEST-PROVEN`	28-crate workspace with explicit boundaries: identity / authority / execution / observation / reconciliation / response / proof. Verticals compose over the core without adding a signer, verdict class or engine, asserted over comment-stripped source in `tests/no_second_architecture.rs`	architecture quality is not deployment evidence
B	**Cryptographic / protocol**	`CODE-PROVEN` `TEST-PROVEN` `EXTERNAL-CORROBORATED`	prefix-free, domain-separated canonical encoding; 26 domain tags; RFC 6962 Merkle with leaf/node separation; Ed25519 + SHA-256 only, no in-tree primitives; the six-branch audit read the encoders line by line	**no post-quantum cryptography exists on this branch**
C	**AIRI**	`TEST-PROVEN` `EXECUTION-PROVEN` `EXTERNAL-CORROBORATED`	34 established properties with cited tests; Rust/Python byte parity across 9 vectors; a real subject agent against two independent observers, 10 adversarial scenarios, 10/10	model-invocation claims are **structurally** self-reported; no host observer can attribute a hosted inference call
D	**Sniffer Dog 2.0**	`EXECUTION-PROVEN` `EXTERNAL-CORROBORATED`	live `perf_event_open(PERF_TYPE_TRACEPOINT)` capture, kernel 6.18.44-fc-v24, sealed artifacts with `SHA256SUMS`; agreement with A3S and with an ftrace reader	one host, one kernel, one architecture; `# CONFIG_KPROBES is not set` removes exit evidence
E	**Observation integrity**	`EXECUTION-PROVEN` `TEST-PROVEN`	threat reproduced by a 2-instruction BPF gate; two independently built experiments agree; mitigation shipped at `12767ea` and re-verified in a sealed run (`baseline=verified`, `interfered=integrity_unknown`)	detection is enumeration of foreign BPF programs; a **root/kernel adversary** that hides programs is not defeated
F	**NEXORA evidence / proof**	`CODE-PROVEN` `TEST-PROVEN` `EXECUTION-PROVEN`	the offline verifier ignores the carried verdict and **re-derives** it, refusing `ClaimNotDerivable`; 20 adversarial cases A–T; a live package mutated 8 ways and refused 8 times by a separate verifier process	anchor distribution is a deployment obligation, not a code property
G	**Linux runtime**	`EXECUTION-PROVEN`	three-process live reference (workload / observer / verifier) reaching	single-host, single-kernel; no fleet, no

#	DIMENSION	CLASSIFICATION	WHAT SUPPORTS IT	WHERE IT STOPS
			`VERIFIED_EXECUTION` on real kernel evidence; process instance is `(pid, pid_start_time_ticks, boot_id)`	scale, no long-run stability data
H	**AI-agent runtime validation**	`EXECUTION-PROVEN` (subprocess execution only)	a signed false claim refused corroboration by two mechanism-independent observers; replay, omission, duplication, delayed evidence and contradictory observers all handled	`REAL_WORLD_VALIDATION_PROVEN` is **withheld**: synthetic subject, unobservable model layer, no egress ordering
I	**UAS profile**	`CODE-PROVEN` `TEST-PROVEN` `DOCUMENTED`	`aip-uas`: six identities kept apart, eleven telemetry sources with declared ceilings, mission commitment through the existing `ExpectedExecution` signer, eleven mission states with the physical tier unreachable	2 of 11 sources can produce an `ObservationRecord`; **no PX4, no SITL, no HITL, no flight**
J	**Robotics profile**	`CODE-PROVEN` `TEST-PROVEN` `DOCUMENTED`	`aip-robotics`: eight-rung embodied chain with `unobserved_boundaries_to_outcome() == 5`; 14 sensing sources, 12 with no mechanism; nine semantic claims computed as unestablishable; a live integration test running the Linux reference *as a companion computer*	the live run proves the **computer**, never the machine; task `Completed` resolves to `Unknown` at every tier
K	**Physical robotics**	`UNKNOWN`	—	*"No robot was involved. Nothing here has been validated against physical hardware."*
L	**Physical-effect accountability**	`CODE-PROVEN` (the boundary) · `UNKNOWN` (the effect)	`aip-effect` implements request ≠ execution ≠ effect; `effect_establishable()` is false for all nine robotics safety responses; `support_for` returns `Bears`, never `Establishes`	no external physical observation mechanism exists in this build
M	**Hardware-rooted trust**	`DOCUMENTED`	ADR-002 is **PROPOSED**; `PlatformBinding` / `ObservedBoot` exist in software	no TPM, no secure element, no measured boot
N	**Production / deployment**	`DOCUMENTED` · partially `TEST-PROVEN`	single workspace root (blocker B-10 closed); CI with fmt/clippy/test/ `cargo audit` / `cargo deny`; gitleaks and trivy; signed release pipeline; offline verifier binary	TLS, rate limiting, KMS/HSM, DR/BCP, metrics and runbook are open. **No field deployment evidence exists**

#	DIMENSION	CLASSIFICATION	WHAT SUPPORTS IT	WHERE IT STOPS
0	**Independent validation**	`EXTERNAL-CORROBORATED` (tooling) · `UNKNOWN` (security assessment)	A3S Observer 0.11.0 (`06105bb`, MIT) built from source and run as an independent witness; the six-branch audit is itself an adversarial read	**no third-party security assessment or penetration test has been performed**

2. The engineering achievement chain

```
Identity
  → Authority
    → Expected Execution
      → Runtime
        → Independent Observation
          → Observation Integrity
            → Reconciliation
              → Effect Assessment
                → NEXORA Evidence / Proof
```

The architecture exists to keep six things apart that most systems collapse:

```
claim  ≠  authorization  ≠  execution  ≠  independent observation
                         ≠  physical effect  ≠  proof
```

STAGE	CRATE	WHAT IT ESTABLISHES	WHAT IT DOES *NOT* ESTABLISH
Identity	`aip-core`	which key speaks for which agent document	that the holder is who they say offline
Authority	`aip-core`, `aip-authorize`	a signed, attenuating delegation chain bound issuer-to-grantee	that the authority was exercised
Expected execution	`aip-authorize`	what a decision point authorised, signed, before the fact	that anything ran
Runtime	`aip-execution`, `aip-edge`	a process instance `(pid, start ticks, boot id)`	that the process did what it claimed
Independent observation	`aip-observe`	that an off-host collector attested these kernel-sourced bytes	the content's truth — host content is root-forgeable and capped below `Proven`
Observation integrity	`aip-observe` (new at `12767ea`)	whether the observation mechanism was itself intact	integrity against a root/kernel adversary
Reconciliation	`aip-reconcile`	one verdict, through one choke point, fail-closed to `CannotProve`	anything the evidence in hand does not license
Effect assessment	`aip-effect`	that a requested effect is separated from an observed one	that a physical effect landed — no mechanism exists
Proof	`aip-nexora`	that a third party, offline, re-derived the verdict from the package's own bytes	that the package's anchors are the right ones

Five of the nine stages carry an explicit “does not establish” column that is enforced in code rather than in prose.

ADDENDUM C

Technology Readiness Level

> TERMINOLOGY BOUNDARY
>
> **NASA-style TRL terminology is used here as an engineering assessment. This is not an official certification, and no certifying body has assessed this programme.**

Overall Vanian programme: approximately TRL 5

TRL 5 — *component and/or breadboard validation in a relevant environment.* The accountability core has been validated on a real Linux kernel, against an

independently built external observer, under adversarial scenarios including a reproduced attack on the observation path itself. That is a relevant environment for *software autonomy*. It is not a relevant environment for *physical autonomy*, and the programme's TRL is therefore not uniform.

ELEMENT	ASSESSMENT	BASIS
Overall programme	≈ TRL 5	relevant-environment validation for software autonomy only
AIRI + Sniffer Dog software accountability core	≈ TRL 5, approaching 6	real Linux execution; independent external observer; 10/10 adversarial scenarios; interference reproduced and mitigated in production
Linux runtime observation	≈ TRL 5	live perf-tracepoint capture, sealed artifacts, cross-mechanism agreement — on one host, one kernel
Observation-integrity mechanism	≈ TRL 5	threat reproduced deterministically, mitigation shipped and re-verified; not exercised outside the reproduction environment
NEXORA evidence / proof infrastructure	≈ TRL 5	offline re-derivation demonstrated end to end from a live run; no external verifier deployment
UAS accountability profile	≈ TRL 4	crate, tests and evidence-boundary ADR exist; no PX4, no SITL, no airframe
Robotics accountability profile	≈ TRL 4	profile, tests, ADRs, and a live run that proves the companion computer only
Physical autonomous-system accountability	≈ TRL 2–3	**until actually demonstrated.** The concept is formulated and partially implemented in software; nothing physical has been observed. This stays at 2–3 regardless of code quality until a real machine is in the loop
Full integrated autonomous-system product	≈ TRL 4–5	the integrated chain runs end to end in software; the physical half of the integration does not exist

Why not TRL 6, 7, 8 or 9

LEVEL	WOULD REQUIRE	DISQUALIFYING EVIDENCE
TRL 6	system/subsystem model demonstrated in a *relevant* environment	close for the software core — one non-synthetic agent deployment away. For anything physical, the relevant environment has not been entered at all
TRL 7	prototype demonstration in an *operational* environment	no operational deployment. TLS, rate limiting, KMS/HSM, backups, DR/BCP, metrics and runbook are all open
TRL 8 / 9	completed, qualified, mission-proven system	no third-party security assessment; no certification mapping; no field deployment

What genuinely supports the TRL 5 assessment

1. **Real Linux runtime evidence exists** — sealed captures, not simulation.


2. **AI-agent accountability has been exercised** — a signed false claim was refused corroboration.
3. **Mechanism-independent observation has been demonstrated** — a different probe site, reached by a different mechanism, decoded by a different project.
4. **Observation interference was reproduced** — deterministically, with a minimal-cause interferer, and with audit-subsystem ground truth proving the suppressed events really occurred.
5. **The observation-integrity weakness was mitigated** — in production, with a single deliberate wire-version bump (`OBSERVE_PROTOCOL_VERSION` 8 → 9), re-verified against the reproduction.
6. **Physical autonomous-system validation remains outstanding** — and the robotics profile says so in its own text rather than being made to say so here.

ADDENDUM D

AIRI / Sniffer Dog 2.0 Validation

Sources: `docs/AIRI_REAL_WORLD_VALIDATION.md` (status `EXPERIMENT_PASSED` , **not** `REAL_WORLD_VALIDATION_PROVEN`), `docs/AIRI_INDEPENDENT_OBSERVATION_REPORT.md` , `validation/scenarios/airi_independent_observation_001/` .

1. The validation architecture



The organising rule, and the reason for every design decision in it: **the actor should not control the evidence used to judge the actor.**

2. Achievements, with evidence class

ACHIEVEMENT	CLASS	NOTE
Real Linux execution	`EXECUTION-PROVEN`	kernel 6.18.44-fc-v24, x86_64, root; sealed traces with `SHA256SUMS`
AI-agent independent-observation experiment	`EXECUTION-PROVEN`	`AIRI-INDEPENDENT-OBSERVATION-001`; observers attach first, the window opens only when each reports attached
Signed false claim scenario	`EXECUTION-PROVEN`	Scenario 1: a correctly signed, chain-consistent claim that a tool ran; two mechanism-independent observers covered the window and saw nothing → `SELF_REPORTED`, never `PROVEN`
Replay handling	`TEST-PROVEN`	`SequenceDuplicate`
Omission handling	`TEST-PROVEN` / stated limit	a middle drop is `SequenceGap`; **head truncation is undetectable and is documented as such**, with a test pinning the limit
Duplication handling	`TEST-PROVEN`	renumbering after deletion caught by `PrevHashMismatch`
Delayed evidence	`EXECUTION-PROVEN`	evidence outside the coverage window is *outside coverage*, never a miss
Contradictory observers	`EXECUTION-PROVEN`	conflict is surfaced, never resolved by majority, recency or self-reported confidence
Mechanism-independent Linux Audit witness	`EXECUTION-PROVEN`	`NETLINK_AUDIT` established as independent of the tracepoint path and used as ground truth
A3S cross-check	`EXTERNAL-CORROBORATED`	A3S Observer 0.11.0 (`06105bb`, MIT), built from source, 23/24 probes working
Observation-interference discovery	`EXECUTION-PROVEN`	found by *running* the independent observer, not by reading the code
Deterministic interference reproduction	`EXECUTION-PROVEN`	a 2-instruction BPF program (`r0 = 0; exit`) via `PERF_EVENT_IOC_SET_BPF`; arm A = 8 execs observed, arm B = 0 observed, reported loss 0
Observation-integrity mitigation	`CODE-PROVEN` `TEST-PROVEN` `EXECUTION-PROVEN`	shipped at `12767ea`; sealed re-run reports `arm_a_baseline_integrity: "verified"`, `arm_b_interfered_integrity: "integrity_unknown"`, `fix_detected_the_gate: true`
`IntegrityUnknown` state	`CODE-PROVEN`	code `0x06`, non-`Active`, fails `permits_attested_use`, carried **inside the signed** `SensorHealth`
Fail-closed `CANNOT_PROVE`	`CODE-PROVEN` `TEST-PROVEN`	maps to `cannot_prove(ObserverIntegrityUnknown)` in every reconciler state gate; `t03d` / `t03e` assert a blinded observer cannot accuse

3. The distinction that matters

THE LOAD-BEARING STATEMENT

The system does not treat a valid signature over a false statement as proof of the underlying execution.

This is observed behaviour, not a slogan. In Scenario 1 the AIRI event verified — authorship and integrity *were* intact and `verify_airi_event` correctly returned `Ok`. The claim still resolved to `SELF_REPORTED` with a cardinality divergence flagged (1 claimed, 0 observed), because two mechanism-independent observers covered the window and saw nothing. A perfect signature over a false statement bought the actor nothing.

The converse case is equally load-bearing. Scenario 6 claimed an act that leaves no host-visible mark. The correct answer is "cannot be established"; the tempting wrong answer is "unsupported, therefore false". It stayed `SELF_REPORTED` and was never called false.

4. The boundary that moved

NEW AT 12767EA

Observation integrity is now treated as part of the evidence boundary.

Before `12767ea`, a live, continuity-verified observer could be silently blind and still sign `Active` coverage — and a blinded window could drive a false `PhantomClaim`, which is an accusation that a claimed execution did not happen. After `12767ea`, the coverage assertion is a function of the observer's own integrity state, and that state is inside the signed record. The fix is **fail-safe and strictly monotone**: every part can only turn a coverage claim into `CannotProve`, never the reverse, and it touches no verdict on the trusted-observation side.

5. What the validation deliberately withholds

GATE	MET?
`TOOLING_READY` · `ENVIRONMENT_READY` · `EXPERIMENT_READY` · `EXPERIMENT_EXECUTED`	yes
`EXPERIMENT_PASSED`	yes — 10/10
`REAL_WORLD_VALIDATION_PROVEN`	NO — deliberately withheld

The reasons are named rather than glossed: the subject is synthetic and its lies are the ones it was written to tell; **no model invocation was independently observed at all**, and none can be by this method; exit status, tool outcome and network ordering are not independently checkable on this host; and two of five named external tools were functionally unavailable because `CONFIG_KPROBES` is absent.

ADDENDUM E

The Observation-Integrity Milestone

> PRINCIPAL ENGINEERING INSIGHT
>
> **THE ACCOUNTABILITY OBSERVER MUST ITSELF BE ACCOUNTABLE.**
>
> This is the programme's most consequential engineering result to date, and it was produced by the validation work rather than by design review.

PHASE	WHAT HAPPENED	EVIDENCE
1	An agent claims an action.	AIRI event chain, agent-signed, verifying
2	Sniffer Dog observes runtime behaviour.	live perf tracepoint samples on a real kernel
3	An independent mechanism corroborates the observation.	A3S at `syscalls:sys_enter_execve`; ftrace; `NETLINK_AUDIT`
4	Observation interference is deliberately introduced.	a 2-instruction no-op eBPF program on `sched:sched_process_exec`
5	Sniffer Dog's blind state is detected.	`PERF_EVENT_IOC_QUERY_BPF` enumerates the foreign program; `mechanism_integrity` → `ForeignTracepointGate`, fail-closed if the query is refused
6	`IntegrityUnknown` causes fail-closed `CANNOT_PROVE`.	signed `SensorHealth` carries `0x06`; reconciler state gates map it to `cannot_prove(ObserverIntegrityUnknown)`

Why the kernel behaves this way

Stated once, so the finding is checkable rather than anecdotal. The kernel gates a tracepoint's *perf* submission on the attached BPF program's return value in `perf_trace_run_bpf_submit()`, keyed per `trace_event_call` — per tracepoint, host-wide. Every `perf_event_open` consumer of that tracepoint therefore stops receiving samples. The ftrace submission path is separate and unaffected, which is exactly the asymmetry observed, and is what makes the diagnosis certain rather than plausible.

What shipped, and what was deliberately not taken

OPTION	DECISION	REASON
H — kernel-side integrity evidence	**shipped**	the direct, synchronous detector for the reproduced gate; no new dependency, no new trust anchor
G — observation-health attestation	**shipped**	a blinded collector signs the truth, so a verifier consumes a coverage claim that is itself evidence
A — independent second mechanism required	**shipped**	always-on, needs no runtime signal, so it holds even where detection cannot run
I — fail-closed coverage assertion	**shipped**	the strongest expression of the existing trust model
C — liveness canary	not taken	a passing canary against a *targeted* gate is false assurance, which is worse than no canary
D / E / F — remote, off-host, hardware-backed	not taken	they raise the ceiling against root and kernel compromise but introduce new trust anchors; deferred to the observer-attestation roadmap rather than guessed at under time pressure

Residual, stated

A **root or kernel-level adversary that hides programs from enumeration is not defeated**, and neither is an adversary who gates both mechanisms. The collector's key-custody boundary is unchanged and is a separate boundary. Both are recorded in the decision record rather than absorbed into a success claim.

ADDENDUM F

Architectural Differentiation & USP

1. Why the architecture is different

Conventional AI-agent security and observability systems primarily address one or more of: policy enforcement, access control, prompt/input security, model security, agent observability, logging, traceability, governance. These are real problems and the products that address them are, in general, good at them.

Vanian's architectural target is a different question: **autonomous intelligence accountability**. The differentiating chain:

> WHO
> → WHAT WAS AUTHORIZED
> → WHAT WAS EXPECTED
> → WHAT ACTUALLY EXECUTED
> → WHAT WAS INDEPENDENTLY OBSERVED
> → WAS OBSERVATION INTEGRITY ESTABLISHED
> → WHAT EFFECT CAN BE ESTABLISHED
> → WHAT CAN BE CRYPTOGRAPHICALLY PROVEN

Four structural commitments make that chain more than a diagram, each `CODE-PROVEN` and `TEST-PROVEN`:

1. **The actor does not control the evidence used to judge the actor.** The probe on the observed host holds **no key** and has **no signing method**; the collector holds the key **off-host**, assigns the sequence and stamps its own clock.
2. **Coverage is re-derived, never read from the artifact being judged.** A NEXORA package has **no field** in which to state its own coverage. Exactly one of five outcomes — `AvailableAndEmpty` — licenses a statement about something *not* having happened.
3. **Severity and evidence strength are never composed into a score.** There is no `confidence: f32` anywhere in the evidence path; the permitted response is a `min` of independent caps.
4. **The proof layer re-derives rather than trusts.** The offline verifier ignores the carried result, re-runs the reconciler under the *verifier's* anchors, and refuses `ClaimNotDerivable`. `CANNOT_PROVE` cannot become `PROVEN` through packaging, export, import or transport.

> BOUNDARY OF THIS CLAIM
>
> **No claim is made that other companies cannot do these things.** This section claims only that this is the problem Vanian is architected around, and that the mechanisms above are present in code with tests that exercise them.

2. Primary USP

> PRIMARY USP
>
> **Vanian makes autonomous systems cryptographically accountable.**

The ten components of that claim, each with the honest bound attached. The term used is **architectural differentiation**, not “best in the market” — because no external benchmark has been run against any competing product.

#	ELEMENT	WHAT IT MEANS	BOUND
1	**Actor-independent accountability**	the evidence used to judge an actor is not authored, signed, sequenced or timestamped by that actor	collector key custody is a deployment obligation; a holder of that key can still lie
2	**Independent runtime observation**	kernel-sourced observation by a keyless probe, attested off-host	demonstrated on one kernel; model invocations are structurally unobservable
3	**Observation-integrity awareness**	the observer reports whether its own mechanism was intact, inside its signed record	defeats a `CAP_BPF` adversary and accidental interference; **not** a root/kernel one
4	**Explicit execution/effect separation**	no event type exists that can assert an external or physical effect	the physical side of the boundary has no mechanism yet
5	**Evidence ceilings and `CANNOT_PROVE`**	host-derived content cannot reach the top evidence class; the default verdict is “cannot prove”	this is a refusal to over-claim, not a detection capability
6	**Cryptographically bound accountability**	26 domain-separated, prefix-free signed objects; offline re-derivation from a package's own bytes	Ed25519 and SHA-256 only; **no post-quantum cryptography exists**
7	**Framework-neutral design**	one schema across LangChain, LangGraph, LlamaIndex, AutoGen, CrewAI, OpenAI-style tool calling and bespoke runtimes; no framework is a trust anchor	validated by a five-name sweep, not by production integrations
8	**One architecture across software and physical autonomy**	the verticals add no signer, verdict class or engine — asserted mechanically over comment-stripped source	the physical verticals are unvalidated against hardware
9	**Defence / UAS / robotics applicability**	profiles exist, with evidence-boundary ADRs, honest ceilings and their own suites	**application targets and roadmap**, not deployments
10	**AI-agent applicability**	exercised against a real subject agent and an independent external observer over ten adversarial scenarios	the subject is synthetic; `REAL_WORLD_VALIDATION_PROVEN` is withheld

ADDENDUM G

Competitive & Adjacent Landscape

> METHOD
>
> A company is **not** a direct competitor merely because it is an AI-security company. **No claim is made that any company cannot do something** — every “not core” reading below is a statement about *public positioning* from September 2026 sources, not about internal capability or roadmap. The objective is to locate whitespace, not to manufacture competitor weakness. Full analysis and sources: `docs/COMPETITIVE_POSITIONING.md`.

COMPANY / PROJECT	PRODUCT	PRIMARY CATEGORY	PRIMARY PROBLEM SOLVED	SW ONLY	PHYSICAL
Palo Alto Networks	Prisma AIRS + Protect AI + CyberArk	AI security platform	discover, govern and secure AI agents across an estate	yes	**no**
CrowdStrike	Falcon (AI/agent extensions)	endpoint & runtime security	detect and stop malicious behaviour on endpoints	yes	**no**
Zenity	agent security platform	AI agent security	discovery, posture, runtime defence; analyses the agent's execution path	yes	**no**
Noma Security	agentic AI security platform	AI agent security	AI discovery, risk mapping, posture, red-teaming, runtime protection	yes	**no**
WitnessAI	AI security & governance	AI governance	network visibility, intent-based controls, runtime defence	yes	**no**
Lasso Security	AI security platform	AI application security	secure adoption and governance of agents and LLM apps	yes	**no**
Aembit	workload IAM	machine identity	runtime access decisions between workloads	yes	**no**
Astrix (Cisco, 2026)	NHI security	non-human identity	discovery, ownership and posture for machine credentials	yes	**no**
Entro (SailPoint, 2026)	NHI security	non-human identity	secret and NHI lifecycle governance	yes	**no**
Oasis (Cyera, 2026)	NHI lifecycle	non-human identity	NHI lifecycle and agentic access governance	yes	**no**
SPIFFE / SPIRE (CNCF)	workload identity standard	machine identity	cryptographic workload identity in a trust domain	yes	any workload
Okta	Agent SSO + Cross App Access (MCP EMA)	agent identity & authorization	how one app's agent calls another app's data on a user's behalf	yes	**no**
Auth0 / Microsoft	Auth for MCP · Entra Agent ID	agent identity	scoped agent access; directory-native agent identity	yes	**no**
Falco (CNCF / Sysdig)	Falco · Sysdig Secure	eBPF runtime security	syscall-level threat detection and alerting	yes	**no**
Tetragon (Cilium / Cisco)	Tetragon	eBPF observability + enforcement	process-level observability and in-kernel enforcement	yes	**no**

COMPANY / PROJECT	PRODUCT	PRIMARY CATEGORY	PRIMARY PROBLEM SOLVED	SW ONLY	PHYSICAL
Tracee (Aqua)	Tracee	eBPF runtime detection	runtime detection and forensics	yes	no
LangSmith · Langfuse · Arize	agent observability	agent observability	tracing, evaluation and monitoring of agent runs	yes	no
OpenTelemetry	GenAI conventions · OBI	telemetry standards	vendor-neutral instrumentation	yes	no
Sigstore · in-toto · SLSA	provenance frameworks	cryptographic provenance	verifiable provenance for artifacts and build pipelines	yes	no
C2PA	Content Credentials	content provenance	provenance and authenticity for media	yes	no
VicOne	physical-AI cybersecurity	physical-AI security	risk assessment, pre-deployment validation and runtime protection for vehicles and AI robots	no	yes
Alias Robotics	CAI · robot security services	robot security	robot vulnerability research and hardening (ROS2)	no	yes
Upstream Security	mobility XDR	automotive security	cloud detection across connected vehicle fleets	no	yes
Nozomi · Claroty · Dragos	OT security platforms	ICS/OT security	asset visibility and threat detection in industrial networks	no	yes
Anduril · Shield AI	Lattice · Hivemind	defence autonomy	edge mission autonomy for uncrewed systems	no	yes
Palantir	Foundry · Gotham	mission data platform	data lineage and analytics for national-security workflows	mixed	as data

The instructive case: co-resident eBPF tooling

> THE MOST USEFUL COMPETITIVE FACT IN THIS DOCUMENT IS NOT COMMERCIAL
>
> Vanian's observation-integrity finding was produced by running a **third-party eBPF observer** alongside Sniffer Dog. The co-resident observer silently blinded it by attaching a program to the same tracepoint — a class of behaviour any eBPF security tool, Tetragon included, can exhibit **entirely benignly**.
>
> Two consequences follow. First, benign and malicious interference are indistinguishable by effect, so the detector must key on the *presence* of a foreign program, not on intent, and the fallback must be `INTEGRITY_UNKNOWN` rather than "attack". That is exactly what shipped. Second, **any customer running Falco, Tetragon or Tracee alongside an observation-based accountability layer is in the**

> **reproduced scenario** — which makes observation integrity a co-existence requirement, not only a security one.

The whitespace, stated conservatively


No vendor surveyed publicly positions the combination of (a) independent runtime observation with the observer's key off the observed host, (b) explicit observation-integrity semantics, (c) an execution-versus-effect distinction enforced by the absence of any event that could assert an effect, (d) `CANNOT_PROVE` as a first-class outcome, (e) offline re-derivation of a verdict by a third party, and (f) one accountability core across both software and physical autonomy.

This is a statement about public positioning as of September 2026. It is not a claim of technical exclusivity, and it should be re-tested before each fundraising cycle.

ADDENDUM H

Software AI + Physical AI

Vanian is not an "AI-agent-only" company. The category it is building in is **autonomous intelligence accountability infrastructure**: AI agents, robotics, UGVs, UAS, autonomous vehicles, industrial autonomous systems, defence autonomy, critical infrastructure and space systems.



The core does not know whether it is watching a Python agent or a companion computer on a chassis. `SystemType::UncrewedAerial` already existed at wire code `0x02` before the UAS profile was written, and the profile added **no** identifier, record type, verdict class, key, signer or proof tree — asserted mechanically, over comment-stripped source, in `tests/no_second_architecture.rs`.

> THE HONEST BOUND ON THIS SECTION
>
> **One accountability core, many autonomous worlds** is a design statement today, not a validated capability. The robotics profile's own eight-rung table shows five unobserved boundaries between an autonomy decision and a physical outcome, and `ExternalCamera` / `ExternalTracking` — the shortest path to real robotics evidence — have no implemented mechanism. **Physical validation is not complete and is not claimed to be.**

ADDENDUM I

Defence & Mission-Critical Applications

> STATUS OF THIS SECTION

> **These are application targets and roadmap. They are not completed defence deployments. No defence deployment, trial, pilot or contract is evidenced anywhere in this repository.**


USE CASE	WHAT VANIAN IS *DESIGNED TO SUPPORT*	CURRENT STATUS
Autonomous UAS	mission authority, expected execution and post-mission evidence around a flight stack	`VALIDATION TARGET` — `aip-uas` exists; no flight controller in the loop
UGVs	task authorisation and execution accountability on the companion computer	`VALIDATION TARGET` — `aip-robotics` exists; no vehicle
Robotic systems	manipulation task plans committed into a signed `ExpectedExecution`	`VALIDATION TARGET`
Mission computers	process-instance-bound execution evidence on a Linux mission computer	**demonstrated in controlled real runtime** for the Linux case
Autonomous edge systems	offline-capable evidence with no call-home and no foreign cloud in the trust path	designed; documented in the Linux edge reference
Distributed autonomous platforms	per-platform identity separate from per-compute-element identity	designed (`aip-platform`, `aip-system`)
Contested communications	evidence that survives partition; a break is reported, never bridged	designed; continuity break taxonomy implemented and tested
Mission execution accountability	reconciliation of what was authorised against what was independently observed	demonstrated for software execution
Post-mission forensic verification	offline, clock-free, network-free re-derivation of a verdict from a sealed package	**demonstrated end to end from a live run**
Operator / autonomy boundary	authorising an action is distinct from the machine performing it; four robotics safety responses are deliberately **not authorisable**	designed and implemented
Evidence preservation	hash-chained collector head with a four-kind break taxonomy carried as signed evidence	implemented and tested

Sovereignty properties relevant to defence procurement (`CODE-PROVEN`): the core depends only on standard open cryptography (Ed25519, SHA-256) through permissively licensed libraries; verification is fully offline and open-specified; there is no call-home and no foreign cloud in the trust path.

ADDENDUM J

Physical AI Validation Roadmap

Eight stages. Each states its objective, environment, independent evidence source, acceptance criteria and — as importantly — what is still *not* proven when the stage passes. Full detail: `docs/TRL_AND_PHYSICAL_VALIDATION_ROADMAP.md`.


Stage 1 → Stage 2 → Stage 3 → Stage 4 ← THE DECISIVE ONE
(DONE) ROS2/Gazebo real UGV external mechanism reaching from_attested
Stage 5 → Stage 6 → Stage 7 → Stage 8
PX4 SITL PX4 HITL controlled UAS defence/industrial pilot

#	OBJECTIVE	ENVIRONMENT	INDEPENDENT EVIDENCE SOURCE	ACCEPTANCE CRITERIA	NOT
1 DONE	reconcile an agent's signed claims against independent kernel-sourced observation	Linux 6.18.44-fc-v24, real `perf_event_open`, real processes	A3S at `sys_enter_execve`; `NETLINK_AUDIT`; ftrace (weakly independent)	10 adversarial scenarios; a signed false claim never reaches `PROVEN`; an unobservable claim is never called false; sealed evidence	non- ager invo exit egre orde `REA LID N` w
2 NEXT	run the core against a robotics autonomy stack with a signed task plan	ROS2 + Gazebo on Linux	kernel process/socket observation. **Simulator ground truth declared non-independent**	task digest reaches `parameter_digest`; autonomy process reaches `VERIFIED_EXECUTION`; every pose/contact/completion claim is `CANNOT_PROVE`	anyt phys simu not phys esta
3 TARGET	put a real controller boundary between autonomy and actuators	physical UGV with companion computer and a separate motion controller	companion-computer observation plus at least one off-machine source	controller acknowledgement recorded and explicitly **not** treated as actuation evidence; a wheel off the ground still yields `CANNOT_PROVE`	that move agre onbo are with name
4 DECISIVE	**create the first mechanism whose physical observations reach `from_attested`**	instrumented cell: fixed external camera and/or motion capture, anchored off the machine	the external tracker, with its own collector and its own key	an `ObservationRecord` from a non-onboard physical mechanism; contradiction is not resolved by majority; tracker outage yields `CANNOT_PROVE`	that trac is t — th crea trus and
5 TARGET	exercise the UAS profile against a real flight stack in SITL	PX4 SITL with companion computer	companion-computer observation only; **flight-controller telemetry is onboard, capped at `Corroborative`**	link state is the one of seven navigation quantities that becomes establishable; the other six remain unestablished	anyt an a SITL
6 TARGET	introduce a real flight controller as a second hardware element under one `PlatformId`	hardware-in-the-loop	the flight controller as a distinct `HardwareId`	a controller swap leaves `PlatformId` intact and reports `NotEstablished` for continuity	that airc
7 TARGET	a real flight with post-flight forensic verification	a permitted flight range	ground-station track and independent radio observation — **both currently unmechanised**, requiring stage 4 first	a signed mission authorisation before the flight; a NEXORA package verified **offline, afterwards, by**	that beyc airf surv oper

#	OBJECTIVE	ENVIRONMENT	INDEPENDENT EVIDENCE SOURCE	ACCEPTANCE CRITERIA	NOT
				a party that did not produce it	not deve
8 TARGET	the first deployment where evidence is consumed by someone with reason to distrust it	operationally representative site, customer-operated	operator-side collectors and operator-held anchors	pre-production blocker list closed; independent security assessment complete and remediated; false-positive budget agreed *before* deployment	unti done abou depl curr evic

Stage 4 gates every physical claim in the programme. Until a mechanism exists whose observations reach `from_attested`, stages 3, 6 and 7 can only demonstrate accountability for the *computer*, never for the *machine*.

ADDENDUM K

Commercialization Roadmap

> FRAMING DISCIPLINE
>
> Every number in this section and the two that follow is a **TARGET** or a **PLANNING ASSUMPTION**. None is committed capital, a term sheet, an indication of interest, a third-party valuation, or a fairness opinion. **No investor is named because none is evidenced. No customer is named because none exists.**

1. Investment thesis

THE PROBLEM	Autonomous systems increasingly act without continuous human supervision, and their own logs and claims are often the evidence used to judge them. When an agent reports it called a tool, when a robot reports a successful grasp, when a UAS reports a completed mission — the report and the actor are the same party. A signature over that report proves authorship, not occurrence.
THE VANIAN THESIS	**The actor should not control the evidence used to judge the actor.** Implemented as a structural property: the probe holds no key and has no signing method; the collector holds the key off-host; the verifier re-derives rather than believes.
THE PRODUCT	Identity + authority + execution accountability + independent observation + observation integrity + evidence/proof.
THE EXPANSION	AI agents → robotics → UAS → autonomous vehicles → industrial autonomy → defence autonomy → critical infrastructure → space systems.
THE MOAT	Not merely models. Not merely telemetry. Not merely IAM. Not merely observability. The moat is the accountability architecture + security semantics + independent observation + evidence/proof model + vertical expansion — with the qualification that the vertical expansion is, today, architecture and documentation rather than validated capability.

2. The round

TARGET: USD 10M Pre-Series A. Not raised, not committed, not term-sheeted.
Its purpose is to convert an evidence-strong software core into a validated physical-autonomy accountability layer with commercial references.

#	WHAT THE ROUND FINANCES
1	Physical validation — roadmap stages 2–4, culminating in the first physical quantity established by an independent mechanism
2	Defence / industrial pilots — the first deployments where evidence is consumed by someone with a reason to distrust it
3	Independent security validation — third-party assessment and remediation, currently a pre-deployment blocker
4	Hardware / edge deployment work, including the hardware-rooted observer trust ADR-002 only proposes today
5	OEM / strategic integrations
6	Production hardening — TLS, rate limiting, KMS/HSM, backups, DR/BCP, metrics, runbook
7	Compliance / certification mapping for target jurisdictions and sectors
8	Deployment and field engineering
9	Expanded observer mechanisms — remote and off-host observation, explicitly deferred by the integrity decision record
10	International go-to-market; category creation is a real cost and is budgeted, not assumed away

3. Milestone-based capital deployment

Milestones are **evidence gates**, not calendar events.

MILESTONE	BECOMES TRUE	STILL UNTRUE AFTERWARDS
M1 AIRI + Sniffer Dog production validation	a non-synthetic agent framework under representative load, with corroboration rates measured and the false-positive rate of `uncorroborated` characterised	anything physical
M2 Physical robotics validation	roadmap stages 2 → 3 → 4; an external mechanism produces an `ObservationRecord` for a physical quantity	that it generalises beyond one cell and one robot
M3 UAS / PX4 validation	stages 5 → 6 → 7; a real flight with post-mission offline verification by a party that did not produce the package	that any navigation quantity is establishable without the stage-4 mechanism
M4 First defence / industrial pilot	an operationally representative deployment with operator-held anchors and an agreed false-positive budget	recurring revenue
M5 Recurring paid deployments	paid, renewing, referenceable customers	distribution leverage — this is still direct sales
M6 OEM / platform integration	the accountability layer embedded in a third-party autonomy platform	—

M2 is the pivotal one. It is the single step that converts “one accountability core, many autonomous worlds” from a design statement into an engineering result.

ADDENDUM L

USD 10M Pre-Series A — Value Creation Logic

```
TECHNICAL DE-RISKING
  → PHYSICAL VALIDATION
    → DEFENCE / INDUSTRIAL PILOTS
      → PRODUCTION HARDENING
        → COMMERCIAL REFERENCES
          → RECURRING REVENUE
            → OEM INTEGRATION
              → NEXT INSTITUTIONAL ROUND
```

NEXT-ROUND PLANNING ASSUMPTION

A **USD 8–10M** institutional round in the subsequent financing step at an **illustrative USD 40–60M pre-money range** — **only if** the milestone evidence supports it. This is a planning framework. It is not a forecast, not a guarantee, and not a statement that any investor has indicated such terms.

Indicative use of proceeds

Indicative only. Not a budget, not a commitment.

AREA	INDICATIVE SHARE	RATIONALE
Physical validation engineering (stages 2–4)	~30%	the pivotal milestone; everything above TRL 4 on the physical axis depends on it
Production hardening + independent security assessment	~20%	the pre-production blocker list gates every pilot
Defence / industrial pilot delivery and field engineering	~20%	the first deployment where evidence is consumed adversarially
UAS / PX4 validation (stages 5–7)	~12%	parallel vertical, shares the software boundary
OEM / integration engineering and partnerships	~10%	the channel that makes the layer worth more embedded than standalone
Compliance, certification mapping, IP prosecution	~8%	jurisdiction-specific and unavoidable for defence and critical infrastructure

---

ADDENDUM M

Valuation Planning Framework


> STATUS OF EVERY FIGURE BELOW
>
> **These are internal strategic planning ranges. They are not third-party valuations, fairness opinions, or guaranteed future company values. No independent valuer has assessed this company.**

Current

FRAME	RANGE	BASIS
Engineering / technology reference assessment	**₹30–50+ Cr** internal strategic range	the code, the validation evidence and the IP position as they stand
Institutional fundraising planning	**₹30–35 Cr** pre-money target range	the round being planned
Strategic floor	**approximately ₹25 Cr** pre-money	the level below which the round is not worth the dilution
Potential strategic premium	**₹40 Cr+**	where a highly strategic investor materially accelerates validation or adoption

Post-validation milestone ladder

Each rung is gated on evidence that does not yet exist. A rung is not reached by time passing.



MILESTONE	PLANNING CLASS	EVIDENCE GATE
Physical reference deployment	**₹50–80 Cr class**	a physical quantity established by an independent mechanism (roadmap stage 4)
Defence / industrial pilot	**₹75–120 Cr class**	operationally representative deployment, operator-held anchors, independent security assessment complete
Recurring commercial deployments	**₹150 Cr+ class**	paid, renewing, referenceable
OEM / platform integration	**₹300 Cr+ potential strategic scale**	the layer embedded in a third-party autonomy platform

---

ADDENDUM N

Technology Moat & IP Position

1. Technology moat

Each differentiator is listed with the evidence class that supports it. Nothing here is asserted at a level the repository does not carry.

MOAT ELEMENT	CLASS	ANCHOR
Fail-closed evidence semantics	`CODE-PROVEN` `TEST-PROVEN`	`finish()` rewrites a failed proposal to `(CannotProve, Heuristic, InvariantNotSatisfied)`
`CANNOT_PROVE` as a first-class security outcome	`CODE-PROVEN` `TEST-PROVEN`	`ReconciliationResult::default()` is `CannotProve`, asserted by test
Independent observation	`CODE-PROVEN` `EXECUTION-PROVEN`	keyless probe / off-host collector split; live capture on a real kernel
Observation-integrity handling	`CODE-PROVEN` `EXECUTION-PROVEN`	`IntegrityUnknown` inside signed health; gate-independent mechanism required for coverage
Execution / effect distinction	`CODE-PROVEN` `TEST-PROVEN`	`aip-effect`; three tool layers with **no** event asserting layer 3
Evidence ceilings	`CODE-PROVEN` `TEST-PROVEN`	content-derived verdicts require `strength == Attested` **exactly**; over-claiming is downgraded
Signed execution/event binding	`CODE-PROVEN` `TEST-PROVEN`	process instance `(pid, start ticks, boot id)`; content-hashed executable, not path
Framework neutrality	`TEST-PROVEN`	`no_framework_is_a_trust_anchor` sweeps five names and asserts identical outcomes
Cryptographic evidence	`CODE-PROVEN`	26 domain-separated tags; prefix-free canonical encoding; RFC 6962 Merkle
NEXORA offline verification	`EXECUTION-PROVEN`	a separate verifier process refused 8 mutations of a live package
Reusable vertical profile architecture	`TEST-PROVEN`	UAS and robotics add no signer, verdict class or engine; ADR-007 governs composition
Linux edge foundation	`EXECUTION-PROVEN`	three-process live reference reaching `VERIFIED_EXECUTION`
UAS / robotics extensions	`CODE-PROVEN` `TEST-PROVEN`	`aip-uas`, `aip-robotics` with their own suites and ADRs
Patent portfolio	see §2	**pending applications — not granted patents**

Two moat elements are deliberately absent because the repository does not support them: post-quantum cryptography (none exists on this branch) and hardware-rooted trust (ADR-002 is PROPOSED).

2. IP position

> STATUS DISCIPLINE
>
> **Pending Indian patent applications** are described as *pending*. Nothing in this document says “patented”, “granted” or “issued”. **No filing receipt, application number or filing date appears anywhere in the repository**; a diligence reader

> should obtain the filing particulars from counsel rather than from this document. **No monetary value is assigned to any patent here.**

#	SUBJECT	REPOSITORY EVIDENCE	IMPLEMENTED IN CURRENT CODE?
1	**Hardware-based AI monitoring / physical containment**	no dossier for this subject was located in `reports_and_patents/`. Adjacent design intent exists as **ADR-002 (PROPOSED)** and in `aip-containment` (cgroup v2 freezer, advisory by default)	**No.** `INVENTION_REGISTER.md` states hardware-backed key storage and kernel-resident eBPF/XDP sensing are not implemented
2	**AI-safe distributed consensus + post-quantum provenance**	`reports_and_patents/PATENT_DOSSIER_CCVL_AIP.md` — Cross-Channel Verification Logic with BFT quorum escalation and a PQC-signed audit trail, prepared for the Indian Patent Office (CRI 2025) and USPTO	**No.** No PQC and no consensus mechanism exists on `main` or the production branch

Patent scope versus current code implementation — different sets, not to be conflated

THE APPLICATIONS ARE INTENDED TO SUPPORT	THE REPOSITORY CURRENTLY IMPLEMENTS
independent hardware monitoring · physical containment · AI-safe distributed consensus · provenance verification · cryptographic trust infrastructure	software-only independent observation · software containment gates (advisory by default, and per the audit's §13 deliberately unreachable from engine-produced evidence) · Ed25519/SHA-256 provenance · offline proof re-derivation

No patent claim should be presented as already reduced to practice in this repository unless it is one of the nine mechanisms catalogued in `docs/IP/INVENTION_REGISTER.md` — and that register itself states that no prior-art search has been performed, that no entry is asserted to be novel or patentable, and that post-quantum cryptography, hardware-backed key storage, kernel-resident eBPF/XDP sensing and field deployment "appear nowhere above, because none of them is implemented."

Two IP risks are carried forward from the audit, unchanged: **IP-2**, the strongest mechanisms exist only on the unmerged production branch, so any filing must be anchored to that tree; and **IP-3**, the commits carrying this work have a single machine author identity, and a documented human conception and reduction-to-practice record does not exist in the repository.

ADDENDUM O

Maturity Scorecard & Remaining Gaps

1. Scorecard

ENGINEERING MATURITY VISUALIZATION — QUALITATIVE		
ARCHITECTURE		boundaries enforced by the compiler and by tests, not by convention
CRYPTOGRAPHY		encoding, domain separation and Merkle construction sound and adversarially tested
AIRI		34 properties with cited tests; exercised against an independent observer
SNIFFER DOG		live capture on a real kernel, corroborated by a third-party observer
OBSERVATION INTEGRITY		reproduced, mitigated, re-verified — all within one environment
NEXORA		offline re-derivation demonstrated end to end from a live run
REAL LINUX		one host, one kernel, `CONFIG_KPROBES` absent
AI AGENT		subprocess execution corroborated; model layer structurally not
ROBOTICS		profile, ADRs, tests, and a live run that proves the computer
UAS		profile, ADR-005, tests; no PX4, no airframe
PHYSICAL EFFECT		the boundary is implemented; the effect is unobservable
HARDWARE TRUST		ADR-002 PROPOSED; nothing implemented
FIELD DEPLOYMENT		none

Engineering maturity visualization — qualitative. The bars are a reading aid. They are NOT mathematical measurements, not percentages, not a score, and nothing in this programme is derived from them. The authoritative statements are the classifications in Addendum B and the TRL assessments in Addendum C.

2. Remaining gaps

Listed without softening. This section is the reason the rest of the document is credible.

Physical and hardware

1. **Physical autonomous-system validation is pending.** No robot, no vehicle, no airframe has been in the loop. *"No robot was involved."*

2. **External physical tracking is pending.** `ExternalCamera` and `ExternalTracking` are named in the profile and have **no implemented mechanism**; positional independence without a mechanism is nobody observing.
3. **Hardware-rooted observation trust is pending.** ADR-002 is PROPOSED. A TPM on a companion computer would strengthen claims about the *computer* and say nothing about the arm.
4. **Controller and chassis substitution are undetectable.** Nothing measures either.

Trust boundaries that remain open

5. **The collector key-custody boundary remains.** A forger holding the collector key can still sign a false state — a separate boundary, not closed by the integrity work.
6. **The root/kernel adversary boundary is not closed.** *"Root is assumed benign. Nothing here survives a root-privileged adversary, and `CAP_BPF` alone is enough."*
7. **Model invocations are structurally unobservable.** Half the AIRI chain cannot be corroborated by any host observer, by construction.
8. **Chain truncation at the head is undetectable**, and an agent that never emits an event leaves an intact chain.
9. **Bundle signer identity is unanchored.** A bundle signature answers "this manifest matches this key", not "this manifest came from anyone in particular".
10. **Packet timestamps are the agent's assertion.** R16 bounds what a verifier will accept; it does not make any timestamp true.

Programme and process

11. **Full defence deployment is not demonstrated.** No pilot, no trial, no contract is evidenced.
12. **Independent third-party security validation is pending** — listed as a pre-deployment blocker.
13. **CI maturity.** The audit's B-10 (two independent Cargo roots) is **closed**; remaining: no metrics/monitoring export, no runbook, and live-kernel tests that are environment-sensitive (see §3).
14. **Production deployment evidence is still incomplete.** TLS, rate limiting, KMS/HSM, backups, DR/BCP, retention controls and control-framework mapping are all open.
15. **`REAL_WORLD_VALIDATION_PROVEN` is deliberately withheld.** The subject agent is synthetic and its lies are the ones it was written to tell.
16. **Two of five named external validation tools were functionally unavailable** (`CONFIG_KPROBES` absent), and one was unavailable entirely.

3. Verification note on the test suite

An independent re-run of `cargo test --workspace` was performed for this addendum on `12767ea`, on `cargo` / `rustc` 1.94.1, Linux 6.18.44-fc-v24, x86_64.

ATTEMPT	RESULT	READING
First	964 passed / **32 failed**	all 32 shared one cause and were **not** product defects — the `aip-edge-observer` helper binary was not present beside the test binaries, and every one panicked with that message from `aip-edge/tests/common/mod.rs:58`
After `cargo build -p aip-edge-observer -p aip-edge-workload`	**1,691 passed / 0 failed / 6 ignored / 165 binaries / 0 warnings / exit 0**	the second run's binaries include `build_boundary`, `key_custody`, `managed_signing`, `replay_ingest` and `temporal_bound` — the `aip-service` suites — so one command now spans the protocol and the tier that serves it. Blocker **B-10** closed, demonstrably

The first attempt is recorded rather than omitted, because a live-kernel suite whose result depends on build ordering is itself a CI maturity finding.

ADDENDUM P

Source Mapping

Every material claim in this addendum, traced to its source, with its evidence type and status. **A claim that is not in this table should be treated as unsupported.** Extended version, including the full reproduction record: `docs/ENGINEERING_MATURITY_SOURCE_MAP.md`.

1. Checkpoint and provenance

CLAIM	SOURCE	EVIDENCE TYPE	STATUS
Production branch head is `12767ea`	`git ls-remote origin`	EXECUTION-PROVEN	verified
`12767ea` closes the observer-integrity boundary in production	commit message + `OBSERVATION_INTEGRITY_DECISION_RECORD.md`	CODE-PROVEN	verified
`ff52dc2` is the observation-integrity / validation work	`git log`	CODE-PROVEN	verified, ancestor of `12767ea`
`main` is `872dbf3` and untouched	`git ls-remote`; `git rev-list --count` = 228	EXECUTION-PROVEN	verified
Skills 16–24 implemented	skill files + crates `aip-system`, `aip-execution`, `aip-platform`, `aip-observation`, `aip-effect`, `aip-edge*`, `aip-uas`, `aip-robotics`	CODE-PROVEN	verified
Skills 25–30 are **specifications only**	skill files present; **no corresponding crates exist**	CODE-PROVEN	verified — no implementation claimed

2. Engineering maturity

CLAIM	SOURCE	EVIDENCE TYPE	STATUS
28-crate workspace with explicit boundaries	root `Cargo.toml` members	CODE-PROVEN	verified
Verticals add no signer, verdict class or engine	`aip-uas/tests/no_second_architecture.rs` ; `aip-robotics/tests/cross_vertical.rs`	TEST-PROVEN	verified
26 distinct domain tags	`aip-nexora/tests/audit.rs::DOMAINS` ; `INVENTION_REGISTER.md` IR-09	TEST-PROVEN	verified
No post-quantum cryptography on this branch	`INVENTION_REGISTER.md` closing section; audit Report 05 §6	CODE-PROVEN	verified
Rust/Python byte parity across 9 vectors	`parity_vectors.rs` ; `test_canonical_parity.py`	EXECUTION-PROVEN	verified
Live perf-tracepoint capture on kernel 6.18.44-fc-v24	`validation/observation_integrity/results/*/environment.txt` , `*_sniffer_dog.jsonl`	EXECUTION-PROVEN	verified
Interference reproduced: 8 execs → 0 observed, loss 0	`results/20260907T154934Z/verdict.json`	EXECUTION-PROVEN	verified
Mitigation detects the gate	`results/20260907T_fix_verified/verdict.json` : `arm_a="verified"` , `arm_b="integrity_unknown"` , `fix_detected_the_gate: true`	EXECUTION-PROVEN	verified
Suppression is total within the confirmed window (15/15 execs missed)	`harness/window_analysis.py` + audit-subsystem ground truth	EXECUTION-PROVEN	verified
`OBSERVE_PROTOCOL_VERSION` 8 → 9, once	`aip-observe/src/observed.rs:51`	CODE-PROVEN	verified
`IntegrityUnknown` is code `0x06` , non-`Active`	`aip-observe/src/health.rs:44,55`	CODE-PROVEN	verified
A blinded observer cannot accuse	`aip-reconcile` `t03d` / `t03e` ; `aip-observe/tests/observer_integrity.rs`	TEST-PROVEN	verified — the binary ran and passed in the re-run
The offline verifier re-derives rather than trusts	`aip-nexora/src/verify.rs` (`rederive` , `ClaimNotDerivable`)	CODE-PROVEN	verified

CLAIM	SOURCE	EVIDENCE TYPE	STATUS
8 mutations of a live package refused by a separate verifier process	`ghost-demo/tests/live_nexora.rs::g14_05`	EXECUTION-PROVEN	verified
10 adversarial AIRI scenarios executed, 10 passed	`AIRI_REAL_WORLD_VALIDATION.md` §9–10; validation matrix	EXECUTION-PROVEN	verified
`REAL_WORLD_VALIDATION_PROVEN` is withheld	same document, §10 acceptance table	DOCUMENTED	verified — deliberately not claimed
2 of 11 UAS telemetry sources can produce an `ObservationRecord`	`UAS_ACCOUNTABILITY_PROFILE.md` §4; ADR-005	CODE-PROVEN	verified
`unobserved_boundaries_to_outcome() == 5`	`ROBOTICS_ACCOUNTABILITY_PROFILE.md` §3	CODE-PROVEN	verified
No robot was involved	same, §12.6	DOCUMENTED	verified — quoted verbatim
Hardware attestation is PROPOSED, not implemented	ADR-002; `INVENTION_REGISTER.md` IR-04	DOCUMENTED	verified
TLS, rate limiting, KMS/HSM, backups, DR/BCP, metrics, runbook are open	`docs/PRODUCTION_READINESS.md`	DOCUMENTED	verified
A3S Observer 0.11.0 built from source and run as an independent witness	`validation/external/a3s_observer/STATUS.md`	EXTERNAL-CORROBORATED	verified
No third-party security assessment has been performed	`PRODUCTION_READINESS.md` (pre-deployment blocker)	DOCUMENTED	verified

3. Commercial, IP and valuation

CLAIM	SOURCE	EVIDENCE TYPE	STATUS
USD 10M Pre-Series A	operator direction	**TARGET**	**not committed capital; no term sheet or indication of interest evidenced**
Illustrative next round USD 8–10M at USD 40–60M pre-money	operator direction	**PLANNING ASSUMPTION**	**illustrative; contingent on milestone evidence**
₹30–50+ Cr technology reference range	operator direction	**INTERNAL PLANNING RANGE**	**not a third-party valuation or fairness opinion**
₹30–35 Cr pre-money target; ₹25 Cr floor; ₹40 Cr+ premium	operator direction	**INTERNAL PLANNING RANGE**	same
₹50–80 / ₹75–120 / ₹150+ / ₹300+ Cr ladder	operator direction	**INTERNAL PLANNING RANGE**	each rung gated on evidence that does not yet exist
Two pending Indian patent applications	operator statement; `PATENT_DOSSIER_CCVL_AIP.md` maps to application 2	**PENDING APPLICATION**	**no filing receipt, number or date in the repository**; no dossier located for application 1
Patent subject matter is **not** implemented in current code	`INVENTION_REGISTER.md` closing section	`CODE-PROVEN`	verified
Copyright owner recorded as K. NAGA SRI GANESH	`README.md`; commit `6c407d0`	`DOCUMENTED`	verified as a repository record; the corporate relationship to the Vanian entity is not asserted here
No defence deployment exists	absence of any such evidence	`UNKNOWN` → treated as **not demonstrated**	no pilot, trial or contract evidenced
No customer exists	same	**TARGET MARKET, not customer**	explicitly not converted

4. Forensic-audit findings — status at `12767ea`

The original findings are not altered. This table records subsequent work against them; its authority is the repository's own reconciliation document plus the spot checks named beside each row.

ID	ORIGINAL FINDING	STATUS AT `12767EA`	EVIDENCE
B-1	verifier had no clock	**CLOSED** in `aip-protocol` (R16)	`FINAL_AUDIT_RECONCILIATION.md` P0-1
B-1a	`aip-service` supplied no verification time	**CLOSED** — `evidence.rs:430` defaults to the service's own clock, so omitting the field means “apply the bound the service knows”, not “apply no bound”	CODE-PROVEN; `tests/temporal_bound.rs` passed in the re-run
B-2	delegation issuer unbound to previous grantee	**CLOSED, unconditional**	`FINAL_AUDIT_RECONCILIATION.md` P0-2
—	(new) chain verified from an unauthenticated root	**CLOSED** — found by the programme itself	P0-3
B-3	containment unreachable from engine output	**ACCEPTED / JUSTIFIED** — a design decision was taken and recorded, not a silent fix	§13
B-4	bundle verified against a self-supplied key	**PARTIALLY ADDRESSED** — reframed as a container-integrity check; **the signer's identity is still unanchored**	bundle section; carried forward as a gap
B-5	private keys written with default permissions	**PARTIALLY FIXED** — `store.rs:362-367` sets mode `0o600`; a passphrase-wrapped backend exists; **the plaintext backend still stores a seed at rest and no KMS/HSM is used**	CODE-PROVEN
B-6	service mints a new identity on an unreadable key	**CLOSED** — a key is created only when the file is *absent*; an existing file that fails permission, base64 or length checks returns an error rather than regenerating	CODE-PROVEN
B-7	private seeds accepted in HTTP bodies	**still present by design in managed/dev mode**, with redacting `Debug`	CODE-PROVEN
B-8	packet replay undetected	`aip-service/tests/replay_ingest.rs` exists and passes; protocol-layer replay not re-verified here	partially addressed
B-9	`Reconciliation` constructible outside the engine	**CLOSED** — `#[non_exhaustive]` with a crate-private `provenance` field	CODE-PROVEN; §14
B-10	`aip-service` in no workspace	**CLOSED** — one workspace root; service suites ran in the re-run command	CODE-PROVEN EXECUTION-PROVEN
B-11	observer-directed verdicts lack a structural precondition	**not re-verified for this addendum**	open unless shown otherwise

One row above is explicitly not re-verified (B-11) and one is only partially so (B-8). They are listed that way rather than assumed closed. **The absence of a finding from this table is not evidence that the corresponding property holds.**

ADDENDUM Q


Milestone Gates & Target State

1. What must be true before each claim can be upgraded

CLAIM TO BE UPGRADED	GATE	CURRENT STATE
Software core → TRL 6	a non-synthetic agent framework under representative load, with a characterised false-positive rate	not started
Robotics profile → TRL 5	ROS2 + Gazebo with a declared, non-independent ground truth, then a real controller boundary	not started
Physical accountability → TRL 4	one physical quantity established by a mechanism reaching `from_attested`	**blocked on an `aip-observation` mechanism that does not exist**
UAS profile → TRL 5	PX4 SITL with the flight stack treated as onboard, not independent	not started
Observation integrity → TRL 6	the detector exercised outside the reproduction environment, across kernels and co-resident tooling	not started
Production readiness	the seven-item pre-production blocker list	open
Any defence claim	a pilot with operator-side independent evidence	not started

2. Target state — 18 to 30 months

> TARGET, NOT STATUS
>
> **Vanian as the accountability layer for autonomous systems** — across AI agents, robotics, UAS, autonomous vehicles, industrial autonomy, defence systems, critical infrastructure and space autonomy, with identity, authority, execution accountability, independent observation, observation integrity, effect assessment and cryptographic proof.
>
> Today, exactly one of those eight domains has been validated in a controlled real runtime, and it is the software one.



ADDENDUM R

Conclusion

The evidence supports a strong engineering position and does not support a finished product.

What is strong

The epistemic discipline is real, implemented, and unusual: a default verdict of "cannot prove", an evidence ceiling that structurally bars host-derived content from the top class, coverage re-derived rather than read, a response ceiling that refuses to compose severity with confidence, and an offline verifier that re-derives instead of believing.

That discipline survived its first contact with an independent external observer, and — more tellingly — that same observer exposed a way to silently blind the observation layer, which was then reproduced deterministically and closed in production **without weakening a single one of those properties**.

What is not finished

The physical half of the thesis is architecture and documentation. There is no robot, no airframe, no external tracker, no hardware root of trust, no third-party security assessment and no field deployment. The UAS and robotics profiles are careful, honest and unvalidated against hardware.

What follows

The next value-creating milestone is not a feature. It is **the first physical quantity established by an independent mechanism rather than asserted by the machine that moved** — because that is the single step that turns "one accountability core, many autonomous worlds" from a design statement into an engineering result.

ENGINEERING STATUS

TRL 5 overall; AIRI/Sniffer Dog software accountability core approaching TRL 6; physical autonomous-system validation pending.

STANDING OF THIS ADDENDUM

This addendum reflects engineering and validation progress after the original forensic audit baseline. It does not retroactively alter the original forensic findings.

Addendum companion documents in the repository: `docs/ENGINEERING_MATURITY_AND_STRATEGIC_READINESS.md` · `docs/ENGINEERING_MATURITY_SOURCE_MAP.md` · `docs/COMPETITIVE_POSITIONING.md` · `docs/PRE_SERIES_A_10M_ROADMAP.md` · `docs/TRL_AND_PHYSICAL_VALIDATION_ROADMAP.md`.
Assessment method: read-only. The production branch tree was obtained with `git archive` into a scratch directory; no product source, test or configuration file was modified on that branch, and no branch was checked out or merged. Test figures were produced by running the suite on that extracted tree.

Read-only forensic audit. No product source, test, or configuration file was modified; no commit was created on any product path; no branch was checked out or merged. Branch trees were obtained via `git archive` into a scratch directory. All 54 resolvable `file:line` citations were mechanically verified in range against the extracted trees.
Two findings were withdrawn during verification and are recorded as such rather than deleted: a suspected `MAX_DELEGATION_DEPTH` off-by-one (the bound is a correctly documented strict inequality) and a suspected domain-tag typo (`AIP/ScopedTokeN/v1` is a deliberate near-miss test fixture).