

Other commonly used text formatting tags:

- The HTML `<u>` element is used to underline text.

```
<p>  
    <u>Batman</u> is a fictional comic character created by artist Bob Kane and  
writer Bill Finger.  
    <br>  
    Batman first appeared in DC comics in the year 1937 and soon became  
popular  
.</p>
```

- The HTML `<mark>` element is used to highlight text.

```
<p>  
    <u>Batman</u> is a fictional comic character created by artist Bob Kane and writer  
Bill Finger. <br> Batman first appeared in DC comics in the year 1937 and soon  
became popular.  
</p>
```

- The HTML `<tt>` element is used to make text appear as if it is typed by a typewriter.

```
<p>  
<tt>Batman</tt> is a fictional comic character created by artist Bob Kane and writer  
Bill Finger.<br>Batman first appeared in DC comics in the year 1937 and soon  
became popular.  
</p>
```

- The HTML `` element is used to define a deleted (removed) text.

```
<p>  
<b>Batman</b> is a fictional comic character created by artist Bob Kane and writer  
Bill Finger.<br>Batman first appeared in DC comics in the year 1937 <del>and soon  
became popular</del>.
```

</p>

The default font-size of heading tags are:

- <h1>: 32px;
- <h2>: 24px;
- <h3>: 19px;
- <h4>: 16px;
- <h5>: 14px;
- <h6>: 13px;