

Quantum Build Manifest & Schematic Overview

1. Core Components

- Dual Shaft Electric Motor (24V or 48V, Base-Mount) – Central driver
- 12 Copper Coil Arrays (6 pairs, opposing vortex spirals)
- 12 Quantum Vacuum Tubes – Frequency resonance amplifiers
- Toroidal Housing – 24" diameter, Golden Ratio-based design
- Magnetic Assemblies – Neodymium pairs per shaft side (NS/SN)
- Crystal Core (optional) – Quartz / Herkimer / Moldavite

2. Functional Modes

- Pulse Mode: Plasma bursts for energy clearing/healing
- Continuous Mode: Constant etheric broadcast to grid
- Inversion Mode: Entropy reversal through reverse torque

3. Assembly Notes

- Ensure magnetic field symmetry to balance plasma flow
- Wire coils in harmonic pairs (based on 432Hz or 528Hz tuning)
- Vacuum tubes may be powered by low voltage or static field taps
- Center crystal is not mandatory but highly recommended

4. Integration & Usage

- Place device in quiet, energetically neutral space
- Ground frame; allow barefoot interaction for human entrainment
- Use intention and breath to activate field
- Document energetic changes (emotions, sensations, dreams)



This schematic is intended for spiritual and experimental energy exploration only. Use with a