

# CIS-2266 Pandas dropbox

- Complete the exercise below
- Output completed notebook to HTML or PDF
- Upload to the Dropbox for grading

## Importing pandas

### Getting started and checking your pandas setup

Difficulty: *easy*

1. Import pandas under the name `pd` . (1 point)

```
In [24]: import pandas as pd
```

2. Print the version of pandas that has been imported. (1 point)

```
In [25]: print('Pandas version ' , pd.__version__)
```

Pandas version 1.1.3

## DataFrame basics

### A few of the fundamental routines for selecting, sorting, adding and aggregating data in DataFrames

Difficulty: easy

Consider the following Python dictionary `data` and Python list `labels` :

```
data = {'animal': ['cat', 'cat', 'snake', 'dog', 'dog', 'cat',  
                  'snake', 'cat', 'dog', 'dog'],  
        'age': [2.5, 3, 0.5, np.nan, 5, 2, 4.5, np.nan, 7, 3],  
        'visits': [1, 3, 2, 3, 2, 3, 1, 1, 2, 1],  
        'priority': ['yes', 'yes', 'no', 'yes', 'no', 'no', 'no', 'no', 'yes', 'no']}
```

```
labels = ['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h', 'i', 'j']
```

**3.** Create a DataFrame `df` from this dictionary `data` which has the index `labels` .(1 point)

```
In [26]: #Use:
import numpy as np
data = {'animal': ['cat', 'cat', 'snake', 'dog', 'dog', 'cat', 'snake',
                  'age': [2.5, 3, 0.5, np.nan, 5, 2, 4.5, np.nan, 7, 3],
                  'visits': [1, 3, 2, 3, 2, 3, 1, 1, 2, 1],
                  'priority': ['yes', 'yes', 'no', 'yes', 'no', 'no', 'no', 'no', 'yes', 'yes']}

labels = ['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h', 'i', 'j']

# Code Goes Below:
df = pd.DataFrame(data, index = labels)
print(df)
```

	animal	age	visits	priority
a	cat	2.5	1	yes
b	cat	3.0	3	yes
c	snake	0.5	2	no
d	dog	NaN	3	yes
e	dog	5.0	2	no
f	cat	2.0	3	no
g	snake	4.5	1	no
h	cat	NaN	1	yes
i	dog	7.0	2	no
j	dog	3.0	1	no

4. Display a summary of the basic information about this DataFrame and its data. (1 point)

```
In [27]: print("Summary of DataFrame and its data: ", df.info())
```

```
<class 'pandas.core.frame.DataFrame'>
Index: 10 entries, a to j
Data columns (total 4 columns):
#   Column      Non-Null Count  Dtype
---  -
0   animal      10 non-null     object
1   age         8 non-null      float64
2   visits      10 non-null     int64
3   priority    10 non-null     object
dtypes: float64(1), int64(1), object(2)
memory usage: 400.0+ bytes
Summary of DataFrame and its data:  None
```

5. Return the first 3 rows of the DataFrame df . (1 point)

In [28]: `print(df.iloc[:3])`

	animal	age	visits	priority
a	cat	2.5	1	yes
b	cat	3.0	3	yes
c	snake	0.5	2	no

6. Select just the 'animal' and 'age' columns from the DataFrame `df` . (1 point)

In [29]: `print(df[['animal', 'age']])`

	animal	age
a	cat	2.5
b	cat	3.0
c	snake	0.5
d	dog	NaN
e	dog	5.0
f	cat	2.0
g	snake	4.5
h	cat	NaN
i	dog	7.0
j	dog	3.0

7. Select the data in rows `[3, 4, 8]` and in columns `['animal', 'age']` . (1 point)

In [30]: `print(df.iloc[[3,4,8], [0,1]])`

	animal	age
d	dog	NaN
e	dog	5.0
i	dog	7.0

8. Select only the rows where the number of visits is greater than 3. (1 point)

In [31]: `print("Rows where number of visits >3: ")`  
`print(df[df['visits']>3])`

```
Rows where number of visits >3:
Empty DataFrame
Columns: [animal, age, visits, priority]
Index: []
```

9. Select the rows where the age is missing, i.e. is `NaN` . (1 point)

In [32]: `print(df[df['age'].isnull()])`

	animal	age	visits	priority
d	dog	NaN	3	yes
h	cat	NaN	1	yes

10. Select the rows where the animal is a cat *and* the age is less than 3. (1 point)

In [33]: `print(df[(df['animal'] == 'cat') & (df['age'] < 3)])`

	animal	age	visits	priority
a	cat	2.5	1	yes
f	cat	2.0	3	no

11. Select the rows the age is between 2 and 4 (inclusive). (1 point)

In [34]: `print(df[df['age'].between(2,4)])`

	animal	age	visits	priority
a	cat	2.5	1	yes
b	cat	3.0	3	yes
f	cat	2.0	3	no
j	dog	3.0	1	no

12. Change the age in row 'f' to 1.5. (1 point)

In [35]: `df.loc['f', 'age'] = 1.5`  
`print(df)`

	animal	age	visits	priority
a	cat	2.5	1	yes
b	cat	3.0	3	yes
c	snake	0.5	2	no
d	dog	NaN	3	yes
e	dog	5.0	2	no
f	cat	1.5	3	no
g	snake	4.5	1	no
h	cat	NaN	1	yes
i	dog	7.0	2	no
j	dog	3.0	1	no

13. Calculate the sum of all visits (the total number of visits). (1 point)

```
In [36]: print(df['visits'].sum())
```

```
19
```

**14.** Calculate the mean age for each different animal in df . (1 point)

```
In [37]: print("mean :", df['age'].mean())
```

```
mean : 3.375
```

**15.** Append a new row 'k' to df with your choice of values for each column. Then delete that row to return the original DataFrame. (1 point)

```
In [38]: df.loc['k'] = ['horse', 5.5, 2, 'yes']
print(df)

df = df.drop('k')
print("\nOriginal DataFrame:")
print(df)
```

	animal	age	visits	priority
a	cat	2.5	1	yes
b	cat	3.0	3	yes
c	snake	0.5	2	no
d	dog	NaN	3	yes
e	dog	5.0	2	no
f	cat	1.5	3	no
g	snake	4.5	1	no
h	cat	NaN	1	yes
i	dog	7.0	2	no
j	dog	3.0	1	no
k	horse	5.5	2	yes

Original DataFrame:

	animal	age	visits	priority
a	cat	2.5	1	yes
b	cat	3.0	3	yes
c	snake	0.5	2	no
d	dog	NaN	3	yes
e	dog	5.0	2	no
f	cat	1.5	3	no
g	snake	4.5	1	no
h	cat	NaN	1	yes
i	dog	7.0	2	no
j	dog	3.0	1	no

**16.** Count the number of each type of animal in `df` . (1 point)

In [ ]:

**17.** Sort `df` first by the values in the 'age' in *descending* order, then by the value in the 'visit' column in *ascending* order. (1 point)

In [39]: `df.sort_values(by=['age', 'visits'], ascending=[False, True])  
print(df)`

	animal	age	visits	priority
a	cat	2.5	1	yes
b	cat	3.0	3	yes
c	snake	0.5	2	no
d	dog	NaN	3	yes
e	dog	5.0	2	no
f	cat	1.5	3	no
g	snake	4.5	1	no
h	cat	NaN	1	yes
i	dog	7.0	2	no
j	dog	3.0	1	no

**18.** The 'priority' column contains the values 'yes' and 'no'. Replace this column with a column of boolean values: 'yes' should be `True` and 'no' should be `False` . (1 point)

In [40]: `print(df['priority'].map({'yes': True, 'no': False}))`

```
a    True
b    True
c   False
d    True
e   False
f   False
g   False
h    True
i   False
j   False
Name: priority, dtype: bool
```

**19.** In the 'animal' column, change the 'snake' entries to 'python'. (1 point)

```
In [41]: df['animal'].replace('snake', 'python')
print(df)
```

	animal	age	visits	priority
a	cat	2.5	1	yes
b	cat	3.0	3	yes
c	snake	0.5	2	no
d	dog	NaN	3	yes
e	dog	5.0	2	no
f	cat	1.5	3	no
g	snake	4.5	1	no
h	cat	NaN	1	yes
i	dog	7.0	2	no
j	dog	3.0	1	no

20. Produce a sum of each 'priority' for each animal type . (1 point)

```
In [42]: print(df['priority'].sum())
```

yesyesnoyesnonononoyesnono

## DataFrames: beyond the basics

**Slightly trickier: you may need to combine two or more methods to get the right answer**

Difficulty: *medium*

The previous section was a tour through some basic but essential DataFrame operations. Below are some ways that you might need to cut your data, but for which there is no single "out of the box" method.

21. You have a DataFrame `df` with a column 'A' of integers. For example:

```
df = pd.DataFrame({'A': [1, 2, 2, 3, 4, 5, 5, 5, 6, 7, 7]})
```

**How do you filter out rows which contain the same integer as the row immediately above? (2 points)**



```
In [43]: #Use:
df = pd.DataFrame({'A': [1, 2, 2, 3, 4, 5, 5, 5, 6, 7, 7]})

#Code goes below:
```

**22.** Given a DataFrame of numeric values, say

```
df = pd.DataFrame(np.random.random(size=(5, 3))) # a 5x3 frame
of float values
```

**How do you subtract the row mean from each element in the row? (2 points)**

```
In [44]: #Use:
df = pd.DataFrame(np.random.random(size=(5, 3)))

#Code goes below:
```

**23.** Suppose you have DataFrame with 10 columns of real numbers, for example:

```
df = pd.DataFrame(np.random.random(size=(5, 10)), columns=list
('abcdefghij'))
```

**Which column of numbers has the smallest sum? (Find that column's label.) (2 points)**

```
In [45]: #Use:
df = pd.DataFrame(np.random.random(size=(5, 10)), columns=list('abcdefghij'))

#Code goes below:
```

**24.** How do you count how many unique rows in DataFrame `df` (i.e. ignore all rows that are duplicates)? (2 points)

In [ ]:

**25.** Using the DataFrame `df` from # 24...

**Create a new DataFrame `df2` of just column 'a' where all values are rounded to the second decimal and output `df2` . (2 points)**

In [ ]:

**End**

In [ ]: