

Package ‘Cer2016’

May 13, 2016

Type Package

Title Phylogeny Summary Statistics Demonstrated

Version 0.1.0

Author Richel Bilderbeek <richel@richelbilderbeek.nl>

Maintainer Richel Bilderbeek <richel@richelbilderbeek.nl>

Description This package contains multiple phylogeny summary statistics: SummaryStatisticA, SummaryStatisticB, SummaryStatisticC and SummaryStatisticD. These statistics are demonstrated on phylogenies created by the protracted and the (non-protracted) birth-death model.

License file LICENSE

LazyData TRUE

Requires adephylo, ape, nLTT, PBD, phangorn, phytools, rBEAST, ribir, testit, tools, TreeSim

Suggests ape, ggplot2, gridExtra, knitr, lintr, rmarkdown, testthat

RoxygenNote 5.0.1

URL <https://github.com/richelbilderbeek/Cer2016>

BugReports <https://github.com/richelbilderbeek/Cer2016/issues>

VignetteBuilder knitr

R topics documented:

add_alignments	3
add_outgroup_to_phylogeny	3
add_pbd_output	4
add_posteriors	4
add_species_trees_with_outgroup	5
branch_sorter	5
check_progress	6
collect_file_gammas	6
collect_gamma_statistics	7

collect_parameters	7
collect_posterior_filenames	8
collect_posterior_gammas	9
collect_posterior_nltt_values	9
collect_species_tree_gammas	10
collect_species_tree_nltts	10
convert_alignment_to_beast_input_file	11
convert_alignment_to_beast_posterior	11
convert_alignment_to_fasta	12
convert_phylogeny_to_alignment	13
extract_erg	13
extract_eri	14
extract_scr	15
extract_sirg	15
extract_siri	16
find_beast_bin_path	17
find_beast_jar_path	17
find_beast_posterior_test_filename	17
find_path	18
get_phylogeny_crown_age	18
is_alignment	19
is_beast_posterior	19
is_pbd_sim_output	20
is_phylogeny	20
is_valid_file	21
is_whole_number	21
load_parameters_from_file	22
normalized_rooted_branch_score	22
plot_alignments	23
plot_extant_incipient_tree	23
plot_posterior_nltts	24
plot_posterior_samples	24
plot_posterior_sample_nltts	25
plot_species_tree_with_outgroup	25
plot_species_tree_with_outgroup_nltt	26
read_file	26
sample_species_trees_from_pbd_sim_output	27
save_parameters_to_file	28
show_parameter_files	29

add_alignments	<i>Add an alignment to a file</i>
----------------	-----------------------------------

Description

Add an alignment to a file

Usage

```
add_alignments(filename)
```

Arguments

filename	Parameter filename
----------	--------------------

Value

Nothing, modifies the parameter file

Author(s)

Richel Bilderbeek

add_outgroup_to_phylogeny	<i>Adds an outgroup to a phylogeny</i>
---------------------------	--

Description

Adds an outgroup to a phylogeny

Usage

```
add_outgroup_to_phylogeny(phylogeny, stem_length, outgroup_name = "Outgroup")
```

Arguments

phylogeny	a phylogeny
stem_length	How long will the length of the outgroup be before the crown?
outgroup_name	How is the outgroup named?

Value

A phylogeny, of type phylo

Author(s)

Richel Bilderbeek

add_pbd_output	<i>Adds a pbd_sim result to a file</i>
----------------	--

Description

Adds a pbd_sim result to a file

Usage

```
add_pbd_output(filename)
```

Arguments

filename	Parameter filename
----------	--------------------

Value

Nothing, modifies the parameter file

Author(s)

Richel Bilderbeek

add_posteriors	<i>Add BEAST2 posteriors to a file</i>
----------------	--

Description

Add BEAST2 posteriors to a file

Usage

```
add_posteriors(filename, skip_if_output_present = FALSE)
```

Arguments

filename	Parameter filename
skip_if_output_present	skip if output files are present, else remove these and start a new BEAST2 run

Value

Nothing, modifies the parameter file

Author(s)

Richel Bilderbeek

`add_species_trees_with_outgroup`*Add a species tree with outgroup to a file*

Description

Add a species tree with outgroup to a file

Usage

```
add_species_trees_with_outgroup(filename)
```

Arguments

filename	Parameter filename
----------	--------------------

Value

Nothing, modifies the parameter file

Author(s)

Richel Bilderbeek

`branch_sorter`*sorts branches for the NRBS analysis*

Description

sorts branches for the NRBS analysis

Usage

```
branch_sorter(filename)
```

Arguments

tree1,	tree2, the trees that are to be sorted.
--------	---

Value

a sorted tree1 and tree2

Author(s)

Femke Thon

check_progress	<i>Function that shows how much parameter files are present, and how far the pipeline has gotten</i>
----------------	--

Description

Function that shows how much parameter files are present, and how far the pipeline has gotten

Usage

```
check_progress(folder = ".")
```

Arguments

folder	The folder containing the parameter files
--------	---

Value

A data table showing the progress

Author(s)

Richel Bilderbeek

collect_file_gammas	<i>Collects the gamm statistics of all phylogenies belonging to a parameter file in the melted/uncast/long form</i>
---------------------	---

Description

Collects the gamm statistics of all phylogenies belonging to a parameter file in the melted/uncast/long form

Usage

```
collect_file_gammas(filename, verbose = FALSE)
```

Arguments

filename	name of the parameter file
----------	----------------------------

Value

A dataframe of gamma statistics of each phylogeny in time

`collect_gamma_statistics`*Collects the gamma statistics of all phylogenies in the melted/uncast/long form*

Description

Collects the gamma statistics of all phylogenies in the melted/uncast/long form

Usage

```
collect_gamma_statistics(phylogenies)
```

Arguments

`phylogenies` the phylogenies, supplied as either a list or a multiPhylo object, where the phylogenies are of type 'phylo'

Value

A dataframe of gamma statistics of each phylogeny in time

`collect_parameters`*Creates tidy data of all parameter files*

Description

Creates tidy data of all parameter files

Usage

```
collect_parameters(filenamees, verbose = FALSE)
```

Arguments

`filenamees` names of the parameter files
`verbose` give verbose output, should be TRUE or FALSE

Author(s)

Richel Bilderbeek

Examples

```

filenames <- c(
  find_path("article_0_0_0_0.RDa"),
  find_path("article_0_1_4_0_2.RDa"),
  find_path("toy_example_1.RDa")
)
df <- collect_parameters(filenames)
testit::assert(nrow(df) == 3)

```

collect_posterior_filenames

Collect posterior filenames

Description

Collect posterior filenames

Usage

```
collect_posterior_filenames(parameter_filename)
```

Arguments

parameter_filename
Name of a parameter file

Value

generates species tree files from the posterior

Author(s)

Richel Bilderbeek and Jolien Gay

Examples

```

parameter_filename <- find_path("toy_example_1.RDa")
posterior_filenames <- collect_posterior_filenames(parameter_filename)
trees_filename <- find_path("toy_example_1_1_1_1.trees")
testit::assert(length(posterior_filenames) == 1)
testit::assert(posterior_filenames[1] == trees_filename)

```

`collect_posterior_gammas`*Collect the gamma statistics of the BEAST2 posteriors*

Description

Collect the gamma statistics of the BEAST2 posteriors

Usage

```
collect_posterior_gammas(filename)
```

Arguments

filename name of the file containing the parameters and results

Value

a data frame

Author(s)

Richel Bilderbeek

`collect_posterior_nltt_values`*Collect the nLTT values of the BEAST2 posteriors*

Description

Collect the nLTT values of the BEAST2 posteriors

Usage

```
collect_posterior_nltt_values(filename, dt = 0.001)
```

Arguments

filename name of the file containing the parameters and results
dt the resolution of the nLTT plot, must be in range <0,1>, default is 0.001

Value

a data frame

Author(s)

Richel Bilderbeek

`collect_species_tree_gammas`*Collect the gamma statistics of the species trees with outgroup*

Description

Collect the gamma statistics of the species trees with outgroup

Usage

```
collect_species_tree_gammas(filename)
```

Arguments

filename name of the file containing the parameters and results

Value

a data frame

Author(s)

Richel Bilderbeek

`collect_species_tree_nltts`*Collect the nLTT values of the species trees with outgroup*

Description

Collect the nLTT values of the species trees with outgroup

Usage

```
collect_species_tree_nltts(filename, dt = 0.001)
```

Arguments

filename name of the file containing the parameters and results
dt the resolution of the nLTT plot, must be in range <0,1>, default is 0.001

Value

a data frame

Author(s)

Richel Bilderbeek

 convert_alignment_to_beast_input_file

Convert an alignment and parameters to a BEAST XML input file

Description

Convert an alignment and parameters to a BEAST XML input file

Usage

```
convert_alignment_to_beast_input_file(alignment_dnabin, mcmc_chainlength,
                                     rng_seed = 42, beast_filename, temp_fasta_filename)
```

Arguments

alignment_dnabin	the DNA alignment of type DNABin
mcmc_chainlength	the BEAST2 MCMC chain length
rng_seed	random number generator seed
beast_filename	the filename of the XML BEAST2 input file created
temp_fasta_filename	the name of a temporary file created

Value

Nothing, creates a file called 'beast_filename'

Author(s)

Richel Bilderbeek

 convert_alignment_to_beast_posterior

Convert an alignment to a BEAST2 XML input file

Description

Convert an alignment to a BEAST2 XML input file

Usage

```
convert_alignment_to_beast_posterior(alignment_dnabin, mcmc_chainlength,
                                     base_filename, rng_seed = 42, beast_bin_path = "",
                                     beast_jar_path = find_beast_jar_path(), skip_if_output_present = FALSE)
```

Arguments

alignment_dnabin	The alignment
mcmc_chainlength	The length of the MCMC chain BEAST2 will generate
base_filename	The base of the filename (the part without the extension)
rng_seed	The random number generator seed used by BEAST2
beast_bin_path	Where the binary 'beast' can be found
beast_jar_path	Where the jar 'beast.jar' can be found
skip_if_output_present	skip if output files are present, else remove these and start a new BEAST2 run

Value

A BEAST2 posterior

Author(s)

Richel Bilderbeek

convert_alignment_to_fasta

Convert an alignment (of type DNABin) to a FASTA file

Description

Convert an alignment (of type DNABin) to a FASTA file

Usage

```
convert_alignment_to_fasta(alignment_dnabin, filename)
```

Arguments

alignment_dnabin	DNA alignment of type DNABin
filename	FASTA filename the alignment will be saved to

Value

Nothing, it will create a FASTA file

Author(s)

Richel Bilderbeek

`convert_phylogeny_to_alignment`*Converts a phylogeny to a random DNA alignment*

Description

Converts a phylogeny to a random DNA alignment

Usage

```
convert_phylogeny_to_alignment(phylogeny, sequence_length, mutation_rate = 1)
```

Arguments

phylogeny	a phylogeny
sequence_length	the number of nucleotides to alignment will have per taxon
mutation_rate	the rate per nucleotide to change, per million years

Value

an alignment

Author(s)

Richel Bilderbeek

`extract_erg`*Extract the ERG ('Extinction Rate of a Good species') parameter value from a file*

Description

Extract the ERG ('Extinction Rate of a Good species') parameter value from a file

Usage

```
extract_erg(file)
```

Arguments

file	A loaded parameter file
------	-------------------------

Value

the value of the ERG parameter

Author(s)

Richel Bilderbeek

Examples

```
file <- read_file(find_path("toy_example_1.RDa"))
erg <- extract_erg(file)
testit::assert(erg >= 0.0)
```

extract_eri	<i>Extract the ERI ('Extinction Rate of an Incipient species') parameter value from a file</i>
-------------	--

Description

Extract the ERI ('Extinction Rate of an Incipient species') parameter value from a file

Usage

```
extract_eri(file)
```

Arguments

file	A loaded parameter file
------	-------------------------

Value

the value of the ERI parameter

Author(s)

Richel Bilderbeek

Examples

```
file <- read_file(find_path("toy_example_1.RDa"))
eri <- extract_eri(file)
testit::assert(eri >= 0.0)
```

extract_scr	<i>Extract the SCR ('Speciation Completion Rate') parameter value from a file</i>
-------------	---

Description

Extract the SCR ('Speciation Completion Rate') parameter value from a file

Usage

```
extract_scr(file)
```

Arguments

file	A loaded parameter file
------	-------------------------

Value

the value of the SCR parameter

Author(s)

Richel Bilderbeek

Examples

```
file <- read_file(find_path("toy_example_1.RDa"))
scr <- extract_scr(file)
testit::assert(scr >= 0.0)
```

extract_sirg	<i>Extract the SIRG ('Speciation Initial Rate of a Good species') parameter value from a file</i>
--------------	---

Description

Extract the SIRG ('Speciation Initial Rate of a Good species') parameter value from a file

Usage

```
extract_sirg(file)
```

Arguments

file	A loaded parameter file
------	-------------------------

Value

the value of the SIRG parameter

Author(s)

Richel Bilderbeek

Examples

```
file <- read_file(find_path("toy_example_1.RDa"))
sirg <- extract_sirg(file)
testit::assert(sirg >= 0.0)
```

extract_siri	<i>Extract the SIRI ('Speciation Initial Rate of an Incipient species') parameter value from a file</i>
--------------	---

Description

Extract the SIRI ('Speciation Initial Rate of an Incipient species') parameter value from a file

Usage

```
extract_siri(file)
```

Arguments

file	A loaded parameter file
------	-------------------------

Value

the value of the SIRI parameter

Author(s)

Richel Bilderbeek

Examples

```
file <- read_file(find_path("toy_example_1.RDa"))
siri <- extract_siri(file)
testit::assert(siri >= 0.0)
```

find_beast_bin_path	<i>Find the path of the BEAST2 binary file</i>
---------------------	--

Description

Find the path of the BEAST2 binary file

Usage

```
find_beast_bin_path()
```

Value

the path of the BEAST2 binary file

find_beast_jar_path	<i>Find the path of the BEAST2 jar file</i>
---------------------	---

Description

Find the path of the BEAST2 jar file

Usage

```
find_beast_jar_path()
```

Value

the path of the BEAST2 jar file

find_beast_posterior_test_filename	<i>Find the path of known-to-be-valid BEAST2 posterior file</i>
------------------------------------	---

Description

Find the path of known-to-be-valid BEAST2 posterior file

Usage

```
find_beast_posterior_test_filename()
```

Value

the path of a known-to-be-valid BEAST2 posterior file

find_path	<i>Finds the full path of a file</i>
-----------	--------------------------------------

Description

Finds the full path of a file

Usage

```
find_path(filename)
```

Arguments

filename	the name of a file
----------	--------------------

Value

the full path of the filename if an existing file could be found, stops otherwise

Author(s)

Richel Bilderbeek

get_phylogeny_crown_age	<i>Obtain the crown age of a phylony</i>
-------------------------	--

Description

Obtain the crown age of a phylony

Usage

```
get_phylogeny_crown_age(phylogeny)
```

Arguments

phylogeny	The phylogeny to obtain the crown age of
-----------	--

Value

the age of the phylogeny

Author(s)

Richel Bilderbeek

is_alignment	<i>Determines if the input is an alignment of type DNABin</i>
--------------	---

Description

Determines if the input is an alignment of type DNABin

Usage

```
is_alignment(input)
```

Arguments

input	The input to be testes
-------	------------------------

Value

TRUE or FALSE

Author(s)

Richel Bilderbeek

is_beast_posterior	<i>Determines if the input is a BEAST2 posterior</i>
--------------------	--

Description

Determines if the input is a BEAST2 posterior

Usage

```
is_beast_posterior(x)
```

Arguments

x	the input
---	-----------

Value

TRUE or FALSE

Author(s)

Richel Bilderbeek

is_pbd_sim_output	<i>Does not use pbd_sim()\$stree, but generates these like PBD does</i>
-------------------	---

Description

Does not use pbd_sim()\$stree, but generates these like PBD does

Usage

```
is_pbd_sim_output(pbd_sim_output, verbose = FALSE)
```

Arguments

pbd_sim_output	the argument tested to output of PBD::pbd_sim
verbose	will the function show why the input is determined not to be output of PBD::pbd_sim

Value

TRUE or FALSE

Author(s)

Richel Bilderbeek

is_phylogeny	<i>Checks if the input is a phylogeny</i>
--------------	---

Description

Checks if the input is a phylogeny

Usage

```
is_phylogeny(x)
```

Arguments

x	input to be checked
---	---------------------

Value

TRUE or FALSE

Author(s)

Richel Bilderbeek

is_valid_file	<i>Checks if a file is a valid parameter file</i>
---------------	---

Description

Checks if a file is a valid parameter file

Usage

```
is_valid_file(filename, verbose = FALSE)
```

Arguments

filename	the name of the file to be checked
verbose	give verbose output, should be TRUE or FALSE

Value

TRUE or FALSE

Author(s)

Richel Bilderbeek

Examples

```
testit::assert(is_valid_file(find_path("toy_example_1.RDa")))
testit::assert(!is_valid_file(find_path("toy_example_1_1_1_1.trees")))
```

is_whole_number	<i>Checks if x is a single, whole-number variable</i>
-----------------	---

Description

Checks if x is a single, whole-number variable

Usage

```
is_whole_number(x, tolerance = .Machine$double.eps^0.5)
```

Arguments

x	the number to check
tolerance	the maximum error a number may deviate from a whole number, before it is labeled as a floating point value

Value

TRUE or FALSE

Author(s)

Richel Bilderbeek

load_parameters_from_file

Load parameters from file

Description

Load parameters from file

Usage

```
load_parameters_from_file(filename)
```

Arguments

filename name of the parameter file

Value

a data frame with all parameters

Author(s)

Richel Bilderbeek

normalized_rooted_branch_score

calculates the normalized rooted branch score

Description

calculates the normalized rooted branch score

Usage

```
normalized_rooted_branch_score(filenamees)
```

Arguments

filenamees the filenames

Value

the normalized rooted branch score

Author(s)

Femke Thon

plot_alignments	<i>Plot alignments</i>
-----------------	------------------------

Description

Plot alignments

Usage

plot_alignments(filename)

Arguments

filename name of the parameter file

Author(s)

Richel Bilderbeek

plot_extant_incipient_tree	<i>Plot the extant incipient species tree</i>
----------------------------	---

Description

Plot the extant incipient species tree
Plot the extant incipient species tree

Usage

plot_extant_incipient_tree(filename)

plot_extant_incipient_tree(filename)

Arguments

filename name of the parameter file

Value

Nothing. It does produce a plot

Author(s)

Richel Bilderbeek

plot_posterior_nltts *Plot multiple BEAST2 posteriors*

Description

Plot multiple BEAST2 posteriors

Usage

```
plot_posterior_nltts(filename, dt = 0.001)
```

Arguments

filename	name of the file containing the parameters and results
dt	the resolution of the nLTT plot, must be in range <0,1>, default is 0.001

Value

Nothing, produces a plot

Author(s)

Richel Bilderbeek

plot_posterior_samples
 Plot a random posterior phylogeny

Description

Plot a random posterior phylogeny

Usage

```
plot_posterior_samples(filename)
```

Arguments

filename	a filename
----------	------------

Value

Nothing, but it does generate some plots

Author(s)

Richel Bilderbeek

plot_posterior_sample_nltts
Plot the nLTTs of the posterior

Description

Plot the nLTTs of the posterior

Usage

```
plot_posterior_sample_nltts(filename, dt = 0.001)
```

Arguments

filename	a filename
dt	the resolution of the nLTT plot, must be in range <0,1>, default is 0.001

Value

Nothing, but it does generate some plots

Author(s)

Richel Bilderbeek

plot_species_tree_with_outgroup
Plot

Description

Plot

Usage

```
plot_species_tree_with_outgroup(filename)
```

Arguments

filename a file name

Value

Nothing, but it does generate plots

Author(s)

Richel Bilderbeek

plot_species_tree_with_outgroup_nltt

Plot species_tree_with_outgroup_nltt

Description

Plot species_tree_with_outgroup_nltt

Usage

```
plot_species_tree_with_outgroup_nltt(filename, dt = 0.001)
```

Arguments

filename parameter filename

dt the resolution of the nLTT plot, must be in range <0,1>, default is 0.001

Author(s)

Richel Bilderbeek

read_file

Read a parameter (.RDa) file

Description

Read a parameter (.RDa) file

Usage

```
read_file(filename)
```

Arguments

filename name of the parameter (.RDa) file

Value

the file as R data

Author(s)

Richel Bilderbeek

Examples

```
file <- read_file(find_path("toy_example_1.RDa"))  
print(names(file))
```

```
sample_species_trees_from_pbd_sim_output
```

*Samples species trees from PBD::pbd_sim its output It does not use
pbd_sim()\$stree, but generates these like PBD does.*

Description

Samples species trees from PBD::pbd_sim its output It does not use pbd_sim()\$stree, but generates these like PBD does.

Usage

```
sample_species_trees_from_pbd_sim_output(n, pbd_sim_output)
```

Arguments

n The number of species trees to sample
pbd_sim_output The output generated by PBD::pbd_sim

Value

A list of length n, containing the n sampled species trees

Author(s)

Richel Bilderbeek, inspired by Rampal Etienne's PBD::pbd_sim function

`save_parameters_to_file`*Creates a valid parameter file*

Description

Creates a valid parameter file

Usage

```
save_parameters_to_file(rng_seed, sirg, siri, scr, erg, eri, age,  
    n_species_trees_samples, mutation_rate, n_alignments, sequence_length,  
    mcmc_chainlength, n_beast_runs, filename)
```

Arguments

<code>rng_seed</code>	the random number generator seed
<code>sirg</code>	the species initiation rate of the good species
<code>siri</code>	the speciation-initiation rate of the incipient species
<code>scr</code>	the rate at which incipient species become good
<code>erg</code>	the rate at which good species get extinct
<code>eri</code>	the rate at which incipient species get extinct
<code>age</code>	crown age of the phylogeny
<code>n_species_trees_samples</code>	the number of species trees that will be sampled from an incipient species tree
<code>mutation_rate</code>	the probability per nucleotide to mutate at a DNA replication
<code>n_alignments</code>	the number of alignments simulated per species tree
<code>sequence_length</code>	the simulated DNA sequence length in nucleotides
<code>mcmc_chainlength</code>	the length of the MCMC chain that BEAST2 will run
<code>n_beast_runs</code>	the number of BEAST2 runs per DNA alignments
<code>filename</code>	the name of the parameter file that will be created by this function

Value

Nothing, it will create a file with filename ‘filename’

Author(s)

Richel Bilderbeek

show_parameter_files *Creates a nice knitr::table to show one or more parameter files*

Description

Creates a nice knitr::table to show one or more parameter files

Usage

```
show_parameter_files(filenamees, verbose = FALSE)
```

Arguments

filenamees	names of the parameter files
verbose	give verbose output, should be TRUE or FALSE

Author(s)

Richel Bilderbeek

Index

add_alignments, [3](#)
add_outgroup_to_phylogeny, [3](#)
add_pbd_output, [4](#)
add_posteriors, [4](#)
add_species_trees_with_outgroup, [5](#)

branch_sorter, [5](#)

check_progress, [6](#)
collect_file_gammas, [6](#)
collect_gamma_statistics, [7](#)
collect_parameters, [7](#)
collect_posterior_filenames, [8](#)
collect_posterior_gammas, [9](#)
collect_posterior_nltt_values, [9](#)
collect_species_tree_gammas, [10](#)
collect_species_tree_nltts, [10](#)
convert_alignment_to_beast_input_file, [11](#)
convert_alignment_to_beast_posterior, [11](#)
convert_alignment_to_fasta, [12](#)
convert_phylogeny_to_alignment, [13](#)

extract_erg, [13](#)
extract_eri, [14](#)
extract_scr, [15](#)
extract_sirg, [15](#)
extract_siri, [16](#)

find_beast_bin_path, [17](#)
find_beast_jar_path, [17](#)
find_beast_posterior_test_filename, [17](#)
find_path, [18](#)

get_phylogeny_crown_age, [18](#)

is_alignment, [19](#)
is_beast_posterior, [19](#)
is_pbd_sim_output, [20](#)
is_phylogeny, [20](#)

is_valid_file, [21](#)
is_whole_number, [21](#)

load_parameters_from_file, [22](#)

normalized_rooted_branch_score, [22](#)

plot_alignments, [23](#)
plot_extant_incipient_tree, [23](#)
plot_posterior_nltts, [24](#)
plot_posterior_sample_nltts, [25](#)
plot_posterior_samples, [24](#)
plot_species_tree_with_outgroup, [25](#)
plot_species_tree_with_outgroup_nltt, [26](#)

read_file, [26](#)

sample_species_trees_from_pbd_sim_output, [27](#)
save_parameters_to_file, [28](#)
show_parameter_files, [29](#)