Cheatography

C Cheat Sheet

by pmg (pmg) via cheatography.com/596/cs/255/

read file char-by-char

```
#include <stdio.h>

FILE *h;
int ch;
h = fopen("filename", "rb");
/* error checking missing */
while ((ch = fgetc(h)) != EOF) {
    /* deal with ch */
}
/* if needed test why last read failed */
if (feof(h) || ferror(h)) /* whatever */;
fclose(h);
```

You can replace fgetc(h) with getchar() to read from standard input.

read file line-by-line

```
#include <stdio.h>
FILE *h;
char line[100];
h = fopen("filename", "rb");
/* error checking missing */
while (fgets(line, sizeof line, h)) {
    /* deal with line */
}
/* if needed test why last read failed */
if (feof(h) || ferror(h)) /* whatever */;
fclose(h);
```

Flexible Array Member

How to declare a FAM?

> By using empty brackets as the last member of a struct.

How to define the size for an object containg a FAM?

```
ptr = malloc(sizeof *ptr + sizeof (FAMTYPE[wantedsize]));
```

Do not use FAMs! They were known as*struct hack* before C99 and, now as then, feel like a dirty hack.

<stdio.h> functions with a FILE pointer at the end

```
char *fgets(char *, int, FILE *);
int fputc(int, FILE *);
int fputs(char *, FILE *);
size_t fread(void *, size_t, size_t, FILE *);
FILE *freopen(char *, char *, FILE *);
size_t fwrite(void *, size_t, size_t, FILE *);
int ungetc(int, FILE *);
```

dynamic memory

Remember to **#include <stdlib.h>**

Allocate

malloc	**ptr = malloc(n * sizeof *ptr);**
calloc	**ptr = calloc(n, sizeof *ptr);**

Change size

realloc	**newsize = n * sizeof *ptr; tmp = realloc(ptr, newsize); if (tmp) ptr = tmp; else /* ptr is still valid */;**

Release

free	**free(ptr);**

remove trailing newline

How do I remove the final newline in a string?

```
len = strlen(data);
if (len && data[len - 1] == '\\n') data[--len] = 0;
```

If len is known in advance, do not call strlen(). You can pass the updated len to the caller.

Casting

Casts in C are almost always wrong. When are they right?

<ctype.h>	isupper((**unsigned char**)ch)
%p printf specifiers	printf("**%p**", **(void*)**ptr)

Specifically a cast to the return value of **malloc()** is a definite sign the code author either didn't know what he was doing or didn't choose a good language for the implementation of whatever he's doing.

(BSD) sockets

Headers needed

```
#include <arpa/inet.h>
#include <netdb.h>
#include <string.h>
#include <sys/socket.h>
#include <unistd.h>
```

initialize with

getaddrinfo()

loop to find and connect a socket

socket()

connect()

if needed: close()

after loop: freeaddrinfo()

getpeername(), getsockname()

send() or recv() or sendto() or recvfrom()

close()

Predefined C macros

__FILE__

> **"filename.c"** or something like that

__LINE__

> **42** or another integer

__STDC__

> **1**

__STDC_VERSION__

> undefined for C89; **199901L** for C99; **201112L** for C11

__DATE__

> **"Feb 17 2012"** for example

__TIME__

> **"15:16:17"** for example

__func__

> **"main"** for example

__STDC_HOSTED__

> **0** or **1**

Reserved identifiers

Reserved for all uses anywhere

_[A-Z]*; __*	E[A-Z]*; E[0-9]*
is[a-z]*; to[a-z]*	SIG[A-Z]*; SIG_[A-Z]*
LC_[A-Z]*	*_t

By **pmg** (pmg)
cheatography.com/pmg/

Published 17th February, 2012.
Last updated 5th June, 2014.

Reserved identifiers (cont)	
str[a-z]*; mem[a-z]*; wcs[a-z]*	
all math functions possibly followed by **f** or **l**	
When **#include <limits.h>** is present	
*_MAX	
When **#include <signal.h>** is present	
SA_*	sa_*
POSIX adds a few other identifiers	
<dirent.h>	d_*
<fcntl.h>	l_*; F_*; O_*; S_*
<grp.h>	gr_*
<pwd.h>	pw_*
<sys/stat.h>	st_*; S_*
<sys/times.h>	tms_*
<termios.h>	C_*; V_*; I_*; O_*; TC*; B[0-9]*