Contents

Chapter 1

Introduction

Chapter 2

Design Evaluation Experiment

2.1   Introduction

After investigating the technical approach and the benefit to including the passive haptics layer, we seek to investigate the use of the Rapidly Reconfigurable Research Cockpit in a more realistic design evaluation study. The advantages of using the R3C system would not be useful if it masked defects in a design study.

2.2 Methods

In order to perform a design evaluation study, it was first needed to have a task that the subjects would be doing using the designs.

2.2.1 Simulator Setup

The simulator workstation as configured for each group is shown and annotated in Figure **??**. It was our goal to have as much as possible to be the same between the two configurations. The joystick and instrument were positioned in the same location for each group. Neither group had out the window visuals, relying only on the attitude indicator on the instrument. For the Virtual Reality (VR) group, the visuals showed a plain interior of a cockpit, but the out the window view was black. Both groups had an aural indication (a click noise of a button being pressed) when a button was activated on the instrument, using the speakers mounted behind the instrument panel.

this is not done yet

The main difference between the two groups, beyond the VR group wearing a virtual reality headset, was the way the instrument was interacted with. The VR group used the hand tracker activated system previously described in Chapter **??**. For this experiment, the buttons were

terrible sentence

Figure 2.1: Simulator Workstation

configured to highlight a blue color when the hand tracker registered a finger within the zone . After the 150 msec delay when the button was activated, the highlight would disappear and the button in the virtual world would move inwards as if it were being pushed in (of course, the physical button could not and did not move). It is also at this time that the press sound would play, as well as any response on the instrument associated with pressing that button. When the finger left the zone after a successful press, a seperate release sound would play and the button would move back to its starting position.

> Find the size of the zone

The Touchscreen (TS) group used a 10.1 inch capacitive touch screen with resolution of 1024x768. The two instruments were drawn in a web browser, using standard HTML elements for the buttons. Javascript press and release events were used to simulate the same behavior as described for the VR group, except for the highlighting before a button press. The

visuals of the tracker were rendered on top of the browser window with the same OpenGL rendering code used for the VR group.

2.2.2   Task Design

With this simulator setup base and the goals of the study, a number of requirements were created to design the task that the subjects would perform.

- Flight task using a standard joystick

- Second task that requires use of multiple buttons on the instrument

- Able to develop simulator for both touchscreen and R3C setup

  could explain what this limits

- Able to design two different layouts with one design having distinct flaws

- Simple design yet complex enough task to have sufficient workload

- Operationally relevant, or analogous to tasks required in a cockpit

Ultimately, we designed a task that required number and letter inputs using the buttons, while simultaneously flying a pitch disturbance profile.

Figure 2.2: Attitude Indicator Display

Tracking Task

The tracking task display was a standard attitude indicator display,

shown in Figure 2.2. Each tick corresponds to 1 degree in the dynamics

simulation, with the major ticks at intervals of 5 degrees. The attitude

indicator was X.X inches square on the instrument. ——————— Thats not a real dimension

Figure 2.3: Tracking Task Dynamics Block Diagram

84   Subjects controlled the one-dimensional (pitch only) task using a joy-

85 stick with their left hand. The joystick is pictured in Figure 2.1. The flight

86 dynamics model of the simulator was a stability derivative based model for

87 a Boeing 747 in a low altitude landing configuration. The dynamics model

88 was updated and recorded at a rate of 125Hz.

Include all the info on the FDM

89   The output of the joystick, r_{js}, varies from -1.0 to 1.0, and the gain of

90 $10°$ was chosen to ensure the pilot had enough control authority to complete

91 the task.

The transfer function of the aircraft dynamics is given as:

$$\frac{\theta}{\theta_{el}} = \frac{-0.572(s + 0.553)(s + 0.0396)}{(s^2 + 2\zeta_1\omega_1 + \omega_1{}^2)(s^2 + 2\zeta_2\omega_2 + \omega_2{}^2)} \tag{2.1}$$

$$\omega_1 = 0.0578 \qquad \zeta_1 = 0.0160$$

$$\omega_2 = 1.12 \qquad \zeta_2 = 0.798$$

92   The disturbance model is based off the model developed in SweetRef.

93 It is designed to provide a broad spectrum of frequencies that the human

94 controller needs to respond to.

$$\theta_D = K \sum_{i=1}^{12} \left[a_i \left(\frac{2\pi k_i}{240} \right) \sin \left(\frac{2\pi k_i}{240} t + \phi_i \right) \right] \qquad (2.2)$$

The k_i terms are given as,

$$k_1 = 7, \qquad k_2 = 11, \qquad k_3 = 16$$

$$k_4 = 25, \qquad k_5 = 38, \qquad k_6 = 61$$

$$k_7 = 103, \qquad k_8 = 131, \qquad k_9 = 151$$

$$k_{10} = 181, \qquad k_{11} = 313, \qquad k_{12} = 523$$

95 The amplitude terms is $a_i = 0.5$ for $i <= 6$ and $a_i = 0.005$ otherwise. The

96 phase terms, ϕ_i, were randomly selected on the $(-\pi, \pi)$ interval ensuring

97 a uniform distribution. This random selection was precalculated for each

98 trial, however the order was repeated for each subject so there was no

99 between subjects variance in the disturbance signal. Furthermore, each

100 subject received the same sequence of disturbance signals for each design,

101 eliminating within subject variance as well. The disturbance amplitude,

102 K, was chosen such that the root-mean square (RMS) of the signal was

103 3.5 degrees.

Prompting Task

105   The prompting task was designed to be both a realistic task as well as

106 demanding to create a high workload. The task would require the subjects

107 to read and memorize a short string of characters and enter it using buttons

108 on the instrument. To reduce the number of buttons needed, the characters

109 were limited to 1 through 6 and A through F.

110   The sequencing of the prompts seperated into 10 second "windows".

111 The prompt would appear between 2 and 3 seconds of the start of the

112 window. From the time of appearance, a seven (7) second timer will start

113 until timeout. When the subject presses the first button of the prompt,

114 the prompt itself was cleared and asterisk symbols (*) were shown after

115 each button entry by the subject. After the subject has entered 4 buttons

116 or the timeout occurs, whichever comes first, the prompt or entry so far

117 would clear. This process is then repeated every 10 seconds.

118   The prompts themselves were composed of three numbers followed by

119 a letter or three letters followed by a number. This structure was decided

120 upon to provide a consistent pattern. The prompts were randomly cho-

121 sen but were not allowed to have repeat numbers or letters, and for the

122 prompts with three letters, common words or acronyms were filtered out

123 (e.g. "BAD", "FDA"). The selection of letters or numbers as the first three

124 characters was randomly chosen as well.

125 2.2.3   Instrument Designs

126   The two different designs used were developed to be both realistic and

127 believable as a cockpit instrument design that would be under considera-

128 tion, yet still have one design with flaws that would be found in a design

129 evaluation. We developed a 'Keypad' design with the prompting task but-

130 ton keys on the right side and the tracking task on the left, and an 'Edgekey'

131 design with the prompt buttons split on either side of the tracking task

132 display. For both designs the tracking task display was the same size on

133 the display. The prompting task text is also placed below the tracking task

134 display, and the same font, size and color is used for both designs. These

135 were kept consistent to limit the number of possible variables between the

136 two designs.

137   The Keypad design is pictured in Figure 2.4. The buttons are 1in by

138 0.75in, with about 0.26in between buttons horizontally and 0.38in verti-

Figure 2.4: Keypad Design

Figure 2.5: Edgekey Design

cally. Each button has the label directly on the top of the button. For the VR group, the 3D printed instrument had the button labels raised to provide a tactile feedback. The font was approximately 0.36in in height, and the labels were raised 0.05in.

The Edgekey design is pictured in Figure 2.5. In this design, there is not a single button for every number and letter. Instead, the bottom button on either would switch the behavior (and labels) of the remaning six buttons from showing 1 through 6 to showing A through F. The labels were

placed offset from the button on the "screen" portion of the instrument,

allowing them to change dynamically. The buttons are slightly smaller in

this design, at 0.76in by 0.55in. The spacing between buttons vertically is

the same as the Keypad design at 0.38in. The center to center distance

between the two sides of the button is 7.3in. For the VR group, the 3D

printed instrument had raised nubs on each button covering half the width,

0.08in tall and raised 0.05in.

While some of the more subtle differences were expected to possibly

be noted by the evaluation study (e.g. having smaller buttons, different

position of the flight task), the major flaw we designed into the Edgekey

design was the switching key to change from letters to numbers and back.

This additional action fundamentally changed the demands of the task,

as the subjects now had to press this additional button to change labels

at least once per prompt. Pressing the switch key was always required

between pressing the third and fourth button, and would be required before

the first button press if the last state of the buttons did not match the

start of the new prompt. Since there was no gaurentee that the next

prompt would start with the instrument on the correct setting, there was an

additional cognitive load in determining whether a switch was neccessary

166 at the beginning of the prompting window.

2.2.4   Experiment Design

168 Subjects were divided into the two groups, TS and VR. The overall

169 sequence of the experiment started with a training session on the simulator

170 and the task, then an evaluation session for each of the two designs, finally

171 finishing with questionnaires asking about the designs. The timeline of

172 the experiment was the same for each subject, except for counterbalancing

173 the order that the designs were evaluated. The training portion started

174 with a slide deck explaining the tasks, the simulator that the subject was

175 using, and the functionality two designs they were to evaluate. Next, they

176 performed practice trials with just the tracking task and then just the

177 prompting task.

178 For the evaluation sessions with each design, they performed six trials

179 with both tasks. The first three were a minute long, and were considered

180 practice trials, and not included in the data analysis. The following three

181 were two minutes each, and were the trials used for the results. Each

182 evaluation session concluded with a two minute trial of just the tracking

183 task. This was included to investigate if the subject had improved or

184 fatigued at the tracking task.

2.2.5 Dependent Measures

186 The dependent measures were chosen to evaluate the performance of

187 each task individually as well as the workload of the subject. For the

188 tracking task, the root-mean square error (RMSE) was calculated for each

189 trial. The error in this case is simply the pitch shown to the subject, the

190 output of the flight model described above.

191 The prompting task has two dependent measures, for speed and accu-

192 racy. For speed we consider the *response time*, defined as the time between

193 the prompt is first shown to the subject and when they press the first

194 button of their response entry. The accuracy is measured by how many

195 prompts they complete correctly. Twelve prompts are shown to the subject

196 within each trial, and these measures are meaned per trial and then per

197 design for each subject.

198 For workload, a NASA Task Load Index (TLX) survey was adminis-

199 tered after they completed each design. The TLX survey asks for a rat-

200 ing of their workload between 0-100 for the following subscales: Mental

201 Demand, Physical Demand, Temporal Demand, Performance, Effort, and

Frustration. Our implementation allowed selection of the ratings within increments of 5, and included anchors of "Low" and "High" at the extrema of 0 and 100, respectively (except for Performance, which uses "Good" and "Bad"). The midpoint (50) was also visually indicated with a larger tick. The ranked pairs modification was used and completed for both times the subject took the survey. This modification asks the subject, for each of the combinations of pairs of subscales, which of the two they felt contributed more to their workload. The number of times they select each subscale is used a weight to calculate a weighted mean for the total TLX score.

Finally, the subjects were given a questionnaire asking for their feedback on each instrument design. For each design, the subjects were asked the following questions:

- Please comment on any difficulties you had performing the prompting task with this design especially in contrast to the other design.

- Please comment on anything you liked in this design.

- Please comment on anything you did not like in this design.

- Any other comments?

Additionally, the following questions were asked:

- Which instrument design did you prefer? Why?

- Did you experience any physical fatigue during the experiment? Where?█

- Any other comments?

An open form text box was used for the response field for each of these questions.

In a standard design evaluation study, the feedback received from the users in this questionnaire (and other debriefing interviews) would often be the main source for carrying out re-design. The goal of this experiment is to determine and document in which ways does this feedback differ. For example, if most subjects in one group noted issues with the size of a button, while no one in the other group found an issue with that button, this would indicate that using this VR system may not highlight the same issues regarding button sizes. The groups were purposely left ambiguous in the example, as it does not matter which group found the flaw and which group did not comment on it. Although we could postulate as to which group are "correct", it is not a useful exercise, as the only result is to document what potential differences could arise.

To analyze these results, the sentences from the open form responses were first separated into single feedback comments, and reworded to use

239 common language. If a subject repeated the same comment in the answers

240 to multiple questions, they were only counted once. Each of these simplified

241 feedback comments were assigned to a category or overall summary of

242 their feedback. This process was completed separately for each group. To

243 summarize the differences, we will look for feedback that is unique to a

244 certain group, as well as the frequency of the comments that are common.

2.2.6 Statistical Tests

246   The quantitative dependent measures are tested with a two-way ANOVA,

247 with one within subjects factor (Design) and one between subjects factor

248 (Group). The Design factor contains two levels, the two designs each sub-

249 ject tested, Edgekey and Keypad. The Group factor also contains two

250 levels, the VR group and the TS group. When the ANOVA showed sig-

251 nificance in the interaction test, post-hoc repeated measured t-tests were

252 undertaken to determine the significance of Design within each Group.

253 An independent samples t-test was used to test the signifinace of Group

254 within each Design. All effects were considered statistically significant

255 at the 0.0125 level. Statistical significance level was corrected using the

256 Bonferroni correction considering the 4 different dependent measures be-

257 ing tested ($\alpha = 0.05/4 = 0.0125$). Effects which have a signifigance level

258 between $0.05 < p < 0.0125$ are considered to be marginally significant.

2.3 Results

2.3.1 Demographics

261   Twenty-three subjects were recruited from the UC Davis engineering

262 undergraduate and graduate student population. Twelve subjects were

263 placed in the VR group, and the remaining eleven in the TS group. The

264 mean age was $21.0(\sigma = 3.14)$, with 19 male and 4 female subjects. The

265 female subjects were balanced between the two groups. Most subjects had

266 no flight experience (two were student pilots), and all of the VR group

267 subjects indicated that they had less than one hour of experience using

268 virtual reality headsets.

2.3.2 Performance Measures

Tracking Task RMSE

271   The performance of the tracking task was measured using the root-mean

272 square average (RMSE) of the pitch. The effect of Group yielded an F ratio

Figure 2.6: Factor Plot of RMSE

of $F(1,21) = 21.4, p < 0.001$ indicating a significant difference between VR

$(M = 1.28\text{deg}, \sigma = 0.38\text{deg})$ and TS $(M = 1.97\text{deg}, \sigma = 0.38\text{deg})$. In both

groups, subjects were performing the tracking task using the same joystick.

The most direct factor that could contribute to the decreased performance

in the tracking task for the VR group is that the visuals of the tracking are

the loss of visual acuity in the tracking. Indirectly, the additional workload

of the prompting task could be taking attention away from the tracking

task. The effect of Design indicated a marginally significant difference

$(F(1,21) = 5.94, p = 0.024)$ for the tracking task RMSE between Keypad

₂₈₂ $(M = 1.57\text{deg}, \sigma = 0.51\text{deg})$ and Edgekey $(M = 1.70\text{deg}, \sigma = 0.52\text{deg})$.

₂₈₃ The only change in the tracking task display between the two instrument

₂₈₄ designs is the position moves from being on the left side for the Keypad

₂₈₅ and the middle for the Edgekey. This suggests that any difference on

₂₈₆ the tracking task performance between the groups would be related to

₂₈₇ additional workload from the prompting task. The interaction effect was

₂₈₈ not significant $(F(1, 21) = 0.17, p = 0.69)$.

₂₈₉ To further investigate the change in performance between the two groups,█

₂₉₀ we can investigate the trials where the subjects were only doing the track-

₂₉₁ ing task. At the end of each evaluation session, the subjects ran a single

₂₉₂ trial that was just the tracking task. These trials were included to be used

₂₉₃ as a test of the assumption that the subjects were no longer learning, but

₂₉₄ can also be used as a test of the Group factor on the tracking task perfor-

₂₉₅ mance. The effect of group on RMSE for the tracking-only trials yielded a

₂₉₆ marginially significant difference $(F(1, 21) = 4.81, p = 0.039)$ between the

₂₉₇ VR Group $(M = 1.32, \sigma = 0.50)$ and the TS Group $(M = 0.91, \sigma = 0.43)$.

₂₉₈ There was no signifigant difference for the effect of design $(F(1, 21) =$

₂₉₉ $0.068, p = 0.80)$. The interaction effect between group and design was also

₃₀₀ not significant $(F(1, 21) = 3.21, p = 0.087)$.

Although the tracking only trials found a marginally significant difference for the group, the difference was much more distinct for the trials with both tasks. This indicates that when the subjects were focused on the single task, they were able to mitigate most of the visual resolution differences between using a touchscreen and the virtual reality screen. Additionally, the marginally significant difference between the designs for the trials with both tasks was reduced to no signifigance when the second prompting task was removed. This also points to the additional workload of the prompting task causing a performance drop on the tracking task. The factors leading to the added workload of the prompting task are investigated in the other performance measures.

Prompt Response Time

The first measure of the prompting task is the response time of the subject. The response time is defined as the time from the prompt is shown to each subject until they press the first button of the prompt. For the Edgekey design, it would be possible that the subject had to start with the switching button if the new prompt did not start with the same mode (letters or numbers) as the previous prompt. Since this button would not clear the prompt when it was pressed, it is not considered the first button

Figure 2.7: Factor Plot of Response Time

320   of their entry. However, this would still require an additional movement of

321   the subject, adding additional time. For this reason, the prompts which

322   required the subject to start with the switch key are filtered out of this

323   analysis.

324   The response time was unique among the dependent measures, as all

325   tests were insignificant. The effect of group yielded an F ratio of $F(1, 21) =$

326    $1.19, p = 0.29$ indicating no significant difference between VR ($M = 2812$msec, $\sigma =$ ▮

327   383msec) and TS ($M = 2594$msec, $\sigma = 567$msec). One factor that could

328   influence the response time between groups is the additional time to acti-

vate a button in the VR environment versus the touchscreen. However, a   [explain this?]

large portion of the response time for the subject is their cognitive pro-

cessing of the prompt – recognizing the new prompt has appeared, reading

it, then memorizing it. Beyond potentially differences in the visual envi-

ronment, the cognitive portion should not take more time for one group or

the other. A potential reason that there could be a lower than expected

difference between the group means is that some VR subjects learned to

keep their hand closer to the instrument so that the hand tracker could

keep it in view. When the hand tracker lost view of the hand, the reac-

quisition time could be significant, so holding it close to the instrument

would prevent this from happening. This issue comes up again when look-

ing at the subjects' response to questions about fatigue. The effect of

design was also insignificant ($F(1, 21) = 0.68, p = 0.42$) between Keypad

($M = 2728$msec$, \sigma = 512$msec) and Edgekey ($M = 2687, \sigma = 471$msec).

The biggest difference between the two designs is the switching key on the

Edgekey design. As described above, the need for an additional switch

press before the first prompt button was filtered out, so we are only com-

paring prompts where the first button was available right away to the

subject. Since the Edgekey design had more time pressure due to the need

Figure 2.8: Factor Plot of Correct Prompts

348 for the switch key, subjects could have learned to respond quicker to adapt

349 for this. However, these differences in the design did not appear to have a

350 significant effect on the response time. Finally, the interaction effect was

351 not significant $(F(1, 21) = 0.001, p = 0.96)$.

352 **Prompts Correct**

353 The second measure of the prompting task is the accuracy of the sub-

354 jects in correctly completing the prompt. To get the prompt correct in-

355 cludes two important components for the subject. First, they must re-

356 member the prompt as they enter it, and second, they must be able to

357 physically press the buttons within the seven second response window. For

358 the statistical test we are using hte count of how many prompts each sub-

359 ject completed successfully per trial. Among the incorrect prompts, we can

360 differentiate between whether the subject entered the prompt incorrectly

361 (failure to remember the prompt) or whether the subject ran out of time

362 (failure to physically press the buttons). There were 12 prompts per trial,

363 and every subject completed three trials for each design.

364 The number of correct prompts had a significant interaction effect

365 between group and design ($F(1,21) = 27.8, p < 0.001$), meaning the

366 main effects must be intrepreted with the post-hoc tests as well. Both

367 main effects were significant, the effect of group yielded an F ratio of

368 $F(1,21) = 43.9, p < 0.001$ while the effect of design yielded an F ratio of

369 $F(1,21) = 64.1, p < 0.001$.

370 For the effect of design on the VR group, the repeated measured t-

371 test indicated a significant difference ($t(11) = 8.0, p < 0.001$) between the

372 Keypad ($M = 8.11, \sigma = 1.62$) and the Edgekey ($M = 4.00, \sigma = 2.37$) The

373 TS group had a marginally significant difference ($t(10) = 2.28, p = 0.045$)

374 between Keypad ($M = 9.82, \sigma = 1.38$) and the Edgekey ($M = 10.6, \sigma =$

Figure 2.9: Result of prompts

0.96).Both groups had trouble with the additional time pressure caused these are backward

by the Edgekey design requiring the use of the switch key. The TS group

performed a lot closer to their performance in the Keypad design, only

getting approximately 1 fewer prompt correct. The VR group had much

more difficulty in the Edgekey design, correctly completing about half as

many as they completed in the Keypad design. However, it appears that

they had more difficulty in both designs compared to the TS group.

This agrees with the post-hoc tests for differences in design between

groups. These tests had significant effects for both the Keypad design $(t(21) = 4.44, p < 0.001)$ between the VR group and the TS group, and the Edgekey design $(t(21) = 7.05, p < 0.001)$ between the VR group and the TS group. The main effect of group clearly has a meaningful effect, which found the VR group $(M = 6.05, \sigma = 2.88))$ had significantly fewer correct prompts than the TS group $(M = 10.2, \sigma = 1.2)$. This difference is largely due to subjects not being able to complete the prompt. Figure 2.9 shows the breakdown of the mean result of each trial for each group and design. Across all groups and designs, very few prompts were completed that were incorrect, and most of the differences in number completed correctly is due to the incomplete prompts. A contributing factor for this would be the method of button activation used for the VR group combined with the time pressure. Another contribution would be the limitations of the hand tracker. When the hand tracker lost tracking or gave bad information, it became hard or impossible for the subject to activate a button until the hand tracker returned to normal. When this happened in the middle of a prompt, the amount of time it took to recover from the bad tracking would lead to a timeout on the prompt entry, causing an incomplete prompt. The variance of number correct was also much larger in in the VR group, which

Figure 2.10: Factor Plot of NASA TLX

could be caused by the unfamiliar nature of the VR environment compared to a touchscreen.

NASA TLX

After the subject completed their trials on each design, they completed a NASA TLX workload survey. Their weighted scores are used here as a measure of their self-reported workload. The interaction effect between group and design was found to be significant ($F(1, 21) = 8.25, p < 0.001$). The main effects showed a significant differene in design

410 $(F(1, 21) = 23.6, p < 0.001)$, but not in group $(F(1, 21) = 1.69, p = 0.21)$.

411 This could mean that the group did not affect the TLX score, but in the

412 presence of an interaction effect, the post-hoc tests will guide the inter-

413 petation.

414 The repeated measures t-tests indicated significance between designs

415 for the VR group $(t(11) = -4.20, p = 0.001)$ between the Keypad design

416 $(M = 54.4, \sigma = 20.4)$ and the Edgekey $(M = 85.6, \sigma = 11.2)$ There was a

417 marginally significant difference between designs for the TS group $(t(10) =$

418 $-2.72, p = 0.02)$ between the Keypad design $(M = 61.5, \sigma = 4.46)$ and the

419 Edgekey $(M = 69.2, \sigma = 10.1)$. The effect of design was much stronger

420 in the VR group, but both groups indicated higher workload on the TLX

421 scores for the Edgekey design. This follows from experimental design which

422 hypothesized that the Edgekey design would be more difficult. One factor

423 that could have contributed to a larger difference in scores for the VR group

424 could be the increased difficulty subjects had in completing the prompt, as

425 seen in the results of the number of incorrect and incomplete prompts for

426 the VR group using the Edgekey design. The effect of group was not shown

427 to be significant in the ANOVA analysis, but the independent samples t-

428 test showed a signifigance for the Edgekey design $(t(21) = 3.69, p < 0.01)$

between the VR Group ($M = 85.6, \sigma = 11.2$) and the TS Group ($M = 69.2, \sigma = 10.1$). With the Keypad design, The effect of group was not significant ($t(21) = -1.13, p = 0.27$) between VR ($M = 54.4, \sigma = 20.4$) and TS ($M = 61.5, \sigma = 4.46$). These tests further illustrate that the VR group found a higher workload for the Edgekey design specifically, as both groups rated the workload in the Keypad design similarly.

Summary

A summary of the signifigance results from the ANOVA and post-hoc t-tests for all the performance measures are shown in Table 2.1. The signifigance is indicated by '*' for $p < 0.0125$, '+' for $0.0125 < p < 0.05$, and '-' for no signifigance. The interaction effect is indicated by the "Group:Design" column. For the measures with significant interaction effect, the post-hoc t-tests are shown per group.

2.3.3   Design Feedback

The categories of feedback and the counts of how many times they occured for each group is summarized in Table 2.2.

By far the issue that received the most feedback was the difficulty of using the switch key (Edgekey, Switch Difficult). Most of the complaints just

	ANOVA		
	Group	Design	Group:Design (Interaction)
Tracking RMSE	*	+	-
Response Time	-	*	-
Prompts Correct	*	*	*
NASA TLX	-	*	*
	t-tests		
	Design		Group
	VR Group	TS Group	Keypad Design	Edgekey Design
Prompts Correct	*	+	*	*
NASA TLX	*	+	-	*

Table 2.1: Statistical Signifigance Test Results. '*' indicates signifigance at the $p < 0.0125$ level, '+' indicates marginally significant ($0.0125 < p < 0.05$), and '-' indicates no signifigance. Group:Design is the interaction effect between Group and Design.

centered around the extra difficultly of habving to press another button.

Some noted that it took extra time (with no extra time given), it added

to the mental demands of the task, it was difficult to see which mode the

instrument was in. Both groups disliked the switch key, and mentioned it

just as frequently.

> Switching from numbers to letters was hard, especially if I was trying to compensate for turbulence and was struggling at the time. (TS Subject)

> I did not like how much extra work it was. It took so much extra focus that I forgot I was flying with the joystick (VR Subject)

Many subjects noted the familiarity of the Keypad design (Keypad,

Topic	Feedback Summary Category	VR Group	TS Group
Edgekey	Switch Difficult	14	12
Keypad	Familiar	6	11
Edgekey	Centered Flight Task Better	3	13
Keypad	Buttons Proximal	6	7
Keypad	Buttons Always Visible	5	5
Other	Hand Tracking Issues	9	0
Edgekey	Hand Blocks View	3	4
Fatigue	Prompting Arm	4	1
Edgekey	Clean Design	3	2
Fatigue	Fatigue from Joystick	0	4
Edgekey	Easier	0	4
Keypad	Buttons Confusable	0	4
Other	Colors Disliked	2	2
Fatigue	Eye Fatigue	3	0
Keypad	Easy Focus Switch	2	1
Keypad	More Mistakes	1	2
Edgekey	Accuracy Worse	1	2
Keypad	Buttons Bad Layout	2	0

Table 2.2: Counts of Design Feedback Comments per Group

Familiar) and that having the buttons close together (Keypad, Buttons Proximal) as things they like about that design. The familiarity was noted more often for the TS Group, but both were some of the more frequent comments within each group.

One comment about the Edgekey design that got more frequent mentions from the TS Group was that they found having the flight task in

the middle of the display, centered between the buttons, was preferred

(Edgekey, Centered Flight Task Better). The subjects who noted they

preferred the Edgekey design almost uniamonously cited this as their rea-

son for their preference. The comments that fed into this category also

included subjects who noted the difficulty of splitting their focus back and

forth with the Keypad design. Interestingly, two of the TS Group subjects

noted that they would have found the Keypad easier if they had tactile

feedback to guide their input. It is possible that the reason the VR Group

subjects did not note this as often is because with the tactile feedback they

were able to keep visual focus on the left half of the screen in the Keypad

design, thus not seeing benefit from the centering of the flight task display.

> [The Edgekey design] forced me to pay more attention to what
> I was typing, this wouldn't have been a problem if the keypad
> was a physical device that allowed me to locate the numbers
> and letters without looking, much like the dots on a computer
> keyboard. (TS Subject)

> I like that the flight control was centred, so you could see it
> even when you were looking at the buttons. (VR Subject)

The most notable exceptions to providing similar feedback between

groups are the categories that relate to fatigue issues. Many subjects in

the TS group noted fatigue cause from using the joystick, yet none in the

VR group did, even though they were using the same joystick setup, and

sitting in the same location. The VR group did note more fatigue caused

by using their other arm for the prompting task. This fatigue seemed to be

caused by the additional effort needed to have the hand tracker recognize

the hand. For example, one subject wrote:

> My right wrist was somewhat fatigued. Though I think this is
> mostly from positioning my hand for the simulator to recognize
> my input. (VR Subject)

Some of this additional effort was due to subjects learning to hold their

prompting task hand "hovering" while waiting for the next prompt. This

was done to keep the hand in view of the hand tracker as when the hand

leaves the field of view, the reacquisition will slow down the entry of first

button. Many subjects organically learned this, and kept their arm in front

of the instrument.

Similarly to the fatigue issues being different, there were some com-

ments that were due to the technology being used moreso than the designs

themselves. The obvious ones are the subjects who noted difficulty using

the hand tracker, but some of the other categories had comments that may

have been caused by this. For example, the keypad design was noted as

causing more mistakes for some subjects. For the TS Group, this was due

to the touchscreen being so quick to use:

> [S]ince I was able to go more quickly with this layout, I had
> more mistakes in the entry. (TS Subject)

One subject in VR noted a common problem caused by the hand tracker which caused more mistakes in the Keypad design. When the hand tracker was having registration issues it would sometimes place the other fingers mistakenly in the activation zone of the buttons underneath the one being targeted, causing multiple buttons to be pressed in a short period of time.

> There's more unintended register since other fingers might trigger the buttons. (VR Subject)

Although only one subject noted this, it was observed happening to many subjects[1].

2.4   Discussion

2.4.1   Effects of Training

2.5   Conclusion

---

[1] For the VR group, eight of the twelve subjects had the wrong button register within 200msec of the last button in the Keypad. In the other designs and groups this happened to only one or two subjects.

521 # Appendices

Appendix A

Result Tables

A.1   Design Evaluation Experiment

Group	Design	Mean	Std. Dev.
TS	—	1.277	0.3789
VR	—	1.967	0.378
—	Edgekey	1.704	0.5188
—	Keypad	1.57	0.5068

Table A.1: RMSE Means

Factor	F ratio	p value
Group	21.42	0.000145
Design	5.944	0.02374
Group:Design	0.1669	0.687

Table A.2: RMSE ANOVA

Group	Design	Mean	Std. Dev.
TS	—	2595	567.3
VR	—	2813	383.2
—	Edgekey	2688	471.1
—	Keypad	2729	512.5

Table A.3: Response Time Means

Factor	F ratio	p value
Group	1.199	0.2859
Design	0.6814	0.4184
Group:Design	0.00184	0.9662

Table A.4: Response Time ANOVA

Group	Design	Mean	Std. Dev.
TS	—	10.2	1.242
VR	—	6.056	2.889
—	Edgekey	6.768	3.525
—	Keypad	9.304	1.831
VR	Edgekey	4	2.37
VR	Keypad	8.111	1.616
TS	Edgekey	9.788	1.393
TS	Keypad	10.61	0.964

Table A.5: Correct Prompts Means

Factor	F ratio	p value
Group	43.56	1.552×10^{-6}
Design	63.93	8.309×10^{-8}
Group:Design	26.89	3.872×10^{-5}

Table A.6: Correct Prompts ANOVA

Table A.7: Correct Prompts t-tests

Group	Design	Mean	Std. Dev.
TS	—	65.35	8.535
VR	—	70.01	22.65
—	Edgekey	77.74	13.4
—	Keypad	57.83	15.18
VR	Edgekey	85.61	11.21
VR	Keypad	54.42	20.4
TS	Edgekey	69.15	10.06
TS	Keypad	61.55	4.468

Table A.8: NASA TLX Means

Factor	F ratio	p value
Group	1.688	0.208
Design	23.57	8.455×10^{-5}
Group:Design	8.252	0.009113

Table A.9: NASA TLX ANOVA

Table A.10: NASA TLX t-tests