

# PRD 12: Topological Mechanical Metamaterials

Pure Thought AI Challenge 12

Pure Thought AI Challenges Project

January 18, 2026

## Abstract

This document presents a comprehensive Product Requirement Document (PRD) for implementing a pure-thought computational challenge. The problem can be tackled using only symbolic mathematics, exact arithmetic, and fresh code—no experimental data or materials databases required until final verification. All results must be accompanied by machine-checkable certificates.

## Contents

**Domain:** Materials Science

**Timeline:** 4-7 months

**Difficulty:** Medium-High

**Prerequisites:** Classical mechanics, elasticity theory, graph theory, computational mechanics

## 0.1 1. Problem Statement

### 0.1.1 Scientific Context

**Mechanical metamaterials** are architected structures whose mechanical properties arise from geometry rather than composition. When combined with **topological physics**, they exhibit:

- **Topological Zero Modes:** Floppy edge modes that cost zero energy to excite
- **Protected Deformations:** Robust against disorder, defects, and manufacturing errors
- **Programmable Mechanics:** Designer elasticity, auxetic behavior, mechanical computing

The key insight is that **phononic band structures** (vibrations in elastic materials) obey the same topological principles as electronic and photonic systems.

**Maxwell Counting:** For a framework of  $N$  sites connected by  $N_b$  bonds with constraints:

$$N_{\text{ZM}} = N_b - dN + N_c$$

where  $d$  is spatial dimension,  $N_c$  is number of constraints. When  $N_{\text{ZM}} = 0$ , the structure has **zero modes** (floppy modes).

**Topological Polarization:** The location of zero modes (bulk vs edge) is determined by topological invariants, analogous to Chern numbers in electronics.

**Recent Breakthroughs:**

- Kane & Lubensky (2014): Topological boundary modes in mechanical systems
- Mechanical Weyl points in 3D metamaterials
- Higher-order topological mechanics with corner modes

### 0.1.2 Core Question

**Can we systematically design mechanical metamaterials with topologically protected zero modes using ONLY graph theory and Maxwell counting—without simulations or trial-and-error?**

Specifically:

- Given target number of edge modes  $N_{\text{edge,constructspring-masslattice}}$
- Prove zero modes are localized to boundaries using topological invariants
- Optimize stiffness matrix for maximum robustness
- Export 3D-printable designs with exact force constants
- Certify protection against bond disorder and manufacturing defects

### 0.1.3 Why This Matters

#### Theoretical Impact:

- Extends topological physics to classical systems
- Connects combinatorics (graph theory) to continuum mechanics
- Provides designer materials with programmable response

#### Practical Benefits:

- Shock-absorbing materials with directional stiffness
- Soft robotics with controlled compliance
- Mechanical computers (logic gates from topological modes)
- Metamaterial actuators and sensors

#### Pure Thought Advantages:

- Stiffness matrices are purely combinatorial (connectivity + spring constants)
- Zero modes found via kernel of dynamical matrix
- Topology determined from graph structure alone
- No material properties needed (geometry dominates)
- Directly 3D-printable (with specified spring constants)

## 0.2 2. Mathematical Formulation

### 0.2.1 Problem Definition

A **mechanical metamaterial** is a network of  $N$  sites (masses) at positions  $\mathbf{r}_i$  connected by springs :  
**Dynamical Matrix** (small oscillations):

$$D_{ij} = \sum_k \left[ k_{ik} \delta_{ij} - \frac{k_{ik} (r_i - r_k)_j}{|r_i - r_k|} \right]$$

where:

- $k_{ik}$  is spring constant for bond  $\langle ik \rangle$
- $r_i$  are spatial components (x,y,z)
- $\langle ik \rangle$  denotes bonded pairs

**Zero Modes:** Solutions to  $D = 0$  (floppy modes with  $\omega^2 = 0$ ).

**Topological Polarization** (1D chain):

$$P = \frac{1}{2\pi} \int_{BZ} A(k) dk \mod 1$$

where  $A(k)$  is geometric phase (analog of Berry connection for phonons).

When  $P$  is fractional, the system has **topological boundary modes**.

**Spectral Flow:** Number of zero modes crossing from  $-$  to  $+$  eigenvalues when interpolating between two configurations gives topological index.

### 0.2.2 Certificate Requirements

- **Maxwell Count Certificate:** Verify  $NZM = Nb - dN + N_c$  *exactly*
- **Zero Mode Localization:** Prove modes decay exponentially from edges
- **Topological Invariant:** Compute polarization P or winding number
- **Robustness Proof:** Show edge modes survive spring constant disorder  $k/k$
- **Fabrication Specs:** Export spring constants and geometry for 3D printing

### 0.2.3 Input/Output Specification

Input:

```

1 from sympy import *
2 import numpy as np
3 import networkx as nx
4 from typing import List, Tuple
5
6 class MechanicalLattice:
7     dimension: int # 1D, 2D, or 3D
8     sites: List[np.ndarray] # Position vectors
9     bonds: List[Tuple[int, int]] # Connectivity (i, j) pairs
10    spring_constants: dict # k_{ij} for each bond
11    constraints: List[Callable] # Constraint functions (e.g., fixed
        sites)

```

Output:

```

1 class MechanicalCertificate:
2     lattice: MechanicalLattice
3
4     # Maxwell counting
5     N_sites: int
6     N_bonds: int
7     N_constraints: int
8     N_zero_modes_predicted: int
9
10    # Spectrum
11    dynamical_matrix: np.ndarray
12    eigenvalues: np.ndarray # values
13    zero_mode_eigenvectors: List[np.ndarray] # Modes with 0
14
15    # Topology
16    topological_polarization: float # P mod 1
17    winding_number: Optional[int] # For 1D systems
18    edge_mode_count: int # Actual number of boundary modes
19
20    # Localization
21    participation_ratio: List[float] # For each zero mode
22    localization_length: float # Decay length from edge
23
24    # Robustness
25    disorder_threshold: float # Max k /k before gap closes
26    fabrication_tolerance: dict # Geometric tolerances

```

```

27
28 # Fabrication
29 stl_file: Path
30 spring_specifications: dict # Material + geometry for each spring
31 assembly_instructions: str

```

### 0.3 3. Implementation Approach

#### 0.3.1 Phase 1: Maxwell Counting and Zero Modes (Months 1-2)

Implement basic topological mechanics infrastructure:

```

1 import numpy as np
2 from scipy.linalg import eigh, null_space
3 import networkx as nx
4
5 def build_dynamical_matrix(lattice: MechanicalLattice) -> np.ndarray:
6     """
7     Construct dynamical matrix D for small oscillations.
8
9     D_ij^{αβ} encodes spring network topology and stiffnesses.
10    """
11    N = len(lattice.sites)
12    d = lattice.dimension
13    D = np.zeros((N*d, N*d))
14
15    for (i, j), k_ij in zip(lattice.bonds,
16        lattice.spring_constants.values()):
17        r_ij = lattice.sites[j] - lattice.sites[i]
18        dist = np.linalg.norm(r_ij)
19
20        # Spring tensor: k_ij * (r_ij ⊗ r_ij) / |r_ij|^3
21        spring_tensor = k_ij * np.outer(r_ij, r_ij) / dist**3
22
23        # Add to dynamical matrix (block structure)
24        for α in range(d):
25            for β in range(d):
26                # Diagonal blocks (i,i) and (j,j)
27                D[i*d + α, i*d + α] += spring_tensor[α, α]
28                D[j*d + β, j*d + β] += spring_tensor[β, β]
29
30                # Off-diagonal blocks (i,j) and (j,i)
31                D[i*d + α, j*d + β] -= spring_tensor[α, β]
32                D[j*d + β, i*d + α] -= spring_tensor[β, α]
33
34    return D
35
36 def maxwell_count(lattice: MechanicalLattice) -> int:
37     """
38     Compute predicted number of zero modes from Maxwell counting.
39
40     N_ZM = N_bonds - d*N_sites + N_constraints
41    """
42    N_sites = len(lattice.sites)

```

```

42     N_bonds = len(lattice.bonds)
43     d = lattice.dimension
44     N_constraints = len(lattice.constraints)
45
46     N_ZM = N_bonds - d*N_sites + N_constraints
47
48     return N_ZM
49
50 def find_zero_modes(D: np.ndarray, tolerance: float = 1e-8) ->
    List[np.ndarray]:
51     """
52     Find zero eigenvalue modes of dynamical matrix.
53
54     Zero modes satisfy  $D = 0$ .
55     """
56     eigenvalues, eigenvectors = eigh(D)
57
58     # Identify zero modes
59     zero_mode_indices = np.where(np.abs(eigenvalues) < tolerance)[0]
60
61     zero_modes = [eigenvectors[:, idx] for idx in zero_mode_indices]
62
63     return zero_modes, eigenvalues[zero_mode_indices]
64
65 def remove_trivial_zero_modes(zero_modes: List[np.ndarray],
66                               lattice: MechanicalLattice) ->
    List[np.ndarray]:
67     """
68     Remove trivial zero modes (rigid translations/rotations).
69
70     In d dimensions:
71     - d translational zero modes
72     - d(d-1)/2 rotational zero modes (for free boundary conditions)
73
74     These are not topological.
75     """
76     N = len(lattice.sites)
77     d = lattice.dimension
78
79     # Generate translations
80     translations = []
81     for i in range(d):
82         trans = np.zeros(N*d)
83         trans[i::d] = 1.0 # All sites move in direction i
84         translations.append(trans)
85
86     # Generate rotations (for d=2: around z-axis; d=3: around x,y,z)
87     rotations = []
88     if d == 2:
89         # Rotation around origin
90         rot = np.zeros(N*d)
91         for i, r in enumerate(lattice.sites):
92             rot[2*i] = -r[1] # x = -y
93             rot[2*i+1] = r[0] # y = x
94         rotations.append(rot)
95

```

```

96     trivial_modes = translations + rotations
97
98     # Project out trivial modes
99     nontrivial_modes = []
100     for mode in zero_modes:
101         # Check if mode is combination of trivial modes
102         projection = sum(np.dot(mode, triv)**2 for triv in
103                           trivial_modes)
104
105         if projection / np.dot(mode, mode) < 0.99: # Less than 99%
106             overlap
107             nontrivial_modes.append(mode)
108
109     return nontrivial_modes

```

**Validation:** Reproduce Kane-Lubensky kagome lattice with topological zero modes.

### 0.3.2 Phase 2: Topological Polarization (Months 2-3)

Compute topological invariants for 1D chains:

```

1 def compute_polarization_1d(lattice: MechanicalLattice, k_values:
2   np.ndarray) -> float:
3     """
4     Compute topological polarization P for 1D mechanical chain.
5
6      $P = (1/2) \int_{-\pi}^{\pi} A(k) dk \mod 1$ 
7
8     where A(k) is geometric phase (Berry connection for phonons).
9     """
10    # Build k-space dynamical matrix
11    def D_k(k: float) -> np.ndarray:
12        # Fourier transform of spring network
13        N_unit_cell = count_sites_per_unit_cell(lattice)
14        D = np.zeros((N_unit_cell, N_unit_cell), dtype=complex)
15
16        for (i, j) in lattice.bonds:
17            # Distance in unit cells
18            delta_n = unit_cell_difference(lattice, i, j)
19
20            k_ij = lattice.spring_constants[(i, j)]
21            r_ij = lattice.sites[j] - lattice.sites[i]
22
23            phase = np.exp(1j * k * delta_n)
24            D[i % N_unit_cell, j % N_unit_cell] += k_ij * phase
25
26        return D
27
28    # Compute Berry connection A(k)
29    A_values = []
30
31    for k in k_values:
32        D_k_val = D_k(k)
33        evals, evecs = eigh(D_k_val)
34
35        # Occupied band (lowest non-zero mode)

```



```

35     occupied_state = evecs[:, 0] # Assuming first mode is occupied
36
37     # Derivative approximation
38     dk = k_values[1] - k_values[0]
39     D_k_plus = D_k(k + dk)
40     evals_plus, evecs_plus = eigh(D_k_plus)
41     occupied_plus = evecs_plus[:, 0]
42
43     # Berry connection:  $A = i \langle u | \nabla_k | u \rangle$ 
44     overlap = np.vdot(occupied_state, occupied_plus)
45     A_k = np.imag(np.log(overlap)) / dk
46
47     A_values.append(A_k)
48
49     # Integrate
50     P = np.trapz(A_values, k_values) / (2*np.pi)
51
52     return P % 1 # Polarization mod 1
53
54 def predict_edge_modes_from_polarization(P: float, N_unit_cells: int)
55     -> int:
56     """
57     Predict number of edge modes from polarization.
58
59     If P = 0, there are topological boundary modes.
60     Number of modes = P * N_unit_cells (for finite system).
61     """
62     if abs(P) < 0.1 or abs(P - 1) < 0.1:
63         # Trivial polarization
64         return 0
65     else:
66         # Non-trivial: edge modes present
67         # Exact count depends on termination
68         return int(np.round(abs(P)))

```

### 0.3.3 Phase 3: 2D Kagome Lattice (Months 3-4)

Implement canonical topological mechanical system:

```

1 def kagome_lattice(N_x: int, N_y: int, spring_const: float = 1.0) ->
2     MechanicalLattice:
3     """
4     Construct kagome lattice with topological edge modes.
5
6     Kagome lattice: 3 sites per unit cell, triangular Bravais lattice.
7     Has Z = 1 (one topological edge mode per edge).
8     """
9     sites = []
10    bonds = []
11
12    # Lattice vectors
13    a1 = np.array([1.0, 0.0])
14    a2 = np.array([0.5, np.sqrt(3)/2])
15
16    # Three sublattice positions within unit cell
17    r_A = np.array([0, 0])

```

[illegible]

```

73     """
74     Compute localization length of edge mode.
75
76     Fit  $| \psi(x) | \sim \exp(-x/\xi)$  where  $\xi$  is localization length.
77     """
78     N = len(lattice.sites)
79     d = lattice.dimension
80
81     # Extract displacement amplitudes
82     amplitudes = np.array([np.linalg.norm(zero_mode[i*d:(i+1)*d])
83                             for i in range(N)])
84
85     # Find edge (assume edge is at x=0)
86     x_positions = np.array([site[0] for site in lattice.sites])
87
88     # Sort by distance from edge
89     sorted_indices = np.argsort(x_positions)
90
91     # Fit exponential decay
92     from scipy.optimize import curve_fit
93
94     def exp_decay(x, xi, A):
95         return A * np.exp(-x / xi)
96
97     try:
98         popt, _ = curve_fit(exp_decay,
99                             x_positions[sorted_indices],
100                             amplitudes[sorted_indices],
101                             p0=[1.0, 1.0])
102         localization_length = popt[0]
103     except:
104         localization_length = np.inf # Delocalized
105
106     return localization_length

```

### 0.3.4 Phase 4: Disorder and Robustness (Months 4-5)

Test topological protection:

```

1 def add_spring_disorder(lattice: MechanicalLattice,
2                           disorder_strength: float) -> MechanicalLattice:
3     """
4     Add disorder to spring constants:  $k \rightarrow k(1 + \delta)$  where  $\delta \sim U(-1, 1)$ .
5     """
6     disordered_springs = {}
7
8     for bond, k_0 in lattice.spring_constants.items():
9         delta = disorder_strength * np.random.uniform(-1, 1)
10        disordered_springs[bond] = k_0 * (1 + delta)
11
12    return MechanicalLattice(
13        dimension=lattice.dimension,
14        sites=lattice.sites,
15        bonds=lattice.bonds,
16        spring_constants=disordered_springs,

```

```

17         constraints=lattice.constraints
18     )
19
20 def test_topological_robustness(lattice: MechanicalLattice,
21                                disorder_levels: List[float],
22                                N_trials: int = 50) -> dict:
23     """
24     Test edge mode survival vs spring constant disorder.
25     """
26     results = {}
27
28     # Count edge modes in clean system
29     D_clean = build_dynamical_matrix(lattice)
30     zero_modes_clean, _ = find_zero_modes(D_clean)
31     N_edge_clean = len(remove_trivial_zero_modes(zero_modes_clean,
32                                                  lattice))
33
34     for disorder in disorder_levels:
35         edge_mode_survival = []
36
37         for trial in range(N_trials):
38             disordered = add_spring_disorder(lattice, disorder)
39             D_disorder = build_dynamical_matrix(disordered)
40             zero_modes, _ = find_zero_modes(D_disorder, tolerance=1e-6)
41             N_edge_disorder = len(remove_trivial_zero_modes(zero_modes,
42                                                            disordered))
43
44             # Check if edge modes survive
45             survival = (N_edge_disorder == N_edge_clean)
46             edge_mode_survival.append(survival)
47
48         results[disorder] = {
49             'survival_rate': np.mean(edge_mode_survival),
50             'mean_edge_modes': np.mean([N_edge_disorder for _ in
51                                         edge_mode_survival])
52         }
53
54     return results

```

### 0.3.5 Phase 5: 3D Printing Export (Months 5-6)

Generate fabrication files:

```

1 def export_metamaterial_stl(lattice: MechanicalLattice,
2                              output_path: Path,
3                              rod_radius: float = 0.05,
4                              node_radius: float = 0.1):
5     """
6     Export mechanical metamaterial as STL for 3D printing.
7
8     Each bond becomes a cylindrical rod, each site a spherical node.
9     Spring constant encoded in rod cross-section.
10    """
11    from stl import mesh
12    import trimesh
13

```

```

14 geometries = []
15
16 # Create nodes (spheres at sites)
17 for site in lattice.sites:
18     sphere = trimesh.creation.icosphere(radius=node_radius)
19     sphere.apply_translation(site)
20     geometries.append(sphere)
21
22 # Create bonds (cylinders)
23 for (i, j) in lattice.bonds:
24     r_i = lattice.sites[i]
25     r_j = lattice.sites[j]
26
27     # Spring constant determines rod thickness
28     k_ij = lattice.spring_constants[(i, j)]
29     rod_thickness = rod_radius * np.sqrt(k_ij) # Encode stiffness
30     in geometry
31
32     cylinder = create_cylinder(r_i, r_j, rod_thickness)
33     geometries.append(cylinder)
34
35 # Combine all geometries
36 combined_mesh = trimesh.util.concatenate(geometries)
37
38 # Export
39 combined_mesh.export(str(output_path))
40
41 def generate_assembly_instructions(lattice: MechanicalLattice) -> str:
42     """
43     Generate human-readable assembly protocol.
44     """
45     instructions = "Mechanical Metamaterial Assembly\n"
46     instructions += "=" * 50 + "\n\n"
47
48     instructions += "1. Material: TPU (Shore 95A hardness)\n"
49     instructions += "2. Print Settings: 0.1mm layer height, 100%
50         infill\n\n"
51
52     instructions += "3. Spring Constants (encoded in rod diameter):\n"
53     for (i, j), k in lattice.spring_constants.items():
54         d = 2 * rod_radius * np.sqrt(k)
55         instructions += f"    Bond ({i},{j}): k={k:.2f} N/m    diameter
56             {d:.3f} mm\n"
57
58     instructions += "\n4. Expected Zero Modes:\n"
59     N_ZM = maxwell_count(lattice)
60     instructions += f"    Total: {N_ZM} zero modes\n"
61     instructions += f"    Edge modes: {N_ZM -
62         lattice.dimension*(lattice.dimension-1)/2}\n"
63
64     return instructions
65
66 def certificate_export(cert: MechanicalCertificate, output_dir: Path):
67     """
68     Export complete certificate as JSON + STL + instructions.
69     """

```

```

66 import json
67
68 # JSON certificate
69 cert_dict = {
70     'maxwell_count': {
71         'N_sites': cert.N_sites,
72         'N_bonds': cert.N_bonds,
73         'N_constraints': cert.N_constraints,
74         'N_zero_modes_predicted': cert.N_zero_modes_predicted
75     },
76     'topology': {
77         'polarization': float(cert.topological_polarization),
78         'edge_mode_count': cert.edge_mode_count
79     },
80     'localization': {
81         'localization_length': float(cert.localization_length),
82         'participation_ratios': [float(pr) for pr in
83                                 cert.participation_ratio]
84     },
85     'robustness': {
86         'disorder_threshold': float(cert.disorder_threshold)
87     },
88     'fabrication': {
89         'stl_file': str(cert.stl_file),
90         'tolerances': cert.fabrication_tolerance
91     }
92 }
93
94 with open(output_dir / 'certificate.json', 'w') as f:
95     json.dump(cert_dict, f, indent=2)
96
97 # Assembly instructions
98 with open(output_dir / 'assembly.txt', 'w') as f:
99     f.write(cert.assembly_instructions)

```

### 0.3.6 Phase 6: Database Generation (Months 6-7)

Catalog topological mechanical systems:

```

1 def generate_metamaterial_database() -> dict:
2     """
3     Generate database of topological mechanical metamaterials.
4     """
5     database = {'models': []}
6
7     # 1D chains
8     for topology in ['SSH', 'dimerized']:
9         lattice = create_1d_chain(topology, N_cells=20)
10        cert = generate_mechanical_certificate(lattice)
11        database['models'].append({
12            'name': f'1D_{topology}',
13            'dimension': 1,
14            'edge_modes': cert.edge_mode_count,
15            'polarization': cert.topological_polarization
16        })
17

```

```

18 # 2D lattices
19 for geometry in ['kagome', 'snub_square', 'honeycomb']:
20     lattice = create_2d_lattice(geometry, N_x=10, N_y=10)
21     cert = generate_mechanical_certificate(lattice)
22     database['models'].append({
23         'name': f'2D_{geometry}',
24         'dimension': 2,
25         'edge_modes': cert.edge_mode_count,
26         'certificate_path': export_certificate(cert)
27     })
28
29 return database

```

## 0.4 4. Example Starting Prompt

```

1 You are a mechanical engineer specializing in topological
  metamaterials. Design spring-mass
2 networks with topologically protected zero modes using ONLY graph
  theory and Maxwell counting.
3
4 OBJECTIVE: Construct kagome lattice with Z=1 edge modes, prove
  topological protection,
5 export 3D-printable STL file.
6
7 PHASE 1 (Months 1-2): Maxwell counting infrastructure
8 - Implement dynamical matrix construction from spring network
9 - Code zero mode finder (kernel of D)
10 - Validate on simple chain: SSH model with edge modes
11 - Verify Maxwell count:  $N_{ZM} = N_b - 2N$ 
12
13 PHASE 2 (Months 2-3): Topological polarization
14 - Compute  $P = \frac{1}{2\pi} \oint \text{Im} \left( \frac{1}{\lambda} \frac{d\lambda}{dk} \right) dk$  for 1D chains
15 - Verify  $P = 1/2$  for SSH model edge modes
16 - Implement winding number calculation
17
18 PHASE 3 (Months 3-4): Kagome lattice
19 - Construct 10x10 kagome with  $N_x, N_y$  unit cells
20 - Compute all zero modes via  $\text{eigh}(D)$ 
21 - Remove trivial modes (translations + rotations)
22 - Verify edge mode count = perimeter length
23
24 PHASE 4 (Months 4-5): Robustness testing
25 - Add spring disorder:  $k = k_0(1 + \delta k)$  with  $\delta k = 5\%, 10\%, 20\%$ 
26 - Test edge mode survival (50 realizations per disorder level)
27 - Find critical disorder  $\delta k_c$  where modes disappear
28
29 PHASE 5 (Months 5-6): Fabrication export
30 - Generate STL with spherical nodes, cylindrical bonds
31 - Encode spring constants in rod thickness:  $d = d_0 k$ 
32 - Specify material: TPU flexible filament
33 - Write assembly instructions
34
35 PHASE 6 (Months 6-7): Database generation

```

```

36 - Catalog 5 different 2D topological lattices
37 - Export certificates for each
38 - Compare edge mode counts, localization lengths
39
40 SUCCESS CRITERIA:
41 - MVR: SSH and kagome lattices with verified zero modes
42 - Strong: Topological polarization computed, disorder tested
43 - Publication: Database of 10 metamaterials with STL files
44
45 VERIFICATION:
46 - Maxwell count exact:  $N_{\text{ZM}} = N_{\text{b}} - dN$  (integer)
47 - Zero modes verified:  $| \quad | < 10$ 
48 - Edge localization:  $\quad < 3$  lattice spacings
49 - Disorder threshold:  $\quad_c > 20\%$ 
50
51 Pure combinatorics + linear algebra. No FEM simulations.
52 All results certificate-based with exact arithmetic.

```

---

## 0.5 5. Success Criteria

### 0.5.1 MVR (2 months)

- SSH chain + kagome with verified zero modes
- Maxwell counting validated

### 0.5.2 Strong (4-5 months)

- Polarization computed for 5 systems
- Disorder robustness tested
- 10 metamaterials cataloged

### 0.5.3 Publication (6-7 months)

- Complete database with STL files
  - Formal proofs of edge mode counts
  - Application to soft robotics
- 

## 0.6 6. Verification Protocol

Automated checks: Maxwell count, zero mode kernel, edge localization fits, disorder statistics.

---

## 0.7 7. Resources Milestones

References:



- Kane Lubensky (2014): "Topological Boundary Modes in Isostatic Lattices"
- Paulose et al. (2015): "Topological Modes Bound to Dislocations"
- Nash et al. (2015): "Topological Mechanics of Gyroscopic Metamaterials"

**Milestones:**

- Month 2: SSH + kagome validated
  - Month 4: Polarization working
  - Month 6: Database + STL export complete
- 

**0.8 8. Extensions**

- **3D Weyl Mechanics:** Mechanical Weyl points
  - **Active Metamaterials:** Motors + topological modes
  - **Quantum Mechanics:** Phonon topology in quantum crystals
- 

**End of PRD 12**