

STAND-ALONE SYSTEM

ELS150

Integrated Active Archive & Preservation Appliance Performance and preservation in one compact system.

ELS150 combines SSD/HDD performance storage with automated dual-sided optical preservation - an integrated platform for Active Archive or preservation-first deployments.

**150**

maximum media

Up to 4

optical drives

30 TB

current 200GB media

550W

maximum power

WHERE IT FITS



For Active Archive, performance storage and nearline preservation work together. For preservation-only deployments, cache can be cleared after successful optical preservation.

BUILT FOR

- Compact integrated Active Archive
- Departmental evidence, records and imaging
- Long-lived data requiring fast local access
- Deployments that need performance plus immutable optical preservation

Technology changes. Information persists.

ELS150

TECHNICAL OVERVIEW

Core specifications

Optical configuration	3 standard magazines; up to 150 discs
Media	Dual-sided optical; up to 200GB per disc
Current max capacity	30 TB
Optical drives	Up to 4; up to 80MB/s concurrent throughput
Performance tier	4 x 3.5 in bays; SSD and/or HDD configuration
Protection	Optical RAID 11+1; one parity disc per 12 discs
Interfaces	Gigabit LAN; SAS expansion; S3-compatible protocol
Power	550W maximum; intelligent disk sleep
Dimensions / weight	331 x 592 x 642 mm; up to 55 kg

INTEGRATION & MANAGEMENT

- Integrated performance and nearline preservation tiers
- Performance copy remains while workload requirements justify it
- Preserved optical copy remains after performance copy is removed
- oRain provides object access and storage management

PRESERVATION & RESILIENCE

- Write-once optical anchors the preserved copy
- Automatic recovery model from optical media
- Electronics MTBF >100,000 hours
- Robotic arm rated >2,000,000 cycles

ONE ELS FAMILY. ONE MANAGED ENVIRONMENT.

ELS systems can operate as preservation infrastructure or as the optical foundation of Active Archive. oRain provides a unified object and storage-management layer across systems.

Specifications are configuration-dependent and subject to final system design. Media capacities shown reflect supported media classes in current product specifications.