

RACK-MOUNT SYSTEM

ELS300

Rack-Mount Nearline Optical Library

High-density nearline preservation in a 7U footprint.

ELS300 provides automated single-sided optical preservation for rack environments. Configure with a separate performance tier for Active Archive.

**288**

maximum media

Up to 4

optical drives

28.8 TB

100GB media

7U

rack footprint

WHERE IT FITS



For Active Archive, performance storage and nearline preservation work together. For preservation-only deployments, cache can be cleared after successful optical preservation.

BUILT FOR

- Rack-based nearline preservation
- Evidence, records, medical imaging and research data
- Active Archive paired with SSD/HDD performance storage
- Data-center deployments requiring compact optical density

Technology changes. Information persists.

ELS300

TECHNICAL OVERVIEW

Core specifications

Optical configuration	24 standard cassettes; up to 288 discs
Media	Single-sided optical; up to 100GB per disc
Maximum capacity	28.8 TB
Optical drives	Up to 4; up to 80MB/s concurrent throughput
Protection	Optical RAID 11+1; one parity disc per 12 discs
Interfaces	Gigabit LAN; SAS expansion; S3-compatible protocol
Power	550W maximum; intelligent power management
Dimensions / weight	448 x 310 x 930 mm; 7U; 80 kg

INTEGRATION & MANAGEMENT

- Separate performance/cache tier supports Active Archive access
- Nearline optical remains available without manual media handling
- oRain provides object access, location awareness and retrieval
- Integrates with larger ELS systems as preservation requirements grow

PRESERVATION & RESILIENCE

- Write-once optical media protects against in-place modification
- Optical RAID protection and automatic recovery model
- Electronics MTBF >100,000 hours
- Robotic arm rated >2,000,000 cycles

ONE ELS FAMILY. ONE MANAGED ENVIRONMENT.

ELS systems can operate as preservation infrastructure or as the optical foundation of Active Archive. oRain provides a unified object and storage-management layer across systems.

Specifications are configuration-dependent and subject to final system design. Media capacities shown reflect supported media classes in current product specifications.