

Login

HOMEPRODUCTSSERVICESSUPPORTCONNECT

LEARN MORECOMPANY



HOMER Pro Features

Flexible options to suit your needs

Download a free trial. Sign up in minutes.

| Project information and setup | HOMER Pro (main) | Add-on Modules | | | | | |
|--------------------------------------|------------------|----------------|---------|-------|-------------------------|----------|---------------|
| | | Advanced Load | Biomass | Hydro | Combined Heat and Power | Hydrogen | Advanced Grid |
| Locate project on map | ✓ | | | | | | |
| View system schematic | ✓ | | | | | | |
| AC and DC buses | ✓ | | | | | | |
| Copy component from model to library | ✓ | | | | | | |
| Linked sensitivities | ✓ | | | | | | |

| | | | | | | | |
|---|---|----------------|---------|-------|-------------------------|----------|---------------|
| International currency and number formats | ✓ | | | | | | |
| Paid license users can disable ads | ✓ | | | | | | |
| Compare scenarios | ✓ | | | | | | |
| | | | | | | | |
| Components | HOMER Pro (main) | Add-on Modules | | | | | |
| | | Advanced Load | Biomass | Hydro | Combined Heat and Power | Hydrogen | Advanced Grid |
| Generators | Up to 20 | | | | | | |
| Capital and replacement cost | S | | | | | | |
| Operations and maintenance cost | S | | | | | | |
| Maintenance scheduling | ✓ | | | | | | |
| Operational scheduling | ✓ | | | | | | |
| Lifetime | S (hours) | | | | | | |
| Fuel curve | ✓ | | | | | | |
| Emissions factors | ✓ | | | | | | |
| Solar PV Arrays | Up to 10 | | | | | | |
| Capital and replacement cost | S | | | | | | |
| Type | Flat plate or concentrating | | | | | | |
| Lifetime | S (years) | | | | | | |
| Derating factor | V | | | | | | |
| Dedicated converter | Inverter or maximum power point tracker | | | | | | |
| Temperature effects | S | | | | | | |

| | | | | | | | |
|-------------------------------------|-------------|--|--|--|--|--|--|
| Tracking, slope, azimuth | S | | | | | | |
| Wind Turbine | 2 | | | | | | |
| Improved wind turbine model builder | ✓ | | | | | | |
| Capital and replacement cost | S | | | | | | |
| Lifetime | S (years) | | | | | | |
| Hub height | S | | | | | | |
| Losses | V (7 types) | | | | | | |
| Scheduled turbine maintenance | ✓ | | | | | | |
| Batteries | Up to 10 | | | | | | |
| Improved battery model builder | ✓ | | | | | | |
| Conventional | ✓ | | | | | | |
| Zinc | ✓ | | | | | | |
| Vanadium | ✓ | | | | | | |
| Capital and replacement cost | S | | | | | | |
| Initial state of charge | S | | | | | | |
| Minimum state of charge | S | | | | | | |
| Lifetime throughput | S | | | | | | |
| Enforce or model minimum life | ✓ | | | | | | |
| Flywheel | 1 | | | | | | |
| Capital and replacement cost | S | | | | | | |
| Lifetime | S | | | | | | |
| DC/AC converter | 1 | | | | | | |

| | | | | | | | | |
|--|---------------------------------|-----------|--|--|-----------|--|--|---|
| | Capital and replacement cost | S | | | | | | |
| | Lifetime | S (years) | | | | | | |
| | Efficiency | S | | | | | | |
| | Grid | ✓ | | | | | | |
| | Grid power price | V | | | | | | |
| | Grid sellback price | V | | | | | | |
| | Sale capacity | V | | | | | | |
| | Net metering | ✓ | | | | | | |
| | Real-time rates | | | | | | | ✓ |
| | Scheduled rates (time of use) | | | | | | | ✓ |
| | Grid extension | | | | | | | ✓ |
| | Hydrokinetic | ✓ | | | | | | |
| | Capital and replacement cost | S | | | | | | |
| | Lifetime | S (years) | | | | | | |
| | Power curve | ✓ | | | | | | |
| | Hydro | | | | ✓ | | | |
| | Capital and replacement cost | | | | S | | | |
| | Operations and maintenance cost | | | | S | | | |
| | Lifetime | | | | S (years) | | | |
| | Available turbine head | | | | S | | | |
| | Design flow rate | | | | S | | | |
| | Minimum flow rate | | | | S | | | |
| | Maximum flow | | | | | | | |

| | | | | | | | |
|-------------------------------------|--|--|--|---|-----------|--------------|--|
| rate | | | | S | | | |
| Efficiency | | | | S | | | |
| Pipe head loss | | | | S | | | |
| Boiler | | | | | ✓ | | |
| Fuel types | | | | | 8 | | |
| Fuel price | | | | | S | | |
| Efficiency | | | | | S | | |
| Emissions | | | | | V | | |
| Thermal load controller (dump load) | | | | | ✓ | | |
| Capital and replacement cost | | | | | S | | |
| Lifetime | | | | | S (years) | | |
| Reformer | | | | | | ✓ | |
| Capital and replacement cost | | | | | | S | |
| Operations and maintenance cost | | | | | | S | |
| Lifetime | | | | | | S (years) | |
| Efficiency | | | | | | S | |
| Hydrogen delivery cost | | | | | | S (\$/kg/km) | |
| Electrolyzer | | | | | | ✓ | |
| Capital and replacement cost | | | | | | S | |
| Operations and maintenance cost | | | | | | S | |
| Lifetime | | | | | | S (years) | |
| Efficiency | | | | | | S | |
| Minimum load ratio | | | | | | S | |

| | | | | | | | | |
|--|--|------------------|----------------|---------|-------|-------------------------|-----------|---------------|
| | Hydrogen tank | | | | | | ✓ | |
| | Capital and replacement cost | | | | | | S | |
| | Operations and maintenance cost | | | | | | S | |
| | Set initial tank level | | | | | | S | |
| | Option to require year-end tank level to equal or exceed initial level | | | | | | ✓ | |
| | Hydrogen fuel cell | | | | | | ✓ | |
| | Capital and replacement cost | | | | | | S | |
| | Operations and maintenance cost | | | | | | S | |
| | Maintenance scheduling | | | | | | S | |
| | Operational scheduling | | | | | | S | |
| | Lifetime | | | | | | S (years) | |
| | Fuel curve | | | | | | ✓ | |
| | | | | | | | | |
| | Loads | HOMER Pro (main) | Add-on Modules | | | | | |
| | | | Advanced Load | Biomass | Hydro | Combined Heat and Power | Hydrogen | Advanced Grid |
| | | | 1 | | | | | |
| | | | S | | | | | |
| | | | V | | | | | |
| | | | 1 | | | | | |
| | | | S | | | | | |
| | | | | | | | | |

| | | | | | | | |
|--|--|----------------|---------|-------|-------------------------|----------|---------------|
| Storage capacity | | S | | | | | |
| Peak | | S | | | | | |
| Minimum load ratio | | S | | | | | |
| Thermal Load | | | | | 2 | | |
| Scaled annual average | | | | | S | | |
| Variability | | | | | V | | |
| Hydrogen Load | | | | | | 1 | |
| Scaled annual average | | | | | | S | |
| Variability | | | | | | V | |
| Penalties for unmet load | | | | | | ✓ | |
| Load inputs | ✓ | | | | | | |
| Easy data entry with typical load profiles | ✓ | | | | Thermal | | |
| Import data | ✓ | | | | Thermal | | |
| Read from library | ✓ | | | | Thermal | | |
| Build from measured data | ✓ | | | | Thermal | | |
| | | | | | | | |
| Resources | HOMER Pro (main) | Add-on Modules | | | | | |
| | | Advanced Load | Biomass | Hydro | Combined Heat and Power | Hydrogen | Advanced Grid |
| Fuels | Diesel, ethanol, methanol, natural gas, biogas, gasoline, propane, biodiesel, hydrogen | | | | | | |
| Fuel price | S | | | | | | |
| Solar GHI | Download from Internet | | | | | | |

| | | | | | | | |
|-----------------------|------------------|----------------|-----------------|-----------------|-------------------------|----------|---------------|
| | or import | | | | | | |
| Scaled annual average | S | | | | | | |
| Solar DNI | Import | | | | | | |
| Scaled annual average | S | | | | | | |
| Wind | Import or enter | | | | | | |
| Scaled annual average | S | | | | | | |
| Surface roughness | S | | | | | | |
| Temperature | Import or enter | | | | | | |
| Scaled annual average | S | | | | | | |
| Biomass | | | Import or enter | | | | |
| Scaled annual average | | | S | | | | |
| Average price | | | S | | | | |
| Carbon content | | | S | | | | |
| Gasification ratio | | | S | | | | |
| Lower heating value | | | S | | | | |
| Hydro | | | | Import or enter | | | |
| Scaled annual average | | | | S | | | |
| Hydrokinetic | Import or enter | | | | | | |
| Scaled annual average | S | | | | | | |
| System Control | HOMER Pro (main) | Add-on Modules | | | | | |
| | | Advanced Load | Biomass | Hydro | Combined Heat and Power | Hydrogen | Advanced Grid |
| Time step size | 1 to 60 minutes | | | | | | |

| | | | | | | | |
|--|------------------|----------------|---------|-------|-------------------------|----------|---------------|
| Fuel minimization option | ✓ | | | | | | |
| Weight minimization option | ✓ | | | | | | |
| Dispatch strategies | 2 | | | | | | |
| Results | HOMER Pro (main) | Add-on Modules | | | | | |
| | | Advanced Load | Biomass | Hydro | Combined Heat and Power | Hydrogen | Advanced Grid |
| Results tables | ✓ | | | | | | |
| Sensitivity table | ✓ | | | | | | |
| Graphic display of sensitivity results | ✓ | | | | | | |
| Optimization table | ✓ | | | | | | |
| Sort results on any metric | ✓ | | | | | | |
| Filter results on any metric | ✓ | | | | | | |
| Choose results to display | ✓ | | | | | | |
| Cost summary | ✓ | | | | | | |
| Comparative economics for IRR and ROI | ✓ | | | | | | |
| Cash flow - General electrical outputs | ✓ | | | | | | |
| Outputs for each component | ✓ | | | | | | |
| Summary report and export | ✓ | | | | | | |
| Time series plot, scatter plot, delta plot, table, time series data export | ✓ | | | | | | |

| | | | | | | | |
|---------------------------------|------------------|----------------|---------|-------|-------------------------|----------|---------------|
| Emissions | ✓ | | | | | | |
| Results recycling | ✓ | | | | | | |
| Economics sensitivity variables | HOMER Pro (main) | Add-on Modules | | | | | |
| | | Advanced Load | Biomass | Hydro | Combined Heat and Power | Hydrogen | Advanced Grid |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| Emissions | HOMER Pro (main) | Add-on Modules | | | | | |
| | | Advanced Load | Biomass | Hydro | Combined Heat and Power | Hydrogen | Advanced Grid |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| Constraints | HOMER Pro (main) | Add-on Modules | | | | | |
| | | Advanced Load | Biomass | Hydro | Combined Heat and Power | Hydrogen | Advanced Grid |
| | | | | | | | |

| | | | | | | | |
|--|---|--|--|--|--|--|--|
| Minimum renewable fraction (%) | ✓ | | | | | | |
| Operating reserve (as % of: current load, peak, solar, wind) | ✓ | | | | | | |

S – Sensitivity variable
V – Single value user-defined variable

[Download a PDF of this table](#) 

You are just 3 steps away

1. Install HOMER Pro
2. Get a Trial License
3. Use right away



Follow on
Twitter
[@homerenergy](#)



HOMER Energy LLC is the world's leading microgrid modeling software company. The HOMER (Hybrid Optimization of Multiple Energy


Top Content



[Lilienthal](#)

Microgrid Value Propositions
123 Jan 2012 | [by Peter](#)

Get in touch

 HOMER Energy
1790 30th St, Suite 100
Boulder, CO 80301 USA

Resources) software navigates the complexities of building cost effective and reliable microgrids that combine traditionally generated and renewable power, storage, and load management. With over 100,000 users in 193 countries, HOMER is the established global leader for microgrid design optimization and feasibility, and HOMER Energy is a nexus for the microgrid market.



Classifying Microgrids
2 Apr 2013 | [by Peter Lilienthal](#)



100% Renewable Energy Challenges
24 Apr 2013 | [by Peter Lilienthal](#)



+(1) 720-565-4046



info@homerenergy.com