Tune Studio

A mono audio tone melody editor software for Windows. Compose your own tone melody, save, playback and output to C/C++ header format.

Revision 1.0.2

by Ricky Gai



MAY 22, 2021

Nexuz Innovation, Malaysia. (MA0255412-M)

Introduction

About this Book

This is a book about the hands-on information of the Tune Studio software for Microsoft Windows.

In the learning Arduino platform especially to the tone melody creation, you need a tone editor to allow you to compose own melody and play it on the physical 8Ω 2W speaker, active and passive buzzer.

You cannot just rely on downloaded third party notes or melodies because it may subject to copyright limitation upon product commercializing later.

Therefore, Tone Studio software is created to allow you to compose tone melody, save it, playback and output to C/C++ header format that can be used as part of Arduino sketch compilation.

Tone Studio is a proprietary software, it is not perfect but you can create, commercialize own composed tone melodies or musics at royalty free and it costs just a cup of coffee :o)

You may get Tone Studio from Microsoft Store.

All the necessary help documentations and tutorial videos are available via Github at: https://github.com/rickygai/tonestudio

For any errors found, suggestions and questions, please do email to: support@nexuzinnovation.com

About the Author

Ricky Gai

The founder and technical director of Nexuz Innovation, a small R&D IT company established in Kuala Lumpur, Malaysia.

He earned a distinction of Oxford Computer Engineering certification discipline in 1992 and mostly exposed to C/C++ programming in his career from the earlier days of MS-DOS until Microsoft Windows environment today.

Nonetheless, much time had been devoted to the electronics studies further before entering into the world of Arduino because the understanding of analog, digital electronics and PCB design are so important to build a stable circuitry beside software programming alone merely.

Thank you for supporting Tone Studio software, I hope you find something useful here.

DISCLAIMER

Abbrevation	Descriptions
NEXUZ INNOVATION / AUTHOR	refers to the author, Ricky Gai.
READER / READER(S) / READER'S	refers to the person who read or experimented the information from the contents of this book.
COMPONENTS / EQUIPMENTS	refers to electronics components, tools, materials that used as part of the circuitry setup.
CONTENTS	Information described in this book, including software source code and hardware circuit designs.
SOFTWARE / PROGRAM / SKETCH	refers to software created by the author.
IP / INTELLECTUAL PROPERTY / COPYRIGHT / PERMISSION	refers to the copyrighted materials (eg. Photo, Diagram, Source Code, Links) that owned by other creators.

The information contained in this book is intended for general reference purposes only and may share portion of extracted information from other resources as part of the illustration usage. Any copyright infringement, please do contact the author to exclude from this book.

While the author endeavour to keep the information up to date and correct, the specification, quality and availability of electronics components may change in time, therefore the author make no representations or warranties of any kind, express or implied, about the completeness, accuracy, reliability, suitability or availability with respect to the information, vendors, products, services, or related graphics contained in the book for any purpose.

Any reliance you place on such information is therefore strictly at your own risk.

In no event will the author be liable for any loss or damage including without limitation, indirect or consequential loss or damage, or any loss or damage whatsoever arising from loss of data or profits arising out of, or in connection with, the use of information derived from this book and the software.

Prerequisition

Tone Studio - Setup

Software & Hardware requirements

Below were the basic requirements to run the Tone Studio software.

Software Requirements:

Microsoft Windows x86/x64


min version: 10.0.17763.0 max version: 10.0.19041.0

- Windows Store.
- .NET framework v4.7.2 or above.
- Tone Studio software.

Hardware Requirements:


- Intel PC i3, i5, i7 or above.
- 2-4 GB RAM.
- 1-2MB Harddisk space.
- Intel/Nvidia standard graphics card.
- Built-in motherboard sound card (eg. Realtek) or built-in internal PC speaker.
- Direct audio jack cable connected to sound card speakers.
- None direct audio jack connected speaker is not supported. eg. USB speakers, Bluetooth speakers are not supported.

The Overview of Tone Studio control functions.




Operating Guidelines

How to play a tone?




The ASPN chords or notes control panel

How to compose a tone melody?




The Melody control panel

How to adjust the tone duration?




How to save the composed melody?




Page

8


How to open the saved melody files?



How to delete or remove unwanted melody files?



The Tone Property (Duration) control panel



The Messages Display Panel

Diagrams	Descriptions & References
Messages The melody file [C:\ToneStudio\melody\My Melody.mex.h] saved OK.	28. The messages display panel is to display the Tone Studio software internal process result as shown on the Figure? where the new file "My Melody" is saved as "My Melody.mex.h" in this case.
Figure 17: The Message Display Panel.	29. DONE.

TONE STUDIO rev 1.0.2 Page 12

Programming Guidelines

How to compile Tone Studio generated melody header?

```
Tone Studio C/C++ melody header demo source - tone.ino
                                                                                   Descriptions & References
#include "pitch.h"
                                                                      The Tone Studio software sample source code
#include "The Twillight Zone.mex.h"
                                                                      tone.ino is available at GitHub.
                                                                      Here, we use Arduino IDE to compile with the
#define melody The_Twillight_Zone
                                                                      melody header such as:
const int max = sizeof( melody ) / sizeof( _MELODYEX );
int n {};
                                                                      The Twillight Zone.mex.h
char buf[100]{};
                                                                      Source code on the left is the simplified version for
void setup()
                                                                      easy understanding.
                                                                      The function is to playback the tone melody
                                                                      "The_Twillight_Zone" through out the Arduino
                                                                      Nano pin 5,6,9 from the floowing sequence
const int speaker = 5;
const int active_buzzer = 6;
                                                                      repeatedly:
const int passive_buzzer = 9;
                                                                      8\Omega 2W speaker -> Active Buzzer -> Passive Buzzer
int pin {};
int cnt{};
int spk {-1};
void loop()
  unsigned int frequency {};
  unsigned long duration {};
  if( spk + 1 < 3 )
    spk++;
  else
    spk = 0;
  switch(spk)
  case 0: // 8 ohm speaker
     pin = speaker;
     break;
  case 1: // active buzzer
                                                                       Figure 18: The Tone Studio Arduino tone project.
     pin = active_buzzer;
     break;
                                                                      The file "pitch.h" contains the followings:
  case 2:
                                                                      typedef struct
     pin = passive_buzzer;
                                                                         float frequency;
                                                                         int duration;
  for( n=0; n<max; n++ )
                                                                      _MELODY;
     frequency = (unsigned int)melody[n].frequency;
     duration = (unsigned long)melody[n].duration;
                                                                      typedef struct
     tone( pin, frequency );
                                                                         char chord[5];
     delay( duration );
                                                                         float frequency;
     noTone( pin );
                                                                         int duration;
                                                                      _MELODYEX;
  delay( 3000 );
                                                                      To save memory without chord string, you may use
                                                                      _MELODY but for display or debug purpose, we use
                                                                      _MELODYEX to show the chord string.
                                                                      Thus, "The Twillight Zone.mex.h" was adopted
                                                                      in this section.
```