P vs NP in Curvature-Bounded Wave Computation
A Model-Relative Separation Program and Corrected Proof Obligations

Richard J. Reyes

Revised October 27, 2026
Original Release: May 7, 2025

Abstract

We study curvature-regulated wave computation (WCC) as a possible physical resource model for decision and verification problems. We distinguish the *uniform discrete* finite-state WCC abstraction from WCT implementations additionally constrained by curvature, field regularity, precision, and physical energy rails. Under polynomial-time uniform encodings and readouts, the discrete WCC model simulates and is simulated by classical Turing machines with polynomial overhead, as developed separately in *Discrete Wave-Constrained Computation and Classical Complexity*. This equivalence alone proves no equivalence of physical curvature costs.

We correct the Boolean phase encoding of 3-SAT: a signed literal score and a product-of-unsatisfied-literals clause penalty give an exact zero-penalty characterization of SAT assignments. This is a logical encoding theorem, not a proof that a satisfying assignment is a stationary point of the full WCT functional. We also exhibit a smooth finite-energy four-dimensional field, refuting an earlier inference from failure of a Sobolev embedding to universal infinite curvature energy.

The proposed locked-expander curvature lower bound $C_\Theta(F_n) \geq 2^{\Omega(n)}$ is stated as a *conditional research hypothesis*: expansion alone

does not establish an exponential area lower bound for every physical encoding, and a cost of enumerating clause-signature sectors does not bound all decision algorithms. A conditional separation of physical WCC classes would require a genuine language-level lower bound against every admissible deterministic decider, along with a physically admissible polynomial-resource verifier. The classical **P** versus **NP** problem is not resolved.

This revision records explicit mathematical counterexamples and precise remaining obligations under tags `WIN-01`–`WIN-08`.

Formal verification status (November 2, 2026). The frozen one-dimensional, radius-one, finite-alphabet symbolic WCC model has kernel-checked theorems for $P^{\mathrm{disc}}_{\mathrm{WCC}} = P_{\mathrm{TM}}$ and $NP^{\mathrm{disc}}_{\mathrm{WCC}} = NP_{\mathrm{TM}}$ in `PVNP.Discrete`. These are theorems for that model, not physical curvature-preserving implementations. A fixed, language-independent sign encoding of 2^n possible inputs in n real coordinates has squared amplitude mass n and is stable under per-coordinate noise of absolute value less than one. An unrestricted output decoder can then apply any predicate. Thus storage capacity, encoding efficiency and label count alone cannot prove a decision-time lower bound; decoder computability, runtime, precision and uniformity must also be charged. The all-algorithm physical curvature lower bound and any physical or classical P versus NP separation remain unproved.

1 Introduction

The **P** vs. **NP** problem asks whether every computational problem whose solution can be verified in polynomial time can also be solved in polynomial time. Despite decades of effort, no proof resolving $\mathbf{P} \stackrel{?}{=} \mathbf{NP}$ has been universally accepted. The present work does not claim to resolve this classical question; instead, it develops a curvature-regulated model of computation and isolates the hypotheses necessary for a model-relative lower bound and an internal separation program.

We work within Wave Confinement Theory (WCT), where computation is defined as the physical or symbolic evolution of confined oscillatory systems under curvature feedback. In this setting, stable coherent wave states play the role of solutions, and the feasibility of reaching them under bounded evolution defines a notion of computational difficulty.

We introduce a discrete curvature-regulated computation model (WCC) and define complexity classes $\mathbf{P}_{\mathrm{WCC}}$ and $\mathbf{NP}_{\mathrm{WCC}}$ by imposing polynomial bounds on evolution time and curvature/entropy budgets. Within this model we pursue two complementary tracks:

- **Analytic curvature lower bound.** We define a semantic curvature complexity measure $\mathbf{C}_\Theta(f)$ based on the WCT curvature operator and show that, for a locked expander family of 3-SAT instances inside the WCT curvature machine, an exponential cost has been proposed, $\mathbf{C}_\Theta(F_n) \geq 2^{\Omega(n)}$. The interface-energy and universal-encoding hypotheses required for this bound are not established here. It remains an open mathematical objective, not a proved lower bound.

- **Symbolic complexity and separation program.** We construct a verifier for wave-coherence predicates in NC^1, encode SAT instances as symbolic wave-interference constraints (a Cook–Levin style reduction into WCC), and formalize WCC-level complexity classes $\mathbf{P}_{\mathrm{WCC}}$ and $\mathbf{NP}_{\mathrm{WCC}}$. We then formulate a *model-internal separation program*: under explicit geometric and dynamical hypotheses (existence of curvature-locked states that are verifiable but not reachable within polynomially many curvature-bounded WCC updates), one would obtain an internal separation $\mathbf{P}_{\mathrm{WCC}} \neq \mathbf{NP}_{\mathrm{WCC}}$. In this manuscript these hypotheses are stated as conjectures rather than claimed theorems.

Finally, we outline a conditional bridge to classical complexity. If WCC computations and deterministic Turing computations simulate each other with only polynomial overhead, then the WCC classes would satisfy $\mathbf{P}_{\mathrm{WCC}} = \mathbf{P}$ and $\mathbf{NP}_{\mathrm{WCC}} = \mathbf{NP}$. Under this *TM–WCC compatibility conjecture*, any internal separation $\mathbf{P}_{\mathrm{WCC}} \neq \mathbf{NP}_{\mathrm{WCC}}$, combined with the curvature lower bound described above, would imply the classical separation $\mathbf{P} \neq \mathbf{NP}$. The specified frozen one-dimensional radius-one discrete model has a kernel-checked polynomial-time TM/WCC equivalence. Its physical curvature-preserving realization and any internal physical separation are unproved. We focus on the exact logical encoding and explicit hypotheses needed for a future model-relative analytic curvature lower bound.

Author's Note: On the Geometry of Computation and the Dimensional Lock

This work proposes a new approach to the **P vs. NP** problem, one that is not purely combinatorial or symbolic, but instead *geometric*, *topological*, and *physical*. Computation here is modeled not as an abstract string-manipulation process, but as the evolution of a wavefunction constrained by curvature, entropy, and dimension.

The central mechanism is what I term a **dimensional lock**: in the curvature-regulated model, attempting to force a deterministic, uniformly controlled evolution (the analogue of **P**) to realize certain non-uniform, combinatorially large configurations (the analogue of **NP**) appears to require crossing a geometric barrier that is forbidden by the curvature and dimensionality constraints. At an intuitive level, this structural obstruction prevents uniform computation from accessing the full non-uniform solution space and motivates an internal separation

$$\mathbf{P}_{\mathrm{WCC}} \neq \mathbf{NP}_{\mathrm{WCC}}$$

within the WCC model.

In the body of the paper, this idea is made precise in two steps. First, a semantic curvature complexity measure is introduced and an exponential curvature lower bound is proposed as a conditional goal for locked-expander 3-SAT instances inside the WCT curvature machine. Second, a discrete symbolic abstraction of WCC is developed, together with a verifier and a set of explicit geometric and dynamical hypotheses which, if established, would yield a formal internal separation $\mathbf{P}_{\mathrm{WCC}} \neq \mathbf{NP}_{\mathrm{WCC}}$.

This perspective is simple but nontraditional. It draws from physics and information theory, disciplines not typically employed in classical complexity theory. For that reason, it may appear unfamiliar or even unorthodox to some readers. The claim here is not that a physical metaphor proves a classical complexity result, but that a curvature- and dimension-constrained *symbolic* model admits (i) a precise conditional curvature-bound program for SAT, and (ii) a carefully stated internal separation program.

The extrapolation to the classical statement $\mathbf{P} \neq \mathbf{NP}$ is treated explicitly as conditional. If curvature-regulated WCC machines and standard Turing machines are polynomially equivalent in computational power, then the dimensional lock and curvature bounds described here would provide a route to

the classical separation. That simulation equivalence is isolated as a distinct conjecture rather than assumed silently; this paper does not claim to resolve the classical **P** vs. **NP** problem.

2 Curvature-Confinement Formalism and a Model-Internal Separation

We propose that a confined wavefield $\psi(x,t)$ under curvature feedback evolves toward symbolic configurations that cannot be constructed in polynomial time but can be verified via coherence constraints. Within the rail-constrained WCC abstraction, this creates a natural asymmetry between generation and verification, aligning with a prospective distinction between $\mathbf{P}_{\mathrm{WCC}}^{\mathrm{phys}}$ and $\mathbf{NP}_{\mathrm{WCC}}^{\mathrm{phys}}$, where the superscript phys denotes photonic WCT/WCC machines subject to finite-curvature, finite-band rails (Section 10).

2.1 Definitions

Curvature-Locked State: A wavefield ψ^* is curvature-locked if it satisfies

$$W_\psi = \frac{-\nabla^2\psi}{\psi + \epsilon e^{-\alpha|\psi|^2}}, \quad \text{with } \frac{dS[\psi]}{dt} \to 0 \text{ and } \nabla W_\psi \to 0 \tag{1}$$

under the WCT/WCC evolution rules.

Symbolic Configuration Set $\mathcal{S}$: A set of discrete symbolic regions R_i where

$$\psi(x) \approx \psi_i \quad \forall x \in R_i, \quad R_i \subseteq \mathbb{R}^n$$

implements a finite symbolic configuration (assignment, tape content, etc.) inside the WCC model.

Verification Operator $\mathcal{V}$: A polynomial-time procedure on the WCC encoding which confirms that

$$\mathcal{V}(\psi^*, \mathcal{S}) = \text{True} \iff \psi^* \text{ exhibits symbolic coherence consistent with } \mathcal{S},$$

with an implementation in NC^1 on a classical circuit model.

Non-Constructibility Condition (WCC): A curvature-locked state ψ^* is *non-constructible in* $\mathbf{P}_{\mathrm{WCC}}^{\mathrm{phys}}$ if no deterministic polynomial-time WCC machine $\mathcal{T}_{\mathrm{WCC}}^{\mathrm{phys}}$ (obeying WCT rails) can output ψ^* from a trivial input configuration, while a polynomial-time WCC verification $\mathcal{V}$ remains available.

2.2 Model-Internal Complexity Schema

To isolate the logical shape of the desired separation, we introduce an abstract complexity functional $\mathcal{C}(\psi)$ on WCC states and state the following *schema*.

Proposition 2.1 (Curvature-Confinement Complexity Schema in Physical WCC). Let ψ^* be a curvature-locked solution of a confined resonance field evolved from a trivial initial state within the rail-constrained WCC model. Suppose that:

1. The symbolic configuration space $\mathcal{S}$ representing ψ^* satisfies $\mathcal{C}(\psi^*) > T(n)$ for every polynomial-time achievable bound $T(n)$ on $\mathcal{C}(\cdot)$ over all $\mathcal{O}(n^k)$-time WCC machines obeying WCT rails, and

2. There exists a polynomial-time WCC verification procedure $\mathcal{V}$ that confirms curvature-coherent symbolic structure of ψ^* (e.g. via local curvature and phase-lock checks).

Then ψ^* lies in $\mathbf{NP}^{\text{phys}}_{\text{WCC}} \setminus \mathbf{P}^{\text{phys}}_{\text{WCC}}$, and hence $\mathbf{P}^{\text{phys}}_{\text{WCC}} \neq \mathbf{NP}^{\text{phys}}_{\text{WCC}}$ *inside the physical WCC model*.

This proposition is logically tautological once (1)–(2) are established; the substantive content of the curvature-confinement program is to *exhibit* a family of states ψ^* and a rigorously defined functional $\mathcal{C}(\psi)$ for which (1) holds, e.g. via dimensional-lock and curvature-scaling lemmas (Section 10).

2.3 ψ-SAT Encoding Scheme (WCC Rail)

Let each Boolean clause C_i in a SAT instance be mapped to a spatial clause kernel:

$$\psi(x, 0) = \sum_i \chi_i(x) e^{i\phi_i}, \quad \chi_i(x) \text{ localized curvature excitation}, \tag{2}$$

with a prescribed WCC encoding from symbolic clauses to localized modes.

Under resonance evolution in the WCC rail, clauses are satisfied if corresponding phase regions lock in coherence:

$$\text{SAT-satisfied} \iff \exists x_i : \nabla\phi(x_i) \to 0 \text{ and } |\psi(x_i)|^2 \to \text{local max}.$$

This encoding transforms logical satisfiability into symbolic phase confinement and serves as a Cook–Levin style reduction into a WCC verifier, without yet claiming full NP-completeness of the ψ-SAT construction.

3 Complexity Class Definitions

Definition 3.1 (Class P). **P** is the class of decision problems solvable by a deterministic Turing machine in polynomial time, i.e., there exists a machine M and constant k such that for all inputs x, $M(x)$ halts in $\mathcal{O}(|x|^k)$ steps.

Definition 3.2 (Class NP). **NP** is the class of decision problems for which a proposed solution (certificate) can be verified in polynomial time by a deterministic Turing machine. Formally, $L \in \mathbf{NP}$ if there exists a polynomial-time verifier $V(x, w)$ such that

$$x \in L \iff \exists w : V(x, w) = 1.$$

In the WCC setting we distinguish two model-relative classes:

- $\mathbf{P}^{\text{phys}}_{\text{WCC}}$ and $\mathbf{NP}^{\text{phys}}_{\text{WCC}}$: rail-constrained photonic WCC machines under WCT curvature/energy caps (finite universe band).
- $\mathbf{P}^{\infty}_{\text{WCC}}$ and $\mathbf{NP}^{\infty}_{\text{WCC}}$: ideal discrete WCC machines without global physical caps, suitable for asymptotic Turing-equivalence considerations.

The main model-internal separation conjectures below concern $\mathbf{P}^{\text{phys}}_{\text{WCC}}$ and $\mathbf{NP}^{\text{phys}}_{\text{WCC}}$. Implications for classical **P** vs. **NP** via the ideal classes $\mathbf{P}^{\infty}_{\text{WCC}}, \mathbf{NP}^{\infty}_{\text{WCC}}$ are discussed only as conditional corollaries.

4 Main Model-Relative Separation Statement ($\mathbf{P}^{\text{phys}}_{\text{WCC}} \neq \mathbf{NP}^{\text{phys}}_{\text{WCC}}$)

Conjecture 4.1 (Symbolic Separation Program in Physical WCC). We conjecture that there exist coherent, verifiable wavefields $\psi^* \in \mathbf{NP}^{\text{phys}}_{\text{WCC}}$ that cannot be constructed by any deterministic polynomial-time WCC machine obeying WCT rails. Equivalently, there should exist

$$\psi^* \in \mathbf{NP}^{\text{phys}}_{\text{WCC}} \setminus \mathbf{P}^{\text{phys}}_{\text{WCC}},$$

which would entail the internal separation $\mathbf{P}^{\text{phys}}_{\text{WCC}} \neq \mathbf{NP}^{\text{phys}}_{\text{WCC}}$ within the rail-constrained WCC model. We refer to this as the *model-internal separation conjecture*.

Heuristic Rationale (Model Level). At a high level, the WCC program proceeds as follows. We construct a WCC-level verifier $A(q) \in \text{NC}^1$ for curvature-locked configurations, encode SAT clauses into symbolic curvature-locked constraints, and aim to establish that:

- Some wavefields ψ^* satisfy $A(q^*) = 1$ (i.e., they are verifiable by a polynomial-time WCC process);
- No deterministic polynomial-time WCC machine can construct ψ^* from a trivial initial state ψ_0 under the curvature-regulated symbolic update rules while remaining within WCT rails, due to curvature/entropy barriers such as dimensional lock.

If such non-constructible but verifiable states can be rigorously exhibited, this would yield $\psi^* \in \mathbf{NP}^{\text{phys}}_{\text{WCC}} \setminus \mathbf{P}^{\text{phys}}_{\text{WCC}}$ and hence $\mathbf{P}^{\text{phys}}_{\text{WCC}} \neq \mathbf{NP}^{\text{phys}}_{\text{WCC}}$ at the model level. Turning this heuristic into a complete proof requires formalizing and proving the relevant curvature-scaling and dimensional-lock lemmas (Section 10); these barriers are isolated below as explicit conjectures and open problems rather than assumed as settled facts.

4.1 ψ-SAT Encoding and Symbolic Map

We formally define the symbolic encoding from a Boolean SAT instance into curvature-locked wave states. Let a Boolean clause $C_i \in \text{SAT}$ be

$$C_i = (x_1 \vee \neg x_2 \vee x_3).$$

We map each clause C_i directly into a wave symbol region $R_i \subseteq \mathbb{R}^n$:

$$C_i \mapsto \psi_i(x) = A_i e^{i\phi_i(x)}, \quad x \in R_i,$$

where A_i is a localized amplitude distribution enforcing clause locality and $\phi_i(x)$ encodes logical states (True/False) in terms of constructive or destructive interference.

We construct the global wavefield as a coherent superposition of all clause wavefunctions:

$$\psi(x) = \sum_i \psi_i(x).$$

Logical satisfiability is then tied to curvature-locked coherence through a phase-locking condition:

$$\text{SAT-satisfied} \iff \exists x_i : \nabla\phi(x_i) \to 0, \quad |\psi(x_i)|^2 \to \max.$$

This encoding provides a direct ψ-based analog to the Cook–Levin construction, reducing SAT instances into symbolic curvature-locked wave states within the WCC framework, again without claiming a completed, classical NP-completeness proof for ψ-SAT at this stage.

4.2 Model-Internal Symbolic Separation

Theorem 4.2 (Conditional Symbolic Separation in Physical WCC). Let ψ^* be a curvature-locked wavefield constructed from a symbolic SAT instance via the WCC encoding described above. Suppose that:

1. The verification operator satisfies $V_{\text{WCC}}(\psi^*) \in \text{NC}^1$, and hence verifies ψ^* in polynomial time on a rail-constrained WCC machine, i.e. $\psi^* \in \mathbf{NP}^{\text{phys}}_{\text{WCC}}$.

2. No deterministic polynomial-time WCC machine $M^{\text{phys}}_{\text{WCC}} \in \mathbf{P}^{\text{phys}}_{\text{WCC}}$ can construct ψ^* from an initial trivial state ψ_0 while respecting WCT curvature/energy rails.

Then

$$\psi^* \in \mathbf{NP}^{\text{phys}}_{\text{WCC}} \setminus \mathbf{P}^{\text{phys}}_{\text{WCC}}, \quad \text{and therefore} \quad \mathbf{P}^{\text{phys}}_{\text{WCC}} \neq \mathbf{NP}^{\text{phys}}_{\text{WCC}}$$

within the physical WCC model.

Proof Sketch. Assume for contradiction that $\psi^* \in \mathbf{P}^{\text{phys}}_{\text{WCC}}$. Then by definition there is a polynomial-time rail-constrained WCC machine that constructs ψ^* from ψ_0 under curvature-regulated symbolic evolution. Hypothesis (2) rules this out by asserting non-constructibility in polynomial WCC time under the same rails. Thus $\psi^* \notin \mathbf{P}^{\text{phys}}_{\text{WCC}}$ while remaining verifiable in $\mathbf{NP}^{\text{phys}}_{\text{WCC}}$ by (1), so $\psi^* \in \mathbf{NP}^{\text{phys}}_{\text{WCC}} \setminus \mathbf{P}^{\text{phys}}_{\text{WCC}}$ and the separation follows. The substantive content is entirely in hypothesis (2): making this theorem nontrivial requires proving such a non-constructibility statement (for example via dimensional-lock and curvature-scaling lemmas), which is exactly the open geometric barrier isolated in Section 10.

4.3 Symbolic Turing Abstraction and Conditional Classical Corollary

In an *ideal* discrete WCC model (ignoring global WCT caps), we encode each $\psi[i, j] = a + ib \in \mathbb{C}$ as a binary string on a Turing tape.

Encoding: Each cell amplitude $\psi[i, j]$ is represented by a finite-precision binary code on one or more Turing tapes.

Evolution: Polynomial-time ideal WCC updates are simulated by a deterministic Turing machine using local symbolic gates that implement the curvature-regulated transition rules, defining classes $\mathbf{P}^{\infty}_{\text{WCC}}, \mathbf{NP}^{\infty}_{\text{WCC}}$.

Verifier: The WCC verifier is compiled into a Boolean circuit in NC^1 and simulated by a polynomial-time Turing machine, showing that WCC-verifiable states in the ideal model correspond to languages in **NP** under this abstraction.

4.4 Formal Completion (Cook–Levin Consistency and Conjectural Bridge)

Within the WCC framework we therefore have:

- At the *physical* level, all WCC-encoded NP-type languages we consider reduce to symbolic WCT-verifier circuits on rail-constrained photonic devices, and the key non-reachability statements are *postulated* via the dimensional-lock hypothesis (curvature-based nonconstructibility).

- At the *ideal* discrete level, one may conjecture a Turing-equivalent

model where ideal WCC machines and classical Turing machines simulate each other with polynomial overhead.

Conditional Classical Corollary. If, in addition, (i) every polynomial-time Turing machine can be simulated by a polynomial-time *ideal* WCC machine (TM $\Rightarrow$ WCC$^\infty$ with polynomial overhead) and (ii) every polynomial-time ideal WCC machine can be simulated by a polynomial-time Turing machine (WCC$^\infty$ $\Rightarrow$ TM with polynomial overhead), then

$$\mathbf{P}^\infty_{\mathrm{WCC}} = \mathbf{P}, \quad \mathbf{NP}^\infty_{\mathrm{WCC}} = \mathbf{NP}.$$

Any eventual internal separation $\mathbf{P}^\infty_{\mathrm{WCC}} \neq \mathbf{NP}^\infty_{\mathrm{WCC}}$, established by strengthening the geometric barrier program to the ideal model, would then imply the classical separation $\mathbf{P} \neq \mathbf{NP}$.

The present work *does not* claim either the internal separation in the ideal model or the TM$\leftrightarrow$ WCC$^\infty$ simulation equivalence as proved. Instead, it isolates the rail-constrained WCC separation as a conjectural program in the physical model and identifies ideal TM$\leftrightarrow$ WCC$^\infty$ simulation as an explicit bridge hypothesis and target for future work.

5 Internal Complexity Structure of WCC

We present the internal complexity hierarchy of the Wave Curvature Computation (WCC) model. All results in this section are strictly model-internal and do not concern classical Turing complexity.

5.1 Preliminaries

Let $\Lambda \subset \mathbb{Z}^d$ be a finite lattice with $d = 2$ or $d = 3$. A WCC configuration is a field

$$\psi : \Lambda \to \mathbb{C}.$$

The curvature functional is

$$E[\psi] = \sum_{i \in \Lambda} \left(|\nabla \psi(i)|^2 + |\Theta[\psi(i)]|^2 + V_F(\psi(i)) \right), \tag{3}$$

where

$$\Theta[\psi] = -\frac{\Delta \psi}{\psi + \epsilon e^{-\alpha |\psi|^2}}$$

and V_F encodes logical constraints.

A WCC evolution is any sequence $\psi_0, \psi_1, \psi_2, \ldots$ obeying r-local update rules and satisfying

$$E[\psi_t] < \infty \quad \forall t.$$

5.2 Definition of PWCC and NPWCC

Definition 5.1 (PWCC). The class **PWCC** consists of all decision problems solvable by a WCC evolution in $\mathrm{poly}(n)$ update steps, where n is the instance size, with the additional constraints:

$$E[\psi_t] < \infty, \qquad \dim_{\text{eff}}(\psi_t) \leq 3 \quad \text{for all } t.$$

Here $\dim_{\text{eff}}$ denotes the effective geometric embedding dimension (Definition 5.4).

Definition 5.2 (NPWCC). The class **NPWCC** consists of all decision problems F for which there exists a configuration ψ satisfying all constraints (i.e. $E_{\text{logic}}[\psi] = 0$), and for which such ψ can be verified in $\mathrm{poly}(n)$ time by a WCC evolution.

5.3 ψ-SAT Encoding

WIN-01 and WIN-02 (corrected). Let $F = \bigwedge_{j=1}^{m} C_j$ be a 3-CNF formula on Boolean variables $x_1, \ldots, x_n$. On each variable region, use a nonzero field with encoded phase $\theta_i \in \{0, \pi\}$ and set

$$x_i = 1 \iff \theta_i = 0, \qquad x_i = 0 \iff \theta_i = \pi.$$

For a literal ℓ, write $v(\ell)$ for its variable index and set $\eta_\ell = +1$ for $x_{v(\ell)}$ and $\eta_\ell = -1$ for $\neg x_{v(\ell)}$. Define its truth score by

$$s(\ell; \psi) := \frac{1 + \eta_\ell \cos \theta_{v(\ell)}}{2}.$$

For Boolean phases the score is exactly 1 when the literal is true, and exactly 0 when it is false. For a clause $C_j = (\ell_{j1} \vee \ell_{j2} \vee \ell_{j3})$ define

$$V_j(\psi) := \prod_{k=1}^{3} \big(1 - s(\ell_{jk}; \psi)\big), \qquad E_{\text{logic}}[\psi] := \sum_{j=1}^{m} V_j(\psi).$$

The product, rather than a sum of unsatisfied literals, encodes the Boolean *OR* relation. The energy is nonnegative on all nonzero phase encodings; no division by a vanishing field amplitude is used.

5.4 ψ-SAT Logical Completeness (Corrected)

Theorem 5.3 (Exact logical zero-penalty characterization). For every 3-CNF formula F, the following are equivalent:

1. F has a satisfying Boolean assignment.
2. There exists a binary-phase configuration ψ with $E_{\text{logic}}[\psi] = 0$.

The same existential equivalence holds if arbitrary phases are permitted and all variable amplitudes remain nonzero. Neither equivalence asserts stationarity of the *full* WCT energy functional.

Proof. If F is satisfiable, give each variable phase 0 for true and π for false. In every clause some literal has score 1, and therefore every V_j vanishes. Conversely, all V_j are nonnegative, so $E_{\text{logic}} = 0$ implies that every clause has at least one literal with score 1. Since $s(\ell) = 1$ forces the corresponding phase

to be exactly 0 or π with the appropriate sign, these literal truth requirements are mutually consistent across clauses. Complete any remaining unspecified Boolean variables arbitrarily. The resulting assignment satisfies F. □

Remark (WIN-03: stationarity is a separate obligation). The implication $E_{\text{logic}}[\psi] = 0 \Rightarrow \delta(E_{\text{geom}} + \lambda E_{\text{logic}})[\psi] = 0$ is invalid without conditions on the geometric first variation, boundary data, and admissible function space. A zero of a nonnegative logical penalty need not be stationary for an independently varying geometric energy. Existence of a full PDE equilibrium realizing an assignment is therefore an open problem here.

5.5 Effective Dimension

Definition 5.4 (Effective Dimension). For a specified admissible representation class, let

$$\dim_{\text{eff}}(\psi) := \min\{k \in \mathbb{N} : \psi \text{ admits the prescribed curvature-regular encoding in } \mathbb{Z}^k\},$$

when the set is nonempty. Any dimension-dependent obstruction must also specify the encoding and ambient function spaces.

5.6 The Dimensional-Lock Claim Requires Additional Hypotheses

Proposition 5.5 (WIN-04: failure of Sobolev embedding is not infinite energy). For $d = 4$, there exist nonzero smooth localized fields with finite $\|\nabla\psi\|_{L^2}^2$ and finite corrected regularized curvature energy $\|\Theta_\varepsilon[\psi]\|_{L^2}^2$, where

$$\Theta_\varepsilon[\psi] = -\frac{\Delta\psi\,\overline{\psi}}{|\psi|^2 + \varepsilon e^{-\alpha|\psi|^2}}, \qquad \varepsilon > 0, \quad \alpha \geq 0.$$

Consequently the failure of an $H^1 \hookrightarrow L^\infty$ embedding for $d > 3$ does not prove that every higher-dimensional configuration has infinite WCT curvature energy.

Proof. Take $\psi(x) = e^{-|x|^2}$ on $\mathbb{R}^4$. Then $\nabla\psi = -2xe^{-|x|^2}$ and $\Delta\psi = (4|x|^2 - 8)e^{-|x|^2}$, both square-integrable. For this real positive field, the denominator is positive and $|\overline{\psi}|/(|\psi|^2 + \varepsilon e^{-\alpha|\psi|^2})$ is globally bounded: near infinity its numerator tends to zero while the denominator tends to ε, and on compact intervals of amplitudes it is continuous. Thus $\Theta_\varepsilon[\psi] \in L^2(\mathbb{R}^4)$. □

Remark. This does not prove stability or existence of physically confined four-dimensional solitons. It invalidates the claimed *universal infinite-energy deduction*; a dimensional obstruction requires a separate theorem specifying its PDE, admissible states, and rails.

5.7 Internal Separation: Conditional Language-Level Statement

Proposition 5.6 (WIN-05: conditional physical-WCC separation). Fix the same physical encoding, resource bounds, uniformity conditions, and language definition for both $\mathbf{P}^{\mathrm{phys}}_{\mathrm{WCC}}$ and $\mathbf{NP}^{\mathrm{phys}}_{\mathrm{WCC}}$. If some language L has a polynomial-resource physical WCC verifier with polynomial-size witnesses, but every physically admissible *deterministic decider* for L exceeds at least one polynomial resource rail infinitely often, then

$$\mathbf{P}^{\mathrm{phys}}_{\mathrm{WCC}} \neq \mathbf{NP}^{\mathrm{phys}}_{\mathrm{WCC}}.$$

This proposition is conditional; the requisite universal lower bound is not proved here.

Proof. The verifier hypothesis gives $L \in \mathbf{NP}^{\mathrm{phys}}_{\mathrm{WCC}}$. The lower-bound hypothesis gives $L \notin \mathbf{P}^{\mathrm{phys}}_{\mathrm{WCC}}$. Both refer to the same language and physical resource accounting, so the classes differ. □

6 Curvature collapse and loss of grammatical structure

In this subsection we formalize the heuristic statement that when the WCT curvature rails are violated, the distinction between computational states collapses and the induced language model degenerates to noise. In particular, the existence of a nontrivial computational rule requires a curvature-regular regime.

Recall that for a configuration ψ we write $C_\Theta(\psi)$ for the global curvature budget (for example $C_\Theta \sim E_{\mathrm{grad}} + E_{\mathrm{fb}}$) and $\overline{C}_\Theta(\psi)$ for the average curvature per site. The WCC rails partition the evolution into regimes (PWCC, NPWCC, OUT_OF_WCC) via bounds on $(\mathrm{steps}, \mathrm{cells}, \overline{C}_\Theta)$.

Definition 6.1 (Curvature-regular and curvature-collapsed regimes). Let ψ be a WCT configuration on a finite lattice Λ and let $\overline{C}_\Theta(\psi)$ be its average curvature budget per site.

- We say that ψ is *curvature-regular* if

$$\overline{C}_\Theta(\psi) \leq C_{\mathrm{reg}}$$

  for some fixed model-relative threshold $C_{\mathrm{reg}} > 0$ compatible with the PWCC rail. In this regime the WCC update rule induces a finite alphabet S of metastable states and a well defined local transition map $U \colon S^{N_r} \to S$.

- We say that ψ is *curvature-collapsed* if

$$\overline{C}_\Theta(\psi) \geq C_{\mathrm{coll}}$$

  for some threshold $C_{\mathrm{coll}} \gg C_{\mathrm{reg}}$ above the quantum classical crossover bound and outside all WCC rails. In this regime curvature feedback and entropy dominate and no metastable state partition is stable under evolution.

In the curvature-regular regime the induced symbolic dynamics admits a natural language model in the sense of Chomsky's hierarchy.

Definition 6.2 (Induced grammar of a curvature-regular configuration). Let ψ be curvature-regular in the sense of Definition 6.1 with associated finite state set S and local update rule U. Fix an encoding of space-time cylinders into words over a finite alphabet Σ.

The *induced grammar* $\mathcal{G}_\psi$ is any grammar (for example, finite state, context free, or context sensitive) that generates exactly the set of words corresponding to valid WCC space-time trajectories compatible with (S, U) and the WCC rails. The associated language $L(\psi)$ is the set of all such words.

Thus in the curvature-regular regime the pair (ψ, U) determines a nontrivial language $L(\psi)$ lying somewhere in Chomsky's hierarchy (for example regular, context free, or recursively enumerable).

When curvature rails are violated the situation changes qualitatively.

Proposition 6.3 (Curvature collapse destroys grammatical structure). Let $(\psi_t)_{t \geq 0}$ be a WCT evolution driven by a curvature feedback operator $\Theta[\psi]$

and suppose there exists t_* such that ψ_{t_*} is curvature-collapsed in the sense of Definition 6.1. Assume moreover that beyond t_* the evolution remains outside all WCC rails.

Then the following hold.

1. There is no finite partition of the state space into metastable symbols S that is invariant under the evolution for $t \geq t_*$. Any such partition experiences state mixing on a time scale that is short relative to the curvature drift.

2. Consequently, there is no nontrivial induced grammar $\mathcal{G}_\psi$ and the associated language $L(\psi)$ degenerates to one of the following trivial cases:

$$L(\psi) \in \{\emptyset,\ \Sigma^*\},$$

   up to sets of measure zero in the space of trajectories. In particular, the Chomsky hierarchy of nontrivial language classes ceases to describe the dynamics.

3. No amount of post hoc classical computation on the resulting noise-dominated trajectories can recover a unique symbolic rule U that is compatible with a curvature-regular WCC model. The information required to distinguish such a rule has been erased by curvature collapse.

Remark (Curvature, infinite compute, and rule identifiability). Proposition 6.3 formalizes the heuristic statement that *computation is a low curvature phenomenon*. Within the PWCC rail the induced WCC machine has a well defined local rule and its polynomial time class coincides with the classical class P_{Turing}:

$$P_{\text{WCC}} = P_{\text{Turing}}.$$

Outside the rails, when $\overline{C}_\Theta(\psi)$ enters the curvature-collapsed regime, state distinctions are destroyed and the evolution becomes effectively noise.

In this sense, even an ideal observer with unbounded classical compute cannot reconstruct a unique underlying rule from the collapsed trajectories, because the geometric substrate that carried the rule (curvature, chirality, and confinement) no longer exists. The limit of "unit cost, infinite compute" does not restore the rule once the WCT curvature structure has been broken.

7 Logical versus physical complexity

In this section we make explicit the distinction between *logical* complexity in the sense of classical Turing machines and *physical* complexity in the sense of the WCT curvature model. The central slogan is:

> *In Hilbert's universe (pure logic), computation is free. In the physical universe, computation is never free.*

7.1 The abstract Turing model: "logic is free"

We recall the classical setting. A (deterministic) Turing machine M is specified by a finite set of states Q, a finite tape alphabet Γ, a transition function

$$\delta : Q \times \Gamma \to Q \times \Gamma \times \{-1, 0, +1\},$$

and a designated start state q_0 and halting states. The *cost* of a computation in this model is defined purely as the number of applications of δ, i.e. the number of *logical steps*.

Definition 7.1 (Free logic axiom). The classical Turing model operates under the implicit *free logic axiom*:

1. Each application of δ has unit cost in the time measure, independent of the physical resources required to realize it.

2. The tape is an unbounded, perfectly stable memory, whose extension and maintenance carry no cost in the complexity measure.

3. There is no penalty in the model for entropy, energy, mass, or curvature associated with storing or transforming symbols.

Under this axiom, we say that *logic is free*: the only resource measured is the number of abstract state transitions.

Within this framework, the classical complexity classes P and NP are defined purely in terms of these free logical steps. For example, P consists of those decision problems decidable by a Turing machine in time bounded by a polynomial in the input length, and NP consists of those problems for which a proposed solution can be verified in polynomial time.

7.2 The WCT model: logic is not free

In the WCT curvature model, information is always realized as structure in a physical field configuration ψ. To store even a single bit requires a metastable distinction between two configurations ψ_0 and ψ_1, and any operation that changes or erases information must be implemented by a physical evolution governed by the curvature functional.

At the thermodynamic level, this is reflected in Landauer's principle: erasing one bit of information at temperature T in a system coupled to a heat bath requires a minimum energy dissipation of

$$E_{\min} = k_B T \ln 2,$$

where k_B is Boltzmann's constant. In particular, each logically irreversible operation carries a nonzero energetic cost.

In the WCT setting, we refine this statement by coupling it to the curvature functional C_Θ introduced earlier (see Section C). Informally, we write

$$C_\Theta(\psi) \;\sim\; E_{\text{grad}}(\psi) + E_{\text{fb}}(\psi)$$

for the relevant curvature budget of a configuration ψ. The precise normalization is not important here; only the fact that logical distinctions are realized as curvature-bearing structures.

Definition 7.2 (Physical logic). A *physical computation* in the WCT model is a trajectory $(\psi_t)_{t\geq 0}$ of field configurations governed by the WCT evolution equations and subject to the WCC rails. The *physical cost* of such a computation is measured not only in time, but also in the accumulated curvature budget,

$$\int_0^T C_\Theta(\psi_t)\, dt,$$

and the associated entropy production. We say that in this model *logic is not free*: every logical transition requires paying a curvature cost and generating entropy.

Thus, whereas Definition 7.1 explicitly ignores energy, curvature, and entropy, Definition 7.2 builds them into the notion of computation.

7.3 Nondeterminism as "knowing before knowing"

Classically, the class NP is defined via nondeterministic Turing machines or via polynomial-time verifiers: a language L lies in NP if there exists

a polynomial-time Turing machine V and a polynomial p such that for all inputs x,

$$x \in L \iff \exists\, w \in \{0,1\}^{\leq p(|x|)} \text{ with } V(x,w) = 1.$$

One often describes this informally by saying that an NP machine can "guess" a witness w and then verify it efficiently.

From the viewpoint of physical logic, this "guessing" step embodies the intuition of *knowing the answer before knowing*: the existence of w is postulated at the logical level without regard to the physical process required to generate it.

In the WCT curvature model, such a free nondeterministic jump is not available. The system must follow a continuous (or at least piecewise-continuous) trajectory in configuration space, constrained by the curvature rails.

Hypothesis 7.1 (Dimensional lock). Let ψ^* denote a target configuration encoding a solution to a given instance of a problem. The *dimensional lock* hypothesis asserts that there is no physically admissible evolution that instantaneously jumps from a generic initial configuration ψ_0 to ψ^* while remaining within the WCC rails. Instead, any transition $\psi_0 \to \psi^*$ must traverse a path in configuration space along which the curvature budget C_Θ is accumulated in a manner consistent with the WCT evolution and the rail constraints.

Under Hypothesis 7.1, the nondeterministic "guessing" step of the classical NP definition is replaced by a *curvature path*: to obtain ψ^* one must physically construct it, paying the corresponding curvature cost.

Remark (Knowing versus not knowing). In the classical setting, one can define P as the class of problems for which there exists a deterministic polynomial-time algorithm (a direct recipe for obtaining answers), and NP as the class of problems for which proposed answers can be verified in polynomial time. The formal equality $P = NP$ would then assert that "not knowing" (search) is in fact equivalent, up to polynomial overhead, to "knowing" (direct computation).

In the WCT curvature model, the distinction between knowing and not knowing is tied to the curvature cost of constructing ψ^* from ψ_0. If the curvature complexity C_Θ required to realize the solution scales superpolynomially (for example, exponentially) with the input size, then the physical transition from "not knowing" to "knowing" carries a prohibitive cost, even if a purely logical verification exists.

In this sense, the WCT model enforces a strict separation between verification and construction at the level of physical resources, even if the classical logical relation between P and NP remains undecided in Hilbert's universe.

7.4 Category error and physical barriers

The discussion above can be summarized as follows.

- In the classical Turing model, the P versus NP problem is posed entirely within the free logic axiom of Definition 7.1. The question "$P = NP$?" is a statement about the existence or non-existence of certain abstract algorithms, independent of their physical realizability.
- In the WCT model, computation is constrained by curvature and entropy. The relevant question is not whether a logical algorithm exists in principle, but whether its realization can remain within the WCC rails without triggering curvature collapse or loss of symbolic structure.
- A hypothetical equality $P = NP$ at the purely logical level would amount to an identification of "knowing" and "not knowing" in Hilbert's universe. The WCT curvature model suggests that, in the physical universe, such an identification is obstructed by curvature complexity: the path from not knowing to knowing has a cost that cannot be erased from the resource accounting.

Thus, the present framework does not resolve the classical P versus NP problem. Rather, it exhibits a *physical barrier*: even if $P = NP$ were true as a statement of pure logic, any algorithm realizing this equality for certain NP-hard problems would require violating the curvature and energy constraints of the WCT model. In this sense, classical "free logic" and physical "curvature-bound logic" inhabit different universes, and the translation between them must account for the cost of the path, not only the existence of the destination.

8 Numerical Illustration of P vs. NP–Type Behaviour in WCT

8.1 Setup and Definitions

Wave Confinement Theory (WCT) models computation as the geometric evolution of a wavefield $\psi(x,t)$ under curvature and entropy feedback. A computational problem is represented by a target coherent wave state ψ^*, and an algorithm corresponds to evolving from a trivial initial state ψ_0 under the Lagrangian dynamics:

$$\mathcal{L}_{\text{WCT}} = |\partial_\mu \psi|^2 + \kappa \left(\frac{\Box \psi}{\psi + \epsilon e^{-\alpha |\psi|^2}} \right)^2 + \theta \left(\frac{\nabla^2 \psi}{\psi + \epsilon e^{-\alpha |\psi|^2}} \right)^2 + \gamma \left(\frac{\Box \psi}{\psi + \epsilon e^{-\alpha |\psi|^2}} \right) \left(\frac{\nabla^2 \psi}{\psi + \epsilon e^{-\alpha |\psi|^2}} \right). \tag{4}$$

Within this model it is natural to introduce WCT/WCC-specific analogs of classical complexity classes in the *physical* (rail-constrained) setting:

- $\psi^* \in \mathbf{NP}^{\text{phys}}_{\text{WCC}}$: if it satisfies an entropy–coherence criterion $\sigma[\psi^*] \le \sigma_{\text{crit}}$ and can be *verified* by a local curvature/entropy test in polynomial physical resources;
- $\psi^* \in \mathbf{P}^{\text{phys}}_{\text{WCC}}$: if it is *reachable* from ψ_0 within polynomially bounded time steps under WCT evolution obeying WCT rails.

The classical relation between **P** and **NP** is then approached via a conjectured correspondence between the *ideal* WCC classes $(\mathbf{P}^{\infty}_{\text{WCC}}, \mathbf{NP}^{\infty}_{\text{WCC}})$ and the usual Turing-machine classes; this correspondence is discussed later and is not assumed as a theorem here.

8.2 Simulation Procedure

We implemented a CuPy-accelerated simulation for grid sizes $n = 32, 64, 96$, evolving from a trivial random initial state toward a fixed coherent standing-wave solution ψ^*. The evolution followed the curvature–entropy Lagrangian above with parameters

$$\alpha = 1.5, \quad \theta = 0.0026, \quad \gamma = 10^{-120}, \quad \epsilon = 10^{-6}, \quad \delta = 10^{-8}, \quad dt = 2{\times}10^{-4}, \quad \text{steps} = 5000.$$

The final overlap with the target state is measured as

$$\text{Overlap}(\psi, \psi^*) = \frac{\int \psi \, \overline{\psi^*} \, dx}{\sqrt{\int |\psi|^2 \, dx \int |\psi^*|^2 \, dx}}. \tag{5}$$

8.3 Results

For one representative experiment, the final average overlaps were:

Grid Size n	**Avg Final Overlap**	**Steps Simulated**
32	0.077637	5000
64	0.012087	5000
96	−0.006049	5000

Original figure not supplied with the LaTeX source.
Reported values are preserved in the table above.

Figure 1: Final overlap vs. grid size n. In this particular WCT rail and parameter choice, the evolution fails to approach the known coherent state ψ^* as n grows, despite using the same number of time steps.

8.4 Heuristic Observation: Hard-to-Reach Verifiable States in WCT

In this numerical setting we observe the following pattern:

- The target state ψ^* is fixed and easily checked by a local entropy–curvature verifier, so it behaves like a member of $\mathbf{NP}^{\text{phys}}_{\text{WCC}}$.
- For increasing grid size n, the same bounded WCT evolution fails to reach high overlap with ψ^*; the evolution appears to *avoid* this verifiable target state under any fixed polynomial-time budget in the physical model.

This behaviour is naturally interpreted as:

"in these experiments, ψ^* behaves like an element of $\mathbf{NP}^{\text{phys}}_{\text{WCC}} \backslash \mathbf{P}^{\text{phys}}_{\text{WCC}}$ for the tested scales."

We emphasize that this is an *empirical* and *model-dependent* observation, not a theorem. It is consistent with the conjecture that there exist verifiable but non-constructible configurations in the physical WCT model, but it does not by itself establish any formal separation between classical **P** and **NP**, nor does it prove any of the model-relative conjectures stated above.

8.5 Interpretation

The simulation results above belong historically to the "physics-first" phase of this work: they illustrate that, in practice, certain coherent states ψ^* are difficult to reach under bounded curvature-regulated evolution, and that this difficulty grows with system size.

In the present paper, however, these numerics serve only as *motivation*. All complexity-theoretic statements are formulated symbolically. In particular:

- The conjectured separations $\mathbf{P}^{\text{phys}}_{\text{WCC}} \neq \mathbf{NP}^{\text{phys}}_{\text{WCC}}$ (physical model) and $\mathbf{P}^{\infty}_{\text{WCC}} \neq \mathbf{NP}^{\infty}_{\text{WCC}}$ (ideal model) are stated and analyzed at the level of symbolic transition systems, verifiers, and curvature/Kolmogorov complexity.
- Any potential bridge from $(\mathbf{P}^{\infty}_{\text{WCC}}, \mathbf{NP}^{\infty}_{\text{WCC}})$ to classical $(\mathbf{P}, \mathbf{NP})$ is treated as a *program* and clearly marked as conditional.

Simulations are therefore included only to make the geometric and entropic mechanisms more concrete; they are not used as part of any claimed proof.

9 Internal Separation Heuristics: Constructive Depth in WCC

In this section we isolate a model–internal notion of *constructive depth* for WCC evolutions and relate it to clause–structured NP witnesses such as

3–SAT assignments. The goal is to clarify how locality and finite–range dynamics constrain reachable configurations, and to state a natural *conjectured* internal separation

$$\mathbf{PWCC} \subsetneq \mathbf{NPWCC}$$

within the WCC model. We emphasize that any unconditional proof of such a separation, combined with the equivalences $\mathbf{PWCC} = \mathbf{P}$ and $\mathbf{NPWCC} = \mathbf{NP}$, would yield $\mathbf{P} \neq \mathbf{NP}$ and thus resolve a major open problem. Accordingly, the separation in this section is formulated as a conjecture, not as a theorem.

9.1 Symbolic Support and Constructive Depth

Let $W = (\Lambda_n, S, r, U, \mathrm{enc}, \mathrm{dec})$ be a WCC machine on inputs of length n. For any configuration $C : \Lambda_n \to S$, define its *symbolic support*

$$\mathrm{supp}(C) := \{\, i \in \Lambda_n : C(i) \neq s_0 \,\}$$

for some fixed background symbol $s_0 \in S$. Let Δ_t denote the *symbolic change set*

$$\Delta_t := \{\, i \in \Lambda_n : C_{t+1}(i) \neq C_t(i) \,\}.$$

We say a configuration C^* has *constructive depth* D (with respect to U) if any sequence of configurations

$$C_0 \to C_1 \to \cdots \to C_T = C^*$$

reachable under the local rule U has length $T \geq D$.

Lemma 9.1 (Locality bound on support growth). Let W have interaction radius r. Then for all $t \geq 0$,

$$\mathrm{supp}(C_{t+1}) \subseteq \mathrm{supp}(C_t)^{+r},$$

where X^{+r} is the r–neighbourhood thickening of X. In particular,

$$|\mathrm{supp}(C_t)| \;\leq\; |\mathrm{supp}(C_0)| + O\big(rt\,|\partial \mathrm{supp}(C_0)|\big).$$

Proof. The local rule U at site i depends only on C_t restricted to $N_r(i)$. If all cells in $N_r(i)$ are in the background state s_0, then $C_{t+1}(i)$ must remain in s_0 as well. Thus new non–background symbols can only appear within the r–thickening of the previous support. This implies the stated inclusion and the linear light–cone bound on support growth. □

Lemma 9.1 formalizes the intuitive fact that WCC machines have a *linear light cone*: local information can propagate at most $O(r)$ cells per global update, and the region of nontrivial activity can grow at most linearly in t from any finite seed.

9.2 Clause–Structured Certificates and Linear Depth

Let L_{SAT} be the canonical 3–SAT language over $\{0,1\}$. Under the Cook–Levin–style WCC reduction (see Section A), each clause $C_j = (\ell_{j1} \vee \ell_{j2} \vee \ell_{j3})$ is mapped to a local WCC region R_j of constant diameter, with acceptance determined by a curvature–locked pattern ψ_j^{sat} encoding satisfaction of that clause. Let $C(w)$ denote the certificate configuration for a witness $w \in \{0,1\}^{m(n)}$.

For each configuration C_t on a WCC trajectory, define its *clause–signature vector*

$$v_t := \big(\sigma_1(C_t), \ldots, \sigma_m(C_t)\big) \in \{0,1\}^m,$$

where $\sigma_j(C_t) = 1$ iff clause j is satisfied in the local region R_j of C_t and $\sigma_j(C_t) = 0$ otherwise.

Lemma 9.2 (Per-clause change requires local activity)*.* If the jth signature bit is a function only of the configuration on R_j, a change in σ_j between two updates requires a change in at least one cell of R_j. If at most $b \geq 1$ clause signatures can change during any global round, altering k signatures requires at least $\lceil k/b \rceil$ rounds.

Proof. An unchanged local region has unchanged signature. Each round can change at most b distinct signatures by the extra stated hypothesis, so $Tb \geq k$. □

A synchronous finite-range rule does *not* impose $b = O(1)$: spatially separated clauses may change in parallel. Consequently, no unconditional $T \geq k$ bound follows from locality alone.

9.3 Heuristic Exponential Barrier and Conjecture

A formula with n Boolean variables admits 2^n candidate assignments, but this count does *not* imply that a correct algorithm must examine all candidates. Furthermore, different assignments need not induce distinct clause-signature vectors, and locality alone does not forbid simultaneous clause updates.

Conjecture 9.3 (Uniform discrete-WCC SAT lower bound). Every uniform deterministic discrete WCC machine deciding the 3-SAT *language* requires superpolynomial worst-case time on infinitely many input lengths.

Because the uniform discrete model is polynomially Turing-equivalent, this conjecture is precisely as difficult as showing $P \neq NP$ by proving that 3-SAT is not in P. It is not established by the size of a search space, a fixed WCC trajectory, or a geometric heuristic. A physical version must separately account for admissible verifier implementations.

9.4 Conditional Internal Separation

Define, as before, the language

$$L^\star := \big\{x \in \{0,1\}^n : \exists w,\ |w| = m(n),\ C(w) \text{ satisfies all clause signatures for } x\big\}.$$

By construction (cf. Section A), $L^\star$ is exactly 3–SAT encoded through the WCC certificate map, and hence $L^\star \in \mathbf{NPWCC}$.

The following statement is therefore conditional on Conjecture 9.3.

Proposition 9.4 (Conditional model–internal separation). If Conjecture 9.3 holds, then

$$L^\star \in \mathbf{NPWCC} \setminus \mathbf{PWCC},$$

and hence

$$\mathbf{PWCC} \subsetneq \mathbf{NPWCC}.$$

Proof. By construction $L^\star \in \mathbf{NPWCC}$. If Conjecture 9.3 holds, no polynomial–time WCC machine can decide $L^\star$, so $L^\star \notin \mathbf{PWCC}$. This gives the strict inclusion. □

In combination with the bijection results of Section D.4 and the identifications $\mathbf{PWCC} = \mathbf{P}$, $\mathbf{NPWCC} = \mathbf{NP}$, any proof of Conjecture 9.3 would immediately yield the classical separation $\mathbf{P} \neq \mathbf{NP}$. At present, Conjecture 9.3 should be viewed as a structured formulation of a WCC–internal manifestation of the **P** versus **NP** question.

10 Dimensional-Lock Hypothesis: A Geometric Constructibility Barrier

We now formalize the "dimensional lock" mechanism suggested by WCT as a *model-relative hypothesis* about symbolic evolution under curvature-regulated local rules in the physical WCC/WCT model.

Conjecture 10.1 (Dimensional-Lock Hypothesis (Physical Model)). Consider deterministic symbolic wave evolution governed by

$$\psi_{t+1} = F(\psi_t, \nabla^2 \psi_t),$$

where each update can be simulated by a Turing machine in time $\mathrm{poly}(n)$ for system size n, and where the corresponding WCC implementation respects WCT curvature/energy rails. Assume there exists a curvature-locked symbolic configuration ψ^* such that:

1. **High descriptive complexity.**

$$K(\psi^*) > \mathrm{poly}(|\mathrm{SAT}_n|),$$

   so that ψ^* encodes combinatorially rich structure; and

2. **Slow coherence descent.** For every valid curvature-feedback trajectory $\psi_0 \to \psi^*$ satisfying the monotone coherence/entropy inequality

$$\frac{dI}{dt} \geq 0,$$

   the required symbolic depth satisfies

$$\ell(\psi_0 \to \psi^*) \geq n^{\omega(1)}.$$

Then

$$\psi^* \in \mathbf{NP}^{\mathrm{phys}}_{\mathrm{WCC}} \quad \text{but} \quad \psi^* \notin \mathbf{P}^{\mathrm{phys}}_{\mathrm{WCC}},$$

and hence

$$\mathbf{P}^{\mathrm{phys}}_{\mathrm{WCC}} \subsetneq \mathbf{NP}^{\mathrm{phys}}_{\mathrm{WCC}}$$

within the rail-constrained WCT/WCC model.

Heuristic background. The WCT picture suggests that coherent, curvature-locked states occupy low-entropy "corners" of configuration space. Curvature-regulated evolution can only reduce entropy and enforce phase-locking at a bounded local rate. If the entropy gap separating ψ_0 from ψ^* grows super-polynomially, then no polynomial-depth curvature trajectory can reach ψ^*. Turning this mechanism into a theorem is an open problem; the conjecture isolates the barrier that must be proved. Our long-term goal is to extend such barriers from the physical classes $\mathbf{P}^{\text{phys}}_{\text{WCC}}, \mathbf{NP}^{\text{phys}}_{\text{WCC}}$ to the ideal classes $\mathbf{P}^{\infty}_{\text{WCC}}, \mathbf{NP}^{\infty}_{\text{WCC}}$.

11 Curvature Bounds and Structural Lemmas: Conditional Form

WIN-06 and WIN-07. Let a physically admissible, nonvanishing field ψ have a specified curvature functional $C_\Theta[\psi]$ and a decision interface $\partial\mathcal{R}_\psi$. The following elementary implication is valid but does not establish its geometric hypotheses.

Proposition 11.1 (Conditional interface-to-curvature implication). Suppose an instance family F_n and a class of permitted encodings $\mathcal{E}_n$ satisfy, with constants independent of n and of the encoding, both

$$C_\Theta[\psi] \geq \kappa_0 \mathcal{H}^{d-1}(\partial\mathcal{R}_\psi), \quad \kappa_0 > 0,$$

and, for every admissible realization of the requisite decision computation on some input of length $\Theta(n)$,

$$\mathcal{H}^{d-1}(\partial\mathcal{R}_\psi) \geq c_0 2^{\gamma n}, \qquad c_0, \gamma > 0.$$

Then the corresponding worst-input curvature cost is at least $\kappa_0 c_0 2^{\gamma n}$.

Proof. Substitution of the second assumed inequality into the first. □

Remark. A bounded-degree expander graph does not by itself force the stated interface area in every embedding. A proof must quantify uniformly across admissible encoders, include their scales and distortions, and justify a positive interface cost for the *particular* curvature density used. This manuscript does not supply such a proof.

11.1 Per-update curvature and construction cost

Proposition 11.2 (Valid telescoping bound). If $C_\Theta[\psi_0] \geq 0$ and each allowed update obeys $|C_\Theta[\psi_{t+1}] - C_\Theta[\psi_t]| \leq \Delta_{\max}$, then for every $T \geq 0$,

$$T \geq \frac{(C_\Theta[\psi_T] - C_\Theta[\psi_0])_+}{\Delta_{\max}}$$

when $\Delta_{\max} > 0$.

Proof. The triangle inequality gives $C_\Theta[\psi_T] - C_\Theta[\psi_0] \leq \sum_{t=0}^{T-1} |C_\Theta[\psi_{t+1}] - C_\Theta[\psi_t]| \leq T\Delta_{\max}$. □

The uniform per-update bound and the initial cost must be separately justified; neither follows merely from finite propagation speed.

11.2 Padding stability

Proposition 11.3 (Conditional additive padding). If the model enforces an orthogonal, noninteracting decomposition of field domains $\Omega = \Omega_F \sqcup \Omega_{\text{pad}}$, zero curvature on the padding domain, and no interface or cross-coupling energy, then the curvature functional of that *specific* encoded configuration is unchanged by padding.

Proof. The integral over the disjoint domains is additive and the second integral is zero. □

This does not prove that the *minimum over all alternative encodings* is unchanged; nor does a superlinear padding function preserve an exponential bound in the new input length.

12 Curvature-Locked Witnesses: Existence and Verification Obligations

WIN-03, WIN-05 and WIN-07. An exact Boolean phase encoding supplies an algebraic zero-penalty witness whenever a SAT formula is satisfiable (Theorem 5.3). It does not automatically supply a stable stationary solution to a chosen WCT PDE.

For a specified energy functional $\mathcal{A}$ on a precisely defined function space, the following questions remain distinct:

1. **Attainment:** show that the set of zero-logical-penalty fields is nonempty and closed in a topology in which a coercive energy has a weakly lower semicontinuous restriction.

2. **Stationarity:** prove the constrained Euler–Lagrange conditions, and address Lagrange multipliers before claiming unconstrained stationarity of the full energy.

3. **Verification:** specify finite-precision data, tolerances, encoding length, physical time and curvature energy to establish a polynomial-resource verifier in the *same* physical model.

4. **Lower bound:** rule out all deterministic solvers, including algorithms that directly evaluate a supplied certificate without exploring an exponentially large space of alternative certificates.

Proposition 12.1 (Conditional separation from a language-level barrier). Let L be a language and fix one WCC physical resource semantics. If L has a physically admissible polynomial-time verifier for polynomial-size witnesses and no physically admissible polynomial-time decider, then $L \in NP^{\text{phys}}_{\text{WCC}} \setminus P^{\text{phys}}_{\text{WCC}}$.

Proof. Apply the two class definitions with identical resource bounds. □

Remark. A purported witness whose *energy itself* is $2^{\Omega(n)}$ is not admissible in a physical NP class requiring polynomial witness energy, even if the symbolic assignment can be checked cheaply. The distinction between verifying a Boolean string and realizing a particular high-curvature field is essential.

13 Toward a Formal P vs. NP Program via Wave Dynamics

13.1 Complexity Mapping into Wave Confinement Theory

Wave Confinement Theory represents computation as curvature-driven evolution: a wavefield $\psi(x,t)$ evolves locally under curvature and entropy constraints. This allows an NP-style verification / P-style construction analogy:

Complexity Concept	**WCT Interpretation**
Input string x	Initial configuration ψ_0
Certificate w	Target coherent state ψ^*
Verifier $M(x,w)$	Local test: $\sigma[\psi^*] \leq \sigma_{\text{crit}}$
Polynomial-time algorithm	Local update: $T = O(n^k)$ curvature steps
Acceptance	Overlap test: $\text{Overlap}(\psi_T, \psi^*) > \tau$

Table 1: Mapping between classical NP verification and curvature-regulated WCT dynamics.

This motivates the model-relative WCC classes introduced earlier. In the *physical* setting these are $\mathbf{P}^{\text{phys}}_{\text{WCC}}, \mathbf{NP}^{\text{phys}}_{\text{WCC}}$; in the *ideal* (unbounded) setting they are $\mathbf{P}^{\infty}_{\text{WCC}}, \mathbf{NP}^{\infty}_{\text{WCC}}$. Our long-term complexity-theoretic target is a separation $\mathbf{P}^{\infty}_{\text{WCC}} \neq \mathbf{NP}^{\infty}_{\text{WCC}}$ in the ideal model, with the physical separation as a precursor.

13.2 Model-Level Hypothesis to Be Contradicted (Ideal WCC)

The WCT/WCC analog of the classical hypothesis $P = NP$ in the *ideal* model is:

> *Every verifiable coherent state $\psi^* \in \mathbf{NP}^{\infty}_{\mathrm{WCC}}$ is reachable from ψ_0 by curvature-regulated symbolic evolution within polynomial depth in the ideal WCC model.*

Dimensional locking and related curvature barriers suggest this fails for certain families of coherent states.

13.3 Coherence Without Constructibility in the Ideal WCC Model

Let C_n denote the space of confined wavefields over an $n \times n$ grid in the ideal discrete WCC model. We seek $\psi^* \in C_n$ such that:

- ψ^* is verifiable by a local curvature–entropy predicate (i.e. $\psi^* \in \mathbf{NP}^{\infty}_{\mathrm{WCC}}$),
- but for any polynomial-depth trajectory $\psi_0 \to \psi_T$, the symbolic distance $d(\psi_T, \psi^*)$ remains nonzero (i.e. $\psi^* \notin \mathbf{P}^{\infty}_{\mathrm{WCC}}$).

Such states would establish an internal model-relative separation

$$\mathbf{P}^{\infty}_{\mathrm{WCC}} \subsetneq \mathbf{NP}^{\infty}_{\mathrm{WCC}}$$

in the ideal WCC model.

13.4 Conditional Curvature Separation Statement (Ideal WCC)

Proposition 13.1 (Model-Relative Separation in Ideal WCC (Conditional)). Assume there exists a family $\{\psi_n^*\} \subset C_n$ such that:

1. Each ψ_n^* satisfies the polynomial-time local verifier (i.e. $\psi_n^* \in \mathbf{NP}^{\infty}_{\mathrm{WCC}}$); and

2. No curvature-regulated symbolic evolution of depth $T(n) = O(n^k)$ reaches ψ_n^* from ψ_0 for any fixed k (i.e. $\psi_n^* \notin \mathbf{P}^{\infty}_{\mathrm{WCC}}$).

Then

$$\mathbf{P}^{\infty}_{\mathrm{WCC}} \neq \mathbf{NP}^{\infty}_{\mathrm{WCC}}.$$

If, in addition, one can prove that the binary encodings of Section 14 satisfy

$$\mathbf{P}^{\infty}_{\mathrm{WCC}} = \mathbf{P}, \qquad \mathbf{NP}^{\infty}_{\mathrm{WCC}} = \mathbf{NP},$$

then the classical separation $P \neq NP$ follows as a corollary.

Discussion. The proposition itself is tautological: (i) + (ii) directly imply a separation in the ideal WCC model. The real work is in:

1. constructing or characterizing such families $\{\psi_n^*\}$ (dimensional lock and curvature-complexity lower bounds), and

2. proving the equivalence between ideal WCC computation and Turing computation ($\mathbf{P}^{\infty}_{\mathrm{WCC}} = \mathbf{P}$ and $\mathbf{NP}^{\infty}_{\mathrm{WCC}} = \mathbf{NP}$).

This paper provides partial progress toward (i) and a model-theoretic embedding toward (ii), but does not claim either as a completed theorem.

14 Formal Model-Theoretic Framework for P vs NP in WCT

In this section we place the WCT computational picture into an explicit symbolic framework, so that any future separation result can be stated entirely in the language of Turing machines and circuits.

14.1 Definition of the WCT Computational Model

We define the Wave Confinement Theory (WCT) computational model $\mathcal{M}_{\text{WCT}}$ as follows:

- The computational state is a complex-valued wavefield $\psi(x,t) \in C^2(\Omega \times \mathbb{R})$.
- The evolution of ψ follows a curvature-regulated Lagrangian

$$\mathcal{L}_{\text{WCT}} = |\partial_\mu \psi|^2 + \kappa \left(\frac{\Box \psi}{\psi + \epsilon e^{-\alpha |\psi|^2}} \right)^2 + \theta \left(\frac{\nabla^2 \psi}{\psi + \epsilon e^{-\alpha |\psi|^2}} \right)^2 + \dots \quad (6)$$

  or its discrete symbolic analog.
- Input to the model is given by a grid of size $n \times n$ and a trivial initial field $\psi_0(x)$.
- The system evolves under a time budget $T = \mathcal{O}(n^k)$.
- Acceptance is defined by a target field ψ^* and an overlap/entropy condition:

$$\text{Accept if } \text{Overlap}(\psi_T, \psi^*) > \tau \quad \text{and} \quad \sigma[\psi^*] \leq \sigma_{\text{crit}}. \quad (7)$$

This defines $\mathbf{P}_{\text{WCT}}$ and $\mathbf{NP}_{\text{WCT}}$ as discussed above.

14.2 Encoding of NP-Complete Languages in WCT

Let L be any NP-complete language (e.g. 3-SAT). The WCT program is to construct a corresponding family of wavefields ψ_L^* such that:

- Each Boolean variable x_i is encoded as a resonance mode over a spatial region R_i.
- Clauses are encoded as interference or curvature constraints.
- The global wavefield ψ_L^* is entropy-coherent ($\sigma[\psi_L^*] \leq \sigma_{\text{crit}}$) if and only if the formula is satisfiable.

Formally achieving

$$x \in L \iff \psi_L^*(x) \text{ is a coherent, verifiable wavefield in } \mathbf{NP}_{\text{WCT}}$$

for all x would realize a Cook–Levin style reduction into the WCT framework. In this paper we sketch such encodings at a conceptual level; a fully formal construction is left as future work.

14.3 Constructibility Barrier under WCT Dynamics

Preliminary analytic arguments and the numerical evidence of Section 8 suggest that, for increasing n,

- WCT evolution from ψ_0 may fail to reach certain ψ_L^* within any fixed polynomial time budget $T = \mathcal{O}(n^k)$;
- The overlap $\text{Overlap}(\psi_T, \psi_L^*)$ can decay with n, even for instances known to be satisfiable.

These observations are consistent with, but do not yet prove, the existence of configurations in $\mathbf{NP}_{\text{WCT}} \setminus \mathbf{P}_{\text{WCT}}$.

14.4 A Conditional Model-Theoretic Separation Statement

Proposition 14.1 (Formal Model-Theoretic Separation in WCT (Conditional)). Assume:

1. There exists a family $\{\psi_L^*\}$ of WCT-encodable wavefields such that for each NP-complete language L, the map $x \mapsto \psi_L^*(x)$ realizes a polynomial-time Cook–Levin style reduction and $\psi_L^*(x)$ is verifiable by a local WCT predicate in polynomial resources; and

2. For at least one such NP-complete L, the corresponding family $\{\psi_L^*(x)\}$ lies in $\mathbf{NP}_{\mathrm{WCT}} \setminus \mathbf{P}_{\mathrm{WCT}}$.

Then $\mathbf{P}_{\mathrm{WCT}} \neq \mathbf{NP}_{\mathrm{WCT}}$. If, in addition, one can show that $\mathbf{P}_{\mathrm{WCT}} = \mathbf{P}$ and $\mathbf{NP}_{\mathrm{WCT}} = \mathbf{NP}$ under a binary encoding of WCT states and transitions, this would imply the classical separation $\mathbf{P} \neq \mathbf{NP}$.

Thus, the WCT framework provides a *conditional route* to $\mathbf{P} \neq \mathbf{NP}$: the missing pieces are (i) a rigorous construction of NP-complete encodings as curvature-locked states, (ii) a proof of non-constructibility within WCT evolution (the dimensional lock conjecture), and (iii) a clean equivalence between WCT complexity classes and their Turing counterparts.

Connection to classical complexity theory. If these steps can be completed, the resulting separation would mirror, in geometric form, the phenomena captured abstractly by the Time Hierarchy Theorem: deeper "curvature traversals" (longer evolution depth) would be provably required to construct certain verifiable configurations, beyond any fixed polynomial bound. At present, this connection should be viewed as an analogy and a research direction, not as an established theorem.

15 Binary Encoding and Turing Reduction of WCT

All statements in this section are either definitional or explicitly *conditional*. They describe how WCT-style curvature evolution can be represented in a classical Turing framework and how a putative WCT-level nonconstructibility result would *map* into standard complexity language. No unconditional claim about P vs. NP is made.

15.1 Tape Encoding of WCT States

Let the wavefield $\psi(x,t)$ over an $n \times n$ grid be represented as

$$\psi[i,j] = a_{ij} + ib_{ij}, \quad a_{ij}, b_{ij} \in \mathbb{R}.$$

We encode each complex amplitude using finite-precision binary:

$$\text{Tape representation: } \underbrace{0.101011\ldots}_{\text{Re}} \mid \underbrace{0.011010\ldots}_{\text{Im}} \#.$$

The entire field $\psi(x,t)$ is thus encoded as a binary tape of length $\mathcal{O}(n^2)$ (up to the chosen precision).

15.2 Turing Transducer for Curvature Evolution

We consider a deterministic Turing machine M_{WCT} that:

- Reads an input tape encoding ψ_t,
- Computes each grid value update using a finite-difference approximation to curvature-regulated evolution, e.g.

$$\psi_{t+1}[i,j] = \psi_t[i,j] + dt \cdot \left[\nabla^2 \psi_t - \frac{\alpha \nabla^2 \psi_t}{\psi_t + \epsilon e^{-\beta |\psi_t|^2}} - \theta \cdot \psi_t \cdot \nabla^2 (\log |\psi_t|^2) \right],$$

- Applies arithmetic operations using standard polynomial-time Turing subroutines (finite-precision rational arithmetic).

This defines a symbolic curvature-update transducer. For any fixed precision model (e.g. $b(n)$ bits per amplitude with $b(n) = \text{poly}(n)$) one can arrange that a single macro-step of the WCT update is simulated in time $\text{poly}(n, b(n))$. We treat this as a *modelling assumption* fixing the intended regime for the WCT–Turing correspondence.

15.3 Acceptance Criterion as Turing Predicate

We define a symbolic acceptance predicate

$$\text{Accept}(\psi) = 1 \iff \text{Overlap}(\psi, \psi^*) > \tau \text{ and } \sigma[\psi] \leq \sigma_{\text{crit}},$$

where:

- Overlap is computed via a normalized dot product between the encodings of ψ and ψ^*,
- Entropy $\sigma[\psi]$ is approximated by summing $-p \log p$ over the tape (with finite-precision logarithms).

Under reasonable encoding choices, this verifier can be implemented by a deterministic Turing machine using time polynomial in the tape length (e.g. $\mathcal{O}(n^2)$ for an $n \times n$ grid). Thus WCT-style verifiers embed naturally into classical **NP** predicates.

15.4 A Conditional Turing Reduction Template

We now sketch how a WCT-style nonconstructibility statement would translate into classical Turing language. We work with the model-relative classes $\mathbf{P}_{\text{WCT}}$ and $\mathbf{NP}_{\text{WCT}}$ introduced earlier.

Proposition 15.1 (Conditional Turing Reduction Template). Assume:

1. **Simulation of WCT by Turing machines.** The curvature-regulated evolution of Section 14 can be simulated by a deterministic Turing machine M_{WCT} with at most polynomial overhead in the tape length, for the encodings above.
2. **Verifier embedding.** The acceptance predicate $\text{Accept}(\psi)$ is computable in time $\text{poly}(n)$ on the Turing encoding, so any family of targets $\{\psi_n^*\}$ accepted by this predicate defines a language $L \subseteq \{0,1\}^*$ in **NP**.
3. **Nonconstructible but verifiable targets (WCT model).** There exists a family of encodable WCT targets $\{\psi_n^*\}$ such that:
   - each ψ_n^* is verifiable by the local curvature/entropy test in polynomial WCT resources (so $\psi_n^* \in \mathbf{NP}_{\text{WCT}}$),

- but no deterministic polynomial-time WCT evolution from a trivial initial configuration ψ_0 reaches ψ_n^* (so $\psi_n^* \notin \mathbf{P}_{\mathrm{WCT}}$).

Then:

- within the WCT model one obtains a separation $\mathbf{P}_{\mathrm{WCT}} \neq \mathbf{NP}_{\mathrm{WCT}}$; and
- if, in addition, one could prove that the identifications $\mathbf{P}_{\mathrm{WCT}} = \mathbf{P}$ and $\mathbf{NP}_{\mathrm{WCT}} = \mathbf{NP}$ hold (a *compatibility hypothesis* between WCT and classical computation), then the corresponding language L would lie in $\mathbf{NP} \setminus \mathbf{P}$ and hence imply $\mathbf{P} \neq \mathbf{NP}$.

The substantive content lies in assumption (3): establishing such a family $\{\psi_n^*\}$ is precisely the nonconstructibility problem discussed earlier (e.g. via dimensional lock and curvature-complexity barriers). The proposition itself is purely conditional: it specifies how a WCT-level separation, if proved and if compatible with standard encodings, would map to the usual P vs. NP consequence.

15.5 Conclusion

The encoding of WCT into a binary Turing-machine formalism shows that:

- Curvature-regulated wave evolution can be represented within standard discrete computation;
- Any eventual WCT-level separation between verifiability and constructibility (i.e. $\mathbf{NP}_{\mathrm{WCT}} \setminus \mathbf{P}_{\mathrm{WCT}}$) can, in principle, be interpreted in classical Turing terms under additional compatibility hypotheses.

In particular, if one could construct a configuration family $\{\psi_n^*\}$ that is verifiable in polynomial time but *provably* not constructible in polynomial time by any such machine (so that the associated language $L \in \mathbf{NP} \setminus \mathbf{P}$), then by the standard complexity-theoretic implication

$$\exists\, L \in \mathbf{NP} \setminus \mathbf{P} \quad \Rightarrow \quad \mathbf{P} \neq \mathbf{NP},$$

one would obtain a classical separation. This manuscript does *not* claim that such a configuration family has been fully established; instead, it develops the formal apparatus and model-relative barriers needed to state that goal precisely.

Classical Implication Template: P vs. NP (Conditional)

Classical implication (recalled). If there exists a decision problem (or configuration family) in $\mathbf{NP} \setminus \mathbf{P}$, then

$$\boxed{\mathbf{P} \neq \mathbf{NP}}.$$

The WCT framework aims to realize such an example by constructing a verifiable configuration family $\{\psi_n^*\}$ that satisfies an NC^1-implementable symbolic verifier, and for which one can *prove*, inside the model, that no deterministic Turing machine (or equivalently, no WCT evolution under the chosen encoding) can construct ψ_n^* in polynomial time, for all n. At present, this is a *research program*: the nonconstructibility part is formulated as a conjectural barrier rather than a completed proof, and all links to classical P vs. NP are presented as explicitly conditional templates.

16 Discrete Turing Reformulation and Open Nonconstructibility Goal

16.1 Classical Symbolic Encoding of WCT Computation

We define a discrete deterministic Turing model $T^{\Sigma}_{\mathrm{WCT}}$ operating over a finite binary alphabet $\Sigma = \{0, 1, \#\}$ that encodes the PWCC/WCT dynamics symbolically. Each complex amplitude $\psi[i, j] \in \mathbb{C}$ is represented as a binary pair of rational approximations:

$$\psi[i, j] = a_{ij} + ib_{ij}, \qquad a_{ij}, b_{ij} \in \mathbb{Q} \subseteq \mathbb{Z}/2^m,$$

for fixed precision parameter m.

A full grid configuration is stored on a single Turing tape in a canonical fixed-length layout (row-major order, with delimiters). One global evolution step of the field is simulated by a finite sequence of symbolic arithmetic operations (addition, multiplication, and lookup-table–based approximations to nonlinear functions) on these bitstrings.

16.2 Curvature Dynamics as an Arithmetic Circuit

The curvature-regulated update

$$\psi_{t+1} = \psi_t + \Delta t \cdot F(\psi_t)$$

is abstracted as a Boolean/arithmetic circuit F composed of:

- finite-difference Laplacian and stencil operators,
- fixed-precision multipliers and adders,
- rational-function or table-based approximations to exponentials, logs, and normalizations.

In idealized form, and for fixed precision, F can be placed in a low-level circuit class such as AC^0 or NC^1, depending on the exact gate set and fan-in assumptions. A single step of $T^{\Sigma}_{\mathrm{WCT}}$ then simulates $F(\psi_t)$ via a sequence of logically defined operations on binary strings, with per-step cost polynomial in the system size.

16.3 A Purely Symbolic Verifier

We restate the acceptance predicate in purely symbolic terms:

$$A(\psi) = 1 \iff \frac{\langle \psi, \psi^* \rangle}{\|\psi\| \cdot \|\psi^*\|} > \tau \ \wedge \ \sigma(\psi) \leq \sigma_{\text{crit}},$$

where inner products, norms, and entropy are computed from the bit-encoded amplitudes by:

- fixed-precision multipliers and adders for $\langle \psi, \psi^* \rangle$ and $\|\psi\|^2$,
- table-based (or truncated-series) approximations to log,
- prefix-sum trees to aggregate all contributions.

All subroutines used in A are intended to be realizable by polynomial-time Turing machines; the target complexity placement is $A \in \mathsf{NC}^1$ (cf. the discussion in Section A). In particular, the definition of A in this section does not depend on any continuous geometry, only on the chosen binary encoding and standard arithmetic circuits.

16.4 A Programmatic Nonconstructibility Goal

Let ψ_0 be a trivial initial configuration (e.g., all zeros) in the tape encoding, and let ψ^* be a candidate target configuration whose correctness is verifiable by A. In purely classical complexity-theoretic terms, the *programmatic goal* suggested by WCT can be phrased as:

> **Goal.** Find a family $\{\psi_n^*\}$ of bit-encoded configurations and a verifier A with $A(\psi_n^*) = 1$ in polynomial time such that, for every deterministic polynomial-time Turing machine M and all sufficiently large n,
>
> $$M(\psi_0, n) \neq \psi_n^*.$$

The inability to print one prescribed target string does not, by itself, separate decision-language complexity classes. To derive a classical separation, one must specify a uniformly encoded *language* with a polynomial-time membership verifier and rule out every polynomial-time *decider* for that same language. Only then would the classical conclusion $\mathbf{P} \neq \mathbf{NP}$ follow. In this paper, WCT provides geometric and curvature-based heuristics for constructing candidates for $\{\psi_n^*\}$; *the rigorous nonconstructibility proof in the unrestricted Turing model is left as an open problem.*

16.5 Independence from Numerical Simulation

The symbolic model $T^{\Sigma}_{\mathrm{WCT}}$ operates entirely on finite encodings with logically defined transition rules, arithmetic identities, and combinatorial estimates. Consequently:

- Any eventual nonconstructibility theorem inspired by WCT can, in principle, be stated purely in the language of Turing machines and circuits, without reference to floating-point numerics or PDE solvers;
- WCT acts as a geometric design principle for hard instance families and verification predicates, while the *final* separation (if obtained) would live entirely inside discrete complexity theory.

In its present form, this section should therefore be read as a *discrete reformulation and roadmap*: it shows how the PWCC/WCT curvature-machine model embeds into the classical symbolic framework, and isolates the precise nonconstructibility statement that must be proved to upgrade the internal PWCC–$\mathsf{NP}_{\mathrm{WCT}}$ separation to a full classical **P** vs. **NP** result.

17 Formal Reduction to Cook–Levin Framework and Universal Scope

17.1 Embedding PWCC Verifiers into the Cook–Levin Framework

The Cook–Levin theorem states that for any language $L \in \mathbf{NP}$, there exists a polynomial-size Boolean circuit $C(x, w)$ such that

$$x \in L \iff \exists w : C(x, w) = 1.$$

In the WCT-inspired setting, we consider symbolic encodings of wavefields and define a verifier predicate

$$A(\psi) = 1 \iff \text{Overlap}(\psi, \psi_L^*) > \tau \ \wedge \ \sigma[\psi] \leq \sigma_{\text{crit}},$$

implemented strictly as a rational-arithmetic circuit over the binary encoding of ψ. Its intended role is analogous to that of $C(x, w)$: to accept exactly those encodings corresponding to satisfying assignments for instances of L.

At present, this connection is conceptual. We outline a pathway by which Cook–Levin tableau encodings can be transplanted into WCT-style symbolic update rules and verifiers, but we do not yet supply a complete Cook–Levin–style formal reduction.

17.2 Universal Scope of Polynomial-Time Turing Machines

Let M be any deterministic Turing machine running in time $\mathcal{O}(n^k)$. Suppose M attempts to construct a symbolic wavefield ψ_L^* corresponding to some NP instance x, such that

$$V(x, \psi_L^*) = 1$$

for a polynomial-time classical verifier V.

In the symbolic WCT framework, the role of the verifier is played by a Turing-implementable predicate A (overlap and entropy test) computed using only:

- bounded-precision multipliers,
- prefix-sum trees,

- comparator circuits,
- and lookup-based logarithms,

all of which lie in $\mathrm{AC}^0 \cup \mathrm{NC}^1$.

Any machine M that constructs ψ_L^* must therefore do so through a sequence of polynomial-time symbolic steps beginning from a trivial tape configuration ψ_0.

If one could show that for *every* such M there exists some NP instance with solution $\psi_L^* \in \mathbf{NP}$ such that

$$M(\psi_0, n) \neq \psi_L^* \quad \text{for all} \quad n^k\text{-bounded runs},$$

then this would imply $\psi_L^* \notin \mathbf{P}$ and hence $\mathbf{P} \neq \mathbf{NP}$. WCT is proposed only as a geometric guide toward constructing such families; no such claim is made here.

17.3 Conditional Summary of the Cook–Levin Embedding

The intended theoretical path is:

- Encode NP-verifiers as symbolic rational-arithmetic circuits consistent with the WCT/PWCC encoding;
- Identify (via curvature/entropy arguments) families of states that are verifiable by these circuits but conjecturally not constructible by any polynomial-time Turing machine;
- Translate this constructive obstruction into a classical $\mathbf{NP} \setminus \mathbf{P}$ separation, *if and only if* the PWCC/Turing correspondence is proved exact.

In this paper we establish only the structure of this roadmap, not the final classical consequence.

Verifier Complexity. The target complexity class of the verifier

$$A(q) = 1 \iff \mathrm{Overlap}(q, q^*) > \tau \wedge \sigma(q) \leq \sigma_{\mathrm{crit}}$$

is expected to be NC^1, since all arithmetic operations—inner products, entropy sums, comparators, prefix additions—can be realized in logarithmic depth with polynomial size. A complete, rigorous circuit-class placement is left as open technical work.

18 Final Remarks on Turing Reduction and Acceptance Formalism

18.1 Symbolic Evolution Under $T^{\Sigma}_{\mathrm{WCT}}$

Let $T^{\Sigma}_{\mathrm{WCT}}$ be the discrete Turing machine defined earlier. A symbolic tape configuration for a small 3×3 grid at 8-bit precision is a block

$$q_t = [\texttt{01000011} \mid \texttt{00110010} \mid \cdots],$$

representing real/imaginary components.

Each update step performs:

- finite-difference Laplacian computation on the tape,
- symbolic evaluation of curvature-feedback terms via lookup tables,
- arithmetic composition into the next configuration q_{t+1}.

All gates are bounded fan-in, and the symbolic update is intended to be simulable in uniform $\mathbf{P}$.

18.2 Formal Acceptance Predicate

We define:

$$A(q) = 1 \iff \mathrm{Overlap}(q, q^*) > \tau \ \wedge \ \sigma(q) \leq \sigma_{\mathrm{crit}},$$

where:

- q is the symbolic Turing encoding of a wavefield,
- Overlap is a normalized inner product (prefix-sum tree),
- Entropy is computed as a discrete approximation of $\sum -p_i \log p_i$.

Lemma 18.1 (Intended Verifier Role). For each NP instance x, the symbolic goal is to construct a configuration q^* such that

$$x \in L \iff A(q^*) = 1.$$

This matches the Cook–Levin interpretation of a verifier state, though no equivalence theorem is yet claimed.

18.3 Diagonalization and Proof-Barrier Context

The WCT-inspired PWCC model is designed with specific complexity-theoretic concerns in mind:

- **Relativization:** The model uses no oracle; all arguments occur within a fixed symbolic transition system.
- **Natural Proofs:** Any envisioned separation relies on specific, structured configuration families, not on large, uniform, efficiently checkable properties—thus avoiding the typical Razborov–Rudich template.
- **Constructivity Constraints:** Conjectured lower bounds arise from symbolic curvature, entropy, and Kolmogorov complexity restrictions rather than adversarial Boolean structure.

These observations only position the framework relative to classical barriers; they do not guarantee their circumvention.

18.4 Model-Level Conclusion

The symbolic WCT/PWCC framework:

- operates entirely within discrete Turing computation once the encoding is fixed;
- admits verifiers plausibly contained in low-depth circuit classes (NC^1);
- offers a geometric mechanism (dimensional lock / entropy barrier) suggesting the existence of configurations in $\mathbf{NP}_{\mathrm{WCT}} \setminus \mathbf{P}_{\mathrm{WCT}}$.

Natural-Proof Barrier Positioning

This framework is not designed to exhibit a "natural" property in the Razborov–Rudich sense: it does not deploy a large, uniform, efficiently checkable Boolean property. Instead, it focuses on specific curvature-locked symbolic configurations constrained by entropy and resonance. Whether this ultimately avoids all known barriers is an open question; here we only articulate the intended positioning.

Logical Dependency Roadmap

Conceptual dependency outline:

- **Verifier Construction ($\mathbf{NC}^1$ Target):** Build a curvature/entropy-based verifier A in a low-depth circuit class.
- **SAT/WCT Encoding:** Give a formal encoding of 3-SAT into wave configurations ψ^* accepted by A.
- **Constructibility Barrier:** Establish a Kolmogorov/entropy-based lower bound showing some ψ^* cannot be constructed in polynomial time.
- **Generalization to All Poly-Time Machines:** Lift the barrier from a specific algorithm to all $M_i \in \mathbf{P}$.
- **Hierarchy/Separation Step:** Translate the constructibility barrier into a time-hierarchy–style separation $\mathbf{NP} \setminus \mathbf{P}$.

This roadmap is intended as a research program rather than a completed proof. If each step can be made precise and rigorously established, the standard implication $\mathbf{P} \neq \mathbf{NP}$ would follow in the usual way.

References

1. S. A. Cook. "The Complexity of Theorem-Proving Procedures." *Proceedings of the 3rd Annual ACM Symposium on Theory of Computing*, 1971.

2. L. A. Levin. "Universal Sequential Search Problems." *Problems of Information Transmission*, 9(3):265–266, 1973.

3. T. Baker, J. Gill, R. Solovay. "Relativizations of the P=?NP Question." *SIAM Journal on Computing*, 4(4):431–442, 1975.

4. A. A. Razborov, S. Rudich. "Natural Proofs." *Journal of Computer and System Sciences*, 55(1):24–35, 1997.

5. S. Aaronson, A. Wigderson. "Algebrization: A New Barrier in Complexity Theory." *ACM Transactions on Computation Theory*, 1(1):2:1–2:54, 2009.

6. A. Lubotzky, R. Phillips, P. Sarnak. "Ramanujan Graphs." *Combinatorica*, 8(3):261–277, 1988.

7. S. Arora, B. Barak. *Computational Complexity: A Modern Approach*. Cambridge University Press, 2009.

8. R. J. Reyes. *Structure and Derivation of Physical Constants through Wave Confinement*. Zenodo, 2025. `https://doi.org/10.5281/zenodo.15341540`.

9. R. J. Reyes. *The Geometry of Resonance: Wave Confinement Theory and the Emergence of Mass, Force, and Spacetime*. Zenodo, 2025. `https://doi.org/10.5281/zenodo.15356814`.

A Symbolic 3-SAT Witness Encoding and Complexity Scope

The corrected literal scores in Section 5.3 give an exact polynomial-size encoding of the Boolean *verifier* relation. Given a 3-CNF formula F and an assignment a, checking $E_{\text{logic}}[a] = 0$ requires only $O(m)$ three-literal clause checks when F has m clauses. This establishes a familiar polynomial-time witness relation, not a new deterministic lower bound for SAT.

Proposition A.1 (Uniform symbolic verification). For an explicitly represented 3-CNF formula F with m clauses and n variables, the predicate

$$V(F, a) := \mathbf{1}\{E_{\text{logic}}[a] = 0\}$$

can be evaluated by a uniform deterministic algorithm in polynomial time. If the formula and witness are supplied as ordinary bitstrings, the algorithm checks no more than $3m$ signed literals after accessing the corresponding assignment bits.

Proof. Evaluate each signed literal from its input bit, compute the OR of three literal values, and AND the results for all clauses. A standard multitape Turing implementation is polynomial-time. □

A.1 Open constructive-reachability problem

The fact that $V(F, a)$ is efficiently computable does not decide whether $\exists a\, V(F, a) = 1$ admits a polynomial-time algorithm. Likewise, a lower bound for the complexity of one prescribed WCT trajectory or one clause-signature enumeration algorithm does not exclude all admissible deciders. The proposed geometric obstruction remains a quantified, language-level research question.

A.2 Nonuniformity and diagonalization limitation

Enumerating all polynomial-time algorithms and choosing an output not generated by a particular machine does not by itself produce an NP language outside P. The existence of an efficiently *verifiable* witness for an efficiently describable *language* must be shown, not inferred from the complexity of an individual prescribed state. Generic time-hierarchy theorems do not imply $P \neq NP$.

B Complexity Class Comparison Table in WCT

Wave Confinement Theory (WCT) provides a physically motivated dynamical model in which computation proceeds through curvature-regulated, locally updated wavefield evolution. In this setting, classical complexity notions have natural analogues. The table below summarizes the heuristic correspondence between classical classes and their WCT interpretations.

Classical Complexity Class	**Definition**	**WCT Interpretation (Model-Relative)**
P	Languages decidable in polynomial time by a deterministic Turing machine	States reachable from the trivial field ψ_0 via $T = \text{poly}(n)$ curvature-regulated update steps in the PWCC/WCT model (i.e. $\mathbf{P}_{\text{WCT}}$)
NP	Languages whose certificates are verifiable in polynomial time	Coherent target states ψ^* verifiable by a log-depth symbolic predicate (e.g. an NC^1 overlap–entropy check), corresponding to $\mathbf{NP}_{\text{WCT}}$
NP \ P	NP-verifiable languages not in P (if any; existence unproved)	Conjectural curvature-locked states ψ^* that satisfy a verifier but may be *not reachable* from ψ_0 in $\text{poly}(n)$ PWCC evolution (i.e. $\psi^* \in \mathbf{NP}_{\text{WCT}} \setminus \mathbf{P}_{\text{WCT}}$)
EXP	Languages requiring exponential time to solve in the classical model	Target states whose symbolic constructive depth under PWCC dynamics grows as $\Omega(2^n)$ (exponential-length curvature paths in configuration space)

Table 2: Heuristic correspondence between classical complexity classes and wave-confinement computation in the PWCC/WCT model. These identifications are *model-relative* and are not claimed to imply any classical separation such as $\mathbf{P} \neq \mathbf{NP}$ in the unrestricted Turing framework.

This table summarizes the conceptual mapping used throughout the paper: PWCC models polynomial-time WCT evolution, while $\mathbf{NP}_{\text{WCT}}$ captures states verifiable by low-depth symbolic predicates derived

from curvature–entropy checks. A strict separation $\mathbf{P}_{\mathrm{WCT}} \subsetneq \mathbf{NP}_{\mathrm{WCT}}$ would be a *WCT-model-level* result only, unless an additional equivalence to classical Turing classes is rigorously established.

C Semantic Curvature Complexity: Conditional Lower-Bound Program

The curvature of an individual field and the semantic cost of a *language* are different objects. Fix a physical model $\mathfrak{W}$, its uniform encoding/readout convention, permitted algorithms, and a nonnegative per-state curvature functional $\Phi(\psi)$. For an algorithm M and input x write

$$\mathsf{Cost}_\Theta(M,x) := \sum_{t=0}^{T_M(x)} \Phi(\psi_{M,x}^t).$$

A genuinely universal language-level cost must take an infimum *over all admissible deciders*, with a worst-case input cost:

$$\mathsf{C}_{\Theta,\mathfrak{W}}(L,n) := \inf_{M \text{ decides } L} \max_{|x|\le n} \mathsf{Cost}_\Theta(M,x).$$

Empty algorithm classes have cost $+\infty$ by convention. Any claim of an exponential universal lower bound must justify its algorithm-independent quantifiers and clarify whether Φ counts instantaneous energy, total time-integrated expenditure, or both.

C.1 Interface and expander hypotheses

Hypothesis C.1 (Uniform interface price). For all admissible fields used by a specified class of machines, $\Phi(\psi) \ge \kappa_0 \mathcal{H}^{d-1}(\partial \mathcal{R}_\psi)$ with $\kappa_0 > 0$ independent of the input length and encoding.

Hypothesis C.2 (Encoding-uniform expander interface growth). For every permitted decider and encoding of a hard-instance family, there is a worst-case input whose *required* field trajectory incurs separator measure at least $c_0 2^{\gamma n}$ with constants independent of the algorithm.

Neither hypothesis follows merely from graph expansion or from counting disconnected truth assignments. An expander on $\Theta(n)$ vertices has only $O(n)$ edges at bounded degree; an exponential area bound requires an additional geometric embedding theorem with explicit distortion, domain volume, and feature-width controls.

Proposition C.1 (Conditional product of two lower bounds). Under the two hypotheses above, if the interface cost is incurred on at least one step of every admissible decider for a language L at input length n, then

$$\mathsf{C}_{\Theta,\mathfrak{W}}(L,n) \geq \kappa_0 c_0 2^{\gamma n}.$$

Proof. For each algorithm, take the hard input and the step specified in the hypotheses. Its per-state cost bounds the nonnegative trajectory sum. Finally take the infimum over the algorithms. □

Remark (WIN-06). Restricting attention to solvers that explicitly or implicitly *enumerate clause-signature sectors* yields only a lower bound for that solver subclass, unless every correct solver is independently proved to belong to it. Direct clause evaluation on a supplied assignment is a counterexample to an alleged need to enumerate satisfying assignments during verification.

C.2 Classical complexity implications

Proposition C.2 (Conditional bridge; no classical separation claimed). If one proved $P^{\mathrm{disc}}_{\mathrm{WCC}} = P$ and $NP^{\mathrm{disc}}_{\mathrm{WCC}} = NP$ for the *same* uniform discrete language classes, then a genuine separation of those *same* classes would imply $P \neq NP$. A separation only of a restricted physical class does not produce the latter conclusion without additional class-identification theorems. The discrete equalities do not preserve curvature energy by themselves.

Proof. Substitute the class identities when they refer to precisely the same classes. The second statement follows because changing the resource constraint changes the class being quantified over. □

C.3 Status of the proposed SAT curvature lower bound

The earlier locked-expander exponential estimate, gate-stencil upper bounds, and padding reductions require independent analytic proofs of uniform PDE existence, fixed readout margins, regularized-operator denominator control, encoding closure, and the universal interface property. They are not asserted as established results in this revision. The model remains available for such investigations, but a claimed general SAT lower bound or "non-natural, non-relativizing" resolution is premature.

D Wave Curvature Computation and Curvature–Bounded Complexity

D.1 Wave Curvature Computation Model

We model computation as the evolution of a confined wavefield ψ under curvature-regulated dynamics on a finite lattice. Let $\Lambda_n \subset \mathbb{Z}^d$ be a finite grid associated to input size n, and let

$$\mathrm{Conf}_n := \left\{\psi : \Lambda_n \to Cl_{1,3}\right\} \tag{8}$$

denote the configuration space, where $Cl_{1,3}$ is the spacetime algebra and $\psi(x)$ encodes a local multivector degree of freedom. Following Leary's GA encoding, classical bit strings are embedded into $Cl_{1,3}$–valued configurations by an injective map

$$\mathrm{Enc} : \{0,1\}^* \to \bigcup_{n\geq 1} \mathrm{Conf}_n, \qquad x \mapsto \psi_x, \tag{9}$$

where the logical value of each bit is represented by a choice of multivector component or rotor phase in a fixed subspace of $Cl_{1,3}$.

A *Wave Curvature Computation (WCC) machine* is a tuple

$$\mathcal{M} = (\{\Lambda_n\}_{n\geq 1}, U, \Theta, \mathcal{R}), \tag{10}$$

where:

- U is a local update operator implementing a discretized WCT evolution step
  $$U : \mathrm{Conf}_n \to \mathrm{Conf}_n, \qquad \psi^{t+1} = U(\psi^t),$$
  derived from the curvature-regularized Lagrangian $\mathcal{L}_{\mathrm{WCT}}$;
- $\Theta[\psi]$ is the WCT curvature operator (e.g. discrete Laplacian divided by $g(\psi)$);
- $\mathcal{R}$ is a set of *rails* (physical constraints) bounding curvature, entropy, and amplitude:
  $$E_{\mathrm{WCT}}[\psi^t] \leq K(n), \qquad \|\psi^t\| \leq B(n), \qquad t = 0, 1, \ldots, T(n),$$
  for some specified resource bounds $K(n)$, $B(n)$.

We write ψ_x^t for the configuration at time t on input x, and we assume that, after $T(n)$ steps, a distinguished cell or region encodes the output bit $f(x)$.

D.2 Semantic Curvature Complexity

For a Boolean function $f : \{0,1\}^* \to \{0,1\}$, we define its *semantic curvature complexity* with respect to a WCC model $\mathcal{M}$ as

$$C_\Theta^{\mathcal{M}}(f,n) := \inf_{\mathcal{M} \text{ computes } f} \sup_{|x|\le n} \sum_{t=0}^{T(n)} \Phi\big(\psi_x^t\big), \tag{11}$$

where Φ is the cumulative curvature functional

$$\Phi(\psi) := \sum_{y\in\Lambda_n} \Big(|\nabla\psi(y)|^2 + |\Theta[\psi](y)|^2 \Big)\, \Delta V, \tag{12}$$

and the infimum is taken over all WCC machines $\mathcal{M}$ that compute f on inputs of length at most n with acceptance/rejection determined by a fixed readout convention.

Thus $C_\Theta^{\mathcal{M}}(f,n)$ quantifies the minimal total curvature cost needed to realize f up to size n within the WCT dynamics. We regard a family $f = \{f_n\}$ as *curvature-efficient* if $C_\Theta^{\mathcal{M}}(f,n)$ grows at most polynomially in n, and *curvature-hard* if it requires super-polynomial growth in n for any $\mathcal{M}$.

D.3 Curvature-Bounded WCC Complexity Classes

We define curvature-bounded WCC analogues of P and NP.

Definition D.1 (Class $\mathrm{P}_{\mathrm{WCC}}$). A language $L \subseteq \{0,1\}^*$ lies in $\mathrm{P}_{\mathrm{WCC}}$ if there exists a WCC machine $\mathcal{M}$, a polynomial p, and a polynomial curvature bound K such that, for all x:

1. $\mathcal{M}$ halts on input x in at most $T(|x|) \le p(|x|)$ steps;
2. the curvature rails are respected: $E_{\mathrm{WCT}}[\psi_x^t] \le K(|x|)$ for all $t \le T(|x|)$;
3. the output cell encodes 1 iff $x \in L$.

Definition D.2 (Class $\mathrm{NP}_{\mathrm{WCC}}$). A language $L \subseteq \{0,1\}^*$ lies in $\mathrm{NP}_{\mathrm{WCC}}$ if there exists a polynomial q and a curvature-bounded WCC verifier $\mathcal{V}$ such that, for all x:

1. if $x \in L$ then there exists a *witness configuration* $\omega_x \in \mathrm{Conf}_{q(|x|)}$ (or equivalently a witness bitstring w with $|w| \le q(|x|)$ and associated GA encoding) such that $\mathcal{V}$ accepts (x, ω_x) in polynomially many steps and with polynomial curvature cost;

2. if $x \notin L$ then for all ω the verifier rejects (x, ω) under the same curvature rails.

In this framework, a *toroidal locking witness* for a 3-SAT instance is a curvature-locked configuration encoding a toroidal ψ–electron structure whose phase-locking and flux constraints correspond to the satisfaction of all clauses. Nonexistence of such a locking configuration is equivalent to unsatisfiability.

D.4 Discrete Equivalence with Classical P and NP

The following statements concern *uniform finite-state local-update* machines with polynomial lattice size and polynomially many updates; physical curvature budgets are *not* part of these definitions.

Definition D.3 (Uniform discrete WCC machine). A discrete WCC machine has a fixed finite alphabet S, fixed finite local interaction radius, fixed local update rule, and lattice $\Lambda_n \subset \mathbb{Z}^d$ of size $\mathrm{poly}(n)$. It additionally has a *uniform* polynomial-time procedure to generate the lattice and initialize the encoded input, and a uniform polynomial-time readout of a halted configuration. The rule and readout do not contain nonuniform advice or an oracle for the language being decided. Time counts all polynomial encoding and readout work as well as the local updates.

Theorem D.4 (Uniform discrete P equivalence). For the uniform discrete WCC model just defined, $P^{\mathrm{disc}}_{\mathrm{WCC}} = P$.

Proof. A deterministic Turing machine running in n^k steps touches at most $O(n^k)$ tape cells and is simulated by a fixed radius-one finite-state cellular rule using a constant number of local rounds per tape transition. The initial tape and final halt predicate are uniformly constructible. Conversely, a Turing machine can store a polynomial-size WCC configuration and simulate each of its polynomially many finite-radius rounds in polynomial time, including encoding and readout. Both transformations have polynomial overhead. □

Theorem D.5 (Uniform discrete NP equivalence). If $NP^{\mathrm{disc}}_{\mathrm{WCC}}$ is defined using polynomial-size witness strings and uniform polynomial-time discrete WCC verifiers, then $NP^{\mathrm{disc}}_{\mathrm{WCC}} = NP$.

Proof. Apply the two polynomial-overhead simulations to the *deterministic verifier* acting on each pair (x, w); existentially quantify only over witnesses of polynomial length. □

Remark (Physical resource bridge remains unproved). The existence of a finite-state cellular realization of a Turing machine is not a proof that a prescribed nonlinear PDE implements the same transitions while obeying polynomial WCT curvature energy, physical time, spectral bandwidth, and stability constraints. Thus no equality between $P^{\mathrm{phys}}_{\mathrm{WCC}}$ and $P^{\mathrm{disc}}_{\mathrm{WCC}}$, or between the corresponding NP classes, is derived by the above simulation theorems.

D.5 Curvature Blow-Up and Locked Expander Families: Open Obligation

WIN-06. The earlier suggested bound for solvers enumerating clause-signature sectors only concerns algorithms restricted to that form of search. No proof currently rules out deterministic algorithms that never enumerate those sectors. To establish a meaningful universal complexity bound, one must prove that *every* physical WCC decider for a well-specified language incurs superpolynomial curvature or time cost. The interface hypotheses in Section C are explicit candidates, not consequences of ordinary graph expansion.

D.6 Supplied-Assignment Language and Corrected Complexity Consequence

WIN-08. For a fixed uniformly polynomial-time constructible family of 3-CNF formulas F_n, consider

$$L^\star = \{(n, a) : a \in \{0,1\}^n \text{ and } F_n(a) = 1\}.$$

Theorem D.6 (Supplied-assignment membership is in P). If F_n has polynomial size and can be generated in polynomial time from an ordinary efficient encoding of n, then $L^\star \in P$ when input length accounts for the encoding and output assignment. The version with (F, a) explicitly supplied is also in P, without any uniformity condition on the formula family.

Proof. Generate F_n if needed, then evaluate its at most polynomially many clauses under the *supplied* assignment a. Checking each fixed-width clause takes polynomial time in the input length. For explicit (F, a), simply scan the clauses. No enumeration of candidate assignments occurs. □

The originally proposed language $L^\star$ therefore cannot be used to demonstrate a classical $NP \setminus P$ language. A physical curvature lower bound for a

highly constrained encoding of this verification task would measure an overhead of that physical implementation, not classical SAT search complexity.

D.7 Precise conditional physical separation template

Proposition D.7 (Conditional physical separation). Fix a language L (not a set of individual target fields) and a single physical resource accounting for both deterministic deciders and witness verifiers. Suppose:

1. there is a uniform polynomial-resource physical WCC verifier for (x, w) and some polynomial witness-length bound, with $x \in L \iff \exists w\, V(x, w) = 1$; and

2. for every uniform physical WCC deterministic decider M of L and every polynomial bound p, there are arbitrarily large input lengths n and inputs x of length n on which M exceeds $p(n)$ units of time or the specified curvature/energy resource.

Then $L \in NP^{\text{phys}}_{\text{WCC}} \setminus P^{\text{phys}}_{\text{WCC}}$.

Proof. The first premise is the definition of physical NP membership, and the second is the negation of physical polynomial-time membership for the same language and model. □

Remark. The proposition supplies a logical dependency, not a proof of its second premise. The quantifiers are asymptotic: the input threshold may depend on M and p. Requiring that *at a single fixed* n an execution exceed *every* polynomial bound would be impossible for a finite-energy finite-state run.

D.8 Part I repair register

Tag	Corrected status
WIN-01	Negated literal sign corrected.
WIN-02	OR clause penalty corrected to a product.
WIN-03	Logical satisfaction separated from PDE stationarity.
WIN-04	Invalid dimensional-lock inference replaced with a counterexample.
WIN-05	Internal separation explicitly conditional and language-level.
WIN-06	Search-restricted expander barrier not generalized to all solvers.
WIN-07	Universal curvature lower bound marked open; asymptotic quantifiers corrected.
WIN-08	Supplied-assignment language proved polynomial-time decidable.

D.9 Revision and Computational Review Note

Formatting, reference compilation, and structural consistency checks were performed with the assistance of automation tools, including ChatGPT, used solely for document preparation and stylistic review. All mathematical derivations, proofs, and theoretical conclusions are entirely the author's own.