

RedHat RHCSA and RHCE Certification Exam Study Ebook (\$35)

Get This Book 




.com

18 Tar Command Examples in Linux

# Setup Caching-Only DNS Server Using "Bind" in CentOS 6.5

by Babin Lonston | Published: September 20, 2014 | Last Updated: January 12, 2016

[DNS Bind](#)[Server Install](#)[Centos](#)

Download Your Free eBooks NOW - [10 Free Linux eBooks for Administrators](#) | [4 Free Shell Scripting eBooks](#)

There are several type of DNS servers such as master, slave, forwarding and cache, among them **Caching-Only DNS** is the one, which is easier to setup. DNS use UDP protocol so it will reduce the query time because UDP protocol does not have an acknowledgement.

**BEGINNER'S GUIDE FOR LINUX** 

Start learning Linux in minutes →

**Vi/Vim Editor BEGINNER'S GUIDE** 

Learn vi/vim as a Full Text Editor 

[RedHat RHCSA and RHCE Certification Exam Study Ebook \(\\$35\)](#)[Get This Book](#) 

## Setup Caching-Only DNS in CentOS 6.5

*Setup Caching-Only DNS in CentOS*

Read Also: [Setup Master-Slave DNS Server in CentOS 6.5](#)

The caching-only DNS server is also known as a resolver. It will query DNS records and get all DNS information from other servers and stores the each query request in its cache for later use. While we are querying same request for the second time, it will serve from its cache, this way it reduces query time.

If you're looking to setup DNS Caching-Only Server in CentOS/RHEL 7, follow this guide here:

[Setting Up Caching-Only DNS Name Server in CentOS/RHEL 7](#)

18 Tar Command Examples in Linux



 **Linux Foundation Certification**   
Exam Study Guide to **LFCS** and **LFCE**

```
IP Address      :      192.168.0.200
Host-name       :      dns.tecmintlocal.com
OS              :      Centos 6.5 Final
Ports Used      :      53
Config File     :      /etc/named.conf
script file     :      /etc/init.d/named
```

## Step 1: Installing Caching-Only DNS

1. The Caching-Only DNS, can be installed by using package 'bind'. Let's do a small search for the package name if we don't remember the full package name using below command.

```
# yum search bind
```



```

Loaded plugins: fastestmirror, security
Loading mirror speeds from cached hostfile
===== N/S Matched: bind =====
PackageKit-device-rebind.x86_64 : Device rebind functionality for PackageKit
bind.x86_64 : The Berkeley Internet Name Domain (BIND) DNS (Domain Name System)
: server
bind-chroot.x86_64 : A chroot runtime environment for the ISC BIND DNS server,
: named(8)
bind-devel.i686 : Header files and libraries needed for BIND DNS development
bind-devel.x86_64 : Header files and libraries needed for BIND DNS development
bind-dyndb-ldap.x86_64 : LDAP back-end plug-in for BIND
bind-libs.i686 : Libraries used by the BIND DNS packages
bind-libs.x86_64 : Libraries used by the BIND DNS packages
bind-sdb.x86_64 : BIND server with database backends and DLZ support

```

*Search Bind Package*

2. In the above result, you see the packages that displayed. From that we need to choose the 'bind' and 'bind-utils' packages, let's install them using following 'yum' command.

```
# yum install bind bind-utils -y
```

```

tecmin@dns:~
[tecmin@dns ~]$
[tecmin@dns ~]$ sudo yum install bind bind-utils -y
Loaded plugins: fastestmirror, security
Loading mirror speeds from cached hostfile
Setting up Install Process
Resolving Dependencies
--> Running transaction check
--> Package bind.x86_64 32:9.8.2-0.17.rc1.el6_4.6 will be installed
--> Package bind-utils.x86_64 32:9.8.2-0.17.rc1.el6_4.6 will be installed
--> Finished Dependency Resolution

```

*Install DNS Utils*

## Step 2: Configure Caching-Only DNS

---

Nagios 4.2.0 Released – Install on RHEL/CentOS 7.x/6.x/5.x and Fedora 24-19

---

Install Cacti (Network Monitoring) on RHEL/CentOS 7.x/6.x/5.x and Fedora 24-12

---

Google Chrome 59 Released – Install on RHEL/CentOS 7/6 and Fedora 25-20

---

How to Install Ubuntu 16.10/16.04 Alongside With Windows 10 or 8 in Dual-Boot

---

Tecmint's Guide to Red Hat RHCSA / RHCE Certification Preparation Study Guide

---

## RedHat RHCSA and RHCE Certification Exam Study Ebook (\$35)

Get This Book 

configure DNS. Open and edit `named.conf` file using vim editor.

```
# vim /etc/named.conf
```

4. Next, make changes as suggested below or you can use your settings as per your requirements. Following are the changes, that we need to do for a caching-only DNS server. Here, by default the **localhost** will be there, we need to add the **'any'** to accept query from any range of network.

```
listen-on port 53 { 127.0.0.1; any; };
allow-query      { localhost; any; };
allow-query-cache { localhost; any; };
```



0



0



9




The image shows the cover of a study guide for Red Hat RHCSA and RHCE certification exams. The cover is red with white text. At the top, it says 'tecmin' with a logo. Below that, it says 'Red Hat RHCSA/RHCE Certification Preparation Study Guide'. In the center, it says 'RedHat RHCSA / RHCE 7' and 'RHCSA (EX200) and RHCE (EX300) exams'. At the bottom, it says 'Buy Now \$35.00'.

Linux System Administrator Bundle  
with 7-Courses (96% off)

Add to Cart - \$69

🕒 Ending In: 3 days

Computer Hacker Professional  
Certification Course (96% Off)

18 Tar Command Examples in Linux

```
// Provided by Red Hat bind package to configure the ISC BIND named(8) DNS
// server as a caching only nameserver (as a localhost DNS resolver only).
//
// See /usr/share/doc/bind*/sample/ for example named configuration files.
//
options {
    listen-on port 53 { 127.0.0.1; any; };
    listen-on-v6 port 53 { ::1; };
    directory "/var/named";
    dump-file "/var/named/data/cache_dump.db";
    statistics-file "/var/named/data/named.stats.txt";
    memstatistics-file "/var/named/data/named.mem.stats.txt";
    allow-query { localhost; any; };
    allow-query-cache { localhost; any; };
    recursion yes;

    dnssec-enable yes;
    dnssec-validation yes;
    dnssec-lookaside auto;

    /* Path to ISC DLV key */
    bindkeys-file "/etc/named.iscdlv.key";

    managed-keys-directory "/var/named/dynamic";
};

logging {
    channel default_debug {
        file "data/named.run";
        severity dynamic;
    };
};

#zone "." IN {
#    type hint;
#    file "named.ca";
#};

include "/etc/named.rfc1912.zones";
include "/etc/named.root.key";

-- INSERT --
```

Configure Caching Only DNS

- **listen-on port 53** – This says that the cache server wants to use the port 53 for query.
- **allow-query** – This specifies which IP address may query the server, here I have defined for localhost, from anywhere anyone can send query.
- **allow-query-cache** – This will add the query request to the bind.

🕒 Ending In: 4 days

## LINUX EBOOKS

- Introducing Learn Linux In One Week and Go from Zero to Hero
- RedHat RHCE/RHCSA Certification Preparation Guide
- Linux Foundations LFCS/LFCE Certification Guide
- Postfix Mail Server Setup Guide for Linux
- Ansible Setup Guide for Linux
- Django Setup Guide for Linux
- Awk Getting Started Guide for Beginners
- Citrix XenServer Setup Guide for Linux



**Never Miss Any Linux Tutorials, Guides, Tips and Free eBooks**

Join Our Community Of **150,000+ Linux Lovers** and get a weekly newsletter in your inbox

**YES! SIGN ME UP**

during query it may send query to other DNS server over the internet and pull back the query.

5. After editing the file, we have to confirm whether the 'named.conf' files ownership was not changed from root:named, because the DNS runs under a system user named.

```
# ls -l /etc/named.conf
# ls -l /etc/named.rfc1912.zones
```

6. If the server enabled with selinux, after editing 'named.conf' file, we need to check for the selinux context, every named config files need to be in "system\_u:object\_r:named\_conf\_t:s0" context as shown in the image below.

```
# ls -lZ /etc/named.conf
# ls -lZ /etc/named.rfc1912.zones
```


Okay, here we need to test DNS configuration now for some syntax error, before starting the bind service, if any error found some can be traced from /var/messages too.

```
# named-checkconf /etc/named.conf
```



service to take effect for above changes and make the service to run persistent while reboot the server and confirm the same.

```
# /etc/init.d/named restart
# chkconfig named on
# chkconfig --list named
```

A terminal window titled 'tecmint@dns:~' showing a series of commands and their outputs. The commands are: 1. 'ls -l /etc/named.conf' showing file permissions and ownership. 2. 'ls -l /etc/named.rfc1912.zones' showing file permissions and ownership. 3. 'ls -lZ /etc/named.conf' showing SELinux context. 4. 'ls -lZ /etc/named.rfc1912.zones' showing SELinux context. 5. 'sudo named-checkconf /etc/named.conf' showing successful configuration check. 6. 'sudo /etc/init.d/named restart' showing the service stopping and starting successfully. 7. 'sudo chkconfig named on' showing the service is set to start on boot. 8. 'chkconfig --list named' showing the service is enabled at all runlevels except 0, 1, and 6.

```
tecmint@dns:~$ ls -l /etc/named.conf
-rw-r----- 1 root named 1061 Sep  3 18:41 /etc/named.conf
tecmint@dns:~$ ls -l /etc/named.rfc1912.zones
-rw-r----- 1 root named 931 Jun 21 2007 /etc/named.rfc1912.zones
tecmint@dns:~$ ls -lZ /etc/named.conf
-rw-r----- . root named system_u:object_r:named_conf_t:s0 /etc/named.conf
tecmint@dns:~$ ls -lZ /etc/named.rfc1912.zones
-rw-r----- . root named system_u:object_r:named_conf_t:s0 /etc/named.rfc1912.zones
tecmint@dns:~$ sudo named-checkconf /etc/named.conf
tecmint@dns:~$ sudo /etc/init.d/named restart
Stopping named: [ OK ]
Starting named: [ OK ]
tecmint@dns:~$ sudo chkconfig named on
tecmint@dns:~$ chkconfig --list named
named 0:off 1:off 2:on 3:on 4:on 5:on 6:off
tecmint@dns:~$
```

*Configure and Start DNS*

7. Next, open the port 53 on the firewall to allow the access.

```
# iptables -I INPUT -p udp --dport 53 -j ACCEPT
```

```
[tecmin@dns ~]$ sudo iptables -I INPUT -p udp --port 53 -j ACCEPT
[tecmin@dns ~]$ sudo iptables -L INPUT
Chain INPUT (policy ACCEPT)
target prot opt source destination
ACCEPT udp -- anywhere anywhere udp dpt:domain
[tecmin@dns ~]$
[tecmin@dns ~]$
```

*Iptables Open DNS Port*

## Step 4: Chroot Caching-Only DNS

8. If you want to run the DNS caching-server under **chroot** environment, you need to install the **chroot** package only, no need of further configuration, as it by default hard-link to chroot.

```
# yum install bind-chroot -y
```

Once **chroot** package has been installed, you can restart the named service to take new changes.

```
# /etc/init.d/named restart
```

9. Once you restart named service, it automatically create a hard-link from the **/etc/named** config files to **/var/named/chroot/etc/** directory. To confirm, just use the **cat**

command under **/var/named/chroot.**

18 Tar Command Examples in Linux

```
tecmin@dns:~$ sudo cat /var/named/chroot/etc/named.conf
//
// named.conf
//
// Provided by Red Hat bind package to configure the ISC BIND named(8) DNS
// server as a caching only nameserver (as a localhost DNS resolver only).
//
// See /usr/share/doc/bind*/sample/ for example named configuration files.
//
options {
    listen-on port 53 { 127.0.0.1; any; };
    listen-on-v6 port 53 { ::1; };
    directory "/var/named";
    dump-file "/var/named/data/cache_dump.db";
    statistics-file "/var/named/data/named_stats.txt";
    memstatistics-file "/var/named/data/named_mem_stats.txt";
    allow-query { localhost; any; };
    allow-query-cache { localhost; any; };
    recursion yes;

    dnssec-enable yes;
    dnssec-validation yes;
    dnssec-lookaside auto;

    /* Path to ISC DLV key */
    bindkeys-file "/etc/named.iscdlv.key";

    managed-keys-directory "/var/named/dynamic";
};

logging {
    channel default_debug {
        file "data/named.run";
        severity dynamic;
    };
};

#zone "." IN {
#    type hint;
#    file "named.ca";
#};

include "/etc/named.rfc1912.zones";
include "/etc/named.root.key";
tecmin@dns:~$
```

*Chroot Caching Only DNS*

In the above configuration, you will see the same `/etc/named.conf` configuration, as it will be replaced while installing `bind-chroot` package.

## Step 5: Client Side DNS Setup

18 Tar Command Examples in Linux

to the client machines.

In **Debian** based machines it will be under **/etc/resolv.conf** and in RPM based machines it will be under **setup** command or we can edit manually under **/etc/sysconfig/network-scripts/ifcfg-eth0** file.

11. Finally it's time to check our cache server using some tools. We can test using **dig** & **nslookup** commands in Linux systems, and in windows you can use the **nslookup** command.

Let's query '**facebook.com**' for first time, so that it will cache its query.

```
# dig facebook.com
```

```
[tecmint@dns ~]$ dig facebook.com

; <<>> DiG 9.8.2rc1-RedHat-9.8.2-0.17.rc1.el6_4.6 <<>> facebook.com
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 61554
;; flags: qr rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 2, ADDITIONAL: 2

;; QUESTION SECTION:
;facebook.com.                IN      A

;; ANSWER SECTION:
facebook.com.                900     IN      A      173.252.110.27

;; AUTHORITY SECTION:
facebook.com.                172799  IN      NS      a.ns.facebook.com.
facebook.com.                172799  IN      NS      b.ns.facebook.com.

;; ADDITIONAL SECTION:
a.ns.facebook.com.          172799  IN      A      69.171.239.12
b.ns.facebook.com.          172799  IN      A      69.171.255.12

;; Query time: 1294 msec
;; SERVER: 192.168.0.200#53(192.168.0.200)
;; WHEN: Thu Sep  4 04:33:02 2014
;; MSG SIZE rcvd: 113
```

*Check DNS using Dig*

Now, issue again same query, you will get replied from our cache server till it expires.

```
# dig facebook.com
```

```
; <<>> DiG 9.8.2rc1-RedHat-9.8.2-0.17.rc1.el6_4.6 <<>> facebook.com
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 15311
;; flags: qr rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 2, ADDITIONAL: 2

;; QUESTION SECTION:
;facebook.com.                IN      A

;; ANSWER SECTION:
facebook.com.                 898     IN      A      173.252.110.27

;; AUTHORITY SECTION:
facebook.com.                 172797  IN      NS      a.ns.facebook.com.
facebook.com.                 172797  IN      NS      b.ns.facebook.com.

;; ADDITIONAL SECTION:
a.ns.facebook.com.           172797  IN      A      69.171.239.12
b.ns.facebook.com.           172797  IN      A      69.171.255.12

;; Query time: 0 msec
;; SERVER: 192.168.0.200#53(192.168.0.200)
;; WHEN: Thu Sep  4 04:33:04 2014
;; MSG SIZE rcvd: 113

[tecmint@dns ~]$
```

*Check DNS Cache*

Use 'nslookup' command to confirm the same.

```
# nslookup facebook.com
```

### *Check DNS Query Cache*

To read more about dig and nslookup command examples and usage, use the following links.

- [8 nslookup commands and usage](#)
- [10 dig commands and usage](#)

Here we have seen how successfully we have setup a DNS caching-only server using bind package and also secured it using chroot package.

## If You Appreciate What We Do Here On TecMint, You Should Consider:

1. Stay Connected to: [Twitter](#) | [Facebook](#) | [Google Plus](#)
2. Subscribe to our email updates: [Sign Up Now](#)
3. Get your own [self-hosted blog with a Free Domain](#) at (\$3.95/month).
4. Become a Supporter - [Make a contribution via PayPal](#)
5. Support us by [purchasing our premium books](#) in PDF format.
6. Support us by taking our [online Linux courses](#)

We are thankful for your never ending support.

Tags: [bind](#) [chroot](#)

**Babin Lonston**

[View all Posts](#)

I'm Working as a System Administrator for last 10 year's

with 4 years experience with Linux Distributions, can provide example

18 Tar Command Examples in Linux



RedHat RHCSA and RHCE Certification Exam Study Ebook (\$35)

Get This Book 

Your name can also be listed here. Got a tip? [Submit it here](#) to become an TecMint author.



PREVIOUS STORY

← Phabricator – An Open Source Powerful “Project Management” Tool for Linux


NEXT STORY

Installing SHOUTCast Radio Server (Online Media Streaming) on Linux →

 YOU MAY ALSO LIKE...

**PowerDNS**  11

Install PowerDNS with MariaDB and PowerAdmin in RHEL/CentOS 7



3

◀ 10

18 Tar Command Examples in Linux

RedHat RHCSA and RHCE Certification Exam Study Ebook (\$35)

Get This Book 

Configure PowerDNS  
(with MariaDB) and  
'PowerAdmin' in  
RHEL/CentOS 7

1 MAY, 2015


Configure Caching-Only  
DNS Server' with  
'Unbound' in  
RHEL/CentOS 7

8 DEC, 2014

Install and Configure  
Caching-Only DNS  
Server in RHEL/CentOS  
7 – Part 10

12 JAN, 2016


## 7 RESPONSES

 **Comments** 7  **Pingbacks** 0

**vinci**  December 1, 2015 at 4:04 pm

Why is the zone "." root hints and the rest of the lines commented out? Isn't the dns cache server supposed to search recursively, meaning to start with the root hints and then go downwards until it finds the domain? If you comment out the root hints zone, how is it supposed to do that? It would need a forwarders directive.

Reply

**Nero**  December 1, 2015 at 2:36 pm

thanks for the great info on setting the caching only dns server up with bind! I was trying to set up with both unbound on one server and bind on another and this was just what I needed. Unbound seems to not be used as much yet, maybe

18 Tar Command Examples in Linux

<https://www.rootusers.com/how-to-configure-a-caching-only-dns-name-server/>

<https://www.digitalocean.com/community/tutorials/how-to-set-up-the-unbound-caching-dns-resolver-on-freebsd-10-1>

Good luck!

Reply

**jhalbrecht** ☉ June 23, 2015 at 8:56 pm

Would/should this configuration be locked down tighter perhaps with an acl that would disallow access to the nameserver from unauthorized/unwanted clients that might attempt to exploit for a DOS attack on another site?

Your config:

```
allow-query { localhost; any; };  
allow-query-cache { localhost; any; };
```

Suggestion:

```
allow-query { friends; };
```

```
acl friends {  
192.168.0/24;  
localhost;  
localnets;  
};
```

Reply

**Giang** ☉ September 28, 2014 at 9:20 pm

how greate! Thank u so much.

Reply

**Babin Lonston** ☉ September 25, 2014 at 7:20 pm

You can use Webmin to manage in GUI, Using Webmin we can manage full server not only DNS.

Reply

**RedHat RHCSA and RHCE Certification Exam Study Ebook (\$35)**[Get This Book](#) 

NICE article, thanks for sharing, is there any option to manage DNS in GUI instead of TUI... any open source tools which could be integrated with this and for the Master/Slave DNS setup??

Reply

**Babin Lonston**  August 5, 2015 at 9:24 pm

@ Vinodh You can use Webmin..

Reply

**GOT SOMETHING TO SAY? JOIN THE DISCUSSION.****Comment****Name \*****Email \*****Website**☐

Notify me of followup comments via e-mail. You can also [subscribe](#) without commenting.

**Post Comment**

18 Tar Command Examples in Linux

**LINUX MONITORING TOOLS**

nload – Monitor Linux Network Bandwidth Usage in Real Time

---

Web VMStat: A Real Time System Statistics (Memory, CPU, Processes, etc) Monitoring Tool for Linux

---

Lynis 2.2.0 Released – Security Auditing and Scanning Tool for Linux Systems

---

Petiti – An Open Source Log Analysis Tool for Linux SysAdmins

---

pyDash – A Web Based Linux Performance Monitoring Tool

---

**LINUX INTERVIEW QUESTIONS**

11 Advance MySQL Database "Interview Questions and Answers" for Linux Users

---

10 Advance VsFTP Interview Questions and Answers – Part II

---

15 Basic MySQL Interview Questions for Database Administrators

---

Shilpa Nair Shares Her Interview Experience on RedHat Linux Package Management

---

10 Useful Interview Questions and Answers on Linux Commands

---

**OPEN SOURCE TOOLS**

6 Best PDF Page Cropping Tools For Linux

---

12 Open Source Cloud Storage Software to Store and Sync Your Data Quickly and Safely

---

8 Best PDF Document Viewers for Linux Systems

---

9 Best Twitter Clients for Linux That You Will Love to Use

---

12 Best Open Source Text Editors (GUI + CLI) I Found in 2015

---

[RedHat RHCSA and RHCE Certification Exam Study Ebook \(\\$35\)](#)[Get This Book](#) 

Tecmint: Linux Howtos, Tutorials & Guides © 2017. All Rights Reserved.

This work is licensed under a (cc) BY-NC

The material in this site cannot be republished either online or offline,  
without our permission.

