

Products: RYANFIRE MASTIC

Approvals: AS 1530.4/AS 4072.1

BK:

Ref: FRT 200058

ID:

Scenario: Ryanfire Mastic cone seal to

copper pipe

Services: Ø65mm copper pipe

Ø115mm Aperture:

116mm fire rated Construction:

plasterboard wall

Fire Integrity: 60 minutes Fire Insulation: 15 minutes

Web based drawings are for example only, fire performance of any system is dependant on, but not limited to size of opening, substrate, if penetrations are passing through, type, size and number. Please refer to Ryanfire technical department for detailed and specific fire performance information.



Client

Job Title

Mastic cone to copper pipe 116mm plasterboard wall

	Scale	Date	
	NTS	October 2020	
	Sheet Size	Drawn By	
	A3		
	Drawing Number		Rev

Please note: Ryanfire Products Ltd owns and has copyright in these drawings. They are to be used only for the purpose for which they were intended and supplied and are not to be sold, transferred or made available for use by a third party.

legal proceedings.

INSTALLATION INSTRUCTIONS

INSTALLATION.

PLASTERBOARD.

CLOTH.

1. ENSURE THE APERTURE IS CLEAN AND FREE OF

WIDE, PLUS THE DEPTH OF THE FIRE RATED

Any misuse of these drawings will result in

All errors and omissions excepted - the Information contained within this drawing is believed to be correct on the date of publication, and is based upon tested and certified solutions. The policy of RyanFire Products Ltd is one of constant improvement. Installers must therefore ensure that they are following the latest published drawings, test evidence and instructions. Whilst RyanFire Products Ltd will endeavour to keep its publications up to date, the accuracy of the information contained within this drawing may be affected by pertinent changes in the law or regulatory requirements and alterations or amendments to the specification of the manufactured products. Terms and conditions of sale apply.

RYANFIRE Technical Support: info@ryanfire.co.nz - Tel 09 443 0362

V1.6

2.0