

COMP 2402 Class Notes

Java Collections Framework (JCF)

The Java Collections Framework (JCF) is a unified architecture for representing and manipulating collections.

A collection – sometimes called a container – is simply an object that groups multiple elements into a single unit. Collections are used to store, retrieve, manipulate, and communicate aggregate data. Typically, they represent data items that form a natural group, such as a poker hand (a collection of cards), a mail folder (a collection of letters), or a telephone directory (a mapping of names to phone numbers). If you have used the Java programming language – or just about any other programming language – you are already familiar with collections.

In order to use the JCF you can import it like this.

```
import java.util.*
```

Sorting

This is how to sort strings based on length by using anonymous object [Comparator].

```
Collections.sort(list, new Comparator<String>() {  
    public int compare(String x, String y) {  
        return x.length() - y.length();  
    }  
})
```

```
});
```

The **compare(x,y)** method works by moving an element left if the **compare(x,y)** method returns a negative integer, and moves the element right if the **compare(x,y)** returns a positive integer. [difference between x and y]

```
(-) x < y  
(0) x = y  
(+) x > y
```

Maps [Haskhap]

Also known as dictionaries in Swift or C#...

```
Map<String, Integer> map = new HashMap<>();  
map.put("Java", 6);  
map.put("Swift", 10);  
map.put("C#", 7);  
map.put("Ruby", 9);  
  
// this will print out every value in the map [foreach]  
for(String str : map.keySet()) {  
    System.out.println(str + " : " + map.get(str))  
}  
  
map.get(key); // fast operation, returns null if no key  
found
```

List

Continuing from previous example

```
List<Map.Entry<String,Integer>> entryList = new  
ArrayList<>();  
entryList.addAll(map.entrySet()); // set containing all  
the elements  
  
for(Map.Entry<String,Integer> entry : entrylist) {  
    System.out.println(entry.getKey() + " : " +  
entry.getValue() );  
}
```

Deque [ArrayDeque]

Fast for reading/writing at *start* or *end* of list. Basically just a flexible stack/queue.

```
Deque<String> dq = new ArrayDeque<>();  
dq.addFirst("second");  
dq.addFirst("first");  
dq.addLast("penultimate");  
dq.addLast("last");
```

Linked Lists

Good for insertion/modification [*add/remove*]

Bad for random access

Priority Queue

Essentially: uses a heap instead of a tree, in order to keep a certain one on top (?).

Not good for sorting, or random access.

```
Queue<String> pq = new PriorityQueue<>();  
pq.addAll(list);  
  
System.out.println(pq.remove());    // remove smallest  
element
```

If alphabetical, one that starts with 'a' will be removed. After first element, the queue is not sorted. Removing one will promote next smallest to the top

Asymptotic Notation [Big O]

Used to analyze complexity of algorithms, to find faster, or which ones requires more space.

Comparing data structures

- Time
- Space
- Correctiveness

Growth rates proportiona to n

- If input doubles in size, how much will runtime increase?

Runtime as a count of primitive operation

- This is machine independent
- Proportional to exact runtime

```
for(int i = 0; i < n; i++) {  
    arr[i] = i;  
}
```

Runtime:

- **1**: assignment [int i = 0]
- **n+1**: comparisons [i < n]
- **n**: increments [i++]
- **n**: array offset calculations [arr[i]]
- **n**: n indirect assignments [arr[i] = i]

Definition of Big O

After a certain point, $g(x)$ will grow as fast [or faster] than $f(x)$


- $g(x)$ is the upper limit to $f(x)$

$$O(g(n)) \forall (f(n) < c \bullet g(n))$$

Orders of growth

Complexity	Name
$O(1)$	Constant
$O(\log n)$	Logarithmic
$O(n)$	Linear
$O(n \log n)$	Quasilinear
$O(n^2)$	Quasilinear
$O(2^n)$	Exponential
$O(n!)$	Factorial

Big-O Complexity Chart



Tips

- Only largest values matter
- Drop all coefficient
- Log bases are all equivalent

Example

```
public class BigO {
    public static void main() {
        String str = "";
        int n = 100;    // O(1)

        for(int i = 0; i < n; i++) {    // O(n)
            str += "x";    // O(1) but n times
        }

        for(int i = 0; i < n; i+=2) {    // n/2 times -
            str += "y"    // O(1)
        }
    }
}
```

> O(n)

```

        // this is roughly the same as if n was n/2
with 0(n)
    for(int i = 0; i < n; i*=2) {    // 0(log n)
        str += "y"                // 0(1)
    }
}
}

```

Array-based Data Structures

ArrayStack

- List interface implemented with an array
- Similar to ArrayList
- Efficient only for stack operations
 - Add/remove last

Stacks vs List

Stack	List
push(x)	add(n,x)
pop()	remove(n-1)
size()	size()
peek(x)	get(n-1)

List Interface

- get(i) / set(i,x)
 - Access element i, and return/replace it
- size()
 - number of items in list
- add(i,x)
 - insert new item x at position i

- remove(i)
 - remove the element from position i

dereferencing: getting the address of a data item