T-SQL Select Star

```
SELECT TOP 3 first_name, last_name, last_statement
FROM dbo.tx_deathrow;

SELECT top 3 first_name FROM dbo.tx_deathrow

SELECT 50 / 2, 51 / 2

SELECT first_name, last_name, Age_at_Execution
FROM dbo.tx_deathrow WHERE Age_at_Execution <= 25

SELECT first_name, last_name, Execution
FROM dbo.tx_deathrow
WHERE first_name = 'Raymond'
  AND last_name LIKE '%Landry%'

SELECT last_statement
FROM dbo.tx_deathrow
WHERE first_name = 'Napoleon'
  AND last_name = 'Beazley';

SELECT COUNT(last_statement)
FROM dbo.tx_deathrow

SELECT COUNT(Execution)
FROM dbo.tx_deathrow

SELECT
    SUM(CASE WHEN county = 'Harris' THEN 1 ELSE 0 END) AS Harris_Count,
    SUM(CASE WHEN county = 'Bexar'  THEN 1 ELSE 0 END) AS Bexar_Count
FROM dbo.tx_deathrow;

SELECT COUNT(*)
FROM dbo.tx_deathrow
WHERE Age_at_Execution > 50;

SELECT COUNT(*) FROM dbo.tx_deathrow WHERE last_statement IS NULL

SELECT MIN(Age_at_Execution), MAX(Age_at_Execution), AVG(Age_at_Execution) FROM
dbo.tx_deathrow

SELECT AVG(LEN(last_statement)) FROM dbo.tx_deathrow

SELECT DISTINCT county
FROM dbo.tx_deathrow
```

```sql
SELECT
    1.0 * COUNT(CASE WHEN last_statement LIKE '%innocent%' THEN 1 END) / COUNT(*) AS
InnocentRatio
FROM dbo.tx_deathrow;

SELECT
    CASE WHEN last_statement IS NOT NULL THEN 1 ELSE 0 END AS has_last_statement,
    county,
    COUNT(*) AS num_executions
FROM dbo.tx_deathrow
GROUP BY
    CASE WHEN last_statement IS NOT NULL THEN 1 ELSE 0 END,
    county;

SELECT county, COUNT(*)
FROM dbo.tx_deathrow
WHERE Age_at_Execution >= 50
GROUP BY County

SELECT county
FROM dbo.tx_deathrow
WHERE Age_at_Execution >= 50
GROUP BY county
HAVING COUNT(*) > 2

SELECT county FROM dbo.tx_deathrow
GROUP BY County;

SELECT first_name, last_name
FROM dbo.tx_deathrow
WHERE LEN(last_statement) = (
    SELECT MAX(LEN(last_statement))
    FROM dbo.tx_deathrow);

SELECT county,
 100.0 * COUNT(*) / (SELECT COUNT(*) FROM dbo.tx_deathrow) AS percentage
FROM dbo.tx_deathrow
GROUP BY county
ORDER BY percentage DESC;

SELECT DATEDIFF(DAY, '1989-07-07', '1993-08-10') AS day_difference;

SELECT Execution + 1 AS ex_number,
  Execution_Date AS last_ex_date
FROM dbo.tx_deathrow
WHERE Execution < 553
```

```sql
SELECT
    previous.last_ex_date AS start_date,
    Execution_Date AS end_date,
    DATEDIFF(DAY, previous.last_ex_date, Execution_Date) AS day_difference
FROM dbo.tx_deathrow AS e
JOIN (
    SELECT
        Execution + 1 AS ex_number,
        Execution_Date AS last_ex_date
    FROM dbo.tx_deathrow
) AS previous
    ON Execution = previous.ex_number
ORDER BY day_difference DESC
OFFSET 0 ROWS FETCH NEXT 10 ROWS ONLY;

SELECT
    p.Execution_Date AS start_date,
    e.Execution_Date AS end_date,
    DATEDIFF(DAY, p.Execution_Date, e.Execution_Date) AS day_difference
FROM dbo.tx_deathrow AS e
JOIN dbo.tx_deathrow AS p
    ON e.Execution = p.Execution + 1
ORDER BY day_difference DESC
OFFSET 0 ROWS FETCH NEXT 10 ROWS ONLY;
```