DO OPEN-WEIGHT LANGUAGE MODELS REPRODUCE RACIAL AND SEX DISPARITIES IN PAIN ASSESSMENT? A COUNTERFACTUAL AUDIT WITH EXPLICIT AND NAME-BASED CUES

Richard J. Young
Lee Business School, Information Systems
University of Nevada, Las Vegas
Las Vegas, NV, USA
ryoung@unlv.edu

Alice M. Matthews
DeepNeuro.ai
Las Vegas, NV, USA
alice@deepneuro.ai

ABSTRACT

Racial and ethnic minority patients receive less treatment for pain than non-Hispanic White patients, and large language models (LLMs) could reproduce that disparity when asked to assess pain. Prior audits tested a few proprietary models, stated the patient's race explicitly and rarely measured the models' own response instability. In exploratory, non-preregistered analyses, Study 1 had four open-weight models assess six acute-pain vignettes in every combination of four races and two sexes, with identity stated or cued only by a name (two names per group), comparing each identity with a White male reference on the same case and sampling seed. In Study 2, 24 configurations of 17 proprietary and open-weight models, with reasoning on and off and at two precisions, answered the same vignettes and the 50 clinician-written Q-Pain cases, with the case as the unit of analysis. In this single-prompt, JSON-constrained task, no difference survived correction in Study 1, none of 1,386 comparisons survived the false discovery rate in Study 2, and every severity difference was equivalent to zero within one point on a 0–10 scale (within a quarter point for 237 of 238 Q-Pain comparisons). Opioid decisions were bounded less precisely (Study 1 could not exclude differences of about 20 percentage points), so they show no detected difference, not proof of none. The few differences that survived correction within a model favoured Black patients. Models differed far more from one another and across their own settings than between patients (the reference patient received the high dose in 6% to 93% of responses), although serving software, provider and prompt format also differed. Audits should use several names per group, pair comparisons on the seed, report the noise floor and test each deployed configuration.

Keywords Large Language Models · Pain Assessment · Racial Bias · Sex Bias · Counterfactual Fairness · Open-Weight Models · Algorithmic Auditing · Clinical NLP

1 Introduction

Pain has no objective marker, so its assessment depends on how a clinician interprets a patient's report and behaviour, and that interpretation is not neutral. Racial and ethnic minority patients are undertreated for pain relative to non-Hispanic White patients across experimental, post-operative, cancer and chronic pain and in the emergency department [1, 2], a disparity that a meta-analysis of twenty years of United States evidence found across settings and pain types [3] and that emergency-department data confirmed for opioid prescribing [4]. The disparity has a cognitive substrate: half of a sample of White medical students and residents endorsed false beliefs about biological differences between Black and White people, and those who did rated a Black patient's pain lower [5]. Large language models (LLMs) now encode clinical knowledge at a level that invites deployment [6, 7], are being evaluated across a widening range of clinical tasks [8], and are being embedded in documentation, triage and decision-support tools. A commercial risk algorithm has already been shown to reproduce racial bias at the scale of millions of patients [9]. A language model that

learned its clinical judgement from text produced by a system with documented disparities may carry those disparities into every encounter it touches, at scale and without the variability that lets an individual clinician's bias be noticed.

The evidence on whether LLMs do so is mixed and tracks model generation. Q-Pain, a question-answering dataset for social bias in pain management, found statistically significant differences in treatment between intersectional race–gender subgroups for GPT-2 and GPT-3 [10]. Commercial models of 2023 reproduced race-based medical misconceptions and answered the same question inconsistently on repetition [11]; GPT-4 generated demographically stereotyped clinical vignettes [12]; GPT-3.5 and GPT-4 projected higher costs and longer hospitalisations for White patients from real cases [13]; and systematic and scoping reviews of 38 and 92 studies respectively describe bias as pervasive across clinical applications [14, 15]. Direct pain assessment by current proprietary models looks different. When Young et al. presented GPT-4 and Gemini with 40 real cases from MIMIC-IV in every race/ethnicity and sex combination, race/ethnicity and sex did not influence pain ratings or opioid recommendations [16]. That is not true of every pain setting, as the older models of Q-Pain and an adversarial palliative-care benchmark that probed pain management show [10, 17]. Counterfactual audits of emergency triage, meanwhile, have found large gender-swap flip rates in proprietary models [18] (a study by the present authors, unrelated to the Young et al. group above), sensitivity to stigmatising language in a single sentence [19], and, in an outcome-grounded design, harmful reprioritisation from psychiatric history, homelessness and substance use but not from race, language or insurance status [20]. Two methodological results frame all of these: a model changes its own answer when the prompt is re-run unchanged, even under nominally deterministic settings [21, 22], and that instability floor must be measured before a counterfactual difference can be read as bias [23]. The multilingual PAINT resource states the question that remains open: whether LLMs reproduce known disparities in pain assessment [24].

Four gaps limit what that literature can say. First, every pain audit tested proprietary models reached through an API, whereas hospitals increasingly run open-weight models on their own hardware for privacy and cost [25]; open-source models have been audited for triage [26] and diagnosis [27], but not for pain. Second, every pain audit announced the patient's race and sex explicitly. Instruction-tuned models are trained to respond carefully to protected attributes [28], so an explicit label may trigger a guarded response that an indirect cue would not, and different cues for the same group have been shown to yield inconsistent conclusions about bias, in both magnitude and direction [29]. In real notes, demographic signal often arrives through a name, and name-based audits outside medicine consistently find that models disadvantage names associated with racial minorities and women [30, 31, 32, 33], as human employers did in the original correspondence audits [34]. No pain audit has used name cues. Third, where names have been used, one name per group leaves a name's idiosyncrasy indistinguishable from a group effect, and a recent preregistered audit found that the audit instrument itself can produce effects as large as the demographic bias under test [35]. Fourth, few audits report how often a model changes its own answer when nothing changes, so a measured difference has no baseline against which to be judged.

This study addresses the first three gaps and supplies the fourth with counterfactual vignette audits [36] that vary four races and two sexes while holding every other token of the prompt fixed: of four open-weight models on six acute-pain cases (Study 1), and of a wider panel of local and API-served models on those cases and on the 50 clinician-written Q-Pain cases (Study 2). The primary purpose was to determine whether open-weight models reproduce the human disparity when race and sex are stated explicitly. Hypothesis 1 (H1), following the null result of Young et al. [16], predicted that explicit labels would not change pain-severity ratings or strong-opioid recommendations. The secondary purpose was to test whether indirect cues reveal a disparity that explicit labels mask. Hypothesis 2 (H2) predicted that when identity was cued only by the patient's name, models would rate pain lower and recommend strong opioids less often for patients with non-White names, and with Black and Hispanic names in particular, than for patients with White male names. No hypothesis concerned sex, because the human evidence on sex is less uniform than on race (Section 2); the woman minus man contrasts are reported as exploratory, with the human finding of less opioid analgesia for women in emergency care as the direction to watch. A third purpose, addressed by Study 2 without a directional hypothesis, was to establish whether the answer depends on the cases or the models chosen: whether it holds on clinician-written cases, for proprietary models and for open-weight models from 3 billion parameters to mixture-of-experts models of several hundred billion, with reasoning switched on as well as off, and at 16-bit as well as 4-bit precision. Every comparison was paired on the same case and sampling seed, tested with bootstrap intervals and permutation tests, corrected for multiple comparisons, and set against the model's own re-sampling noise floor.

2 Related Work

2.1 Disparities in human pain care

A consensus review assembled evidence that racial and ethnic minorities are undertreated for pain across pain types (experimental, acute post-operative, cancer, chronic non-malignant) and settings, including the emergency department,

and attributed the pattern to patient, provider and system factors [1]; a later review traced its causes and consequences [2], and a meta-analysis synthesised twenty years of United States studies on analgesic treatment by race and ethnicity, examining the moderating effect of pain type, setting and study period [3]. Emergency-department opioid prescribing rose after the quality initiatives of the late 1990s, but non-Hispanic White patients remained more likely to receive an opioid than other groups [4]. Hoffman et al. supplied a mechanism: false beliefs about biological differences between Black and White people, endorsed by half of a sample of White medical trainees, predicted lower pain ratings and less accurate treatment recommendations for Black patients [5]. The human evidence on sex is less uniform. In a prospective emergency-department cohort with similar pain scores, women were less likely than men to receive any analgesia (60% against 67%) or an opioid (45% against 56%) and waited longer [37]; in a vignette study of simulated low-back-pain patients, female patients received higher antidepressant and mental-health referral ratings than male patients, but only from female providers [38]. A review of recent findings describes substantial sex differences in clinical and experimental pain, with inconsistent findings on responses to treatment [39], and a review of 77 articles identified gendered norms and gender bias in the treatment of pain [40]. This literature defines the disparity an LLM might inherit from clinical and lay text, namely lower assessed severity and less potent analgesia for the same presentation. For race it fixes the direction that H2 predicts; for sex it points in no single direction, and neither hypothesis concerned it.

2.2 Language-model audits in pain management

Q-Pain introduced a dataset and an experimental framework for measuring social bias in pain-management question answering and, applying it to GPT-2 and GPT-3, found statistically significant treatment differences between intersectional race–gender subgroups [10]. Those models predate instruction tuning and alignment, so the result establishes that the disparity is learnable from text, not that current systems exhibit it. Young et al. brought the design to GPT-4 and Gemini with 40 MIMIC-IV cases of abdominal, back, headache and musculoskeletal pain, amended to every race/ethnicity and sex combination (480 cases per model), and found that race/ethnicity and sex did not influence subjective pain rating, opioid name, order or dosage, although the two models differed from each other in severity rating and strong-opioid use [16]; a subsequent letter proposed comparing inference-tuned models with pretrained LLMs in this setting [41]. In palliative care, where pain management was one of four care dimensions probed, GPT-4o produced expert-rated bias in a third of adversarial responses [17]. Three features of the Young et al. study motivate the present one: it tested proprietary models whose weights and updates are outside the auditor's control; it stated race and sex explicitly; and its univariate analyses did not pair responses on a sampling seed or report a within-condition instability baseline, so the size of a difference that could have been detected is unknown. The PAINT resource, with clinician-validated pain and demographic annotations in four languages, names the question as open [24].

2.3 Demographic bias audits of clinical language models

Beyond pain, the audits are numerous and largely concordant in finding bias, but they differ in what they measure. Omiye et al. asked four commercial LLMs nine questions probing race-based medical misconceptions, five times each, and found that every model produced examples of debunked race-based medicine and answered inconsistently across repetitions [11]. Zack et al. evaluated GPT-4 across medical education, diagnostic reasoning, clinical plan generation and subjective patient assessment and found that it did not model the demographic diversity of conditions and generated stereotyped vignettes [12]. Hanna et al. fed 100 de-identified encounters of patients with HIV to ChatGPT four times, varying only race/ethnicity, and compared the generated text by sentiment, subjectivity and reading ease [42]; Yang et al. found GPT-3.5 and GPT-4 projecting higher costs and longer hospitalisations for White patients [13]; Ayoub et al. sampled simulated physicians choosing one patient to save under resource scarcity [43]. Benchmark-scale work followed: Poulain et al. evaluated eight LLMs on three clinical question-answering datasets with red-teaming prompts and examined how architecture and prompting shape the biases observed [44], then proposed a preference-optimisation alignment to reduce them [45]; FairMedQA built 4,806 counterfactual question pairs from 801 vignettes and found accuracy disparities of 3 to 19 percentage points across demographic groups in twelve LLMs [46]; Purkayastha et al. found that demographic prefixes changed 20.3% of answers across six models on MedQA items [47]; Lee et al. identified intersectional sex-by-race gaps in LLM emergency triage [48]; and Pendse et al. altered names, pronouns and descriptors across 39 demographic groups in 97 psychiatric training cases to probe implicit bias in automated diagnosis [49]. Audits of emergency triage that pair each case with a counterfactual have found gender-swap flip rates between 9.9% and 43.8% in five proprietary models [18], a dose-response skew toward less aggressive management from stigmatising language [19], and, when grounded in patient outcomes, harmful reprioritisation from psychiatric history, frequent-visitor status, homelessness, age and substance use but not from race, language or insurance [20]. Two systematic syntheses describe bias as pervasive across clinical applications [14, 15], and broader surveys catalogue the evaluation and mitigation techniques available [50, 51].

Read critically, this body of work has three recurrent limitations that the present study is designed around. Most audits test proprietary models through an API, so results are tied to an unversioned endpoint. Nearly all state the protected

attribute explicitly, which is the cue most likely to trigger alignment behaviour. And the common metric, the share of answers that change when the attribute changes, is rarely compared with the share that change when nothing changes.

2.4 Open-weight models

Open-weight models are now deployed on institutional hardware. Nowak et al. describe an isolation-first, on-premise inference stack for radiology that served an open-weights model to 22 residents and radiologists in a prospective pilot [25]. Audits of such models are beginning: Aljohani et al. compared ten open-source LLMs, including Qwen2.5, MedGemma, MedLLaMA2 and GPT-OSS variants, on paediatric Emergency Severity Index prediction with paired counterfactuals that change one demographic, socioeconomic or system-context variable [26]; Ahmed and Sadka audited Mistral 7B-Instruct, served locally through Ollama, on 4,659 counterfactual MedQA items under stochastic and deterministic decoding [27]; Kitahara and Yamaguchi found that job-posting language triggers gender and racial bias in six open-weight models applied to recruitment, among them Llama 3.2, Gemma 3 and Qwen 3 [52]; and Bhetwal et al. measured consistent name bias in 300,000 responses from six local LLMs on a fill-in-the-blank task [33]. The model families audited here are documented in their technical reports [53, 54, 55], and all are instruction-tuned in the lineage of reinforcement learning from human feedback [28]. None has been audited for pain assessment.

2.5 Name-based cues and audit instruments

Name-based correspondence audits originate in labour economics, where otherwise identical résumés with White-sounding names received more call-backs than those with Black-sounding names [34]. Applied to LLMs, the design shows that advice systematically disadvantages names associated with racial minorities and women, with Black women receiving the least advantageous outcomes across 42 prompt templates [30]; that hiring emails favour White over Hispanic applicants, although the pattern is prompt-sensitive and idiosyncratic [31]; that hiring and salary recommendations over 750,000 prompts favour White female-sounding names [32]; and that a method varying demographics across 70 decision scenarios can surface discrimination before deployment [56]. Cues beyond the name matter too: models make covertly racist decisions from dialect alone [57], and demographic identity leaks from unstructured prose in de-identified résumés across nine open-weight models [58]. Two recent results bear directly on how such audits should be built. Tonneau et al. showed over 14.8 million prompts that different cues for the same group induce only partially overlapping changes in model responses, so that bias conclusions vary in magnitude and direction with the cue chosen [29]. Vohra and Ravikiran, in a preregistered replication across hiring, lending and medical triage with applications that differed only by name, found that none of 36 planned contrasts survived correction and that the audit instrument (rating versus ranking) produced effects rivalling the demographic ones [35].

2.6 Instability as a baseline

Atil et al. documented accuracy variation of up to 15% across runs of LLMs configured to be deterministic [21], and Song et al. argued that evaluation should not ignore non-determinism [22]. For fairness audits specifically, Bellibatlu et al. measured how often a clinical LLM agent changes its action when the prompt is re-run unchanged: 8.7% of replicate pairs at default sampling for one agent, from 2.2% for intensive-care escalation to 17.9% for controlled-substance caution, and pooled floors of 2.5% to 23.7% across six models from five vendors [23]. A counterfactual flip rate below that floor cannot be attributed to the demographic change, and controlled-substance decisions sat at the unstable end of their range, which is directly relevant to an opioid audit.

2.7 Position of the present study

To the authors' knowledge this is the first audit of open-weight, locally deployable models for racial and sex disparities in pain assessment; the first in this task to cue identity by name alone with two names per group, so that a name's idiosyncrasy can be separated from a group effect; and the first to pair every counterfactual comparison on the sampling seed and to report the re-sampling noise floor and the minimum detectable effect alongside the estimates. It extends the explicit-label design of Young et al. [16] to open-weight models, imports the name-based audit design from labour economics and general LLM auditing [34, 30] into pain assessment, and adopts the instability baseline of Bellibatlu et al. [23].




Figure 1: Study workflow, in six numbered steps. Design (top row, steps 1 to 3): authored and Q-Pain cases were presented under eight patient identities, cued either by an explicit label or by a name, to local and API-served models. Analysis (bottom row, steps 4 to 6, right to left): every exchange was saved before parsing and scored; each non-reference identity was compared with the White male reference on the same case and seed; and each estimate was set against the models' own re-sampling noise floor, a case-level bootstrap and equivalence margins.

3 Methods

3.1 Study design

Two studies used the same within-case counterfactual design [36] (Figure 1): a clinical case was presented to a model under eight patient identities (four races × two sexes) with every other token of the prompt held fixed, and each non-reference identity was compared with the White male reference on the same case and sampling seed. *Study 1* audited four open-weight models running locally on six authored acute-pain cases in three conditions run in sequence: a pilot in which the case stated the patient's self-reported pain rating, and two main conditions without it, one stating race and sex explicitly and one cueing them only through the patient's name. *Study 2*, designed after Study 1's results were known, repeated the two main conditions on the same six cases and on the 50 clinician-written cases of Q-Pain [10], across a panel of 24 model configurations: the Study 1 models, larger open-weight models served locally and through a commercial API, proprietary API models, the same weights with reasoning switched on and off, and one model at two numeric precisions. No model was trained, fine-tuned or prompted with examples, so neither study has a training, validation or test partition.

3.2 Data sources: vignettes

Authored cases (Studies 1 and 2). Six acute-pain cases typical of emergency or post-operative presentation were drafted with the assistance of a large language model (Claude, Anthropic) and edited by the first author; they were not reviewed by a clinician: renal colic (age 38), closed mid-shaft femur fracture (45), sickle cell vaso-occlusive crisis (24), mechanical low back pain (41), migraine (33) and post-operative day one after laparoscopic appendectomy (29). Each case gave the history, observed pain behaviour (for example pacing, guarding the limb, lying still in a dark room), vital signs and the absence of drug allergies; the renal colic case also stated no history of substance use. The pilot versions replaced the behavioural sentence with a self-reported rating ("Rates pain 9/10"; ratings 9, 10, 9, 7, 8 and 8 for the six cases). Appendix A gives the full text of the main versions. No case was drawn from a patient record. The cases were unpublished when the models were queried, so their exact text cannot have appeared in any model's training data, although the presentations themselves are textbook cases.

Q-Pain cases (Study 2). Q-Pain [10] (PhysioNet, CC BY-SA 4.0) contains 55 vignettes in five contexts: acute cancer pain, acute non-cancer pain, chronic cancer pain, chronic non-cancer pain and post-operative pain. A clinical expert

Table 1: Names used to cue identity in the name-cue condition on the authored cases.

Race	Men	Women
White	Greg Baker; Todd Walsh	Emily Walsh; Allison Baker
Black	Jamal Washington; DeShawn Jefferson	Lakisha Washington; Tamika Jefferson
Hispanic	Jose Hernandez; Luis Garcia	Maria Hernandez; Guadalupe Garcia
Asian	Wei Zhang; Hiroshi Tanaka	Mei Chen; Yuki Tanaka

Table 2: Study 1 models. All ran at Q4_K_M quantisation under Ollama 0.40.14.

Model	Ollama tag	Developer	Parameters	Quantisation	Licence
gemma3 12B	`gemma3:12b`	Google	12.2B	Q4_K_M	Gemma Terms of Use
qwen3 14B	`qwen3:14b`	Alibaba	14.8B	Q4_K_M	Apache 2.0
ministral-3 14B	`ministral-3:14b`	Mistral AI	13.9B	Q4_K_M	Apache 2.0
llama3.2 3B	`llama3.2:latest`	Meta	3.2B	Q4_K_M	Llama 3.2 Community

with four years of medical experience designed each scenario, and two internal-medicine physicians who had not designed them reviewed a random selection for credibility, coherence and sufficiency of information. Each context has ten vignettes for which the reference answer is to offer an opioid, at a stated low or high dose or supply, and one "No" vignette written for use as a closed example, with fewer placeholders; the 50 open vignettes were used and the five closed ones were not. Each vignette names the patient "Patient D", carries `[race]` `[gender]` and pronoun placeholders, and ends with Q-Pain's own question, for example "Would you offer Patient D intravenous hydromorphone for pain control? Yes or no? If yes, what dose – Low (0.5 mg), or High (1 mg)? Explain." Q-Pain has been public since 2021, so its text may have appeared in the training data of the models audited; because the identity is inserted by the audit, any such exposure applies equally to every identity arm of a case. The files were downloaded from PhysioNet and checked against the published SHA-256 sums.

3.3 Independent variables: identity manipulation

Authored cases. In the explicit-label condition the patient line read "Patient: a {age}-year-old {race} {sex}." with race in {White, Black, Hispanic, Asian} and sex in {man, woman}. In the name-cue condition the line read "Patient: {name}, age {age}." with no race or sex stated. Two names were assigned to each identity (Table 1). The White and Black names follow the correspondence-audit tradition of Bertrand and Mullainathan [34]; the Hispanic and Asian names were selected by the authors as names commonly associated with each group, without external validation of perceived race. Each name's responses are paired with the same name slot of the reference identity, so a comparison never crosses name slots.

Q-Pain cases. In the explicit-label condition the placeholders were filled as Q-Pain specifies ("Patient D is a 62-year-old Black woman ..."), with matching pronouns). In the name-cue condition the race and sex words were removed and "Patient D" was replaced throughout by a first name from Q-Pain's own list of ten names per race–sex group, drawn from the first-name demographic data of Tzioumis [59]; sex was also carried by the pronouns, which the Q-Pain template requires. The i-th name of each group was used for the i-th vignette of every context, so each identity was represented by all ten of its names and each comparison paired two names on the same case.

3.4 Models

Study 1. Four open-weight models were selected to span four developers and the parameter range (3 to 15 billion) that runs on a single workstation GPU at 4-bit quantisation, the configuration under which such models are deployed locally (Table 2) [53, 54, 55]. All were served by Ollama 0.40.14 on one workstation with two NVIDIA RTX A4000 GPUs. qwen3 is a reasoning model; its thinking mode was disabled (`think: false`) because the model returns an empty body for structured-output prompts otherwise. The appropriate baseline for a counterfactual audit is not a competing model but the model's own behaviour: the White male reference arm supplies the comparison and the re-sampling noise floor (Section 3.8) supplies the scale.

Study 2. The panel (Table 3) was chosen to answer three questions that Study 1 could not. *Scale and provenance*: one current model from each major developer reachable through the OpenRouter API, proprietary (GPT-4.1 mini, Claude Haiku 4.5, Gemini 2.5 Flash) and open-weight (Llama 3.3 70B, Qwen3 235B-A22B, DeepSeek V4.1 Flash, GLM-4.6, gpt-oss 120B), and larger open-weight models served locally (qwen3.8 27B, qwen3.6 35B, gpt-oss 20B).

Table 3: Study 2 model configurations. Provider and precision are those pinned for every request; "not disclosed" marks proprietary models whose serving precision is not published. Output tokens are the mean generated tokens per response, including reasoning tokens; – marks records saved before token counts were captured. Cost is the provider charge reported for the responses analysed.

Configuration	Access	Provider	Precision	Reasoning	Responses	Invalid	Output tokens	Cost (USD)
gemma3 12B	local	Ollama	Q4_K_M	off	3,120	0	67	–
qwen3 14B, reasoning off	local	Ollama	Q4_K_M	off	3,120	0	74	–
qwen3 14B, reasoning on	local	Ollama	Q4_K_M	on	720	0	620	–
ministral-3 14B	local	Ollama	Q4_K_M	off	3,120	0	90	–
llama3.2 3B	local	Ollama	Q4_K_M	off	3,120	0	72	–
qwen3.8 27B, reasoning off	local	Ollama	Q4_K_M	off	720	0	67	–
qwen3.8 27B, reasoning on	local	Ollama	Q4_K_M	on	720	0	612	–
gpt-oss 20B, effort low	local	Ollama	MXFP4	low	720	0	97	–
gpt-oss 20B, effort high	local	Ollama	MXFP4	high	720	0	849	–
qwen3.6 35B, reasoning off	local	Ollama	Q4_K_M	off	720	0	70	–
qwen3.6 35B, reasoning on	local	Ollama	Q4_K_M	on	720	13	1339	–
GPT-4.1 mini	API	openai	not disclosed	off	3,120	0	56	0.66
Claude Haiku 4.5	API	google-vertex	not disclosed	off	3,120	0	87	2.98
Gemini 2.5 Flash	API	google-ai-studio	not disclosed	off	3,120	0	61	0.70
GLM-4.6, reasoning off	API	deepinfra	fp4	off	3,120	0	60	0.50
Llama 3.3 70B	API	deepinfra	fp8	off	3,120	0	71	0.15
DeepSeek V4.1 Flash, reasoning off	API	deepinfra	fp8	off	3,120	0	72	0.17
Qwen3 235B-A22B	API	deepinfra	fp8	off	3,120	0	67	0.19
gpt-oss 120B, effort low	API	deepinfra	bf16	low	3,120	0	113	0.09
gpt-oss 120B, effort high	API	deepinfra	bf16	high	3,120	4	990	0.56
Gemma 3 12B (bf16)	API	deepinfra	bf16	off	3,120	0	66	0.07
DeepSeek V4.1 Flash, reasoning on	API	deepinfra	fp8	on	3,120	46	1326	1.80
GLM-4.6, reasoning on	API	deepinfra	fp4	on	3,120	6	1325	6.81
Beam 501B-A23B, reasoning on	API	Ollama Cloud	not disclosed	on	3,120	1	1460	0.00

Beam (Reflection AI; open weights, a sparse mixture-of-experts with 501B total and 23B active parameters), released in October 2026 and available only through Ollama's cloud service, was added during data collection as the newest open-weight model in the panel. *Reasoning*: the same weights were run with reasoning disabled and enabled (DeepSeek V4.1 Flash and GLM-4.6 through the API; qwen3 14B, qwen3.8 27B and qwen3.6 35B locally) or at low and high reasoning effort (gpt-oss 120B through the API; gpt-oss 20B locally). *Precision*: Gemma 3 12B was run at bf16 through the API, against the 4-bit local copy of the same weights used in Study 1. A configuration is one model at one reasoning setting, and a model is one served model identifier: the 24 configurations comprise 17 models, of which 16 have distinct weights (the 4-bit local and 16-bit API copies of Gemma 3 12B share them) and 14 have Q-Pain responses. The local reasoning configurations were run on the authored cases only, to keep the run time of long reasoning outputs on local hardware feasible.

3.5 Procedure

Prompts. Every request was a single user message with no system prompt. For the authored cases, shown for the explicit-label condition with the renal colic case:

```
You are an emergency physician.  Read the case and answer with JSON only:
{"pain_severity":  <integer 0-10, your assessment of the patient's true pain>,
  "analgesic":  one of ['none', 'non-opioid', 'weak-opioid', 'strong-opioid'],
  "rationale":  <one sentence>}

Patient:  a 38-year-old Black woman.
Presents with 3 hours of sudden left flank pain radiating to the groin, vomiting
twice.  Pacing the room, unable to sit still, grimacing.  HR 104, BP 142/88.
Urinalysis shows blood.  No known drug allergies.  No history of substance use.
```

For the Q-Pain cases the instruction read "You are a physician. Read the case and answer the question with JSON only", followed by fields for `pain_severity` (integer 0–10), `offer` (`yes` or `no`), `dose` (`low`, `high`, or `none` if not offered) and a one-sentence `explanation`, then the rendered vignette and Q-Pain's question.

Local inference. Requests went to the Ollama `/api/generate` endpoint with temperature 0.7 and the `seed` option set to the replicate index; all other decoding options were left at Ollama defaults. On the authored cases the output was requested as free JSON (`format: json`). On the Q-Pain cases it was constrained to a JSON schema of the answer fields, after the smallest model omitted a required field under free JSON in a pre-test. Reasoning was set with Ollama's `think` field (`false`, `true`, or an effort level for gpt-oss). Ollama fixes how much of a model it places on the GPUs

when it loads the model. The workstation also served an unrelated embedding job, and one load coincided with it: the first 21 of qwen3 14B's 50 explicit-label Q-Pain cases ran with a third of the model on the GPUs and the rest on the CPU (176 against 27 ms per generated token). The model was reloaded only between cases, so the responses compared within any case shared one placement. From then on, a script checked the placement after each load and reloaded a split model at the next case boundary. qwen3.6 35B was the one model too large to load whole: every load placed 95% of it on the GPUs, and its generation speed stayed within 14–17 ms per token across all four of its configurations, so its placement did not vary between cases. Generation speed per configuration showed no other split. The Study 1 records do not include timings, so their placement cannot be checked after the fact.

API inference. Requests went to the OpenRouter chat-completions endpoint with temperature 0.7, the seed set to the replicate index, and the answer constrained by a strict JSON schema (`response_format` of type `json_schema`) with the same fields as the local runs. Each configuration was pinned to one provider, with fallback routing disabled and the requirement that the provider honour every parameter sent, so that a request was refused rather than silently served by a provider that ignores the seed or the schema; where the provider offered several precisions, the precision was pinned too. Two exceptions followed from what providers support: Claude Haiku 4.5 was served through Google Vertex, which does not accept a seed, so its replicates are independent samples paired by replicate index; and GLM-4.6 was served by the only endpoint that honoured both seed and schema, DeepInfra's fp4 tier. Reasoning was disabled, enabled, or set to an effort level through OpenRouter's `reasoning` parameter, with an output limit of 600 tokens, raised to 6,000 when reasoning was enabled. Beam was reached through Ollama Cloud with the same request code and output formats as the local models (free JSON on the authored cases, the schema on Q-Pain). A pre-run check showed that its reasoning could not be disabled (a request with reasoning off still returned reasoning) and that it did not honour the seed, so it was run once, with reasoning on, and its pairs share a replicate index but not a seed; its serving precision is not disclosed. Responses were collected from 5 to 7 November 2026: the local models on 5 to 7 November, the OpenRouter models on 5 to 6 November and Beam on 6 November. Hosted models can change without notice, and the time of every request is saved with its response.

Sampling. Each case $\times$ identity cell of the authored cases was sampled with five seeds (0–4) in the pilot and explicit-label conditions, and with five seeds for each of the two names in the name-cue condition: 720 requests per configuration. Each Q-Pain case $\times$ identity cell was sampled with three seeds (0–2) under each cue: 2,400 requests per configuration. An API configuration therefore comprised 3,120 requests.

Capture and error handling. Every response was written to disk before parsing, keyed by model, reasoning setting, case, identity, cue, name and seed, so that an interrupted run resumed without repeating a request. In Study 2 each record holds the exact request body sent, the complete response body returned, the HTTP status and response headers, and every attempt with its start time and duration; the API key was never stored. Records were written atomically (to a temporary file, then renamed). Transfer failures (timeouts, dropped connections, HTTP 408, 429 and 5xx) were retried up to three times with increasing back-off; a request that failed every attempt was written in full to an error log and re-requested on the next run. A verification script counted corrupt, partial and invalid records and moved any it found to a quarantine folder for re-request; nothing was deleted. API spend was checked against a cap before each request (USD 15, raised to USD 16 during collection so that the last configuration could finish), from a ledger of the cost reported for every completed request. Records collected before full capture was introduced were set aside unanalysed and re-requested, so every Study 2 API response and every Q-Pain response carries the full exchange; the Study 1 records predate it and hold the prompt, response and sampling parameters.

3.6 Dependent variables

On the authored cases two outcomes were scored. *Pain severity* was the integer returned for `pain_severity` on the 0–10 scale. *Strong-opioid recommendation* was a binary indicator that the returned analgesic class was `strong-opioid` rather than `none`, `non-opioid` or `weak-opioid`. On the Q-Pain cases, following Q-Pain's own measures, three outcomes were scored: pain severity as above, *opioid offered* (`offer` = `yes`), and *high dose* (offered at the high dose or supply). As a descriptive check that answers were clinically plausible, each Q-Pain response was also compared with the clinical expert's reference answer, which in all 50 open cases is to offer the opioid at the low dose or supply. A response counted as valid only if it parsed as JSON and every field held a permitted value; invalid responses were counted and reported, never dropped silently. The free-text rationale was stored but not analysed.

3.7 Sample size

Five seeds per cell, and two names per identity in the name-cue condition, were chosen for feasibility on local hardware: 30 pairs per identity comparison in the explicit-label conditions and 60 in the name-cue condition. Q-Pain gave 150 pairs

per identity and cue (50 cases $\times$ 3 seeds). Rather than a prior power analysis, Study 1 reports the minimum detectable paired difference for each model, condition and outcome (Section 3.8). In Study 2 the number of cases, not of pairs, limits case-level inference: with six authored cases the smallest attainable two-sided case-level p is $2/64 = 0.031$, so no authored-case comparison can survive correction over seven identities, and the 50 Q-Pain cases carry the inferential weight.

3.8 Data analysis

Study 1. For each model, condition and non-reference identity, the analysis formed the paired difference (identity minus White male reference) on the same vignette, seed and, in the name-cue condition, name slot. It reports the mean paired difference with a percentile bootstrap 95% confidence interval (10,000 resamples) [60] and a two-sided sign-flip permutation p-value (10,000 permutations), which assumes only that the sign of each paired difference is exchangeable under the null. Within each model, condition and outcome the seven identity comparisons form one family, corrected by the Holm procedure [61] at $\alpha = 0.05$. Because all seven comparisons share the same reference responses, their signs are correlated by construction and agreement in sign across identities is not treated as independent evidence.

Two further quantities place the estimates in context. The *noise floor* is the proportion of pairs of responses to the identical prompt (same vignette, identity, name and model, different seeds) whose strong-opioid decision, or severity rating, differed; it is compared with the proportion of same-seed reference-versus-identity pairs that differed [23]. Because the floor pairs differ in seed whereas the counterfactual pairs share one, the floor is also compared with identity-versus-reference pairs drawn from different seeds, which matches its construction. The *minimum detectable difference* is the paired mean difference detectable with 80% power at two-sided $\alpha = 0.05$, $2.80 \times s/\sqrt{n}$, where s is the standard deviation of the paired differences pooled over the seven identities and n the pairs per identity. A name-level analysis computed the mean severity for each of the sixteen names and split each model's paired differences by reference name. Because the 30 or 60 pairs per identity come from only six vignettes, a robustness analysis treated the vignette as the unit: per-vignette mean differences were bootstrapped over vignettes, and equivalence was assessed with two one-sided tests (TOST), declaring a difference equivalent to zero when its 90% cluster-bootstrap interval lay within ± 1 severity point (half the approximately two-point clinically important change on the 0–10 scale [62]) or ± 0.10 in strong-opioid proportion. That two-point change was measured within patients with chronic pain, so the margin is generous for a between-group question about assessment bias; Study 2 therefore also reports tighter margins. With only six clusters the percentile bootstrap intervals of this analysis are approximate.

Study 2. The case was the unit of analysis throughout. For each configuration, case set, cue, outcome and identity, the paired differences were averaged within each case; the estimate is the mean of the case means, its 95% interval a percentile bootstrap over cases (10,000 resamples), and its p-value a two-sided sign-flip test on the case means, exact over all 2^k sign patterns when there were $k \leq 16$ cases and from 200,000 random patterns otherwise, which puts the Monte Carlo standard error of a p-value near 0.007 at about 0.0002. The resamples and sign patterns of each comparison were drawn from a seed derived from that comparison's own data, so no result depends on which other comparisons were computed. The pair-level p-value of Study 1 is reported alongside for continuity. Holm correction was applied over the seven identities within each configuration, case set, cue and outcome, and the Benjamini–Hochberg false discovery rate [63] over all 1,386 identity comparisons in the study. Equivalence used the Study 1 margins, with ± 0.10 also for the proportions offered an opioid and offered a high dose. To show how the conclusion depends on the margin, severity equivalence was also assessed within ± 0.5 and ± 0.25 points and the proportions within ± 0.05, and the smallest margin within which every difference was equivalent was recorded (a difference is equivalent within a margin exactly when the larger absolute end of its 90% interval is smaller than the margin). Two pooled contrasts summarised each configuration: each minority group minus White within sex, averaged over sex, and women minus men within race, averaged over race. The noise floor and identity flip rates were computed as in Study 1, and are reported for every configuration with the minimum detectable difference (2.80 times the standard error of the mean of the case means, so that the case, not the pair, is the unit) in Appendix Tables 12 and 13. Whether pairing on the seed helps was checked by comparing, for each configuration, the identity flip rate on the same seed with that on a different seed, in the rows whose same-prompt floor was at least 0.05 so that pairing had room to matter (Appendix Table 15): a seed that is honoured lowers the same-seed rate, and for the two unseeded models the rates should coincide. This is an indirect check; sending an identical prompt and seed twice was not done. Because invalid answers are dropped from paired comparisons, whether they depend on identity was tested separately by permuting the failure flags across the eight identities within each case-and-seed block (20,000 permutations, chi-square statistic), so that a case that fails for every identity cannot look like an identity effect, with Holm correction over the cells tested (Appendix Table 14). The share of severity variance explained by the case (η^2) indexed whether a model's ratings responded to the clinical content at all. *Reasoning and precision contrasts* compared two configurations of the same weights: for each case and identity, the identity difference under one setting was subtracted from that under the other (reasoning on minus off, high minus

low effort, bf16 minus 4-bit), and the per-case results were bootstrapped and tested as above with Holm correction over the seven identities; the same procedure gave the shift in the baseline level of each outcome across all identities. For the precision pair, prompt-level means over seeds were also correlated between the two copies of the weights.

All analyses used Python 3.10 with NumPy 1.26 and fixed random seeds; the scripts regenerate every table, figure and number in this paper from the saved responses.

3.9 Ethics

The study involved no human participants, patient records or identifiable private information. The authored cases are synthetic, drafted with a language model and edited by the authors; the Q-Pain cases are synthetic vignettes written by its authors' clinical expert and reused under their CC BY-SA 4.0 licence. The work therefore does not meet the definition of human-subjects research under 45 CFR 46.102 and is exempt from Institutional Review Board review; no IRB protocol was required. Study 1 inference ran entirely on local hardware. In Study 2 the synthetic prompts were also sent to commercial inference providers through OpenRouter and Ollama Cloud; no personal or institutional data was transmitted.

3.10 Preregistration

Neither study was preregistered. For Study 1, the project log recorded the name-cue design, and the intention to compare indirect with explicit cues, before the name-cue condition was run, but H1 and H2 were written in their present form after the results of all three conditions were known; their directions follow the prior literature [16, 1], and the analyses should be read as exploratory. The pilot's anchoring result (Section 4.1.2) led to the removal of the self-reported rating before either main condition was run, and the case-level and equivalence analyses (Section 4.1.7) were added after review of the first draft. For Study 2, the model panel, sample sizes and analysis script were committed to version control before data collection finished. Interim output, covering the configurations complete at that time, was viewed while the script was being tested; the version-control history records every later change to the analysis code. One change followed that output: the case-level p-values had been drawn from 10,000 sign patterns in a single random stream shared by all comparisons, so adding a configuration re-drew the p-values of others, and one Holm-adjusted value moved from 0.064 to 0.044 between two interim runs without any change in its data. The final analysis therefore seeds each comparison separately and uses 200,000 patterns, as described above. The change was made on 6 November 2026 in the analysis script's inference function and is recorded in the working repository's history; the public repository holds the final code.

3.11 Reproducibility

The repository accompanying this paper (`https://github.com/ricyoung/qpain-llm-counterfactual-audit`) contains the authored cases in both versions, the name tables, the panel definition with every provider and precision pin, the request, capture, verification and scoring code, the saved exchange for every request (58,080 responses analysed across both studies), the spend ledger, the analysis scripts and the generated tables and figures. The Q-Pain files are redistributed under their licence. API responses cost USD 14.68 (Beam, through Ollama Cloud, was free); the ledger total of USD 15.18 includes the connection tests and the superseded early records. No model weights were produced; the audited checkpoints are those distributed under the tags and identifiers in Tables 2 and 3. There is no train/test split and no tuning, so the only leakage pathway is pre-training exposure: none for the authored cases, which were unpublished, and possible for Q-Pain, which is public.

4 Results

The research question was whether LLMs assess pain or recommend opioids differently by the patient's race or sex, first when race and sex are stated (H1) and then when they are cued only by a name (H2). Section 4.1 reports Study 1, four open-weight models on the six authored cases: response validity and baseline behaviour (Table 4), the paired differences (Figure 2, Table 5), the name-level means (Appendix B) and the noise floor (Figure 3, Table 6). Section 4.2 reports Study 2, the panel of 24 configurations on the authored and Q-Pain cases: validity and baselines, agreement with the Q-Pain reference answers, the identity differences (Figures 4 and 5, Table 7) and the reasoning and precision contrasts (Tables 8 and 9).

Table 4: Response validity and baseline behaviour by condition and model. Severity is on the 0–10 scale; the strong-opioid rate is the proportion of responses recommending a strong opioid.

Condition	Model	Responses	Parsed	Mean severity (SD)	Range	Strong-opioid rate
Pilot (self-rated)	gemma3 12B	240	240	8.33 (0.75)	7–9	0.47
	qwen3 14B	240	240	8.50 (0.96)	7–10	0.49
	ministral-3 14B	240	240	8.30 (1.00)	6–10	0.53
	llama3.2 3B	240	240	8.50 (0.96)	7–10	0.50
Explicit labels	gemma3 12B	240	240	7.72 (1.09)	6–9	0.29
	qwen3 14B	240	240	7.07 (1.06)	5–8	0.47
	ministral-3 14B	240	240	7.56 (1.03)	6–9	0.51
	llama3.2 3B	240	240	7.33 (0.94)	6–8	0.48
Name cues	gemma3 12B	480	480	7.78 (1.07)	6–9	0.28
	qwen3 14B	480	480	7.11 (0.99)	5–8	0.49
	ministral-3 14B	480	480	7.53 (1.05)	6–9	0.45
	llama3.2 3B	480	480	7.33 (0.94)	6–8	0.44

4.1 Study 1: four open-weight models on the authored cases

4.1.1 Response validity and baseline behaviour

All 3,840 responses across the three conditions parsed as valid JSON with an in-range severity and a permitted analgesic class (Table 4). In the two main conditions, mean severity ranged from 7.07 (qwen3) to 7.78 (gemma3) with within-model standard deviations of about one point and case-to-case ranges of 5–9. The strong-opioid rate ranged from 0.28 (gemma3) to 0.51 (ministral-3), and gemma3 recommended strong opioids markedly less often than the other three models under both cue types.

4.1.2 Pilot: anchoring on the self-reported rating

In the pilot, which stated the patient's own rating, the models reproduced that number rather than assessing the case: the returned severity equalled the stated rating in 100% of responses for qwen3 and llama3.2, 83.3% for gemma3 and 60.8% for ministral-3. Paired severity differences were exactly zero for three models and at most 0.067 for ministral-3, with every Holm-adjusted $p = 1$. Because a copied number cannot carry a disparity, the self-reported rating was removed and the pilot is not used to test H1 or H2.

4.1.3 Explicit labels (H1)

With race and sex stated (Figure 2, left column, blue), no identity differed from the White male reference in severity or strong-opioid recommendation. The largest severity difference was -0.10 points for Asian men under gemma3 (95% CI $[-0.20, 0.00]$, pair-level $p = 0.253$); all other severity differences lay within ± 0.07, and llama3.2 returned identical severity for every identity on every seed. The largest strong-opioid difference was -0.100 for Black women under gemma3 (pair-level $p = 0.374$). Every Holm-adjusted p-value in this condition was 1.000 (Table 5). Study 1's p-values are pair-level: the 30 or 60 pairs per identity come from six cases, so they are conditional on those cases (the case-level analysis follows below).

4.1.4 Name cues (H2)

With identity cued only by name (Figure 2, orange), no difference survived correction. gemma3 rated every non-reference identity slightly higher than the reference, by $+0.03$ to $+0.12$ points; the largest, Hispanic women at $+0.117$ (95% CI $[0.050, 0.200]$), had an uncorrected $p = 0.015$ and a Holm-adjusted $p = 0.103$, and Black women and Asian women ($+0.083$ each, $p = 0.064$) had Holm-adjusted $p = 0.381$. The other models' severity differences lay within ± 0.083 (ministral-3, Black men $+0.083$, $p = 0.124$; qwen3, Asian women -0.067, $p = 0.288$), and llama3.2 again returned identical severity for every identity. Strong-opioid differences lay within ± 0.067 for every model and identity; the smallest uncorrected p-values were 0.123 (ministral-3, Black men, -0.067) and 0.124 (qwen3, Hispanic women, -0.067), with Holm-adjusted values of 0.864 and 0.866. For ministral-3 and llama3.2 all seven strong-opioid differences were negative (-0.017 to -0.067), and for gemma3 all seven were zero or positive (0 to $+0.050$); as noted in Section 3.8, the seven comparisons share the reference responses, so this agreement in sign is not independent evidence. The direction H2 predicted, lower severity and fewer strong opioids for Black and Hispanic names, did not appear in any model.




Figure 2: Paired differences from the White male reference for each identity, model and cue type. Left: pain severity (0–10 points). Right: proportion recommending a strong opioid. Markers show the mean paired difference and bars the percentile bootstrap 95% CI; blue circles are the explicit-label condition (30 pairs per identity), orange diamonds the name-cue condition (60 pairs). A difference to the right of zero means the identity received a higher severity rating, or strong opioids more often, than the reference. The shaded band is the ± 0.10 equivalence margin for the strong-opioid proportion; the ± 1-point severity margin lies far outside the plotted range.

Table 5: Largest paired difference per model, condition and outcome, with its identity and bootstrap 95% CI, and the smallest uncorrected and Holm-adjusted p-values across the seven identity comparisons. n/arm is the number of pairs per identity. The p-values are pair-level: the pairs come from six cases, so they are conditional on those cases.

Condition	Model	Outcome	n/arm	Largest Δ	Identity	95% CI	min p	min p_{Holm}
Explicit labels	gemma3 12B	Severity	30	-0.10	Asian man	[-0.20, 0.00]	0.253	1.000
		Strong opioid	30	-0.100	Black woman	[-0.233, 0.033]	0.374	1.000
	qwen3 14B	Severity	30	+0.03	Black woman	[0.00, 0.10]	1.000	1.000
		Strong opioid	30	-0.033	Black man	[-0.100, 0.000]	1.000	1.000
	ministral-3 14B	Severity	30	+0.07	Black man	[-0.07, 0.20]	0.503	1.000
		Strong opioid	30	-0.067	Black woman	[-0.200, 0.067]	0.612	1.000
	llama3.2 3B	Severity	30	0	all identities	–	1.000	1.000
		Strong opioid	30	-0.033	White woman	[-0.100, 0.000]	1.000	1.000
Name cues	gemma3 12B	Severity	60	+0.12	Hispanic woman	[0.05, 0.20]	0.015	0.103
		Strong opioid	60	+0.050	Hispanic man	[-0.017, 0.117]	0.374	1.000
	qwen3 14B	Severity	60	-0.07	Asian woman	[-0.15, 0.02]	0.288	1.000
		Strong opioid	60	-0.067	Hispanic woman	[-0.133, -0.017]	0.124	0.866
	ministral-3 14B	Severity	60	+0.08	Black man	[0.00, 0.17]	0.124	0.872
		Strong opioid	60	-0.067	White woman	[-0.150, 0.000]	0.123	0.864
	llama3.2 3B	Severity	60	0	all identities	–	1.000	1.000
		Strong opioid	60	-0.050	Black man	[-0.117, 0.000]	0.249	1.000

4.1.5 Name-level analysis

Mean severity by name (Appendix B, Table 10) spanned 7.67–7.83 for gemma3, 7.03–7.13 for qwen3, 7.43–7.67 for ministral-3, and exactly 7.33 for every name under llama3.2. For gemma3 the lowest of the sixteen names was one of the two White male reference names, Greg Baker (7.67); the other reference name, Todd Walsh (7.77), sat within the range of the non-reference names (7.73–7.83), and a White female name, Emily Walsh, shared the highest value (7.83). Splitting gemma3's paired differences by reference name located the shift: against Greg Baker the mean difference across the seven identities was $+0.133$, with 13.3% of pairs rated higher and none lower; against Todd Walsh it was $+0.010$, with 3.8% higher and 2.9% lower.

4.1.6 Noise floor and sensitivity

Figure 3 and Table 6 compare how often a model changed its answer between two seeds of the identical prompt (the floor) with how often it changed between the reference and another identity on the same seed. For the strong-opioid decision the same-seed counterfactual rate never exceeded the floor in either condition: under name cues the floors were 0.083, 0.017, 0.160 and 0.110 for gemma3, qwen3, ministral-3 and llama3.2 against counterfactual rates of 0.076, 0.014, 0.086 and 0.029, and under explicit labels 0.179, 0.062, 0.171 and 0.029 against 0.057, 0.010, 0.076 and 0.029. For the severity rating the counterfactual rate exceeded the floor only for gemma3, in both conditions (0.105 against 0.083 with explicit labels; 0.100 against 0.071 with names); ministral-3's severity floor of 0.354 was the highest instability observed. Because the same-seed pairs share a seed and the floor pairs do not, the comparison was repeated with identity and reference responses drawn from different seeds. Under that matched construction the strong-opioid flip rate was close to the floor for every model (explicit labels: 0.193, 0.064, 0.188 and 0.045 against floors of 0.179, 0.062, 0.171 and 0.029; name cues: 0.118, 0.014, 0.189 and 0.092 against 0.083, 0.017, 0.160 and 0.110), and gemma3's severity rate under name cues (0.130) exceeded its floor (0.071). The minimum detectable paired difference at 80% power was 0.08–0.17 severity points and 0.04–0.14 in strong-opioid proportion across the models and conditions with any variation; llama3.2's severity showed no variation between identities at all.

4.1.7 Case-level robustness

With the vignette as the unit of analysis, every severity difference, for every model, identity and cue type, was equivalent to zero within ± 1 point: the largest mean was $+0.117$ (gemma3, Hispanic women, name cues; cluster-bootstrap 95% CI $[0.000, 0.283]$). The strong-opioid differences were not shown to be equivalent within ± 0.10 for any model: with six clusters the 95% intervals extended to -0.25 and $+0.20$. The clinical case explained 86% to 100% of the variance in severity ratings, the models used only two to four distinct severity values across all responses, and llama3.2 assigned one fixed rating to each case regardless of identity or seed. Excluding the sickle cell case left every conclusion unchanged (largest severity mean $+0.140$). Across the 112 identity comparisons in the two main conditions, one uncorrected




Figure 3: Noise floor against counterfactual change. Grey: proportion of pairs of responses to the identical prompt on two seeds whose answer differed. Blue circles (explicit labels) and orange diamonds (name cues): proportion of same-seed pairs, White male reference versus another identity, whose answer differed. Left: strong-opioid decision. Right: severity rating.

Table 6: Noise floor, counterfactual change and minimum detectable paired difference (80% power, two-sided $\alpha = 0.05$). A minimum detectable difference of 0.00 indicates no variation in the paired differences. The minimum detectable differences are pair-level and conditional on the six cases.

		Strong-opioid flip rate		Severity disagreement rate		Minimum detectable Δ	
Condition	Model	Floor	Identity	Floor	Identity	Severity	Opioid
Explicit labels	gemma3 12B	0.179	0.057	0.083	0.105	0.17	0.120
	qwen3 14B	0.062	0.010	0.092	0.029	0.09	0.050
	ministral-3 14B	0.171	0.076	0.354	0.052	0.12	0.141
	llama3.2 3B	0.029	0.029	0.000	0.000	0.00	0.086
Name cues	gemma3 12B	0.083	0.076	0.071	0.100	0.11	0.099
	qwen3 14B	0.017	0.014	0.079	0.048	0.08	0.043
	ministral-3 14B	0.160	0.086	0.354	0.055	0.08	0.104
	llama3.2 3B	0.110	0.029	0.000	0.000	0.00	0.060

p-value fell below 0.05; because the comparisons share reference responses and the tests are discrete, this count is reported without a chance benchmark.

4.2 Study 2: the model panel on authored and Q-Pain cases

4.2.1 Response validity and baseline behaviour

The 24 configurations returned 58,080 responses, of which 70 were invalid. Every invalid response came from a reasoning configuration: 46 from DeepSeek V4.1 Flash with reasoning on, each of which spent the whole 6,000-token output allowance on reasoning (45 ended with no answer and one with a truncated answer), six from GLM-4.6 with reasoning on, which did the same and ended with no answer, four from gpt-oss 120B at high effort (three ended with no answer, one at the token limit), 13 from qwen3.6 35B with reasoning on, which reasoned to completion and then

returned an empty answer object (12 of them under name cues), and one from Beam, whose answer used field values outside the schema. A paired comparison used a pair only when both of its responses were valid. Invalid answers did not depend on identity: in each of the 10 configuration, case-set and cue cells with at least one, the failures were spread across the eight identities no more unevenly than chance would produce (a permutation test within case-and-seed blocks; smallest $p = 0.28$ among the 6 cells with three or more failures, every Holm-adjusted $p = 1.00$; Appendix Table 14), although with so few failures in any cell only a large imbalance would have been detected. On the Q-Pain cases the share of severity variance explained by the clinical case ranged from 0.79 (GLM-4.6, reasoning on) to 0.99 (qwen3 14B, reasoning off). For the White male reference under explicit labels, mean severity ranged from 7.51 (gemma3 12B) to 8.30 (Gemini 2.5 Flash), the proportion of responses offering an opioid from 0.74 (gemma3 12B) to 1.00 (Llama 3.3 70B), and the proportion recommending the high dose from 0.06 (gemma3 12B) to 0.93 (llama3.2 3B) (Table 7).

4.2.2 Agreement with the Q-Pain reference answers

In all 50 open Q-Pain cases the reference answer written by the dataset's clinical expert is to offer the opioid at the low dose. The share of responses matching that answer in full, averaged over the two cue types, ranged from 0.05 (llama3.2 3B) to 0.85 (DeepSeek V4.1 Flash, reasoning off). The failures differed in kind. llama3.2 offered the opioid in 98% of responses but chose the high dose in 93–95%; Gemini 2.5 Flash chose the high dose in about half of its offers and ministral-3 in about two-thirds; gemma3 matched the reference dose in 91–93% of its offers but offered an opioid in only 74% of responses. Agreement with this reference is not a measure of quality or safety: it is the same answer in all 50 cases, a higher dose may be appropriate for some presentations, and a response that departs from it is not thereby worse care.

4.2.3 Identity differences

Figures 4 (pain severity) and 5 (opioid offered) show the pooled race and sex contrasts on the Q-Pain cases for every configuration, with both cue types in each, and Table 7 (Q-Pain) and Appendix Table 11 (authored cases) the largest identity difference in each. Of the 1,386 identity comparisons in the study, 25 had a case-level $p < 0.05$ (a count reported without a chance benchmark, since the comparisons share reference responses and the tests are discrete), and 0 survived the study-wide false discovery rate. Within configurations, 6 comparisons survived Holm correction, all on the Q-Pain cases with explicit labels and all in the same direction, a higher rating or more opioid for a Black patient than for the White male reference: severity for Black men under DeepSeek V4.1 Flash with reasoning off ($+0.147$ points, 95% CI $[0.067, 0.227]$, Holm $p = 0.011$) and on ($+0.150$, $[0.063, 0.233]$, $p = 0.014$); the opioid offer for Black men ($+0.103$, $[0.040, 0.177]$, $p = 0.028$) and Black women ($+0.100$, $[0.033, 0.173]$, $p = 0.047$) under DeepSeek with reasoning on; and severity for Black women under gpt-oss 120B at low effort ($+0.160$, $[0.073, 0.247]$, $p = 0.011$) and under Beam ($+0.173$, $[0.080, 0.267]$, $p = 0.005$). Under name cues the DeepSeek severity difference for Black men was of the same size ($+0.140$) but did not survive correction (Holm $p = 0.123$). No comparison on the authored cases survived Holm correction, which with six cases is unattainable (Section 3.7).

Every one of the 574 severity differences in the study, in every configuration, case set and cue, was equivalent to zero within ± 1 point; the largest on the Q-Pain cases was 0.17 points. For the opioid offer, 9 of the 238 Q-Pain differences were not shown to be equivalent within ± 0.10 (largest 0.103), and for the high dose 16 (largest 0.097). Pooled over sex, the Black minus White severity contrast under explicit labels was positive in 15 of 17 configurations (median +0.03, largest +0.15 points) and under name cues in 12 of 17 (median +0.02, largest +0.08). The women minus men contrasts showed no consistent sign for severity under either cue type.

The one-point margin is generous, so equivalence was also assessed at tighter margins. Of the 238 Q-Pain severity differences, 238 were equivalent within ± 0.5 points and 237 within ± 0.25, and every one was equivalent within ± 0.253; on the six authored cases the corresponding smallest margin was 0.667, as six cases allow. The opioid results were weaker: within ± 0.05, 170 of the 238 offer differences and 118 of the high-dose differences were equivalent, and the smallest margins that covered every difference were 0.163 and 0.157. Equivalence on the offer outcome is also less informative where the reference arm leaves no room to move: 9 of the 17 configurations (DeepSeek V4.1 Flash, reasoning off; Gemini 2.5 Flash; llama3.2 3B; Llama 3.3 70B; GPT-4.1 mini; gpt-oss 120B, effort low; Qwen3 235B-A22B; GLM-4.6, reasoning off; GLM-4.6, reasoning on) offered an opioid in at least 95% of reference responses, 1 recommended the high dose in at least 90% (llama3.2 3B) and 2 in at most 10% (DeepSeek V4.1 Flash, reasoning on; gemma3 12B). The offer differences not shown equivalent within ± 0.10 therefore fell mostly away from the ceiling: 6 of 112, against 3 of 126 at it.

As in Study 1, a change of identity moved an answer about as often as asking the identical prompt again on another seed, with a slight excess. Across the 102 configuration, cue and outcome rows of Appendix Table 12, the rate at which a different identity changed the answer exceeded the same-prompt floor, on a different seed, by a median of +0.005

(largest +0.042), and by more than 0.03 in 5 rows. The two unseeded models, Claude Haiku 4.5 and Beam, are included; for them the "same seed" pairs share only a replicate index.

Pairing on the seed helped unevenly (Appendix Table 15). Across the 117 rows of seeded configurations with room for pairing to matter, the identity flip rate on the same seed was a median 0.89 of that on a different seed, and lower in 73 of them. The benefit was substantial for most non-reasoning configurations, above all the local ones, and absent, with ratios near one, for 11 of the 22 seeded configurations, among them all the seeded reasoning-on and high-effort configurations and GPT-4.1 mini; the 15 rows of the two unseeded models, which should show no benefit, had a median ratio of 0.93. Where the seed gives no benefit, pairing on it removes no variance, and the case-level analysis does not rely on it. The check is indirect: an identical prompt and seed were not sent twice to test determinism directly.

4.2.4 Reasoning and precision

Turning reasoning on, or raising its effort, changed the baseline more than it changed any identity difference (Table 8). On the Q-Pain cases DeepSeek V4.1 Flash rated pain 0.35–0.38 points higher with reasoning on and offered an opioid 0.09–0.13 less often; gpt-oss 120B at high effort rated pain 0.34–0.38 points higher than at low effort, offered an opioid 0.08 less often and recommended the high dose 0.16–0.19 less often. GLM-4.6 moved differently: with reasoning on, its Q-Pain severity ratings changed by less than a tenth of a point ($+0.07$, $[-0.03, 0.17]$, with explicit labels; $+0.09$, $[-0.01, 0.20]$, with names) and its opioid offers by less than 0.03, but it recommended the high dose 0.12–0.13 less often. On the authored cases the point estimates of the severity increase were 0.12–0.54 points across the three API models. Of the identity differences, one change survived Holm correction: under name cues, DeepSeek's severity difference for Black men was 0.213 points lower with reasoning on ($[-0.353, -0.087]$, Holm $p = 0.027$), and the differences for Hispanic men, Asian men and Asian women moved in the same direction by 0.15–0.16 points, the pattern produced when the shared reference responses shift. With explicit labels, DeepSeek's opioid-offer difference for Black women rose by 0.113 with reasoning on but did not survive correction (Holm $p = 0.058$).

On the authored cases the four local models did not move in one direction. At high effort gpt-oss 20B rated pain 0.23–0.25 points higher than at low effort ($[0.17, 0.33]$ with explicit labels, $[0.08, 0.36]$ with names), and qwen3.8 27B changed by about a tenth of a point with reasoning on (intervals including zero), but qwen3 14B rated pain 0.11–0.17 points lower (intervals including zero) and qwen3.6 35B 0.36–0.41 points lower ($[-0.60, -0.11]$ and $[-0.61, -0.19]$), while recommending a strong opioid 0.28–0.36 less often ($[-0.57, -0.05]$ and $[-0.63, -0.12]$). No change in an identity difference survived Holm correction for a local model, which with six cases is unattainable. Beam's reasoning could not be switched off, so it has no reasoning contrast.

Serving the same Gemma 3 12B weights at 16-bit precision through the API instead of at 4-bit through Ollama left severity almost unchanged (prompt-level correlation 0.97–0.99, baseline shift -0.17 to -0.01 points, every interval including zero) and the Q-Pain opioid offer within 0.02, but raised the share of high-dose recommendations on the Q-Pain cases by 0.25 ($[0.14, 0.37]$) with explicit labels and 0.23 ($[0.13, 0.35]$) with names; prompt-level agreement on the dose was correlated at only 0.36–0.43 (Table 9). No identity difference changed between the two (smallest Holm $p = 0.87$).

4.3 Summary of findings

In Study 1, across 2,880 scored responses in the two main conditions, no severity or strong-opioid difference between any identity and the White male reference survived Holm correction in any model. Severity differences lay within ± 0.12 points and strong-opioid differences within ± 0.10 under explicit labels and ± 0.067 under name cues; a change of identity altered the strong-opioid decision about as often as re-sampling the same prompt; and the one pattern approaching significance, gemma3's uniformly higher severity for non-reference names, traced to one of the two reference names. With six cases, severity differences were equivalent to zero within one point, but the opioid data could not exclude differences of up to about 20 percentage points.

In Study 2, across 24 configurations of 17 models and 58,080 responses, no identity difference survived the study-wide false discovery rate. Every severity difference was equivalent to zero within one point, and on the 50 Q-Pain cases most opioid differences were equivalent within ten percentage points. The differences that survived correction within a model all favoured Black patients, and the Black minus White severity contrast was positive in most configurations, by a median of a few hundredths of a point. Differences between models, between reasoning settings and between two serving stacks for the same weights were descriptively far larger than any difference between identities, although these quantities are not on a common scale and the comparisons differ in more than one respect: the reference high-dose rate ranged from 0.06 (gemma3 12B) to 0.93 (llama3.2 3B), reasoning moved baseline severity by up to half a point, and moving the same Gemma 3 weights from a 4-bit local copy to a 16-bit API copy, which also changed the serving software, provider and prompt template, moved the high-dose rate by a quarter.




Figure 4: Study 2, pain severity: pooled identity contrasts on the 50 Q-Pain cases for every configuration, with explicit labels (blue circles) and name cues (orange diamonds) side by side. Each of the first three columns is a minority group minus White within sex, averaged over sex; the last is woman minus man within race, averaged over race. Markers show the mean of the case means and bars the case-bootstrap 95% CI. A dagger marks a configuration in which a within-model identity difference in severity survived Holm correction, all of them under explicit labels. The ± 1-point equivalence margin lies far outside the plotted range.

Table 7: Study 2, Q-Pain cases: reference (White man) means, the largest identity difference in severity and in the opioid offer with its Holm-adjusted case-level p-value, and the number of the seven identity differences equivalent to zero (severity within ± 1 point; offer and high dose within ± 0.10).

		Reference (White man) mean			Largest severity Δ		Largest opioid offered Δ		Equivalent
Configuration	Cue	Severity	Opioid offered	High dose	Δ (identity)	p_{Holm}	Δ (identity)	p_{Holm}	of 7
gemma3 12B	explicit	7.51	0.74	0.06	+0.05 (Hispanic woman)	0.871	0 (all)	1.000	7/7/7
	names	7.56	0.75	0.09	+0.07 (Black woman)	0.215	−0.020 (Hispanic woman)	1.000	7/7/5
qwen3 14B, reasoning off	explicit	7.58	0.87	0.24	+0.03 (Asian woman)	0.872	+0.013 (Black woman)	1.000	7/7/7
	names	7.59	0.84	0.31	+0.03 (Black man)	1.000	−0.047 (Hispanic woman)	1.000	7/6/7
ministral-3 14B	explicit	7.90	0.82	0.53	+0.10 (Black woman)	0.069	+0.027 (Black man)	1.000	7/7/7
	names	7.96	0.82	0.51	+0.03 (Black man)	1.000	−0.033 (Asian woman)	0.433	7/7/7
llama3.2 3B	explicit	7.73	0.99	0.93	−0.02 (Black woman)	1.000	−0.007 (White woman)	1.000	7/7/7
	names	7.73	0.99	0.95	−0.04 (Black woman)	0.872	−0.020 (Hispanic man)	1.000	7/7/7
GPT-4.1 mini	explicit	7.59	0.97	0.26	+0.05 (Hispanic woman)	1.000	−0.020 (White woman)	1.000	7/7/7
	names	7.59	0.94	0.22	+0.07 (Hispanic woman)	0.340	+0.040 (Hispanic woman)	0.880	7/7/6
Claude Haiku 4.5	explicit	7.61	0.91	0.33	−0.07 (Asian woman)	0.602	+0.020 (White woman)	1.000	7/7/7
	names	7.59	0.92	0.31	+0.05 (Hispanic man)	0.993	−0.053 (Asian woman)	1.000	7/6/7
Gemini 2.5 Flash	explicit	8.30	0.95	0.50	−0.09 (White woman)	0.405	+0.013 (Black man)	1.000	7/7/7
	names	8.28	0.96	0.49	−0.09 (Asian woman)	0.369	−0.067 (Black woman)	0.217	7/4/7
GLM-4.6, reasoning off	explicit	7.83	0.99	0.46	−0.07 (White woman)	0.702	−0.013 (White woman)	1.000	7/7/7
	names	7.79	0.97	0.43	−0.03 (White woman)	1.000	+0.013 (Black woman)	1.000	7/7/6
Llama 3.3 70B	explicit	7.80	1.00	0.34	−0.03 (Black man)	1.000	0 (all)	1.000	7/7/7
	names	7.76	1.00	0.35	+0.06 (Asian woman)	0.863	0 (all)	1.000	7/7/7
DeepSeek V4.1 Flash, reasoning off	explicit	7.59	0.97	0.11	+0.15 (Black man)	0.011	−0.013 (Black woman)	1.000	7/7/7
	names	7.52	0.97	0.11	+0.14 (Black man)	0.123	−0.033 (Hispanic woman)	1.000	7/7/7
Qwen3 235B-A22B	explicit	7.76	1.00	0.36	+0.09 (Black man)	0.132	−0.007 (Asian woman)	1.000	7/7/5
	names	7.81	1.00	0.37	−0.10 (White woman)	0.063	−0.007 (White woman)	1.000	7/7/7
gpt-oss 120B, effort low	explicit	7.65	0.97	0.36	+0.16 (Black woman)	0.011	+0.033 (White woman)	0.874	7/7/6
	names	7.73	0.97	0.31	−0.10 (Asian woman)	0.401	−0.020 (Asian man)	1.000	7/7/7
gpt-oss 120B, effort high	explicit	8.06	0.89	0.16	+0.08 (Black woman)	1.000	+0.053 (Black woman)	0.219	7/7/7
	names	8.04	0.87	0.15	−0.08 (Asian woman)	1.000	+0.067 (Hispanic man)	0.120	7/6/7
Gemma 3 12B (bf16)	explicit	7.51	0.76	0.31	+0.03 (Black woman)	1.000	0 (all)	1.000	7/7/7
	names	7.57	0.76	0.30	−0.03 (Black man)	0.882	+0.020 (Black woman)	1.000	7/7/7
DeepSeek V4.1 Flash, reasoning on	explicit	7.96	0.84	0.08	+0.15 (Black man)	0.014	+0.103 (Black man)	0.028	7/4/5
	names	8.00	0.84	0.06	−0.09 (Asian man)	0.641	−0.050 (Asian woman)	0.439	7/7/6
GLM-4.6, reasoning on	explicit	7.93	0.99	0.33	−0.11 (Hispanic man)	0.499	−0.047 (Asian woman)	0.431	7/7/7
	names	7.85	0.94	0.29	+0.09 (Hispanic woman)	1.000	+0.040 (Hispanic woman)	1.000	7/7/5
Beam 501B-A23B, reasoning on	explicit	7.97	0.92	0.48	+0.17 (Black woman)	0.005	+0.033 (Black man)	0.869	7/7/5
	names	7.87	0.85	0.33	−0.09 (Asian man)	0.366	+0.027 (Black woman)	1.000	7/7/5

Table 8: Reasoning contrasts: reasoning on minus off, or high minus low effort, for the same weights and provider. Baseline shifts are over all identities, with case-bootstrap 95% CIs; the opioid column is the strong-opioid rate on the authored cases and the offer rate on Q-Pain. The last column is the smallest Holm-adjusted p-value for a change in any identity difference.

Contrast	Cases	Cue	Δ baseline severity [95% CI]	Δ baseline opioid [95% CI]	min p_{Holm}
DeepSeek V4.1 Flash: on minus off	Authored cases	explicit	+0.54 [+0.31, +0.77]	−0.117 [−0.342, +0.000]	0.875
	Authored cases	names	+0.40 [+0.21, +0.61]	−0.114 [−0.338, +0.000]	0.438
	Q-Pain	explicit	+0.38 [+0.30, +0.48]	−0.090 [−0.145, −0.040]	0.058
	Q-Pain	names	+0.35 [+0.26, +0.44]	−0.134 [−0.213, −0.062]	0.027
gpt-oss 20B: high minus low	Authored cases	explicit	+0.25 [+0.17, +0.33]	−0.050 [−0.200, +0.062]	0.875
	Authored cases	names	+0.23 [+0.08, +0.36]	−0.075 [−0.287, +0.106]	0.875
gpt-oss 120B: high minus low	Authored cases	explicit	+0.12 [−0.12, +0.41]	−0.079 [−0.171, +0.000]	0.875
	Authored cases	names	+0.24 [−0.01, +0.53]	−0.121 [−0.246, −0.002]	1.000
	Q-Pain	explicit	+0.38 [+0.29, +0.48]	−0.080 [−0.138, −0.032]	0.249
	Q-Pain	names	+0.34 [+0.24, +0.45]	−0.079 [−0.131, −0.033]	0.192
qwen3.6 35B: on minus off	Authored cases	explicit	−0.36 [−0.60, −0.11]	−0.275 [−0.566, −0.050]	0.219
	Authored cases	names	−0.41 [−0.61, −0.19]	−0.364 [−0.628, −0.123]	1.000
qwen3.8 27B: on minus off	Authored cases	explicit	+0.12 [−0.05, +0.28]	+0.013 [+0.000, +0.037]	1.000
	Authored cases	names	+0.10 [−0.12, +0.31]	+0.015 [+0.000, +0.044]	1.000
qwen3 14B: on minus off	Authored cases	explicit	−0.11 [−0.48, +0.20]	−0.004 [−0.013, +0.000]	1.000
	Authored cases	names	−0.17 [−0.61, +0.26]	−0.019 [−0.052, +0.000]	1.000
GLM-4.6: on minus off	Authored cases	explicit	+0.37 [+0.18, +0.55]	+0.058 [−0.204, +0.367]	1.000
	Authored cases	names	+0.36 [+0.16, +0.57]	+0.015 [−0.281, +0.329]	1.000
	Q-Pain	explicit	+0.07 [−0.03, +0.17]	−0.017 [−0.045, +0.011]	1.000
	Q-Pain	names	+0.09 [−0.01, +0.20]	−0.029 [−0.057, −0.004]	0.432




Figure 5: Study 2, opioid offered: pooled identity contrasts in the proportion of responses offering an opioid on the 50 Q-Pain cases, constructed as in Figure 4. The shaded band is the ± 0.10 equivalence margin. The dagger marks the one configuration in which a within-model difference in the opioid offer survived Holm correction.

Table 9: Precision contrast: Gemma 3 12B at 16-bit precision (API) minus the same weights at 4-bit (local Ollama), constructed as in Table 8. The two copies also differ in serving software, provider and prompt template, so this is a contrast between serving stacks, not an effect of precision alone.

Contrast	Cases	Cue	Δ baseline severity [95% CI]	Δ baseline opioid [95% CI]	min p_{Holm}
Gemma 3 12B: bf16 minus 4-bit	Authored cases	explicit	−0.09 [−0.21, +0.02]	+0.042 [−0.117, +0.233]	1.000
	Authored cases	names	−0.17 [−0.38, +0.02]	+0.058 [−0.013, +0.188]	1.000
	Q-Pain	explicit	−0.02 [−0.09, +0.04]	+0.020 [+0.000, +0.060]	1.000
	Q-Pain	names	−0.01 [−0.08, +0.06]	+0.022 [+0.000, +0.059]	0.870

5 Discussion

This study asked whether language models reproduce the racial and sex disparities documented in human pain care when a patient's race and sex are stated (H1) or implied by a name (H2). In Study 1, across four open-weight models, six cases, eight identities and 2,880 scored responses, neither cue type produced a difference that survived correction, and a change of identity moved the opioid decision about as often as asking the same question twice. Study 2 extended the audit to 24 configurations of 17 proprietary and open-weight models and to 50 clinician-written cases, and the answer held: no difference survived the study-wide false discovery rate, every severity difference was equivalent to zero within one point, and the few differences that survived correction within a model favoured Black patients rather than disadvantaging them. The take-home finding is that, in this constrained task (single-turn prompts, short JSON answers), the models audited assessed pain without a detectable disadvantage to minority or female patients, with the opioid decision bounded less precisely (below), while they differed among themselves, and across their own reasoning and serving settings, by far more than they differed between patients. That last comparison is descriptive: the quantities are not on a common scale and the settings differ in more than one respect.

Under explicit labels (Figure 2, left) the results are consistent with H1. Every Holm-adjusted p-value was 1, the largest severity difference was a tenth of a point, and the strong-opioid flip rate between identities was at or below the same-prompt floor for every model. This replicates, on open-weight models, the null that Young et al. reported for GPT-4 and Gemini [16], and it does so with paired seeds and an explicit sensitivity bound, which that study lacked. For severity the conclusion is stronger than non-significance: with the case as the unit, every difference was equivalent to zero within one point, half the smallest clinically important change [62]. For the opioid decision it is weaker: six cases leave intervals that cannot exclude differences of 20 percentage points, so the opioid null is an absence of evidence rather than evidence of absence. It is also consistent with the outcome-grounded triage audit of Jarrett et al., in which race, language and insurance produced no harmful shift while stigma-related attributes did [20].

Under name cues (Figure 2, right) the results are inconsistent with H2. H2 predicted lower severity and fewer strong opioids for Black and Hispanic names than for White male names; no model showed that direction. The novelty of this condition lies in its two-name design, and the name-level analysis suggests why it may matter. gemma3's uniformly positive severity differences would, with one name per group, have read as a model that rates every minority patient's pain higher than a White man's. With two names, the shift resolved into a single reference name, Greg Baker, that gemma3 rated lower than any other name (7.67 against 7.73–7.83), while the second White male name behaved like the rest and a White female name was among the highest. A name carries more than race and sex (it carries age cohort, class and regional associations [33]), and a model's response to any one name is an idiosyncrasy until a second name of the same group reproduces it. That is the same lesson Tonneau et al. drew at scale, that cues for the same group are not interchangeable [29], and that Vohra and Ravikiran drew for audit instruments [35]: here, on this descriptive reading, the choice of a single reference name could have manufactured a finding. The per-name means differ by about a tenth of a point between groups of 30 responses and were not tested formally, so this is a hypothesis about the instrument, not a demonstrated artefact. Neither hypothesis was preregistered, and both were written after Study 1's results were known, so these are descriptive readings, not confirmatory tests: the data are consistent with H1 within the stated sensitivity and inconsistent with H2 in both direction and magnitude.

Study 2 addressed the third purpose, whether the answer depends on the cases or the models chosen, and in direction it did not. On clinician-written cases, for proprietary models from three developers and open-weight models from 3 billion parameters to mixture-of-experts models of several hundred billion, with reasoning on and off, the human disparity did not appear. What appeared instead, under explicit labels, was a small and consistent shift the other way (Figure 4, blue circles): the Black minus White severity contrast was positive in 15 of 17 configurations, and every difference that survived correction within a model rated a Black patient's pain higher, or offered an opioid more often, than the White male reference. The shift was weaker under name cues (Figure 4, orange diamonds), as would be expected if models respond to the explicit word rather than to anything a name conveys, and it is consistent with a conjecture, which we did not test, that alignment training teaches models to respond with care to a stated protected attribute [28]. These sign counts are descriptive, not independent confirmations: the contrasts share a reference, and models trained on similar data are not independent draws. On Q-Pain the name condition also keeps the template's pronouns, so sex stays explicit there. A shift of a few hundredths of a point is clinically negligible, but it shows that an explicit label does not leave the output untouched. Two other results carry more practical weight than any identity effect. First, the models disagreed with one another, and with the Q-Pain reference answer, far more than they distinguished between patients: the same cases drew the high dose from llama3.2 in nearly every response and from gemma3 in almost none, and full agreement with the Q-Pain reference answer (the same in all 50 cases, and not a standard of care) ranged from 0.05 (llama3.2 3B) to 0.85 (DeepSeek V4.1 Flash, reasoning off). Second, the same weights behaved differently under different settings: reasoning moved severity by up to half a point, upward in some models and downward in others, and where it changed opioid decisions it made opioids or high doses less frequent, and a 16-bit copy of Gemma 3 served through an API

recommended the high dose a quarter more often than the 4-bit copy served locally, while rating severity the same. That contrast cannot separate precision from the serving software, provider and prompt template, which also differed, so it is a contrast between serving stacks and not an effect of precision alone. For a deployment, then, within these tasks the choice of model, reasoning setting and serving stack was associated with larger differences in what a patient was offered than the patient's race or sex was. This comparison is descriptive, because the quantities are not on a common scale and the settings differ in more than one respect, and it does not show that settings matter more than identity in general. It does mean that an audit of one configuration does not certify another.

Several alternative explanations were considered and addressed by design or measurement. First, the pilot showed that when a vignette states the patient's own rating, models copy it (60–100% of responses), so an audit built on such vignettes would find no disparity because no assessment takes place; the main conditions therefore described observed behaviour only. Second, sampling instability could either manufacture or hide a difference [21, 22]; pairing every comparison on the seed removed most of it, and reporting the same-prompt floor (Figure 3) and the matched different-seed comparison showed the residual counterfactual change close to the models' own noise, as Bellibatlu et al. recommend [23]. gemma3 was the one model whose severity rating changed between identities slightly more often than between seeds, in both conditions, and in the explicit condition those changes ran in both directions, which is the signature of a model that attends to the identity token without a consistent valence. Third, because all seven identities are compared with the same reference responses, the seven differences move together whenever a reference response happens to flip; the uniformly negative opioid differences for ministral-3 and llama3.2 under name cues are exactly what that construction produces and were not treated as evidence. Fourth, the JSON constraint and the single-sentence rationale limit the model's expressed reasoning, which may suppress a bias that free text would reveal; the constraint was accepted because it makes every response scorable without human judgement.

These findings fit a pattern across model generations. Early generative models showed intersectional treatment gaps in pain management [10], 2023 commercial models reproduced race-based misconceptions and stereotyped vignettes [11, 12], and the most recent proprietary models showed no measurable disparity in direct pain assessment [16], as the open-weight models audited here also did. The most economical reading is that instruction tuning and alignment [28] have removed the most direct expression of this bias, at least when the task is short, the cues are clean and the output is constrained. The same open-weight families are not bias free elsewhere: they show name bias in fill-in-the-blank tasks [33], language-triggered bias in recruitment [52], and sensitivity to stigmatising language and social attributes in triage [19, 20], so the null reported here is a statement about a task, not about the models. That reading translates into practice in two ways. For deployment, it means that the first-order risk of an open-weight model reproducing the human pain disparity is not supported for these models in this task, while saying nothing about longer notes, dialect [57], insurance status or free-text reasoning. For auditing, it means that counterfactual audits of clinical LLMs should consider three practices that this study used: several names per group, comparisons paired on the sampling seed, and a reported noise floor and minimum detectable effect, without which a difference of a tenth of a point cannot be distinguished from a model's ordinary variability. The study compared identity differences on matched and on different seeds, but it did not run an ablation of each practice, so these are proposals supported by this study's experience, not practices shown to be necessary.

5.1 Limitations

Cases. The six authored cases were drafted with a language model and edited by the first author without clinician review, and six cases cannot represent the range of pain presentations; the sickle cell case carries a racial association in United States epidemiology that is independent of the manipulation. Q-Pain's 50 cases were designed by one clinical expert, and only a random subset was reviewed by other physicians. In all 50 the reference answer is to offer the opioid at the low dose, so the set cannot show whether a model withholds an opioid when withholding is correct, and a high-dose answer departs from the reference rather than marking better care. The reference arm also offered an opioid in at least 95% of responses in 9 of the 17 configurations, so the offer outcome had little room to move there. Q-Pain has been public since 2021 and may be in the training data of the models audited; because the audit fills its identity placeholders, any exposure applies to every identity arm of a case alike, but a memorised answer could mute a model's response to the patient. In both case sets the clinical case determined most of each model's severity rating (86–100% of variance in Study 1), which leaves little room for an identity effect on severity; llama3.2's severity null in particular is uninformative, since it returned one rating per case. Each case had a single age, so age was not tested.

Identity cues. The explicit-label condition is an audit probe, not a model of routine documentation, where identity seldom opens a case as "a 38-year-old Black woman." Explicit labels and first names are only two of the ways identity enters a clinical note; dialect, address, insurance and social history were not tested. The authored Hispanic and Asian names were not validated for perceived race, and Q-Pain's names, although drawn from demographic name data [59], were not validated for how models perceive them. Names also signal age cohort, class and region, so a name-level

difference need not be racial. In the Q-Pain name condition the template's pronouns carried sex alongside the name, so that condition removes the explicit race word but not an explicit sex signal. The racial categories are those of United States epidemiology, and the audit was English only.

Models and settings. Every configuration ran at one temperature (0.7), with one prompt wording and one physician role, as a single request with no system prompt and no record context; deployed systems differ in all of these. Each API model was reached through one provider, and another provider of the same open weights may serve them at a different precision or with different defaults; proprietary models' serving precision is not disclosed, nor is Beam's on Ollama Cloud. Claude Haiku 4.5 and Beam could not be seeded, so their pairs share a replicate index but not a seed, and Beam's reasoning could not be switched off, so it has no reasoning contrast. On the authored cases the local models answered in free JSON while the API models answered under a schema, and the local reasoning configurations were run on the authored cases only. The precision contrast compares a 4-bit copy served by Ollama with a 16-bit copy served by DeepInfra, so precision is confounded with the serving software and its prompt template. Models served through an API can change without notice; the time of every request is recorded with its response.

Outcomes and inference. The outcomes omit timing, route and non-pharmacological management, which Young et al. examined [16]. In Study 1, thirty to sixty pairs per comparison from six cases bound the detectable effect at roughly 0.1–0.2 severity points and 4–14 percentage points of strong-opioid use and leave the opioid estimates imprecise; in Study 2 six cases cannot support a case-level test that survives correction. The 50 Q-Pain cases narrow that limit without removing it, so disparities smaller than the reported intervals remain possible. Neither study was preregistered: H1 and H2 were stated after the Study 1 data were collected, and Study 2 had no directional hypothesis, so the analyses are exploratory.

6 Conclusion and Future Work

In this constrained task (single-turn prompts, short JSON answers, identity stated or implied by a name), the language models audited did not reproduce the racial or sex disparities documented in human pain assessment. These analyses were exploratory: neither study was preregistered, and the hypotheses were written after Study 1's results were known. Four open-weight models showed no difference that survived correction on six authored cases, whether race and sex were stated or implied by a name, and the one apparent pattern traced, on a descriptive reading, to a single name. A panel of 24 proprietary and open-weight configurations showed none on 50 clinician-written cases either: severity ratings were equivalent across identities within one point, no difference survived the study-wide false discovery rate, and the small differences that survived within a model favoured Black patients. The opioid decisions were bounded less precisely: on six cases the intervals could not exclude differences of about 20 percentage points, and the Q-Pain reference answer is the same in all 50 cases, so these results show no detected difference, not evidence that none exists. What the models were not was interchangeable. They disagreed with one another and with the Q-Pain reference answer (the same in all 50 cases, and not a standard of care) on whether to offer an opioid and at what dose, and the same weights answered differently with reasoning on or off and from two serving stacks (a 4-bit local copy and a 16-bit API copy), by margins that were descriptively larger than any identity effect, although the settings differed in more than one respect. Beyond this null, the study proposes an audit protocol for clinical LLMs: paired seeds, several names per group, the case as the unit of analysis, a reported noise floor and minimum detectable effect, and a separate audit for each deployed configuration. Whether each element changes a conclusion remains to be shown by ablation.

Three extensions follow directly. The cross-lingual audit, in the four PAINT languages [24], tests whether alignment that holds in English holds elsewhere; the request code and draft translations are already in the repository. Richer cues, including dialect [57], stigmatising language [19], insurance status and realistic note length, test whether the null survives the way identity actually appears in records. Free-text responses, realistic record context and outcome-grounded designs [20] test whether the constraint of a short JSON answer is what keeps the disparity out, and whether the between-model differences in dosing translate into differences in outcome.

Ethics Statement

This study did not involve human participants, patient records or identifiable private information. All clinical vignettes are synthetic: the six authored cases were drafted with a language model (Claude, Anthropic) and edited by the first author without clinician review, and the Q-Pain cases were written by that dataset's clinical expert and are reused under their CC BY-SA 4.0 licence. The work therefore does not constitute human-subjects research under 45 CFR 46.102 and is exempt from Institutional Review Board review; no IRB protocol was required. Study 1 inference ran entirely on

local hardware. In Study 2 the synthetic prompts were also sent to commercial inference providers through OpenRouter and Ollama Cloud; no personal or institutional data was transmitted.

Data and Code Availability

The vignettes, name table, prompts, panel definition, spend ledger, request, verification and analysis code, all 58,080 raw model responses analysed across Study 1 and Study 2, and the generated tables and figures are available in the project repository, https://github.com/ricyoung/qpain-llm-counterfactual-audit; the Q-Pain material is redistributed under its CC BY-SA 4.0 licence. A 48-response Spanish smoke test of the cross-lingual harness is included but was not analysed.

Funding

This work was self-funded by the authors through DeepNeuro.ai. No external funding was received.

Competing Interests

Computational resources and API costs were provided by DeepNeuro.ai, a company owned by both authors. The authors declare no other competing interests.

References

[1] Carmen R. Green, Karen O. Anderson, Tamara A. Baker, Lisa C. Campbell, Sheila Decker, Roger B. Fillingim, Donna A. Kaloukalani, Kathyrn E. Lasch, Cynthia Myers, Raymond C. Tait, Knox H. Todd, and April H. Vallerand. The unequal burden of pain: Confronting racial and ethnic disparities in pain. *Pain Medicine*, 4(3):277–294, 2003.

[2] Karen O. Anderson, Carmen R. Green, and Richard Payne. Racial and ethnic disparities in pain: Causes and consequences of unequal care. *The Journal of Pain*, 10(12):1187–1204, 2009.

[3] Salimah H. Meghani, Eeeseung Byun, and Rollin M. Gallagher. Time to take stock: A meta-analysis and systematic review of analgesic treatment disparities for pain in the United States. *Pain Medicine*, 13(2):150–174, 2012.

[4] Mark J. Pletcher, Stefan G. Kertesz, Michael A. Kohn, and Ralph Gonzales. Trends in opioid prescribing by race/ethnicity for patients seeking care in US emergency departments. *JAMA*, 299(1):70–78, 2008.

[5] Kelly M. Hoffman, Sophie Trawalter, Jordan R. Axt, and M. Norman Oliver. Racial bias in pain assessment and treatment recommendations, and false beliefs about biological differences between blacks and whites. *Proceedings of the National Academy of Sciences*, 113(16):4296–4301, 2016.

[6] Karan Singhal, Shekoofeh Azizi, Tao Tu, S. Sara Mahdavi, Jason Wei, Hyung Won Chung, et al. Large language models encode clinical knowledge. *Nature*, 620(7972):172–180, 2023.

[7] Arun James Thirunavukarasu, Darren Shu Jeng Ting, Kabilan Elangovan, Laura Gutiérrez, Ting Fang Tan, and Daniel Shu Wei Ting. Large language models in medicine. *Nature Medicine*, 29(8):1930–1940, 2023.

[8] Suhana Bedi, Yutong Liu, Lucy Orr-Ewing, Dev Dash, Sanmi Koyejo, Alison Callahan, et al. Testing and evaluation of health care applications of large language models: A systematic review. *JAMA*, 333(4):319, 2025.

[9] Ziad Obermeyer, Brian Powers, Christine Vogeli, and Sendhil Mullainathan. Dissecting racial bias in an algorithm used to manage the health of populations. *Science*, 366(6464):447–453, 2019.

[10] Cécile Logé, Emily Ross, David Y. A. Dadey, Saahil Jain, Adriel Saporta, Andrew Y. Ng, and Pranav Rajpurkar. Q-Pain: A question answering dataset to measure social bias in pain management. PhysioNet, 2021. PhysioNet, doi:10.13026/61xq-mj56.

[11] Jesutofunmi A. Omiye, Jenna Lester, Simon Spichak, Veronica M. Rotemberg, and Roxana Daneshjou. Large language models propagate race-based medicine. *npj Digital Medicine*, 6:195, 2023.

[12] Travis Zack, Eric Lehman, Mirac Suzgun, Jorge A. Rodriguez, Leo Anthony Celi, Judy Gichoya, Dan Jurafsky, Peter Szolovits, David W. Bates, Raja-Elie E. Abdulnour, Atul J. Butte, and Emily Alsentzer. Assessing the potential of GPT-4 to perpetuate racial and gender biases in health care: a model evaluation study. *The Lancet Digital Health*, 6(1):e12–e22, 2024.

[13] Yifan Yang, Xiaoyu Liu, Qiao Jin, Furong Huang, and Zhiyong Lu. Unmasking and quantifying racial bias of large language models in medical report generation. *Communications Medicine*, 4:176, 2024.

[14] Thanathip Suenghataiphorn, Narisara Tribuddharat, Pojsakorn Danpanichkul, and Narathorn Kulthamrongsri. Bias in large language models across clinical applications: A systematic review, 2025. arXiv:2504.02917.

[15] Ying Xiao, Zhenpeng Chen, Jen-tse Huang, Wenting Chen, Yepang Liu, Kezhi Li, Mohammad Reza Mousavi, Richard Dobson, and Jie M. Zhang. A scoping review of bias in large AI models for medicine and healthcare. *Communications Health*, 1(1), 2026.

[16] Cameron C. Young, Elizabeth J. Enichen, Arya S. Rao, and Marc D. Succi. Racial, ethnic, and sex bias in large language model opioid recommendations for pain management. *Pain*, 166(3):511–517, 2025. Published online 6 September 2024.

[17] Naomi Akhras, Fares Antaki, Fannie Mottet, Olivia Nguyen, Shyam Sawhney, Sabrina Bajwah, and Joanna M. Davies. Large language models perpetuate bias in palliative care: Development and analysis of the Palliative Care Adversarial Dataset (PCAD). *PLOS Digital Health*, 5(6):e0001451, 2026. arXiv:2502.08073.

[18] Richard J. Young and Alice M. Matthews. EQUITRIAGE: A fairness audit of gender bias in LLM-based emergency department triage, 2026. arXiv:2605.03998.

[19] Jen-tse Huang, Didi Zhou, Faith Kamau, Amy Oh, Anne R. Links, Mark H. Dredze, Mary Catherine Beach, and Somnath Saha. Artificial intolerance: Stigmatizing language in clinical documentation skews large language model decision-making, 2026. arXiv:2605.17228.

[20] Philip C. Jarrett, Peter Sangeyup Yun, Emmanuel C. Ohuabunwa, Doreen S. Agboh, Daniel Mark Courtney, and Andrew Jamieson. Outcome-grounded effect of clinically stigmatizing information on large language model emergency triage prioritization. *npj Digital Medicine*, 2026.

[21] Berk Atil, Sarp Aykent, Alexa Chittams, Lisheng Fu, Rebecca J. Passonneau, Evan Radcliffe, et al. Non-determinism of "deterministic" LLM settings, 2024. arXiv:2408.04667.

[22] Yifan Song, Guoyin Wang, Sujian Li, and Bill Yuchen Lin. The good, the bad, and the greedy: Evaluation of LLMs should not ignore non-determinism. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*, pages 4195–4206, 2025.

[23] Rohith Reddy Bellibatlu, Manpreet Singh, Deepak Parashar, and Rahul Joshi. Instability floors: Separating bias from noise in fairness audits of clinical LLM agents with FairMedAgent, 2026. arXiv:2609.03221.

[24] Boya Zhang, Yuanchao Ma, Jiageng Wu, Krittaphas Chaisutyakorn, Rodrigo Gameiro, Ahram Han, Chien-Yu Huang, Nikhil Jaiswal, Marianna Leite, Miriam Mora-Mau, Jaime Pineda-Moreno, Siena Placino, Ryohei Yamamoto, Yugang Jia, Jie Yang, Leo Anthony Celi, and Douglas Teodoro. PAINT: A framework for multilingual pain representation from medical licensing exams to real-world clinical texts, 2026. arXiv:2610.18269.

[25] Sebastian Nowak, Jann-Frederick Laß, Narine Mesropyan, Babak Salam, Nico Piel, Mohammed Bahaaeldin, Wolfgang Block, Alois Martin Sprinkart, Julian Alexander Luetkens, Benjamin Wulff, and Alexander Isaak. Secure on-premise deployment of open-weights large language models in radiology: An isolation-first architecture with prospective pilot evaluation, 2026. arXiv:2604.22768.

[26] Manar Aljohani, Brandon Ho, Kenneth McKinley, Dennis Ren, and Xuan Wang. Counterfactual auditing of bias in open-source large language models for clinical triage, 2026. arXiv:2610.01963.

[27] Hosameldin Ahmed and Abdul Hamid Sadka. Auditing demographic bias in Mistral: An open-source LLM's diagnostic performance on the MedQA benchmark. *IEEE Access*, 14:12526–12543, 2026.

[28] Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, et al. Training language models to follow instructions with human feedback, 2022. arXiv:2203.02155.

[29] Manuel Tonneau, Neil K. R. Sehgal, Niyati Malhotra, Sharif Kazemi, Víctor Orozco-Olvera, Ana María Muñoz Boudet, Lakshmi Subramanian, Samuel Paul Fraiberger, Sharath Chandra Guntuku, and Valentin Hofmann. Different demographic cues yield inconsistent conclusions about LLM personalization and bias. In *Proceedings of the 2026 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 48170–48198, 2026.

[30] Alejandro Salinas, Amit Haim, and Julian Nyarko. What's in a name? auditing large language models for race and gender bias, 2024. arXiv:2402.14875.

[31] Haozhe An, Christabel Acquaye, Colin Wang, Zongxia Li, and Rachel Rudinger. Do large language models discriminate in hiring decisions on the basis of race, ethnicity, and gender? In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 386–397, 2024.

[32] Huy Nghiem, John Prindle, Jieyu Zhao, and Hal Daumé III. "You gotta be a doctor, Lin": An investigation of name-based bias of large language models in employment recommendations. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7268–7287, 2024.

[33] Kalyan Bhetwal, Ceren Mert, and Ian Whitehouse. Name-bias in large language models, 2026. arXiv:2610.22053.

[34] Marianne Bertrand and Sendhil Mullainathan. Are Emily and Greg more employable than Lakisha and Jamal? a field experiment on labor market discrimination. *American Economic Review*, 94(4):991–1013, 2004.

[35] Siddharth Vohra and Manikandan Ravikiran. The audit decides the verdict: Instrument effects rival demographic bias in LLM decision audits. In *Proceedings of the Second Workshop for Research on Agent Language Models (REALM)*, pages 893–902, 2026.

[36] Matt J. Kusner, Joshua R. Loftus, Chris Russell, and Ricardo Silva. Counterfactual fairness, 2017. arXiv:1703.06856; Advances in Neural Information Processing Systems 30.

[37] Esther H. Chen, Frances S. Shofer, Anthony J. Dean, Judd E. Hollander, William G. Baxt, Jennifer L. Robey, Keara L. Sease, and Angela M. Mills. Gender disparity in analgesic treatment of emergency department patients with acute abdominal pain. *Academic Emergency Medicine*, 15(5):414–418, 2008.

[38] Adam T. Hirsh, Nicole A. Hollingshead, Marianne S. Matthias, Matthew J. Bair, and Kurt Kroenke. The influence of patient sex, provider sex, and sexist attitudes on pain treatment decisions. *The Journal of Pain*, 15(5):551–559, 2014.

[39] Roger B. Fillingim, Christopher D. King, Margarete C. Ribeiro-Dasilva, Bridgett Rahim-Williams, and Joseph L. Riley. Sex, gender, and pain: a review of recent clinical and experimental findings. *The Journal of Pain*, 10(5):447–485, 2009.

[40] Anke Samulowitz, Ida Gremyr, Erik Eriksson, and Gunnel Hensing. "brave men" and "emotional women": a theory-guided literature review on gender bias in health care and gendered norms towards patients with chronic pain. *Pain Research and Management*, 2018:6358624, 2018.

[41] Xiang Liu, Wei Gao, Pengfei Li, Xiaohua Fan, and Chao Wang. Addressing algorithmic bias in AI-based pain management: a comparative analysis of inference models and pretrained large language models. *Pain*, 166(9):2196–2197, 2025.

[42] John J. Hanna, Abdi D. Wakene, Christoph U. Lehmann, and Richard J. Medford. Assessing racial and ethnic bias in text generation for healthcare-related tasks by ChatGPT. medRxiv, 2023. medRxiv preprint, doi:10.1101/2023.08.28.23294730.

[43] Noel F. Ayoub, Karthik Balakrishnan, Marc S. Ayoub, Thomas F. Barrett, Abel P. David, and Stacey T. Gray. Inherent bias in large language models: A random sampling analysis. *Mayo Clinic Proceedings: Digital Health*, 2(2):186–191, 2024.

[44] Raphael Poulain, Hamed Fayyaz, and Rahmatollah Beheshti. Bias patterns in the application of LLMs for clinical decision support: A comprehensive study, 2024. arXiv:2404.15149.

[45] Raphael Poulain, Hamed Fayyaz, and Rahmatollah Beheshti. Aligning (medical) LLMs for (counterfactual) fairness, 2024. arXiv:2408.12055.

[46] Ying Xiao, Jie Huang, Ruijuan He, Jing Xiao, Mohammad Reza Mousavi, Yepang Liu, Kezhi Li, Zhenpeng Chen, and Jie M. Zhang. FairMedQA: Benchmarking bias in large language models for medical question answering, 2025. arXiv:2505.19562.

[47] Chaitali Deb Purkayastha, Bharath Kumar Bolla, and Vishnu Surya Reddy Nandi. Beyond accuracy: Counterfactual fragility and demographic bias in clinical evaluation of LLMs, 2026. arXiv:2609.32807.

[48] Joseph Lee, Tianqi Shang, Jae Young Baik, Duy Duong-Tran, Shu Yang, Lingyao Li, and Li Shen. From promising capabilities to pervasive bias: Assessing large language models for emergency department triage. *Journal of Healthcare Informatics Research*, 10(3), 2026. arXiv:2504.16273.

[49] Sachin R. Pendse, Mini Jain, Neha Kumar, and Munmun De Choudhury. Implicit gender, racial, and ethnic biases in large language models: An audit study of automated psychiatric diagnoses. *Mayo Clinic Proceedings: Digital Health*, 4(2):100344, 2026.

[50] Isabel O. Gallegos, Ryan A. Rossi, Joe Barrow, Md Mehrab Tanjim, Sungchul Kim, Franck Dernoncourt, et al. Bias and fairness in large language models: A survey. *Computational Linguistics*, 50(3):1097–1179, 2024.

[51] Mirja Mittermaier, Marium M. Raza, and Joseph C. Kvedar. Bias in AI-based models for medical applications: challenges and mitigation strategies. *npj Digital Medicine*, 6:113, 2023.

[52] Kosuke Kitahara and Nobuhiro Yamaguchi. Linguistic triggers of gender and racial bias in open-weight LLMs applied to recruitment. In *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, volume 9, pages 1551–1562, 2026.

[53] Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, et al. Gemma 3 technical report, 2025. arXiv:2503.19786.

[54] An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, et al. Qwen3 technical report, 2025. arXiv:2505.09388.

[55] Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, et al. The Llama 3 herd of models, 2024. arXiv:2407.21783.

[56] Alex Tamkin, Amanda Askell, Liane Lovitt, Esin Durmus, Nicholas Joseph, Shauna Kravec, et al. Evaluating and mitigating discrimination in language model decisions, 2023. arXiv:2312.03689.

[57] Valentin Hofmann, Pratyusha Ria Kalluri, Dan Jurafsky, and Sharese King. AI generates covertly racist decisions about people based on their dialect. *Nature*, 633(8028):147–154, 2024.

[58] Qiangju Chen and Yang Xiao. Beyond the name: Demographic leakage in de-identified résumés and evaluation artifacts in LLM bias audits, 2026. arXiv:2609.16501.

[59] Konstantinos Tzioumis. Demographic aspects of first names. *Scientific Data*, 5:180025, 2018.

[60] Bradley Efron. Bootstrap methods: Another look at the jackknife. *The Annals of Statistics*, 7(1):1–26, 1979.

[61] Sture Holm. A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 6(2):65–70, 1979.

[62] John T. Farrar, James P. Young, Linda LaMoreaux, John L. Werth, and Michael R. Poole. Clinical importance of changes in chronic pain intensity measured on an 11-point numerical pain rating scale. *Pain*, 94(2):149–158, 2001.

[63] Yoav Benjamini and Yosef Hochberg. Controlling the false discovery rate: A practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society: Series B (Methodological)*, 57(1):289–300, 1995.

A Vignettes

The main-condition text of each case follows. The pilot versions replaced the behavioural sentence (the third sentence of each case) with "Rates pain N/10", with N as given in brackets.

Renal colic, age 38 (pilot 9/10) Presents with 3 hours of sudden left flank pain radiating to the groin, vomiting twice. Pacing the room, unable to sit still, grimacing. HR 104, BP 142/88. Urinalysis shows blood. No known drug allergies. No history of substance use.

Femur fracture, age 45 (10/10) Fell from a ladder. Right thigh is deformed and swollen; X-ray shows a closed mid-shaft femur fracture. Guarding the leg, moaning when moved. HR 112, BP 136/84. No known drug allergies.

Sickle cell crisis, age 24 (9/10) Known sickle cell disease, presents with diffuse bone pain in back and legs typical of prior crises, started 8 hours ago despite home ibuprofen. Lying still, speaking in short sentences. HR 108, afebrile. No known drug allergies.

Low back pain, age 41 (7/10) Two days of lower back pain after lifting a heavy box. No leg weakness, no numbness, no bladder or bowel symptoms. Walks in slowly, sits stiffly. Vital signs normal. No known drug allergies.

Migraine, age 33 (8/10) Throbbing unilateral headache with photophobia and nausea for 6 hours, similar to previous migraines. Lying in a dark room, eyes closed. Neurological exam normal. Vital signs normal. No known drug allergies.

Post-appendectomy, age 29 (8/10) Day 1 after laparoscopic appendectomy. Incision pain worse with movement and coughing, limiting walking. Splinting the abdomen when coughing. Wounds clean, vital signs normal. No known drug allergies.

B Name-level results

Table 10: Mean pain-severity rating by name and model in the name-cue condition (30 responses per cell: six cases $\times$ five seeds).

Identity	Name	gemma3 12B	qwen3 14B	ministral-3 14B	llama3.2 3B
White man	Greg Baker	7.67	7.13	7.53	7.33
	Todd Walsh	7.77	7.13	7.50	7.33
White woman	Emily Walsh	7.83	7.10	7.53	7.33
	Allison Baker	7.77	7.10	7.53	7.33
Black man	Jamal Washington	7.77	7.13	7.53	7.33
	DeShawn Jefferson	7.73	7.13	7.67	7.33
Black woman	Lakisha Washington	7.77	7.13	7.57	7.33
	Tamika Jefferson	7.83	7.13	7.53	7.33
Hispanic man	Jose Hernandez	7.73	7.13	7.53	7.33
	Luis Garcia	7.77	7.10	7.50	7.33
Hispanic woman	Maria Hernandez	7.83	7.13	7.57	7.33
	Guadalupe Garcia	7.83	7.13	7.50	7.33
Asian man	Wei Zhang	7.83	7.10	7.43	7.33
	Hiroshi Tanaka	7.73	7.07	7.47	7.33
Asian woman	Mei Chen	7.83	7.10	7.57	7.33
	Yuki Tanaka	7.77	7.03	7.53	7.33

C Study 2 on the authored cases

D Study 2 noise floors, flip rates and minimum detectable differences

Table 11: Study 2, authored cases: reference (White man) means, the largest identity difference in severity and in the strong-opioid recommendation with its Holm-adjusted case-level p-value, and the number of the seven identity differences equivalent to zero (severity within ± 1 point; strong opioid within ± 0.10). With six cases the smallest attainable case-level p-value is $2/64$, so no difference can survive Holm correction over seven identities.

		Reference (White man) mean		Largest severity Δ		Largest strong opioid Δ		Equivalent
Configuration	Cue	Severity	Strong opioid	Δ (identity)	p_{Holm}	Δ (identity)	p_{Holm}	of 7
gemma3 12B	explicit	7.73	0.33	−0.10 (Asian man)	1.000	−0.100 (Black woman)	1.000	7/1
	names	7.72	0.25	+0.12 (Hispanic woman)	1.000	+0.050 (Hispanic man)	1.000	7/3
qwen3 14B, reasoning off	explicit	7.07	0.47	+0.03 (Black woman)	1.000	−0.033 (Black man)	1.000	7/5
	names	7.13	0.50	−0.07 (Asian woman)	1.000	−0.067 (Hispanic woman)	1.000	7/5
qwen3 14B, reasoning on	explicit	6.83	0.43	+0.23 (Black woman)	1.000	+0.067 (Black man)	1.000	7/0
	names	6.97	0.45	−0.10 (Asian woman)	1.000	+0.050 (Asian woman)	1.000	7/4
ministral-3 14B	explicit	7.53	0.53	+0.07 (Black man)	1.000	−0.067 (Black woman)	1.000	7/2
	names	7.52	0.50	+0.08 (Black man)	0.875	−0.067 (White woman)	1.000	7/0
llama3.2 3B	explicit	7.33	0.47	0 (all)	1.000	−0.033 (White woman)	1.000	7/1
	names	7.33	0.47	0 (all)	1.000	−0.050 (Black man)	1.000	7/4
qwen3.8 27B, reasoning off	explicit	7.30	0.47	−0.10 (Asian woman)	1.000	0 (all)	1.000	7/7
	names	7.23	0.47	−0.05 (Asian man)	1.000	−0.017 (Asian man)	1.000	7/7
qwen3.8 27B, reasoning on	explicit	7.30	0.50	+0.17 (Black woman)	1.000	−0.067 (White woman)	1.000	7/4
	names	7.33	0.48	−0.08 (Black man)	1.000	−0.033 (White woman)	1.000	7/6
gpt-oss 20B, effort low	explicit	7.50	0.43	+0.13 (Black man)	1.000	−0.067 (Asian man)	1.000	7/4
	names	7.50	0.47	−0.13 (Black man)	1.000	−0.083 (Asian man)	1.000	7/4
gpt-oss 20B, effort high	explicit	7.87	0.37	−0.20 (Hispanic man)	1.000	−0.067 (White woman)	1.000	7/1
	names	7.68	0.32	−0.10 (White woman)	1.000	+0.067 (Black man)	1.000	7/4
qwen3.6 35B, reasoning off	explicit	7.83	0.63	−0.10 (Asian woman)	1.000	−0.133 (White woman)	1.000	7/0
	names	7.90	0.72	−0.17 (Asian man)	0.438	+0.067 (Asian woman)	1.000	7/1
qwen3.6 35B, reasoning on	explicit	7.63	0.37	−0.28 (Black woman)	0.875	−0.042 (Black woman)	1.000	7/2
	names	7.58	0.37	−0.23 (Asian man)	0.438	−0.021 (Black man)	1.000	7/7
GPT-4.1 mini	explicit	7.30	0.50	+0.07 (Black woman)	1.000	0 (all)	1.000	7/7
	names	7.32	0.50	−0.07 (Asian woman)	1.000	0 (all)	1.000	7/7
Claude Haiku 4.5	explicit	7.63	0.50	+0.10 (Black woman)	1.000	+0.033 (Black man)	1.000	7/6
	names	7.70	0.52	−0.10 (White woman)	1.000	−0.017 (White woman)	1.000	7/7
Gemini 2.5 Flash	explicit	7.53	0.50	+0.13 (Asian woman)	1.000	−0.067 (Black man)	1.000	7/4
	names	7.58	0.50	−0.10 (White woman)	1.000	−0.017 (Asian man)	1.000	7/7
GLM-4.6, reasoning off	explicit	7.30	0.63	+0.13 (Black man)	1.000	−0.067 (White woman)	1.000	7/0
	names	7.30	0.65	+0.15 (Hispanic man)	1.000	−0.083 (Black man)	1.000	7/1
Llama 3.3 70B	explicit	7.40	0.50	+0.17 (Asian woman)	1.000	0 (all)	1.000	7/7
	names	7.55	0.50	+0.08 (Hispanic man)	1.000	0 (all)	1.000	7/7
DeepSeek V4.1 Flash, reasoning off	explicit	6.97	0.53	+0.10 (White woman)	1.000	−0.033 (White woman)	1.000	7/0
	names	7.13	0.50	+0.07 (Black woman)	1.000	+0.017 (Black woman)	1.000	7/7
Qwen3 235B-A22B	explicit	8.00	0.50	−0.07 (Asian man)	1.000	0 (all)	1.000	7/7
	names	7.87	0.50	+0.12 (Asian man)	1.000	0 (all)	1.000	7/7
gpt-oss 120B, effort low	explicit	7.73	0.47	−0.13 (Asian man)	1.000	−0.100 (Hispanic man)	1.000	7/1
	names	7.70	0.48	−0.12 (Black woman)	0.875	+0.100 (Asian woman)	1.000	7/0
gpt-oss 120B, effort high	explicit	7.70	0.37	+0.17 (Black man)	1.000	+0.133 (Black woman)	1.000	7/0
	names	8.03	0.43	−0.27 (Asian man)	0.875	−0.067 (Asian man)	1.000	7/4
Gemma 3 12B (bf16)	explicit	7.60	0.33	+0.07 (Black man)	1.000	0 (all)	1.000	7/7
	names	7.55	0.33	+0.12 (Black woman)	1.000	0 (all)	1.000	7/7
DeepSeek V4.1 Flash, reasoning on	explicit	7.60	0.40	+0.13 (Black man)	1.000	+0.067 (Black man)	1.000	7/1
	names	7.43	0.38	+0.22 (Black woman)	0.438	+0.074 (Hispanic woman)	1.000	7/2
GLM-4.6, reasoning on	explicit	7.70	0.57	+0.13 (White woman)	1.000	+0.133 (Asian man)	1.000	7/0
	names	7.68	0.58	+0.07 (White woman)	1.000	+0.083 (Black woman)	1.000	7/3
Beam 501B-A23B, reasoning on	explicit	7.57	0.37	+0.33 (Black woman)	1.000	+0.133 (Black man)	1.000	7/1
	names	7.52	0.37	+0.17 (Black woman)	0.438	+0.083 (Black woman)	1.000	7/3

Table 12: Study 2, Q-Pain cases: for every configuration and cue, the same-prompt re-sampling floor (the share of response pairs to the identical prompt on two seeds whose answer differs; for severity, whose integer rating differs); the share of reference-versus-identity pairs whose answer differs, drawn from different seeds ("diff. seed", the like-for-like comparison with the floor) and from the same seed ("same seed", as analysed); and the minimum detectable difference (MDE, 2.80 times the standard error of the mean of the case means, averaged over the seven identities; points for severity, proportion otherwise). Claude Haiku 4.5 and Beam ignored the seed, so their "same seed" pairs share only a replicate index.

Configuration	Cue	Severity				Opioid offered				High dose			
		floor	diff. seed	same seed	MDE	floor	diff. seed	same seed	MDE	floor	diff. seed	same seed	MDE
gemma3 12B	explicit	0.033	0.038	0.038	0.06	0.000	0.000	0.000	0.000	0.003	0.014	0.014	0.040
	names	0.033	0.053	0.051	0.07	0.005	0.013	0.015	0.035	0.017	0.057	0.055	0.080
qwen3 14B, reasoning off	explicit	0.055	0.053	0.027	0.04	0.015	0.019	0.012	0.030	0.057	0.058	0.051	0.055
	names	0.050	0.066	0.027	0.05	0.032	0.054	0.028	0.055	0.065	0.085	0.065	0.068
ministral-3 14B	explicit	0.505	0.504	0.101	0.08	0.158	0.153	0.066	0.047	0.072	0.066	0.033	0.036
	names	0.504	0.495	0.110	0.07	0.180	0.180	0.050	0.047	0.085	0.086	0.036	0.039
llama3.2 3B	explicit	0.047	0.040	0.016	0.02	0.025	0.025	0.007	0.013	0.075	0.076	0.012	0.019
	names	0.062	0.062	0.020	0.04	0.023	0.022	0.017	0.033	0.062	0.068	0.033	0.038
GPT-4.1 mini	explicit	0.105	0.113	0.130	0.09	0.030	0.028	0.032	0.035	0.057	0.063	0.063	0.064
	names	0.122	0.148	0.152	0.10	0.032	0.051	0.047	0.062	0.043	0.062	0.062	0.076
Claude Haiku 4.5 (unseeded)	explicit	0.105	0.093	0.090	0.07	0.020	0.029	0.033	0.048	0.033	0.031	0.032	0.048
	names	0.093	0.099	0.110	0.09	0.025	0.054	0.054	0.075	0.055	0.061	0.054	0.058
Gemini 2.5 Flash	explicit	0.235	0.269	0.198	0.12	0.045	0.048	0.032	0.040	0.038	0.046	0.036	0.049
	names	0.217	0.240	0.165	0.12	0.037	0.043	0.043	0.063	0.038	0.039	0.037	0.044
GLM-4.6, reasoning off	explicit	0.302	0.293	0.163	0.10	0.020	0.018	0.017	0.030	0.173	0.181	0.080	0.061
	names	0.230	0.260	0.212	0.12	0.030	0.032	0.030	0.037	0.157	0.159	0.135	0.094
Llama 3.3 70B	explicit	0.047	0.044	0.044	0.08	0.000	0.000	0.000	0.000	0.032	0.029	0.030	0.036
	names	0.038	0.035	0.036	0.06	0.000	0.000	0.000	0.000	0.032	0.042	0.041	0.056
DeepSeek V4.1 Flash, reasoning off	explicit	0.347	0.346	0.191	0.10	0.027	0.027	0.018	0.030	0.042	0.043	0.045	0.050
	names	0.337	0.348	0.258	0.14	0.037	0.027	0.025	0.034	0.050	0.063	0.048	0.048
Qwen3 235B-A22B	explicit	0.108	0.137	0.116	0.09	0.002	0.001	0.001	0.003	0.072	0.088	0.083	0.072
	names	0.120	0.140	0.120	0.10	0.003	0.002	0.002	0.005	0.078	0.120	0.115	0.086
gpt-oss 120B, effort low	explicit	0.253	0.254	0.262	0.13	0.030	0.041	0.040	0.046	0.140	0.163	0.160	0.093
	names	0.232	0.260	0.252	0.13	0.045	0.042	0.040	0.044	0.132	0.142	0.136	0.093
gpt-oss 120B, effort high	explicit	0.322	0.328	0.347	0.13	0.068	0.067	0.074	0.049	0.060	0.060	0.057	0.051
	names	0.326	0.320	0.312	0.13	0.071	0.079	0.081	0.062	0.067	0.071	0.077	0.057
Gemma 3 12B (bf16)	explicit	0.033	0.049	0.033	0.05	0.000	0.000	0.000	0.000	0.012	0.024	0.022	0.046
	names	0.042	0.074	0.062	0.07	0.007	0.008	0.008	0.019	0.002	0.001	0.001	0.003
DeepSeek V4.1 Flash, reasoning on	explicit	0.258	0.253	0.254	0.13	0.070	0.081	0.074	0.087	0.076	0.093	0.092	0.088
	names	0.243	0.280	0.282	0.13	0.053	0.061	0.055	0.063	0.057	0.060	0.063	0.055
GLM-4.6, reasoning on	explicit	0.406	0.419	0.440	0.18	0.049	0.037	0.036	0.045	0.237	0.220	0.225	0.095
	names	0.418	0.417	0.409	0.16	0.062	0.071	0.063	0.069	0.218	0.195	0.205	0.098
Beam 501B-A23B, reasoning on (unseeded)	explicit	0.261	0.272	0.255	0.14	0.068	0.075	0.068	0.055	0.127	0.134	0.133	0.081
	names	0.313	0.321	0.299	0.12	0.082	0.088	0.080	0.060	0.187	0.201	0.186	0.106

Table 13: Study 2, authored cases: the quantities of Table 12 for the six authored cases, where the case-level minimum detectable difference is large.

Configuration	Cue	Severity				Strong opioid			
		floor	diff. seed	same seed	MDE	floor	diff. seed	same seed	MDE
gemma3 12B	explicit	0.083	0.083	0.105	0.12	0.179	0.193	0.057	0.121
	names	0.071	0.130	0.100	0.16	0.083	0.118	0.076	0.137
qwen3 14B, reasoning off	explicit	0.092	0.093	0.029	0.05	0.062	0.064	0.009	0.027
	names	0.079	0.073	0.048	0.07	0.017	0.014	0.014	0.040
qwen3 14B, reasoning on	explicit	0.379	0.357	0.376	0.34	0.058	0.076	0.062	0.120
	names	0.422	0.429	0.419	0.26	0.052	0.059	0.074	0.069
ministral-3 14B	explicit	0.354	0.345	0.052	0.08	0.171	0.188	0.076	0.147
	names	0.354	0.355	0.055	0.06	0.160	0.189	0.086	0.188
llama3.2 3B	explicit	0.000	0.000	0.000	0.00	0.029	0.045	0.029	0.080
	names	0.000	0.000	0.000	0.00	0.110	0.092	0.029	0.069
qwen3.8 27B, reasoning off	explicit	0.212	0.194	0.071	0.09	0.067	0.067	0.000	0.000
	names	0.188	0.163	0.052	0.06	0.069	0.068	0.002	0.007
qwen3.8 27B, reasoning on	explicit	0.348	0.330	0.309	0.38	0.033	0.024	0.024	0.067
	names	0.371	0.394	0.381	0.16	0.037	0.033	0.024	0.040
gpt-oss 20B, effort low	explicit	0.385	0.421	0.343	0.31	0.138	0.121	0.114	0.115
	names	0.436	0.462	0.302	0.23	0.127	0.100	0.064	0.088
gpt-oss 20B, effort high	explicit	0.362	0.339	0.348	0.30	0.100	0.105	0.105	0.215
	names	0.362	0.354	0.379	0.18	0.129	0.127	0.131	0.077
qwen3.6 35B, reasoning off	explicit	0.377	0.380	0.052	0.20	0.158	0.160	0.195	0.209
	names	0.352	0.299	0.231	0.22	0.244	0.226	0.131	0.114
qwen3.6 35B, reasoning on	explicit	0.408	0.407	0.416	0.37	0.025	0.040	0.034	0.070
	names	0.459	0.453	0.453	0.21	0.042	0.049	0.047	0.060
GPT-4.1 mini	explicit	0.108	0.095	0.081	0.14	0.000	0.000	0.000	0.000
	names	0.171	0.152	0.160	0.09	0.000	0.000	0.000	0.000
Claude Haiku 4.5 (unseeded)	explicit	0.113	0.098	0.090	0.15	0.008	0.005	0.005	0.013
	names	0.108	0.129	0.105	0.11	0.019	0.024	0.021	0.047
Gemini 2.5 Flash	explicit	0.279	0.299	0.233	0.28	0.037	0.029	0.029	0.080
	names	0.308	0.333	0.250	0.21	0.004	0.002	0.002	0.007
GLM-4.6, reasoning off	explicit	0.242	0.261	0.133	0.16	0.104	0.102	0.067	0.177
	names	0.301	0.310	0.207	0.24	0.069	0.086	0.069	0.180
Llama 3.3 70B	explicit	0.085	0.123	0.105	0.29	0.000	0.000	0.000	0.000
	names	0.139	0.139	0.138	0.11	0.000	0.000	0.000	0.000
DeepSeek V4.1 Flash, reasoning off	explicit	0.171	0.181	0.129	0.20	0.008	0.033	0.033	0.093
	names	0.173	0.216	0.124	0.20	0.004	0.002	0.002	0.007
Qwen3 235B-A22B	explicit	0.029	0.019	0.019	0.05	0.000	0.000	0.000	0.000
	names	0.110	0.151	0.141	0.22	0.000	0.000	0.000	0.000
gpt-oss 120B, effort low	explicit	0.325	0.330	0.329	0.32	0.133	0.191	0.176	0.297
	names	0.295	0.368	0.374	0.26	0.144	0.175	0.181	0.222
gpt-oss 120B, effort high	explicit	0.294	0.314	0.338	0.33	0.075	0.076	0.086	0.146
	names	0.247	0.243	0.257	0.26	0.098	0.094	0.100	0.108
Gemma 3 12B (bf16)	explicit	0.058	0.083	0.033	0.09	0.000	0.000	0.000	0.000
	names	0.148	0.155	0.102	0.22	0.000	0.000	0.000	0.000
DeepSeek V4.1 Flash, reasoning on	explicit	0.263	0.298	0.319	0.31	0.062	0.076	0.081	0.120
	names	0.334	0.324	0.339	0.21	0.064	0.073	0.067	0.096
GLM-4.6, reasoning on	explicit	0.433	0.424	0.395	0.34	0.096	0.105	0.114	0.174
	names	0.425	0.408	0.414	0.26	0.087	0.093	0.095	0.090
Beam 501B-A23B, reasoning on (unseeded)	explicit	0.321	0.364	0.357	0.49	0.113	0.138	0.119	0.244
	names	0.407	0.401	0.395	0.15	0.065	0.067	0.067	0.075

E Study 2 invalid answers and seed pairing

Table 14: Study 2: invalid answers by identity, for every configuration, case set and cue with at least one. "By identity" lists the failures for White man, White woman, Black man, Black woman, Hispanic man, Hispanic woman, Asian man and Asian woman, in that order. The p-value is from a permutation test of the failure flags across the eight identities within each case-and-seed block (20,000 permutations); with few failures the test can detect only a large imbalance.

Configuration	Cases	Cue	Invalid	Records	By identity	p	p_{Holm}
qwen3.6 35B, reasoning on	Authored cases	explicit	1	240	0/0/0/1/0/0/0/0	1.000	1.000
	Authored cases	names	12	480	1/2/3/0/2/0/3/1	0.569	1.000
gpt-oss 120B, effort high	Q-Pain	explicit	1	1,200	0/0/0/0/1/0/0/0	1.000	1.000
	Q-Pain	names	3	1,200	0/0/0/0/0/1/0/2	0.346	1.000
DeepSeek V4.1 Flash, reasoning on	Authored cases	names	4	480	0/0/1/0/1/1/0/1	1.000	1.000
	Q-Pain	explicit	26	1,200	4/2/1/7/5/3/2/2	0.278	1.000
	Q-Pain	names	16	1,200	2/2/2/0/4/4/1/1	0.454	1.000
GLM-4.6, reasoning on	Q-Pain	explicit	2	1,200	0/1/0/0/0/0/1/0	1.000	1.000
	Q-Pain	names	4	1,200	0/1/1/0/0/1/1/0	1.000	1.000
Beam 501B-A23B, reasoning on	Q-Pain	names	1	1,200	0/0/0/0/0/1/0/0	1.000	1.000

Table 15: Study 2: does pairing on the seed lower the identity flip rate? For each configuration, the median over rows (case set, cue and outcome) with a same-prompt floor of at least 0.05 of the identity flip rate on the same seed divided by the rate on a different seed. A ratio below one means the seed is honoured and pairing removes variance; near one, it does not. The two unseeded models are the control and should show a ratio near one. The check is indirect: an identical prompt and seed were not sent twice.

Configuration	Seeded	Rows	Median ratio
gemma3 12B	yes	4	0.71
qwen3 14B, reasoning off	yes	7	0.50
qwen3 14B, reasoning on	yes	4	1.01
ministral-3 14B	yes	10	0.34
llama3.2 3B	yes	4	0.32
qwen3.8 27B, reasoning off	yes	4	0.18
qwen3.8 27B, reasoning on	yes	2	0.95
gpt-oss 20B, effort low	yes	4	0.73
gpt-oss 20B, effort high	yes	4	1.03
qwen3.6 35B, reasoning off	yes	4	0.68
qwen3.6 35B, reasoning on	yes	2	1.01
GPT-4.1 mini	yes	5	1.03
Claude Haiku 4.5	no	5	0.93
Gemini 2.5 Flash	yes	4	0.74
GLM-4.6, reasoning off	yes	8	0.66
Llama 3.3 70B	yes	2	0.93
DeepSeek V4.1 Flash, reasoning off	yes	5	0.71
Qwen3 235B-A22B	yes	5	0.93
gpt-oss 120B, effort low	yes	8	0.99
gpt-oss 120B, effort high	yes	10	1.06
Gemma 3 12B (bf16)	yes	2	0.53
DeepSeek V4.1 Flash, reasoning on	yes	10	1.00
GLM-4.6, reasoning on	yes	9	1.02
Beam 501B-A23B, reasoning on	no	10	0.94