



TOOLBOX TALK #16

UTILITY LINE SAFETY

LOCATE IT. EXPOSE IT. IDENTIFY IT.

DO NOT ASSUME — EXPOSE THE LINE

Never assume a utility marking shows the exact location or depth of an underground utility.

Before mechanical excavation proceeds around a known utility, it must be safely located, exposed, and positively identified.

If you do not know exactly where the utility is — STOP DIGGING.

STAY 3 FEET FROM THE MARKING

When working around a marked underground utility, crews should allow **3 feet on either side of the utility marking** before using mechanical excavation.

Within this area, use extreme care and appropriate safe-excavation methods to locate and expose the utility, such as:

- Hand digging
- Vacuum excavation
- Air knife
- Other approved safe methods

Locate and expose the utility before mechanical excavation proceeds around it.

POSITIVELY IDENTIFY THE UTILITY

Finding a pipe, conduit, or line does not mean you should assume what service it belongs to.

Once exposed, make sure the crew knows:

- **What type of utility it is**
- **Where it is actually located**
- **Which direction it travels**
- **How the crew will safely work around it**

Never assume an exposed utility is **electrical, gas, water, irrigation, communication, abandoned, or another type of service** based only on its appearance.

If the utility cannot be positively identified, STOP WORK and notify your foreman before continuing.

HUDDLE BEFORE YOU DIG

Before mechanical excavation continues around an exposed utility, the foreman and crew should have a quick huddle.

The operator and ground crew need to know:

WHERE IS THE UTILITY?

WHAT TYPE OF UTILITY IS IT?

HOW ARE WE GOING TO WORK AROUND IT SAFELY?

Make sure everyone understands the location of the utility and the plan before excavation continues.

IF SOMETHING DOESN'T MATCH — STOP

Stop digging if:

- The utility is not where the markings indicate
- You cannot locate a marked utility
- You uncover an unknown or unmarked utility

- The markings appear inaccurate
- An exposed utility cannot be positively identified
- Conditions change while excavating

DO NOT GUESS AND KEEP DIGGING.

Stop work, notify your foreman, and get the situation figured out before continuing.

REMEMBER

ALLOW 3 FEET ON EITHER SIDE OF THE UTILITY MARKING BEFORE MECHANICAL EXCAVATION.

MARKED DOES NOT MEAN EXPOSED.

PAINT AND FLAGS DO NOT GUARANTEE EXACT LOCATION OR DEPTH.

EXPOSE AND POSITIVELY IDENTIFY THE UTILITY.

HUDDLE WITH THE CREW BEFORE DIGGING AROUND IT.

WHEN IN DOUBT — STOP DIGGING.

Our goal is simple: **prevent utility strikes and make sure everyone goes home safe and uninjured at the end of the day.**

RIDGE ROCK LLC

CHARLA DE SEGURIDAD #016

SEGURIDAD CON SERVICIOS SUBTERRÁNEOS

LOCALICE. EXPONGA. IDENTIFIQUE.

NO ASUMA — EXPONGA EL SERVICIO

Nunca asuma que una marca muestra la ubicación o profundidad exacta de un servicio subterráneo.

Antes de continuar la excavación mecánica alrededor de un servicio conocido, debe localizarse, exponerse e identificarse correctamente.

Si no sabe exactamente dónde está el servicio — DEJE DE EXCAVAR.

MANTENGA 3 PIES DE DISTANCIA DE LA MARCA

Cuando trabaje alrededor de un servicio subterráneo marcado, deje **3 pies a cada lado de la marca** antes de utilizar excavación mecánica.

Dentro de esta área, use extremo cuidado y métodos seguros para localizar y exponer el servicio, como:

- Excavación manual
- Excavación por vacío
- Cuchillo de aire
- Otros métodos seguros aprobados

Localice y exponga el servicio antes de continuar la excavación mecánica alrededor de él.

IDENTIFIQUE CORRECTAMENTE EL SERVICIO

Encontrar una tubería, conducto o línea no significa que deba asumir a qué servicio pertenece.

Una vez expuesto, asegúrese de que la cuadrilla sepa:

- **Qué tipo de servicio es**
- **Dónde está realmente**
- **En qué dirección continúa**
- **Cómo trabajará la cuadrilla alrededor de él de manera segura**

Nunca asuma que un servicio expuesto es **eléctrico, gas, agua, riego, comunicación, abandonado u otro tipo de servicio** solamente por su apariencia.

Si el servicio no puede identificarse correctamente, DETENGA EL TRABAJO e informe a su capataz antes de continuar.

REÚNANSE ANTES DE EXCAVAR

Antes de continuar la excavación mecánica alrededor de un servicio expuesto, el capataz y la cuadrilla deben tener una breve reunión.

El operador y la cuadrilla deben saber:

¿DÓNDE ESTÁ EL SERVICIO?

¿QUÉ TIPO DE SERVICIO ES?

¿CÓMO VAMOS A TRABAJAR ALREDEDOR DE ÉL DE MANERA SEGURA?

Asegúrese de que todos entiendan la ubicación del servicio y el plan antes de continuar.

SI ALGO NO COINCIDE — DETÉNGASE

Deje de excavar si:

- El servicio no está donde indican las marcas
- No puede localizar un servicio marcado
- Encuentra un servicio desconocido o sin marcar
- Las marcas parecen incorrectas
- Un servicio expuesto no puede identificarse correctamente
- Las condiciones cambian durante la excavación

NO ADIVINE Y SIGA EXCAVANDO.

Detenga el trabajo, informe a su capataz y resuelva la situación antes de continuar.

RECUERDE

DEJE 3 PIES A CADA LADO DE LA MARCA ANTES DE UTILIZAR EXCAVACIÓN MECÁNICA.

MARCADO NO SIGNIFICA EXPUESTO.

LA PINTURA Y LAS BANDERAS NO GARANTIZAN LA UBICACIÓN O PROFUNDIDAD EXACTA.

EXPONGA E IDENTIFIQUE CORRECTAMENTE EL SERVICIO.

REÚNASE CON LA CUADRILLA ANTES DE EXCAVAR A SU ALREDEDOR.

SI TIENE DUDAS — DEJE DE EXCAVAR.

Nuestro objetivo es simple: **prevenir daños a servicios subterráneos y asegurar que todos regresen a casa seguros y sin lesiones al final del día.**