

1. Create a file called playlist.txt and write the names of your top 3 favorite songs from Spotify into it using write mode (w).

```
2. #include <stdio.h>
3.
4. int main() {
5.     FILE *fp;
6.
7.     // Open the file in write mode
8.     fp = fopen("playlist.txt", "w");
9.
10.    if (fp == NULL) {
11.        printf("Error opening file!\n");
12.        return 1;
13.    }
14.
15.    // Write the song names to the file
16.    fprintf(fp, "Perfect - Ed Sheeran\n");
17.    fprintf(fp, "Shape of You - Ed Sheeran\n");
18.    fprintf(fp, "Blinding Lights - The Weeknd\n");
19.
20.    // Close the file
21.    fclose(fp);
22.
23.    printf("Songs have been written to playlist.txt successfully.\n");
24.
25.    return 0;
26.}
```

2. Open playlist.txt in read mode (r) and display each song name on a separate line in the console.

```
    #include <stdio.h>

int main() {
    FILE *fp;
    char song[100];

    // Open the file in read mode
    fp = fopen("playlist.txt", "r");

    if (fp == NULL) {
        printf("Error: Could not open playlist.txt\n");
        return 1;
    }

    printf("Songs in Playlist:\n");

    // Read and display each line
    while (fgets(song, sizeof(song), fp) != NULL) {
```

```

        printf("%s", song);
    }

    // Close the file
    fclose(fp);

    return 0;
}

```

3. Add two more song names to playlist.txt without deleting the existing ones by opening the file in append mode (a).

```

#include <stdio.h>

int main() {
    FILE *fp;

    // Open the file in append mode
    fp = fopen("playlist.txt", "a");

    if (fp == NULL) {
        printf("Error opening file!\n");
        return 1;
    }

    // Append two new songs
    fprintf(fp, "Levitating - Dua Lipa\n");
    fprintf(fp, "Believer - Imagine Dragons\n");

    // Close the file
    fclose(fp);

    printf("Two songs have been added to playlist.txt successfully.\n");

    return 0;
}

```

4. Write a program that reads all song names from playlist.txt and prints only those that contain the word 'love' (case-insensitive).

Hint: Use the 'in' keyword or equivalent string method for filtering.

```

#include <stdio.h>
#include <string.h>
#include <ctype.h>

int main() {
    FILE *fp;
    char song[100];
    char temp[100];
}

```

```
// Open the file in read mode
fp = fopen("playlist.txt", "r");

if (fp == NULL) {
    printf("Error: Could not open playlist.txt\n");
    return 1;
}

printf("Songs containing 'love':\n");

while (fgets(song, sizeof(song), fp) != NULL) {
    strcpy(temp, song);

    // Convert to lowercase
    for (int i = 0; temp[i] != '\0'; i++) {
        temp[i] = tolower((unsigned char)temp[i]);
    }

    // Check if "love" exists
    if (strstr(temp, "love") != NULL) {
        printf("%s", song);
    }
}

fclose(fp);

return 0;
}
```