

1. Given the following buggy code meant to calculate the total price of a Zomato order, identify and fix the syntax and runtime errors:

let items = ["Burger", "Pizza", "Fries"];
let prices = [120, 250, 90];
let total = 0;
for (i = 0; i < items.length; i++) {
 total += prices[i]
}
console.log("Total price is: " + total);

Hint: Watch for assignment and loop variable issues.

```
2. #include <stdio.h>
3.
4. int main() {
5.     char *items[] = {"Burger", "Pizza", "Fries"};
6.     int prices[] = {120, 250, 90};
7.     int total = 0;
8.
9.     for (i = 0; i < 3; i++) {    // Error: i is not declared
10.         total += prices[i];    // Error: += instead of +=
11.     }
12.
13.     printf("Total price is: %d\n", total);
14.
15.     return 0;
16. }
```

2. Rewrite the following code to improve its indentation and add comments explaining each step, so that a beginner can understand what it does:

function isEven(num){if(num%2==0){return true;}else{return false;}}

```
#include <stdio.h>

// Function to check whether a number is even or odd
int isEven(int num)
{
    // Check if the number is divisible by 2
    if (num % 2 == 0)
    {
        // If the remainder is 0, the number is even
        return 1;    // True
    }
    else
    {
        // Otherwise, the number is odd
        return 0;    // False
    }
}

int main()
{
```

```

int number;

// Ask the user to enter a number
printf("Enter a number: ");
scanf("%d", &number);

// Call the function and display the result
if (isEven(number))
{
    printf("%d is an Even number.\n", number);
}
else
{
    printf("%d is an Odd number.\n", number);
}

return 0;
}

```

3. Write a function `formatFollowersCount(count)` that takes a number and returns a formatted string like Instagram: 1500 as '1.5K', 1200000 as '1.2M', and numbers below 1000 as-is. Add clear comments and use proper indentation.

```

#include <stdio.h>

// Function to format follower count
void formatFollowersCount(int count)
{
    // If followers are 1,000,000 or more
    if (count >= 1000000)
    {
        printf("%.1fM\n", count / 1000000.0);
    }
    // If followers are 1,000 or more
    else if (count >= 1000)
    {
        printf("%.1fK\n", count / 1000.0);
    }
    // If followers are less than 1,000
    else
    {
        printf("%d\n", count);
    }
}

int main()
{
    int followers;

```

```

// Ask the user to enter the follower count
printf("Enter Followers Count: ");
scanf("%d", &followers);

// Display the formatted follower count
printf("Formatted Followers Count: ");
formatFollowersCount(followers);

return 0;
}

```

4. You are given a piece of JavaScript code that should print all even numbers from 1 to 10, but it doesn't work as expected:
 for (let i = 1; i <= 10; i++) {
 if (i % 2 = 0) {
 console.log(i)
 }
}
 Find and fix the error, then rewrite the code with good indentation and at least one comment explaining the logic.

```

#include <stdio.h>

int main()
{
    int i;

    for(i = 1; i <= 10; i++)
    {
        if(i % 2 = 0)    // Error
        {
            printf("%d\n", i);
        }
    }

    return 0;
}

```