

1. Declare a 1D array called `dailySteps` with 7 elements to store your step count for each day of the week, assign sample values, and print each value using a loop.

```
2. #include <stdio.h>
3.
4. int main() {
5.     // Declare and initialize the array
6.     int dailySteps[7] = {5000, 6500, 7200, 8000, 9000, 10000, 7500};
7.
8.     // Print the array elements using a loop
9.     printf("Daily Step Count:\n");
10.
11.    for (int i = 0; i < 7; i++) {
12.        printf("Day %d: %d steps\n", i + 1, dailySteps[i]);
13.    }
14.
15.    return 0;
16.}
```

2. Create a 2D array called `playlistRatings` to store ratings for 3 Spotify playlists over 5 days (rows = playlists, columns = days). Fill it with sample numbers and print the ratings for the second playlist.

```
    #include <stdio.h>

int main() {
    // 3 Playlists x 5 Days
    int playlistRatings[3][5] = {
        {5, 4, 5, 3, 4}, // Playlist 1
        {4, 5, 5, 4, 5}, // Playlist 2
        {3, 4, 4, 5, 4}  // Playlist 3
    };

    printf("Ratings for the Second Playlist:\n");

    for (int i = 0; i < 5; i++) {
        printf("Day %d: %d\n", i + 1, playlistRatings[1][i]);
    }

    return 0;
}
```

3. Build a function that takes a 1D array of 7 integers representing your daily Zomato order amounts and calculates the average spend for the week.
Hint: Use a loop to sum the values, then divide by the array length.

```

#include <stdio.h>

// Function to calculate average spend
float calculateAverage(int orders[], int size)
{
    int sum = 0;

    for (int i = 0; i < size; i++)
    {
        sum += orders[i];
    }

    return (float)sum / size;
}

int main()
{
    // Daily Zomato order amounts for 7 days
    int dailyOrders[7] = {250, 320, 180, 400, 275, 350, 225};

    float average = calculateAverage(dailyOrders, 7);

    printf("Average Zomato Spend for the Week: Rs. %.2f\n", average);

    return 0;
}

```

4. Given a 2D array called `cricketScores` where each row represents an IPL match and columns represent runs scored by each team, write code to print the highest score from each match.

```

#include <stdio.h>

int main() {
    // Rows = Matches, Columns = Team Scores
    int cricketScores[3][2] = {
        {185, 178}, // Match 1
        {210, 198}, // Match 2
        {165, 172}  // Match 3
    };

    int highest;

    printf("Highest Score from Each Match:\n");

    for (int i = 0; i < 3; i++) {
        highest = cricketScores[i][0];

        for (int j = 1; j < 2; j++) {

```

```
        if (cricketScores[i][j] > highest) {  
            highest = cricketScores[i][j];  
        }  
    }  
  
    printf("Match %d: %d runs\n", i + 1, highest);  
}  
  
return 0;  
}
```