

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

[*www.MyPlacementPrep.com*](http://www.MyPlacementPrep.com)

Pro Material Series

Join Telegram Channel for more updates:

<https://t.me/MyPlacementprepApp>

Visit www.MyPlacementPrep.com .

India's No1 website for Placement Materials and Free mock test Series

Free Placement Learning path now available with free video course.

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

1. printcharecterpattern

Input:

5

Expected output: a

ab

abc

abcd

abcde

testcase 2: input:

1

Output:

A

Given Code:

```
#include<stdio.h>
void printcharecterpattern( int num) {

int i,j,value=1;
char ch = 'a';
char print = ch;
for(int i=1;i<=num;i++,printf("\n")) {

ch=print; for(j=1;j<=i;j++)

printf("%c",ch++); }

}
```

```
int main() {

int num; scanf("%d",&num); printcharecterpattern(num);

}
```

Corrected Code:

```
#include<stdio.h>
void printcharecterpattern( int num) {

int i,j,value=1;
char ch = 'a';
char print = ch; for(i=1;i<=num;i++,printf("\n")) {
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
ch=print; for(j=1;j<=i;j++)  
  
printf("%c",ch++); }  
  
}
```

2. You are required to fix all logical errors in the given code. You can click on Compile , Run anytime to check the compilation/execution status of the program. You can use System.out.println to debug your code. The submitted code should be logically/syntactically correct and pass all testcases. Do not write the main() function as it is not required. Code Approach: For this question, you will need to correct the given implementation. We do not expect you to modify the approach or incorporate any additional library methods. The method printColor(intnum) of the class Color is supposed to print names of color according to given input numbers num When the values of num equal 1,2,3,4 the function prints “Red”,”Black”,”White”,”Green” respectively for any other values of num it should print “No color”. The method complies fine but fails to return the desired results for some cases. Your task is to fix code so that it passes all the testcases

Given Code:

```
int printcolor(int num) {  
  
switch (num) {  
  
} }
```

Corrected Code:

```
int printcolor(int num) {  
  
case 1:  
printf("red");  
  
case 2:  
printf("black");  
  
case 3:  
printf("white");  
  
case 4:  
printf("green");  
  
default:  
printf("no color");  
  
break;
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
case 1:
printf("red");

break; case 2:

printf("black");

break; case 3:

printf("white");

break; case 4:

printf("green");

break; default:

printf("no color"); break;

} }
```

```
switch (num) {
```

3.

The method printpattern(int) of class drawpattern is expected to print the first n (n > 0)

Lines of the pattern

TESTCASES

TestCase 1

Input:

4

Expected Return value:

11

1111

111111

11111111

TestCase 2:

Input:

1

Expected Return Value:

11

Given Code:

```
int printpattern(int n)
```

```
{
```

```
int i,j,print =1; for(i=1;i<=n;i++) for(j=1;j<=2 * i;j++) {
```

```
printf("%d",print ); }
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
printf("\n"); }
```

Corrected Code:

```
int printpattern(int n) {  
    int i,j,print =1; for(i=1;i<=n;i++) {  
        for(j=1;j<=2 * i;j++) {  
            printf("%d",print ); }  
        printf("\n"); }  
    }
```

4. Multiply the middle number with maximum of three numbers TESTCASE 1

Input

5,7,4

Expected return value: 35

TESTCASE 2

Input

11,12,13

Expected return value:

156

Given Code:

```
#include<stdio.h>
```

```
int multiplynumber(int a,int b,int c)
```

```
{  
    int result,min,max,mid;
```

```
    max=(a>b)?((a>c)?a:c)((b>c)?b:c); min=(a<b)?((a<c)?a:c)((b<c)?b:c); mid=(a+b+c)-(min+max);  
    result=(max*mid);
```

```
    return result; }
```

Corrected Code:

```
#include<stdio.h>
```

```
int multiplynumber(int a,int b,int c) {
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
int result,min,max,mid;
max= (a>b)?((a>c)?a:c):((b>c)?b:c); min=(a<b)?((a<c)?a:c):((b<c)?b:c);
//max= (a>b) ? ((a>c)?a:c) : ((b>c)?b:c); //min= (a<b) ? ((a<c)?a:c) : ((b<c)?b:c);

mid=(a+b+c)-(min+max); result=(max* mid); return result;

}
```

Question :5

You are required to fix all logical errors in the given code. You can click on Compile & Run anytime to check the compilation/execution status of the program. You can use System.out.println to debug your code. The submitted code should be logically/syntactically correct and pass all test cases. Do not write the main() function as it is not required. Code Approach: For this question, you will need to correct the given implementation We do not expect you to modify the approach or incorporate any additional library methods. The function sortArray(int * arr,intlen) accepts an integer array arr of length (len>0) as an input and perform an in place sort operation on it. The function is expected to return the input array sorted in descending order The function compiles successfully but fails to return the desired results due to logical errors Your task is to debug the program to pass all the test cases

TESTCASE 1:

Input:

[23, 12, 14, 24, 21], 5

Expected Return Value:

[24, 23, 21, 14, 12]

TESTCASE 2:

Input:

[1, 1, 1, 1, 1], 5 **Expected Return Value:** [1, 1, 1, 1, 1]

Given Code:

```
int *sortArray(int *arr,int *len) {

int i=0,j=0,temp=0,index=0; for(i=0;i<len;i++)
{

for(j=i+1;j<len;j++) {

if(arr[i]>arr[j]) {

temp=arr[i];

arr[i]=arr[j];

arr[j]=temp; }

return arr;
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
} }
```

```
}
```

Corrected Code:

```
int *sortArray(int *arr, int len) {  
  
    int i=0,j=0,temp=0,index=0; for(i=0;i<len;i++)  
    {  
  
        for(j=i+1;j<len;j++) {  
  
            if(arr[i]<arr[j]) {  
  
                } }  
  
        }  
        return arr;  
  
    }  
  
    temp=arr[i]; arr[i]=arr[j]; arr[j]=temp;
```

Question:6

You are required to complete the given code by reusing existing functions. click on the helper code tab to find out the details of functions/classes provided for reuse you can click on compile & run anytime to check the compilation /execution status of the program you can use system.out.println to debug your code The submitted code should be logically/syntactically correct and pass all testcase . . Do not write the main() function as it is not required.

Code Approach: For this question, you will need to correct the given implementation. We do not expect you to modify the approach or incorporate any additional library methods. The function countElement(int *arr, int len, int n) is supposed to return the numbers of elements in the inputs array arr of length len, which are greater than twice of the input number n The function looks fine but given a compilation error Your task is to fix the program so that it passes all the testcases

TESTCASE 1:

Input:

[-2, -4, -3, -5, -6, -7, -8], 7, 3

Expected Return Value:

0

TESTCASE 2:

Input:

[22, 55, 66, 33, 44, 77], 6,13

Expected Return Value:

5

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

PROGRAM:

Given Code:

```
int countElement(int arr, int len, int n) {
```

```
    inti,count=0;
```

```
    for(int i=0;i<len;i++) {
```

```
        if(arr[i]>2n) {
```

```
            count=-1;
```

```
int countElement(int arr, int len, int n) {
```

```
int i,count=0; for(i=0;i<len;i++) {
```

```
    if(arr[i]>2*n) {
```

```
        } }
```

```
return count; }
```

Corrected Code:

```
//count=-1;
```

```
count+=1;
```

```
    } }
```

```
return count; }
```

Question:7

The method countdigit(int sum) of class digits is supposed to return the value remainder when the input arguments num(num>0) is divided by the number of digits in num.

Given Code:

```
countdigit(int sum)
```

```
{
```

```
    int count=0;
```

```
    while(num) {
```

```
        num=num/10;
```

```
        count++; }
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
return (num%count); }
```

Corrected Code:

```
countdigit(int sum) {
```

```
int count=0,safe;
```

```
safe=num;
```

```
while(num) {
```

```
num=num/10;
```

```
count++; }
```

```
num=safe;
```

```
return (num%count); }
```

Question:8

The Function reverseArray(intarr[]) of class sort Array arr of an arguments For example, if the input array arr is {20,30,10,40,50} the function is expected to return {50,40,10,30,20}

The function compiles successfully but fails to return the desired result due to logical errors Given Code:

```
int arrayReverse(int *arr,int len)
{
```

```
int i,temp,originallen=len; for(i=0;i<=originallen/2;i++) {
```

```
temp=arr[len-1]; arr[len-1]=arr[i]; arr[i]=temp; len+=1;
```

```
}
```

```
return arr; }
```

Corrected Code:

```
int arrayReverse(int *arr,int len) {
```

```
int i,temp,originallen=len; for(i=0;i<=originallen/2;i++) {
```

```
temp=arr[len-1]; arr[len-1]=arr[i]; arr[i]=temp; len+=1;
```

```
len-=1;
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
}

return arr; }

Question:9
Given Code:
char checkGrade(int score) {

if(score<=60) return „D“;

else if((61<=score)&&(score<=75)) return „C“;

else if((76<=score)&&(score<=90)) return „B“;

else
return „A“;

}
int main() {

int score;
scanf(“%d”,&score); printf(“%c”, checkGrade(score)); return 0;

}
```

Corrected Code:

```
char checkGrade(int score) {

if(score<=60)

return „D“;
else if((61>=score)&&(score<=75))

return „C“;
else if((76>=score)&&(score<=90))

return „B“; else

return „A“;

}
int main() {

int score;
scanf(“%d”,&score); printf(“%c”, checkGrade(score)); return 0;
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
}
```

Question:10

The function findMaxElement(int *arr1,int len1,int *arr2,int len2) accepts two integer arrays arr1,arr2 of length len1,len2 respectively. It is supposed to return the largest element in both the input arrays. Another function sortArray(int *arr,intlen) sorts the input array arr of length len in ascending order and returns the sorted array.

Your task is to use sortArray(int *arr,intlen) function and complete the code in findMaxElement(int *arr1,int len1,int *arr2,int len2) so that it passes all test cases.

TESTCASE 1:

Input:

[2, 5, 1, 3, 9, 8, 4, 6, 5, 2, 3, 11], 12,
[11, 13, 2, 4, 15, 17, 67, 44, 2, 100, 0, 23]11

Expected Return Value:

100

TESTCASE 2:

Input:

[100, 22, 43, 912, 56, 89, 85], 7, [234, 123, 456, 234, 890, 101], 6 Expected Return Value:
912

Given Code:

```
int *sortArray(int *arr,int *len)
{
```

```
int i=0,j=0,temp=0,index=0; for(i=0;i<len;i++)
{
```

```
for(j=i+1;j<len;j++) {
```

```
if(arr[i]>arr[j]) {
```

```
temp=arr[i]; arr[i]=arr[j]; arr[j]=temp;
```

```
}} 
```

```
 }
```

```
return arr; }
```

```
findMaxElement(int *arr1,int len1,int *arr2,int len2) {
```

```
//WRITE DOWN CODE HERE
```

```
else
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
}
```

```
arr1= sortArray(arr1,len1); arr2= sortArray(arr2,len2);
```

```
if(arr1[len1-1]>arr2[len2-1])
```

```
return arr1[len1-1];
```

```
return arr2[len2-1];
```

Question 11:

The function getarraysum(int * arr, int len) is supported to calculate and return the sum

of elements of the input array arr of length len (len > 0). The function compiles successfully but fails to return the desired result due to logical errors.

Given Code:

```
int getarraysum(int *arr, int len)
```

```
{  
int sum = 0;
```

```
for(i=0;i<len;i-i-1) {
```

```
sum = arr[i];
```

```
}
```

```
return sum; }
```

Corrected Code:

```
int getarraysum(int *arr, int len) {
```

```
int sum = 0; for(i=0;i<len;i++) {
```

```
sum+ = arr[i];
```

```
}
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
return sum; }
```

Question:12

The methods GetDigitSum(intarr[]) of class DigitSum accepts an integers array arr it is supposed to calculate the sum of digits of the even of the smallest elements in the input array it returns 1 if the calculated sum is even and returns 0 otherwise However there is a compliation error in the code your task is to fix it so that the program works for all the input values Note The methods getdigitSum uses another method getSum(int sum) which returns the sum of the digits of the input number num

Given Code:

```
int getDigitSum(int arr[i])
{

int result,len=arr.length;
for(int i=0;min=arr[0];i<len;i++) {

if(arr[i]<min)

min=arr[i]; }

results=getSum(min)

if(results%2==0) return 1;

else

}
int getSum(int num) {

//WRITE YOUR CODE HERE }
```

Corrected Code:

```
int getDigitSum(int arr[i]) {

int result,len=arr.length;

int min;

for(int i=0;min=arr[0];i<len;i++) {

if(arr[i]<min)

min=arr[i]; }

results=getSum(min) if(results%2==0) return 1;
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

else

}

int getSum(int num) {

//WRITE YOUR CODE HERE

}

Question:13

Code Approach: For this question, you will need to correct the given implementation. We do not expect you to modify the approach or incorporate any additional library methods.

Lisa always forgets her birthday which is on 5th july

In order to help her we have function CheckBirthDay(char *month,int day) which takes day and month as inputs and returns 1 if its her birthday and returns a 0 otherwise The function compiles fine but to return desired results for some cases Your task to fix the code so but that it passes at test cases 15(1)

TestCase 1;

Input

July 13

Expected Return Value: 0

TestCase 2: Input

min==arr[j]:

return 0;

int rem,sum=0;

while(num)

{

rem=num%10;

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
sum+=rem;
```

```
    }
```

```
}
```

```
num/=10;
```

```
    }
```

```
return sum;
```

April 3

Expected Return Value:

0

Given Code:

```
int checkBirthday(char* month,int day) {
```

```
if(strcmp(month,"july") || (day ==5)) return 1;
```

```
else
```

```
return 0;
```

```
}
```

```
int main() {
```

```
char inp[]="july";
```

```
int day=5; if(checkBirthday(inp,day)==1)
```

```
printf("Yes"); else
```

```
printf("No"); return 0 ;
```

```
}
```

Corrected Code:

```
int checkBirthday(char* month,int day) {
```

```
if(strcmp(month,"july")==0 && return 1;
```

```
else
```

```
return 0;
```

```
}
```

```
int main() {
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
char inp[]="july";
int day=5; if(checkBirthDay(inp,day)==1)

printf("Yes"); else

printf("No"); return 0 ;

}
```

(day ==5))

Question:14

Matrix Adding odd diagonal elements

```
int calculateMatrixSum(int m, int n, int mat[m][n]) {
```

```
//WRITE YOUR CODE HERE
```

```
int i,j,sum=0,row=m,col=n;
```

```
if(row>0 && col>0)
```

```
{
```

```
for(i=0;i<row;i++)
```

```
{
```

```
for(j=0;j<col;j++)
```

```
{
```

```
if(i==j)
```

```
{
```

```
if(mat[i][j]%2==0)
```

```
sum+=mat[i][j];
```

```
}
```

```
}
```

```
return sum;
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
}
```

Question:15

Manchester Encoding

```
int Manchester(int *arr, int len) {
```

```
//WRITE YOUR CODE HERE
```

```
int i;
```

```
}
```

Question:16

Matrix Sum

Given Code:

```
int MatrixSum(int m, int n, int mat[m][n]) {
```

```
int i,j,sum=0; for(i=0;i<m;i++) {
```

```
for(j=0;j<n;j++) {
```

```
int *res=(int *)malloc(sizeof(int)*len);
```

```
res[0]=arr[0]; //res[0]=(arr[0]!=0);
```

```
for(i=1;i<len;i++)
```

```
res[i]=arr[i]^arr[i-1];
```

```
return res;
```

```
} }
```

```
return sum; }
```

```
}
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
sum+=mat[i][j];
```

```
}
```

```
sum+=mat[i][j];
```

Corrected Code:

```
int MatrixSum(int m, int n, int mat[m][n]) {
```

```
int i,j,sum=0; for(i=0;i<m;i++) {
```

```
for(j=0;j<n;j++) {
```

```
    }
```

```
return sum; }
```

```
sum+=mat[i][j];
```

Question 17:

Replace all the elements of the array with the maximum element of array. **//WRITE DOWN YOUR CODE HERE**

```
#include<stdio.h>
```

```
int * maxReplace(int *arr, int len)
```

```
{
```

```
int i if(len>0) {
```

```
int max=arr[0]; for(i=1;i<len;i++) {
```

```
if(max<arr[i]) max=arr[i];
```

```
for(i=0;i<len;i++)
```

```
}
```

```
return arr; }
```

```
arr[i]=max;
```

Question 18:

Find the number of occurrences of a given value in the array. Given Code:

```
#include<stdio.h>
```

```
int occurrence(int *arr, int len,int value)
```

```
{
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
int i=0,count=0; while(i<len)
{

if(arr[i]==value) count++;

}

return count; }
```

Corrected Code:

```
#include<stdio.h>
int occurrence(int *arr, int len,int value) {

int i=0,count=0; while(i<len)
{

if(arr[i]==value) count++;

i++; }

return count; }
```

Question 19:

The function patternPrint(int n) supposed to print n number of lines in the following pattern For n=4 the pattern should be:

```
1
11
11 1
111 1
```

The function complies successfully but fails to return the desired results due to logical errors Your task is to debug the program to pass all the test cases

Given Code:

```
void patternPrint(int n)
{

int print=1,i,j; for(int i=0;i<n;i++) {

for(j=0;j<=i;j++) {

printf("%d",print); }

}
print("\n");

} }
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

Corrected Code:

```
void patternPrint(int n) {  
  
int print=1,i,j; for(i=0;i<n;i++) {  
  
for(j=0;j<=i;j++) {  
  
printf("%d",print); }  
  
print("\n"); }  
  
}
```

Question:20 The function removeElement(int *arr,intlen,int index)takes an array arr of length len as an input. It is supposed to return an array len-1 after removing the integer at the given index in the input arrayarr. If the given index is out of bounds, then this function should return the input array arr. The function compiles successfully but fails to return the desired result due to logical errors */

WRITE YOUR CODE

```
int* removeelement( int *arr, int len, int index) {  
  
int i,j; if(index<len) {  
  
for(i=index;i<len-1;i++) {  
  
arr[i]=arr[i+1];  
  
}  
int *rarr =(int*)malloc(sizeof(int)*(len-1)); for(i=0;i<len-1;i++)  
  
rarr[i]=arr[i]; return rarr;  
  
}  
else  
  
}  
  
return arr;
```

Question:21 Replace a given array with zeros and ones depending on the even or odd criteria of the array length. **WRITE DOWN YOUR CODE HERE**

```
int *replaceValues(int *arr, int len)  
{
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
int i; for(i=0;i<len;i++)  
  
arr[i]=len%2; return arr;  
  
}
```

Question: 22 Selection Sort Given Code:

```
int * sortArray(int *arr, int len) {  
  
int x=0,y=0,n=len;  
int index_of_min, temp; for(x=0;x<n;x++)  
{  
  
index_of_min=x; for(y=x;y<n;y++) {  
  
if(arr[index_of_min]>arr[y]) {  
  
index_of_min=y; }  
  
}  
temp = arr[x];  
arr[x] = arr[index_of_min]; arr[index_of_min] = temp;  
  
}  
  
return arr; }
```

Corrected Code:

```
int * sortArray(int *arr, int len) {  
  
int x=0,y=0,n=len;  
int index_of_min, temp; for(x=0;x<n;x++)  
{  
  
index_of_min=x; for(y=x;y<n;y++) {  
  
if(arr[index_of_min]>arr[y]) {  
  
index_of_min=y; }  
  
}  
temp = arr[x];  
arr[x] = arr[index_of_min]; arr[index_of_min] = temp;  
  
}  
  
}
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
return arr; }
```

QUESTION:23

Return the difference between two given times in seconds TESTCASE

TestCase1:

Input:

Time:1:58:42, Time:2:1:45

Expected Return values:

183

Testcase 2

Input:

Time:3:49:57, Time:2:45:57

Expected Return Values

3600

```
#include<stdio.h> struct Time
```

```
{
```

```
int h; int m; int s;
```

```
};
```

```
typedef struct Time TIME; toSeconds(TIME * gt)
```

```
{
```

```
int in_seconds;
```

```
in_seconds = gt->h * 3600 + gt->m * 60 + gt->s; return in_seconds;
```

```
}
```

```
int abs(int val) {
```

```
if (val< 0)
```

```
return -val;
```

```
else
```

```
return val;
```

```
}
```

```
diff_in_times(TIME *t1, TIME *t2) {
```

```
}
```

```
int main() {
```

```
TIME t1 = {1,58,42}, t2 = {2,59,45}; printf("%d", diff_in_times(&t1, &t2)); return 0;
```

```
}
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

Question:24

Print the following Pattern

1
12 1
1232 1
1 2 3 4 3 2 1

//WRITE DOWN YOUR CODE HERE void printPattern(int n)
{

int i,j; for(i=1;i<=n;i++,printf("\n")) {

int t5,t6,res,result;

t5= toSeconds(t1); t6= toSeconds(t2);

res= t5-t6;

result=abs(res);

return result;

} }

Or

//WRITE DOWN YOUR CODE HERE

for(j=1;j<=i;j++) {

printf("%d",j); }

for(j--;j>=1;j--) {

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
printf("%d",j); }

void printPattern(int n) {

int i,j,num=1; for(i=1;i<=n;i++) {

num=num*10+1;

printf("%d\n", num*num); }

}
```

Question:25

You are required to fix all logical errors in the given code. You can click on Compile & Run anytime to check the compilation/execution status of the program. You can use System.out.println to debug your code. The submitted code should be logically/syntactically correct and pass all testcases. Do not write the main() function as it is not required. Code Approach: For this question, you will need to correct the given implementation. We do not expect you to modify the approach or incorporate any additional library methods.

The method deleteDuplicate(intarr[]) of classDistinctArray takes an array as an input it is supposed to remove duplicates integers from the input array arr such that for each distinct integer the first occurrence is retained and all the duplicates elements following it are removed for Example given input array

(2,3,2,2,5,6,6,7)

the expected output is (2,3,5,6,7)

The function complies successfully but fails to return the desired results due to logical errors Your task is debug the program to pass all the test cases

Given Code:

```
int* deleteDuplicate (int *arr, int len)
{

int count=0,p,i,j,k=0,originalLength=len; for(i=0;i<len;i++)
{

for(j=i+1;j<len;j++) {

} }

return arr; }
```

Corrected Code:

```
if(arr[j]==arr[i]) {

arr[k]=arr[k+1]; }

len=len-1; count=count+1; j=i;
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
int* deleteDuplicate (int *arr, int len) {  
  
    int count=0,p,i,j,k=0,originalLength=len; for(i=0;i<len;i++)  
    {  
  
        for(j=i+1;j<len;j++) {  
  
            if(arr[j]==arr[i]) {  
  
                for(k=j;k<len-1;k++)  
  
                    arr[k]=arr[k+1]; }  
  
            len=len-1; count=count+1; j=i;  
  
        } }  
  
    return arr; }
```

QUESTION:26

The function sameelementcount(int *arr,intlen) accepts an integer array arr of length len as a input and returns the number of elements in an arr which are even numbers and equal to the element to its right

//WRITE DOWN YOUR CODE HERE

```
int sameelementcount(int *arr, int len)  
{  
  
    int i,count=0; for(i=0;i<len-1;i++) {  
  
        if((arr[i]%2==0)&&(arr[i]==arr[i+1])) count++;  
  
    }  
  
    return count; }
```

QUESTION:27

Given a string str, write a program to eliminate all the vowels from the given string. The list of vowels in the English alphabet is : {a,e,i,o,u,A,E,l,0,U}. The Input to the function eliminateVowelString shall consist of a string str (containing only English letters) and returns a pointer to a string which does not contain vowels.

EXAMPLE:

Input ="abcdefghijklmnopqrstuvwxy"

Output="bcdfghjklmnpqrstvwxyz"

USEFUL COMMANDS:

strlen() is used to calculate the length of the string. The statement -

int len = strlen(str); Returns the length of the string str

TESTCASE 1:

Input: "abcdefghijklmnopgrstu"

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

Expected Return Value: "bcd fghjklmnpqrst"

TESTCASE 2:

Input: "bacdcfgh"

Expected Return Value: "bcdlgh"

char * removeVowel(char *str)

{

int trav,,hold=0; for(trav=0;str[trav]!='\0';trav++) {

if(str[trav]=='a' || str[trav]=='e' || str[trav]=='i' || str[trav]=='o' || str[trav]=='u' || str[trav]=='A' || str[trav]=='E' || str[trav]=='I' || str[trav]=='O' || str[trav]=='U')

{

} else {

str[hold]=str[trav];

hold++; }

}

str[hold]='\0'; printf("%s",str); return 0;

}

QUESTION:28 Half sort Array: #include<stdio.h> #include<limits.h> int main()

{

int arr[]={ 10,12,25,6,13,8,19};

int index,size,max,maxpos,min,minpos,temp,score; size=sizeof(arr)/sizeof(arr[0]);
for(index= 0 ; index < size; printf("%2d ",arr[index++]));

if(index%2==0) {

min = INT_MAX;

for(index =1; index<size; index++) {

if(arr[index] < min) {

min = arr[index];

minpos=index; }

}

temp = arr[index]; arr[index] = arr[minpos]; arr[minpos]=temp;

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

```
} else {  
  
max = INT_MIN;  
for(index = 0 ; index<size; index++) {  
  
if(arr[index] > max) {  
  
max = arr[index];  
  
maxpos=index; }  
  
}  
temp = arr[index]; arr[index] = arr[maxpos]; arr[maxpos]=temp;  
  
}  
for(printf("\n"),index= 0 ; index < size;printf("%2d ",arr[index++])); return 0;  
  
}
```

Question : 30 **WRITE YOUR CODE** Pyramid of alphabets

a bcd efghi

jklmnop

```
#include<stdio.h> void printPattern(int n) {  
  
int i,j;  
char ch='a';  
  
for(i=1;i<=n;i++) {  
  
for(j=1;j<=n-i;j++) printf(" ");  
  
for(j=1;j<=2*i-1;j++) printf("%c",ch++);  
  
printf("\n"); }  
  
}
```

QUESTION:31

You have to encrypt a non-empty string phrase. The encryption adds a 'cyclic shift' to each letter where the value of this 'cyclic shift' is decided by the position of the letter from the end of its word. The shift value for each letter of a word is its index value (starting from 0) from the right-most character of the word.

EXAMPLE:

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

The shift values in 'yum feed' will be

yum: m->0, u->1, y->2

feed: d->0, e->1, e->2, f->3

which gives the encryption avmigfd

Here, adding the shift with value 0 to letter 'm' gives 'm' + 0 = m;

values 1 to 'u' gives 'u' + 1 = v and values 2 to 'y' gives 'y' + 2 = a and so on

Note that the shift wraps around on reaching the end of the alphabets, i.e., the shift values for 'y' as shown above is 'a'.

INPUT:

The input to the function/method consists of a string.

OUTPUT:

Return the encrypted string

NOTE:

Assume that the input string contains single space separating set of words

```
#include<stdio.h>
```

```
char* encryption(char* str); int main()
```

```
{
```

```
char str[]="zebra tiger"; printf("%s",encryption(str)); return 0;
```

```
}
```

```
char* encryption(char* str) {
```

```
//your CODE
```

```
int len,index,value; for(len=0;str[len]!='\0';len++) {
```

```
if(str[index]!='\0') {
```

```
value=0;
```

```
continue; }
```

```
if(str[index]+value<=122) str[index]=str[index]+value++;
```

```
else
```

```
str[index]=str[index]+value++ -26;
```

```
}
```

```
return str; }
```

QUESTION:32

The LeastRecentlyUsed(LRU) cache algorithm exists the element from the cache(when it's full) that was leastrecentlyused. After an element is requested from the cache, it should be added to the cache(if not already there) and considered the most recently used element in the cache. Initially, the cache is

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

empty. The input to the function LruCountMiss shall consist of an integer max_cache_size, an array pages and its length len. The function should return an integer for the number of cache misses using the LRU cache algorithm. Assume that the array pages always has pages numbered from 1 to 50.

TEST CASE1:

Input: 3 16 7 0 1 2 0 3 0 4 2 3 0 3 2 1 2 0

Expected Return Value: 11

TESTCASE 2:

Input: 2 9 2 3 1 3 2 1 4 3 2

Expected Return Value: 8

```
#include <stdio.h> int main()
{
int max_cache_size,pages_len,i,j,cache[100],pages[100],k,pageincache=0,misscount=0;

scanf("%d %d",&max_cache_size,&pages_len); for(i=0;i< max_cache_size;i++)

cache[i]=-1;

for(i=0;i<pages_len;i++) {

pageincache=0; scanf("%d",&pages[i]);

for(j=0;j<max_cache_size;j++) {

if(pages[i]==cache[j]) {

pageincache=1; for(k=j;k<max_cache_size;k++)
{ cache[k]=cache[k+1];

}

cache[max_cache_size-1]=pages[i]; }

} if(pageincache==0) {

misscount++; for(k=0;k<max_cache_size;k++) {

cache[k]=cache[k+1]; }

cache[max_cache_size-1]=pages[i]; }

}

printf("%d",misscount); }
```

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>

Free Placement Video Tutorial with Mock Test visit:

www.MyPlacementPrep.com

www.MyPlacementPrep.com

*Free Mock Test and Video
Tutorial*

Visit www.MyPlacementPrep.com .

India's No1 website Placement and Mock Test series
Free Placement Learning Path with Free Video Course.

Join Telegram Channel: <https://t.me/MyPlacementprepApp>

Join Telegram Group: <https://t.me/myPlacementPrep>