FIRE SAFETY INSPECTION CHECKLIST

BASED ON REPUBLIC ACT 9514 (FIRE CODE OF THE PHILIPPINES)

1.	GENERAL INFORMATION	
	Name of Building	CVSU MARAG HS BLOG
	Address	*
	Business Name	
	Nature of Business	
	Name of owner/Representa	· Rudy St Endonila Hipa
	Contact No.	09252909463
П.	CONSTRUCTION TYPE	
	[] Type I : Concrete & Stee	el (Fire Resistive)
	[] Type II : Concrete & Exp	posed Steel (Noncombustible)
	[] Type III : Concrete & Wo	ood (Ordinary)
	[] Type IV : Heavy Timber	(Large mass wood)
	[] Type V : Wood frame (Li	ightweight wood)
III.	SECTIONAL OCCUPANCY (II THE BUILDING) Basement :	NDICATE SPECIFIC USAGE OF EACH FLOOR, PART OR PORTION OF
		READING ROOM, CLINIC, COMLAB, ADMIN, FACULTY, STOCK
	Second floor : CLASSROOM	, , , , , , , , , , , , , , , , , , , ,
	Third floor :	
	Use separate sheet if necessary	
IV.	GENERAL OCCUPANCY CLAS	SSIFICATION
		onal /[] Day Care / [] Health Care
		onal / [] Residential / [] Residential Board and Care
	[] wercarrule / [] busines	ss / [] Industrial / [] Storage / [] Special Structure.
V.	OTHER INFORMATION	
	Maximum Occupant Load:	P/Floor Number of Stories: Storey
		m Highrise: [] Yes / [] No
		J 1 1 1 1 W

VI. MEANS OF EGRESS

• EXIT ACCESS

[] Doors / [] Corridors / [] Hallways / [] Passageways / [] Anterooms / [] Ramps

	Passed	Failed
Doors that open directly one exit access corridors shall be self-closing and self- latching	[/	[]
There shall no openings in the corridor partitions other than door openings	[X	[]
Free from any obstruction	[1]	[]
No flammable material stored	[]	[]

• EX	ITS	
	[/ Normal Stairs /	[] Curved Stairs / [] Spiral Stairs / [] Winding Stairs
	[] Horizontal Exits /	[] Outside Stairs / Exit Passageways / Fire Escape Stairs
	[] Fire Escape Ladde	er (for 1 & 2 family dwelling only)
	[] Slide Escape (for In	ndustrial Occupancy Only)

	Passed	Failed
Exits doors open and close properly		[]
Doors swing in direction of egress.	[X	[]
Exit Doors provided with panic hardware, vision panel, and self-closing mechanism.	[1]	[]
There shall be no enclosed usable space under the stairs in an exit enclosure nor shall the open space under such stairs be used for any purpose.	- [1]	[]
Interior finish: Class B	[]	[]
Exterior grounds are kept clear of objects that might impede evacuation or firefighting equipment	[1]	[]
Terminate directly at a public way or at an exterior exit discharge	[/	[]

VII. SIGNS, LIGHTING, AND EXITS SIGNAGE

• MARKING OF MEANS OF EGRESS (EXIT)

	Actual Dim.	Passed	Failed
Minimum letter height, 150 mm	0.45	[]	[]
EXIT signs are posted along Exit access, Exits and Exit dischar	ge	1	[]
EXIT signs are properly illuminated		W	[]

MARKING OF MEANS OF EGRESS (EMERGENCY EVACUATION PLAN)

E .		Passed	Failed
Posted on strategic and conspicuous location inside the building		M	[]
Drawn with a photo-luminescent background to be readable in case of power	er failure.	[1]	[]
Containing the following basic information below 1. "You Are Here/ room number/ building" Marking 2. Fire Exits 3. Primary Route to Exit (Nearest to the viewer) 4. Secondary Route to Exit (Second nearest to the viewer) 5. Fire alarm pull stations and annunciators 6. Fire extinguishers/ hose cabinets 7. Emergency Light 8. First Aid Kits locations (if applicable) 9. Emergency Call stations (if applicable 10. Areas of safe refuge (for high-rise building) 11. Assembly areas instructions 12. "In Case of Emergency" instructions			
	Actual Dim.	Passed	Failed
Emergency Evacuation Plan:			
 Size 330.2 mm wide * 215.9 mm height (Floor area < 50 m²) Room or spaces 	*	[]	[]
 Size 609.6 mm wide * 457.2 mm height (Floor area = 50 - 150 m²) Room or spaces Building lobbies upon entry. Elevator lobbies at every floor. Hallways and corridors. On every bend/corner Or every 15m interval in the case of long hallway. 		[]	[]
 [] Size 609.6 mm height * 914.4 mm wide (Floor area ≥ 151m²) Room or spaces Upon entry of the building Area of assembly or every 25m interval in the case auditorium & gymnasium. 		[]	[]
Symbols/icons/logos to be used for the marking shall be in accordance with NFPA 170, Standard for Signs and Symbols.			

VIII. HAZARD

OTHER FLAMMABLE LIQUIDS (I.E. ALCOHOL, ETHER, ETC...)

		Failed
Stored in sealed metal containers	H	[]
Properly dispensed as per SOP	M	[]
Provided with "NO SMOKING" sign. SIGN	[was	

MISCELLANEOUS HAZARDS (MECHANICAL EQUIPMENT ROOM, STORAGE, SUPPLY ROOM)

ř.		Passed	Failed
All no smoking areas has adequate signs.	M SIGN	-	[]
Gasoline/ Diesel is stored in the proper place and i	n a metal safety can.	W	[]

HOUSEKEEPING, MAINTENANCE, STORAGE & WASTE DISPOSAL

	Passed	Failed
Brooms, mops, rags and other cleaning supplies stored in metal cabinets or approved cans	[1]	[]
Paints, solvents and other flammables stored in metal cabinet: oily rags in metal containers	[]	[]
Dry leaves, shrubbery trimmings and other combustibles kept away from buildings		[]

IX. FIRE PROTECTION

\sim			
Item to Inspect	Procedure How to Inspect	Passed	Failed
Sprinkler Pumps	Check automatic start and pressure.	\[]	[]
Sprinkler Valves	Valves are locked in the open position, no leaks, corrosion, or other defects noted.	[1]	[]
Sprinkler water flow alarm	Open test valve and ensure manual alarm bell functions and sprinkler pumps start.	[]	[1
Wet Standpipe/Fire Hose	Cabinet NO FAKE		
Cabinet Door Operative	Check that door is unobstructed and opens properly.	[1]	[]
Hose Condition	Check that hose is not rotted, wet, moldy, etc.	[]	[]
Nozzle	Check that nozzle is in place and operates correctly.	[]	[]
Hose hung properly	Check that hose is hung properly so that it can easily be un-rolled if needed.	[]	[]
Valves and valve handles	Check that valve handles are in place and that valves operate properly and are in the open position.	[]	1/1
Fire Pump	20		
Pump System	Inspect accuracy of pressure gauges and sensors	11	[]
Pipings	Check pipings if there is leak	11	[]

Motor	Check unusual noise or vibrations	Y 1/			
Electrical System		M	[]		
	Check if there is corrosion in PCBs, cracked cable/wire insulation, leak in plumbing parts, sign of water in electrical part		41		
Fire Detection System					
Fire Detection System	Random Test of call points and smoke detectors.	[]	[-]		
Fire Alarm Facilities	*		1		
Location Signs	Check all signs are in place and legible.	[1]	[]		
Alarm Panels	Check that all alarm panels are functioning correctly and are unobstructed.	[]	[]		
Lifts (Elevator)	NO LIFT				
Lifts	All lifts "home" to ground floor during fire test, doors open and lift stops.	ŢĪ.	[]		
Fans	All lift fans operate correctly.	[]	[]		
Fireman's lift	Fireman's lift can be keyed to operate during fire alarm test.	[]	[]		
First Aid Fire Protection (Fire Extinguishers)					
Fire Extinguisher Size	Minimal sizes of fire extinguishers for the listed grades of hazards shall be provided on the basis of table 7 & 8 of RIRR of RA 9514.	r'i	[]		
Minimum number of Extinguisher.	The minimum number of extinguishers shall be sufficient to meet the requirements of table 7 & 8 of RIRR of RA 9514.	14	[]		
Location	All extinguishers are in their proper location.		[]		
Seals & Tags	Extinguisher seals and tags are intact and extinguisher was serviced in the last 12 months.		[]		
Markings	Proper marking on extinguisher to indicate the type of fire the extinguisher can be used on.	[]	[]		
Condition	No leaks, corrosion or other defects noticed.		[]		
Pressure	Pressure gauge reads in the "green" area.		[]		
Emergency Lighting Sy	vstems		•		
Battery Lights	All battery powered emergency lighting turns on when mains power is removed	[1]	[]		
Kitchen					
Hoods & Vents	Hoods, vents, fans and ducts in good condition and free from grease	11	[]		
Hood Filters	Date of Last Cleaning	[]	[]		

ŧ.	Passed	Fai
Utilities:		
Cooking equipment protected by AKHFSS (Restaurant and similar establishment with Occupant Load > 50p)	[]] [
Heating, Ventilating and Air-conditioning: Design & Installation in accordance with PMEC	V]
Smoke Control Systems/Smoke Management shall be provided in the following:		
 [] All high-rise buildings (stairwells, at least 1 elevator shaft, zoned smoke control, and vestibule). [] Pressurization of smoke refuge area. 	[]	1
[] Every Atrium of covered mall of over 2- levels / Other type of Occupancy over 3 – levels.		
[] Underground structure and windowless facilities. [] All movie houses.		
All other buildings or structures with at least 1,115m² single floor area.		
Rubbish Chutes, Laundry Chutes, and Flue-Fed Incinerators: (not apply to detached single- or two-family dwelling)	**	
[] Chutes & Incinerators shall be enclosed.	[]	r
Design and Maintained in accordance with the latest edition of PMEC.	1 1	F

Devided William St. Market	
Provided with Fire Wall (minimum 2 hours fire resistance)	[]Yes/[]No
FW extension above the roof surface shall not be less than 760mm (See MC No. 2021-064 dated 28 June 2021 for Alternative)	[]Yes/[]No
Wall type: [] 125mm Solid Concrete / [] 150mm Solid Masonry / [] 200m	nm Hallow I Init Masonny