



Clustering

Part II




Restriction of Cluster Shapes




Clusters are Voronoi-diagrams of centers

Limitations of K-Means: Part I




Cluster boundaries equidistant to centers

Limitations of K-Means: Part II



Can't model covariances well



Limitations of K-Means: Part III





Only simple cluster shapes





Local Optima: Part I



Local Optima: Part II



Local Optima: Part III



K-Means Optimization Objective

$c^{(i)}$ = index of cluster $(1, 2, \dots, K)$ to which example $x^{(i)}$ is currently assigned

μ_k = cluster centroid k ($\mu_k \in \mathbb{R}^n$)

$\mu_{c^{(i)}}$ = cluster centroid of cluster to which example $x^{(i)}$ has been assigned

Optimization objective:

$$J(c^{(1)}, \dots, c^{(m)}, \mu_1, \dots, \mu_K) = \frac{1}{m} \sum_{i=1}^m \|x^{(i)} - \mu_{c^{(i)}}\|^2$$

$$\min_{\substack{c^{(1)}, \dots, c^{(m)}, \\ \mu_1, \dots, \mu_K}} J(c^{(1)}, \dots, c^{(m)}, \mu_1, \dots, \mu_K)$$



Random Initialization: Part II

For $i = 1$ to 100 {

Randomly initialize K-means.

Run K-means. Get $c^{(1)}, \dots, c^{(m)}, \mu_1, \dots, \mu_K$.

Compute cost function (distortion)


$$J(c^{(1)}, \dots, c^{(m)}, \mu_1, \dots, \mu_K)$$

}

Pick clustering that gave lowest cost $J(c^{(1)}, \dots, c^{(m)}, \mu_1, \dots, \mu_K)$





Choosing the Value of K: Part I



Choosing the Value of K: Part II

Elbow method:



Choosing the Value of K: Part III

Sometimes, you're running K-means to get clusters to use for some later/downstream purpose. Evaluate K-means based on a metric for how well it performs for that later purpose.

