

COMP519 Web Programming

Lecture 25: PHP (Part 7)

Handouts

Ullrich Hustadt

Department of Computer Science
School of Electrical Engineering, Electronics, and Computer Science
University of Liverpool

Contents

- ① Classes
 - Defining and Instantiating a Class
 - Visibility
 - Class Constants
 - Static Properties and Methods
 - Destructors
 - Inheritance
 - Interfaces
 - Introspection Functions
- ② The PDO Class
 - Introduction
 - Connections
 - Queries and Processing of Results
 - Prepared Statements
 - Transactions
- ③ Revision and Further Reading

Defining and Instantiating a Class

- PHP is an object-oriented language with **classes**
- A **class** can be defined as follows:

```
class identifier {  
    property_definitions  
    function_definitions  
}
```

- The **class name** *identifier* is **case-sensitive**
- The body of a class consists of **property definitions** and **function definitions**
- The function definitions may include the definition of a **constructor**
- An **object** of a class is created using

```
new identifier(arg1, arg2, ...)
```

where $\text{arg1}, \text{arg2}, \dots$ is a possibly empty list of arguments passed to the constructor of the class *identifier*

A Closer Look at Class Definitions

In more detail, the definition of a `class` typically looks as follows

```
class identifier {  
  # Properties  
  vis $attrib1  
  ...  
  vis $attribN = value  
  
  # Constructor  
  function __construct(p1, ...) {  
    statements  
  }  
  # Methods  
  vis function method1(p1, ...) {  
    statements  
  }  
  vis function methodN(p1, ...) {  
    statements  
  }  
}
```

- Every instance obj of this class will have `attributes` *attrib1*, ... and `methods` *method1*(), ... accessible as `obj->attrib1` and `obj->method1(a1...)`
- `__construct` is the `constructor` of the class and will be called whenever `new identifier(a1, ...)` is executed
- `vis` is a declaration of the `visibility` of each attribute and method

A Closer Look at Class Definitions

- The pseudo-variable `$this` is available when a method is called from within an object context and is a reference to the calling object
- Inside method definitions, `$this` can be used to refer to the properties and methods of the calling object
- The **object operator** `->` is used to access methods and properties of the calling object

```
class Rectangle {  
    protected $height;  
    protected $width;  
  
    function __construct($height,$width) {  
        $this->width  = $width;  
        $this->height = $height;  
    }  
}
```

Visibility

- Properties and methods can be declared as
 - `public` accessible everywhere
 - `private` accessible only within the same class
 - `protected` accessible only within the class itself and by inheriting and parent classes
- For `properties`, a `visibility` declaration is required
- For `methods`, a `visibility` declaration is optional
 - ↪ by default, `methods` are `public`
- Accessing a `private` or `protected` property / method outside its visibility is a **fatal error**

```
class Vis {  
    public      $public      = 1;  
    private    $private      = 2;  
    protected  $protected    = 3;  
    protected  function proFc() {}  
    private    function priFc() {}  
}  
$v = new Vis();  
echo $v->public;      # prints 1  
echo $v->private;     # Fatal Error  
echo $v->protected;   # Fatal Error  
echo $v->priFc();      # Fatal Error  
echo $v->proFc();     # Fatal Error
```

Constants

- Classes can have their own **constants** and **constants** can be declared to be **public**, **private** or **protected**
~> by default, **class constants** are public

```
vis const identifier = value;
```

- Accessing a private or protected constant outside its visibility is a **fatal error** ~> execution of the script stops
- Class constants are allocated once per class, and not for each class instance
- Class constants are accessed using the **scope resolution operator** `::`

```
class MyClass {  
    const SIZE = 10;  
}  
  
echo MyClass::SIZE;    # prints 10  
$o = new MyClass();  
echo $o::SIZE;         # prints 10
```

Static Properties and Methods

- Class **properties** or **methods** can be declared **static**
- Static class properties and methods are accessed (via the class) using the **scope resolution operator** `::`
- **Static class properties** cannot be accessed via an instantiated class object, but **static class methods** can
- **Static class method** have no access to `$this`

```
class Employee {  
    static $totalNumber = 0;  
    public $name;  
  
    function __construct($name) {  
        $this->name = $name;  
        Employee::$totalNumber++;  
    }  
}  
  
$e1 = new Employee("Ada");  
$e2 = new Employee("Ben");  
echo Employee::$totalNumber    # prints 2
```


Destructors

- A class can have a **destructor method** `__destruct` that will be called as soon as there are no references to a particular object

```
class Employee {
    static $totalNumber = 0;
    public $name;

    function __construct($name) {
        $this->name = $name;
        Employee::$totalNumber++;
    }
    function __destruct() {
        Employee::$totalNumber--;
    }
}

$e1 = new Employee("Ada");
$e2 = new Employee("Ben");
echo Employee::$totalNumber    # prints 2
$e1 = null;
echo Employee::$totalNumber    # prints 1
```

Inheritance

- In a class definition it is possible to specify one **parent class** from which a class inherits constants, properties and methods:

```
class identifier1 extends identifier2 { ... }
```

- The constructor of the parent class is **not** automatically called it must be called explicitly from the child class
- Inherited constants, properties and methods can be **overridden** by redeclaring them with the same name defined in the parent class
- The declaration **final** can be used to prevent a method from being overridden
- Using **parent::** it is possible to access overridden methods or static properties of the parent class
- Using **self::** it is possible to access static properties and methods of the current class

Inheritance

```
class Rectangle {  
    protected $height;  
    protected $width;  
  
    function __construct($height,$width) {  
        $this->height = $height;  
        $this->width  = $width;  
    }  
    function area() {  
        return $this->width * $this->height;  
    }  
}
```

```
class Square extends Rectangle {  
    function __construct($size) {  
        parent::__construct($size,$size);  
    }  
}
```

```
$rt1 = new Rectangle(3,4);  
echo "\$rt1 area = ",$rt1->area(),"\n";  
$sq1 = new Square(5);  
echo "\$sq1 area = ",$sq1->area(),"\n";
```

```
$rt1 area = 12
```

```
$sq1 area = 25
```

Interfaces

- **Interfaces** specify which methods a class must implement without providing an implementation
- **Interfaces** are defined in the same way as a class with the keyword **class** replaced by **interface**
- All methods in an interface must be declared **public**
- A class can declare that it implements one or more interfaces using the **implements** keyword

```
interface Shape {  
    public function area();  
}  
  
class Rectangle implements Shape {  
    ...  
}
```

Introspection Functions

There are functions for inspecting objects and classes:

```
bool class_exists(string class)
```

returns **TRUE** iff a class *class* exists

```
class_exists('Rectangle')           # returns TRUE
```

```
string get_class(object obj)
```

returns the name of the class to which an object belongs

```
get_class($sql)                     # returns 'Square'
```

```
bool is_a(object obj, string class)
```

returns **TRUE** iff *obj* is an instance of class named *class*

```
is_a($sql, 'Rectangle')            # returns TRUE
```

```
bool method_exists(object obj, string method)
```

returns **TRUE** iff *obj* has a method named *method*

```
method_exists($sql, 'area')        # returns TRUE
```

Introspection Functions

There are functions for inspecting objects and classes:

```
bool property_exists(object obj, string property)
```

returns **TRUE** iff object has a property named *property*

```
property_exists($sq1, 'size')  # returns FALSE
```

```
get_object_vars(object)
```

returns an array with the accessible non-static properties of object mapped to their values

```
get_object_vars($e2)  
# returns ["name" => "Ben"]
```

```
get_class_methods(class)
```

returns an array of method names defined for *class*

```
get_class_methods('Square')  
# returns ["__construct", "area"]
```

The PDO Class

- The **PHP Data Objects** (PDO) extension defines an **interface** for accessing databases in PHP
- Various **PDO drivers** implement that interface for specific database management systems
 - **PDO_MYSQL** implements the PDO interface for MySQL 3.x to 5.x
 - **PDO_SQLSRV** implements the PDO interface for MS SQL Server and SQL Azure

Connections

- Before we can interact with a DBMS we need to establish a **connection** to it
- A connection is established by **creating an instance** of the **PDO class**
- The **constructor** for the **PDO class** accepts arguments that specify the database source (DSN), username, password and additional options

```
$pdo = new PDO(dsn, username, password, options);
```

- Upon successful connection to the database, the constructor returns an instance of the PDO class
- The connection remains **active** for the lifetime of that PDO object
- Assigning **NULL** to the variable storing the PDO object destroys it and **closes the connection**

```
$pdo = NULL
```


Connections: Example

```
# Connection information for the Departmental MySQL Server
$host      = "studdb.csc.liv.ac.uk";
$user      = "sgfsurn";  # your University username
$passwd    = "-----";  # your MySQL server account password
$db        = "sgfsurn";  # your University username
$charset   = "utf8mb4";
$dsn       = "mysql:host=$host;dbname=$db;charset=$charset";

# Useful options
$opt = array(
    PDO::ATTR_ERRMODE            => PDO::ERRMODE_EXCEPTION ,
    PDO::ATTR_DEFAULT_FETCH_MODE => PDO::FETCH_ASSOC ,
    PDO::ATTR_EMULATE_PREPARES  => false
);

try {
    $pdo = new PDO($dsn,$user,$passwd,$opt);
} catch (PDOException $e) {
    echo 'Connection failed: ', $e->getMessage();
}
```

Queries

- The `query()` method of PDO objects can be used to execute an SQL query

```
$result = $pdo->query(statement)
```

```
$result = $pdo->query("SELECT_*_FROM_meetings")
```

- `query()` returns the result set (if any) of the SQL query as a PDOStatement object
- The `exec()` method of PDO objects executes an SQL statement, returning the number of rows affected by the statement

```
$rowNum = $pdo->exec(statement)
```

```
$rowNum = $pdo->exec("DELETE_*_FROM_meetings")
```

Processing Result Sets

- To get a single row as an array from a result set stored in a PDOStatement object, we can use the `fetch()` method
- By default, PDO returns each row as an `array` indexed by the `column name` and 0-indexed `column position` in the row

```
$row = $result->fetch()  
array('slot' => 1,  
      'name' => 'Michael_North',  
      'email' => 'M.North@student.liverpool.ac.uk',  
      0 => 1,  
      1 => 'Michael_North',  
      2 => 'M.North@student.liverpool.ac.uk')
```

- After the last call of `fetch()` the result set should be released using

```
$rows = $result->closeCursor()
```

- To get all rows as an array of arrays from a result set stored in a PDOStatement object, we can use the `fetchAll()` method

```
$rows = $result->fetchAll()
```

Processing Result Sets

- We can use a while-loop together with the `fetch()` method to iterate over all rows in a result set

```
while ($row = $result->fetch()) {  
    echo "Slot:␣␣", $row["slot"], "<br>\n";  
    echo "Name:␣␣", $row["name"], "<br>\n";  
    echo "Email:␣", $row["email"], "<br><br>\n";  
}
```

- Alternatively, we can use a `foreach-loop`

```
foreach($result as $row) {  
    echo "Slot:␣␣", $row["slot"], "<br>\n";  
    echo "Name:␣␣", $row["name"], "<br>\n";  
    echo "Email:␣", $row["email"], "<br><br>\n";  
}
```

- `fetch()` uses a cursor that moves through the rows in a result set and does **not** reset at the end
 ↪ store the result set in an array first (e.g., using `fetchAll()`),
 then iterate over the array as often as you want

Processing Result Sets

- Using `bindColumn()` we can bind a variable a particular column in the result set from a query
 - columns can be specified by `number` (starting with 1!)
 - columns can be specified by `name` (matching case)
- Each call to `fetch()` and `fetchAll()` will then update all the variables that are bound to columns
- The binding needs to be renewed after each query execution

```
$result->bindColumn(1, $slot);           # bind by column no
$result->bindColumn(2, $name);
$result->bindColumn('email', $email);    # bind by column name
while ($row = $result->fetch(PDO::FETCH_BOUND)) {
    echo "Slot:  ", $slot, "<br>\n";
    echo "Name:  ", $name, "<br>\n";
    echo "Email: ", $email, "<br><br>\n";
}
```

Prepared Statements

- The use of parameterised **prepared statements** is preferable over queries
- **Prepared statements** are are parsed, analysed, compiled and optimised only once
- **Prepared statements** can be executed repeatedly with different arguments
- **Arguments** to prepared statements do not need to be quoted and **binding** of parameters to arguments will automatically prevent SQL injection
- PDO can **emulate prepared statements** for a DBMS that does not support them
- MySQL supports prepared statements natively, so PDO emulation should be turned off

```
$pdo->setAttribute(PDO::ATTR_EMULATE_PREPARES , FALSE );
```

Prepared Statements: SQL Templates

- Using a prepared statement requires three steps
 - ① Preparing a statement using a SQL template containing parameters
 - ② Binding the parameters to values
 - ③ Executing the prepared statements

Prepared Statements: SQL Templates

- An **SQL template** is an SQL query (as a string) possibly containing either
 - named parameters of the form `:name`, where *name* is a PHP identifier, or
 - question marks ?

for which values will be substituted when the query is executed

```
$tpl1 = "select slot from meetings where  
        name=:name and email=:email";  
$tpl2 = "select slot from meetings where name=?";
```

- The PDO method `prepare()` turns an **SQL template** into a **prepared statement** (by asking the DBMS to do so)
 - on success, a PDOStatement object is returned
 - on failure, **FALSE** or an error will be returned

```
$stmt1 = $pdo->prepare($tpl1);  
$stmt2 = $pdo->prepare("select * from fruit where col=?");
```


Prepared Statements: Binding

- We can **bind** the **parameters** of a PDOStatement object **to a value** using the **bindValue()** method
 - **Named parameters** are bound by **name**
 - **Question mark parameters** are bound by **position** (starting from 1!)
 - the datatype of the value can optionally be declared (to match that of the corresponding database field)
 - the value is bound to the parameter at the time **bindValue()** is executed

```
$stmt1->bindValue(':name','Ben',PDO::PARAM_STR);  
$email = 'bj1@liv.ac.uk';  
$stmt1->bindValue(':email',$email);  
$stmt2->bindValue(1,20,PDO::PARAM_INT);
```

Prepared Statements: Binding

- We can **bind** the **parameters** of a PDOStatement object **to a variable** using the **bindParam()** method
 - **Named parameters** are bound by **name**
 - **Question mark parameters** are bound by **position** (starting from 1!)
 - the datatype of the value can optionally be declared (to match that of the corresponding database field)
 - the **variable** is bound to the parameter as a **reference**
 - a **value** is only substituted when the statement is executed

```
$name = 'Ben';  
$stmt1->bindParam(':name', $name, PDO::PARAM_STR);  
$stmt1->bindParam(':email', $email);  
$email = 'bj1@liv.ac.uk';  
$slot = 20;  
$stmt2->bindParam(1, $slot, PDO::PARAM_INT);
```

- It is possible to mix **bindParam()** and **bindValue()**

Prepared Statements: Execution

- Prepared statements are executed using `execute()` method
- Parameters must
 - previously have been bound using `bindValue()` or `bindParam()`, or
 - be given as an array of values to `execute`
 - ↪ take precedence over previous bindings
 - ↪ are bound using `bindValue()`
- `execute()` returns `TRUE` on success or `FALSE` on failure
- On success, the `PDOStatement` object stores a result set (if appropriate)

```
$stmt1->execute();  
$stmt1->execute(array(':name' => 'Eve', ':email' => $email));  
$stmt2->execute(array(10));
```

Transactions

- There are often situations where a single 'unit of work' requires a sequence of database operations
 ~> e.g., bookings, transfers
- By default, PDO runs in "auto-commit" mode
 ~> successfully executed SQL statements cannot be 'undone'
- To execute a **sequence of SQL statements** whose changes are
 - only committed at the end once all have been successful or
 - rolled back otherwise,PDO provides the methods
 - `beginTransaction()`
 - `commit()`
 - `rollBack()`

Transactions

To support transactions, PDO provides the methods

`beginTransaction()`

- turns off auto-commit mode; **changes** to the database are **not committed** until `commit()` is called
- returns **TRUE** on **success** or **FALSE** on **failure**
- throws an **exception** if another transaction is already active

`commit()`

- **changes** to the database are **made permanent**; auto-commit mode is turned on
- returns **TRUE** on **success** or **FALSE** on **failure**
- throws an **exception** if no transaction is active

`rollback()`

- **discard changes** to the database; auto-commit mode is restored
- returns **TRUE** on **success** or **FALSE** on **failure**
- throws an **exception** if no transaction is active

Transactions: Example (Part 1)

- We want to transfer £10.50 from one account at a bank to another, but only if the payer has enough money
- Either both subtracting the money from one account and adding it to another should be successful or neither

```
$balance = array();

// storeBalance($id,$b)
// $id: account id
// $b : balance for the account with id $id
// maps $id to $b in the array $balance
function storeBalance($id,$b) {
    global $balance;
    $balance[$id] = $b;
}

$pdo = new PDO('mysql:host=...;dbname=...','...','...',
    array(PDO::ATTR_ERRMODE => PDO::ERRMODE_EXCEPTION,
        PDO::ATTR_EMULATE_PREPARES => false));

try {
    // Details of the transaction: payer, payee, amount
    $payerId = 1;  $payeeId = 2;  $paymentAmount = 10.50;
```

Transactions: Example (Part 2)

```
$pdo->beginTransaction();  
// Obtain payee's and payer's account balances  
// and lock access to both records  
$sql1 = "select id,balance from accounts where id=? or id=? for update";  
$stmt = $pdo->prepare($sql1);  
$stmt->execute(array($payerId,$payeeId));  
  
// Store the data retrieved from the database in $balance array  
$stmt->fetchAll(PDO::FETCH_FUNC,'storeBalance');  
  
// Check whether there is enough money in the payer's account  
if ($balance[$payerId] < $paymentAmount) {  
    echo "Insufficient funds in payer's account";  
} else {  
    $sql = "UPDATE accounts SET balance = balance + ? WHERE id = ?";  
    $stmt = $pdo->prepare($sql);  
  
    // Increase balance of payee's account by payment amount  
    $stmt->execute(array($paymentAmount,$payeeId));  
  
    // Decrease balance of payer's account by payment amount  
    $stmt->execute(array(-$paymentAmount,$payerId));  
}
```

Transactions: Example (Part 3)

```
// Commit the transaction (whether money was transferred or not)
$pdo->commit();

} catch (PDOException $e) {
    // Something went wrong at some point
    echo "Error: ", $e->getMessage(), "<br>\n";

    // Roll back the transaction
    $pdo->rollBack();
}
```


Revision and Further Reading

Read

- Language Reference: Classes and Objects
<http://php.net/manual/en/language.oop5.php>
- The PDO Class
<http://php.net/manual/en/class.pdo.php>

of P. Cowburn (ed.): PHP Manual. The PHP Group, 25 Oct 2019.
<http://uk.php.net/manual/en> [accessed 26 Oct 2019]