

Colour Usage

The primary colour palette has been designed to use colour to make Test and Tag Supplies stand out. Red should be used as the primary colour wherever possible. The Seafoam is used as an accent, and cooling accompaniment to the Red. Charcoal offers a substitute for black, with TTS White used as an alternative to pure white. Beige provides a richer white alternative, that is tonally interesting when paired with the rest of the palette. This ties the entire colour palette together, while offering a good amount of contrast and visual interest.

*NB there is some discrepancy between screen and print. It's advised to consult your printer to confirm the PMS colours prior to printing.

TTS Vibrant Red HEX #CC0000 RGB 204, 0, 0 CMYK 13, 100, 100, 4 PMS 485 C	80%	60%	40%	20%
TTS Seafoam HEX #99CCCC RGB 135, 204, 204 CMYK 40, 5, 20, 0 PMS 7478 U	80%	60%	40%	20%
TTS Charcoal HEX #312F2F RGB 49, 47, 47 CMYK 69, 64, 63, 62 PMS Hexachrome Black C	80%	60%	40%	20%
TTS Beige HEX #E5E8DC RGB 229, 230, 220 CMYK 9, 6, 12, 0 PMS P 162-1 C	80%	60%	40%	20%

TTS White HEX #F7F7F7 RGB 247, 247, 247 CMYK 2, 1, 1, 0 PMS P 179-1 C	80%	60%	40%	20%