

TTS REPORTS

V1.0 Stable Build

Report Accuracy Testing Checklist

A structured QA checklist to protect against clean-looking but incorrect compliance-style reports.

Purpose

This checklist proves that imported data, on-screen asset review, PDF preview, and downloaded PDF output remain accurate against the source file before TTS Reports is released to pilot customers or a wider customer group.

Document Item	Detail
Product	TTS Reports
Build baseline	TTS_REPORTS_v1_0_STABLE_BUILD_VERSION_LABEL
Document type	Internal QA / release-readiness checklist
Primary risk controlled	A report that looks professional but contains incorrect, missing, or misleading test data
Recommended owner	Product owner or technical maintainer
Use before	Pilot release, customer release, and every build update that changes import or report output

Core QA principle: the generated report must never be trusted because it looks clean. It must be checked against the source data.

1. Testing scope

This checklist applies to TTS Reports V1.0 Stable and any V1.0.x maintenance build that changes importing, parsing, dashboard display, report generation, PDF preview, or PDF download behaviour.

Area	Must be tested
Import and parsing	Supported files must import and produce the expected asset/test data.
Asset Register dashboard	The on-screen asset data must match the source file before report generation.
Basic Report	The simpler PDF output must contain correct summary and result data.
Pro Report	The detailed/branded PDF output must contain correct asset, customer, and result data.
Upcoming Retest Report	Due/overdue items and date windows must calculate correctly.
PDF preview/download	The previewed report and downloaded PDF must match.

Scope control note

This checklist is not a request to add features. It exists to confirm that the existing V1.0 Stable build is safe enough to pilot. Any feature gaps discovered during testing should go into the Feature Request Register, not directly into the current build.

2. Required test file set

Testing should use a controlled file pack that represents the real export formats customers are expected to use. Where possible, each file should contain the same underlying project data so output consistency can be compared across file types.

File type	Source workflow	Minimum test requirement	Status
.padfx	aPAT project export	Import, asset count, pass/fail count, failed items, retest dates, Basic/Pro reports	Required
.apx	ES Manager / aPAT compatible export	Import, data mapping, status counts, report output consistency	Required
.xlsx	ES Manager spreadsheet export	Import, column mapping, dates, asset count, reports	Required if supported in deployed build
.pdf	aPAT PDF export	PDF text extraction, imported asset/result data, missing-field handling	Required if supported in deployed build
Known-bad/unsupported file	Wrong file, corrupt file, empty file, unsupported export	Error message must be clear and safe; no false report generation	Required

3. Pre-test setup checklist

- ☐ Confirm the build under test is labelled TTS Reports V1.0 Stable or a named V1.0.x maintenance build.
- ☐ Record the exact build/version number in the test record.
- ☐ Use a fresh browser session or clear localStorage where settings may affect report output.
- ☐ Load known sample files with expected source counts already recorded.

- [] Prepare a source-truth worksheet for each test file: total assets, pass count, fail count, retest dates, customer/site details, and known failed items.
- [] Confirm the tester is using the intended browser: Chrome, Edge, Firefox, or Safari latest version.
- [] Confirm downloaded PDFs can be opened locally and compared against preview output.

4. Master accuracy test matrix

Test area	Primary question	Pass condition	Evidence required
Imported asset count	Does the app import the same number of assets as the source file?	Asset total matches source-truth record.	Screenshot of dashboard count and source count.
Pass/fail count	Do result totals match source data?	Pass, fail, and other status counts match expected values.	Dashboard/report screenshots and source values.
Failed item visibility	Are all failed items visible and correctly labelled?	Every known failed item appears with correct status and details.	Failed item list comparison.
Retest dates	Are due dates and overdue status correct?	Retest dates and due windows match source/calculation rules.	Retest report and source date evidence.
Customer/site details	Are business, customer, site, and report details correct?	Details match imported data and/or settings.	PDF title/header screenshots.
Duplicate/latest tests	Does latest-test handling avoid old or duplicate results?	Latest result shown where expected; duplicates handled consistently.	Asset history comparison.
Basic Report	Is the Basic PDF correct?	Summary and rows match source-truth values.	Preview and PDF copy.
Pro Report	Is the Pro PDF correct?	Detailed output matches source-truth values and expected layout.	Preview and PDF copy.
Upcoming Retest Report	Are due/overdue assets correctly included/excluded?	Items match date-window rules.	Retest report comparison.
Preview vs download	Does downloaded PDF match preview?	No data/layout differences between preview and downloaded file.	Side-by-side comparison.

5. Imported asset count checklist

- ☐ Open the source file and confirm the expected total number of assets/items.
- ☐ Import the file into TTS Reports.
- ☐ Confirm the Asset Register dashboard displays the same total number of imported assets.
- ☐ Expand grouped/location views and confirm no assets are hidden or dropped.
- ☐ Check that blank rows, headers, or duplicated metadata have not been counted as assets.
- ☐ Generate Basic and Pro reports and confirm the report asset count matches the dashboard.
- ☐ Record pass/fail result and attach evidence.

Release risk

Stop wider release if the app drops assets, invents extra assets, or produces different asset totals between dashboard and PDF output.

6. Pass/fail count checklist

- ☐ Record expected pass, fail, and other result counts from the source file.
- ☐ Import the file and review dashboard totals, rows, or result indicators.
- ☐ Confirm every failed item is counted as failed and not incorrectly shown as passed.
- ☐ Confirm pass totals do not include failed, skipped, incomplete, or missing-result assets.
- ☐ Generate Basic Report and compare pass/fail counts.
- ☐ Generate Pro Report and compare pass/fail counts.
- ☐ Record any mismatch as Critical unless clearly caused by unsupported/incomplete source data.

Release risk

Any pass/fail mismatch is a Critical defect because it can create misleading compliance-style output.

7. Failed items checklist

- ☐ Prepare a list of all known failed items from the source file.
- ☐ Confirm each failed item appears in the Asset Register.
- ☐ Confirm failed items retain correct asset ID, description, location, test date, result, and comments where available.
- ☐ Confirm failed items appear in any report summary/failed-items section where expected.
- ☐ Confirm failed items are not hidden by latest-test filtering or grouping logic unless this is correct and documented.
- ☐ Confirm failed items are clearly distinguishable in Basic and Pro reports.
- ☐ Check for any failed item accidentally labelled as passed.

Release risk

Stop wider release if any failed item is missing, mislabelled, or made difficult to identify in the generated report.

8. Retest date checklist

- ☐ Record expected retest dates from the source data.
- ☐ Confirm imported retest dates display correctly in the dashboard.
- ☐ Check date format consistency and avoid month/day confusion.
- ☐ Confirm overdue items are identified correctly.

- ☐ Confirm 30/60/90-day due windows include and exclude the correct assets.
- ☐ Generate Upcoming Retest Report and compare against expected due/overdue list.
- ☐ Confirm assets without retest dates are handled safely and not silently misclassified.

Release risk

Retest-date errors should be High or Critical depending on whether they cause customers to miss overdue/failing assets.

9. Customer and site details checklist

- ☐ Record expected business, customer, site, phone/email, licence, and report settings values.
- ☐ Confirm imported customer/site details display correctly where the app supports them.
- ☐ Confirm user-entered settings appear correctly on report outputs.
- ☐ Confirm no details from a previous file/session appear in a new report.
- ☐ Confirm report title page, header, footer, and summary sections use the correct customer/site details.
- ☐ Confirm missing source details are handled as blank or clearly labelled, not replaced with wrong data.
- ☐ Confirm Basic, Pro, and Upcoming Retest reports are consistent.

Release risk

Wrong customer or site details should block release if they could cause a report to be issued to the wrong client or property.

10. Duplicate and latest-test handling checklist

- ☐ Identify assets in the source file that have multiple historical tests.
- ☐ Confirm the app uses the latest test where latest-test behaviour is expected.
- ☐ Confirm older results are not incorrectly shown as current results.
- ☐ Confirm duplicate asset IDs do not merge incorrectly when they represent distinct records.
- ☐ Confirm duplicate/history handling is consistent across dashboard, Basic Report, Pro Report, and Retest Report.
- ☐ Record any edge cases where historical data appears in one report but not another.
- ☐ Confirm the behaviour is documented in the Known Limitations or User Guide.

Release risk

Incorrect duplicate/latest-test handling can make old passed results hide newer failed results. Treat this as Critical where status is affected.

11. Basic Report output checklist

- ☐ Generate Basic Report from a known-good imported file.
- ☐ Confirm report title, business/customer details, and source summary are correct.
- ☐ Confirm asset rows match the dashboard and source file.
- ☐ Confirm pass/fail counts match expected values.
- ☐ Confirm failed items are shown correctly.
- ☐ Confirm retest dates are correct where shown.
- ☐ Confirm PDF formatting does not hide, truncate, or overlap important data.
- ☐ Download the Basic Report PDF and compare to preview.

Release risk

The Basic Report should be simple, but still must be data-accurate. Cosmetic issues are lower priority than data mismatches.

12. Pro Report output checklist

- ☐ Generate Pro Report from a known-good imported file.
- ☐ Confirm title page and branding are correct.
- ☐ Confirm business profile and customer/site details are correct.
- ☐ Confirm detailed asset rows match dashboard/source values.
- ☐ Confirm pass/fail status, test dates, retest dates, asset IDs, descriptions, and locations are correct.
- ☐ Confirm summary sections match source totals.
- ☐ Confirm long tables paginate correctly and no rows disappear at page breaks.
- ☐ Download the Pro Report PDF and compare to preview.

Release risk

The Pro Report is likely to be customer-facing. Any missing rows, incorrect statuses, or broken pagination should block wider release.

13. Upcoming Retest Report output checklist

- ☐ Prepare expected 30/60/90-day and overdue lists from source data.
- ☐ Generate Upcoming Retest Report.

- ☐ Confirm overdue items are included.
- ☐ Confirm due-soon items fall into the correct date window.
- ☐ Confirm items outside the selected/reporting window are excluded.
- ☐ Confirm retest dates are not shifted by timezone, formatting, or parsing issues.
- ☐ Confirm missing retest dates are handled consistently.
- ☐ Download the Retest Report PDF and compare to preview.

Release risk

A retest report should not falsely reassure users that no items are due or overdue. Missing overdue items should block release.

14. PDF preview and downloaded PDF match checklist

- ☐ Preview each report type in the browser/app.
- ☐ Download the generated PDF.
- ☐ Open the downloaded PDF locally.
- ☐ Compare title page, summary, asset rows, failed items, retest dates, page count, and footer/version details.
- ☐ Confirm no data appears in preview but disappears in the PDF.
- ☐ Confirm no old/cached report downloads instead of the newly generated report.
- ☐ Confirm report filename is appropriate and not misleading.
- ☐ Save evidence of preview and downloaded PDF comparison.

Release risk

Preview/download mismatch must block release because the user may approve one report but send another.

15. Defect severity and release blocking rules

Severity	Examples	Release decision
Critical	Wrong pass/fail status; missing failed item; missing asset; wrong customer/site on report; preview/download mismatch; old result shown as current	Stop wider release until fixed and retested.
High	Retest date error; incomplete report section; parser failure for supported file; long table loses rows; major formatting hides data	Do not expand pilot until reviewed and resolved or clearly documented.
Medium	Cosmetic formatting issue; awkward spacing; minor text wrapping; non-critical field missing where source data is incomplete	Can continue pilot if documented and not misleading.
Low	Spelling, minor visual polish, non-blocking wording, small help text changes	Add to backlog; does not block release.

Automatic stop condition

Any defect that could cause a user to issue an incorrect report to their customer must stop wider release until fixed, retested, and recorded in the changelog.

16. Test evidence record template

Field	Record
Test ID	
Date tested	
Tester name	
Build/version	
Browser/device	
File type tested	
Source file name	
Expected asset count	
Actual asset count	
Expected pass/fail count	
Actual pass/fail count	
Report type tested	Basic / Pro / Upcoming Retest
Result	Pass / Fail / Needs review
Evidence saved	Screenshots / source file / generated PDF / notes
Defect ID if failed	
Retest completed	Yes / No
Approved for release	Yes / No

17. Minimum acceptance criteria

- ☐ All required supported file types import successfully using the current V1.0 Stable workflow.
- ☐ Imported asset count matches source file for all test files.
- ☐ Pass/fail counts match source data for all test files.
- ☐ All known failed items appear correctly in dashboard and reports.
- ☐ Retest dates and due/overdue status are correct for test files with retest data.
- ☐ Customer/site details are correct and no stale previous-session data appears.
- ☐ Duplicate/latest-test behaviour is correct or documented as a limitation.
- ☐ Basic Report, Pro Report, and Upcoming Retest Report outputs are accurate.
- ☐ Previewed reports and downloaded PDFs match.
- ☐ No unresolved Critical defects remain.
- ☐ All High defects have either been fixed, retested, or accepted by management with documented limitations.

18. QA sign-off

Role	Name	Signature/approval	Date
Product owner			
Technical maintainer			
Support representative			

Management approver			
---------------------	--	--	--

Recommended sign-off statement

Based on the completed accuracy testing checklist, TTS Reports V1.0 is / is not approved for pilot or wider customer release. Any limitations, unresolved issues, or customer warnings must be documented before release.

19. One-page release blocker checklist

- ☐ No wrong pass/fail results.
- ☐ No missing failed items.
- ☐ No missing assets.
- ☐ No incorrect customer/site details.
- ☐ No incorrect retest due/overdue lists.
- ☐ No report rows lost during PDF generation.
- ☐ No stale/cached previous report data.
- ☐ No mismatch between preview and downloaded PDF.
- ☐ No unsupported file silently producing a report.
- ☐ No unresolved Critical defects.

Final control: TTS Reports should only expand after it proves report accuracy, not before.