
Document Intelligence Service — Design

Give it a scanned PDF and it returns every person mentioned, with the page and the exact box where the name sits, so a reviewer can check it. It also compares those names with a list you send, and answers questions about uploaded documents, citing the page each answer comes from.

100 % / 98 %	**54 of 54**	**15 of 15**	**0**
of names found are real people / of real people are found	boxes checked by re-reading what is inside them	questions answered correctly, three runs in a row	made-up sources in any answer


Details: DECISIONS.md (decisions, limitations, use of AI) · run with **docker compose up --build**, then open http://localhost:8000/viewer

1 · How the pieces fit together



Each engine sits behind its own small interface: it can be swapped through configuration, or replaced by a fake in tests.

2 · Finding names and where they are



Real result on company_memo.pdf


"Robert Chen" → page 0, x 59.76, y 266.88, width 53.04, height 7.2 (PDF points, top-left origin) → matches "Robert Chen", score 1.0

- **Boxes are in PDF points, not image pixels** (72 per inch, origin at the top-left), so they line up with the PDF whatever resolution was used to read it.
- **The box comes from the person's own words.** The name finder marks a person in the page text; we take exactly the OCR words it covers and draw the box around them. A name that appears five times gets five boxes, and titles like "Dr." stay outside.
- **Matching compares whole names**, ignoring case, accents and punctuation: *María González* matches *Maria Gonzalez*, but *Ana* does not match *Ana María Rodríguez*.

3 · Answering a question

- **Indexing.** Each uploaded document is read the same way, then split into chunks of whole paragraphs (never cutting a word, never crossing a page). Chunk ids start with a fingerprint of the file, so a second document can't overwrite the first and uploading the same file twice doesn't duplicate it.
- **Two searches, then a ranking.** A search by meaning finds paraphrases; a search by exact words finds names and figures the first one misses. A re-ranker then reads each candidate next to the question and keeps the best five.
- **The LLM decides if the answer is there.** It answers only from those five passages, or says it isn't in the documents. We first tried a score cut-off to decide that, and dropped it: it rejected easy questions like "Who is the CEO?".

- **Sources can't be invented.** The LLM only cites passage numbers; the service turns them into "file, page n" from the passages it actually sent.



4 · Technology choices and trade-offs


NEED	CHOICE	WHY	TRADE-OFF
Read text	Tesseract	Free, runs on CPU, gives each word's position	Weak on poor scans; a cloud OCR could replace it
PDF → images	PyMuPDF	Fast, knows page sizes in points	AGPL licence; pypdfium2 if that matters
Find people	spaCy, large English	Best on our samples; the small one took a project for a person	~400 MB more; weak on ALL CAPS
Compare names	rapidfuzz	Whole-name similarity, fast	Fixed 0.90 threshold (configurable)
Search by meaning	e5 multilingual + Chroma	Spanish and English, no extra servers	One writer; a database service at scale
Rank results	Multilingual cross-encoder	~1.5 s per question on CPU	A stronger one took 21 s on CPU
Write answers	Groq, gpt-oss-120b	Free, fast; any OpenAI-compatible provider	Free-tier limits; text leaves the machine

5 · Scaling to 1000+ PDFs an hour

Today one process does everything: it reads the PDF, embeds it, stores it and answers questions. To scale we follow a document and a question through our own components, find where each one gets stuck, and fix that point.

PATH	STAGE	WHERE IT GETS STUCK TODAY	FIX AT SCALE
Document	Read + find names	The request does the work in the one API process: a few big PDFs at once fill the CPU and the other requests wait	The API stores the PDF and returns a job id; Temporal queues one workflow per PDF; OCR workers pull from the queue and are added as it grows
Document	Embeddings	The model runs on CPU inside the API, loaded again in every process	Model workers on GPU, embedding many chunks per call
Document	Vector DB writes	Embedded Chroma: one process owns its files, so many workers can't write to it	Qdrant service: many writers at once, more replicas as data grows
Question	Hybrid search	Keyword search reads every stored chunk on every question: slower with each document added	Qdrant runs meaning + keyword search on its own indexes; read replicas for many questions
Question	Re-ranking	~1.5 s of CPU per question inside the API; a burst of questions queues up	Re-ranker on a GPU model server that scores several questions together
Question	LLM	Free tier with a per-minute limit; a burst gets rejected	Paid tier; calls go through a queue capped at the limit, so they wait instead of failing; simple questions use the small model (§7)

Temporal is a workflow engine built on queues and workers. Each PDF is one **workflow**, our recipe: check, read, find names, split, embed, store. Each step that calls an engine is an **activity**, with its own time limit and retries. Activities wait in **task queues** that **workers** pull from.



Why Temporal and not a plain queue. It remembers every finished step: a worker that dies mid-PDF is replaced and the PDF carries on from the last finished step. Temporary failures are retried with growing waits; a bad file fails once. The file's fingerprint is the workflow id, so a duplicate upload runs once. A queue can be capped at a provider's limit, and every step stays in history: an audit trail.

Engines that fall short. Each engine sits behind its own interface, so a replacement is a plug-in plus a config change, kept only if it wins on a golden set of real documents. Embeddings, re-ranker and LLM already handle Spanish; OCR and the name finder do not.

ENGINE	WHAT FALLS SHORT	AT SCALE
Find people	No real names on an ALL-CAPS Spanish property certificate	Rewrite ALL-CAPS lines in normal case (same length, boxes don't move); then measure a multilingual model such as GLiNER
Read text	English only	Spanish language pack: a config change
Search by meaning	e5-small misses exact names and figures (why keyword search exists)	bge-m3: one multilingual model gives meaning and keyword vectors, both searched in Qdrant
Rank results	The stronger re-ranker took 21 s on CPU	bge-reranker-v2-m3 once it runs on GPU

6 · What can go wrong and what happens

FAILURE	WHAT WE DO	CALLER SEES
Not a PDF, empty, too big, too many pages, password	Checked before any work starts	4xx with a specific code
OCR engine missing or stuck	Time limit per page	503
Poor scan	Words the OCR is unsure of are dropped: no box over noise	fewer names
LLM slow, busy or down	Time limit and automatic retries; names and indexing keep working	503 / 502
Answer not in the documents	The LLM says so; an answer citing nothing is "not found"	"not found"
A document tries to give the LLM orders	Document text is marked as data; the LLM has no tools	normal answer
Same file uploaded twice	Same fingerprint, so it replaces itself	no duplicates
Text in ALL CAPS, other languages	Known limits of the name finder; fix in §5	fewer names

7 · Choosing a model by question difficulty

An **orchestrator** in front of the models picks one, checks its answer and escalates when needed: a short Temporal workflow the API waits on, deciding in plain code (cheap, reproducible).

- **Classify from the question's words:** "compare", "why", "total", "difference" or more than one name → large model; otherwise → small, cheap model. Search, embeddings and re-ranking are shared; each model is a config entry with its own capped queue.
- **Check, then escalate once:** if the small model says "not found" or cites nothing valid, the large one gets the same passages. Citations are the signal we trust; re-ranker scores are not (answerable and unanswerable questions score alike).
- **Measure:** log route, model and cost per question; tune the rules on questions kept apart from the test set.