Desired behaviour:
1: ~DRIVE_SEL high, ~Write_gate low, DE low, RE high
2: ~DRIVE_SEL high, ~Write_gate high, DE low, RE high
2: ~DRIVE_SEL low, ~Write_gate low, DE high, RE high
3: ~DRIVE_SEL low, ~Write_gate high, DE low, RE low

U9D
74LS03
DRIVE_SEL
~WRITE_GATE
J8
J7
Unsure if this is needed, if not:
By not placing the jumbers, the tranciever is always active
R13 100R
R14 100R
WRITE_GATE
MFM_IN
MFM_OUT
+3.3V
R3 470R
R2 470R
R12 DNP
GND
U5
SN65HVD33DR
NC1
RO
RE
DE
DI
GND1
GND2
VCC2
VCC1
RI_A
RI_B
DO_Z
DO_Y
NC2
J9
Conn_01x04
R4 DNP
R1 100R
C5 100n
~DRIVE_SEL
Drive_Selected
MFM_Write+
MFM_Write−
MFM_Read+
MFM_Read−
P1
CON20

SW1
SW_Push
J4
Conn_01x16
RUN
3V3_EN
GPIO0
GPIO1
GPIO2
GPIO3
GPIO4
GPIO5
GPIO6
GPIO7
GPIO8
GPIO9
GPIO10
GPIO11
GPIO12
GPIO13
GPIO14
GPIO15
GPIO16
GPIO17
GPIO18
GPIO19
GPIO20
GPIO21
GPIO22
ADC_VREF
GPIO26_ADC0
GPIO27_ADC1
GPIO28_ADC2
AGND
WRITE_GATE
MFM_IN
HEAD_1
MFM_OUT
INDEX
WRITE_FAULT
READY
TRACK_0
SEEK_COMPL
STEP
DIR_IN
HEAD_0
HEAD_2
HEAD_3
R5 1K
R6 1K
R7 1K
R8 1K
R9 1K
R10 1K
R11 1K
D1
1N5818
LED/Buzzer
J6
Conn_01x02
JP1
JP2
JP3
JP4
JP5
JP6
JP7
JP8
SCLK
MOSI
MISO/D0
CS/D3
D1
D2
For possible SDIO use for faster SD speeds
For SPI mode solder: JP1, JP3, JP5, JP7
A1
RaspberryPi_Pico
J3
Micro_SD_Card_Det1
DAT2
DAT3/CD
CMD
VDD
CLK
VSS
DAT0
DAT1
DET
SHIELD
C1 100n

HEAD_3
HEAD_2
WRITE_GATE
SEEK_COMPL
DRIVE_SEL
TRACK_0
WRITE_FAULT
HEAD_0
HEAD_1
INDEX
READY
STEP
DIR_IN
U3A
U3B
U4C
U2B
U2C
U2D
U3D
U4A
U9A
U9B
U4B
U3C
74LS33
74LS03
~DRIVE_SEL
~WRITE_GATE
J2
Conn_02x04_Odd_Even
J1
ECON34
Head_3/REDWR
Head_2
Write_gate
Seek_Complete
Track_0
Write_Fault
Head_0
Recovery
Head_1
Index
Ready
Step
Drive_Select_1
Drive_Select_2
Drive_Select_3
Drive_Select_4
Direction_In
RN1
R_Network09

U9C
74LS03

J5
Conn_01x04
+12V
U2E
U3E
U4E
U9E
74LS03
C2 100n
C4 100n
C6 100n
C8 100n

H1 MountingHole
H2 MountingHole
H3 MountingHole
H4 MountingHole
H5 MountingHole
H6 MountingHole

U2A
74LS03

Sheet: /
File: MFMPico.kicad_sch
Title:
Size: A3
Date:
Rev:
KiCad E.D.A. 10.0.0
Id: 1/1