

Mining for **Meaning**

**Knowledge Representation Methods
in Process Mining for Transparency,
Verifiability, and Replicability.**

Riley Moher
23.07.2025
CPMC Annual
Meeting

What's wrong here?

Timestamp	Event	Patient
12:02	Patient Intake	John Smith
12:05	Patient Intake	John Smith
12:06	Diagnostic	John Smith

What's wrong here?

-
- Issue: Patient Intake should only occur once for the same patient.

Timestamp	Event	Patient
12:02	Patient Intake	John Smith
12:05	Patient Intake	John Smith
12:06	Diagnostic	John Smith

What's wrong here?

-
- Issue: Patient Intake should only occur once for the same patient.
 - Solution: The event label was wrong

Timestamp	Event	Patient
12:02	Patient Intake	John Smith
12:05	Additional Screening	John Smith
12:06	Diagnostic	John Smith

What's wrong here?

Timestamp	Event	Lifecycle Transition
14:20	Process Application	Start
15:30	Credit Check	Complete
15:38	Credit Check	Start

What's wrong here?

- Issue: Activities cannot end before they begin

Timestamp	Event	Lifecycle Transition
14:20	Process Application	Start
15:30	Credit Check	Complete
15:38	Credit Check	Start

What's wrong here?

- Issue: Activities cannot end before they begin
- Solution: Fix the timestamp with the correct ordering

Timestamp	Event	Lifecycle Transition
14:20	Process Application	Start
16:30	Credit Check	Complete
15:38	Credit Check	Start

- **Process data is given meaning once interpreted**

- **Process data is given meaning once interpreted**
- **Interpretations rely on process knowledge**

- **Process data is given meaning once interpreted**
- **Interpretations rely on process knowledge**
- **Process knowledge comes in many different forms**

- **Process data is given meaning once interpreted**
- **Interpretations rely on process knowledge**
- **Process knowledge comes in many different forms**

Idea: provide the means to **capture** these interpretations & knowledge

Agenda

- What does it mean to represent knowledge?
- What's so special about process knowledge?
- How do we apply this to process mining?

Agenda

- What does it mean to represent knowledge?
- What's so special about process knowledge?
- How do we apply this to process mining?

Knowledge Representation (KR)

- As humans, we can easily understand, interpret, and reason with knowledge
- We leverage that knowledge every day to achieve goals in the real world
- How can machines do the same?

Knowledge versus Data

- Storage \neq Representation

Knowledge versus Data

- Storage \neq Representation
- KR enables inference and verification

Knowledge versus Data


Inference

Facts and rules produce
new facts



Verification

Facts and rules produce
proofs of compliance or
non-compliance.



Knowledge versus Data

But what does this actually look like?


Inference

Facts and rules produce
new facts



Verification

Facts and rules produce
proofs of compliance or
non-compliance.



KR in practice

- Data is translated into a set of **logically represented** facts
- Rules about a domain are given by an **ontology**

KR in practice

- Data is translated into a set of **logically represented** facts
- Rules about a domain are given by an **ontology**
- What is an ontology?

KR in practice

- Data is translated into a set of **logically represented** facts
- Rules about a domain are given by an **ontology**
- What is an ontology?
 - A structured vocabulary for a domain
 - An unambiguous model of knowledge
 - Rules for entities and their relationships

Agenda

- What does it mean to represent knowledge?
- What's so special about process knowledge?
- How do we apply this to process mining?

Process Knowledge

- Not only do we need to represent the world, but how it **changes**

Process Knowledge

- Not only do we need to represent the world, but how it **changes**
- Levels of knowledge – both **domain-level** and **fundamental**

Process Knowledge

- Not only do we need to represent the world, but how it **changes**
- Levels of knowledge – both **domain-level** and **fundamental**
- Overloaded concepts – the event

What makes an event?

- “An atomic granule of an activity that has been observed” – XES definition of an event

What makes an event?

- “An atomic granule of an activity that has been observed” – XES definition of an event
- “Awaiting Assignment”, “Loan Approval”, “Create Purchase Order Item”

What makes an event?

- “An atomic granule of an activity that has been observed” – XES definition of an event
- “Awaiting Assignment”, “Loan Approval”, “Create Purchase Order Item”
- How do events relate to tasks, resources, processes, occurrences?

Agenda

- What does it mean to represent knowledge?
- What's so special about process knowledge?
- How do we apply this to process mining?

Ontology-Aware Process Mining

- Make process knowledge used throughout the process mining lifecycle **explicit**

Ontology-Aware Process Mining

- Make process knowledge used throughout the process mining lifecycle **explicit**
- Enable new kinds of **reasoning** over event log data

Ontology-Aware Process Mining

- Make process knowledge used throughout the process mining lifecycle **explicit**
- Enable new kinds of **reasoning** over event log data
- Done by **mapping** data to a knowledge base, and augmenting it through **knowledge patterns**

Mapping and Formalization

Raw Event Data

Ad-Hoc Interpretations

Business Questions


Business Validations

Knowledge Base

Data Theory

Logical Queries

Logical Proofs




Mapping and Formalization

Raw Event Data

Ad-Hoc Interpretations

Business Questions

Business Validations





Knowledge Base

Data Theory

Logical Queries

Logical Proofs





Mapping Data

- Tabular data from event logs becomes enriched **relational** data

Mapping Data

- Tabular data from event logs becomes enriched **relational** data

Activity	Timestamp	Case
pending	10:22	c1
approval	10:23	c1
submission	12:10	c2


Mapping Data

- Tabular data from event logs becomes enriched **relational** data

Activity	Timestamp	Case
pending	10:22	c1
approval	10:23	c1
submission	12:10	c2


Mapping Data

- Tabular data from event logs becomes enriched **relational** data



Mapping Data

- Tabular data from event logs becomes enriched **relational** data





This forms our **ground process data**

Mapping Data

- Tabular data from event logs becomes enriched **relational** data

Map
Formalize
Analyze

Activity	Timestamp	Case
pending	10:22	c1
approval	10:23	c1
submission	12:10	c2





This forms our **ground process data**

Mapping Data


- Tabular data from event logs becomes enriched **relational** data

Map
Formalize
Analyze

Activity	Timestamp	Case
pending	10:22	c1
approval	10:23	c1
submission	12:10	c2



This forms our **ground process data**



Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?



Timestamp	Event	Lifecycle Transition
14:20	Process Application	Start
15:30	Credit Check	Complete
15:38	Credit Check	Start

Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?



Timestamp	Event	Lifecycle Transition
14:20	Process Application	Start
15:30	Credit Check	Complete
15:38	Credit Check	Start

Event(e2)
hasActivity(e0, creditCheck)
hasTransition(e2, complete)

Event(e3)
hasActivity(e3, creditCheck)
hasTransition(e3, start)

Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?



Timestamp	Event	Lifecycle Transition
14:20	Process Application	Start
15:30	Credit Check	Complete
15:38	Credit Check	Start

Event(e2)
hasActivity(e0, creditCheck)
hasTransition(e2, complete)

Event(e3)
hasActivity(e3, creditCheck)
hasTransition(e3, start)

Ground Data

Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?



Timestamp	Event	Lifecycle Transition
14:20	Process Application	Start
15:30	Credit Check	Complete
15:38	Credit Check	Start

Event(e2)
hasActivity(e0, creditCheck)
hasTransition(e2, complete)

Event(e3)
hasActivity(e3, creditCheck)
hasTransition(e3, start)

Ground Data

Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?



Ground Data

Event(e2)
hasActivity(e0, creditCheck)
hasTransition(e2, complete)

Event(e3)
hasActivity(e3, creditCheck)
hasTransition(e3, start)



Ontology Translations

“Two events sharing an activity
each with a start and end
transition indicates an activity
occurrence”

Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?



Ground Data

Event(e2)
hasActivity(e0, **creditCheck**)
hasTransition(e2, complete)

Event(e3)
hasActivity(e3, **creditCheck**)
hasTransition(e3, start)



Ontology Translations

“Two events **sharing an activity** each with a start and end transition indicates an activity occurrence”

Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?



Ground Data

Event(e2)
hasActivity(e0, **creditCheck**)
hasTransition(e2, **complete**)

Event(e3)
hasActivity(e3, **creditCheck**)
hasTransition(e3, **start**)



Ontology Translations

“Two events **sharing an activity** each with a **start** and **end** transition indicates an activity occurrence”

Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?



Ground Data

Event(e2)
hasActivity(e0, **creditCheck**)
hasTransition(e2, **complete**)

Event(e3)
hasActivity(e3, **creditCheck**)
hasTransition(e3, **start**)



Ontology Translations

“Two events **sharing an activity** each with a **start** and **end** transition indicates an **activity occurrence**”

Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?



Ground Data


Event(e2)
hasActivity(e0, creditCheck)
hasTransition(e2, complete)

Event(e3)
hasActivity(e3, creditCheck)
hasTransition(e3, start)




Ontology Translations

“Two events sharing an activity each with a start and end transition indicates an activity occurrence”



Translated Data

occurrence(o1)
beginOf(o1, 15:38)
endOf(o1, 15:30)



Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?



Ground Data


Event(e2)
hasActivity(e0, creditCheck)
hasTransition(e2, complete)

Event(e3)
hasActivity(e3, creditCheck)
hasTransition(e3, start)




Ontology Translations

“Two events sharing an activity each with a start and end transition indicates an activity occurrence”



Translated Data

occurrence(o1)
beginOf(o1, 15:38)
endOf(o1, 15:30)




Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?



Translated Data

```
occurrence(o1)
beginOf(o1, 15:38)
endOf(o1, 15:30)
```



Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?

Map
Formalize
Analyze


Translated Data

Ontology

occurrence(o1)
beginOf(o1, 15:38)
endOf(o1, 15:30)



“Activity occurrences
start points are less
than or equal to their
end points”



$$t_1 \leq t_2$$

Reasoning with Event Data

- How can we formally (and automatically) identify **ordering errors**?

Map
Formalize
Analyze


Translated Data

occurrence(o1)
beginOf(o1, 15:38)
endOf(o1, 15:30)



Ontology

“Activity occurrences
start points are less
than or equal to their
end points”




Proof of
Inconsistency

$t_1 = 15 : 38$

$t_2 = 15 : 30$


$t_1 > t_2$

$t_1 \leq t_2$



$t_1 \leq t_2$

**What about domain-specific
analysis?**



Knowledge Patterns

- “When a fragile object is dropped, it breaks”
- “Patient Intake should only occur once for the same patient.”

Knowledge Patterns

- “When a fragile object is dropped, it breaks”
- “Patient Intake should only occur once for the same patient.”

Knowledge Patterns

- “When a fragile object is dropped, it breaks”

State Based Effect

- “Patient Intake should only occur once for the same patient.”

Occurrence Constraint

Knowledge Patterns

- “When a fragile object is dropped, it breaks”

State Based Effect

- “Patient Intake should only occur once for the same patient.”

Occurrence Constraint

Knowledge Patterns

- State-Based Effects (SBE)
- “When a fragile object is dropped, it breaks”

Knowledge Patterns

- State-Based Effects (SBE)
- “When a fragile object is dropped, it breaks”
- While some initial condition holds, and an occurrence happens, some resulting condition holds afterwards

Knowledge Patterns

- State-Based Effects (SBE)
- “When a fragile object is dropped, it breaks”
- While some initial condition holds, and an occurrence happens, some resulting condition holds afterwards

Knowledge Patterns

- State-Based Effects (SBE)
- “When a **fragile** object is **dropped**, it **breaks**”
- While some **initial condition** holds, and an **occurrence** happens, some **resulting condition** holds afterwards
- Patterns abstract common process knowledge
- $\text{SBE}(c1, a, c2)$

Knowledge Patterns in Reasoning

- For **domain specific** reasoning problems
 - Use patterns to declare business rules, data interpretations (the data theory)
 - “Patient Intake occurs exactly once for one patient visit”

Knowledge Patterns in Reasoning

- For **domain specific** reasoning problems
 - Use patterns to declare business rules, data interpretations (the data theory)
 - “Patient Intake occurs exactly once for one patient visit”
- For **general** reasoning problems
 - The process ontology contains fundamental knowledge about how processes work
 - “Occurrences cannot end before they begin”

Ontology-Driven Process Mining



Ontology-Driven Process Mining



Data



Rules

Ontology-Driven Process Mining




Data




Rules


Ontology-Driven Process Mining



Ontology-Driven Process Mining



Ontology-Driven Process Mining



Ontology-Driven Process Mining

Making Ontology-Driven Process Mining a Reality

Making Ontology-Driven Process Mining a Reality

- We are developing a python library to implement our framework – OPAL (Ontology-driven Process Mining AnaLysis engine)

Making Ontology-Driven Process Mining a Reality

- We are developing a python library to implement our framework – OPAL (Ontology-driven Process Mining AnaLysis engine)
- Our work is benefitting the knowledge representation and process mining communities alike

Making Ontology-Driven Process Mining a Reality

- We are developing a python library to implement our framework – OPAL (Ontology-driven Process Mining AnaLysis engine)
- Our work is benefitting the knowledge representation and process mining communities alike
- We are interested in collaborating on new domains, datasets, and problems!

Making Ontology-Driven Process Mining a Reality

- We are developing a python library to implement our framework – OPAL (Ontology-driven Process Mining AnaLysis engine)
- Our work is benefitting the knowledge representation and process mining communities alike
- We are interested in collaborating on new domains, datasets, and problems!

Thank you!

